




Fig.44. Conducted spurious emission: 8DPSK, Channel 0, 30MHz - 1GHz




Fig.45. Conducted spurious emission: 8DPSK, Channel 0, 1GHz - 3GHz




Fig.46. Conducted spurious emission: 8DPSK, Channel 0, 3GHz - 10GHz




Fig.47. Conducted spurious emission: 8DPSK, Channel 0, 10GHz - 26GHz




Fig.48. Conducted spurious emission: 8DPSK, Channel 39, 2441MHz




Fig.49. Conducted spurious emission: 8DPSK, Channel 39, 30MHz - 1GHz




Fig.50. Conducted spurious emission: 8DPSK, Channel 39, 1GHz - 3GHz




Fig.51. Conducted spurious emission: 8DPSK, Channel 39, 3GHz - 10GHz




Fig.52. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz




Fig.53. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz






Fig.54. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz




Fig.55. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz




Fig.56. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz




Fig.57. Conducted spurious emission: 8DPSK, Channel 78, 10GHz - 26GHz

## A.5. Radiated Emission

### Measurement Limit:

| Standard                               | Limit                        |
|----------------------------------------|------------------------------|
| FCC 47 CFR Part 15.247, 15.205, 15.209 | 20dB below peak output power |

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

The measurement is made according to ANSI C63.10

### Limit in restricted band:

| Frequency of emission (MHz) | Field strength(uV/m) | Field strength(dBuV/m) |
|-----------------------------|----------------------|------------------------|
| 30-88                       | 100                  | 40                     |
| 88-216                      | 150                  | 43.5                   |
| 216-960                     | 200                  | 46                     |
| Above 960                   | 500                  | 54                     |

### Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

| Frequency of emission (MHz) | RBW/VBW       | Sweep Time(s) |
|-----------------------------|---------------|---------------|
| 30-1000                     | 100KHz/300KHz | 5             |
| 1000-4000                   | 1MHz/1MHz     | 15            |
| 4000-18000                  | 1MHz/1MHz     | 40            |
| 18000-26500                 | 1MHz/1MHz     | 20            |

### Measurement Results:

Result= $P_{Mea}$ +ARPL

#### For GFSK

| Channel | Frequency Range    | Test Results | Conclusion |
|---------|--------------------|--------------|------------|
| Power   | 2.38GHz~2.4GHz---L | Fig.58       | P          |
| Power   | 2.45GHz~2.5GHz---H | Fig.59       | P          |

#### For $\pi/4$ DQPSK

| Channel | Frequency Range    | Test Results | Conclusion |
|---------|--------------------|--------------|------------|
| Power   | 2.38GHz~2.4GHz---L | Fig.60       | P          |
| Power   | 2.45GHz~2.5GHz---H | Fig.61       | P          |

#### For 8DPSK

| Channel | Frequency Range    | Test Results | Conclusion |
|---------|--------------------|--------------|------------|
| Power   | 2.38GHz~2.4GHz---L | Fig.62       | P          |
| Power   | 2.45GHz~2.5GHz---H | Fig.63       | P          |



**GFSK Ch 0 - Average**

| Frequency (MHz) | Measurement Result (dBμV/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dBμV) | Limit (dBμV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|------------------------|----------------|-------------|--------------------|
| 2382.000        | 46.3                        | 2.9             | 32.0                  | 11.37                  | 54.0           | 7.7         | V                  |
| 2387.000        | 46.3                        | 2.9             | 32.0                  | 11.40                  | 54.0           | 7.7         | V                  |
| 4804.500        | 28.1                        | -32.8           | 34.5                  | 26.41                  | 54.0           | 25.9        | H                  |
| 7206.000        | 30.3                        | -31.6           | 36.1                  | 25.80                  | 54.0           | 23.7        | V                  |
| 9607.500        | 32.8                        | -30.0           | 37.0                  | 25.85                  | 54.0           | 21.2        | H                  |
| 12010.500       | 35.3                        | -29.8           | 39.3                  | 25.81                  | 54.0           | 18.7        | H                  |

**GFSK Ch 39 - Average**

| Frequency (MHz) | Measurement Result (dBμV/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dBμV) | Limit (dBμV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|------------------------|----------------|-------------|--------------------|
| 2383.400        | 46.6                        | 2.9             | 32.0                  | 11.71                  | 54.0           | 7.4         | H                  |
| 2517.700        | 46.5                        | 3.0             | 32.6                  | 10.96                  | 54.0           | 7.5         | V                  |
| 4882.500        | 28.8                        | -32.7           | 34.5                  | 27.01                  | 54.0           | 25.2        | H                  |
| 7323.000        | 30.2                        | -31.9           | 36.1                  | 26.05                  | 54.0           | 23.8        | V                  |
| 9763.500        | 32.7                        | -30.6           | 37.2                  | 26.07                  | 54.0           | 21.3        | H                  |
| 12205.500       | 35.1                        | -29.4           | 39.2                  | 25.36                  | 54.0           | 18.9        | H                  |

**GFSK Ch 78 - Average**

| Frequency (MHz) | Measurement Result (dBμV/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dBμV) | Limit (dBμV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|------------------------|----------------|-------------|--------------------|
| 2483.800        | 47.3                        | 2.9             | 32.8                  | 11.60                  | 54.0           | 6.7         | H                  |
| 2484.700        | 47.1                        | 2.9             | 32.7                  | 11.46                  | 54.0           | 6.9         | V                  |
| 4960.500        | 27.7                        | -33.4           | 34.5                  | 26.57                  | 54.0           | 26.3        | V                  |
| 7440.000        | 30.2                        | -31.8           | 36.0                  | 25.97                  | 54.0           | 23.8        | V                  |
| 9919.500        | 33.8                        | -29.9           | 37.4                  | 26.34                  | 54.0           | 20.2        | H                  |
| 12400.500       | 34.7                        | -29.5           | 39.1                  | 25.02                  | 54.0           | 19.3        | H                  |

**π/4 DQPSK Ch 0 - Average**

| Frequency (MHz) | Measurement Result (dBμV/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dBμV) | Limit (dBμV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|------------------------|----------------|-------------|--------------------|
| 2383.600        | 46.3                        | 2.9             | 32.0                  | 11.40                  | 54.0           | 7.7         | V                  |
| 2388.700        | 46.3                        | 2.9             | 32.0                  | 11.45                  | 54.0           | 7.7         | H                  |
| 4804.500        | 28.6                        | -32.8           | 34.5                  | 26.98                  | 54.0           | 25.4        | V                  |
| 7206.000        | 30.6                        | -31.6           | 36.1                  | 26.10                  | 54.0           | 23.4        | H                  |
| 9607.500        | 33.1                        | -30.0           | 37.0                  | 26.17                  | 54.0           | 20.9        | H                  |
| 12010.500       | 35.4                        | -29.8           | 39.3                  | 25.98                  | 54.0           | 18.6        | V                  |

**$\pi/4$  DQPSK Ch 39 - Average**

| Frequency (MHz) | Measurement Result (dB $\mu$ V/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dB $\mu$ V) | Limit (dB $\mu$ V/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------------|-----------------|-----------------------|------------------------------|----------------------|-------------|--------------------|
| 2371.100        | 46.4                              | 2.9             | 32.0                  | 11.52                        | 54.0                 | 7.6         | H                  |
| 2533.800        | 46.4                              | 3.0             | 32.8                  | 10.54                        | 54.0                 | 7.7         | V                  |
| 4882.500        | 29.0                              | -32.7           | 34.5                  | 27.24                        | 54.0                 | 25.0        | V                  |
| 7323.000        | 30.4                              | -31.9           | 36.1                  | 26.29                        | 54.0                 | 23.6        | H                  |
| 9763.500        | 32.9                              | -30.6           | 37.2                  | 26.30                        | 54.0                 | 21.1        | H                  |
| 12205.500       | 35.4                              | -29.4           | 39.2                  | 25.56                        | 54.0                 | 18.7        | V                  |

 **$\pi/4$  DQPSK Ch 78 - Average**

| Frequency (MHz) | Measurement Result (dB $\mu$ V/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dB $\mu$ V) | Limit (dB $\mu$ V/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------------|-----------------|-----------------------|------------------------------|----------------------|-------------|--------------------|
| 2484.100        | 47.0                              | 2.9             | 32.7                  | 11.34                        | 54.0                 | 7.0         | V                  |
| 2485.600        | 47.0                              | 2.9             | 32.7                  | 11.33                        | 54.0                 | 7.0         | H                  |
| 4960.500        | 28.1                              | -33.4           | 34.5                  | 26.99                        | 54.0                 | 25.9        | H                  |
| 7440.000        | 30.5                              | -31.8           | 36.0                  | 26.25                        | 54.0                 | 23.5        | V                  |
| 9919.500        | 34.2                              | -29.9           | 37.4                  | 26.68                        | 54.0                 | 19.8        | H                  |
| 12400.500       | 34.9                              | -29.5           | 39.1                  | 25.25                        | 54.0                 | 19.1        | H                  |

**8DPSK Ch 0 - Average**

| Frequency (MHz) | Measurement Result (dB $\mu$ V/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dB $\mu$ V) | Limit (dB $\mu$ V/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------------|-----------------|-----------------------|------------------------------|----------------------|-------------|--------------------|
| 2382.400        | 46.3                              | 2.9             | 32.0                  | 11.38                        | 54.0                 | 7.7         | V                  |
| 2387.800        | 46.3                              | 2.9             | 32.0                  | 11.45                        | 54.0                 | 7.7         | V                  |
| 4804.500        | 28.6                              | -32.8           | 34.5                  | 26.94                        | 54.0                 | 25.4        | H                  |
| 7206.000        | 30.6                              | -31.6           | 36.1                  | 26.13                        | 54.0                 | 23.4        | H                  |
| 9607.500        | 33.1                              | -30.0           | 37.0                  | 26.16                        | 54.0                 | 20.9        | H                  |
| 12010.500       | 35.5                              | -29.8           | 39.3                  | 26.05                        | 54.0                 | 18.5        | V                  |

**8DPSK Ch 39 - Average**

| Frequency (MHz) | Measurement Result (dB $\mu$ V/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dB $\mu$ V) | Limit (dB $\mu$ V/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------------|-----------------|-----------------------|------------------------------|----------------------|-------------|--------------------|
| 2376.800        | 46.5                              | 2.9             | 32.1                  | 11.56                        | 54.0                 | 7.5         | H                  |
| 2516.800        | 46.5                              | 3.0             | 32.6                  | 11.01                        | 54.0                 | 7.5         | V                  |
| 4882.500        | 29.1                              | -32.7           | 34.5                  | 27.34                        | 54.0                 | 24.9        | H                  |
| 7323.000        | 30.5                              | -31.9           | 36.1                  | 26.34                        | 54.0                 | 23.5        | H                  |
| 9763.500        | 33.0                              | -30.6           | 37.2                  | 26.35                        | 54.0                 | 21.0        | V                  |
| 12205.500       | 35.4                              | -29.4           | 39.2                  | 25.63                        | 54.0                 | 18.6        | H                  |

**8DPSK Ch 78 - Average**

| Frequency (MHz) | Measurement Result (dBμV/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dBμV) | Limit (dBμV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|------------------------|----------------|-------------|--------------------|
| 2484.100        | 47.1                        | 2.9             | 32.7                  | 11.43                  | 54.0           | 6.9         | H                  |
| 2486.300        | 47.0                        | 2.9             | 32.7                  | 11.41                  | 54.0           | 7.0         | H                  |
| 4960.500        | 28.2                        | -33.4           | 34.5                  | 27.06                  | 54.0           | 25.8        | H                  |
| 7440.000        | 30.5                        | -31.8           | 36.0                  | 26.23                  | 54.0           | 23.5        | V                  |
| 9919.500        | 34.1                        | -29.9           | 37.4                  | 26.59                  | 54.0           | 19.9        | H                  |
| 12400.500       | 35.0                        | -29.5           | 39.1                  | 25.32                  | 54.0           | 19.0        | V                  |

**GFSK Ch 0 – Peak**

| Frequency (MHz) | Measurement Result (dBμV/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dBμV) | Limit (dBμV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|------------------------|----------------|-------------|--------------------|
| 2382.282        | 59.2                        | 2.9             | 32.0                  | 24.29                  | 74.0           | 14.8        | H                  |
| 2389.394        | 59.1                        | 2.9             | 32.0                  | 24.28                  | 74.0           | 14.9        | V                  |
| 4803.750        | 39.6                        | -32.9           | 34.5                  | 37.93                  | 74.0           | 34.4        | V                  |
| 7206.000        | 41.0                        | -31.6           | 36.1                  | 36.57                  | 74.0           | 33.0        | V                  |
| 9608.250        | 43.8                        | -30.0           | 37.0                  | 36.83                  | 74.0           | 30.2        | V                  |
| 12009.750       | 47.0                        | -29.8           | 39.3                  | 37.57                  | 74.0           | 27.0        | V                  |

**GFSK Ch 39 - Peak**

| Frequency (MHz) | Measurement Result (dBμV/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dBμV) | Limit (dBμV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|------------------------|----------------|-------------|--------------------|
| 2382.800        | 52.4                        | -25.1           | 32.0                  | 45.45                  | 74.0           | 21.6        | H                  |
| 2519.000        | 51.1                        | -26.7           | 32.6                  | 45.15                  | 74.0           | 22.9        | H                  |
| 4881.750        | 39.8                        | -32.7           | 34.5                  | 38.01                  | 74.0           | 34.2        | V                  |
| 7323.000        | 41.9                        | -31.9           | 36.1                  | 37.74                  | 74.0           | 32.1        | V                  |
| 9764.250        | 43.0                        | -30.6           | 37.2                  | 36.33                  | 74.0           | 31.0        | H                  |
| 12204.750       | 45.3                        | -29.4           | 39.2                  | 35.49                  | 74.0           | 28.7        | H                  |

**GFSK Ch 78 - Peak**

| Frequency (MHz) | Measurement Result (dBμV/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dBμV) | Limit (dBμV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|------------------------|----------------|-------------|--------------------|
| 2486.590        | 60.1                        | 2.9             | 32.7                  | 24.54                  | 74.0           | 13.9        | H                  |
| 2487.560        | 60.0                        | 2.9             | 32.6                  | 24.39                  | 74.0           | 14.0        | V                  |
| 4959.750        | 39.0                        | -33.4           | 34.5                  | 37.90                  | 74.0           | 35.0        | H                  |
| 7440.000        | 40.6                        | -31.8           | 36.0                  | 36.38                  | 74.0           | 33.4        | H                  |
| 9920.250        | 44.7                        | -29.9           | 37.4                  | 37.22                  | 74.0           | 29.3        | H                  |
| 12399.750       | 45.3                        | -29.5           | 39.1                  | 35.64                  | 74.0           | 28.7        | H                  |

**$\pi/4$  DQPSK Ch 0 - Peak**

| Frequency (MHz) | Measurement Result (dB $\mu$ V/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dB $\mu$ V) | Limit (dB $\mu$ V/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------------|-----------------|-----------------------|------------------------------|----------------------|-------------|--------------------|
| 2386.398        | 59.4                              | 2.9             | 32.0                  | 24.54                        | 74.0                 | 14.6        | H                  |
| 2387.784        | 59.5                              | 2.9             | 32.0                  | 24.60                        | 74.0                 | 14.5        | H                  |
| 4803.750        | 38.5                              | -32.9           | 34.5                  | 36.84                        | 74.0                 | 35.5        | V                  |
| 7206.000        | 41.4                              | -31.6           | 36.1                  | 36.97                        | 74.0                 | 32.6        | V                  |
| 9608.250        | 46.2                              | -30.0           | 37.0                  | 39.24                        | 74.0                 | 27.8        | V                  |
| 12009.750       | 46.9                              | -29.8           | 39.3                  | 37.46                        | 74.0                 | 27.1        | V                  |

 **$\pi/4$  DQPSK Ch 39 -Peak**

| Frequency (MHz) | Measurement Result (dB $\mu$ V/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dB $\mu$ V) | Limit (dB $\mu$ V/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------------|-----------------|-----------------------|------------------------------|----------------------|-------------|--------------------|
| 2372.400        | 49.9                              | -26.8           | 32.1                  | 44.66                        | 74.0                 | 24.1        | H                  |
| 2520.600        | 51.0                              | -26.7           | 32.6                  | 45.06                        | 74.0                 | 23.0        | H                  |
| 4881.750        | 39.9                              | -32.7           | 34.5                  | 38.07                        | 74.0                 | 34.1        | H                  |
| 7323.000        | 41.4                              | -31.9           | 36.1                  | 37.26                        | 74.0                 | 32.6        | H                  |
| 9764.250        | 43.4                              | -30.6           | 37.2                  | 36.77                        | 74.0                 | 30.6        | H                  |
| 12204.750       | 45.9                              | -29.4           | 39.2                  | 36.08                        | 74.0                 | 28.1        | V                  |

 **$\pi/4$  DQPSK Ch 78 - Peak**

| Frequency (MHz) | Measurement Result (dB $\mu$ V/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dB $\mu$ V) | Limit (dB $\mu$ V/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------------|-----------------|-----------------------|------------------------------|----------------------|-------------|--------------------|
| 2495.260        | 60.4                              | 2.9             | 32.4                  | 25.05                        | 74.0                 | 13.6        | H                  |
| 2497.980        | 60.4                              | 2.9             | 32.4                  | 25.07                        | 74.0                 | 13.6        | H                  |
| 4959.750        | 40.0                              | -33.4           | 34.5                  | 38.86                        | 74.0                 | 34.0        | V                  |
| 7440.000        | 41.4                              | -31.8           | 36.0                  | 37.15                        | 74.0                 | 32.6        | V                  |
| 9920.250        | 44.6                              | -29.9           | 37.4                  | 37.12                        | 74.0                 | 29.4        | V                  |
| 12399.750       | 45.3                              | -29.5           | 39.1                  | 35.72                        | 74.0                 | 28.7        | V                  |

**8DPSK Ch 0 -Peak**

| Frequency (MHz) | Measurement Result (dB $\mu$ V/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dB $\mu$ V) | Limit (dB $\mu$ V/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------------|-----------------|-----------------------|------------------------------|----------------------|-------------|--------------------|
| 2381.890        | 59.2                              | 2.9             | 32.0                  | 24.31                        | 74.0                 | 14.8        | H                  |
| 2387.742        | 59.4                              | 2.9             | 32.0                  | 24.57                        | 74.0                 | 14.6        | H                  |
| 4803.750        | 39.2                              | -32.9           | 34.5                  | 37.53                        | 74.0                 | 34.8        | V                  |
| 7206.000        | 41.6                              | -31.6           | 36.1                  | 37.16                        | 74.0                 | 32.4        | H                  |
| 9608.250        | 44.4                              | -30.0           | 37.0                  | 37.43                        | 74.0                 | 29.6        | H                  |
| 12009.750       | 46.2                              | -29.8           | 39.3                  | 36.69                        | 74.0                 | 27.8        | H                  |

### 8DPSK Ch 39 - Peak

| Frequency (MHz) | Measurement Result (dBμV/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dBμV) | Limit (dBμV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|------------------------|----------------|-------------|--------------------|
| 2376.000        | 50.4                        | -26.6           | 32.1                  | 44.92                  | 74.0           | 23.6        | H                  |
| 2536.400        | 50.9                        | -26.8           | 32.9                  | 44.78                  | 74.0           | 23.1        | H                  |
| 4881.750        | 38.6                        | -32.7           | 34.5                  | 36.79                  | 74.0           | 35.4        | V                  |
| 7323.000        | 40.9                        | -31.9           | 36.1                  | 36.75                  | 74.0           | 33.1        | H                  |
| 9764.250        | 45.3                        | -30.6           | 37.2                  | 38.67                  | 74.0           | 28.7        | V                  |
| 12204.750       | 46.5                        | -29.4           | 39.2                  | 36.69                  | 74.0           | 27.5        | V                  |

### 8DPSK Ch 78 - Peak

| Frequency (MHz) | Measurement Result (dBμV/m) | Cable loss (dB) | Antenna Factor (dB/m) | Receiver eading (dBμV) | Limit (dBμV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|------------------------|----------------|-------------|--------------------|
| 2480.420        | 60.2                        | 2.9             | 32.8                  | 24.40                  | 74.0           | 13.8        | H                  |
| 2492.200        | 60.0                        | 2.9             | 32.5                  | 24.53                  | 74.0           | 14.0        | H                  |
| 4959.750        | 39.3                        | -33.4           | 34.5                  | 38.20                  | 74.0           | 34.7        | H                  |
| 7440.000        | 41.7                        | -31.8           | 36.0                  | 37.43                  | 74.0           | 32.3        | V                  |
| 9920.250        | 44.4                        | -29.9           | 37.4                  | 36.90                  | 74.0           | 29.6        | V                  |
| 12399.750       | 45.4                        | -29.5           | 39.1                  | 35.82                  | 74.0           | 28.6        | V                  |

**Conclusion: PASS**

**Test graphs as below:**




Fig.58. Radiated emission (Power): GFSK, low channel



RE - Power-2.45GHz-2.5GHz




Fig.59. Radiated emission (Power) GFSK, high channel

RE - Power-2.38GHz-2.45GHz




Fig.60. Radiated emission (Power):  $\pi/4$  DQPSK, low channel

RE - Power-2.45GHz-2.5GHz




Fig.61. Radiated emission (Power):  $\pi/4$  DQPSK, high channel

RE - Power-2.38GHz-2.45GHz




Fig.62. Radiated emission (Power): 8DPSK, low channel

RE - Power-2.45GHz-2.5GHz




Fig.63. Radiated emission (Power): 8DPSK, high channel

## A.6. Time of Occupancy (Dwell Time)

**Method of Measurement: See ANSI C63.10-clause 7.8.4**

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = zero span, centered on a hopping channel
- RBW = 1 MHz
- VBW  $\geq$  RBW
- Sweep = as necessary to capture the entire dwell time per hopping channel
- Detector function = peak
- Trace = max hold

Measure a pulse time in time domain at middle frequency and then count the hopping number in 31.6s(which equals with 0.4 multiply 79) of middle frequency ,then multiply the pulse time and hopping number and record them.

### Measurement Limit:

| Standard                           | Limit (ms) |
|------------------------------------|------------|
| FCC 47 CFR Part 15.247(a) (1)(iii) | < 400      |

### Measurement Result:

#### For GFSK

| Channel | Packet | Dwell Time (ms) |        | Conclusion |
|---------|--------|-----------------|--------|------------|
| 39      | DH1    | Fig.64          | 117.74 | P          |
|         |        | Fig.65          |        |            |
|         | DH3    | Fig.66          | 174.03 | P          |
|         |        | Fig.67          |        |            |
|         | DH5    | Fig.68          | 181.08 | P          |
|         |        | Fig.69          |        |            |

#### For $\pi/4$ DQPSK

| Channel | Packet | Dwell Time (ms) |        | Conclusion |
|---------|--------|-----------------|--------|------------|
| 39      | DH1    | Fig.70          | 120.43 | P          |
|         |        | Fig.71          |        |            |
|         | DH3    | Fig.72          | 161.34 | P          |
|         |        | Fig.73          |        |            |
|         | DH5    | Fig.74          | 187.04 | P          |
|         |        | Fig.75          |        |            |

#### For 8DPSK

| Channel | Packet | Dwell Time (ms) |        | Conclusion |
|---------|--------|-----------------|--------|------------|
| 39      | DH1    | Fig.76          | 121.07 | P          |
|         |        | Fig.77          |        |            |
|         | DH3    | Fig.78          | 154.71 | P          |

|  |     |        |        |   |
|--|-----|--------|--------|---|
|  | DH5 | Fig.79 | 161.26 | P |
|  |     | Fig.80 |        |   |
|  |     | Fig.81 |        |   |

**Conclusion: PASS**

**Test graphs as below:**




Fig.64. Time of occupancy (Dwell Time): Channel 39, Packet DH1




Fig.65. Number of Transmissions Measurement:Channel 39,Packet DH1




Fig.66. Time of occupancy (Dwell Time): Channel 39, Packet DH3




Fig.67. Number of Transmissions Measurement:Channel 39,Packet DH3






Fig.68. Time of occupancy (Dwell Time): Channel 39, Packet DH5




Fig.69. Number of Transmissions Measurement:Channel 39,Packet DH5




Fig.70. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1




Fig.71. Number of Transmissions Measurement:Channel 39,Packet 2-DH1




Fig.72. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3




Fig.73. Number of Transmissions Measurement:Channel 39,Packet 2-DH3




Fig.74. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5




Fig.75. Number of Transmissions Measurement:Channel 39,Packet 2-DH5






Fig.76. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1




Fig.77. Number of Transmissions Measurement:Channel 39,Packet 3-DH1




Fig.78. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3




Fig.79. Number of Transmissions Measurement:Channel 39,Packet 3-DH3




Fig.80. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5




Fig.81. Number of Transmissions Measurement:Channel 39,Packet 3-DH5



## A.7. 20dB Bandwidth

**Method of Measurement: See ANSI C63.10-clause 6.9.2**

Measurement Procedure - Unwanted Emissions

1. Set RBW = 30kHz.
2. Set VBW = 100 kHz.
3. Set span to 3MHz
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

### Measurement Limit:

| Standard                     | Limit |
|------------------------------|-------|
| FCC 47 CFR Part 15.247(a)(1) | NA *  |

Use NdB Down function of the SA to measure the 20dB Bandwidth

\* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for “carrier frequency separation” test case, in Annex A.8.

### Measurement Results:

#### For GFSK

| Channel | 20dB Bandwidth (kHz) |        | Conclusion |
|---------|----------------------|--------|------------|
| 0       | Fig.82               | 950.25 | NA         |
| 39      | Fig.83               | 946.50 | NA         |
| 78      | Fig.84               | 950.25 | NA         |

#### For $\pi/4$ DQPSK

| Channel | 20dB Bandwidth (kHz) |         | Conclusion |
|---------|----------------------|---------|------------|
| 0       | Fig.85               | 1268.25 | NA         |
| 39      | Fig.86               | 1289.25 | NA         |
| 78      | Fig.87               | 1281.00 | NA         |

#### For 8DPSK

| Channel | 20dB Bandwidth (kHz) |         | Conclusion |
|---------|----------------------|---------|------------|
| 0       | Fig.88               | 1293.00 | NA         |
| 39      | Fig.89               | 1269.75 | NA         |
| 78      | Fig.90               | 1267.50 | NA         |

**Conclusion: NA**

**Test graphs as below:**




Fig.82. 20dB Bandwidth: GFSK, Channel 0




Fig.83. 20dB Bandwidth: GFSK, Channel 39




Fig.84. 20dB Bandwidth: GFSK, Channel 78




Fig.85. 20dB Bandwidth:  $\pi/4$  DQPSK, Channel 0




Fig.86. 20dB Bandwidth:  $\pi/4$  DQPSK, Channel 39




Fig.87. 20dB Bandwidth:  $\pi/4$  DQPSK, Channel 78




Fig.88. 20dB Bandwidth: 8DPSK, Channel 0




Fig.89. 20dB Bandwidth: 8DPSK, Channel 39




Fig.90. 20dB Bandwidth: 8DPSK, Channel 78



## A.8. Carrier Frequency Separation

**Method of Measurement: See ANSI C63.10-clause 7.8.2**

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = 3MHz
- RBW=300kHz
- VBW=300kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

Search the peak marks of the middle frequency and adjacent channel, then record the separation between them.

\* Comment: This limit should be over 25 kHz or  $(2/3) * 20\text{dB}$  bandwidth, whichever is greater.

### Measurement Limit:

| Standard                     | Limit(kHz)                                     |
|------------------------------|------------------------------------------------|
| FCC 47 CFR Part 15.247(a)(1) | over 25 kHz or $(2/3) * 20\text{dB}$ bandwidth |

### Measurement Result:

#### For GFSK

| Channel | Carrier frequency separation (kHz) |         | Conclusion |
|---------|------------------------------------|---------|------------|
| 39      | Fig.91                             | 1309.50 | P          |

#### For $\pi/4$ DQPSK

| Channel | Carrier frequency separation (kHz) |         | Conclusion |
|---------|------------------------------------|---------|------------|
| 39      | Fig.92                             | 1029.00 | P          |

#### For 8DPSK

| Channel | Carrier frequency separation (kHz) |         | Conclusion |
|---------|------------------------------------|---------|------------|
| 39      | Fig.93                             | 1358.25 | P          |

**Conclusion: PASS**

**Test graphs as below:**