



# FCC PART 15C TEST REPORT

**BLUETOOTH LOW ENERGY (BLE) PART**

**No. I17Z60685-SRD02**

**for**

**TCL Communication Ltd.**

**LTE / UMTS / GSM mobile phone**

**Model Name: 5085Y**

**FCC ID: 2ACCJH074**

**with**

**Hardware Version: PIO**

**Software Version: 1AA4**

**Issued Date: 2017-06-08**



**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

**Test Laboratory:**

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT.  
No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email:ctl\_terminals@catr.cn, website:www.chinattl.com



## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I17Z60685-SRD02	Rev.0	1st edition	2017-05-24
I17Z60685-SRD02	Rev.1	Delete charger CBA0058ABAC3	2017-06-06
I17Z60685-SRD02	Rev.2	Add charger CBA0058AGAC2, CBA0058AGAC4, CBA0058AGAC3	2017-06-08

## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>5</b>
<b>1.1. TESTING LOCATION .....</b>	<b>5</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>5</b>
<b>1.3. PROJECT DATA .....</b>	<b>5</b>
<b>1.4. SIGNATURE .....</b>	<b>5</b>
<b>2. CLIENT INFORMATION .....</b>	<b>6</b>
<b>2.1. APPLICANT INFORMATION .....</b>	<b>6</b>
<b>2.2. MANUFACTURER INFORMATION .....</b>	<b>6</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>7</b>
<b>3.1. ABOUT EUT .....</b>	<b>7</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT .....</b>	<b>7</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE .....</b>	<b>7</b>
<b>3.4. EUT SET-UPS .....</b>	<b>9</b>
<b>3.5. NORMAL ACCESSORY SETTING .....</b>	<b>9</b>
<b>3.6. GENERAL DESCRIPTION .....</b>	<b>9</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>10</b>
<b>4.1. DOCUMENTS SUPPLIED BY APPLICANT .....</b>	<b>10</b>
<b>4.2. REFERENCE DOCUMENTS FOR TESTING .....</b>	<b>10</b>
<b>5. TEST RESULTS .....</b>	<b>11</b>
<b>5.1. SUMMARY OF TEST RESULTS .....</b>	<b>11</b>
<b>5.2. STATEMENTS .....</b>	<b>11</b>
<b>6. TEST FACILITIES UTILIZED .....</b>	<b>12</b>
<b>7. MEASUREMENT UNCERTAINTY .....</b>	<b>13</b>
<b>7.1. PEAK OUTPUT POWER - CONDUCTED .....</b>	<b>13</b>
<b>7.2. FREQUENCY BAND EDGES .....</b>	<b>13</b>
<b>7.3. CONDUCTED EMISSION .....</b>	<b>13</b>
<b>7.4. RADIATED EMISSION .....</b>	<b>13</b>
<b>7.5. 6dB BANDWIDTH .....</b>	<b>13</b>
<b>7.6. MAXIMUM POWER SPECTRAL DENSITY LEVEL .....</b>	<b>13</b>
<b>7.7. AC POWERLINE CONDUCTED EMISSION .....</b>	<b>14</b>
<b>ANNEX A: DETAILED TEST RESULTS .....</b>	<b>15</b>
<b>A.1. MEASUREMENT METHOD .....</b>	<b>15</b>
<b>A.2. PEAK OUTPUT POWER - CONDUCTED .....</b>	<b>16</b>

A.3. FREQUENCY BAND EDGES - CONDUCTED.....	17
A.4. TRANSMITTER SPURIOUS EMISSION - CONDUCTED .....	19
A.5. TRANSMITTER SPURIOUS EMISSION - RADIATED .....	28
A.6. 6dB BANDWIDTH.....	32
A.7. MAXIMUM POWER SPECTRAL DENSITY LEVEL .....	35
A.8. AC POWERLINE CONDUCTED EMISSION.....	38

## 1. Test Laboratory

### 1.1. Testing Location

Conducted testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,  
P. R. China100191

Radiated testing Location: CTTL(BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology  
Development Area, Beijing, P. R. China 100176

### 1.2. Testing Environment

Normal Temperature: 15-35°C


Relative Humidity: 20-75%

### 1.3. Project data

Testing Start Date: 2016-11-21

Testing End Date: 2017-05-22

### 1.4. Signature



Wu Le

(Prepared this test report)



Sun Zhenyu

(Reviewed this test report)



Li Zhuofang

(Approved this test report)



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: TCL Communication Ltd.  
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China. 201203  
City: Shanghai  
Postal Code: 201203  
Country: China  
Telephone: 0086-21-31363544  
Fax: 0086-21-61460602

### **2.2. Manufacturer Information**

Company Name: TCL Communication Ltd.  
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China. 201203  
City: Shanghai  
Postal Code: 201203  
Country: China  
Telephone: 0086-21-31363544  
Fax: 0086-21-61460602

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	LTE / UMTS / GSM mobile phone
Model Name	5085Y
FCC ID	2ACCJH074
Frequency Band	ISM 2400MHz~2483.5MHz
Type of Modulation(LE mode)	GFSK (Bluetooth Low Energy)
Number of Channels(LE mode)	40
Power Supply	3.8V DC by Battery

#### **3.2. Internal Identification of EUT**

<b>EUT ID*</b>	<b>SN or IMEI</b>	<b>HW Version</b>	<b>SW Version</b>
EUT1	357577080000207	PIO	1AA4
EUT2	357577080000215	PIO	1AA4

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE**

<b>AE ID*</b>	<b>Description</b>	<b>SN</b>	<b>Remarks</b>
AE1	Battery	/	inbuilt
AE2	Battery	/	inbuilt
AE3	Battery	/	inbuilt
AE4	Charger	/	16TCT-CH-1489
AE5	Charger	/	16TCT-CH-1565
AE6	Charger	/	16TCT-CH-0860
AE7	USB Cable	/	16TCT-DC-0493
AE8	USB Cable	/	16TCT-DC-0501
AE9	USB Cable	/	/
AE10	USB Cable	/	/
AE21	Charger	/	/
AE23	Travel charger	/	/
AE24	Travel charger	/	/
AE25	Travel charger	/	/
AE1			
Model	CAC2710008CJ		
Manufacturer	COSLIGHT		
Capacitance	2710 mAh		
AE2			
Model	CAC2710004C1		
Manufacturer	BYD		
Capacitance	2710 mAh		

AE3

Model CAC2710005CC  
Manufacturer Jinneng  
Capacitance 2710 mAh

AE4

Model CBA0058AAC2  
Manufacturer TEPAO  
Length of cable /

AE5

Model CBA0058AAC4  
Manufacturer Aohai  
Length of cable /

AE6

Model CBA0058AAC3  
Manufacturer YINGJU  
Length of cable /

AE7

Model CDA3122005C2  
Manufacturer Shenhua  
Length of cable 100cm

AE8

Model CDA3122005C1  
Manufacturer Juwei  
Length of cable 100cm

AE9

Model CDA3122002C2  
Manufacturer Shenhua  
Length of cable 100cm

AE10

Model CDA3122002C1  
Manufacturer Juwei  
Length of cable 100cm

AE21

Model CBA0058ABAC2  
Manufacturer TENPAO  
Length of cable /

AE23

Model CBA0058AGAC2  
Manufacturer Tenpao

AE24

Model CBA0058AGAC4  
Manufacturer Aohai

AE25

Model CBA0058AGAC3  
Manufacturer YINGJU

\*AE ID: is used to identify the test sample in the lab internally.

### **3.4. EUT set-ups**

<b>EUT set-up No.</b>	<b>Combination of EUT and AE</b>	<b>Remarks</b>
Set.10	EUT4+ AE1+ AE4+ AE7	Charger
Set.11	EUT4+ AE1+ AE5+ AE7	Charger
Set.12	EUT4+ AE1+ AE6+ AE7	Charger

### **3.5. Normal Accessory setting**

Fully charged battery is used during the test.

### **3.6. General Description**

The Equipment Under Test (EUT) is a model of LTE / UMTS / GSM mobile phone with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfill the test. Samples undergoing test were selected by the Client.

## **4. Reference Documents**

### **4.1. Documents supplied by applicant**

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

### **4.2. Reference Documents for testing**

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz.	2015
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	June,2013

## 5. Test Results

### 5.1. Summary of Test Results

Abbreviations used in this clause:

**P** Pass, The EUT complies with the essential requirements in the standard.  
**F** Fail, The EUT does not comply with the essential requirements in the standard  
**NA** Not Applicable, The test was not applicable  
**NP** Not Performed, The test was not performed by CTTL

SUMMARY OF MEASUREMENT RESULTS	Sub-clause	Verdict
6dB Bandwidth	15.247 (a)(2)	<b>P</b>
Peak Output Power - Conducted	15.247 (b)(1)	<b>P</b>
Maximum Power Spectral Density Level	15.247(e)	<b>P</b>
Conducted Emission	15.247 (d)	<b>P</b>
Radiated Emission	15.247, 15.205, 15.209	<b>P</b>
Frequency Band Edges	15.247 (d)	<b>P</b>
AC Powerline Conducted Emission	15.107, 15.207	<b>P</b>

Please refer to **ANNEX A** for detail.

The measurement is made according to ANSI C63.10.

### 5.2. Statements

CTTL has evaluated the test cases requested by the applicant /manufacturer as listed in section 5.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.2

Note: The LTE / UMTS / GSM mobile phone 5085Y manufactured by TCL Communication Ltd. is a variant model based on 5085A for conformance test. According to the declaration of changes, the following items are tested on Set.10, Set.11 and Set.12

Mode of Feature	EUT set-up No	Test Item
BLE	Set.10, Set 11, Set 12	Radiated Emission

Other results are inherited from the initial model. The report number of initial model is I16Z42266-SRD02.

## 6. Test Facilities Utilized

### Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ26	200136	Rohde & Schwarz	1 year	2017-10-25
2	Shielding Room	S81	/	ETS-Lindgren	/	/
3	LISN	ENV216	101200	Rohde & Schwarz	1 year	2017-07-10
4	Test Receiver	ESCI	100344	Rohde & Schwarz	1 year	2017-03-01

### Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESCI 7	100948	Rohde & Schwarz	1 year	2017-07-05
2	Loop antenna	HFH2-Z2	829324/00 7	Rohde & Schwarz	3 years	2017-12-16
3	BiLog Antenna	VULB9163	235	Schwarzbeck	3 years	2019-05-10
4	Dual-Ridge Waveguide Horn Antenna	3115	6914	EMCO	3 years	2017-12-15
5	Dual-Ridge Waveguide Horn Antenna	3116	2661	ETS-Lindgren	3 years	2017-06-30
6	Vector Signal Analyzer	FSV	101047	Rohde & Schwarz	1 year	2017-06-28

## **7. Measurement Uncertainty**

### **7.1. Peak Output Power - Conducted**

**Measurement Uncertainty:**

Measurement Uncertainty (k=2)	0.66dB
-------------------------------	--------

### **7.2. Frequency Band Edges**

**Measurement Uncertainty:**

Measurement Uncertainty (k=2)	0.66dB
-------------------------------	--------

### **7.3. Conducted Emission**

**Measurement Uncertainty:**

Frequency Range	Uncertainty (k=2)
30 MHz ~ 8 GHz	1.22dB
8 GHz ~ 12.75 GHz	1.51dB
12.7GHz ~ 26 GHz	1.51dB

### **7.4. Radiated Emission**

**Measurement Uncertainty:**

Frequency Range	Uncertainty (k=2)
< 1 GHz	4.86dB
> 1 GHz	5.26dB

### **7.5. 6dB Bandwidth**

**Measurement Uncertainty:**

Measurement Uncertainty (k=2)	61.936Hz
-------------------------------	----------

### **7.6. Maximum Power Spectral Density Level**

**Measurement Uncertainty:**

Measurement Uncertainty (k=2)	0.66dB
-------------------------------	--------

## 7.7. AC Powerline Conducted Emission

### Measurement Uncertainty:

Measurement Uncertainty (k=2)	3.38dB
-------------------------------	--------

## **ANNEX A: Detailed Test Results**

### **A.1. Measurement Method**

#### **A.1.1. Conducted Measurements**

The measurement is made according to ANSI C63.10.

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).
- 3). Set the EUT to the required channel.
- 4). Set the EUT hopping mode (hopping or hopping off).
- 5). Set the spectrum analyzer to start measurement.
- 6). Record the values. Vector Signal Analyzer



#### **A.1.2. Radiated Emission Measurements**


The measurement is made according to ANSI C63.10.

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 1MHz;



## A.2. Peak Output Power - Conducted

**Method of Measurement: See ANSI C63.10-clause 11.9.1.1**

- a) Set the RBW = 1 MHz.
- b) Set VBW = 3 MHz.
- c) Set span = 3 MHz.
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

**Measurement Limit:**

Standard	Limit (dBm)
FCC Part 15.247(b)(1)	< 30

**Measurement Results:**

**For GFSK**

Channel No.	Frequency (MHz)	Peak Conducted Output Power (dBm)	Conclusion
0	2402	-0.48	P
19	2440	-0.23	P
39	2480	-0.78	P

**Conclusion: PASS**

### A.3. Frequency Band Edges - Conducted

**Method of Measurement: See ANSI C63.10-clause 6.10.4**

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below.

- a) Set Span = 8MHz
- b) Sweep Time: coupled
- c) Set the RBW= 100 kHz
- c) Set the VBW= 300 kHz
- d) Detector: Peak
- e) Trace: Max hold

Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not an absolute field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.

#### Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	< -20

#### Measurement Result:

##### For GFSK

Channel No.	Frequency (MHz)	Hopping	Band Edge Power ( dBc)		Conclusion
0	2402	Hopping OFF	Fig.1	-45.92	P
39	2480	Hopping OFF	Fig.2	-49.11	P

**Conclusion: PASS**

Test graphs as below




Fig.1. Frequency Band Edges: GFSK, 2402 MHz, Hopping Off




Fig.2. Frequency Band Edges: GFSK, 2480 MHz, Hopping Off

#### A.4. Transmitter Spurious Emission - Conducted

**Method of Measurement:** See ANSI C63.10-clause 11.11.2 and clause 11.11.3

##### **Measurement Procedure – Reference Level**

1. Set the RBW = 100 kHz.
2. Set the VBW = 300 kHz.
3. Set the span to  $\geq 1.5$  times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum PSD level. Next, determine the power in 100 kHz band segments outside of the authorized frequency band using the following measurement:

##### **Measurement Procedure - Unwanted Emissions**

1. Set RBW = 100 kHz.
2. Set VBW = 300 kHz.
3. Set span to encompass the spectrum to be examined.
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified above.

##### **Measurement Limit:**

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

**Measurement Results:**
**For GFSK**

Channel No.	Frequency (MHz)	Frequency Range	Test Results	Conclusion
0	2402	Center Frequency	Fig.3	P
		30 MHz ~ 1 GHz	Fig.4	P
		1 GHz ~ 3 GHz	Fig.5	P
		3 GHz ~ 10 GHz	Fig.6	P
		10GHz ~ 26 GHz	Fig.7	P
19	2440	Center Frequency	Fig.8	P
		30 MHz ~ 1 GHz	Fig.9	P
		1 GHz ~ 3 GHz	Fig.10	P
		3 GHz ~ 10 GHz	Fig.11	P
		10GHz ~ 26 GHz	Fig.12	P
39	2480	Center Frequency	Fig.13	P
		30 MHz ~ 1 GHz	Fig.14	P
		1 GHz ~ 3GHz	Fig.15	P
		3 GHz ~ 10 GHz	Fig.16	P
		10 GHz ~ 26 GHz	Fig.17	P


**Conclusion: PASS**
**Test graphs as below**


Fig.3. Transmitter Spurious Emission - Conducted: GFSK,2402MHz




Fig.4. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz, 30MHz - 1GHz




Fig.5. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz,1GHz - 3GHz




Fig.6. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz,3GHz - 10GHz




Fig.7. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz,10GHz - 26GHz




Fig.8. Transmitter Spurious Emission - Conducted: GFSK, 2440MHz




Fig.9. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 30MHz - 1GHz




Fig.10. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 1GHz – 3GHz




Fig.11. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 3GHz – 10GHz




Fig.12. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 10GHz – 26GHz



Fig.13. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz




Fig.14. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 30MHz - 1GHz




Fig.15. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 1GHz - 3GHz




Fig.16. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 3GHz - 10GHz




Fig.17. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 10GHz - 26GHz

### A.5. Transmitter Spurious Emission - Radiated

#### Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

The measurement is made according to ANSI C63.10

#### Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

#### Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15
4000-18000	1MHz/1MHz	40
18000-26500	1MHz/1MHz	20

#### Measurement Results:

A "reference path loss" is established and the  $A_{RPL}$  is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{RPL}$$

#### For GFSK

Frequency	Frequency Range	Test Results	Conclusion
Power	2.38GHz~2.4GHz---L	Fig.18	P
Power	2.45GHz~2.5GHz---H	Fig.19	P

**GFSK 2402MHz-Peak**

Frequency (MHz)	Measurement Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
2385.446	59.7	2.9	32.0	24.79	74.0	14.3	H
2389.576	59.5	2.9	32.0	24.63	74.0	14.5	V
4803.750	38.7	-32.9	34.5	37.02	74.0	35.3	V
7206.000	41.0	-31.6	36.1	36.49	74.0	33.0	V
9608.250	42.5	-30.0	37.0	35.58	74.0	31.5	V
12009.750	47.2	-29.8	39.3	37.70	74.0	26.8	V

**GFSK 2440MHz-Peak**

Frequency (MHz)	Measurement Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
2348.600	49.5	-27.7	31.6	45.56	74.0	24.5	V
2502.800	51.0	-26.3	32.3	44.97	74.0	23.0	V
4881.750	38.9	-32.7	34.5	37.11	74.0	35.1	V
7323.000	40.7	-31.9	36.1	36.51	74.0	33.3	H
9764.250	42.6	-30.6	37.2	35.99	74.0	31.4	V
12204.750	45.6	-29.4	39.2	35.77	74.0	28.4	H

**GFSK 2480MHz-Peak**

Frequency (MHz)	Measurement Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
2483.520	59.8	2.9	32.8	24.12	74.0	14.2	V
2483.990	59.8	2.9	32.7	24.13	74.0	14.2	H
4959.750	37.8	-33.4	34.5	36.72	74.0	36.2	V
7440.000	41.3	-31.8	36.0	37.00	74.0	32.7	V
9920.250	44.0	-29.9	37.4	36.57	74.0	30.0	V
12399.750	45.4	-29.5	39.1	35.81	74.0	28.6	V

**GFSK 2402MHz–Average**

Frequency (MHz)	Measurement Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
2387.500	46.3	2.9	32.0	11.42	54.0	7.7	H
2389.200	46.3	2.9	32.0	11.41	54.0	7.7	V
4804.500	35.1	-32.8	34.5	33.40	54.0	18.9	H
7206.000	37.9	-31.6	36.1	33.38	54.0	16.1	H
9607.500	40.5	-30.0	37.0	33.52	54.0	13.5	H
12010.500	43.2	-29.8	39.3	33.74	54.0	10.8	H

**GFSK 2440MHz–Average**

Frequency (MHz)	Measurement Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
2385.790	46.5	2.9	32.0	11.62	54.0	7.5	V
2488.620	46.6	2.9	32.6	11.07	54.0	7.4	H
4882.500	35.3	-32.7	34.5	33.47	54.0	18.7	H
7323.000	37.6	-31.9	36.1	33.45	54.0	16.4	H
9763.500	40.1	-30.6	37.2	33.45	54.0	13.9	H
12205.500	43.6	-29.4	39.2	33.83	54.0	10.4	H

**GFSK 2480MHz–Average**

Frequency (MHz)	Measurement Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
2483.500	47.0	2.9	32.8	11.32	54.0	7.0	H
2484.500	47.0	2.9	32.7	11.29	54.0	7.0	V
4960.500	34.7	-33.4	34.5	33.60	54.0	19.3	H
7440.000	37.7	-31.8	36.0	33.41	54.0	16.3	H
9919.500	40.9	-29.9	37.4	33.46	54.0	13.1	H
12400.500	43.9	-29.5	39.1	34.25	54.0	10.1	H

**Conclusion: PASS**
**Test graphs as below for Set.10:**




Fig.18. Transmitter Spurious Emission - Radiated (Power): GFSK low channel




Fig.19. Transmitter Spurious Emission - Radiated (Power): GFSK high channel

## A.6. 6dB Bandwidth

### Method of Measurement:

The measurement is made according to ANSI C63.10 clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) = 300 kHz.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(2)	>= 500KHz

### Measurement Results:

#### For GFSK

Channel No.	Frequency (MHz)	6dB Bandwidth (kHz)	Conclusion
0	2402	Fig.20	P
19	2440	Fig.21	P
39	2480	Fig.22	P

Conclusion: PASS

Test graphs as below:




Fig.20. 6dB Bandwidth: GFSK, 2402 MHz




Fig.21. 6dB Bandwidth: GFSK, 2440 MHz




Fig.22. 6dB Bandwidth: GFSK, 2480 MHz

## A.7. Maximum Power Spectral Density Level

### Method of Measurement:

The measurement is made according to ANSI C63.10 clause 11.10.2

1. Set the RBW = 3 kHz.
2. Set the VBW = 10 kHz.
3. Set the span to 2 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.

### Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(e)	<=8.0dBm/3kHz

### Measurement Results:

#### For GFSK

Channel No.	Frequency (MHz)	Maximum Power Spectral Density Level(dBm/3kHz)	Conclusion
0	2402	Fig.23	-15.98
19	2440	Fig.24	-15.92
39	2480	Fig.25	-16.48

Test graphs as below:




Fig.23. Maximum Power Spectral Density Level Function: GFSK, 2402 MHz




Fig.24. Maximum Power Spectral Density Level Function: GFSK, 2440 MHz




Fig.25. Maximum Power Spectral Density Level Function: GFSK, 2480 MHz

## A.8. AC Powerline Conducted Emission

**Method of Measurement: See ANSI C63.10-clause 6.2**

1. the one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.
2. If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.
3. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.
4. If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.
5. If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements.<sup>36</sup> Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

### Test Condition

Voltage (V)	Frequency (Hz)
120	60

### Measurement Result and limit:

#### Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB $\mu$ V)	Conclusion
0.15 to 0.5	66 to 56	P
0.5 to 5	56	
5 to 30	60	

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

**Bluetooth (Average Limit)**

Frequency range (MHz)	Average Limit (dB $\mu$ V)	Conclusion
0.15 to 0.5	56 to 46	P
0.5 to 5	46	
5 to 30	50	


NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

The measurement is made according to ANSI C63.10

**Conclusion: PASS**

**Test graphs as below:**

Traffic: Set.10




## Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.324500	48.6	GND	L1	10.3	7.4	56.0
1.378500	49.7	GND	N	10.4	6.3	56.0
1.437000	50.2	GND	N	10.4	5.8	56.0
1.495500	48.5	GND	L1	10.3	7.5	56.0
1.855500	48.1	GND	L1	10.4	7.9	56.0
1.918500	49.3	GND	N	10.4	6.7	56.0

## Final Result 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.960000	36.8	GND	L1	10.3	9.2	46.0
1.275000	36.6	GND	N	10.4	9.4	46.0
1.329000	38.2	GND	N	10.4	7.8	46.0
1.383000	38.7	GND	L1	10.3	7.3	46.0
1.437000	38.2	GND	N	10.4	7.8	46.0
1.864500	36.6	GND	L1	10.4	9.4	46.0

Traffic: Set.11




## Final Result 1

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.555000	45.4	GND	L1	10.3	10.6	56.0
0.748500	39.7	GND	N	10.4	16.3	56.0
1.135500	40.3	GND	L1	10.3	15.7	56.0
2.080500	38.8	GND	L1	10.4	17.2	56.0
2.125500	38.8	GND	N	10.5	17.2	56.0
2.485500	38.3	GND	N	10.5	17.7	56.0

## Final Result 2

Frequency (MHz)	Average (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.564000	34.1	GND	N	10.4	11.9	46.0
1.108500	29.9	GND	L1	10.3	16.1	46.0
1.639500	28.1	GND	L1	10.3	17.9	46.0
2.116500	28.8	GND	N	10.5	17.2	46.0
2.125500	29.0	GND	N	10.5	17.0	46.0
2.526000	28.0	GND	L1	10.4	18.0	46.0

Traffic: Set.12




## Final Result 1

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.573000	42.4	GND	N	10.4	13.6	56.0
4.969500	37.1	GND	L1	10.5	18.9	56.0
9.784500	40.9	GND	L1	10.7	19.1	60.0
10.693500	39.6	GND	N	10.7	20.4	60.0
10.954500	40.8	GND	N	10.7	19.2	60.0
11.598000	39.7	GND	N	10.7	20.3	60.0

## Final Result 2

Frequency (MHz)	Average (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.258000	36.4	GND	L1	10.3	15.1	51.5
0.312000	34.2	GND	L1	10.3	15.7	49.9
0.361500	34.2	GND	L1	10.3	14.5	48.7
0.415500	31.5	GND	L1	10.3	16.0	47.5
0.573000	36.3	GND	L1	10.3	9.7	46.0
4.416000	29.9	GND	N	10.5	16.1	46.0

Idle: Set.10



## Final Result 1

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
1.378500	49.9	GND	L1	10.3	6.1	56.0
1.437000	50.2	GND	N	10.4	5.8	56.0
1.495500	48.8	GND	L1	10.3	7.2	56.0
1.797000	46.0	GND	L1	10.4	10.0	56.0
1.860000	49.3	GND	N	10.4	6.7	56.0
1.918500	49.5	GND	L1	10.4	6.5	56.0

## Final Result 2

Frequency (MHz)	Average (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
1.329000	38.2	GND	L1	10.3	7.8	46.0
1.387500	36.6	GND	L1	10.3	9.4	46.0
1.437000	38.4	GND	N	10.4	7.6	46.0
1.806000	37.0	GND	N	10.4	9.0	46.0
1.864500	36.8	GND	N	10.4	9.2	46.0
1.918500	36.8	GND	L1	10.4	9.2	46.0

\*\*\*END OF REPORT\*\*\*