



TEST REPORT

No. I17Z60685-EMC01

for

TCL Communication Ltd.

LTE / UMTS / GSM mobile phone

Model Name: 5085Y

FCC ID: 2ACCJH074

with

Hardware Version: PIO

Software Version: 1AA4

Issued Date: 2017-06-08

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

FCC 2.948 Listed: No.525429

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: ctl_terminals@catr.cn, website: www.chinattl.com

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I17Z60685-EMC01	Rev.0	1 st edition	2017-05-24
I17Z60685-EMC01	Rev.1	Delete charger CBA0058ABAC3	2017-06-06
I17Z60685-EMC01	Rev.2	Add charger CBA0058AGAC2, CBA0058AGAC4, CBA0058AGAC3	2017-06-08

CONTENTS

1. TEST LABORATORY	4
1.1. TESTING LOCATION	4
1.2. TESTING ENVIRONMENT	4
1.3. PROJECT DATA	4
1.4. SIGNATURE	4
2. CLIENT INFORMATION	5
2.1. APPLICANT INFORMATION	5
2.2. MANUFACTURER INFORMATION	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT	6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	6
3.4. EUT SET-UPS	8
4. REFERENCE DOCUMENTS	9
4.1. REFERENCE DOCUMENTS FOR TESTING	9
5. LABORATORY ENVIRONMENT	10
6. SUMMARY OF TEST RESULTS	11
7. TEST EQUIPMENTS UTILIZED	12
ANNEX A: MEASUREMENT RESULTS	13

1. Test Laboratory

1.1. Testing Location

CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China
100191


1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2016-12-08
Testing End Date: 2017-05-22


1.4. Signature



Wang Junqing
(Prepared this test report)



Zhang Ying
(Reviewed this test report)



Liu Baodian
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Contact Person: Gong Zhizhou
Contact Email: zhizhou.gong@tcl.com
Telephone: 0086-21-31363544
Fax: 0086-21-61460602

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Contact Person: Gong Zhizhou
Contact Email: zhizhou.gong@tcl.com
Telephone: 0086-21-31363544
Fax: 0086-21-61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	LTE / UMTS / GSM mobile phone
Model Name	5085Y
FCC ID	2ACCJH074
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.8VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	357577080000223	PIO	1AA4

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN	Remarks
AE1	Battery	/	inbuilt
AE2	Battery	/	inbuilt
AE3	Battery	/	inbuilt
AE4	Charger	/	16TCT-CH-1489
AE5	Charger	/	16TCT-CH-1565
AE6	Charger	/	16TCT-CH-0860
AE7	USB Cable	/	16TCT-DC-0493
AE8	USB Cable	/	16TCT-DC-0501
AE9	USB Cable	/	/
AE10	USB Cable	/	/
AE11	Headset	/	16TCT-HS-1704
AE12	Headset	/	16TCT-HS-1602
AE21	Charger	/	/
AE23	Travel charger	/	/
AE24	Travel charger	/	/
AE25	Travel charger	/	/

AE1

Model	CAC2710008CJ
Manufacturer	COSLIGHT
Capacitance	2710 mAh
Nominal voltage	V

AE2

Model	CAC2710004C1
Manufacturer	BYD
Capacitance	2710 mAh

Nominal voltage	V
AE3	
Model	CAC2710005CC
Manufacturer	Jinneng
Capacitance	2710 mAh
Nominal voltage	V
AE4	
Model	CBA0058AAC2
Manufacturer	TEPAO
Length of cable	/
AE5	
Model	CBA0058AAC4
Manufacturer	Aohai
Length of cable	/
AE6	
Model	CBA0058AAC3
Manufacturer	YINGJU
Length of cable	/
AE7	
Model	CDA3122005C2
Manufacturer	Shenhua
Length of cable	100cm
AE8	
Model	CDA3122005C1
Manufacturer	Juwei
Length of cable	100cm
AE9	
Model	CDA3122002C2
Manufacturer	Shenhua
Length of cable	100cm
AE10	
Model	CDA3122002C1
Manufacturer	Juwei
Length of cable	100cm
AE11	
Model	CCB0049A10C1
Manufacturer	Juwei
Length of cable	120cm
AE12	
Model	CCB0049A10C4
Manufacturer	Meihao

Length of cable	124cm
AE21	
Model	CBA0058ABAC2
Manufacturer	TENPAO
Length of cable	/
AE23	
Model	CBA0058AGAC2
Manufacturer	Tenpao
AE24	
Model	CBA0058AGAC4
Manufacturer	Aohai
AE25	
Model	CBA0058AGAC3
Manufacturer	YINGJU

*AE ID: is used to identify the test sample in the lab internally.

Note: The USB cables are shielded.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1/AE2/AE3+ AE4+ AE7/AE8	Charger
Set.2	EUT1+ AE1/AE2/AE3+ AE5+ AE7/AE8	Charger
Set.3	EUT1+ AE1/AE2/AE3+ AE6+ AE7/AE8	Charger
Set.5	EUT1+ AE1/AE2/AE3+ AE7/AE8	USB mode

Note: The LTE / UMTS / GSM mobile phone 5085Y manufactured by TCL Communication Ltd. is a variant model based on 5085A for conformance test. According to the declaration of changes, the following items are tested on Set.1, Set 2, Set 3 and Set.5

Mode of Feature	EUT set-up No	Test Item
GSM1900MHz	Set.1, Set 2, Set 3 and Set.5	Radiated Emission

Other results are inherited from the initial model. The report number of initial model is I16Z42266-EMC01.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices - Unintentional Radiators	10-1-15
ANSI C63.4	American National Standard for Methods of Measurement of Radio- Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	Edition 2014

Note: The test methods have no deviation with standards.

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber SAC-1 (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ±4 dB, 10 m distance
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 6GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Shielded room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:		
Verdict Column	P	Pass
	NA	Not applicable
	F	Fail

Items	Test Name	Clause in FCC rules	Section in this report	Verdict	Test Location
1	Radiated Emission	15.109(a)	B.1	P	CTTL(huayuan North Road)
2	Conducted Emission	15.107(a)	B.2	P	CTTL(huayuan North Road)

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE	CALIBRATION INTERVAL
1	Test Receiver	ESU26	100235	R&S	2018-04-01	1 year
2	Test Receiver	ESCI 7	100344	R&S	2017-07-05	1 year
3	Universal Radio Communication Tester	CMW500	143008	R&S	2017-12-01	1 year
4	Universal Radio Communication Tester	CMW500	155415	R&S	2017-01-11	1 year
5	LISN	ENV216	101200	R&S	2017-07-10	1 year
6	EMI Antenna	VULB 9163	9163-301	Schwarzbeck	2017-12-16	3 years
7	EMI Antenna	3115	6914	ETS-Lindgren	2017-12-15	3 years
8	PC	OPTIPLEX 380	2X1YV2X	DELL	N/A	N/A
9	Printer	P1606dn	VNC3L52122	HP	N/A	N/A
10	Keyboard	L100	CN0RH6596589 07ATOI40	DELL	N/A	N/A
11	Mouse	M-UAE119	LZ935220ZRC	Lenovo	N/A	N/A

Test Item	Test Software and Version	Software Vendor
Radiated Continuous Emission	EMC32 V9.01	R&S
Conducted Emission	EMC32 V8.52.0	R&S

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission

Reference

FCC: CFR Part 15.109(a).

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at distances of 10 meters(for 30MHz-1GHz) and 3 meters (for above 1GHz) is tested. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

A.1.3 Measurement Limit

Frequency range (MHz)	Field strength limit (μ V/m)		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

Note: the above limit is for 3 meters test distance. 10 meters' limit is got by converting.

A.1.4 Test Condition

Frequency range (MHz)	RBW/VBW	Sweep Time (s)	Detector
30-1000	120kHz (IF Bandwidth)	5	Peak/Quasi-peak
Above 1000	1MHz/1MHz	15	Peak, Average

A.1.5 Measurement Results

A "reference path loss" is established and the A_{RPL} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{RPL} = P_{\text{Mea}} + G_A + G_{PL}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Measurement uncertainty (worst case): $U = 4.3 \text{ dB}$, $k=2$.

Measurement results for Set.1:

Charging Mode/Average detector

Frequency(MHz)	Result(dB μ V/m)	G_{PL} (dB)	G_A (dB/m)	P_{Mea} (dB μ V)	Polarity
17943.333	44.1	-17.7	45.6	16.200	V
17958.067	44.1	-17.7	45.6	16.200	H
17911.033	44.0	-18.5	45.6	16.900	H
17926.900	43.9	-17.7	45.6	16.000	V
17900.267	43.9	-18.5	45.6	16.800	V
17916.700	43.8	-17.7	45.6	15.900	H

Charging Mode/Peak detector

Frequency(MHz)	Result(dB μ V/m)	G_{PL} (dB)	G_A (dB/m)	P_{Mea} (dB μ V)	Polarity
17896.867	55.4	-18.5	45.6	28.300	V
17868.533	55.2	-18.5	45.6	28.100	H
17839.067	55.2	-18.5	45.6	28.100	H
17936.533	55.0	-17.7	45.6	27.100	V
17758.033	55.0	-18.5	45.6	27.900	H
17895.733	55.0	-18.5	45.6	27.900	H

Sample calculation: Peak detector, 17895.733MHz

$$\text{Result} = P_{\text{Mea}} (27.900 \text{dB}\mu\text{V}) + G_A (45.6 \text{dB/m}) + G_{PL} (-18.5 \text{ dB}) = 55.0 \text{dB}\mu\text{V/m}$$

Measurement results for Set.2:
Charging Mode/Average detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17956.933	44.1	-17.7	45.6	16.200	V
17921.233	44.1	-17.7	45.6	16.200	H
17933.700	43.9	-17.7	45.6	16.000	H
17952.400	43.9	-17.7	45.6	16.000	V
17945.600	43.9	-17.7	45.6	16.000	V
17911.600	43.8	-18.5	45.6	16.700	H

Charging Mode/Peak detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17971.100	54.9	-17.7	45.6	27.000	H
17949.000	54.8	-17.7	45.6	26.900	V
17885.533	54.8	-18.5	45.6	27.700	V
17945.600	54.8	-17.7	45.6	26.900	V
17860.600	54.7	-18.5	45.6	27.600	H
17931.433	54.6	-17.7	45.6	26.700	H

Sample calculation: Peak detector, 17860.600MHz

$$\text{Result} = P_{\text{Mea}} (27.600 \text{dB}\mu\text{V}) + G_A (45.6 \text{dB/m}) + G_{\text{PL}} (-18.5 \text{dB}) = 54.7 \text{dB}\mu\text{V/m}$$

Measurement results for Set.3:
Charging Mode/Average detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17964.300	44.4	-17.7	45.6	16.500	V
17925.200	43.9	-17.7	45.6	16.000	H
17960.900	43.9	-17.7	45.6	16.000	H
17991.500	43.9	-17.7	45.6	16.000	H
17946.733	43.9	-17.7	45.6	16.000	H
17935.400	43.8	-17.7	45.6	15.900	V

Charging Mode/Peak detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17949.567	55.5	-17.7	45.6	27.600	H
17820.933	55.2	-18.5	45.6	28.100	V
17921.800	54.7	-17.7	45.6	26.800	H
17852.100	54.7	-18.5	45.6	27.600	V
17883.833	54.6	-18.5	45.6	27.500	V
17938.800	54.6	-17.7	45.6	26.700	H

Sample calculation: Peak detector, 17938.800MHz

$$\text{Result} = P_{\text{Mea}} (26.700 \text{dB}\mu\text{V}) + G_A (45.6 \text{dB/m}) + G_{\text{PL}} (-17.7 \text{dB}) = 54.6 \text{dB}\mu\text{V/m}$$

Measurement results for Set.5:
USB Mode/Average detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{mea} (dB μ V)	Polarity
17940.500	44.1	-17.7	45.6	16.200	V
17945.600	44.0	-17.7	45.6	16.100	H
17969.400	44.0	-17.7	45.6	16.100	V
17923.500	44.0	-17.7	45.6	16.100	V
17853.233	43.9	-18.5	45.6	16.800	H
17947.867	43.8	-17.7	45.6	15.900	H

USB Mode/ Peak detector


Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{mea} (dB μ V)	Polarity
17898.000	55.4	-18.5	45.6	28.300	V
17847.000	54.9	-18.5	45.6	27.800	H
17875.333	54.8	-18.5	45.6	27.700	V
17841.900	54.7	-18.5	45.6	27.600	H
17955.233	54.6	-17.7	45.6	26.700	V
17858.333	54.4	-18.5	45.6	27.300	H

Sample calculation: Peak detector, 17858.333MHz


$$\text{Result} = P_{\text{Mea}} (27.300 \text{dB}\mu\text{V}) + G_A (45.6 \text{dB/m}) + G_{\text{PL}} (-18.5 \text{ dB}) = 54.4 \text{dB}\mu\text{V/m}$$

Charging Mode, Set.1

15B RE 30MHz-1GHz

**Figure A.1 Radiated Emission from 30MHz to 1GHz**

Full Spectrum

**Figure A.2 Radiated Emission from 1GHz to 18GHz**

Charging Mode, Set.2




Figure A.3 Radiated Emission from 30MHz to 1GHz






Figure A.4 Radiated Emission from 1GHz to 18GHz

Charging Mode, Set.3

15B RE 30MHz-1GHz


**Figure A.3 Radiated Emission from 30MHz to 1GHz**

Full Spectrum


**Figure A.4 Radiated Emission from 1GHz to 18GHz**

USB Mode, Set.5

15B RE 30MHz-1GHz


Figure A.7 Radiated Emission from 30MHz to 1GHz
Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
135.633000	36.9	100.0	V	259.0	-20.8	6.6	43.5


Figure A.8 Radiated Emission from 1GHz to 18GHz

A.2 Conducted Emission

Reference

FCC: CFR Part 15.107(a).

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 7.3.

A.2.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW/IF bandwidth	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results

Measurement uncertainty: $U= 2.9$ dB, $k=2$.

Charging Mode, Set.1





Figure A.9 Conducted Emission

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
1.486500	45.1	GND	L1	10.3	10.9	56.0
1.545000	45.1	GND	L1	10.3	10.9	56.0
1.797000	45.4	GND	L1	10.4	10.6	56.0
1.828500	45.4	GND	L1	10.4	10.6	56.0
1.959000	43.8	GND	L1	10.4	12.2	56.0
1.986000	44.5	GND	L1	10.4	11.5	56.0

Final Result 2


Frequency (MHz)	Average (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.406500	39.3	GND	N	10.4	8.5	47.7
0.537000	39.1	GND	N	10.4	6.9	46.0
0.874500	38.2	GND	N	10.4	7.8	46.0
0.942000	37.7	GND	N	10.4	8.3	46.0
1.414500	36.6	GND	N	10.4	9.4	46.0
4.510500	34.3	GND	L1	10.5	11.7	46.0

Charging Mode, Set.2

Figure A.10 Conducted Emission
Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	47.3	GND	L1	10.3	18.7	66.0
0.258000	37.8	GND	L1	10.3	23.7	61.5
0.564000	40.5	GND	L1	10.3	15.5	56.0
0.775500	30.4	GND	N	10.4	25.6	56.0
1.167000	31.3	GND	N	10.4	24.7	56.0
2.107500	30.4	GND	N	10.5	25.6	56.0

Final Result 2


Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	32.5	GND	L1	10.3	23.5	56.0
0.186000	31.3	GND	L1	10.3	22.9	54.2
0.568500	32.5	GND	L1	10.3	13.5	46.0
1.167000	27.6	GND	L1	10.3	18.4	46.0
1.252500	26.3	GND	L1	10.3	19.7	46.0
2.148000	26.8	GND	L1	10.4	19.2	46.0

Charging Mode, Set.3

Figure A.10 Conducted Emission
Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.195000	45.8	GND	L1	10.3	18.0	63.8
0.240000	44.0	GND	L1	10.3	18.1	62.1
0.586500	41.6	GND	L1	10.3	14.4	56.0
10.923000	41.2	GND	L1	10.7	18.8	60.0
10.941000	41.3	GND	L1	10.7	18.7	60.0
11.008500	39.5	GND	L1	10.7	20.5	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.240000	36.7	GND	L1	10.3	15.4	52.1
0.289500	35.2	GND	L1	10.3	15.3	50.5
0.339000	34.5	GND	L1	10.3	14.7	49.2
0.388500	33.2	GND	L1	10.3	14.9	48.1
0.577500	35.7	GND	L1	10.3	10.3	46.0
0.627000	31.7	GND	L1	10.3	14.3	46.0

USB Mode, Set.5

Figure A.12 Conducted Emission
Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.195000	46.4	GND	L1	10.3	17.4	63.8
2.022000	47.1	GND	L1	10.4	8.9	56.0
2.134500	43.0	GND	N	10.5	13.0	56.0
3.246000	42.5	GND	L1	10.4	13.5	56.0
3.871500	29.5	GND	N	10.5	26.5	56.0
4.348500	35.0	GND	L1	10.5	21.0	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.195000	41.4	GND	L1	10.3	12.4	53.8
0.262500	31.2	GND	L1	10.3	20.1	51.4
1.999500	38.4	GND	N	10.5	7.6	46.0
2.125500	34.1	GND	L1	10.4	11.9	46.0
3.246000	31.4	GND	L1	10.4	14.6	46.0
4.389000	26.7	GND	L1	10.5	19.3	46.0

*****END OF REPORT*****