



TEST REPORT

No. I18Z61180-EMC01

for

TCL Communication Ltd.

GSM/UMTS/LTE mobile phone

Model Name: 5059R

FCC ID: 2ACCJH092

with

Hardware Version: 01

Software Version: AQ33UA30

Issued Date: 2018-07-23



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn



REPORT HISTORY

Report Number	Revision	Description	Issue Date
I18Z61180-EMC01	Rev.0	1 st edition	2018-07-23

CONTENTS

1. TEST LABORATORY	4
1.1. TESTING LOCATION	4
1.2. TESTING ENVIRONMENT	4
1.3. PROJECT DATA	4
1.4. SIGNATURE.....	4
2. CLIENT INFORMATION.....	5
2.1. APPLICANT INFORMATION.....	5
2.2. MANUFACTURER INFORMATION.....	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT.....	6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	6
3.4. EUT SET-UPS	7
4. REFERENCE DOCUMENTS.....	8
4.1. REFERENCE DOCUMENTS FOR TESTING.....	8
5. LABORATORY ENVIRONMENT.....	9
6. SUMMARY OF TEST RESULTS.....	10
7. TEST EQUIPMENTS UTILIZED.....	11
ANNEX A: MEASUREMENT RESULTS	12
ANNEX B: PERSONS INVOLVED IN THIS TESTING	22

1. Test Laboratory

1.1. Testing Location

Location: CTTL (huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China
100191

1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2018-07-04
Testing End Date: 2018-07-20

1.4. Signature




Li Yan

(Prepared this test report)



Zhang Ying

(Reviewed this test report)



Liu Baodian

Deputy Director of the laboratory

(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.
7/F, Block F4, TCL Communication Technology Building, TCL
Address /Post: International E City, Zhong Shan Yuan Road, Nanshan District,
Shenzhen, Guangdong, P.R. China 518052
Contact Person: Gong Zhizhou
Contact Email: zhizhou.gong@tcl.com
Telephone: 0086-755-36611722
Fax: 0086-75536612000-81722

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
7/F, Block F4, TCL Communication Technology Building, TCL
Address /Post: International E City, Zhong Shan Yuan Road, Nanshan District,
Shenzhen, Guangdong, P.R. China 518052
Contact Person: Gong Zhizhou
Contact Email: zhizhou.gong@tcl.com
Telephone: 0086-755-36611722
Fax: 0086-75536612000-81722

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	GSM/UMTS/LTE mobile phone
Model Name	5059R
FCC ID	2ACCJH092
Extreme vol. Limits	3.5VDC to 4.4VDC (nominal: 3.8VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, CAICT.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT2	015242000001041	01	AQ33UA30

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN	Remarks
AE1	Battery	/	/
AE2	Charger	/	/
AE3	Charger	/	/
AE4	USB cable	/	/
AE5	USB cable	/	/

AE1

Model	CAC2400038C1
Manufacturer	BYD
Capacitance	2460mAh
Nominal voltage	/

AE2

Model	CBA0058AGHC5
Manufacturer	Puan
Length of cable	/

AE3

Model	CBA0058AGAC7
Manufacturer	CHENYANG
Length of cable	/

AE4

Model	CDA3122006C1
Manufacturer	JUWEI
Length of cable	/

AE5

Model	CDA3122006C2
Manufacturer	SHENGHUA
Length of cable	/

*AE ID: is used to identify the test sample in the lab internally.

Note: The USB cables are shielded.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT2+AE1+AE2+AE4/AE5	Charger
Set.2	EUT2+AE1+AE3+AE4/AE5	Charger
Set.3	EUT2+AE1+AE4/AE5	USB mode

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices - Unintentional Radiators	2016
ANSI C63.4	American National Standard for Methods of Measurement of Radio- Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

Note: The test methods have no deviation with standards.

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber SAC-1 (23meters × 17meters × 10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ±4 dB, 10 m distance
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 6GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Semi-anechoic chamber SAC-2 (10meters × 6.7meters × 6.1meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ± 4 dB, 3m distance, from 30 to 1000 MHz
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Shielded room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz – 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:		
Verdict Column	P	Pass
	NA	Not applicable
	F	Fail

Items	Test Name	Clause in FCC rules	Section in this report	Verdict	Test Location
1	Radiated Emission	15.109(a)	A.1	P	CTTL(huayuan North Road)
2	Conducted Emission	15.107(a)	A.2	P	CTTL(huayuan North Road)

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE	CALIBRATION INTERVAL
1	Test Receiver	ESU26	100235	R&S	2019-03-31	1 year
2	Universal Radio Communication Tester	CMW500	143008	R&S	2018-12-26	1 year
3	Test Receiver	ESCI 3	100344	R&S	2019-02-28	1 year
4	Universal Radio Communication Tester	CMW500	116588	R&S	2018-11-26	1 year
5	LISN	ENV216	101200	R&S	2018-08-03	1 year
6	EMI Antenna	VULB9163	9163-302	Schwarzbeck	2020-02-27	3 years
7	EMI Antenna	3115	00167250	ETS-Lindgren	2020-05-21	3 years
8	PC	OPTIPLEX 380	2X1YV2X	DELL	N/A	N/A
9	Printer	P1606dn	VNC3L52122	HP	N/A	N/A
10	Keyboard	L100	CN0RH6596589 07ATOI40	DELL	N/A	N/A
11	Mouse	M-UAE119	LZ935220ZRC	Lenovo	N/A	N/A

Test Item	Test Software and Version	Software Vendor
Radiated Continuous Emission	EMC32 V9.01	R&S
Conducted Emission	EMC32 V8.52.0	R&S

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission

Reference

FCC: CFR Part 15.109(a).

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at distances of 10 meters(for 30MHz-1GHz) and 3 meters (for above 1GHz) is tested. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

A.1.3 Measurement Limit

Frequency range (MHz)	Field strength limit (μ V/m)		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

Note: the above limit is for 3 meters test distance. 10 meters' limit is got by converting.

A.1.4 Test Condition

Frequency range (MHz)	RBW/VBW	Sweep Time (s)	Detector
30-1000	120kHz (IF Bandwidth)	5	Peak/Quasi-peak
Above 1000	1MHz/1MHz	15	Peak, Average

A.1.5 Measurement Results

A "reference path loss" is established and the A_{RPL} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{RPL} = P_{\text{Mea}} + G_A + G_{PL}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Measurement uncertainty (worst case): 4.3dB, $k=2$.

Measurement results for Set.1:

Charging Mode/Average detector

Frequency(MHz)	Result(dB μ V/m)	G_{PL} (dB)	G_A (dB/m)	P_{Mea} (dB μ V)	Polarity
17983.567	49.4	-25.5	43.4	31.502	H
17970.533	49.1	-25.5	43.4	31.202	H
17981.300	49.9	-25.5	43.4	32.002	V
17988.667	50.8	-25.5	43.4	32.902	H
17976.767	50.0	-25.5	43.4	32.102	H
17987.533	49.1	-25.5	43.4	31.202	H

Charging Mode/Peak detector

Frequency(MHz)	Result(dB μ V/m)	G_{PL} (dB)	G_A (dB/m)	P_{Mea} (dB μ V)	Polarity
17982.433	51.7	-25.5	43.4	33.802	H
17761.433	50.9	-25.7	43.4	33.242	H
17992.633	50.8	-25.5	43.4	32.902	V
17988.667	50.8	-25.5	43.4	32.902	H
17864.567	50.7	-25.7	43.4	33.042	H
17967.133	50.7	-25.5	43.4	32.802	H

Measurement results for Set.2:
Charging Mode/Average detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17983.567	40.2	-25.5	43.4	22.302	H
17993.767	39.9	-25.5	43.4	22.002	H
17981.867	39.9	-25.5	43.4	22.002	V
17976.200	39.8	-25.5	43.4	21.902	H
17985.267	39.7	-25.5	43.4	21.802	H
17977.333	39.7	-25.5	43.4	21.802	H

Charging Mode/Peak detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17975.633	52.1	-25.5	43.4	34.202	H
17958.633	51.3	-25.5	43.4	33.402	H
17973.367	51.2	-25.5	43.4	33.302	V
17968.267	51.1	-25.5	43.4	33.202	H
17986.967	50.9	-25.5	43.4	33.002	H
17977.333	50.8	-25.5	43.4	32.902	H



Measurement results for Set.3:
USB Mode/Average detector



Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17977.900	40.1	-25.5	43.4	22.202	H
17958.633	39.8	-25.5	43.4	21.902	H
17976.200	39.7	-25.5	43.4	21.802	V
17965.433	39.7	-25.5	43.4	21.802	H
17978.467	39.7	-25.5	43.4	21.802	H
17990.933	39.7	-25.5	43.4	21.802	H

USB Mode/Peak detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
1493.000	54.1	-39.8	23.3	70.582	H
1494.133	53.4	-39.8	23.3	69.882	H
1492.433	53.4	-39.8	23.3	69.882	V
1498.667	53.0	-39.8	23.3	69.482	H
1499.233	52.8	-39.8	23.3	69.282	H
1493.567	52.8	-39.8	23.3	69.282	H

Note: The measurement results of Set.1, Set.2 and Set.3 showed here are worst cases of the combinations of different batteries and USB cables.

Charging Mode, Set.1**Figure A.1 Radiated Emission from 30MHz to 1GHz****Figure A.2 Radiated Emission from 1GHz to 18GHz**

Charging Mode, Set.2**Figure A.3 Radiated Emission from 30MHz to 1GHz****Figure A.4 Radiated Emission from 1GHz to 18GHz**

USB Mode, Set.3




Figure A.5 Radiated Emission from 30MHz to 1GHz




Figure A.6 Radiated Emission from 1GHz to 18GHz

A.2 Conducted Emission

Reference

FCC: CFR Part 15.107(a).

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 7.3.

A.2.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW/IF bandwidth	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results

Measurement uncertainty: $U = 2.9 \text{ dB}$, $k=2$.

Charging Mode, Set.1




Figure A.7 Conducted Emission


Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.181500	44.7	2000.0	9.000	On	L1	19.8	19.7
0.541500	41.3	2000.0	9.000	On	L1	19.9	14.7
1.081500	39.7	2000.0	9.000	On	L1	19.6	16.3
1.558500	37.7	2000.0	9.000	On	L1	19.7	18.3
2.953500	35.8	2000.0	9.000	On	L1	19.7	20.2
4.236000	33.6	2000.0	9.000	On	L1	19.6	22.4

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.312000	29.3	2000.0	9.000	On	L1	19.8	20.7
0.541500	31.3	2000.0	9.000	On	L1	19.9	14.7
0.811500	31.7	2000.0	9.000	On	L1	19.7	14.3
1.608000	28.1	2000.0	9.000	On	L1	19.7	17.9
2.971500	26.1	2000.0	9.000	On	L1	19.7	19.9
3.903000	24.2	2000.0	9.000	On	L1	19.6	21.8

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.


Charging Mode, Set.2

Figure A.8 Conducted Emission
Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.168000	38.1	2000.0	9.000	On	L1	19.8	27.0
0.528000	46.6	2000.0	9.000	On	L1	19.9	9.4
1.059000	39.2	2000.0	9.000	On	L1	19.6	16.8
1.536000	39.3	2000.0	9.000	On	L1	19.7	16.7
2.476500	37.9	2000.0	9.000	On	L1	19.7	18.1
4.254000	34.0	2000.0	9.000	On	L1	19.6	22.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.339000	27.7	2000.0	9.000	On	N	19.9	21.6
0.528000	39.6	2000.0	9.000	On	N	19.9	6.4
1.059000	31.2	2000.0	9.000	On	L1	19.6	14.8
1.540500	31.0	2000.0	9.000	On	N	19.6	15.0
2.463000	28.2	2000.0	9.000	On	N	19.6	17.8
4.276500	26.5	2000.0	9.000	On	N	19.7	19.5

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

USB Mode, Set.3

Figure A.9 Conducted Emission
Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.222000	47.9	2000.0	9.000	On	N	19.8	14.9
0.258000	46.2	2000.0	9.000	On	N	19.8	15.3
0.658500	33.8	2000.0	9.000	On	N	19.9	22.2
0.739500	30.6	2000.0	9.000	On	N	19.9	25.4
3.151500	30.7	2000.0	9.000	On	N	19.6	25.3
4.236000	29.4	2000.0	9.000	On	N	19.7	26.6

Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.222000	45.7	2000.0	9.000	On	N	19.8	7.1
0.258000	44.3	2000.0	9.000	On	N	19.8	7.2
0.654000	31.0	2000.0	9.000	On	N	19.9	15.0
0.739500	29.0	2000.0	9.000	On	N	19.9	17.0
1.662000	26.2	2000.0	9.000	On	N	19.6	19.8
2.197500	25.9	2000.0	9.000	On	L1	19.7	20.1

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

ANNEX B: Persons involved in this testing

Test Item	Tester
Radiated Emission	Shi Suolan
Conducted Emission	Li Jinpeng

END OF REPORT