

Appendix B

GSM 850 & 1900

TABLE OF CONTENTS

1.	MAIN TEST INSTRUMENTS	3
2.	MEASUREMENT UNCERTAINTY.....	3
3.	EFFECTIVE (ISOTROPIC) RADIATED POWER OUTPUT DATA.....	4
3.1.	Test Result	4
4.	PEAK-TO-AVERAGE RATIO	5
4.1.	Test Result	5
4.2.	Part II - Test Plots	5
5.	MODULATION CHARACTERISTICS	10
5.1.	For GSM	10
5.1.1.	Test Band = GSM 850.....	10
5.1.1.1.	Test Mode = GSM/TM1.....	10
5.1.1.1.1.	Test Channel = MCH.....	10
5.1.1.2.	Test Mode = GSM/TM2.....	11
5.1.1.2.1.	Test Channel = MCH.....	11
5.1.2.	Test Band = GSM 1900	11
5.1.2.1.	Test Mode = GSM/TM1.....	11
5.1.2.1.1.	Test Channel = MCH.....	11
5.1.2.2.	Test Mode = GSM/TM2.....	12
5.1.2.2.1.	Test Channel = MCH.....	12
6.	26dB BANDWIDTH AND OCCUPIED BANDWIDTH	13
6.1.	Test Result	13
6.2.	Test Plots.....	13
7.	BAND EDGE COMPLIANCE.....	18
7.1.	Test Plots.....	18
8.	SPURIOUS EMISSION AT ANTENNA TERMINAL	21
8.1.	Test Plots.....	21
9.	FREQUENCY STABILITY.....	42
9.1.	Frequency Error Vs Voltage	42
9.2.	Frequency Error Vs Temperature	43

1. Main Test Instruments

RE in Chamber					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date	Cal.Due date
				(yyyy-mm-dd)	(yyyy-mm-dd)
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018/3/13	2021/3/12
Spectrum Analyzer (20Hz-43GHz)	Rohde & Schwarz	FSU43	SEM004-08	2019/3/2	2020/3/1
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017/6/27	2020/6/26
Horn Antenna (800MHz-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018/4/13	2021/4/12
Horn Antenna (15-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017/10/17	2020/10/16
Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2018/9/2	2019/9/2
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2018/9/2	2019/9/2
Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	EMC2063	2018/10/20	2019/10/19
Pre-amplifier (26-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2019/3/2	2020/3/1
Band filter	N/A	N/A	N/A	N/A	N/A
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2019/6/12	2020/6/11
Wideband Radio CommunicationTeste	Anristu	MT8821C	6201462742	2019/4/3	2020/4/3
Wideband Radio CommunicationTester	Rohde & Schwarz	CMW500	W005-02	2019/1/13	2020/1/12
RF conducted test					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date	Cal.Due date
				(yyyy-mm-dd)	(yyyy-mm-dd)
Dual Output Mobile Communication DC Source	Agilent Technologies Inc	66311B	W009-09	2018/11/2	2019/11/1
Signal Analyzer	Rohde & Schwarz	FSV	W005-02	2019/3/2	2020/3/1
Coaxial Cable	SGS	N/A	SEM031-01	2019/6/12	2020/6/11
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2018/11/2	2019/11/1
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	HTC-1	W006-17	2018/11/2	2019/11/1
Temperature Chamber	GIANT FORCE	ICT-150-40-CP-AR	W027-03	2018/11/2	2019/11/1
Wideband Radio CommunicationTeste	Anristu	MT8821C	6201462742	2019/3/2	2020/3/1
Wideband Radio CommunicationTester	Rohde & Schwarz	CMW500	W005-02	2018/11/2	2019/11/1

2. Measurement Uncertainty

For a 95% confidence level ($k = 2$), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Test Item	Extended Uncertainty	Data
Transmit Output Power Data	Power [dBm]	$U = \pm 0.37 \text{ dB}$
Bandwidth	Magnitude [%]	$U = \pm 0.2\%$
Band Edge Compliance	Disturbance Power [dBm]	$U = \pm 2.0 \text{ dB}$
Spurious Emissions, Conducted	Disturbance Power [dBm]	$U = \pm 2.0 \text{ dB}$
Frequency Stability	Frequency Accuracy [ppm]	$U = \pm 0.24 \text{ ppm}$

3. Effective (Isotropic) Radiated Power Output Data

3.1. Test Result

Band	Channel	Slot	Conducted Power (dBm)	ERP (dBm)	Limit(dBm)	Verdict
GSM850	128	---	32.44	27.17	38.45	PASS
GSM850	190	---	32.48	27.21	38.45	PASS
GSM850	251	---	32.52	27.25	38.45	PASS
EGPRS850	128	1	26.93	21.66	38.45	PASS
EGPRS850	128	2	25.26	19.99	38.45	PASS
EGPRS850	128	3	23.42	18.15	38.45	PASS
EGPRS850	128	4	21.22	15.95	38.45	PASS
EGPRS850	190	1	26.66	21.39	38.45	PASS
EGPRS850	190	2	25.34	20.07	38.45	PASS
EGPRS850	190	3	23.34	18.07	38.45	PASS
EGPRS850	190	4	21.41	16.14	38.45	PASS
EGPRS850	251	1	26.62	21.35	38.45	PASS
EGPRS850	251	2	25.44	20.17	38.45	PASS
EGPRS850	251	3	23.44	18.17	38.45	PASS
EGPRS850	251	4	21.29	16.02	38.45	PASS

Band	Channel	Slot	Conducted Power (dBm)	EIRP (dBm)	Limit(dBm)	Verdict
GSM1900	512	---	29.54	28.41	33.00	PASS
GSM1900	661	---	29.63	28.5	33.00	PASS
GSM1900	810	---	29.64	28.51	33.00	PASS
EGPRS1900	512	1	25.3	24.17	33.00	PASS
EGPRS1900	512	2	23.93	22.8	33.00	PASS
EGPRS1900	512	3	22.64	21.51	33.00	PASS
EGPRS1900	512	4	20.08	18.95	33.00	PASS
EGPRS1900	661	1	25.24	24.11	33.00	PASS
EGPRS1900	661	2	24.29	23.16	33.00	PASS
EGPRS1900	661	3	22.36	21.23	33.00	PASS
EGPRS1900	661	4	20.24	19.11	33.00	PASS
EGPRS1900	810	1	25.29	24.16	33.00	PASS
EGPRS1900	810	2	23.96	22.83	33.00	PASS
EGPRS1900	810	3	22.89	21.76	33.00	PASS
EGPRS1900	810	4	20.41	19.28	33.00	PASS

Remark:

a: For getting the EIRP (Efficient Isotropic Radiated Power), the following formula should be taken to calculate it,

ERP [dBm] = Conducted Power [dBm] + Gain [dBd]


EIRP [dBm] = Conducted Power [dBm] + Gain [dBi]

4. Peak-to-Average Ratio


4.1. Test Result

Band	Channel	Peak-to-Average Ratio(dB)	Limit(dB)	Verdict
GSM850	128	7.74	13	PASS
GSM850	190	7.71	13	PASS
GSM850	251	7.68	13	PASS
EGPRS850	128	10.29	13	PASS
EGPRS850	190	10.35	13	PASS
EGPRS850	251	10.41	13	PASS
GSM1900	512	7.71	13	PASS
GSM1900	661	7.74	13	PASS
GSM1900	810	7.74	13	PASS
EGPRS1900	512	10.75	13	PASS
EGPRS1900	661	10.61	13	PASS
EGPRS1900	810	10.23	13	PASS


4.2. Part II - Test Plots




GSM850_190




GSM850_251




EGPRS850_128




EGPRS850_190




EGPRS850_251




GSM1900_512




GSM1900_661




GSM1900_810



EGPRS1900_512






5. Modulation Characteristics

5.1. For GSM

5.1.1. Test Band = GSM 850


5.1.1.1. Test Mode = GSM/TM1

5.1.1.1.1. Test Channel = MCH



5.1.1.2. Test Mode = GSM/TM2


5.1.1.2.1. Test Channel = MCH



5.1.2. Test Band = GSM 1900


5.1.2.1. Test Mode = GSM/TM1

5.1.2.1.1. Test Channel = MCH



5.1.2.2. Test Mode = GSM/TM2

5.1.2.2.1. Test Channel = MCH




6. 26dB Bandwidth and Occupied Bandwidth


6.1. Test Result

Band	Channel	Occupied Bandwidth (kHz)	26dB Bandwidth (kHz)	Limit(kHz)	Verdict
GSM850	128	244.57	301.45	---	PASS
GSM850	190	247.47	298.55	---	PASS
GSM850	251	246.02	315.94	---	PASS
EGPRS850	128	250.36	301.45	---	PASS
EGPRS850	190	253.26	295.65	---	PASS
EGPRS850	251	253.26	307.25	---	PASS
GSM1900	512	244.57	286.96	---	PASS
GSM1900	661	244.57	300.00	---	PASS
GSM1900	810	244.57	314.49	---	PASS
EGPRS1900	512	250.36	307.25	---	PASS
EGPRS1900	661	243.13	304.35	---	PASS
EGPRS1900	810	248.91	314.49	---	PASS

6.2. Test Plots




GSM850_190




Date: 12 AUG 2019 22:48:23

GSM850_251




Date: 12 AUG 2019 22:48:49

EGPRS850_128




Date: 12 AUG 2019 22:56:30


EGPRS850_190




EGPRS850_251



GSM1900_512




GSM1900_661




Date: 12 AUG 2019 22:29:44

GSM1900_810




Date: 12 AUG 2019 22:30:15

EGPRS1900_512




Date: 12 AUG 2019 22:38:53

EGPRS1900_661




EGPRS1900_810




7. Band Edge Compliance


7.1. Test Plots




EGPRS850_128




EGPRS850_251



GSM1900_512




GSM1900_810




Date: 12 AUG 2019 22:31:29

EGPRS1900_512



Date: 12 AUG 2019 22:40:37

EGPRS1900_810




Date: 12 AUG 2019 22:41:11

8. Spurious Emission at Antenna Terminal


Remark1: For the averaged unwanted emissions measurements, the measurement points in each sweep is greater than twice the Span/RBW in order to ensure bin-to-bin spacing of $< RBW/2$ so that narrowband signals are not lost between frequency bins. As to the present test item, the "Measurement Points = $k * (\text{Span} / RBW)$ " with k between 4 and 5, which results in an acceptable level error of less than 0.5 dB.

Remark2: only the worst case data displayed in this report.


8.1. Test Plots




GSM850_128




GSM850_128




GSM850_190




GSM850_190




GSM850_190




GSM850_190




GSM850_251




GSM850_251




GSM850_251




GSM850_251




EGPRS850_128




EGPRS850_128




EGPRS850_128




EGPRS850_128




EGPRS850_190




EGPRS850_190




EGPRS850_190




EGPRS850_190




EGPRS850_251




EGPRS850_251




EGPRS850_251




EGPRS850_251




GSM1900_512




GSM1900_512




GSM1900_512




GSM1900_512




GSM1900_512




GSM1900_512




GSM1900_661




GSM1900_661




GSM1900_661




GSM1900_661




GSM1900_661




GSM1900_661




GSM1900_810




GSM1900_810




GSM1900_810




GSM1900_810




GSM1900_810




GSM1900_810




EGPRS1900_512




EGPRS1900_512




EGPRS1900_512




EGPRS1900_512



EGPRS1900_512




EGPRS1900_512




Date: 12 AUG 2019 22:42:39

EGPRS1900_661




Date: 12 AUG 2019 22:42:57

EGPRS1900_661




Date: 12 AUG 2019 22:43:09


EGPRS1900_661




EGPRS1900_661




EGPRS1900_661




EGPRS1900_661




EGPRS1900_810




EGPRS1900_810




EGPRS1900_810




EGPRS1900_810



EGPRS1900_810





9. Frequency Stability

9.1. Frequency Error Vs Voltage

Voltage							
Band	Channel	Voltage (Vdc)	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
GSM850	128	VL	TN	1.87	0.002272	±2.5	PASS
GSM850	128	VN	TN	-0.29	-0.000353	±2.5	PASS
GSM850	128	VH	TN	2.42	0.002938	±2.5	PASS
GSM850	190	VL	TN	3.13	0.003743	±2.5	PASS
GSM850	190	VN	TN	4.36	0.005210	±2.5	PASS
GSM850	190	VH	TN	4.71	0.005634	±2.5	PASS
GSM850	251	VL	TN	2.23	0.002625	±2.5	PASS
GSM850	251	VN	TN	0.71	0.000837	±2.5	PASS
GSM850	251	VH	TN	3.94	0.004641	±2.5	PASS
EGPRS850	128	VL	TN	-5.62	-0.006816	±2.5	PASS
EGPRS850	128	VN	TN	-1.19	-0.001449	±2.5	PASS
EGPRS850	128	VH	TN	3.55	0.004309	±2.5	PASS
EGPRS850	190	VL	TN	-2.52	-0.003010	±2.5	PASS
EGPRS850	190	VN	TN	-5.13	-0.006136	±2.5	PASS
EGPRS850	190	VH	TN	4.26	0.005094	±2.5	PASS
EGPRS850	251	VL	TN	-7.01	-0.008254	±2.5	PASS
EGPRS850	251	VN	TN	1.10	0.001293	±2.5	PASS
EGPRS850	251	VH	TN	1.23	0.001445	±2.5	PASS
GSM1900	512	VL	TN	4.33	0.002338	±2.5	PASS
GSM1900	512	VN	TN	10.88	0.005881	±2.5	PASS
GSM1900	512	VH	TN	11.59	0.006265	±2.5	PASS
GSM1900	661	VL	TN	8.01	0.004259	±2.5	PASS
GSM1900	661	VN	TN	8.88	0.004723	±2.5	PASS
GSM1900	661	VH	TN	7.01	0.003727	±2.5	PASS
GSM1900	810	VL	TN	9.49	0.004970	±2.5	PASS
GSM1900	810	VN	TN	9.07	0.004750	±2.5	PASS
GSM1900	810	VH	TN	9.01	0.004717	±2.5	PASS
EGPRS1900	512	VL	TN	-0.65	-0.000349	±2.5	PASS
EGPRS1900	512	VN	TN	-0.13	-0.000070	±2.5	PASS
EGPRS1900	512	VH	TN	4.26	0.002303	±2.5	PASS
EGPRS1900	661	VL	TN	3.94	0.002095	±2.5	PASS
EGPRS1900	661	VN	TN	0.39	0.000206	±2.5	PASS
EGPRS1900	661	VH	TN	1.03	0.000550	±2.5	PASS
EGPRS1900	810	VL	TN	2.91	0.001521	±2.5	PASS
EGPRS1900	810	VN	TN	4.78	0.002502	±2.5	PASS
EGPRS1900	810	VH	TN	-4.94	-0.002587	±2.5	PASS

JianYan Testing Group Shenzhen Co., Ltd.

Report No: JYTSZ-R12-2200349

9.2.Frequency Error Vs Temperature

Temperature							
Band	Channel	Voltage (Vdc)	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
GSM850	128	VN	-30	0.97	0.001175	± 2.5	PASS
GSM850	128	VN	-20	-1.16	-0.001410	± 2.5	PASS
GSM850	128	VN	-10	4.81	0.005837	± 2.5	PASS
GSM850	128	VN	0	2.45	0.002977	± 2.5	PASS
GSM850	128	VN	10	3.84	0.004662	± 2.5	PASS
GSM850	128	VN	20	5.07	0.006150	± 2.5	PASS
GSM850	128	VN	30	4.36	0.005288	± 2.5	PASS
GSM850	128	VN	40	4.58	0.005562	± 2.5	PASS
GSM850	128	VN	50	2.52	0.003055	± 2.5	PASS
GSM850	190	VN	-30	7.26	0.008683	± 2.5	PASS
GSM850	190	VN	-20	5.26	0.006290	± 2.5	PASS
GSM850	190	VN	-10	2.91	0.003473	± 2.5	PASS
GSM850	190	VN	0	3.84	0.004592	± 2.5	PASS
GSM850	190	VN	10	1.00	0.001196	± 2.5	PASS
GSM850	190	VN	20	4.23	0.005056	± 2.5	PASS
GSM850	190	VN	30	0.32	0.000386	± 2.5	PASS
GSM850	190	VN	40	-1.90	-0.002277	± 2.5	PASS
GSM850	190	VN	50	-0.06	-0.000077	± 2.5	PASS
GSM850	251	VN	-30	-0.45	-0.000533	± 2.5	PASS
GSM850	251	VN	-20	8.10	0.009547	± 2.5	PASS
GSM850	251	VN	-10	5.71	0.006733	± 2.5	PASS
GSM850	251	VN	0	4.26	0.005021	± 2.5	PASS
GSM850	251	VN	10	0.84	0.000989	± 2.5	PASS
GSM850	251	VN	20	2.00	0.002358	± 2.5	PASS
GSM850	251	VN	30	2.10	0.002472	± 2.5	PASS
GSM850	251	VN	40	5.13	0.006048	± 2.5	PASS
GSM850	251	VN	50	1.84	0.002168	± 2.5	PASS
EGPRS850	128	VN	-30	2.94	0.003565	± 2.5	PASS
EGPRS850	128	VN	-20	3.81	0.004622	± 2.5	PASS
EGPRS850	128	VN	-10	-3.91	-0.004740	± 2.5	PASS
EGPRS850	128	VN	0	2.55	0.003095	± 2.5	PASS
EGPRS850	128	VN	10	1.58	0.001919	± 2.5	PASS
EGPRS850	128	VN	20	3.52	0.004270	± 2.5	PASS
EGPRS850	128	VN	30	5.33	0.006463	± 2.5	PASS
EGPRS850	128	VN	40	-0.52	-0.000627	± 2.5	PASS
EGPRS850	128	VN	50	6.75	0.008187	± 2.5	PASS
EGPRS850	190	VN	-30	2.13	0.002547	± 2.5	PASS
EGPRS850	190	VN	-20	1.42	0.001698	± 2.5	PASS
EGPRS850	190	VN	-10	1.10	0.001312	± 2.5	PASS
EGPRS850	190	VN	0	2.16	0.002586	± 2.5	PASS
EGPRS850	190	VN	10	1.94	0.002316	± 2.5	PASS
EGPRS850	190	VN	20	4.16	0.004978	± 2.5	PASS
EGPRS850	190	VN	30	3.84	0.004592	± 2.5	PASS
EGPRS850	190	VN	40	3.65	0.004361	± 2.5	PASS
EGPRS850	190	VN	50	5.55	0.006638	± 2.5	PASS
EGPRS850	251	VN	-30	-2.74	-0.003233	± 2.5	PASS
EGPRS850	251	VN	-20	1.84	0.002168	± 2.5	PASS
EGPRS850	251	VN	-10	-4.97	-0.005858	± 2.5	PASS

JianYan Testing Group Shenzhen Co., Ltd.

Report No: JYTSZ-R12-2200349

EGPRS850	251	VN	0	-2.78	-0.003271	±2.5	PASS
EGPRS850	251	VN	10	1.10	0.001293	±2.5	PASS
EGPRS850	251	VN	20	4.75	0.005591	±2.5	PASS
EGPRS850	251	VN	30	-1.13	-0.001331	±2.5	PASS
EGPRS850	251	VN	40	-0.97	-0.001141	±2.5	PASS
EGPRS850	251	VN	50	3.68	0.004336	±2.5	PASS
GSM1900	512	VN	-30	14.50	0.007835	±2.5	PASS
GSM1900	512	VN	-20	10.91	0.005898	±2.5	PASS
GSM1900	512	VN	-10	11.24	0.006073	±2.5	PASS
GSM1900	512	VN	0	8.07	0.004362	±2.5	PASS
GSM1900	512	VN	10	5.49	0.002966	±2.5	PASS
GSM1900	512	VN	20	8.78	0.004746	±2.5	PASS
GSM1900	512	VN	30	5.78	0.003124	±2.5	PASS
GSM1900	512	VN	40	-1.49	-0.000803	±2.5	PASS
GSM1900	512	VN	50	6.88	0.003717	±2.5	PASS
GSM1900	661	VN	-30	9.36	0.004980	±2.5	PASS
GSM1900	661	VN	-20	11.30	0.006011	±2.5	PASS
GSM1900	661	VN	-10	12.33	0.006560	±2.5	PASS
GSM1900	661	VN	0	4.91	0.002610	±2.5	PASS
GSM1900	661	VN	10	1.39	0.000738	±2.5	PASS
GSM1900	661	VN	20	4.78	0.002542	±2.5	PASS
GSM1900	661	VN	30	1.49	0.000790	±2.5	PASS
GSM1900	661	VN	40	3.55	0.001889	±2.5	PASS
GSM1900	661	VN	50	1.52	0.000807	±2.5	PASS
GSM1900	810	VN	-30	7.36	0.003854	±2.5	PASS
GSM1900	810	VN	-20	8.43	0.004412	±2.5	PASS
GSM1900	810	VN	-10	6.13	0.003212	±2.5	PASS
GSM1900	810	VN	0	6.81	0.003567	±2.5	PASS
GSM1900	810	VN	10	0.71	0.000372	±2.5	PASS
GSM1900	810	VN	20	8.17	0.004277	±2.5	PASS
GSM1900	810	VN	30	9.33	0.004886	±2.5	PASS
GSM1900	810	VN	40	3.58	0.001876	±2.5	PASS
GSM1900	810	VN	50	-4.16	-0.002181	±2.5	PASS
EGPRS1900	512	VN	-30	0.42	0.000227	±2.5	PASS
EGPRS1900	512	VN	-20	-1.10	-0.000593	±2.5	PASS
EGPRS1900	512	VN	-10	1.84	0.000995	±2.5	PASS
EGPRS1900	512	VN	0	5.33	0.002879	±2.5	PASS
EGPRS1900	512	VN	10	-1.55	-0.000838	±2.5	PASS
EGPRS1900	512	VN	20	-0.71	-0.000384	±2.5	PASS
EGPRS1900	512	VN	30	-0.68	-0.000366	±2.5	PASS
EGPRS1900	512	VN	40	0.45	0.000244	±2.5	PASS
EGPRS1900	512	VN	50	1.84	0.000995	±2.5	PASS
EGPRS1900	661	VN	-30	0.26	0.000137	±2.5	PASS
EGPRS1900	661	VN	-20	-0.06	-0.000034	±2.5	PASS
EGPRS1900	661	VN	-10	-3.23	-0.001717	±2.5	PASS
EGPRS1900	661	VN	0	-2.10	-0.001116	±2.5	PASS
EGPRS1900	661	VN	10	1.97	0.001048	±2.5	PASS
EGPRS1900	661	VN	20	2.55	0.001357	±2.5	PASS
EGPRS1900	661	VN	30	4.13	0.002198	±2.5	PASS
EGPRS1900	661	VN	40	6.59	0.003503	±2.5	PASS
EGPRS1900	661	VN	50	-5.13	-0.002731	±2.5	PASS
EGPRS1900	810	VN	-30	-3.75	-0.001961	±2.5	PASS
EGPRS1900	810	VN	-20	-1.81	-0.000947	±2.5	PASS

JianYan Testing Group Shenzhen Co., Ltd.

Report No: JYTSZ-R12-2200349

EGPRS1900	810	VN	-10	-2.42	-0.001268	± 2.5	PASS
EGPRS1900	810	VN	0	-2.84	-0.001488	± 2.5	PASS
EGPRS1900	810	VN	10	-3.97	-0.002079	± 2.5	PASS
EGPRS1900	810	VN	20	-0.13	-0.000068	± 2.5	PASS
EGPRS1900	810	VN	30	-2.49	-0.001302	± 2.5	PASS
EGPRS1900	810	VN	40	-2.42	-0.001268	± 2.5	PASS
EGPRS1900	810	VN	50	-2.07	-0.001082	± 2.5	PASS

The End