



TEST REPORT

No.I20N02478-HAC T-coil

For

TCL Communication Ltd.

GSM/UMTS/LTE Mobile phone

Model Name: 5007S

With

Hardware Version: 03

Software Version: v2D23UZ31

FCC ID: 2ACCJH130

Results Summary: T Category = T4

Issued Date: 2020-10-20

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SAICT.

Test Laboratory:

SAICT, Shenzhen Academy of Information and Communications Technology

Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518026.

Tel:+86(0)755-33322000, Fax:+86(0)755-33322001

Email: yewu@caict.ac.cn www.saict.ac.cn



CAICT

I20N02478-HAC T-coil

REPORT HISTORY

| Report Number | Revision | Description | Issue Date |
|----------------------|-----------------|--------------------|-------------------|
| I20N02478-HAC T-coil | Rev.0 | 1st edition | 2020-10-20 |

CONTENTS

| | |
|-------------------------------------------------------------------------|-----------|
| 1. SUMMARY OF TEST REPORT..... | 5 |
| 1.1. TEST ITEMS | 5 |
| 1.2. TEST STANDARDS | 5 |
| 1.3. TEST RESULT | 5 |
| 1.4. TESTING LOCATION | 5 |
| 1.5. PROJECT DATA | 5 |
| 1.6. SIGNATURE | 5 |
| 2. CLIENT INFORMATION | 6 |
| 2.1. APPLICANT INFORMATION..... | 6 |
| 2.2. MANUFACTURER INFORMATION | 6 |
| 3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) | 7 |
| 3.1. ABOUT EUT..... | 7 |
| 3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST | 7 |
| 3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST..... | 7 |
| 3.4 AIR INTERFACES / BANDS INDICATING OPERATING MODES..... | 7 |
| 4. REFERENCE DOCUMENTS..... | 8 |
| 5. OPERATIONAL CONDITIONS DURING TEST | 9 |
| 5.1. HAC MEASUREMENT SET-UP | 9 |
| 5.2. AM1D PROBE | 11 |
| 5.3. AMCC..... | 11 |
| 5.4. AMMI | 11 |
| 5.5. TEST ARCH PHANTOM & PHONE POSITIONER | 12 |
| 5.6. ROBOTIC SYSTEM SPECIFICATIONS..... | 13 |
| 5.7. T-COIL MEASUREMENT POINTS AND REFERENCE PLANE | 13 |
| 6. T-COIL TEST PROCEDURES..... | 15 |
| 7. T-COIL PERFORMANCE REQUIREMENTS | 16 |
| 7.1. T-COIL COUPLING FIELD INTENSITY..... | 16 |
| 7.2. FREQUENCY RESPONSE..... | 16 |
| 7.3. SIGNAL QUALITY | 17 |
| 8. CMRS VOICE DUT CONFIGURATION..... | 18 |
| 8.1. GSM CODEC INVESTIGATION..... | 18 |
| 8.2. UMTS CODEC INVESTIGATION..... | 18 |
| 9. VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION..... | 19 |
| 9.1. TEST SYSTEM SETUP FOR VOLTE OVER IMS T-COIL TESTING..... | 19 |
| 9.2. CODEC CONFIGURATION..... | 20 |
| 9.3. RADIO CONFIGURATION..... | 20 |
| 10. OTT VOIP TEST SYSTEM SETUP AND DUT CONFIGURATION..... | 21 |
| 10.1. TEST SYSTEM SETUP FOR OTT VOIP T-COIL TESTING | 21 |
| 10.2. CODEC CONFIGURATION..... | 25 |
| 10.3. RADIO CONFIGURATION FOR OTT VOIP (LTE)..... | 26 |
| 11. HAC T-COIL TEST DATA SUMMARY..... | 27 |
| 11.1. TEST RESULTS FOR 2/3G | 27 |
| 11.2. TEST RESULTS FOR LTE | 27 |
| 11.3. TEST RESULTS FOR OTT VOIP | 28 |
| 11.4. TOTAL MEASUREMENT CONCLUSION | 29 |
| 12. MEASUREMENT UNCERTAINTY | 30 |

| | |
|---------------------------------------------|----|
| 13. MAIN TEST INSTRUMENTS..... | 31 |
| ANNEX A: TEST LAYOUT | 32 |
| ANNEX B: TEST PLOTS..... | 33 |
| ANNEX C: FREQUENCY RESPONSE CURVES..... | 49 |
| ANNEX D: PROBE CALIBRATION CERTIFICATE..... | 51 |
| ANNEX E: DAE CALIBRATION CERTIFICATE | 54 |
| ANNEX F: ACCREDITATION CERTIFICATE | 57 |



1. Summary of Test Report

1.1. Test Items

Description: GSM/UMTS/LTE Mobile phone
Model Name: 5007S
Applicant's name: TCL Communication Ltd.
Manufacturer's Name: TCL Communication Ltd.

1.2. Test Standards

ANSI C63.19-2011

1.3. Test Result

Pass

1.4. Testing Location

Address: Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518026

1.5. Project Data

Testing Start Date: 2020-09-18

Testing End Date: 2020-09-22

1.6. Signature

Li Yongfu

(Prepared this test report)

Zhang Yunzhan

(Reviewed this test report)

Cao Junfei

(Approved this test report)

2. Client Information

2.1. Applicant Information

| | |
|---------------|-----------------------------------------------------------------------------------------------|
| Company Name: | TCL Communication Ltd. |
| Address: | 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong |
| City: | Hong Kong |
| Country: | China |
| Telephone: | 0086-755-36611722 |

2.2. Manufacturer Information

| | |
|---------------|-----------------------------------------------------------------------------------------------|
| Company Name: | TCL Communication Ltd. |
| Address: | 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong |
| City: | Hong Kong |
| Country: | China |
| Telephone: | 0086-755-36611722 |

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

| | |
|-------------------------------|---------------------------------------------------------------------------|
| Description: | GSM/UMTS/LTE Mobile phone |
| Mode Name: | 5007S |
| Condition of EUT as received: | No obvious damage in appearance |
| Operating mode(s) : | GSM 850/900/1800/1900, UMTS FDD 2/4/5, BT, Wi-Fi, LTE Band 2/4/5/12/13/66 |

3.2. Internal Identification of EUT used during the test

| EUT ID* | IMEI | HW Version | SW Version |
|---------|-----------------|------------|------------|
| EUT1 | 015794000205402 | 03 | v2D23UZ31 |

*EUT ID: is used to identify the test sample in the lab internally.

Note: It is performed to test HAC with the EUT1.

3.3. Internal Identification of AE used during the test

| AE ID* | Description | Model | Manufacturer |
|--------|-------------|----------|--------------|
| AE1 | Battery | TLp034G1 | BYD |

*AE ID: is used to identify the test sample in the lab internally.

3.4 Air Interfaces / Bands Indicating Operating Modes

| Air-interface | Band(MHz) | Type | C63.19/tested | Simultaneous Transmissions | Name of Voice Service |
|-----------------|----------------------|------|---------------|----------------------------|-----------------------|
| GSM | 850 | VO | Yes | BT, WLAN | CMRS Voice |
| | 1900 | | | | Google duo |
| GPRS/ EDGE | 850 | DT | Yes | BT, WLAN | CMRS Voice |
| | 1900 | | | | Google duo |
| WCDMA (UMTS) | 850 | VO | Yes | BT, WLAN | CMRS Voice |
| | 1700 | | | | Google duo |
| | 1900 | | | | |
| | HSPA | DT | Yes | | |
| LTE FDD | Band2/5/12/13/6 6 | V/D | Yes | BT, WLAN | VoLTE, Google duo |
| BT | 2450 | DT | NA | GSM, WCDMA, LTE | NA |
| WLAN | 2450 | V/D | Yes | GSM, WCDMA, LTE | NA |

NA: Not Applicable VO: Voice Only V/D: CMRS and IP Voice Service over Digital Transport

DT: Digital Transport

* HAC Rating was not based on concurrent voice and data modes, Non current mode was found to represent worst case rating for both M and T rating

Note1 = No Associated T-Coil measurement has been made in accordance with 285076 D02 T-Coil testing for CMRS IP

4. Reference Documents

The following document listed in this section is referred for testing.

| Reference | Title | Version |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| ANSI C63.19-2011 | American National Standard for Methods of Measurement of Compatibility between Wireless Communication Devices and Hearing Aids | 2011 Edition |
| KDB285076 D01v05r01 | Equipment Authorization Guidance for Hearing Aid Compatibility | 2020 Edition |
| KDB285076 D02v03 | Guidance for performing T-Coil tests for air interfaces supporting voice over IP (e.g., LTE and WiFi) to support CMRS based telephone services | 2017 Edition |

5. Operational Conditions during Test

5.1. HAC Measurement Set-up

These measurements are performed using the DASY5 NEO automated dosimetric assessment system. It is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland. It consists of high precision robotics system (Stäubli), robot controller, Intel Core2 computer, near-field probe, probe alignment sensor. The robot is a six-axis industrial robot performing precise movements. A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The PC consists of the HP Intel Core2 1.86 GHz computer with Windows XP system and HAC Measurement Software DASY5 NEO, A/D interface card, monitor, mouse, and keyboard. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification; signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.




Figure 5.1 HAC Test Measurement Set-up

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.




Figure 5.2 T-Coil setup with HAC Test Arch and AMCC

5.2. AM1D probe

The AM1D probe is an active probe with a single sensor. It is fully RF-shielded and has a rounded tip 6mm in diameter incorporating a pickup coil with its center offset 3mm from the tip and the sides. The symmetric signal preamplifier in the probe is fed via the shielded symmetric output cable from the AMMI with a 48V "phantom" voltage supply. The 7-pin connector on the back in the axis of the probe does not carry any signals. It is mounted to the DAE for the correct orientation of the sensor. If the probe axis is tilted 54.7 degree from the vertical, the sensor is approximately vertical when the signal connector is at the underside of the probe (cable hanging downwards).

Specification:

| | |
|------------------------|---------------------------------------------------------------|
| Frequency range | 0.1~20kHz (RF sensitivity < -100dB, fully RF shielded) |
| Sensitivity | < -50dB A/m @ 1kHz |
| Pre-amplifier | 40dB, symmetric |
| Dimensions | Tip diameter/length: 6/290mm, sensor according to ANSI-C63.19 |

5.3. AMCC

The Audio Magnetic Calibration coil is a Helmholtz Coil designed for calibration of the AM1D probe. The two horizontal coils generate a homogeneous magnetic field in the z direction. The DC input resistance is adjusted by a series resistor to approximately 50Ohm, and a shunt resistor of 10Ohm permits monitoring the current with a scale of 1:10

Port description:

| Signal | Connector | Resistance |
|---------------|------------------|-----------------------------------------|
| Coil In | BNC | Typically 50Ohm |
| Coil Monitor | BNO | 10Ohm±1% (100mV corresponding to 1 A/m) |

Specification:

| | |
|-------------------|----------------------------------------------|
| Dimensions | 370 x 370 x 196 mm, according to ANSI-C63.19 |
|-------------------|----------------------------------------------|

5.4. AMMI



Figure 5.3 AMMI front panel

The Audio Magnetic Measuring Instrument (AMMI) is a desktop 19-inch unit containing a sampling unit, a waveform generator for test and calibration signals, and a USB interface.

Specification:

| | |
|-------------------------------|---------------------------------------------------------------------------|
| Sampling rate | 48 kHz / 24 bit |
| Dynamic range | 85 dB |
| Test signal generation | User selectable and predefined (vis PC) |
| Calibration | Auto-calibration / full system calibration using AMCC with monitor output |
| Dimensions | 482 x 65 x 270 mm |

5.5. Test Arch Phantom & Phone Positioner

The Test Arch phantom should be positioned horizontally on a stable surface. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. It enables easy and well defined positioning of the phone and validation dipoles as well as simple teaching of the robot (Dimensions: 370 x 370 x 370 mm).

The Phone Positioner supports accurate and reliable positioning of any phone with effect on near field $<\pm 0.5$ dB.




Figure 5.4 HAC Phantom & Device Holder

5.6. Robotic System Specifications

Specifications

Positioner: Stäubli Unimation Corp. Robot Model: RX160L

Repeatability: ± 0.02 mm

No. of Axis: 6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor: Intel Core2

Clock Speed: 1.86 GHz

Operating System: Windows XP

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter, and control logic

Software: DASY5 software

Connecting Lines: Optical downlink for data and status info.

Optical uplink for commands and clock

5.7. T-Coil measurement points and reference plane

Figure 6.5 illustrates the standard probe orientations. Position 1 is the perpendicular orientation of the probe coil; orientation 2 is the transverse orientations. The space between the measurement positions is not fixed. It is recommended that a scan of the WD be done for each probe coil orientation and that the maximum level recorded be used as the reading for that orientation of the probe coil.

- 1) The reference plane is the planar area that contains the highest point in the area of the phone that normally rests against the user's ear. It is parallel to the centerline of the receiver area of the phone and is defined by the points of the receiver-end of the WD handset, which, in normal handset use, rest against the ear.
- 2) The measurement plane is parallel to, and 10 mm in front of, the reference plane.
- 3) The reference axis is normal to the reference plane and passes through the center of the receiver speaker section (or the center of the hole array); or may be centered on a secondary inductive source. The actual location of the measurement point shall be noted in the test report as the measurement reference point.
- 4) The measurement points may be located where the axial and radial field intensity measurements are optimum with regard to the requirements. However, the measurement points should be near the acoustic output of the WD and shall be located in the same half of the phone as the WD receiver. In a WD handset with a centered receiver and a circularly symmetrical magnetic field, the measurement axis and the reference axis would coincide.
- 5) The relative spacing of each measurement orientation is not fixed. The axial and two radial orientations should be chosen to select the optimal position.
- 6) The measurement point for the axial position is located 10 mm from the reference plane on the measurement axis. The actual location of the measurement point shall be noted in test reports and designated as the measurement reference point.




Figure 5.5 Axis and planes for WD audio frequency magnetic field measurements

6. T-Coil Test Procedures

The following illustrate a typical test scan over a wireless communications device:

- 1) Geometry and signal check: system probe alignment, proper operation of the field probe, probe measurement system, other instrumentation, and the positioning system was confirmed. A surface calibration was performed before each setup change to ensure repeatable spacing and proper maintenance of the measurement plane using the test Arch.
- 2) Set the reference drive level of signal voice defined in C63.19 per 7.4.2.1.
- 3) The ambient and test system background noise (dB A/m) was measured as well as ABM2 over the full measurement. The maximum noise level must be at least 10dB below the limit.
- 4) The DUT was positioned in its intended test position, acoustic output point of the device perpendicular to the field probe.
- 5) The DUT operation for maximum rated RF output power was configured and connected by using of coaxial cable connection to the base station simulator at the test channel and other normal operating parameters as intended for the test. The battery was ensured to be fully charged before each test. The center sub-grid was centered over the center of the acoustic output (also audio band magnetic output, if applicable). The DUT audio output was positioned tangent (as physically possible) to the measurement plane.
- 6) The DUT's RF emission field was eliminated from T-coil results by using a well RF-shielding of the probe, AM1D, and by using of coaxial cable connection to a Base Station Simulator. One test channel was pre-measurement to avoid this possibility.
- 7) Determined the optimal measurement locations for the DUT by following the three steps, coarse resolution scan, fine resolution scans, and point measurement, as described in C63.19 per 7.4.4.2. At each measurement locations, samples in the measurement window duration were evaluated to get ABM1 and the signal spectrum. The noise measurement was performed after the scan with the signal, the same happened, just with the voice signal switched off. The ABM2 was calculated from this second scan.
- 8) All results resulting from a measurement point in a T-Coil job were calculated from the signal samples during this window interval. ABM values were averaged over the sequence of these samples.
- 9) At an optimal point measurement, the SNR (ABM1/ABM2) was calculated for perpendicular and transverse orientation, and the frequency response was measured for perpendicular.
- 10) Corrected for the frequency response after the DUT measurement since the DASY5 system had known the spectrum of the input signal by using a reference job.
- 11) In SEMCAD postprocessing, the spectral points are in addition scaled with the high-pass (half-band) and the A-weighting, bandwidth compensated factor (BWC) and those results are final as shown in this report.

7. T-Coil Performance Requirements


In order to be rated for T-Coil use, a WD shall meet the requirements for signal level and signal quality contained in this part.

7.1. T-Coil coupling field intensity

When measured as specified in ANSI C63.19, the T-Coil signal shall be ≥ -18 dB (A/m) at 1 kHz, in a 1/3 octave band filter for all orientations.


7.2. Frequency response

The frequency response of the axial component of the magnetic field, measured in 1/3 octave bands, shall follow the response curve specified in this sub-clause, over the frequency range 300 Hz to 3000 Hz. Figure 7.1 and Figure 7.2 provide the boundaries for the specified frequency. These response curves are for true field strength measurements of the T-Coil signal. Thus the 6 dB/octave probe response has been corrected from the raw readings.



NOTE—Frequency response is between 300 Hz and 3000 Hz.

Figure 7.1—Magnetic field frequency response for WDs with a field ≤ -15 dB (A/m) at 1 kHz



NOTE—Frequency response is between 300 Hz and 3000 Hz.

Figure 7.2—Magnetic field frequency response for WDs with a field that exceeds -15 dB (A/m) at 1 kHz

7.3. Signal quality

This part provides the signal quality requirement for the intended T-Coil signal from a WD. Only the RF immunity of the hearing aid is measured in T-Coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. So, the only criteria that can be measured is the RF immunity in T-Coil mode. This is measured using the same procedure as for the audio coupling mode and at the same levels.

The worst signal quality of the three T-Coil signal measurements shall be used to determine the T-Coil mode category per Table 1

Table 1: T-Coil signal quality categories

| Category | Telephone parameters |
|-----------------|--------------------------------------------------------------------------------------|
| | WD signal quality [(signal + noise) – to – noise ratio in decibels] |
| Category T1 | 0 dB to 10 dB |
| Category T2 | 10 dB to 20 dB |
| Category T3 | 20 dB to 30 dB |
| Category T4 | > 30 dB |

8. CMRS Voice DUT Configuration

8.1. GSM Codec Investigation

The middle channel of each frequency band is used for T-coil testing according ANSI C63.19-2011. Choose worst case from radio configuration investigation. After investigation was performed to determine the audio codec configuration to be used for testing, the following tests results which the worst case codec would be remarked to be used for the testing for the DUT. According to C63 and KDB 285076 D02v03, GSM input level is -16dBm0.

Table 8-1 GSM CMRS Codec Investigation

| Codec Setting | FR VR | HR V1 | EFR | Orientation | Band | Channel |
|--------------------|-------|-------|-------|-------------|---------|---------|
| ABM1 (dBA/m) | 10.88 | 9.72 | 10.16 | Z(axial) | GSM1900 | 661 |
| Frequency Response | PASS | PASS | PASS | | | |
| SNR (dB) | 39.80 | 40.27 | 40.82 | | | |

8.2. UMTS Codec Investigation

The middle channel of each frequency band is used for T-coil testing according ANSI C63.19-2011. Choose worst case from radio configuration investigation. After investigation was performed to determine the audio codec configuration to be used for testing, the following tests results which the worst case codec would be remarked to be used for the testing for the DUT. According to C63 and KDB 285076 D02v03, UMTS input level is -16dBm0.

Table 8-2 WCDMA/UMTS CMRS Codec Investigation

| Codec Setting | AMR 12.2kbps | AMR 7.95kbps | AMR 4.75kbps | Orientation | Band | Channel |
|--------------------|--------------|--------------|--------------|-------------|------------|---------|
| ABM1 (dBA/m) | -1.30 | -1.25 | -1.37 | Z(axial) | WCDMA 1900 | 9400 |
| Frequency Response | PASS | PASS | PASS | | | |
| SNR (dB) | 40.77 | 40.98 | 41.46 | | | |

9. VoLTE Test System Setup and DUT Configuration

9.1. Test System Setup for VoLTE over IMS T-coil Testing

The general test setup used for VoLTE over IMS is shown below. The callbox used when performing VoLTE over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server. According to C63 and KDB 285076 D02v03, VoLTE input level is -20dBm0.




Figure 9.1 Test Setup for VoLTE over IMS T-coil Measurements

No correction gain factors were measured for VoLTE due to the Rohde & Schwarz CMW500, hosting a calibrated audio board. The gains used to measure VoLTE are set to 100. The following software/firmware was used to simulate the VoLTE server for testing:

| Firmware | License Keys | Software Name |
|-------------------|--------------|-----------------------|
| V3.7.50 for LTE | KS500 | LTE FDD R8 SIG BASIC |
| | KS550 | LTE TDD R8 SIG BASIC |
| | KA100 | IP APPL ENABLING IPv4 |
| | KA150 | IP APPL ENABLING IPv6 |
| V3.7.20 for Audio | KAA20 | IP APPL IMS BASIC |
| | KM050 | DATA APPL MEAS |
| | KS104 | EVS SPEECH CODEC |

9.2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. NB AMR 4.75kbps setting was used for the audio codec on the CMW500 for VoLTE over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

Table 9-1 AMR Codec Investigation – VoLTE over IMS

| Codec Setting | WB AMR 23.85kbps | WB AMR 6.60kbps | NB AMR 12.2kbps | NB AMR 4.75kbps | Orientation | Band/BW | Channel |
|--------------------|---------------------|--------------------|--------------------|--------------------|-------------|---------|---------|
| ABM1 (dBA/m) | 12.87 | 10.76 | 11.82 | 12.94 | Z(axial) | B2/20M | 18900 |
| Frequency Response | PASS | PASS | PASS | PASS | | | |
| SNR (dB) | 52.21 | 50.67 | 42.67 | 39.80 | | | |

Table 9-2 EVS Codec Investigation – VoLTE over IMS

| Codec Setting | EVS Primary WB 13.2kbps | EVS Primary WB 5.9kbps | EVS Primary NB 13.2kbps | EVS Primary NB 5.9kbps | Orientation | Band /BW | Channel |
|--------------------|-------------------------------|---------------------------|----------------------------|---------------------------|-------------|----------|---------|
| ABM1 (dBA/m) | 11.26 | 9.84 | 10.72 | 11.28 | Z(axial) | B2/20M | 18900 |
| Frequency Response | PASS | PASS | PASS | PASS | | | |
| SNR (dB) | 41.24 | 40.93 | 41.28 | 42.53 | | | |

9.3. Radio Configuration

An investigation was performed to determine the modulation, the bandwidth configuration and RB configuration to be used for testing. 3MHz BW, QPSK, 1RB, 50%RB offset was used for the testing as the worst-case configuration for the handset. See below table for comparisons between different radio configurations:

Table 9-3 VoLTE over IMS SNR by Radio Configuration

| Band | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset(%) | ABM1 [dB(A/m)] | SNR [dB] |
|--------|---------|-----------------|------------|---------|--------------|----------------|----------|
| LTE B2 | 18900 | 20 | QPSK | 1 | 0 | 11.53 | 40.93 |
| LTE B2 | 18900 | 20 | QPSK | 1 | 50 | 12.94 | 39.80 |
| LTE B2 | 18900 | 20 | QPSK | 1 | 100 | 11.59 | 41.69 |
| LTE B2 | 18900 | 20 | QPSK | 50 | 0 | 10.28 | 42.87 |
| LTE B2 | 18900 | 20 | QPSK | 50 | 50 | 10.11 | 41.37 |
| LTE B2 | 18900 | 20 | QPSK | 50 | 100 | 11.66 | 41.66 |
| LTE B2 | 18900 | 20 | QPSK | 100 | 0 | 10.29 | 41.52 |
| LTE B2 | 18900 | 20 | 16QAM | 1 | 50 | 11.27 | 39.90 |
| LTE B2 | 18900 | 15 | QPSK | 1 | 50 | 11.18 | 40.15 |
| LTE B2 | 18900 | 10 | QPSK | 1 | 50 | 10.22 | 40.19 |
| LTE B2 | 18900 | 5 | QPSK | 1 | 50 | 12.05 | 42.27 |
| LTE B2 | 18900 | 3 | QPSK | 1 | 50 | 11.20 | 39.68 |
| LTE B2 | 18900 | 1.4 | QPSK | 1 | 50 | 10.27 | 41.53 |

10. OTT VoIP Test System Setup and DUT Configuration

10.1. Test System Setup for OTT VoIP T-coil Testing

Note1: the yellow highlight section has been approved for reuse.

General Note2:

Regards the protocols, Google Duo, the highlighting section of the test set up, reference levels used, codec(s) and the fact that an investigation was done to determine the worst-case codec/rate documented in the test results below, will be re-used in future.


OTT VoIP Application

Google Duo is a pre-installed application on the DUT which allows for VoIP calls in a head-to-ear scenario. Duo uses the OPUS audio codec and supports a bitrate range of 6kbps to 75kbps. All air interfaces capable of a data connection were evaluated with Google Duo. When HAC testing we are using the Google Duo version is 26.0.179825522.alpha.DEV and the bitrate configuration can find at settings → Voice call parameters settings → Audio codec bitrate(6-75kbps).


Test Procedure and Equipment Setup

The test procedure for OTT testing is identical to the section above, except for how the signal is sent to the DUT, as outlined in the diagram below.

The AMMI is connected to the support device's Mic via Audio Data Line. The support device is connected to the Internet via Wi-Fi and the DUT is connected to the mobile base station via the technology under test. Using the DUT's OTT application, a VoIP call is established with the support device. The test signal is sent from the DASY PC to the AMMI, from the AMMI to the support device, and finally to the DUT. To exercise the license antenna, the DUT was simultaneously connected to an external AP and to a mobile base station.



Device1:



Device2:



Device3:



Device4:



Device5: The auxiliary device is pre-installed with a test version of Google duo app, The test version app can control the configurations of audio codec bitrate

Device6: The photo of DUT are presented in the additional document: Appendix to test report No.I20Z61322-SEM01/02 The photos of HAC test

Audio Level Settings

According to KDB 285076 D02, the average speech level of -20dBm0 shall be used for protocols not specifically listed in Table 7.1 of ANSI C63.19-2011.

Determine Input Audio level is based on the Added additional dBFS level readout by Google Duo customize application and three steps need to do.

1. Input a gain value to readout the -23dBFS level as reference. (0dBFS = 3.14 dBm0)
2. Adjust gain level to readout the dBFS level until it changes to -24dBFS.
3. Based on the step 1 and 2, and then calculate the gain value(dB) by interpolation to get the -20dBm0 corresponding gain value.

Codec Bit-rate Investigation

An investigation between the various bit-rate configurations (Low/Mid/High bit rates for Narrowband, Wideband, and EVS) are documented (ABM, SNNR, frequency response) to determine the worst case bit-rate for each voice service type. The tables below compare the varying bit-rate configurations

Air Interface Investigation

Using the worst-case bit-rate and Radio Configuration found in §11.2/11.3/11.4, a limited set of bands/channel/ bandwidths were then tested to confirm that there is no effect to the T-rating when changing the band/channel/bandwidth, it is necessary to report only a set band/channel/bandwidth for each orientation for a voice service/air interface.

10.2. Codec Configuration

An investigation was performed for each applicable data mode to determine the audio codec configuration to be used for testing. The 6kbps codec setting was used for the audio codec on the auxiliary VoIP unit for OTT VoIP T-coil testing. See below tables for comparisons between codec data rates on all applicable data modes:

Table 10-1 Codec Investigation – OTT over EDGE

| Codec Setting | 64kbps | 6kbps | Orientation | Channel |
|--------------------|--------|-------|-------------|---------|
| ABM1 (dBA/m) | 1.21 | 0.84 | Z(axial) | 661 |
| Frequency Response | Pass | Pass | | |
| SNR (dB) | 38.76 | 38.51 | | |

Table 10-2 Codec Investigation – OTT over HSPA

| Codec Setting | 64kbps | 6kbps | Orientation | Channel |
|--------------------|--------|-------|-------------|---------|
| ABM1 (dBA/m) | 2.06 | 1.54 | Z(axial) | 9400 |
| Frequency Response | Pass | Pass | | |
| SNR (dB) | 45.21 | 44.67 | | |

Table 10-3 Codec Investigation – OTT over LTE

| Codec Setting | 64kbps | 6kbps | Orientation | Band/BW | Channel |
|--------------------|--------|-------|-------------|---------|---------|
| ABM1 (dBA/m) | 9.21 | 10.12 | Z(axial) | B2/20M | 18900 |
| Frequency Response | Pass | Pass | | | |
| SNR (dB) | 52.63 | 51.59 | | | |

10.3. Radio Configuration for OTT VoIP (LTE)

An investigation was performed to determine the modulation and RB configuration to be used for testing. 10MHz BW, QPSK, 1RB, 50%RB offset was used for the testing as the worst-case configuration for the handset. See below table for comparisons between different radio configurations:

Table 10-4 OTT VoIP (LTE) SNR by Radio Configuration

| Band | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset(%) | ABM1 [dB(A/m)] | SNR [dB] |
|--------|---------|-----------------|------------|---------|--------------|----------------|----------|
| LTE B2 | 18900 | 20 | QPSK | 1 | 0 | 8.17 | 52.27 |
| LTE B2 | 18900 | 20 | QPSK | 1 | 50 | 10.12 | 51.59 |
| LTE B2 | 18900 | 20 | QPSK | 1 | 100 | 9.12 | 52.61 |
| LTE B2 | 18900 | 20 | QPSK | 50 | 0 | 8.24 | 51.93 |
| LTE B2 | 18900 | 20 | QPSK | 50 | 50 | 9.22 | 52.36 |
| LTE B2 | 18900 | 20 | QPSK | 50 | 100 | 8.26 | 52.84 |
| LTE B2 | 18900 | 20 | QPSK | 100 | 0 | 7.17 | 52.58 |
| LTE B2 | 18900 | 20 | 16QAM | 1 | 50 | 6.17 | 51.88 |
| LTE B2 | 18900 | 15 | QPSK | 1 | 50 | 7.17 | 52.69 |
| LTE B2 | 18900 | 10 | QPSK | 1 | 50 | 8.71 | 49.17 |
| LTE B2 | 18900 | 5 | QPSK | 1 | 50 | 6.14 | 50.63 |
| LTE B2 | 18900 | 3 | QPSK | 1 | 50 | 5.78 | 51.21 |
| LTE B2 | 18900 | 1.4 | QPSK | 1 | 50 | 4.91 | 50.86 |

An investigation was performed to determine the worst-case LTE band to be used for OTT VoIP testing. LTE Band 66 of FDD was used for the testing as the worst-case configuration for the handset. See below table for comparisons between different LTE bands:

Table 10-5 OTT VoIP (LTE) SNR by LTE bands

| Band | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset(%) | ABM1 [dB(A/m)] | SNR [dB] |
|---------|---------|-----------------|------------|---------|--------------|----------------|----------|
| LTE B2 | 18900 | 10 | QPSK | 1 | 50 | 8.71 | 49.17 |
| LTE B5 | 20525 | 10 | QPSK | 1 | 50 | 3.21 | 49.28 |
| LTE B12 | 23095 | 10 | QPSK | 1 | 50 | 4.26 | 50.19 |
| LTE B13 | 23230 | 10 | QPSK | 1 | 50 | 3.27 | 50.37 |
| LTE B66 | 132322 | 10 | QPSK | 1 | 50 | 1.76 | 40.15 |

11. HAC T-Coil TEST DATA SUMMARY

11.1. Test Results for 2/3G

Table 11-1 Test results for 2/3G

| Probe Position | Band | Ch. | Measurement Position (x mm, y mm) | ABM1 (dB A/m) | SNR (dB) | T category |
|----------------|------------------|------|-----------------------------------|---------------|----------|------------|
| transverse | GSM 850 | 190 | -5.8,3.7 | -2.07 | 39.18 | T4 |
| | GSM 1900 | 661 | -3.7,0.8 | 1.97 | 39.27 | T4 |
| | WCDMA850 | 4182 | -5,-5.8 | 0.16 | 42.22 | T4 |
| | WCDMA1900 | 9400 | -4.2,-6.3 | 0.74 | 42.13 | T4 |
| | WCDMA1700 | 1412 | -8.3,-6.3 | -3.68 | 42.15 | T4 |
| perpendicular | GSM 850 | 190 | 4.2,-19.6 | 9.43 | 39.31 | T4 |
| | GSM 1900 | 661 | 1.3,-15.8 | 10.88 | 39.80 | T4 |
| | WCDMA850 | 4182 | -8.3,6.2 | -9.13 | 43.62 | T4 |
| | WCDMA1900 | 9400 | 0.4,8.7 | -1.30 | 40.77 | T4 |
| | WCDMA1700 | 1412 | 0.4,8.7 | -1.29 | 39.98 | T4 |

Note:

1. Bluetooth and WiFi function is turn off and microphone is muted.
2. Signal strength measurement scan plots are presented in Annex B.
3. The volume is adjusted to maximum level during T-Coil testing.

11.2. Test Results for LTE

Table 11-2 Test results for LTE

| Probe Position | Band | Ch. | Bandwidth | Measurement Position (x mm, y mm) | ABM1 (dB A/m) | SNR (dB) | Category T ? |
|-----------------|----------------|--------|-----------|-----------------------------------|---------------|----------|--------------|
| Transverse y | LTE B2 | 18900 | 3M | -2.5,0.4 | 1.19 | 42.88 | T4 |
| | LTE B5 | 20525 | 3M | -1.3,0.9 | 3.21 | 42.69 | T4 |
| | LTE B12 | 23095 | 3M | -1.8,0.2 | 3.93 | 42.14 | T4 |
| | LTE B13 | 23230 | 10M | 3.6,0.6 | 2.54 | 41.58 | T4 |
| | LTE B66 | 132322 | 3M | 4.2,0 | 5.75 | 40.51 | T4 |
| Perpendicular z | LTE B2 | 18900 | 3M | 5.-8.8 | 11.20 | 39.68 | T4 |
| | LTE B5 | 20525 | 3M | 4.6,-9.2 | 11.24 | 41.65 | T4 |
| | LTE B12 | 23095 | 3M | 5.1,-10.7 | 10.93 | 40.98 | T4 |
| | LTE B13 | 23230 | 10M | 3.6,-11.3 | 9.71 | 41.36 | T4 |
| | LTE B66 | 132322 | 3M | 4.2,-12.5 | 10.87 | 39.97 | T4 |

Note:

1. Bluetooth and WiFi function is turn off and microphone is muted.
2. The worse case of each band for signal strength measurement scan plots are presented in Annex B.
3. The volume is adjusted to maximum level during T-Coil testing.

11.3. Test Results for OTT VoIP

Table 11-3 Test results for 2/3G

| Probe Position | Band | Ch. | Measurement Position (x mm, y mm) | ABM1 (dB A/m) | SNR (dB) | Category T ? |
|-----------------|----------|------|-----------------------------------|---------------|----------|--------------|
| Transverse y | EDGE850 | 190 | 12.5,4.2 | -4.98 | 34.97 | T4 |
| | EDGE1900 | 661 | 11.8,3.7 | -5.21 | 35.21 | T4 |
| | W850 | 4407 | 2.6,-19.3 | -1.26 | 49.57 | T4 |
| | W1900 | 9800 | 3.8,-21.7 | -0.72 | 48.90 | T4 |
| | W1700 | 1637 | 3.1,-20.6 | -0.91 | 49.16 | T4 |
| Perpendicular z | EDGE850 | 190 | 7.9,-15.4 | 0.39 | 38.00 | T4 |
| | EDGE1900 | 661 | 6.7,-13.2 | 0.84 | 38.51 | T4 |
| | W850 | 4407 | 7.4,-15.1 | 1.21 | 45.67 | T4 |
| | W1900 | 9800 | 8.3,-16.7 | 1.54 | 44.67 | T4 |
| | W1700 | 1637 | 8.2,-11.9 | 2.63 | 45.32 | T4 |

Note:

1. Bluetooth and WiFi function is turn off and microphone is muted.
2. Signal strength measurement scan plots are presented in Annex B.
3. The volume is adjusted to maximum level during T-Coil testing.

Table 11-4 Test results for LTE

| Probe Position | Band | Ch. | Band width | Measurement Position (x mm, y mm) | ABM1 (dB A/m) | SNR (dB) | Category T ? |
|-----------------|---------|-------|------------|-----------------------------------|---------------|----------|--------------|
| Transverse y | LTE B66 | 18900 | 10M | 4.2,-2.9 | 2.52 | 45.60 | T4 |
| Perpendicular z | LTE B66 | 18900 | 10M | 7.9,-14.2 | 1.76 | 40.15 | T4 |

Note:

1. Bluetooth and WiFi function is turn off and microphone is muted.
2. The worse case of each band for signal strength measurement scan plots are presented in Annex B.
3. The volume is adjusted to maximum level during T-Coil testing.

11.4. Total Measurement Conclusion

| Probe Position | Frequency Band(MHz) | ABM1 | Frequency Response | T Category |
|----------------|---------------------|------|--------------------|------------|
| Transverse | GSM 850 | Pass | / | T4 |
| | GSM 1900 | Pass | | T4 |
| | WCDMA850 | Pass | | T4 |
| | WCDMA1900 | Pass | | T4 |
| | WCDMA1700 | Pass | | T4 |
| | LTE B2 | Pass | | T4 |
| | LTE B5 | Pass | | T4 |
| | LTE B12 | Pass | | T4 |
| | LTE B13 | Pass | | T4 |
| | LTE B66 | Pass | | T4 |
| Perpendicular | GSM 850 | Pass | Pass | T4 |
| | GSM 1900 | Pass | Pass | T4 |
| | WCDMA850 | Pass | Pass | T4 |
| | WCDMA1900 | Pass | Pass | T4 |
| | WCDMA1700 | Pass | Pass | T4 |
| | LTE B2 | Pass | Pass | T4 |
| | LTE B5 | Pass | Pass | T4 |
| | LTE B12 | Pass | Pass | T4 |
| | LTE B13 | Pass | Pass | T4 |
| | LTE B66 | Pass | Pass | T4 |

12. Measurement Uncertainty


| No. | Error source | Type | Uncertainty Value a _i (%) | Prob. Dist. | Div. | ABM1 ci | ABM2 ci | Std. Unc. ABM1 u _i (%) | Std. Unc. ABM2 u _i (%) |
|---------------------------------------|--------------------------------------|--------------------------------------------|-----------------------------------------|-------------|------------|------------|------------|-----------------------------------------|-----------------------------------------|
| 1 | System Repeatability | A | 0.016 | N | 1 | 1 | 1 | 0.016 | 0.016 |
| Probe Sensitivity | | | | | | | | | |
| 2 | Reference Level | B | 3.0 | R | $\sqrt{3}$ | 1 | 1 | 3.0 | 3.0 |
| 3 | AMCC Geometry | B | 0.4 | R | $\sqrt{3}$ | 1 | 1 | 0.2 | 0.2 |
| 4 | AMCC Current | B | 0.6 | R | $\sqrt{3}$ | 1 | 1 | 0.4 | 0.4 |
| 5 | Probe Positioning during Calibration | B | 0.1 | R | $\sqrt{3}$ | 1 | 1 | 0.1 | 0.1 |
| 6 | Noise Contribution | B | 0.7 | R | $\sqrt{3}$ | 0.014 3 | 1 | 0.0 | 0.4 |
| 7 | Frequency Slope | B | 5.9 | R | $\sqrt{3}$ | 0.1 | 1 | 0.3 | 3.5 |
| Probe System | | | | | | | | | |
| 8 | Repeatability / Drift | B | 1.0 | R | $\sqrt{3}$ | 1 | 1 | 0.6 | 0.6 |
| 9 | Linearity / Dynamic Range | B | 0.6 | N | 1 | 1 | 1 | 0.4 | 0.4 |
| 10 | Acoustic Noise | B | 1.0 | R | $\sqrt{3}$ | 0.1 | 1 | 0.1 | 0.6 |
| 11 | Probe Angle | B | 2.3 | R | $\sqrt{3}$ | 1 | 1 | 1.4 | 1.4 |
| 12 | Spectral Processing | B | 0.9 | R | $\sqrt{3}$ | 1 | 1 | 0.5 | 0.5 |
| 13 | Integration Time | B | 0.6 | N | 1 | 1 | 5 | 0.6 | 3.0 |
| 14 | Field Distribution | B | 0.2 | R | $\sqrt{3}$ | 1 | 1 | 0.1 | 0.1 |
| Test Signal | | | | | | | | | |
| 15 | Ref. Signal Spectral Response | B | 0.6 | R | $\sqrt{3}$ | 0 | 1 | 0.0 | 0.4 |
| Positioning | | | | | | | | | |
| 16 | Probe Positioning | B | 1.9 | R | $\sqrt{3}$ | 1 | 1 | 1.1 | 1.1 |
| 17 | Phantom Thickness | B | 0.9 | R | $\sqrt{3}$ | 1 | 1 | 0.5 | 0.5 |
| 18 | DUT Positioning | B | 1.9 | R | $\sqrt{3}$ | 1 | 1 | 1.1 | 1.1 |
| External Contributions | | | | | | | | | |
| 19 | RF Interference | B | 0.0 | R | $\sqrt{3}$ | 1 | 0.3 | 0.0 | 0.0 |
| 20 | Test Signal Variation | B | 2.0 | R | $\sqrt{3}$ | 1 | 1 | 1.2 | 1.2 |
| Combined Std. Uncertainty (ABM Field) | | $u_c = \sqrt{\sum_{i=1}^{20} c_i^2 u_i^2}$ | | | | | | 4.1 | 6.1 |
| Expanded Std. Uncertainty | | $u_e = 2u_c$ | | N | | $k = 2$ | | 8.2 | 12.2 |

13. Main Test Instruments

Table 13-1: List of Main Instruments

| No. | Name | Type | Serial Number | Calibration Date | Valid Period |
|-----|---------------------------------|--------|---------------|------------------|--------------|
| 01 | Audio Magnetic 1D Field Probe | AM1DV3 | 3086 | 2018-02-22 | Three year |
| 02 | Audio Magnetic Calibration Coil | AMCC | 1105 | / | / |
| 03 | Audio Measuring Instrument | AMMI | 1121 | / | / |
| 04 | HAC Test Arch | N/A | 1150 | / | / |
| 05 | DAE | DAE4 | 1527 | 2019-11-11 | One year |
| 06 | BTS | CMU500 | 152499 | 2020-07-17 | One year |
| 07 | Software | DASY5 | 52.8.8.1222 | / | / |

ANNEX A: Test Layout



Picture A1: HAC T-Coil System Layout

ANNEX B: Test Plots**T-Coil GSM 850 Transverse**

Date: 2020-9-18

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature: 22.5°C

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Probe: AM1DV3 - 3086;

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal)**4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 100

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 8.65 dBA/m

BWC Factor = 0.16 dB

Location: 7.9, -4.2, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal)**4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 100

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 39.18 dB

ABM1 comp = -2.07 dBA/m

BWC Factor = 0.16 dB

Location: -5.8, 3.7, 3.7 mm




Fig B.1 T-Coil GSM 850

T-Coil GSM 850 Perpendicular

Date: 2020-9-18

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature: 22.5°C

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Probe: AM1DV3 - 3086;

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm

50 x 50 NB12.2/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 41.7

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 15.01 dBA/m

BWC Factor = 0.16 dB

Location: 7.9, -12.9, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm

50 x 50 NB12.2/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 41.7

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 39.31 dB

ABM1 comp = 9.43 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, -19.6, 3.7 mm




Fig B.2 T-Coil GSM 850

T-Coil LTE B66 Transverse

Date: 2020-9-20

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature: 22.5°C

Communication System: LTE B66; Frequency: 1745 MHz; Duty Cycle: 1:1

Probe: AM1DV3 - 3086;

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal)

4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 100

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 8.29 dBA/m

BWC Factor = 0.16 dB

Location: 10.8, -2.9, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal)

4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 100

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 40.51 dB

ABM1 comp = 5.75 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 0, 3.7 mm




Fig B.3 T-Coil LTE B66

T-Coil LTE B2 Perpendicular

Date: 2020-9-19

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature: 22.5°C

Communication System: LTE B2; Frequency: 1880 MHz; Duty Cycle: 1:1

Probe: AM1DV3 - 3086;

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm

50 x 50 NB 3m/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 41.7

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 14.67 dBA/m

BWC Factor = 0.16 dB

Location: 10.8, -10.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm

50 x 50 NB 3m/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 41.7

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 39.68 dB

ABM1 comp = 11.20 dBA/m

BWC Factor = 0.16 dB

Location: 5, -8.8, 3.7 mm




Fig B.4 T-Coil LTE B2

T-Coil EDGE 850 Transverse - OTT VoIP

Date: 2020-9-21

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature: 22.5°C

Communication System: EDGE 850; Frequency: 836.6MHz; Duty Cycle: 1:4

Probe: AM1DV3 - 3086;

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal)

4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 100

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = -0.22 dBA/m

BWC Factor = 0.16 dB

Location: 11.3, -21.3, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal)

4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 100

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 34.97 dB

ABM1 comp = -4.98 dBA/m

BWC Factor = 0.16 dB

Location: 12.5, 4.2, 3.7 mm




Fig B.5 T-Coil EDGE 850

T-Coil EDGE 850 Perpendicular - OTT VoIP

Date: 2020-9-21

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature: 22.5°C

Communication System: EDGE 850; Frequency: 836.6 MHz; Duty Cycle: 1:4

Probe: AM1DV3 - 3086;

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm

50 x 50 NB12.2/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 41.7

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 2.15 dBA/m

BWC Factor = 0.16 dB

Location: 9.2, -12.9, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm

50 x 50 NB12.2/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 41.7

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 38.00 dB

ABM1 comp = 0.39 dBA/m

BWC Factor = 0.16 dB

Location: 7.9, -15.4, 3.7 mm




Fig B.6 T-Coil EDGE 850

T-Coil LTE B66 Transverse - OTT VoIP

Date: 2020-9-22

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature: 22.5°C

Communication System: LTE B66; Frequency: 1745MHz; Duty Cycle: 1:1

Probe: AM1DV3 - 3086;

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal)

4.2mm 50 x 50/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 100

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 3.08 dBA/m

BWC Factor = 0.16 dB

Location: 4.6, -3.8, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal)

4.2mm 50 x 50/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 100

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 45.60 dB

ABM1 comp = 2.52 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, -2.9, 3.7 mm




Fig B.7 T-Coil LTE B66

T-Coil LTE B66 Perpendicular - OTT VoIP

Date: 2020-9-22

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Ambient Temperature: 22.5°C

Communication System: LTE B66; Frequency: 1745 MHz; Duty Cycle: 1:1

Probe: AM1DV3 - 3086;

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm

50 x 50 NB12.2/ABM Interpolated Signal(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 41.7

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = 3.37 dBA/m

BWC Factor = 0.16 dB

Location: 11.3, -10.4, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm

50 x 50 NB12.2/ABM Interpolated SNR(x,y,z) (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 41.7

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 40.15 dB

ABM1 comp = 1.76 dBA/m

BWC Factor = 0.16 dB

Location: 7.9, -14.2, 3.7 mm




Fig B.8 T-Coil LTE B66

ANNEX C: Frequency Response Curves




Figure C.1 Frequency Response of GSM 850




Figure C.2 Frequency Response of LTE B2




Figure C.3 Frequency Response of EDGE850 - OTT VoIP




Figure C.4 Frequency Response of LTE B66 – OTT VoIP

ANNEX D: Probe Calibration Certificate

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client CTTL-SZ (Auden)

Certificate No: AM1DV3-3086_Feb18

CALIBRATION CERTIFICATE

| | |
|--------------------------|--------------------------------------------------------------------------------------------------|
| Object | AM1DV3 - SN: 3086 |
| Calibration procedure(s) | QA CAL-24.v4 Calibration procedure for AM1D magnetic field probes and TMFS in the audio range |
| Calibration date: | February 22, 2018 |

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|---------------------------------|-------------|-----------------------------------|-----------------------|
| Keithley Multimeter Type 2001 | SN: 0810278 | 31-Aug-17 (No. 21092) | Aug-18 |
| Reference Probe AM1DV2 | SN: 1008 | 03-Jan-18 (No. AM1DV2-1008_Jan18) | Jan-19 |
| DAE4 | SN: 781 | 17-Jan-18 (No. DAE4-781_Jan18) | Jan-19 |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
| AMOC | SN: 1050 | 01-Oct-13 (in house check Oct-17) | Oct-19 |
| AMMI Audio Measuring Instrument | SN: 1062 | 26-Sep-12 (in house check Oct-17) | Oct-19 |

Calibrated by: Name: Leif Klysnér Function: Laboratory Technician Signature: 

Approved by: Name: Katja Pokovic Function: Technical Manager Signature: 

Issued: February 23, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

[References

- [1] ANSI-C63.19-2007 American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [2] ANSI-C63.19-2011 American National Standard, Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [3] DASY5 manual, Chapter: Hearing Aid Compatibility (HAC) T-Coil Extension

Description of the AM1D probe

The AM1D Audio Magnetic Field Probe is a fully shielded magnetic field probe for the frequency range from 100 Hz to 20 kHz. The pickup coil is compliant with the dimensional requirements of [1+2]. The probe includes a symmetric low noise amplifier for the signal available at the shielded 3 pin connector at the side. Power is supplied via the same connector (phantom power supply) and monitored via the LED near the connector. The 7 pin connector at the end of the probe does not carry any signals, but determines the angle of the sensor when mounted on the DAE. The probe supports mechanical detection of the surface.

The single sensor in the probe is arranged in a tilt angle allowing measurement of 3 orthogonal field components when rotating the probe by 120° around its axis. It is aligned with the perpendicular component of the field, if the probe axis is tilted nominally 35.3° above the measurement plane, using the connector rotation and sensor angle stated below.

The probe is fully RF shielded when operated with the matching signal cable (shielded) and allows measurement of audio magnetic fields in the close vicinity of RF emitting wireless devices according to [1+2] without additional shielding.

Handling of the item

The probe is manufactured from stainless steel. In order to maintain the performance and calibration of the probe, it must not be opened. The probe is designed for operation in air and shall not be exposed to humidity or liquids. For proper operation of the surface detection and emergency stop functions in a DASY system, the probe must be operated with the special probe cup provided (larger diameter).

Methods Applied and Interpretation of Parameters

- *Coordinate System:* The AM1D probe is mounted in the DASY system for operation with a HAC Test Arch phantom with AMCC Helmholtz calibration coil according to [3], with the tip pointing to "southwest" orientation.
- *Functional Test:* The functional test preceding calibration includes test of Noise level RF immunity (1kHz AM modulated signal). The shield of the probe cable must be well connected. Frequency response verification from 100 Hz to 10 kHz.
- *Connector Rotation:* The connector at the end of the probe does not carry any signals and is used for fixation to the DAE only. The probe is operated in the center of the AMCC Helmholtz coil using a 1 kHz magnetic field signal. Its angle is determined from the two minima at nominally +120° and -120° rotation, so the sensor in the tip of the probe is aligned to the vertical plane in z-direction, corresponding to the field maximum in the AMCC Helmholtz calibration coil.
- *Sensor Angle:* The sensor tilting in the vertical plane from the ideal vertical direction is determined from the two minima at nominally +120° and -120°. DASY system uses this angle to align the sensor for radial measurements to the x and y axis in the horizontal plane.

Sensitivity: With the probe sensor aligned to the z-field in the AMCC, the output of the probe is compared to the magnetic field in the AMCC at 1 kHz. The field in the AMCC Helmholtz coil is given by the geometry and the current through the coil, which is monitored on the precision shunt resistor of the coil.

AM1D probe identification and configuration data

| | |
|-----------|--------------------------------------|
| Item | AM1DV3 Audio Magnetic 1D Field Probe |
| Type No | SP AM1 001 BA |
| Serial No | 3086 |

| | |
|--------------------|------------------------------------|
| Overall length | 296 mm |
| Tip diameter | 6.0 mm (at the tip) |
| Sensor offset | 3.0 mm (centre of sensor from tip) |
| Internal Amplifier | 20 dB |


| | |
|-----------------------|------------------------------------------------------|
| Manufacturer / Origin | Schmid & Partner Engineering AG, Zurich, Switzerland |
| Manufacturing date | May 28, 2010 |

Calibration data

| | | | |
|--------------------------|------------------|-------------------|-----------------|
| Connector rotation angle | (in DASY system) | 204.7° | +/- 3.6 ° (k=2) |
| Sensor angle | (in DASY system) | 0.95 ° | +/- 0.5 ° (k=2) |
| Sensitivity at 1 kHz | (in DASY system) | 0.00743 V / (A/m) | +/- 2.2 % (k=2) |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

ANNEX E: DAE Calibration Certificate



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504
E-mail: ctli@chinattl.com <http://www.chinattl.cn>



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Client : CTTL(South Branch)

Certificate No: Z19-60419

CALIBRATION CERTIFICATE

Object DAE4 - SN: 1527

Calibration Procedure(s) FF-Z11-002-01
Calibration Procedure for the Data Acquisition Electronics (DAEx)

Calibration date: November 11, 2019

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.


All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date(Calibrated by, Certificate No.) | Scheduled Calibration |
|------------------------|---------|------------------------------------------|-----------------------|
| Process Calibrator 753 | 1971018 | 24-Jun-19 (CTTL, No.J19X05126) | Jun-20 |

Calibrated by: Name Yu Zongying Function SAR Test Engineer Signature 

Reviewed by: Name Lin Hao Function SAR Test Engineer Signature 

Approved by: Name Qi Dianyuan Function SAR Project Leader Signature 

Issued: November 13, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504
E-mail: cfl@chinattl.com Http://www.chinattl.cn

Glossary:

DAE data acquisition electronics
Connector angle information used in DASY system to align probe sensor X to the robot coordinate system.

Methods Applied and Interpretation of Parameters:

- *DC Voltage Measurement:* Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle:* The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The report provide only calibration results for DAE, it does not contain other performance test results.

**CAICT**

No. I20N02478-HAC T-coil



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)

DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB = $6.1\mu V$, full range = $-100...+300\text{ mV}$
Low Range: 1LSB = 61nV , full range = $-1...+3\text{mV}$

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| Calibration Factors | X | Y | Z |
|---------------------|------------------------------------|------------------------------------|------------------------------------|
| High Range | $403.867 \pm 0.15\% \text{ (k=2)}$ | $403.590 \pm 0.15\% \text{ (k=2)}$ | $403.811 \pm 0.15\% \text{ (k=2)}$ |
| Low Range | $3.96119 \pm 0.7\% \text{ (k=2)}$ | $3.99117 \pm 0.7\% \text{ (k=2)}$ | $3.97030 \pm 0.7\% \text{ (k=2)}$ |

Connector Angle

| | |
|-------------------------------------------|-------------------------|
| Connector Angle to be used in DASY system | $223^\circ \pm 1^\circ$ |
|-------------------------------------------|-------------------------|

ANNEX F: Accreditation Certificate



Accredited Laboratory

A2LA has accredited

SHENZHEN ACADEMY OF INFORMATION AND COMMUNICATIONS TECHNOLOGY

Shenzhen, People's Republic of China

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-IAC-IAF Communiqué dated April 2017).

Presented this 30th day of October 2019.



Vice President Accreditation Services
For the Accreditation Council
Certificate Number 4359.01
Valid to November 30, 2021



For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

END OF REPORT