



TEST REPORT

No.B22N02534-BLE

for

TCL Communication Ltd.

GSM/UMTS/LTE /NR Mobile phone

Model Name: T609DL

with

Hardware Version: 04

Software Version: JSS8

FCC ID: 2ACCJH168

Issued Date: 2022-12-15

Designation Number: CN1210

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SAICT.

Test Laboratory:

SAICT, Shenzhen Academy of Information and Communications Technology

Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518000.

Tel:+86(0)755-33322000, Fax:+86(0)755-33322001

Email: yewu@caict.ac.cn www.caict.ac.cn

©Copyright. All rights reserved by SAICT.



No.B22N02534-BLE

REPORT HISTORY

Report Number	Revision	Description	Issue Date
B22N02534-BLE	Rev.0	1st edition	2022-12-15

Note: the latest revision of the test report supersedes all previous versions.

CONTENTS

1. SUMMARY OF TEST REPORT	5
1.1. TEST ITEMS.....	5
1.2. TEST STANDARDS	5
1.3. TEST RESULT	5
1.4. TESTING LOCATION.....	5
1.5. PROJECT DATA.....	5
1.6. SIGNATURE	5
2. CLIENT INFORMATION	6
2.1. APPLICANT INFORMATION.....	6
2.2. MANUFACTURER INFORMATION.....	6
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	7
3.1. ABOUT EUT	7
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST.....	7
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	7
3.4. GENERAL DESCRIPTION.....	8
4. REFERENCE DOCUMENTS	9
4.1. DOCUMENTS SUPPLIED BY APPLICANT	9
4.2. REFERENCE DOCUMENTS FOR TESTING	9
5. TEST RESULTS.....	10
5.1. TESTING ENVIRONMENT.....	10
5.2. TEST RESULTS.....	10
5.3. STATEMENTS.....	10
6. MEASURING APPARATUS UTILIZED.....	11
7. LABORATORY ENVIRONMENT	12
8. MEASUREMENT UNCERTAINTY	13
ANNEX A: DETAILED TEST RESULTS.....	14
TEST CONFIGURATION.....	14
A.1 TRANSMITTER SPURIOUS EMISSION - RADIATED	17
A.2 AC POWER LINE CONDUCTED EMISSION	31



No.B22N02534-BLE



1. Summary of Test Report

1.1. Test Items

Description GSM/UMTS/LTE /NR Mobile phone
Model Name T609DL
Applicant's name TCL Communication Ltd.
Manufacturer's Name TCL Communication Ltd.

1.2. Test Standards

FCC Part15-2021; ANSI C63.10-2013.

1.3. Test Result

Pass

Please refer to "5.2. Test Results"

1.4. Testing Location

Address: EMC Laboratory, Building G, Shenzhen International Innovation Center, No.1006
Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China

1.5. Project data

Testing Start Date: 2022-12-06
Testing End Date: 2022-12-14

1.6. Signature

Huang Kaiyang
(Prepared this test report)

Huang Yuqing
(Reviewed this test report)

Cao Junfei
(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong
Contact Person: Annie Jiang
E-Mail: nianxiang.jiang@tcl.com
Telephone: +86 755 3661 1621
Fax: +86 755 3661 2000-81722

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong
Contact Person: Annie Jiang
E-Mail: nianxiang.jiang@tcl.com
Telephone: +86 755 3661 1621
Fax: +86 755 3661 2000-81722

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	GSM/UMTS/LTE /NR Mobile phone
Model Name	T609DL
Frequency Range	ISM 2400MHz~2483.5MHz
Equipment type	Bluetooth® Low Energy
Type of Modulation	GFSK
PHY	LE 1M/2M
Number of Channels	40
Antenna Type	Integrated antenna
Power Supply	3.85V DC by Battery
FCC ID	2ACCJH168
Condition of EUT as received	No abnormality in appearance

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Shenzhen Academy of Information and Communications Technology.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of Receipt
UT03aa	016320000014344	04	JSS8	2022-12-05
UT05aa	016320000013742	04	JSS8	2022-12-05

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE No.	Description	AE ID*
AE1	Battery	
AE2	Charger	
AE3	USB Cable	

AE1-1

Model	TLp048D7
S/N	CAC4850007C7
Manufacturer	VEKEN
Capacity	5000mAh
Nominal Voltage	3.85 V

AE2-1

Model	CBA0064BGTC5
Manufacturer	PUAN

AE2-2

Model	CBA0064BGTC1
Manufacturer	BYD



AE3-1

Model CDA0000198C1
Manufacturer JUWEI

AE3-2

Model CDA0000198C2
Manufacturer SHENGHUA

AE3-3

Model CDA0000201C2
Manufacturer SHENGHUA

AE3-4

Model CDA0000202C1
Manufacturer JUWEI

*AE ID: is used to identify the test sample in the lab internally.

AE: ancillary equipment.

3.4. General Description

The Equipment under Test (EUT) is a model of GSM/UMTS/LTE /NR Mobile phone with integrated antenna and battery.

It consists of normal options: Battery, Charger, and USB Cable.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.



4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz	2021
ANSI C63.10	American National Standard of Procedures for Compliance 2013 Testing of Unlicensed Wireless Devices	

5. Test Results

5.1. Testing Environment

Normal Temperature: 15~35°C

Relative Humidity: 20~75%

5.2. Test Results

No	Test cases	Sub-clause of Part 15C	Verdict
1	Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	P
2	AC Power line Conducted Emission	15.107, 15.207	P

See **ANNEX A** for details.

5.3. Statements

SAICT has evaluated the test cases requested by the applicant/manufacturer as listed in section 5.2 of this report, for the EUT specified in section 3, according to the standards or reference documents listed in section 4.2.

Disclaimer:

- A. After confirmation with the customer, the sample information provided by the customer may affect the validity of the measurement results in this report, and the impact and consequences arising therefrom shall be borne by the customer.
- B. The samples in this report are provided by the customer, and the test results are only applicable to the samples received.

6. Measuring Apparatus Utilized

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date	Calibration Period
1	Test Receiver	ESR7	101676	Rohde & Schwarz	2023-11-23	1 year
2	BiLog Antenna	3142E	0224831	ETS-Lindgren	2024-05-27	3 years
3	Horn Antenna	3117	00066577	ETS-Lindgren	2025-04-17	3 years
4	Anechoic Chamber	FACT3-2.0	1285	ETS-Lindgren	2023-05-29	2 years
5	Spectrum Analyzer	FSV40	101192	Rohde & Schwarz	2023-01-12	1 year
6	Loop Antenna	HLA6120	35779	TESEQ	2025-05-10	3 years
7	Horn Antenna	QSH-SL-1 8-26-S-20	17013	Q-par	2023-01-06	3 years
8	Test Receiver	ESCI	100702	Rohde & Schwarz	2023-01-12	1 year
9	LISN	ENV216	102067	Rohde & Schwarz	2023-07-14	1 year

Test software

No.	Equipment	Manufacturer	Version
2	EMC32	Rohde & Schwarz	10.50.40

EUT is engineering software provided by the customer to control the transmitting signal.

The EUT was programmed to be in continuously transmitting mode.

7. Laboratory Environment

Shielded room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4Ω

Anechoic chamber (FACT3-2.0) did not exceed following limits along the EMC testing:

9.10mx6.10mx5.60m (LxWxH)

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4Ω
Normalised site attenuation (NSA)	< ±4 dB, 3 m distance, from 30 to 1000 MHz
Voltage Standing Wave Ratio (VSWR)	≤ 6 dB, from 1 to 18 GHz, 3 m distance
Uniformity of field strength	Between 0 and 6 dB, from 80 to 6000 MHz

8. Measurement Uncertainty

Test Name	Uncertainty (<i>k</i> =2)	
Transmitter Spurious Emission - Radiated	9kHz≤f<30MHz	1.79dB
	30MHz≤f<1GHz	4.86dB
	1GHz≤f<18GHz	4.82dB
	18GHz≤f≤40GHz	2.90dB
AC Power line Conducted Emission	150kHz≤f≤30MHz	2.62dB

ANNEX A: Detailed Test Results

Test Configuration


The measurement is made according to ANSI C63.10.

1) Radiated Measurements

Test setup:



9kHz-30MHz:


The EUT are measured in a anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 3m from the receiving antenna. The center of the receiving loop antenna is 1.0 meter above the ground. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT and adjusting the receiver antenna polarization.




30MHz-26.5GHz:

The EUT are measured in a anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 3m from the receiving antenna. The center of the receiving antenna is 1.0 meter to 4.0 meter above the ground. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT and adjusting the receiver antenna polarization.

30MHz-1GHz:

1GHz-3GHz:


3GHz-26.5GHz:

2) AC Power line Conducted Emission Measurement

For Bluetooth LE, the EUT is working under test mode. The EUT is commanded to operate at maximum transmitting power.



A.1 Transmitter Spurious Emission - Radiated

Method of Measurement: See ANSI C63.10-clause 11.11&11.12.

Measurement Limit:

Standard	Limit (dBm)
FCC 47 CFR Part 15.247, 15.205, 15.209	20dBm below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(μ V/m)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Condition:

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	120kHz/300kHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

Note: According to the performance evaluation, the radiated emission margin of EUT is over 20dB in the band from 9kHz to 30MHz. Therefore, the measurement starts from 30MHz to tenth harmonic. The measurement results include the horizontal polarization and vertical polarization measurements. For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

Measurement Results:

Mode	Frequency (MHz)	Frequency Range	Test Results	Conclusion
LE 1M	2402(CH0)	1 GHz ~18 GHz	Fig.1	P
	2440(CH19)	1 GHz ~18 GHz	Fig.2	P
	2480(CH39)	1 GHz ~18 GHz	Fig.3	P
	Restricted Band(CH0)	2.38 GHz ~ 2.45 GHz	Fig.4	P
	Restricted Band(CH39)	2.45 GHz ~ 2.5 GHz	Fig.5	P
	All channels	9 kHz ~30 MHz	Fig.6	P
		30 MHz ~1 GHz	Fig.7	P
		18 GHz ~ 26.5 GHz	Fig.8	P
LE 2M	2402(CH0)	1 GHz ~18 GHz	Fig.9	P
	2440(CH19)	1 GHz ~18 GHz	Fig.10	P
	2480(CH39)	1 GHz ~18 GHz	Fig.11	P
	Restricted Band(CH0)	2.38 GHz ~ 2.45 GHz	Fig.12	P
	Restricted Band(CH39)	2.45 GHz ~ 2.5 GHz	Fig.13	P
	All channels	9 kHz ~30 MHz	Fig.14	P
		30 MHz ~1 GHz	Fig.15	P
		18 GHz ~ 26.5 GHz	Fig.16	P

Worst Case Result:
For LE 1M:
CH19 (1-18GHz)

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2806.400000	48.11	74.00	25.89	V	10.77
3796.500000	35.71	74.00	38.29	V	-12.41
5678.100000	39.08	74.00	34.92	V	-7.44
9003.200000	45.96	74.00	28.04	H	-1.74
14271.600000	50.49	74.00	23.51	H	6.65
17980.400000	55.64	74.00	18.36	V	14.21

Frequency (MHz)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2806.400000	35.37	54.00	18.63	V	10.77
3796.500000	22.49	54.00	31.51	V	-12.41
5678.100000	26.40	54.00	27.60	V	-7.44
9003.200000	31.26	54.00	22.74	H	-1.74
14271.600000	37.78	54.00	16.22	H	6.65
17980.400000	43.06	54.00	10.94	V	14.21

For LE 2M:

CH39(1-18GHz)

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2938.800000	47.74	74.00	26.26	V	10.81
3519.600000	34.87	74.00	39.13	H	-13.44
4678.200000	38.49	74.00	35.51	H	-9.59
7309.600000	43.15	74.00	30.85	H	-1.64
14260.800000	50.93	74.00	23.07	H	6.89
17987.600000	55.36	74.00	18.64	H	14.07

Frequency (MHz)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2938.800000	34.75	54.00	19.25	V	10.81
3519.600000	22.86	54.00	31.14	H	-13.44
4678.200000	25.32	54.00	28.68	H	-9.59
7309.600000	30.69	54.00	23.31	H	-1.64
14260.800000	38.16	54.00	15.84	H	6.89
17987.600000	43.48	54.00	10.52	H	14.07

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and Antenna Factor, the gain of the preamplifier, the cable loss. P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= P_{Mea} +Cable Loss +Antenna Factor-Gain of the preamplifier.

See below for test graphs.

Conclusion: Pass




Fig.1 Radiated Spurious Emission (CH0, 1GHz ~18GHz), LE 1M




Fig.2 Radiated Spurious Emission (CH19, 1GHz ~18GHz), LE 1M




Fig.3 Radiated Spurious Emission (CH39, 1GHz ~18GHz), LE 1M




Fig.4 Radiated Band Edges (CH0, 2.38GHz~2.45GHz), LE 1M




Fig.5 Radiated Band Edges (CH39, 2.45GHz~2.50GHz), LE 1M




Fig.6 Radiated Spurious Emission (All Channels, 9kHz-30MHz), LE 1M




Fig.7 Radiated Spurious Emission (All Channels, 30MHz-1GHz), LE 1M





Fig.8 Radiated Spurious Emission (All Channels, 18GHz-26.5GHz), LE 1M**Fig.9 Radiated Spurious Emission (CH0, 1GHz ~18GHz), LE 2M**




Fig.10 Radiated Spurious Emission (CH19, 1GHz ~18GHz), LE 2M




Fig.11 Radiated Spurious Emission (CH39, 1GHz ~18GHz), LE 2M





Fig.12 Radiated Band Edges (CH0, 2.38GHz~2.45GHz), LE 2M**Fig.13 Radiated Band Edges (CH39, 2.45GHz~2.50GHz), LE 2M**




Fig.14 Radiated Spurious Emission (All Channels, 9kHz-30MHz), LE 2M




Fig.15 Radiated Spurious Emission (All Channels, 30MHz-1GHz), LE 2M




Fig.16 Radiated Spurious Emission (All Channels, 18GHz-26.5 GHz), LE 2M

A.2 AC Power line Conducted Emission

Method of Measurement: See ANSI C63.10-clause 6.2.

Test Condition:

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:

BLE-AE2, AE3

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Average-peak Limit (dB μ V)	Result (dB μ V)		Conclusion
			Traffic	Idle	
0.15 to 0.5	66 to 56	56 to 46	Fig.17	Fig.18	P
0.5 to 5	56	46			
5 to 30	60	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Note: The measurement results include the L1 and N measurements.

See below for test graphs.

Conclusion: Pass




Fig.17 AC Power line Conducted Emission (Traffic)

Measurement Results: Quasi Peak

Frequency (MHz)	Quasi Peak (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.430000	41.29	57.25	15.96	N	ON	10
0.550000	52.88	56.00	3.12	N	ON	10
0.742000	39.53	56.00	16.47	N	ON	10
1.382000	33.36	56.00	22.64	N	ON	10
3.230000	36.07	56.00	19.93	N	ON	10
5.338000	56.07	60.00	3.93	N	ON	10

Measurement Results: Average

Frequency (MHz)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.430000	34.09	47.25	13.16	N	ON	10
0.554000	42.39	46.00	3.61	N	ON	10
0.738000	33.35	46.00	12.65	N	ON	10
1.882000	26.14	46.00	19.86	N	ON	10
2.414000	26.82	46.00	19.18	N	ON	10
5.338000	42.88	50.00	7.12	N	ON	10




Fig.18 AC Power line Conducted Emission (Idle)

Measurement Results: Quasi Peak

Frequency (MHz)	Quasi Peak (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.426000	37.91	57.33	19.42	N	ON	10
0.546000	52.56	56.00	3.44	N	ON	10
1.034000	45.20	56.00	10.80	N	ON	10
1.390000	35.44	56.00	20.56	N	ON	10
3.046000	41.13	56.00	14.87	N	ON	10
5.450000	50.27	60.00	9.73	N	ON	11

Measurement Results: Average

Frequency (MHz)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.430000	32.97	47.25	14.28	N	ON	10
0.546000	42.87	46.00	3.13	N	ON	10
1.034000	33.62	46.00	12.38	N	ON	10
1.462000	32.50	46.00	13.50	N	ON	10
2.238000	24.83	46.00	21.17	N	ON	11
5.390000	44.13	50.00	5.87	N	ON	11

END OF REPORT