N66 Head

Date: 11/9/2024

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used (interpolated): f = 1777.5 MHz; σ = 1.358 S/m; ε_r = 42.022; ρ = 1000 kg/m^3

Ambient Temperature:23.3°C Liquid Temperature: 22.5°C

Communication System: UID 0, 5G N66 (0) Frequency: 1777.5 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN7673 ConvF(8.45, 8.45, 8.45);

Area Scan (81x141x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.01 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.04 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 1.21 W/kg
SAR(1 g) = 0.635 W/kg; SAR(10 g) = 0.352 W/kg
Maximum value of SAR (measured) = 0.971 W/kg



N66 Body

Date: 11/9/2024

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used (interpolated): f = 1777.5 MHz; σ = 1.358 S/m; ε_r = 42.022; ρ = 1000 kg/m^3

Ambient Temperature:23.3°C Liquid Temperature: 22.5°C

Communication System: UID 0, 5G N66 (0) Frequency: 1777.5 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN7673 ConvF(8.45, 8.45, 8.45);

Area Scan (81x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.427 W/kg

Zoom Scan (7x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.79 V/m; Power Drift = 0.10 dB
Peak SAR (extrapolated) = 0.747 W/kg
SAR(1 g) = 0.389 W/kg; SAR(10 g) = 0.219 W/kg
Maximum value of SAR (measured) = 0.599 W/kg



N77H PC2 Head

Date: 11/19/2024

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used (interpolated): f = 3822 MHz; σ = 3.178 S/m; ε_r = 37.959; ρ = 1000 kg/m^3

Ambient Temperature:23.3°C Liquid Temperature: 22.5°C

Communication System: UID 0, 5g n77 (0) Frequency: 3822 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN7673 ConvF(6.44, 6.44, 6.44);

Area Scan (121x211x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.18 W/kg

Zoom Scan (8x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 8.633 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 1.53 W/kg
SAR(1 g) = 0.545 W/kg; SAR(10 g) = 0.213 W/kg
Maximum value of SAR (measured) = 1.04 W/kg



N77L PC2 Body

Date: 11/17/2024

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 3540 MHz; σ = 2.896 S/m; ε_r = 38.49; ρ = 1000 kg/m^3

Ambient Temperature:23.3°C Liquid Temperature: 22.5°C

Communication System: UID 0, 5g n77 (0) Frequency: 3540 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN7673 ConvF(6.73, 6.73, 6.73);

Area Scan (81x201x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.86 W/kg

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 4.773 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 2.40 W/kg
SAR(1 g) = 0.938 W/kg; SAR(10 g) = 0.360 W/kg
Maximum value of SAR (measured) = 1.76 W/kg



WLAN2.4G Head

Date: 10/29/2024

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used (interpolated): f = 2412 MHz; σ = 1.822 S/m; ε_r = 40.898; ρ = 1000 kg/m^3

Ambient Temperature:23.3°C Liquid Temperature: 22.5°C

Communication System: UID 0, WLan 2450 (0) Frequency: 2412 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN7673 ConvF(7.6, 7.6, 7.6);

Area Scan (101x171x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 1.36 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 10.89 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 1.65 W/kg
SAR(1 g) = 0.747 W/kg; SAR(10 g) = 0.361 W/kg
Maximum value of SAR (measured) = 1.24 W/kg



WLAN2.4G Body

Date: 10/29/2024

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used (interpolated): f = 2412 MHz; σ = 1.822 S/m; ε_r = 40.898; ρ = 1000 kg/m^3

Ambient Temperature:23.3°C Liquid Temperature: 22.5°C

Communication System: UID 0, WLan 2450 (0) Frequency: 2412 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN7673 ConvF(7.6, 7.6, 7.6);

Area Scan (101x101x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.624 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 15.44 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 0.773 W/kg
SAR(1 g) = 0.407 W/kg; SAR(10 g) = 0.211 W/kg
Maximum value of SAR (measured) = 0.635 W/kg





WLAN5G Head

Date: 11/2/2024

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 5745 MHz; σ = 5.241 S/m; ε_r = 34.298; ρ = 1000 kg/m^3

Ambient Temperature:23.3°C Liquid Temperature: 22.5°C

Communication System: UID 0, WLan 11a (0) Frequency: 5745 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN7673 ConvF(4.71, 4.71, 4.71);

Area Scan (121x211x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 2.06 W/kg

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 3.423 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 3.92 W/kg
SAR(1 g) = 0.818 W/kg; SAR(10 g) = 0.271 W/kg
Maximum value of SAR (measured) = 2.14 W/kg



WLAN5G Body

Date: 11/2/2024

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 5745 MHz; σ = 5.241 S/m; ε_r = 34.298; ρ = 1000 kg/m^3

Ambient Temperature:23.3°C Liquid Temperature: 22.5°C

Communication System: UID 0, WLan 11a (0) Frequency: 5745 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN7673 ConvF(4.71, 4.71, 4.71);

Area Scan (121x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 2.27 W/kg

Zoom Scan (8x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 9.503 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 3.71 W/kg
SAR(1 g) = 0.903 W/kg; SAR(10 g) = 0.337 W/kg
Maximum value of SAR (measured) = 2.15 W/kg



BT Body

Date: 10/29/2024

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 2480 MHz; σ = 1.873 S/m; ε_r = 40.751; ρ = 1000 kg/m^3

Ambient Temperature:23.3°C Liquid Temperature: 22.5°C

Communication System: UID 0, Bluetooth (0) Frequency: 2480 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN7673 ConvF(7.6, 7.6, 7.6);

Area Scan (101x101x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.0148 W/kg

Zoom Scan (8x10x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.247 V/m; Power Drift = 0.19 dB
Peak SAR (extrapolated) = 0.0240 W/kg
SAR(1 g) = 0.014 W/kg; SAR(10 g) = 0.00743 W/kg
Maximum value of SAR (measured) = 0.0203 W/kg





ANNEX B System Verification Results

750 MHz

Date: 2024/10/25
Electronics: DAE4 Sn1331
Medium: H700-6000M
Medium parameters used: f = 750 MHz; σ =0.864 mho/m; εr =44.49; ρ = 1000 kg/m3
Ambient Temperature: 22.5oC Liquid Temperature: 22.3oC
Communication System: CW Frequency: 750 MHz Duty Cycle: 1:1
Probe: EX3DV4 – SN7673 ConvF(10.45, 10.45, 10.45)

System Validation /Area Scan (81x191x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 2.81 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value =58.91 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 3.28 W/kg
SAR(1 g) = 2.09 W/kg; SAR(10 g) = 1.37 W/kg
Maximum value of SAR (measured) = 2.87 W/kg



0 dB = 2.87 W/kg = 4.58 dB W/kg

835 MHz

Date: 2024/10/29

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 835 MHz; σ =0.8558 mho/m; εr = 44.22; ρ = 1000 kg/m3

Ambient Temperature: 22.5oC Liquid Temperature: 22.3oC

Communication System: CW Frequency: 835 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(10.45, 10.45, 10.45)

System Validation /Area Scan (81x191x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 3.41 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value =57.88 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 3.72 W/kg

SAR(1 g) = 2.41 W/kg; SAR(10 g) = 1.54 W/kg

Maximum value of SAR (measured) = 3.34 W/kg



0 dB = 3.34 W/kg = 5.24 dB W/kg

1750 MHz

Date: 2024/11/9

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 1750 MHz; σ =1.342 mho/m; εr = 42.03; ρ = 1000 kg/m3

Ambient Temperature: 22.5oC Liquid Temperature: 22.3oC

Communication System: CW Frequency: 1750 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(8.45,8.45,8.45)

System Validation /Area Scan (81x191x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 13.17 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value =99.87 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 15.2 W/kg

SAR(1 g) = 9.58 W/kg; SAR(10 g) = 4.98 W/kg

Maximum value of SAR (measured) = 13.46 W/kg



0 dB = 13.46 W/kg = 11.29 dB W/kg

1900 MHz

Date: 2024/11/12

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 1900 MHz; σ =1.439mho/m; εr =41.79; ρ = 1000 kg/m3

Ambient Temperature: 22.5oC Liquid Temperature: 22.3oC

Communication System: CW Frequency: 1900 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(8.10,8.10,8.10)

System Validation /Area Scan (81x191x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 15.1 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value =81.35 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 18.8 W/kg

SAR(1 g) = 9.89 W/kg; SAR(10 g) = 5.16 W/kg

Maximum value of SAR (measured) = 15.5 W/kg



0 dB = 15.5 W/kg = 11.90 dBW/kg

2300MHz

Date: 2024/11/14

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 2300 MHz; σ = 1.731 S/m; εr = 41.11; ρ = 1000 kg/m3

Ambient Temperature:23.3oC Liquid Temperature: 22.5oC

Communication System: CW (0) Frequency: 2300 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(7.85, 7.85, 7.85)

Area Scan (61x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 19.2 W/kg

Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 101.5 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 23.4 W/kg

SAR(1 g) = 11.8 W/kg; SAR(10 g) = 5.78 W/kg

Maximum value of SAR (measured) = 20.2 W/kg



0 dB = 20.2 W/kg = 13.05 dBW/kg

2450 MHz

Date: 2024/10/29

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 2450 MHz; σ =1.854mho/m; εr = 40.79; ρ = 1000 kg/m3

Ambient Temperature: 22.5oC Liquid Temperature: 22.3oC

Communication System: CW Frequency: 2450 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(7.60, 7.60, 7.60)

System Validation /Area Scan (81x191x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 21.5 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value =103.8 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 27.5 W/kg

SAR(1 g) = 13.4 W/kg; SAR(10 g) = 6.35 W/kg

Maximum value of SAR (measured) = 22.3 W/kg



0 dB = 22.3 W/kg = 13.48 dBW/kg

2600 MHz

Date: 2024/11/15

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 2600 MHz; σ =2.058 mho/m; εr = 40.57; ρ = 1000 kg/m3

Ambient Temperature: 22.5oC Liquid Temperature: 22.3oC

Communication System: CW Frequency: 2600 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(7.44, 7.44, 7.44)

System Validation /Area Scan (61x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 24.6 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value =110.8 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 30.1 W/kg

SAR(1 g) = 14.1 W/kg; SAR(10 g) = 6.42 W/kg

Maximum value of SAR (measured) = 23.6 W/kg



0 dB = 23.6 W/kg = 13.73 dBW/kg

2600 MHz

Date: 2024/11/30

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 2600 MHz; σ =2.047 mho/m; εr = 40.44; ρ = 1000 kg/m3

Ambient Temperature: 22.5oC Liquid Temperature: 22.3oC

Communication System: CW Frequency: 2600 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(7.44, 7.44, 7.44)

System Validation /Area Scan (61x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 23.1 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value =102.9 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 28.6 W/kg

SAR(1 g) = 14.0 W/kg; SAR(10 g) = 6.35 W/kg

Maximum value of SAR (measured) = 23.5 W/kg



0 dB = 23.5 W/kg = 13.71 dBW/kg

3500MHz

Date: 2024/11/17

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 3500 MHz; σ = 2.869 S/m; εr = 38.54; ρ = 1000 kg/m3

Ambient Temperature:23.3oC Liquid Temperature: 22.5oC

Communication System: CW (0) Frequency: 3500 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(6.73, 6.73, 6.73)

Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 12.5 W/kg

Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x8)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 67.78 V/m; Power Drift = 0.1 dB

Peak SAR (extrapolated) = 16.7 W/kg

SAR(1 g) = 6.52 W/kg; SAR(10 g) = 2.51 W/kg

Maximum value of SAR (measured) = 12.8 W/kg



0 dB = 12.8 W/kg = 11.07 dBW/kg

3700MHz

Date: 2024/11/18

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 3700 MHz; σ = 3.048 S/m; εr = 38.21; ρ = 1000 kg/m3

Ambient Temperature:23.3oC Liquid Temperature: 22.5oC

Communication System: CW (0) Frequency: 3700 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(6.48, 6.48, 6.48)

Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 12.8 W/kg

Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x8)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 51.52 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 17.2 W/kg

SAR(1 g) = 6.61 W/kg; SAR(10 g) = 2.49 W/kg

Maximum value of SAR (measured) = 13.1 W/kg



0 dB = 13.1 W/kg = 11.17 dBW/kg

3700MHz

Date: 2024/12/2

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 3700 MHz; σ = 3.037 S/m; εr = 38.12; ρ = 1000 kg/m3

Ambient Temperature:23.3oC Liquid Temperature: 22.5oC

Communication System: CW (0) Frequency: 3700 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(6.48, 6.48, 6.48)

Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 12.9 W/kg

Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x8)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 66.01 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 17.6 W/kg

SAR(1 g) = 6.94 W/kg; SAR(10 g) = 2.56 W/kg

Maximum value of SAR (measured) = 12.6 W/kg



0 dB = 12.6 W/kg = 11.00 dBW/kg

3900MHz

Date: 2024/11/19

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 3900 MHz; σ = 3.256 S/m; εr = 37.91; ρ = 1000 kg/m3

Ambient Temperature:23.3oC Liquid Temperature: 22.5oC

Communication System: CW (0) Frequency: 3900 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(6.44, 6.44, 6.44)

Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 14.2 W/kg

Zoom Scan (8x8x7)/Cube 0: : Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 56.85 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 18.1 W/kg

SAR(1 g) = 6.65 W/kg; SAR(10 g) = 2.47 W/kg

Maximum value of SAR (measured) = 14.3 W/kg



0 dB = 14.3 W/kg = 11.55 dBW/kg

5250 MHz

Date: 2024/11/1

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 5250 MHz; σ =4.705 S/m; εr = 35.23; ρ = 1000 kg/m3

Ambient Temperature: 22.5oC Liquid Temperature: 22.3oC

Communication System: CW Frequency: 5250 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(5.18, 5.18, 5.18)

Area Scan (51x51x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 18.5 W/kg

Zoom Scan (7x7x6)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value =66.57 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 31.8 W/kg

SAR(1 g) = 7.69 W/kg; SAR(10 g) = 2.28 W/kg

Maximum value of SAR (measured) = 18.7 W/kg



0 dB = 18.7 W/kg = 12.72dBW/kg

5600 MHz

Date: 2024/11/2

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 5600 MHz; σ =5.095 S/m; εr = 34.53; ρ = 1000 kg/m3

Ambient Temperature: 22.5oC Liquid Temperature: 22.3oC

Communication System: CW Frequency: 5600 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(4.60, 4.60, 4.60)

System Validation /Area Scan (81x191x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 19.4 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value =67.78 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 35.1 W/kg

SAR(1 g) = 7.95 W/kg; SAR(10 g) = 2.35 W/kg

Maximum value of SAR (measured) = 19.5 W/kg



0 dB = 19.5 W/kg = 12.90 dBW/kg

5750 MHz

Date: 2024/11/2

Electronics: DAE4 Sn1331

Medium: H700-6000M

Medium parameters used: f = 5750 MHz; σ =5.25 S/m; εr = 34.28; ρ = 1000 kg/m3

Ambient Temperature: 22.5oC Liquid Temperature: 22.3oC

Communication System: CW Frequency: 5750 MHz Duty Cycle: 1:1

Probe: EX3DV4 –SN7673 ConvF(4.71, 4.71, 4.71)

System Validation /Area Scan (81x191x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 19.1 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value =66.86 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 34.1 W/kg

SAR(1 g) = 7.97 W/kg; SAR(10 g) = 2.31 W/kg

Maximum value of SAR (measured) = 19.7 W/kg



0 dB = 19.7 W/kg = 12.94 dBW/kg

13 MHz

Date: 2024-11-14

Electronics: DAE4 Sn1524

Medium: 13M

Medium parameters used: f = 13 MHz; σ = 0.73 S/m; εr = 53.4; ρ = 1000 kg/m3

Ambient Temperature:23.3°C Liquid Temperature: 22.5°C

Communication System: UID 0, CW (0) Frequency: 13 MHz Duty Cycle: 1:1

Probe: EX3DV4 - SN7464 ConvF(17.62, 17.62, 17.62)

Area Scan (101x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.141 W/kg

Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 3.338 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.202 W/kg

SAR(1 g) = 0.331 W/kg; SAR(10 g) = 0.546 W/kg

Maximum value of SAR (measured) = 0.137 W/kg



0 dB = 0.137 W/kg = -8.63 dBW/kg

ANNEX C SAR Measurement Setup

C.1 Measurement Set-up

The Dasy5 or DASY6 system for performing compliance tests is illustrated above graphically. This system consists of the following items:



Picture C.1SAR Lab Test Measurement Set-up

- A standard high precision 6-axis robot (StäubliTX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY5 or DASY6 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as
- warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

C.2 Dasy5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY5 or DASY6 software reads the reflection durning a software approach and looks for the maximum using 2nd ord curve fitting. The approach is stopped at reaching the maximum.

Probe Specifications:

Model: ES3DV3, EX3DV4
Frequency 10MHz — 6.0GHz(EX3DV4)
Range: 10MHz — 4GHz(ES3DV3)
Calibration: In head and body simulating tissue at Frequencies from 835 up to 5800MHz
Linearity: ± 0.2 dB(30 MHz to 6 GHz) for EX3DV4
± 0.2 dB(30 MHz to 4 GHz) for ES3DV3
DynamicRange: 10 mW/kg — 100W/kg
Probe Length: 330 mm
Probe Tip
Length: 20 mm
Body Diameter: 12 mm
Tip Diameter: 2.5 mm (3.9 mm for ES3DV3)
Tip-Center: 1 mm (2.0mm for ES3DV3)
Application: SAR Dosimetry Testing
Compliance tests ofmobile phones
Dosimetry in strong gradient fields

Picture C.2Near-field Probe

Picture C.3E-field Probe

C.3 E-field Probe Calibration

Each E-Probe/Probe Amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm^2) using an RF Signal generator, TEM cell, and RF Power Meter.

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and inn a waveguide or

other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm^2.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C\frac{\Delta T}{\Delta t}$$

Where:

Δt = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

ΔT = Temperature increase due to RF exposure.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

σ = Simulated tissue conductivity,

ρ = Tissue density (kg/m^3).

C.4 Other Test Equipment

C.4.1 Data Acquisition Electronics(DAE)

The data acquisition electronics consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

PictureC.4: DAE

C.4.2 Robot

The SPEAG DASY system uses the high precision robots (DASY5: RX160L) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchron motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

Picture C.5 DASY 5

C.4.3 Measurement Server

The Measurement server is based on a PC/104 CPU broad with CPU (DASY5: 400 MHz, Intel Celeron), chipdisk (DASY5: 128MB), RAM DASY5: 128MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O broad, which is directly connected to the PC/104 bus of the CPU broad.

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.

Picture C.6 Server for DASY 5

C.4.4 Device Holder for Phantom

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5mm distance, a positioning uncertainty of ±0.5mm would produce a SAR uncertainty of ±20%. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.
The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.
The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity ε=3 and loss tangent δ=0.02. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.
<Laptop Extension Kit>
The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin-SAM and ELI phantoms.

Picture C7-1: Device Holder



Picture C.7-2: Laptop Extension Kit

C.4.5 Phantom

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a table. The shape of the shell is based on data from an anatomical study designed to
Represent the 90th percentile of the population. The phantom enables the dissymmetric evaluation of SAR for both left and right handed handset usage, as well as body-worn usage using the flat phantom region. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. The shell phantom has a 2mm shell thickness (except the ear region where shell thickness increases to 6 mm).

Shell Thickness:	2±0. 2 mm
Filling Volume:	Approx. 25 liters
Dimensions:	810 x l000 x 500 mm (H x L x W)
Available:	Special

Picture C.8: SAM Twin Phantom

ANNEX D Position of the wireless device in relation to the phantom

D.1 General considerations

This standard specifies two handset test positions against the head phantom – the “cheek” position and the “tilt” position.





W_t	Width of the handset at the level of the acoustic
W_b	Width of the bottom of the handset
A	Midpoint of the width W_t of the handset at the level of the acoustic output
B	Midpoint of the width W_b of the bottom of the handset

Picture D.1-a Typical “fixed” case handset **Picture D.1-b Typical “clam-shell” case handset**



Picture D.2 Cheek position of the wireless device on the left side of SAM