



FCC PART 15C TEST REPORT No.25T04Z100239-030

for

TCL Communication Ltd.

GSM/UMTS/LTE/NR Mobile phone

T513V

FCC ID:2ACCJH187

with

Hardware Version: 04

Software Version: 9ABJ

Issued Date: 2025-04-16

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn

REPORT HISTORY

Report Number	Revision	Description	Issue Date
25T04Z100239-030	Rev.0	1st edition	2025-04-16

Note: the latest revision of the test report supersedes all previous version.

CONTENTS

1. TEST LABORATORY	5
1.1. INTRODUCTION & ACCREDITATION	5
1.2. TESTING LOCATION	5
1.3. TESTING ENVIRONMENT	6
1.4. PROJECT DATE	6
1.5. SIGNATURE	6
2. CLIENT INFORMATION	7
2.1. APPLICANT INFORMATION	7
2.2. MANUFACTURER INFORMATION	7
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	8
3.1. ABOUT EUT	8
3.2. INTERNAL IDENTIFICATION OF EUT	8
3.3. INTERNAL IDENTIFICATION OF AE	8
3.4. GENERAL DESCRIPTION	9
3.5. INTERPRETATION OF THE TEST ENVIRONMENT	9
4. REFERENCE DOCUMENTS	9
4.1. DOCUMENTS SUPPLIED BY APPLICANT	9
4.2. REFERENCE DOCUMENTS FOR TESTING	9
5. LABORATORY ENVIRONMENT	10
6. TEST RESULTS	10
6.1. SUMMARY OF TEST RESULTS	10
6.2. STATEMENTS	10
6.3. TEST CONDITIONS	10
7. TEST FACILITIES UTILIZED	11
8. MEASUREMENT UNCERTAINTY	12
8.1. MAXIMUM OUTPUT POWER	12
8.2. PEAK POWER SPECTRAL DENSITY	12
8.3. DTS 6-DB SIGNAL BANDWIDTH	12
8.4. BAND EDGES COMPLIANCE	12
8.5. TRANSMITTER SPURIOUS EMISSION	12
8.6. RADIATED UNWANTED EMISSION	12
8.7. AC POWER-LINE CONDUCTED EMISSION	12
ANNEX A: DETAILED TEST RESULTS	13
A.1. MEASUREMENT METHOD	13
A.2. MAXIMUM OUTPUT POWER	14

A.2.1 ANTENNA GAIN	14
A.2.2. PEAK OUTPUT POWER-CONDUCTED	14
A.3. PEAK POWER SPECTRAL DENSITY	16
A.4. DTS 6-DB SIGNAL BANDWIDTH	23
A.5. BAND EDGES COMPLIANCE	30
A.6. TRANSMITTER SPURIOUS EMISSION	35
A.6.1 TRANSMITTER SPURIOUS EMISSION – CONDUCTED	35
A.7. RADIATED UNWANTED EMISSION	55
A.8. AC POWER-LINE CONDUCTED EMISSION	71
A.9. ANTENNA REQUIREMENT	74
ANNEX B: EUT PARAMETERS	74
ANNEX C: ACCREDITATION CERTIFICATE	74

1. Test Laboratory

1.1.Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under American Association for Laboratory Accreditation (A2LA) with lab code 7049.01, and is also an FCC accredited test laboratory (CN1349), and ISED accredited test laboratory (CAB identifier:CN0066). The detail accreditation scope can be found on A2LA website.

1.2.Testing Location

Location 1:CTTL(Gaolizhang Road)

Address: Cuihu Cloud Center, No.1, Gaolizhang Road, Wenquan,
Haidian District, Beijing, China

Location 2:CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
100191, P. R. China

1.3. Testing Environment


Normal Temperature: 15-35°C

Relative Humidity: 20-75%

1.4. Project date


Testing Start Date: 2025-02-14

Testing End Date: 2025-03-27

1.5. Signature

Xie Xiuzhen

(Prepared this test report)



Zheng Wei

(Reviewed this test report)



Pang Shuai

(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address/Post: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Contact Person: Ting Wang
Contact Email: ting.wang.hz@tcl.com
Telephone: +86 752 2639091
Fax: 0086-755-36612000-81722

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address/Post: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Contact Person: Ting Wang
Contact Email: ting.wang.hz@tcl.com
Telephone: +86 752 2639091
Fax: 0086-755-36612000-81722

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	GSM/UMTS/LTE/NR Mobile phone
Model name	T513V
FCC ID	2ACCJH187
With WLAN Function	Yes
Frequency Band	ISM 2400MHz~2483.5MHz
Type of Modulation	DSSS/CCK/OFDM
Number of Channels	11
Antenna	Integral Antenna
MAX Conducted Power	24.98dBm
Normal Voltage	3.87V
Extreme High Voltage	4.45V
Extreme Low Voltage	3.6V

3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
UT13a	016644000212016/	04	9CS4	2025-02-17
(Initial model)	016644000212024			
UT53a	016644000213576/	04	9CS4	2025-03-10
(Initial model)	016644000213584			

*EUT ID: is used to identify the test sample in the lab internally.

UT13a is used for Conduction test, UT53a is used for Radiation test.

3.3. Internal Identification of AE

AE ID*	Description	Model	Manufacturer
AE1	Cable	CDA0000218C1	JUWEI
AE2	Charger(Provided by the lab.)	/	/

*AE ID: is used to identify the test sample in the lab internally. The information of manufacturer was provided by the client.

3.4. General Description

The Equipment under Test (EUT) is a model of GSM/UMTS/LTE/NR Mobile phone with integrated antenna and inbuilt battery.

It consists of normal options: travel charger, USB cable.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

3.5. Interpretation of the Test Environment

For the test methods, the test environment uncertainty figures correspond to an expansion factor $k=2$.

Measurement Uncertainty

Parameter	Uncertainty
temperature	0.48°C
humidity	2 %
DC voltages	0.003V

4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15, Subpart C:	2021
	15.205 Restricted bands of operation;	
	15.207 Conducted limits;	
	15.209 Radiated emission limits, general requirements;	
ANSI C63.10	15.247 Operation within the bands 902-928MHz, 2400-2483.5 MHz, and 5725-5850 MHz.	2013
	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	
	Federal Communications Commission Office of Engineering and Technology Laboratory Division	
KDB 558074 D01	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES	2019

Note: KDB 558074 D01 is not in the scope of ISO/IEC 17025 accreditation by A2LA.

5. LABORATORY ENVIRONMENT

Conducted RF performance testing is performed in shielding room.

EMC performance testing is performed in Semi-anechoic chamber.

6. Test Results

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15C	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.247 (b)	/	BR
Peak Power Spectral Density	15.247 (e)	/	BR
DTS 6-dB Signal Bandwidth	15.247 (a)	/	BR
Band Edges Compliance	15.247 (d)	/	BR
Transmitter Spurious Emission - Conducted	15.247 (d)	/	BR
Radiated Unwanted Emission	15.247, 15.205, 15.209	/	BR
AC Powerline Conducted Emission	15.207	/	BR

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NP	Not Perform, The test was not performed by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard
BR	Re-use test data from basic model report.

6.2. Statements

CTTL has evaluated the test cases as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.

This report only deals with the WLAN function among the features described in section 3.

The Equipment Under Test (EUT) model T513V (FCC ID: 2ACCJH187) is a variant product of T513SP(FCC ID: 2ACCJH187), according to the declaration of changes provided by the applicant, all results are derived from test report 25T04Z100239-005.

For detail differences between two models please refer the Declaration of Changes document.

6.3. Test Conditions

For this report, all the test cases are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	26°C
Voltage	3.87V
Humidity	44%

7. Test Facilities Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	1 year	2025-08-11
2	Vector Signal Analyzer	FSW67	104051	Rohde & Schwarz	1 year	2025-04-30
3	LISN	ENV216	101200	Rohde & Schwarz	1 year	2025-05-16
4	Test Receiver	ESCI	100344	Rohde & Schwarz	1 year	2025-04-01
5	Attenuator	10dB/2W	/	Rosenberger	/	/
6	Shielding Room	S81	/	ETS-Lindgren	/	/
7	Data Acquisition Unit	U2531A	TW54433522	Agilent	/	/
8	Power Sensor	U2021XA	MY54460006	Agilent	1 year	2025-06-15

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESW44	103023	R&S	1 year	2025-06-06
2	EMI Antenna	VULB 9163	01222	SCHWARZBECK	1 year	2025-09-11
3	EMI Antenna	3115	0016725	ETS-Lindgren	1 year	2025-04-11

8. Measurement Uncertainty

8.1. Maximum Output Power

Measurement Uncertainty: 0.387dB,k=1.96

8.2. Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

8.3. DTS 6-dB Signal Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

8.4. Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

8.5. Transmitter Spurious Emission

Conducted (k=1.96)

Frequency Range	Uncertainty(dB)
$30\text{MHz} \leq f \leq 2\text{GHz}$	1.22
$2\text{GHz} \leq f \leq 3.6\text{GHz}$	1.22
$3.6\text{GHz} \leq f \leq 8\text{GHz}$	1.22
$8\text{GHz} \leq f \leq 12.75\text{GHz}$	1.51
$12.75\text{GHz} \leq f \leq 26\text{GHz}$	1.51
$26\text{GHz} \leq f \leq 40\text{GHz}$	1.59

8.6. Radiated Unwanted Emission

Frequency Range	Uncertainty(dB) k=2
9kHz-30MHz	/
$30\text{MHz} \leq f \leq 1\text{GHz}$	4.72
$1\text{GHz} \leq f \leq 18\text{GHz}$	4.84
$18\text{GHz} \leq f \leq 40\text{GHz}$	5.12

8.7. AC Power-line Conducted Emission

Measurement Uncertainty : 3.08dB,k=2

ANNEX A: Detailed Test Results

A.1. Measurement Method

A.1.1. Conducted Measurements

Connect the EUT to the test system as Fig.A.1.1.1 shows.

Set the EUT to the required work mode.

Set the EUT to the required channel.

Set the Vector Signal Analyzer and start measurement.

Record the values. Vector Signal Analyzer




Fig.A.1.1.1: Test Setup Diagram for Conducted Measurements

A.1.2. Radiated Emission Measurements

The measurement is made according to ANSI C63.10

The radiated emission test is performed in semi-anechoic chamber. The EUT was placed on a non-conductive table with 80cm above the ground plane for measurement below 1GHz and 1.5m above the ground plane for measurement above 1GHz. The measurement antenna was placed at a distance of 3 meters from the EUT. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated from 0° to 360° and the measurement antenna is moved from 1m to 4m to get the maximization result. The maximization process was repeated with the EUT positioned in each of its three orthogonal orientations

A.2. Maximum Output Power

Method of Measurement: See ANSI C63.10-2013-clause 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

Measurement Limit:

Standard	Limit (dBm)
FCC CRF Part 15.247(b)	< 30

A.2.1 Antenna Gain

Antenna gain is -4.55dBi and the value is supplied by the applicant or manufacturer.

A.2.2. Peak Output Power-conducted

EUT ID: UT13a

Measurement Results:

802.11b/g mode

Mode	Data Rate (Mbps)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11b	1	19.96	19.53	19.93
802.11g	6	24.82	24.78	24.25

The data rate 1Mbps and 6Mbps are selected as worst condition, and the following cases are performed with this condition.

802.11n-HT20 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11n (20MHz)	MCS0	24.98	24.79	24.34

The data rate MCS0 is selected as worst condition, and the following cases are performed with this condition.

802.11n-HT40 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		2422MHz (Ch3)	2437MHz (Ch6)	2452 MHz (Ch9)
802.11n (40MHz)	MCS0	23.97	23.92	23.98

The data rate MCS0 is selected as worst condition, and the following cases are performed with this condition.

The duty cycle of all mode

TestMode	Frequency[MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	2412	8.39	8.42	99.64
	2437	8.38	8.41	99.64
	2462	8.38	8.41	99.64
11G	2412	1.39	1.43	97.20
	2437	1.40	1.43	97.90
	2462	1.40	1.43	97.90
11N20SISO	2412	1.30	1.34	97.01
	2437	1.30	1.34	97.01
	2462	1.30	1.34	97.01
11N40SISO	2422	0.64	0.67	95.52
	2437	0.64	0.67	95.52
	2452	0.64	0.67	95.52



Duty cycle

Conclusion: Pass

A.3. Peak Power Spectral Density

Method of Measurement: See ANSI C63.10-2013-clause 11.10.2

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to RBW = 3 kHz.
- d) Set the VBW = 10 kHz.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.

Measurement Limit:

Standard	Limit
FCC CRF Part 15.247(e)	< 8 dBm/3 kHz


EUT ID: UT13a

Measurement Results:

TestMode	Frequency[MHz]	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11B	2412	-4.36	≤8.00	PASS
	2437	-4.39	≤8.00	PASS
	2462	-4.68	≤8.00	PASS
11G	2412	-7.24	≤8.00	PASS
	2437	-7.56	≤8.00	PASS
	2462	-7.11	≤8.00	PASS
11N20SISO	2412	-7.52	≤8.00	PASS
	2437	-7.02	≤8.00	PASS
	2462	-7.22	≤8.00	PASS
11N40SISO	2422	-13.59	≤8.00	PASS
	2437	-13.73	≤8.00	PASS
	2452	-13.35	≤8.00	PASS


Test graphs as below:

11B_2412




13:48:03 21.03.2025

11B_2437




13:50:46 21.03.2025

11B_2462




13:53:13 21.03.2025

11G_2412




13:56:16 21.03.2025

11G_2437




14:01:19 21.03.2025

11G_2462




14:03:04 21.03.2025

11N20SISO_2412




14:05:05 21.03.2025

11N20SISO_2437




14:07:00 21.03.2025

11N20SISO_2462




14:08:49 21.03.2025

11N40SISO_2422




14:16:39 21.03.2025

11N40SISO_2437



14:13:00 21.03.2025

11N40SISO_2452



14:14:42 21.03.2025

Conclusion: Pass

A.4. DTS 6-dB Signal Bandwidth

Method of Measurement: See ANSI C63.10-2013 section 11.8.1.

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) = 300 kHz.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.247 (a)	≥ 500

EUT ID: UT13a

Measurement Result:

TestMode	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	2412	7.60	2408.44	2416.04	0.5	PASS
	2437	8.08	2432.96	2441.04	0.5	PASS
	2462	8.04	2457.96	2466.00	0.5	PASS
11G	2412	15.48	2404.44	2419.92	0.5	PASS
	2437	15.32	2429.44	2444.76	0.5	PASS
	2462	15.16	2454.40	2469.56	0.5	PASS
11N20SISO	2412	15.12	2404.44	2419.56	0.5	PASS
	2437	15.12	2429.44	2444.56	0.5	PASS
	2462	15.16	2454.40	2469.56	0.5	PASS
11N40SISO	2422	35.04	2404.48	2439.52	0.5	PASS
	2437	35.12	2419.40	2454.52	0.5	PASS
	2452	35.12	2434.40	2469.52	0.5	PASS

Test graphs as below:

11B_2412



13:47:42 21.03.2025

11B_2437




13:50:25 21.03.2025

11B_2462




13:52:52 21.03.2025

11G_2412




13:55:55 21.03.2025

11G_2437



14:00:58 21.03.2025

11G_2462




14:02:43 21.03.2025

11N20SISO_2412




14:04:44 21.03.2025

11N20SISO_2437



14:06:38 21.03.2025

11N20SISO_2462



14:08:28 21.03.2025

11N40SISO_2422




14:10:29 21.03.2025

11N40SISO_2437



14:12:39 21.03.2025

11N40SISO_2452



14:14:22 21.03.2025

Conclusion: Pass

A.5. Band Edges Compliance

Method of Measurement: See ANSI C63.10-2013-clause 6.10.4

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below.

- a) Set Span = 100MHz
- b) Sweep Time: coupled
- c) Set the RBW= 100 kHz
- c) Set the VBW= 300 kHz
- d) Detector: Peak
- e) Trace: Max hold

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	> 20

EUT ID: UT13a

Measurement Result:

TestMode	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Low	2412	8.78	-36.71	≤-11.22	PASS
	High	2462	8.88	-44.59	≤-11.12	PASS
11G	Low	2412	6.49	-26.88	≤-13.51	PASS
	High	2462	6.39	-34.68	≤-13.61	PASS
11N20SISO	Low	2412	6.55	-27.46	≤-13.45	PASS
	High	2462	6.60	-34.5	≤-13.4	PASS
11N40SISO	Low	2422	0.73	-35.69	≤-19.27	PASS
	High	2452	1.17	-37.59	≤-18.83	PASS


Test graphs as below:

11B_Low_2412



13:48:13 21.03.2025

11B_High_2462



13:53:23 21.03.2025

11G_Low_2412



13:56:26 21.03.2025

11G_High_2462



14:03:14 21.03.2025

11N20SiSO_Low_2412



14:05:15 21.03.2025

11N20SISO_High_2462



14:08:59 21.03.2025

11N40SISO_Low_2422



14:11:00 21.03.2025

11N40SISO_High_2452



14:14:52 21.03.2025

Conclusion: Pass

A.6. Transmitter Spurious Emission

A.6.1 Transmitter Spurious Emission – Conducted

Method of Measurement: See ANSI C63.10-2013-clause 11.11

Establish a reference level by using the following procedure:

- Set instrument center frequency to DTS channel center frequency
- Set the span to ≥ 1.5 times the DTS bandwidth
- Set the RBW= 100 kHz
- Set the VBW= 300 kHz
- Detector = Peak
- Sweep time = auto couple
- Trace mode = max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum PSD level

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

Establish an emission level by using the following procedure:

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW = 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

EUT ID: UT13a


Measurement Results:

TestMode	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	2412	Reference	9.11	9.11	---	PASS
		30~1000	9.11	-56.42	≤ -10.89	PASS
		1000~26500	9.11	-43.68	≤ -10.89	PASS
	2437	Reference	8.61	8.61	---	PASS
		30~1000	8.61	-56.28	≤ -11.39	PASS

		1000~26500	8.61	-43.68	≤-11.39	PASS
	2462	Reference	8.83	8.83	---	PASS
		30~1000	8.83	-56.76	≤-11.17	PASS
		1000~26500	8.83	-44.31	≤-11.17	PASS
11G	2412	Reference	6.92	6.92	---	PASS
		30~1000	6.92	-56.44	≤-13.08	PASS
		1000~26500	6.92	-43.89	≤-13.08	PASS
	2437	Reference	6.24	6.24	---	PASS
		30~1000	6.24	-56.41	≤-13.76	PASS
		1000~26500	6.24	-44.11	≤-13.76	PASS
	2462	Reference	6.42	6.42	---	PASS
		30~1000	6.42	-55.87	≤-13.58	PASS
		1000~26500	6.42	-43.65	≤-13.58	PASS
	11N20SISO	2412	Reference	6.96	6.96	---
30~1000			6.96	-57.05	≤-13.04	PASS
1000~26500			6.96	-43.54	≤-13.04	PASS
2437		Reference	6.25	6.25	---	PASS
		30~1000	6.25	-56.67	≤-13.75	PASS
		1000~26500	6.25	-44.04	≤-13.75	PASS
2462		Reference	6.61	6.61	---	PASS
		30~1000	6.61	-56.72	≤-13.39	PASS
		1000~26500	6.61	-43.48	≤-13.39	PASS
11N40SISO	2422	Reference	0.68	0.68	---	PASS
		30~1000	0.68	-56.33	≤-19.32	PASS
		1000~26500	0.68	-43.53	≤-19.32	PASS
	2437	Reference	0.67	0.67	---	PASS
		30~1000	0.67	-56.66	≤-19.33	PASS
		1000~26500	0.67	-44.14	≤-19.33	PASS
	2452	Reference	1.15	1.15	---	PASS
		30~1000	1.15	-56.67	≤-18.85	PASS
		1000~26500	1.15	-43.61	≤-18.85	PASS


Test graphs as below:

11B_2412_0~Reference




13:48:21 21.03.2025

11B_2412_30~1000




13:48:35 21.03.2025

11B_2412_1000~26500




13:49:11 21.03.2025

11B_2437_0~Reference




13:50:54 21.03.2025

11B_2437_30~1000




13:51:07 21.03.2025

11B_2437_1000~26500




13:51:43 21.03.2025

11B_2462_0~Reference



13:53:32 21.03.2025

11B_2462_30~1000



13:53:45 21.03.2025

11B_2462_1000~26500