



FCC RF Test Report

APPLICANT : TCL Communication Ltd
EQUIPMENT : GSM Quad-band / UMTS Quad-band / LTE 4 band mobile phone
BRAND NAME : ALCATEL ONETOUCH
MODEL NAME : 6045O
MARKETING NAME : ALCATEL ONETOUCH IDOL 3 (5.5)
FCC ID : 2ACCJN005
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was completed on Feb. 26, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification subjective to this standard	6
1.5 Modification of EUT	6
1.6 Accessories and Support Equipment	7
1.7 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	8
1.8 Spot Check for Maximum EIRP Power	8
1.9 Testing Location	9
1.10 Applicable Standards	9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
2.1 Test Mode.....	10
2.2 Connection Diagram of Test System	12
2.3 Support Unit used in test configuration	12
2.4 Measurement Results Explanation Example	13
3 TEST RESULT	14
3.1 Conducted Output Power Measurement.....	14
3.2 Peak-to-Average Ratio	16
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	26
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	30
3.5 Band Edge Measurement.....	54
3.6 Conducted Spurious Emission Measurement.....	69
3.7 Field Strength of Spurious Radiation Measurement	124
3.8 Frequency Stability Measurement.....	135
4 LIST OF MEASURING EQUIPMENT	141
5 UNCERTAINTY OF EVALUATION	142
APPENDIX A. SETUP PHOTOGRAPHS	
APPENDIX B. PRODUCT EQUALITY DECLARATION	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG511301-29A	Rev. 01	This is a variant product of 6045O. Added a new battery, and only the EIRP and the worst case of Radiated spurious emission from original test report (Sporton Report Number FG511301-21A) were verified for the difference and the original test data were remain representative.	Mar. 07, 2016
FG511301-29A	Rev. 02	Update page 8 and page 29 for typo error.	Mar. 15, 2016

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.4	§2.1049 §22.917(b) §24.238(b) §27.53(g)	Occupied Bandwidth	Reporting Only	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 29.58 dB at 7521.000 MHz
3.8	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22 Within Authorized Band	PASS	-
	§2.1055 §24.235 §27.54				

1 General Description

1.1 Applicant

TCL Communication Ltd

FLAT/RM 1910-12A BLOCK 3 19/F CHINA HONG KONG CITY 33 CANTON ROAD TSIMSHATSUI KL

1.2 Manufacturer

TCL Communication Ltd

FLAT/RM 1910-12A BLOCK 3 19/F CHINA HONG KONG CITY 33 CANTON ROAD TSIMSHATSUI KL

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	GSM Quad-band / UMTS Quad-band / LTE 4 band mobile phone
Brand Name	ALCATEL ONETOUCH
Model Name	6045O
Marketing Name	ALCATEL ONETOUCH IDOL 3 (5.5)
FCC ID	2ACCJN005
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ HSPA+(16QAM uplink is not supported)/LTE/NFC/ WLAN2.4GHz 802.11b/g/n HT20/ WLAN 5GHz 802.11a/n HT20/HT40/ Bluetooth v3.0+EDR/Bluetooth v4.1 LE
IMEI Code	Radiation: 014497000004012 ERP&EIRP: 014497000004145 Spot Check: Radiation: 014497000003857 EIRP: 014497000004269
HW Version	03
SW Version	5A18
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 32.14 dBm GSM1900 : 29.31 dBm WCDMA Band V : 22.66 dBm WCDMA Band IV : 22.06 dBm WCDMA Band II : 21.80 dBm
Antenna Type	PIFA Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+ : 16QAM uplink is not supported

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Accessories and Support Equipment

Specification of Accessory				
AC Adapter	Brand Name	ALCATEL ONETOUCH	Model Name	UC13US
	Power Rating	I/P: 100-240Vac, 500mA, O/P: 5Vdc, 2000mA		
	P/N	CBA0059AG0C1		
Original Battery	Brand Name	ALCATEL ONETOUCH	Model Name	TLp029A2-S
	Power Rating	3.8Vdc, 2910mAh		
	P/N	C2910002C2YHVOJE		
Added Battery	Brand Name	ALCATEL ONETOUCH	Model Name	TLp029AJ
	Power Rating	3.8Vdc, 2910mAh		
	P/N	C2910003CJY9411D		
USB Cable	Brand Name	ALCATEL ONETOUCH	Model Name	CDA0000043C2
	Signal Line Type	1.01m shielded without core		

1.7 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.6618	0.0359 ppm	248KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.1337	0.0418 ppm	246KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.0860	0.0395 ppm	4M16F9W
Part 24	GSM1900 GSM	GMSK	0.8615	0.0229 ppm	246KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.2623	0.0149 ppm	246KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.1861	0.0229 ppm	4M18F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK	0.2560	0.0225 ppm	4M18F9W

1.8 Spot Check for Maximum EIRP Power

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 24	GSM1900 GSM	8PSK	0.7974	-	-
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.1673	-	-
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK	0.2146	-	-



1.9 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC Registration No.
	TH01-KS	03CH02-KS	418269

1.10 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI / TIA / EIA-603-D-2010
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for WCDMA Band IV
3. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
GSM 1900	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link




Conducted Power Measurement Results:


Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	31.92	32.07	32.14	28.86	29.30	29.31
GPRS class 8	31.85	32.02	32.10	29.17	29.26	29.28
GPRS class 10	29.97	30.04	30.25	27.33	27.50	27.55
EGPRS class 8	25.75	25.76	25.80	25.37	25.54	25.58
EGPRS class 10	24.65	24.67	24.73	23.90	23.96	24.01

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
AMR 12.2Kbps	22.48	22.38	22.65	21.72	21.83	22.05	21.78	21.72	21.76
RMC 12.2Kbps	22.53	22.42	22.66	21.74	21.84	22.06	21.80	21.74	21.74
HSDPA Subtest-1	21.57	21.50	21.68	20.76	20.85	20.88	20.81	20.77	20.75
HSDPA Subtest-2	21.57	21.49	21.68	20.72	20.78	20.86	20.81	20.75	20.73
HSDPA Subtest-3	20.96	20.90	21.09	20.24	20.30	20.40	20.25	20.26	20.27
HSDPA Subtest-4	21.01	20.93	21.12	20.26	20.33	20.61	20.29	20.28	20.27
HSUPA Subtest-1	22.27	22.15	21.79	21.70	21.71	21.42	21.28	21.10	21.11
HSUPA Subtest-2	21.23	20.92	21.37	20.38	20.44	20.85	20.70	20.72	20.63
HSUPA Subtest-3	21.09	21.20	21.12	20.61	20.23	20.72	20.52	20.40	20.55
HSUPA Subtest-4	21.28	21.57	21.38	20.73	20.77	21.17	21.10	20.88	21.13
HSUPA Subtest-5	22.35	22.23	22.43	21.72	21.73	21.90	21.76	21.69	21.74

2.2 Connection Diagram of Test System



Spot Check for EGPRS1900/WCDMA Band II



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Earphone	Lenovo	SH100	N/A	N/A	N/A



2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 5.2 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5.2 + 10 = 15.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GSM)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	31.92	32.07	32.14	25.75	25.76	25.80	22.53	22.42	22.66

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	28.86	29.30	29.31	25.37	25.54	25.58	21.74	21.84	22.06

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	21.80	21.74	21.74

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. For GSM/EGPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector on spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector on spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator has synchronized with the spectrum analyzer.
4. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option on the spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.34	0.35	0.35	2.77	2.71	2.61	2.64	2.60	3.00


AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Peak-to-Average Ratio (dB)	3.12	3.16	3.20



3.2.6 Test Result (Plots) of Peak-to-Average Ratio


Band :	GSM 1900	Test Mode :	GSM Link (GMSK)
--------	----------	-------------	-----------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 19.MAR.2015 23:56:07


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 19.MAR.2015 23:57:11



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 19. MAR. 2015 23:57:56




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 20. MAR 2015 00:02:49


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 20. MAR 2015 00:02:09



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 20 MAR 2015 00:01:36




Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 1312 (1712.4 MHz)



Date: 16.MAR.2015 22:29:56


Peak-to-Average Ratio on Channel 1413 (1732.6 MHz)



Date: 16.MAR.2015 22:29:23



Peak-to-Average Ratio on Channel 1513 (1752.6 MHz)




Date: 16.MAR.2015 22:28:46




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Date: 16.MAR.2015 21:53:20


Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 16.MAR.2015 21:54:05



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 16.MAR.2015 21:54:49

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-D-2010, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
2. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
3. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by dipole antenna (substitution antenna) at the same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$.

	GSM/GPRS/EDGE	WCDMA/HSPA
SPAN	500kHz	10MHz
RBW	10kHz	100kHz
VBW	30kHz	300kHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100

3.3.4 Test Result of ERP

GSM850 (GSM) Radiated Power ERP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	824.2	25.52	0.3566	15.54	0.0358
Middle	836.4	27.47	0.5591	16.58	0.0455
Highest	848.8	28.21	0.6618	17.01	0.0503
Limit	ERP < 7W	Result		PASS	

GSM850 (EDGE class 8) Radiated Power ERP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	824.2	18.39	0.0690	8.25	0.0067
Middle	836.4	20.16	0.1038	9.18	0.0083
Highest	848.8	21.26	0.1337	9.94	0.0099
Limit	ERP < 7W	Result		PASS	

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	826.4	18.68	0.0737	8.40	0.0069
Middle	836.4	19.17	0.0826	8.08	0.0064
Highest	846.6	19.35	0.0860	7.89	0.0062
Limit	ERP < 7W	Result		PASS	

3.3.5 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1850.2	28.55	0.7154	28.83	0.7643
Middle	1880.0	29.04	0.8022	29.35	0.8615
Highest	1909.8	28.93	0.7811	29.18	0.8270
Limit	EIRP < 2W	Result		PASS	

GSM1900 (EDGE class 8) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1850.2	23.36	0.2168	23.94	0.2475
Middle	1880.0	23.97	0.2497	24.19	0.2623
Highest	1909.8	24.06	0.2545	23.98	0.2498
Limit	EIRP < 2W	Result		PASS	

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1852.4	22.38	0.1730	22.70	0.1861
Middle	1880.0	22.19	0.1657	22.57	0.1806
Highest	1907.6	22.13	0.1635	22.34	0.1714
Limit	EIRP < 2W	Result		PASS	

WCDMA Band IV(RMC 12.2Kbps) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1712.4	24.08	0.2560	23.76	0.2376
Middle	1732.6	24.01	0.2518	23.90	0.2454
Highest	1752.6	23.86	0.2432	23.99	0.2508
Limit	EIRP < 1W	Result		PASS	

3.3.6 Spot Check for Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1850.2	28.34	0.6816	28.88	0.7729
Middle	1880.0	28.61	0.7254	29.02	0.7974
Highest	1909.8	28.81	0.7611	28.64	0.7313
Limit	EIRP < 2W	Result		PASS	

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1852.4	21.83	0.1525	22.24	0.1673
Middle	1880.0	21.73	0.1490	22.01	0.1587
Highest	1907.6	21.78	0.1505	22.03	0.1596
Limit	EIRP < 2W	Result		PASS	

WCDMA Band IV(RMC 12.2Kbps) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1712.4	23.30	0.2137	23.03	0.2009
Middle	1732.6	23.32	0.2146	23.06	0.2022
Highest	1752.6	23.14	0.2061	23.21	0.2093
Limit	EIRP < 1W	Result		PASS	

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, peak detector, trace maximum hold.
5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GSM)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	248.00	242.00	244.00	246.00	244.00	244.00
26dB BW (kHz)	314.00	316.00	308.00	310.00	310.00	308.00

PCS Band						
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	246.00	244.00	242.00	246.00	246.00	246.00
26dB BW (kHz)	316.00	314.00	316.00	310.00	312.00	314.00

Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.14	4.16	4.16
26dB BW (MHz)	4.68	4.68	4.68

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
99% OBW (MHz)	4.18	4.18	4.18
26dB BW (MHz)	4.68	4.70	4.70




PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.18	4.18	4.18
26dB BW (MHz)	4.70	4.68	4.68

3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GSM Link (GMSK)
---------------	---------	--------------------	-----------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 16.MAR.2015 19:07:43


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 16.MAR.2015 19:00:51




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 16.MAR.2015 19:06:41


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 16.MAR.2015 19:02:02




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 16.MAR.2015 19:04:57

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 16.MAR.2015 19:02:48




Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 16.MAR.2015 20:29:03


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 16.MAR.2015 20:22:49




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 16.MAR.2015 20:28:15


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 16.MAR.2015 20:24:23




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 16.MAR.2015 20:27:31

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 16.MAR.2015 20:25:28




Band :	GSM 1900	Test Mode :	GSM Link (GMSK)
--------	----------	-------------	-----------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 16.MAR.2015 23:02:00


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 16.MAR.2015 22:50:41




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 16.MAR.2015 23:00:14


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 16.MAR.2015 22:52:07




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 16.MAR.2015 22:56:31

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 16.MAR.2015 23:33:43




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 17.MAR.2015 00:03:59


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 16.MAR.2015 23:59:15

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 17.MAR.2015 00:03:02

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)


Date: 16.MAR.2015 23:59:54




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 17.MAR.2015 00:02:33

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 17.MAR.2015 00:00:29




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 16.MAR.2015 21:01:42


26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 16.MAR.2015 20:58:08




99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 16.MAR.2015 21:01:08


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 16.MAR.2015 20:59:03




99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 16.MAR.2015 21:00:36

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 16.MAR.2015 20:59:37




Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 1312 (1712.4 MHz)



Date: 16.MAR.2015 22:25:46


26dB Bandwidth Plot on Channel 1312 (1712.4 MHz)



Date: 16.MAR.2015 22:22:59




99% Occupied Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 16.MAR.2015 22:25:26


26dB Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 16.MAR.2015 22:23:31




99% Occupied Bandwidth Plot on Channel 1513 (1752.6 MHz)




Date: 16.MAR.2015 22:25:03

26dB Bandwidth Plot on Channel 1513 (1752.6 MHz)




Date: 16.MAR.2015 22:24:06

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 16.MAR.2015 21:49:57

26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)


Date: 16.MAR.2015 21:46:49




99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 16.MAR.2015 21:49:26

26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 16.MAR.2015 21:47:14

99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 16.MAR.2015 21:48:59

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 16.MAR.2015 21:47:46

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.5.4 Test Setup






3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GSM Link (GMSK)
--------	--------	-------------	-----------------

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 16.MAR.2015 19:21:14



Band :	GSM850	Test Mode :	GSM Link (GMSK)
--------	--------	-------------	-----------------

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 24.MAR.2015 10:04:57



Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
--------	--------	-------------	--------------------------

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 16.MAR.2015 20:36:41



Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
--------	--------	-------------	--------------------------

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 16.MAR.2015 20:39:10



Band :	GSM1900	Test Mode :	GSM Link (GMSK)
--------	---------	-------------	-----------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 16.MAR.2015 23:07:17



Band :	GSM1900	Test Mode :	GSM Link (GMSK)
--------	---------	-------------	-----------------

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 16.MAR.2015 23:09:29



Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 17.MAR.2015 00:12:05



Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 17.MAR.2015 00:15:12



Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

Lower Band Edge Plot on Channel 4132 (826.4 MHz)




Date: 16.MAR.2015 21:07:38



Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

Higher Band Edge Plot on Channel 4233 (846.6 MHz)




Date: 16.MAR.2015 21:09:35



Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Lower Band Edge Plot on Channel 1312 (1712.4 MHz)




Date: 17.MAR.2015 15:29:46



Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Higher Band Edge Plot on Channel 1513 (1752.6 MHz)




Date: 16.MAR.2015 22:35:44



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)




Date: 16.MAR.2015 21:57:56



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 16.MAR.2015 22:00:04

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$.

3.6.4 Test Setup




3.6.5 Test Result (Plots) of Conducted Spurious Emission

Band :	GSM850	Channel :	CH128
Test Mode :	GSM Link (GMSK)	Frequency :	824.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 16.MAR.2015 19:52:31

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 16.MAR.2015 19:58:14




Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 16.MAR.2015 19:59:37

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 16.MAR.2015 20:03:47

Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 16.MAR.2015 19:54:07

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 16.MAR.2015 19:57:33




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 20:00:22


Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 16.MAR.2015 20:03:21



Band :	GSM850	Channel :	CH251
Test Mode :	GSM Link (GMSK)	Frequency :	848.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 19:54:40

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 19:57:00




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 20:01:08


Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 16.MAR.2015 20:02:39



Band :	GSM850	Channel :	CH128
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	824.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 20:20:56

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 20:15:01




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 20:13:44


Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 16.MAR.2015 20:52:58



Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 20:19:45

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 20:16:11




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 20:13:08


Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 16.MAR.2015 20:10:44



Band :	GSM850	Channel :	CH251
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	848.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 20:19:01

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 20:17:03




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 20:12:40


Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 16.MAR.2015 20:11:28



Band :	GSM1900	Channel :	CH512
Test Mode :	GSM Link (GMSK)	Frequency :	1850.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 23:12:25

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 23:14:02




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 23:18:30


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 16.MAR.2015 23:21:16




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 16.MAR.2015 23:26:06



Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 23:11:58

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 23:15:06




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 23:17:57


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 16.MAR.2015 23:22:10




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 16.MAR.2015 23:25:37



Band :	GSM1900	Channel :	CH810
Test Mode :	GSM Link (GMSK)	Frequency :	1909.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 23:11:22

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 23:15:48




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 23:17:10


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 16.MAR.2015 23:22:45




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 16.MAR.2015 23:24:46



Band :	GSM1900	Channel :	CH512
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1850.2 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 23:45:31

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 23:48:31




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 23:50:24


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 16.MAR.2015 23:54:13




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 16.MAR.2015 23:55:32



Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 23:45:51

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 23:47:52




Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 16.MAR.2015 23:50:48

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 16.MAR.2015 23:53:49


Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 16.MAR.2015 23:56:02



Band :	GSM1900	Channel :	CH810
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1909.8 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 23:46:11

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 23:47:19




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 23:52:26


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 16.MAR.2015 23:53:26




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 16.MAR.2015 23:56:24



Band :	WCDMA Band V	Channel :	CH4132
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	826.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 21:18:47

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 21:20:24




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 21:23:30


Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 16.MAR.2015 21:24:32



Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 21:18:18

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 21:20:46




Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 16.MAR.2015 21:22:30

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 16.MAR.2015 21:25:02

Band :	WCDMA Band V	Channel :	CH4233
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	846.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 16.MAR.2015 21:17:46

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 16.MAR.2015 21:21:10




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 21:22:08


Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 16.MAR.2015 21:25:30




Band :	WCDMA Band IV	Channel :	CH1312
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1712.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 22:12:56

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 22:16:06

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 22:16:58

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz


Date: 16.MAR.2015 22:19:24




Conducted Spurious Emission Plot between 13.6GHz ~ 18GHz




Date: 16.MAR.2015 22:20:19



Band :	WCDMA Band IV	Channel :	CH1413
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1732.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 22:13:28

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 22:15:31




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 22:17:25


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 16.MAR.2015 22:19:04




Conducted Spurious Emission Plot between 13.6GHz ~ 18GHz




Date: 16.MAR.2015 22:20:44



Band :	WCDMA Band IV	Channel :	CH1513
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1752.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 22:14:04

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 22:14:56




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 22:17:50


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 16.MAR.2015 22:18:44




Conducted Spurious Emission Plot between 13.6GHz ~ 18GHz




Date: 16.MAR.2015 22:21:07



Band :	WCDMA Band II	Channel :	CH9262
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1852.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 21:35:58

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 21:39:19




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 21:40:20


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 16.MAR.2015 21:42:50




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 16.MAR.2015 21:43:52



Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 21:36:24

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 22:04:02




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 22:05:08


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 16.MAR.2015 21:42:24




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 16.MAR.2015 21:44:17



Band :	WCDMA Band II	Channel :	CH9538
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1907.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 16.MAR.2015 21:36:50

Conducted Spurious Emission Plot between 1GHz ~ 3GHz

Date: 16.MAR.2015 21:38:09




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 16.MAR.2015 21:41:12


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 16.MAR.2015 21:42:03



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 16.MAR.2015 21:44:41

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures


1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.7.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1674	-52.59	-13	-39.59	-54.77	-54.48	1.86	5.90	H	Pass
2510	-52.50	-13	-39.50	-61.53	-54.84	2.31	6.80	H	Pass
3345	-53.87	-13	-40.87	-66.50	-56.27	2.85	7.40	H	Pass

Band :	GSM850	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1674	-51.93	-13	-38.93	-52.98	-53.82	1.86	5.90	V	Pass
2510	-45.59	-13	-32.59	-58.22	-47.93	2.31	6.80	V	Pass
3345	-53.54	-13	-40.54	-67.52	-55.94	2.85	7.40	V	Pass



Band :	GSM850	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1672	-53.84	-13	-40.84	-56.02	-55.73	1.86	5.90	H	Pass
2509	-55.72	-13	-42.72	-64.75	-58.06	2.31	6.80	H	Pass
3345	-54.39	-13	-41.39	-67.02	-56.79	2.85	7.40	H	Pass

Band :	GSM850	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1674	-57.35	-13	-44.35	-56.21	-59.24	1.86	5.90	V	Pass
2510	-51.99	-13	-38.99	-62.96	-54.33	2.31	6.80	V	Pass
3345	-53.16	-13	-40.16	-67.14	-55.56	2.85	7.40	V	Pass



Band :	GSM1900	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)			(dB)	(dBm)	(dBm)	(dB)	(dBi)		
3759	-52.27	-13	-39.27	-66.47	-56.87	3	7.60	H	Pass
5640	-48.38	-13	-35.38	-62.17	-54.64	3.84	10.10	H	Pass
7521	-43.52	-13	-30.52	-63.30	-51.02	4.43	11.93	H	Pass

Band :	GSM1900	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3759	-54.19	-13	-41.19	-66.68	-58.79	3	7.60	V	Pass
5640	-50.48	-13	-37.48	-62.89	-56.74	3.84	10.10	V	Pass
7521	-45.02	-13	-32.02	-62.81	-52.52	4.43	11.93	V	Pass



Band :	GSM1900	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3759	-51.26	-13	-38.26	-65.46	-55.86	3	7.60	H	Pass
5640	-48.46	-13	-35.46	-62.25	-54.72	3.84	10.10	H	Pass
7521	-43.08	-13	-30.08	-62.86	-50.58	4.43	11.93	H	Pass

Band :	GSM1900	Temperature :	23~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA Reading	S.G. Power	TX Cable loss	TX Antenna Gain	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3759	-53.67	-13	-40.67	-66.16	-58.27	3	7.60	V	Pass
5640	-50.91	-13	-37.91	-63.32	-57.17	3.84	10.10	V	Pass
7521	-45.26	-13	-32.26	-63.05	-52.76	4.43	11.93	V	Pass



Band :	WCDMA Band V	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1676	-45.31	-13	-32.31	-49.94	-47.20	1.86	5.90	H	Pass
2509	-55.78	-13	-42.78	-64.81	-58.12	2.31	6.80	H	Pass
3345	-53.98	-13	-40.98	-66.61	-56.38	2.85	7.40	H	Pass

Band :	WCDMA Band V	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)			(dB)	(dBm)	(dBm)	(dB)	(dBi)		
1676	-43.53	-13	-30.53	-48.41	-45.42	1.86	5.90	V	Pass
2509	-54.19	-13	-41.19	-65.16	-56.53	2.31	6.80	V	Pass
3345	-52.67	-13	-39.67	-66.65	-55.07	2.85	7.40	V	Pass



Band :	WCDMA Band IV	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3465	-51.92	-13	-38.92	-66.05	-56.29	3.12	7.49	H	Pass
5197	-50.51	-13	-37.51	-63.66	-56.31	3.65	9.45	H	Pass
6930	-44.38	-13	-31.38	-61.24	-51.58	4.15	11.35	H	Pass

Band :	WCDMA Band IV	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3465	-53.27	-13	-40.27	-66.09	-57.64	3.12	7.49	V	Pass
5197	-48.33	-13	-35.33	-62.34	-54.13	3.65	9.45	V	Pass
6930	-46.19	-13	-33.19	-61.44	-53.39	4.15	11.35	V	Pass



Band :	WCDMA Band II	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
3759	-52.42	-13	-39.42	-66.62	-57.02	3	7.60	H	Pass
5640	-48.97	-13	-35.97	-62.76	-55.23	3.84	10.10	H	Pass
7521	-42.58	-13	-29.58	-62.36	-50.08	4.43	11.93	H	Pass

Band :	WCDMA Band II	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Sam Li	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3759	-53.51	-13	-40.51	-66	-58.11	3	7.60	V	Pass
5640	-50.20	-13	-37.20	-62.61	-56.46	3.84	10.10	V	Pass
7521	-44.71	-13	-31.71	-62.5	-52.21	4.43	11.93	V	Pass

3.7.6 Spot Check for Test Result of Field Strength of Spurious Radiated

Band :	GSM1900	Temperature :	22~23°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	42~43%						
Test Engineer :	Jason Peng	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3759	-50.34	-13	-37.34	-64.54	-54.94	3	7.60	H	Pass
5640	-47.70	-13	-34.70	-61.49	-53.96	3.84	10.10	H	Pass
7521	-44.25	-13	-31.25	-64.03	-51.75	4.43	11.93	H	Pass

Band :	GSM1900					Temperature :	22~23°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~43%		
Test Engineer :	Jason Peng					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-53.16	-13	-40.16	-65.65	-57.76	3	7.60	V	Pass
5640	-48.32	-13	-35.32	-60.73	-54.58	3.84	10.10	V	Pass
7521	-45.97	-13	-32.97	-63.76	-53.47	4.43	11.93	V	Pass



Band :	WCDMA Band II					Temperature :	22~23°C		
Test Mode :	RMC 12.2Kbps Link (QPSK)					Relative Humidity :	42~43%		
Test Engineer :	Jason Peng					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3759	-50.02	-13	-37.02	-64.22	-54.62	3	7.60	H	Pass
5640	-47.45	-13	-34.45	-61.24	-53.71	3.84	10.10	H	Pass
7521	-43.81	-13	-30.81	-63.59	-51.31	4.43	11.93	H	Pass

Band :	WCDMA Band II	Temperature :	22~23°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~43%						
Test Engineer :	Jason Peng	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3759	-53.47	-13	-40.47	-65.96	-58.07	3	7.60	V	Pass
5640	-49.09	-13	-36.09	-61.5	-55.35	3.84	10.10	V	Pass
7521	-45.86	-13	-32.86	-63.65	-53.36	4.43	11.93	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GSM	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0060	0.0024	PASS
40	0.0036	0.0012	
30	0.0120	0.0347	
20(Ref.)	0.0000	0.0000	
10	0.0120	0.0060	
0	0.0084	0.0155	
-10	0.0359	0.0395	
-20	0.0000	0.0407	
-30	0.0024	0.0048	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	GSM	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0223	0.0043	PASS
40	0.0207	0.0016	
30	0.0229	0.0128	
20(Ref.)	0.0000	0.0000	
10	0.0154	0.0005	
0	0.0021	0.0027	
-10	0.0149	0.0128	
-20	0.0176	0.0011	
-30	0.0149	0.0144	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0024	PASS
40	0.0335	
30	0.0108	
20(Ref.)	0.0000	
10	0.0395	
0	0.0012	
-10	0.0048	
-20	0.0347	
-30	0.0000	

Band :	WCDMA Band IV	Channel :	1413
Limit (ppm) :	within authorized band	Frequency :	1732.6 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0115	PASS
40	0.0029	
30	0.0127	
20(Ref.)	0.0000	
10	0.0167	
0	0.0104	
-10	0.0121	
-20	0.0069	
-30	0.0225	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0037	PASS
40	0.0011	
30	0.0186	
20(Ref.)	0.0000	
10	0.0223	
0	0.0011	
-10	0.0181	
-20	0.0144	
-30	0.0186	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.80	0.0048	2.5	PASS
		BEP	0.0072		
		4.35	0.0084		
	EDGE class 8	3.80	0.0072		
		BEP	0.0096		
		4.35	0.0418		
GSM 1900 CH661	GSM	3.80	0.0202	(Note 3.)	
		BEP	0.0154		
		4.35	0.0011		
	EDGE class 8	3.80	0.0149		
		BEP	0.0005		
		4.35	0.0011		
WCDMA Band V CH4182	RMC 12.2Kbps	3.80	0.0024	2.5	
		BEP	0.0048		
		4.35	0.0371		
WCDMA Band IV CH1413	RMC 12.2Kbps	3.80	0.0139	(Note 3.)	
		BEP	0.0046		
		4.35	0.0092		
WCDMA Band II CH9400	RMC 12.2Kbps	3.80	0.0165	(Note 3.)	
		BEP	0.0229		
		4.35	0.0027		

Note:

1. Normal Voltage = 3.80V.
2. Battery End Point (BEP) = 3.50 V.
3. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 28, 2014	Mar. 16, 2015~ Mar. 24, 2015	Oct. 27, 2015	Conducted (TH01-KS)
Spectrum Analyzer	R&S	FSV30	101338	9kHz~30GHz	May 04, 2014	Mar. 16, 2015~ Mar. 24, 2015	May 03, 2015	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 25, 2014	Mar. 16, 2015~ Mar. 24, 2015	Oct. 24, 2015	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz; Max 30dBm	Sep. 29, 2014 Sep. 10, 2015	Aug. 22, 2015 Feb. 26, 2016	Sep. 28, 2015 Sep. 09, 2016	Radiation (03CH02-KS)
Spectrum Analyzer	R&S	FSV40	101040	10kHz~40GHz;Ma x 30dBm	Sep. 25, 2014 Sep. 10, 2015	Aug. 22, 2015 Feb. 26, 2016	Sep. 24, 2015 Sep. 09, 2016	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30MHz~2GHz	Sep. 13, 2014 Sep. 12, 2015	Aug. 22, 2015 Feb. 26, 2016	Sep. 12, 2015 Sep. 11, 2016	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 08, 2014 Nov. 07, 2015	Aug. 22, 2015 Feb. 26, 2016	Nov. 07, 2015 Nov. 06, 2016	Radiation (03CH02-KS)
Horn Antenna	Schwarzbeck	BBHA9120 D	9120D-1356	1GHz~18GHz	Jun. 25, 2015	Aug. 22, 2015 Feb. 26, 2016	Jun. 24, 2016	Radiation (03CH02-KS)
SHF-EHF Horn	com-power	AH-840	101070	18GHz~40GHz	Sep. 04, 2014 Mar. 03, 2015	Aug. 22, 2015 Feb. 26, 2016	Sep. 03, 2015 Mar. 02, 2016	Radiation (03CH02-KS)
Amplifier	com-power	PA-103A	161069	1kHz~1000MHz / 32 dB	May 04, 2015	Aug. 22, 2015 Feb. 26, 2016	May 03, 2016	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1GHz~26.5GHz Gain 30dB	Oct. 28, 2014 Oct. 24, 2015	Aug. 22, 2015 Feb. 26, 2016	Oct. 27, 2015 Oct. 23, 2016	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	Aug. 22, 2015 Feb. 26, 2016	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Aug. 22, 2015 Feb. 26, 2016	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
---	-------



Appendix B. Product Equality Declaration