

# **TEST REPORT**

**Applicant:** TCL Communication Ltd.

**EUT Description:** TCL LINKPORT IK511

**Model:** IK511US

**Brand:** TCL

**FCC ID:** 2ACCJSCD004

**Standards:** FCC CFR Title 47 Part 2

FCC CFR Title 47 Part 96.47


**Date of Receipt:** 2025/05/17

**Date of Test:** 2025/05/17 to 2025/05/28

**Date of Issue:** 2025/05/28

TOWE tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

the results documented in this report apply only the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility assure that additional production units of the model are manufactured with identical electrical and mechanical components. All sample tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise. without written approval of TOWE, the test report shall not be reproduced except in full.



---

Huang Kun  
Approved By:



---

Chen Chengfu  
Reviewed By:

## Revision History

Rev.	Issue Date	Description	Revised by
01	2025/05/28	Original	Chen Chengfu

## Summary of Test Results

FCC Part	Test Item	Verdict
§96.47	End user device additional requirements	Pass

## Contents

<b>1</b>	<b>General Description</b>	<b>5</b>
1.1	Lab Information	5
1.1.1	Testing Location	5
1.1.2	Test Facility / Accreditations	5
1.2	Client Information	5
1.2.1	Applicant	5
1.2.2	Manufacturer	5
1.3	Product Information	6
<b>2</b>	<b>Test Configuration</b>	<b>7</b>
2.1	Description of test setup	7
2.2	Test Environment	7
2.3	Test RF Cable	7
2.4	Modifications	7
<b>3</b>	<b>Equipment and Measurement Uncertainty</b>	<b>8</b>
3.1	Test Equipment List	8
3.2	Measurement Uncertainty	8
<b>4</b>	<b>Test Results</b>	<b>9</b>
4.1	End user Device Additional Requirements	9
<b>5</b>	<b>Test Setup Photos</b>	<b>10</b>
	Appendix	11

# 1 General Description

## 1.1 Lab Information

### 1.1.1 Testing Location

These measurements tests were conducted at the Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. facility located at F401 and F101, Building E, Hongwei Industrial Zone, Liuxian 3rd Road, Bao'an District, Shenzhen, China. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014

Tel.: +86-755-27212361

Contact Email: [info@towewireless.com](mailto:info@towewireless.com)

### 1.1.2 Test Facility / Accreditations

#### A2LA (Certificate Number: 7088.01)

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017

General requirements for the competence of testing and calibration laboratories. This accreditation

demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

#### FCC Designation No.: CN1353

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN1353.

#### ISED CAB identifier: CN0152

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0152

Company Number: 31000

## 1.2 Client Information

### 1.2.1 Applicant

Applicant:	TCL Communication Ltd.
Address:	5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong

### 1.2.2 Manufacturer

Manufacturer:	TCL Communication Ltd.
Address:	5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong

### 1.3 Product Information

EUT Description:	TCL LINKPORT IK511		
Model:	IK511US		
Brand:	TCL		
Hardware Version:	V3.0		
Software Version:	IK511USV1_ZZ_01.00_01		
IMEI:	358028850002110		
Technical specification:			
Modulation Type:	LTE: <input checked="" type="checkbox"/> QPSK, <input checked="" type="checkbox"/> 16QAM, <input checked="" type="checkbox"/> 64QAM, <input checked="" type="checkbox"/> 256QAM		
Operation Frequency Range:	Band	TX Frequency	RX Frequency
	LTE Band 48	3550 to 3700 MHz	3550 to 3700 MHz
Antenna Type:	<input checked="" type="checkbox"/> External, <input type="checkbox"/> Integrated		
Antenna Gain:	Band	Main Antenna (dBi)	Diversity Antenna (dBi)
	LTE Band 48	2.4	1.2
Remark: The above EUT's information was declared by applicant, please refer to the specifications or user manual for more detailed description.			

## 2 Test Configuration

### 2.1 Description of test setup

Description	Manufacturer	Model	FCC ID
LTE Base Station	Baicells	mBS31001	2AG32MBS3100196N
Router	TP Link	TL-WDR6300	/
Laptop	DELL	Latitude 3510	/

### 2.2 Test Environment

Temperature:	22°C ~ 25°C
Relative Humidity	37-52 % RH Ambient
Voltage:	Nominal: 5 Vdc

### 2.3 Test RF Cable

**For all conducted test items:** The offset level is set spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

### 2.4 Modifications

No modifications were made during testing.

### 3 Equipment and Measurement Uncertainty

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, whichever is less, and where applicable is traceable recognized national standards.

#### 3.1 Test Equipment List

Radiated Emission					
Description	Manufacturer	Model	SN	Last Due	Cal Due
Signal Analyzer	Keysight	N9020A	US46470468	2025/03/14	2026/03/13
Power Divider	Qotana	DBPD0200001800C	22122900036	2025/03/11	2026/03/10

#### 3.2 Measurement Uncertainty

Parameter	$U_{lab}$
Frequency error	371.88Hz

Uncertainty figures are valid to a confidence level of 95%

## 4 Test Results

### 4.1 End user Device Additional Requirements.

#### Limits


End User Devices will operate only after it receives authorization from an associated CBSD, including the frequencies and power limits for their operation.

End User Devices discontinues operation, changes Frequency, and changes its operational power level within 10 s of receiving instructions from its associated CBSD.

#### Test Procedure

KDB 940660 D01 Part 96 CBRS Eqpt v02, WINNF-TS-0122 V1.0.2

#### Test Setup



#### Test Settings

Based on the End user device additional requirements. During the test, use a certified Ruckus CBSD device (LTE Base Station FCC ID: 2AG32MBS3100196N) as a companion device.

1. Configure CBSD to operate at 3600MHz~3630MHz, and Power level 10dBm/MHz
2. Enable AP service from Ruckus Cloud management
3. Check End User Devices Frequency and Power
4. Disable AP service from Ruckus Cloud management, check whether the EUT stops transmitting within 10s
5. Repeat step 2 to step 4 with the CBSD operating at 3670MHz~3690MHz, and Power level 20dBm/MHz.

#### Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

#### Test Result

The detailed test data see: **Appendix**.


## 5 Test Setup Photos

The detailed test data see: **Appendix-A PART96.47 Setup Photos**


# Appendix


## LTE

Bandwidth: 10MHz Setup with frequency 3625MHz and power level 10dBm/MHz




EUT stops transmission within 10 seconds of receiving instructions from its associated CBSD.





EUT stops transmission within 10 seconds of receiving instructions from its associated CBSD.



~The End~