



# FCC RADIO TEST REPORT

## FCC ID: 2ACLEAR-101US

**Product** : Access Controller

**Trade Mark** : SOYAL

**Model Name** : AR-101US

**Family Model** : AR-101H

**Report No.** : S19042400604001

### Prepared for

SOYAL TECHNOLOGY CO., LTD.

11F, No.368, Gongjian Rd., Xizhi Dist, New Taipei City 221, Taiwan, R.O.C.

### Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street  
Bao'an District, Shenzhen 518126 P.R. China

Tel.: +86-755-6115 6588 Fax.: +86-755-6115 6599  
Website: <http://www.ntek.org.cn>

## TEST RESULT CERTIFICATION

**Applicant's name** ..... : SOYAL TECHNOLOGY CO., LTD.

Address ..... : 11F, No.368, Gongjian Rd., Xizhi Dist, New Taipei City 221, Taiwan, R.O.C.

**Manufacturer's Name** ..... : SOYAL TECHNOLOGY CO., LTD.

Address ..... : 11F, No.368, Gongjian Rd., Xizhi Dist, New Taipei City 221, Taiwan, R.O.C.

### Product description

Product name ..... : Access Controller

Model and/or type reference : AR-101US

Family Model : AR-101H

**Standards** ..... : FCC Part15.225

Test procedure ..... : ANSI C63.10-2013

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.


This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

**Date of Test** ..... :

Date (s) of performance of tests ..... : 20 May. 2019~ 04 Jun. 2019

Date of Issue ..... : 11 Jun. 2019

Test Result ..... : **Pass**

Testing Engineer : 

(Mary Hu)

Technical Manager : 

(Jason Chen)

Authorized Signatory : 

(Sam Chen)

Table of Contents	Page
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>4</b>
<b>1.1 TEST FACILITY</b>	<b>5</b>
<b>1.2 MEASUREMENT UNCERTAINTY</b>	<b>5</b>
<b>2 . GENERAL INFORMATION</b>	<b>6</b>
<b>2.1 GENERAL DESCRIPTION OF EUT</b>	<b>6</b>
<b>2.2 DESCRIPTION OF TEST MODES</b>	<b>7</b>
<b>2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED</b>	<b>8</b>
<b>2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)</b>	<b>9</b>
<b>2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS</b>	<b>10</b>
<b>3 . ANTENNA REQUIREMENT</b>	<b>11</b>
<b>3.1 STANDARD REQUIREMENT</b>	<b>11</b>
<b>3.2 EUT ANTENNA</b>	<b>11</b>
<b>4 . EMC EMISSION TEST</b>	<b>12</b>
<b>4.1 CONDUCTED EMISSION MEASUREMENT</b>	<b>12</b>
<b>4.1.1 POWER LINE CONDUCTED EMISSION LIMITS</b>	<b>12</b>
<b>4.1.2 TEST CONFIGURATION</b>	<b>12</b>
<b>4.1.3 TEST PROCEDURE</b>	<b>12</b>
<b>4.1.4 TEST RESULT</b>	<b>13</b>
<b>4.2 RADIATED EMISSION MEASUREMENT</b>	<b>17</b>
<b>4.2.1 RADIATED EMISSION LIMITS</b>	<b>17</b>
<b>4.2.2 TEST PROCEDURE</b>	<b>18</b>
<b>4.2.3 DEVIATION FROM TEST STANDARD</b>	<b>18</b>
<b>4.2.4 TEST SETUP</b>	<b>19</b>
<b>4.2.5 TEST RESULTS (BELOW 30MHZ)</b>	<b>20</b>
<b>4.2.6 TEST RESULTS (BETWEEN 30 – 1000 MHZ)</b>	<b>22</b>
<b>5 . BANDWIDTH TEST</b>	<b>24</b>
<b>5.1 TEST PROCEDURE</b>	<b>24</b>
<b>5.2 DEVIATION FROM STANDARD</b>	<b>24</b>
<b>5.3 TEST SETUP</b>	<b>24</b>
<b>5.4 TEST RESULTS</b>	<b>25</b>
<b>6. FREQUENCY TOLERANCE</b>	<b>26</b>

## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

### FCC Part15, Subpart C (15.225)

Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	Pass	
15.205(a) 15.209 15.225	Radiated Spurious Emission	Pass	
15.215	20dB Bandwidth	Pass	
15.225	Frequency Tolerance	Pass	
15.203	Antenna Requirement	Pass	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report.

## 1.1 TEST FACILITY

All measurement facilities used to collect the measurement data are located at 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

### Site Description

CNAS-Lab. : The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)  
The Certificate Registration Number is L5516.

IC-Registration The Certificate Registration Number is 9270A.

CAB identifier:CN0074

FCC- Accredited Test Firm Registration Number: 463705.

Designation Number: CN1184

A2LA-Lab. The Certificate Registration Number is 4298.01  
This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories.  
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system  
(refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 % .

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Access Controller
Trade Mark	SOYAL
Model Name	AR-101US
Family Model	AR-101H
Model Difference	All the model are the same circuit and RF module, except the model name.
Product Description	The EUT is a Access Controller
	Operation Frequency: 13.56MHz
	Modulation Type: ASK
	Number Of Channel 1CH.
	Antenna Designation: Loop Antenna
	Antenna Gain(Peak) 1.0 dBi
	N/A
	N/A
	DC 12V
	N/A
SW Version	N/A

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	Loop Antenna	N/A	1.0	Antenna

## 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Pretest Mode	Description
Mode 1	TX-13.56MHz

For Conducted Emission	
Final Test Mode	Description
Mode 1	TX-13.56MHz

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX-13.56MHz

### 2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

## 2.4 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.0m	
C-2	YES	NO	0.1m	

**Note:**

(1) The support equipment was authorized by Declaration of Confirmation.  
(2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

## 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2019.05.13	2020. 05.12	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2019.05.13	2020. 05.12	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2019.05.13	2020. 05.12	1 year
4	Test Receiver	R&S	ESPI7	101318	2019.05.13	2020.05.12	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2019.04.15	2020.04.14	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2018.05.19	2020.05.18	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2019.05.13	2020. 05.12	1 year
8	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2018.12.11	2019.12.10	1 year
9	LF Cable	N/A	R-03	N/A	2018.06.05	2021.06.05	3 year
10	PSG Analog Signal Generator	Agilent	E8257D	MY51110112	2018.08.05	2019.08.04	1 year
11	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2017.04.21	2020.04.20	3 year
12	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2017.04.21	2020.04.20	3 year

Note:

1. We will use the temporary antenna connector (soldered on the PCB board) When conducted test  
And this temporary antenna connector is listed within the instrument list
2. Each piece of equipment is scheduled for calibration once a year except the Test Cable& Aux Equipment which is scheduled for calibration every 3 years.

### 3. ANTENNA REQUIREMENT

#### 3.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 3.2 EUT ANTENNA

The EUT antenna is permanent attached antenna. It comply with the standard requirement.

## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)


Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. \*Decreases with the logarithm of the frequency

2. The lower limit shall apply at the transition frequencies

3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.1.2 TEST CONFIGURATION



### 4.1.3 TEST PROCEDURE

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.


#### 4.1.4 TEST RESULT

EUT :	Access Controller	Model Name :	1
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 12V from DC Source AC 120V/60Hz	Test Mode :	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V)	(dB $\mu$ V)	(dB)	
0.3980	23.59	9.83	33.42	57.89	-24.47	QP
0.3980	14.72	9.83	24.55	47.89	-23.34	AVG
0.5540	27.50	9.83	37.33	56.00	-18.67	QP
0.5540	17.66	9.83	27.49	46.00	-18.51	AVG
1.0060	25.26	9.93	35.19	56.00	-20.81	QP
1.0060	14.67	9.93	24.60	46.00	-21.40	AVG
1.6858	21.89	9.87	31.76	56.00	-24.24	QP
1.6858	12.09	9.87	21.96	46.00	-24.04	AVG
2.3699	20.51	9.91	30.42	56.00	-25.58	QP
2.3699	10.06	9.91	19.97	46.00	-26.03	AVG
3.7219	18.80	10.05	28.85	56.00	-27.15	QP
3.7219	8.51	10.05	18.56	46.00	-27.44	AVG

##### Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Access Controller	Model Name :	1
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 12V from DC Source AC 120V/60Hz	Test Mode :	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V)	(dB $\mu$ V)	(dB)	
0.1507	35.68	9.92	45.60	65.96	-20.36	QP
0.1507	18.64	9.92	28.56	55.96	-27.40	AVG
0.4500	23.90	9.93	33.83	56.87	-23.04	QP
0.4500	17.23	9.93	27.16	46.87	-19.71	AVG
0.6018	26.67	9.93	36.60	56.00	-19.40	QP
0.6018	19.23	9.93	29.16	46.00	-16.84	AVG
0.8980	21.85	9.93	31.78	56.00	-24.22	QP
0.8980	14.70	9.93	24.63	46.00	-21.37	AVG
1.5260	19.36	9.94	29.30	56.00	-26.70	QP
1.5260	12.79	9.94	22.73	46.00	-23.27	AVG
1.8812	18.16	9.94	28.10	56.00	-27.90	QP
1.8812	10.35	9.94	20.29	46.00	-25.71	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Access Controller	Model Name :	1
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 12V from DC Source AC 240V/60Hz	Test Mode :	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V)	(dB $\mu$ V)	(dB)	
0.5611	27.50	9.93	37.43	56.00	-18.57	QP
0.5611	16.02	9.93	25.95	46.00	-20.05	AVG
1.0045	25.26	9.93	35.19	56.00	-20.81	QP
1.0045	14.67	9.93	24.60	46.00	-21.40	AVG
1.7071	21.89	9.94	31.83	56.00	-24.17	QP
1.7071	12.09	9.94	22.03	46.00	-23.97	AVG
2.3584	20.51	9.94	30.45	56.00	-25.55	QP
2.3584	10.04	9.94	19.98	46.00	-26.02	AVG
2.9933	18.75	9.95	28.70	56.00	-27.30	QP
2.9933	9.10	9.95	19.05	46.00	-26.95	AVG
3.7197	18.80	9.95	28.75	56.00	-27.25	QP
3.7197	8.51	9.95	18.46	46.00	-27.54	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Access Controller	Model Name :	1
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 12V from DC Source AC 240V/60Hz	Test Mode :	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V)	(dB $\mu$ V)	(dB)	
0.5580	28.69	9.93	38.62	56.00	-17.38	QP
0.5580	22.21	9.93	32.14	46.00	-13.86	AVG
0.9940	25.11	9.93	35.04	56.00	-20.96	QP
0.9940	19.53	9.93	29.46	46.00	-16.54	AVG
1.6700	22.49	9.94	32.43	56.00	-23.57	QP
1.6700	16.39	9.94	26.33	46.00	-19.67	AVG
2.3820	22.32	9.94	32.26	56.00	-23.74	QP
2.3820	16.58	9.94	26.52	46.00	-19.48	AVG
3.1099	21.20	9.95	31.15	56.00	-24.85	QP
3.1099	14.78	9.95	24.73	46.00	-21.27	AVG
4.3605	20.09	9.96	30.05	56.00	-25.95	QP
4.3605	14.18	9.96	24.14	46.00	-21.86	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 Radiated Emission Limits ( FCC 15.209 )

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).

### LIMITS OF RADIATED EMISSION MEASUREMENT ( FCC 15.225 )

- (a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters, equal to 104dBuV/m at 3 meters.
- (b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters, equal to 74.5dBuV/m at 3 meters.
- (c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters, equal to 60.5dBuV/m at 3 meters.
- (d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

#### 4.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz And above 1GHz,
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

#### 4.2.3 DEVIATION FROM TEST STANDARD


No deviation

#### 4.2.4 TEST SETUP

##### (A) Radiated Emission Test-Up Frequency Below 30MHz




##### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz




#### 4.2.5 TEST RESULTS (BELOW 30MHz)

EUT :	Access Controller	Model Name. :	1
Temperature :	20 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX-13.56MHz		


Freq.	Reading	Factor	Emission Level	Limit	Margin	Polar
(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/@3m)	(dB)	
13.5609	62	0	62	124.0 0	-62	X



Freq.	Reading	Factor	Emission Level	Limit	Margin	Polar
(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/@3m)	(dB)	
13.5609	61.4	0	61.4	124.0 0	-62.6	Y



Freq.	Reading	Factor	Emission Level	Limit	Margin	Polar
(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/@3m)	(dB)	
13.5609	61.1	0	61.1	124.0 0	-62.9	Z



Spurious emissions at 9kHz~13.110MHz & 14.010MHz~30MHz

Frequency	Ant.Pol.	Emission Level	Limits	Margin	Detector
		(dBuV/m)			
(MHz)	dB $\mu$ V @3m	@3m	dB $\mu$ V/m @3m	(dB)	
0.061	X	48.59	111.90	-63.31	QP
1.512	X	46.26	64.01	-17.75	QP
8.521	X	41.58	69.54	-27.96	QP
13.441	X	42.58	69.54	-26.96	QP
22.230	X	38.36	69.54	-31.18	QP

Note:

Below 30MHz, Pre-test the X, Y, Z axis to find X axis is worst case, so only record X axis test data.

X: Field strength which this device generates since the position of the charging coil and loop antenna differ by 0 degrees.

Y: Field strength which this device generates since the position of the charging coil and loop antenna differ by 90 degrees.

Z: Field strength which this device generates since the position of the charging coil and loop antenna differ by 180 degrees

#### 4.2.6 TEST RESULTS (BETWEEN 30 – 1000 MHZ)


EUT :	Access Controller	Model Name :	1
Temperature :	20 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX	Polarization :	Horizontal

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	502.9395	6.33	22.15	28.48	46.00	-17.52	QP
V	552.8831	6.20	24.51	30.71	46.00	-15.29	QP
V	649.6597	7.94	24.68	32.62	46.00	-13.38	QP
V	771.4486	7.07	27.44	34.51	46.00	-11.49	QP
V	916.0687	9.15	29.82	38.97	46.00	-7.03	QP
V	959.7608	7.05	31.15	38.20	46.00	-7.80	QP

##### Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit

72.0 dBuV/m




EUT :	Access Controller	Model Name :	1
Temperature :	20 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX	Polarization :	Vertical

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	554.8252	6.16	24.48	30.64	46.00	-15.36	QP
H	647.3854	7.21	24.70	31.91	46.00	-14.09	QP
H	734.4913	6.94	27.43	34.37	46.00	-11.63	QP
H	842.1295	6.85	28.62	35.47	46.00	-10.53	QP
H	916.0687	8.85	29.82	38.67	46.00	-7.33	QP
H	959.9600	7.41	31.15	38.56	46.00	-7.44	QP

**Remark:**

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



## 5. BANDWIDTH TEST


### 5.1 TEST PROCEDURE

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak mode.
2. 20dB Bandwidth the resolution bandwidth of 1 kHz and the video bandwidth of 1 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.

### 5.2 DEVIATION FROM STANDARD

FCC Part15.225


### 5.3 TEST SETUP



## 5.4 TEST RESULTS

EUT :	Access Controller	Model Name :	1
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1020 hPa	Test Power :	DC 12V
Test Mode :	TX		

Test Channel	Frequency (MHz)	20 dBc Bandwidth (kHz)
CH01	13.56	0.753



## 6. FREQUENCY TOLERANCE

### 6.1 Requirement:

Test Requirement: FCC Part15.225

Test Method: ANSI C63.4:2003

Requirement: The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### 6.2 Test Procedure

- 1.The EUT was placed on a turn table which is 0.8m above ground plane.
- 2.Set EUT as normal operation
- 3.Set SPA Center Frequency = fundamental frequency, RBW, VBW= 10kHz, Span =100kHz.
- 4.Set SPA Max hold. Mark peak.

**Test Result**

Power Supply	Temperature (°C)	Measured Frequency (MHz)	Frequency Error (MHz)	Result (ppm)	Part 15.225 Limit
DC 10.2V	-20	13.561009	0.001009	74.4100295	+/- 0.01%(100ppm)
	20	13.56101	0.00101	74.4837758	+/- 0.01%(100ppm)
	50	13.561014	0.001014	74.7787611	+/- 0.01%(100ppm)
DC 12V	-20	13.561012	0.001012	74.6312684	+/- 0.01%(100ppm)
	20	13.56101	0.00101	74.4837758	+/- 0.01%(100ppm)
	50	13.56101	0.00101	74.4837758	+/- 0.01%(100ppm)
DC 13.8V	-20	13.561103	0.001103	81.3421829	+/- 0.01%(100ppm)
	20	13.561011	0.001011	74.5575221	+/- 0.01%(100ppm)
	50	13.561007	0.001007	74.2625369	+/- 0.01%(100ppm)

END REPORT