Applicant/Grantee Yellowstone Technology Ltd. Taiwan branch (Hong Kong)						
FCC ID:		2ACRR-BT1	IC:	12172A-BT1		
Section 15.212 Modular Transmitters / Section 3.2 of RSS-Gen						
	Request for Mo		est for Limited Mo		Committee (X/NI)	
		Requirements Single Moduler		e Conditions	Comply (Y/N)	
	The radio ele	Single Modular A The radio elements must have the radio		s own RF shielding "		
1	frequency circ Physical/discr may be locate	cuitry must be shielded. rete and tuning capacitors ed external to the shield, but e module assembly.	The module has its own RF shielding." Shield Can is employed on the board structure, please see exhibition External Photo, the emission measurement was conducted without further shielding added.		Y	
2	modulation/daprovided) to ecomply with the applicable RS	hall have buffered ata input(s) (if such inputs are ensure that the module will the requirements set out in the SS standard under conditions data rates or over-modulation.	inputs, it is integra	T has buffered data	Y	
3	supply regula ensure that th the requirements standard regat power supply device which Requirements standard regat design of the	hall have its own power tion on the module. This is to e module will comply with ents set out in the applicable rdless of the design of the ing circuitry in the host houses the module. It is set out in the applicable rdless of the power supplying circuitry in the which houses the module.	The TI CC2541 ha	as an On-Chip	Y	
4	provisions for and antennas Equipment ce contain a deta configuration	provisions for external power amplifiers Re		e FCC antenna rinted PCB trace on	Υ	
5	with the appli alone configu	hall be tested for compliance cable standard in a stand- ration, i.e. the module must another device during testing.	stand-alone config Interface.	mitter was tested in a uration via a serial	Y	
6		hall comply with the uipment labelling		DEM manual, there are to the OEM on how to act.	Y	

7	The modular transmitter complies with all specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer will provide adequate instructions along with the module to explain any such requirements. A copy of these instructions is included in this application for equipment authorization:	Instructions in User Manual	Y
8a	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247(b)(4).	Please refer the Maximum Permissible Exposure Information.	Y
8b	The module shall comply with applicable RSS-102 exposure requirements, which are based on the intended use/configurations. Please refer the Maximum Permissible Exposure Information.		Y
9	Is the modular device for an Industry Canada licensed exempt service?		Y

A limited modular approval may be granted for single or split modular transmitters that do not comply with all of the above requirements, *e.g.*, shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.

Signature

Name/Title:

Jean-Luc De Meulemeester

Company Name:

Yellowstone Technology Ltd. Taiwan branch (Hong Kong)

Date: 10 December 2014