

**RF EXPOSURE REPORT FOR CERTIFICATION  
On Behalf of**

**mophie LLC**

**mophie snap+ multi-device travel charger**

**Model Number: SNP-MULTI-CHGR**

**FCC ID: 2ACWB-MULTICHGR**



<b>Applicant:</b>	mophie LLC
<b>Address:</b>	6244 Technology Ave. Kalamazoo, MI 49009, United States of America.
<b>Prepared By:</b>	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808

<b>Report Number:</b>	ESTE-R2206151
<b>Date of Test:</b>	May. 19~Jun. 12, 2022
<b>Date of Report:</b>	Jun. 16, 2022

## TABLE OF CONTENTS

<u>Description</u>	<u>Page</u>
TEST REPORT VERIFICATION.....	3
1. SUMMARY OF TEST .....	4
1.1. Summary of test result.....	4
1.2. Test Mode.....	4
1.3. Test Equipment List .....	4
2. MAXIMUM PERMISSIBLE EXPOSURE .....	5
2.1. Limit.....	5
2.2. Test Setup A .....	6
2.3. Test Procedure.....	6
2.4. Equipment Approval Considerations .....	7
2.5. Test Result for Test setup A:.....	8
3. TEST SETUP PHOTO.....	9

## EST Technology Co., Ltd.

<b>Applicant:</b>	mophie LLC	
<b>Address:</b>	6244 Technology Ave. Kalamazoo, MI 49009, United States of America.	
<b>Manufacturer:</b>	mophie LLC	
<b>Address:</b>	6244 Technology Ave. Kalamazoo, MI 49009, United States of America.	
<b>E.U.T:</b>	mophie snap+ multi-device travel charger	
<b>Model Number:</b>	SNP-MULTI-CHGR	
<b>Power Supply:</b>	Input: 5V---3A, 9V---3A, 12V---2.5A Output(Pad): 5W   Output(USB-C): 5V---2A, 9V---2.22A Output(USB-A): 5V---2.4A   Output(Magnetic): 15W multi Output: Pad 3W, USB-C+A 5V 3A, Magnetic 7.5W	
<b>Trade Name:</b>	mophie	Serial No.: -----
<b>Date of Receipt:</b>	May. 19, 2022	Date of Test: May. 19~Jun. 12, 2022
<b>Test Specification:</b>	FCC CFR 47 Part 1.1307(b)&1.1310 KDB 680106 D01 RF Exposure Wireless Charging Apps v03r01	
<b>Test Result:</b>	The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC CFR 47 Part 1.1307(b)&1.1310 requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.	
		 Date: Jun. 16 2022
Prepared by:	Reviewed by:	Approved by:
 Ring Yang / Assistant	 Seven Wang / Engineer	 Iceman Hu / Manager
<b>Other Aspects:</b>	None.	
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested		
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.		

## 1. SUMMARY OF TEST

### 1.1. Summary of test result

Serial Number	Description of Test Item	FCC Standard Section	Results
1	Maximum Permissible Exposure	Part 1.1307(b)&1.1310	PASS

### 1.2. Test Mode

Test Item	Test Mode
Maximum Permissible Exposure	Pad:5W
	Magnetic:15W
	Multi Output:Pad:3W+Magnetic:7.5W

Note: The worst Full Load status is recorded in the report, worse case is multi output mode, and only report worse case multi output mode.

### 1.3. Test Equipment List

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Electric and Magnetic Field Probe-Analyzer	Narda S.T.S./PMM	EHP-200A	EST-E106	June 13,21	1 Year
Simulated load	/	/	EST-306	N/A	N/A
Simulated load	/	/	EST-307	N/A	N/A
Test Software	Narda	EHP200-TS	Rel 1.92	N/A	N/A

## 2. MAXIMUM PERMISSIBLE EXPOSURE

### 2.1. Limit


**Limits for Maximum Permissible Exposure (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

Note:

1. f = frequency in MHz \* = Plane-wave equivalent power density.
2. For devices designed for typical desktop applications, such as a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 15 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm measured from the center of the probe(s) to the edge of the device. Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

## 2.2. Test Setup A



## 2.3. Test Procedure

- a. The test was performed on 360 degree turn table in anechoic chamber.
- b. The probe was placed at 15 cm surrounding the device and 20 cm above the top of the charger and the geometric centre of the probe, for test setup A.
- c. The highest emission level was recorded and compared with limit as soon as measurement of each point; A, B, C, D, E were completed.

## 2.4. Equipment Approval Considerations

Inductive wireless power transfer applications with supporting field strength results and meeting all of the following requirements are not required to submit a KDB inquiry for devices approved using SDoC or a PAG for equipment approved using certification to address RF exposure compliance.

1	Power transfer frequency is less than 1 MHz YES; the device operated in the frequency range from 110.5-205KHz.
2	Output power from each primary coil is less than or equal to 15 watts. No; Pad:5W, Magnetic:15W, Multi Output:Pad:3W+Magneticl:7.5W
3	The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time. YES; the transfer system includes only single primary and secondary coils.
4	Client device is placed directly in contact with the transmitter. YES; Client device is placed directly in contact with the transmitter.
5	Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion). YES.
6	The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit. YES; The EUT field strength levels are 50% x MPE limits.


## 2.5. Test Result for Test setup A:

<b>E-field strength</b>	
Frequency range (KHz)	110.5 to 205
Test Mode	Multi Output:Pad:+Magneticl
Position A(V/m)	1.552
Position B(V/m)	1.632
Position C(V/m)	1.453
Position D(V/m)	1.313
Position E(V/m)	6.789
Limits (V/m)	614
50% Limits(V/m)	307

<b>H-field strength</b>	
Frequency range (KHz)	110.5 to 205
Test Mode	Multi Output:Pad:+Magneticl
Position A(A/m)	0.052
Position B(A/m)	0.035
Position C(A/m)	0.065
Position D(A/m)	0.054
Position E(A/m)	0.081
Limits (A/m)	1.630
50% Limits (A/m)	0.815

### 3. TEST SETUP PHOTO

Position A  
Pad+Magnetic




Position B  
Pad



Position B  
Pad+Magnetic



Position B  
Magnetic




Position C  
Pad+Magnetic



Position D  
Pad



Position D  
Pad+Magnetic




Position D  
Magnetic



Position E  
Pad



Position E  
Pad+Magnetic



Position E  
Magnetic



**End of Test Report**