

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.247

Report Reference No.....: **A1407096052-RB**

FCC ID..... : **2ACWO-TM7**

Compiled by
(position+printed name+signature)..: File administrators Tony Li

Supervised by
(position+printed name+signature)..: Technique principal Robin Fang

Approved by
(position+printed name+signature)..: Manager James Wu

Date of issue.....: July,29 2014

Representative Laboratory Name: Shenzhen CTL Electron Technology Co., Ltd.

Address: A0402, Block 1, Kefa Industrial District, Huanguan Nan Rd, Xintian community, Guanlan, Baoan, Shenzhen, China

Testing Laboratory Name: Dongguan Dongdian Testing Service Co.,Ltd

Address: No.17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China

Applicant's name.....: **AURA TECHNOLOGY LIMITED**

Address: FLAT/RM810, Star House, 3 Salisbury Road, Tsimshatsui, Hong Kong

Test specification

Standard.....: **FCC Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz**

TRF Originator.....: Shenzhen CTL Electron Technology Co., Ltd.

Master TRF.....: Dated 2012-06

Shenzhen CTL Electron Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Electron Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Electron Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Telpad

Trade Mark: /

Model/Type reference.....: TM7

Listed Models: /

Manufacturer: SHENZHEN KWANG SUNG ELECTRONICS CO.,LTD

Modulation Type: GFSK,II/4DQPSK,8DPSK

Operation Frequency.....: From 2402MHz to 2480MHz

Rating: DC 3.7V

Result.....: **PASS**

Tony Li
Robin Fang
James Wu

TEST REPORT

Test Report No. :	A1407096052-RB	July,29 2014
		Date of issue

Equipment under Test : Telpad

Model /Type : TM7

Listed Models : /

Applicant : **AURA TECHNOLOGY LIMITED**

Address : FLAT/RM810, Star House, 3 Salisbury Road, Tsimshatsui, Hong Kong

Manufacturer : **SHENZHEN KWANG SUNG ELECTRONICS CO.,LTD**

Address : Shitoushan Industrial Zone, Shi Yan Town, Baoan District, Shenzhen, PRC

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>TEST STANDARDS</u>	<u>4</u>
<u>2.</u>	<u>SUMMARY</u>	<u>5</u>
2.1.	General Remarks	5
2.2.	Equipment Under Test	5
2.3.	Short description of the Equipment under Test (EUT)	5
2.4.	EUT operation mode	5
2.5.	Block Diagram of Test Setup	6
2.6.	Related Submittal(s) / Grant (s)	7
2.7.	Modifications	7
2.8.	NOTE	7
<u>3.</u>	<u>TEST ENVIRONMENT</u>	<u>8</u>
3.1.	Address of the test laboratory	8
3.2.	Test Facility	8
3.3.	Environmental conditions	8
3.4.	Test Description	8
3.5.	Statement of the measurement uncertainty	8
3.6.	Equipments Used during the Test	9
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>10</u>
4.1.	AC Power Conducted Emission	10
4.2.	Radiated Emission.....	13
4.3.	Maximum Peak Output Power.....	18
4.4.	20dB Bandwidth	19
4.5.	Frequency Separation	25
4.6.	Band Edge Compliance of RF Emission	32
4.7.	Spurious RF Conducted Emission	53
4.8.	Number of hopping frequency	64
4.9.	Time Of Occupancy(Dwell Time)	67
4.10.	Pseudorandom Frequency Hopping Sequence	83
4.11.	Antenna Requirement.....	84
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>85</u>
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>86</u>

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2009](#): American National Standard for Testing Unlicensed Wireless Devices

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	July 15, 2014
Testing commenced on	:	July 15, 2014
Testing concluded on	:	July 29, 2014

2.2. Product Description

The **AURA TECHNOLOGY LIMITED**'s Model: TM7 or the "EUT" as referred to in this report; more general information as follows, for more details, refer to the user's manual of the EUT.

Name of EUT	Telpad
Model Number	TM7
FCC ID	2ACWO-TM7
WLAN	Supported 802.11b/802.11g/802.11n
Bluetooth	Supported BT v2.1+EDR
Antenna Type	Internal
WLAN FCC Operation frequency	IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE 802.11n HT20: 2412MHz—2462MHz IEEE 802.11n HT40: 2422MHz—2452MHz
Bluetooth FCC Operation frequency	2402MHz-2480MHz
WLAN Modulation	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)
Bluetooth Modulation	GFSK,8DPSK, π /4DQPSK
Android Version	Android 4.1.1

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/> 120V / 60 Hz	<input type="radio"/> 115V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input checked="" type="radio"/> Other (specified in blank below)	

DC 3.70V/DC 5.0V Adapter from AC 120V/60Hz

2.4. Short description of the Equipment under Test (EUT)

2.4GHz (Telpad (M/N: TM7))

For more details, refer to the user's manual of the EUT.

2.5. EUT operation mode

The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing. There are 79 channels of EUT, and the test carried out at the lowest channel, middle channel and highest channel .

Channel	Frequency(MHz)	Channel	Frequency(MHz)
00	2402	40	2442
01	2403	41	2443
02	2404	42	2444
03	2405	43	2445
04	2406	44	2446
05	2407	45	2447
06	2408	46	2448
07	2409	47	2449
08	2410	48	2450
09	2411	49	2451
10	2412	50	2452
11	2413	51	2453
12	2414	52	2454
13	2415	53	2455
14	2416	54	2456
15	2417	55	2457
16	2418	56	2458
17	2419	57	2459
18	2420	58	2460
19	2421	59	2461
20	2422	60	2462
21	2423	61	2463
22	2424	62	2464
23	2425	63	2465
24	2426	64	2466
25	2427	65	2467
26	2428	66	2468
27	2429	67	2469
28	2430	68	2470
29	2431	69	2471
30	2432	70	2472
31	2433	71	2473
32	2434	72	2474
33	2435	73	2475
34	2436	74	2476
35	2437	75	2477
36	2438	76	2478
37	2439	77	2479
38	2440	78	2480
39	2441		

2.6. Block Diagram of Test Setup

Fig. 2-1 Configuration of Tested System



Adapter:

MODEL: JHD-AP012U-050210AB
 INPUT: 100-240V ~ 0.3A 50/60Hz 0.35A
 OUTPUT: 5V DC 2100mA
 Power Cable: 60cm
 ◇ Shielded ◆ Unshielded

2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2ACWO-TM7** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.8. Modifications

No modifications were implemented to meet testing criteria.

2.9. NOTE

1. The EUT is a Telpad with WLAN and Bluetooth function, The functions of the EUT listed as below:

	Test Standards	Reference Report
WLAN	FCC Part 15 Subpart C	A1407096052-RW
Bluetooth	FCC Part 15 Subpart C	A1407096052-RB
JBP	FCC Part 15 Subpart B	A1407096052-JBP
SAR	FCC Per 47 CFR 2.1093(d)	A1407096052-SAR

2. The frequency bands used in this EUT are listed as follows:

Frequency Band(MHz)	2400-2483.5	5150-5350	5470-5725	5725-5850
EUT	√	—	—	—

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Dongguan Dongdian Testing Service Co.,Ltd

No.17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2003) and CISPR Publication 22.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 10288A-1

The 3m alternate test site of Dongguan Dongdian Testing Service Co.,Ltd EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 10288A-1 on Mar, 2012.

FCC-Registration No.: 270092

Dongguan Dongdian Testing Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 270092, Mar 06, 2012.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Test Description

FCC PART 15 15.247		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(1)(i)	20dB Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Peak Output Power	PASS
FCC Part 15.247(b)	Pseudorandom Frequency Hopping Sequence	PASS
FCC Part 15.247(a)(1)(iii)	Number of hopping frequency& Time of Occupancy	PASS
FCC Part 15.247(a)(1)	Frequency Separation	PASS
FCC Part 15.109/ 15.205/ 15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge Compliance of RF Emission	PASS
FCC Part 15.203/15.247 (b)	Antenna Requirement	PASS
FCC Part1.1307 (b)	MPE Evaluation	PASS

Remark: The measurement uncertainty is not included in the test result.

3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Dongguan Dongdian Testing Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested

may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Dongguan Dongdian Testing Service Co.,Ltd laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	1.60 dB	(1)
Radiated spurious emission 9KHz-40 GHz	2.20 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.24 dB	(1)
Radiated Emissio 1~18GHz	5.16 dB	(1)
Radiated Emissio 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6. Equipments Used during the Test

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	462	2013/11/26
2	EMI TEST RECEIVER	Rohde&Schwarz	ESU8	100316	2013/11/13
3	EMI TEST Software	Audix	E3	N/A	N/A
4	Horn Antenna	EMCO	3116	00060095	2013/11/16
5	Pre-Amplifier	Rohde&Schwarz	SCU-01	10049	2013/11/26
6	Pre-Amplifier	A.H.	PAM0-0118	360	2013/11/16
7	Pre-Amplifier	A.H.	PAM-1840VH	562	2013/11/16
8	Double Ridged Horn Antenna	Rohde&Schwarz	HF907	100265	2013/11/16
9	Active Loop Antenna	Schwarz beck	FMZB1519	0.38	2013/11/16
10	Loop Antenna	Rohde&Schwarz	HFH2-Z2	100020	2013/10/28
11	TURNTABLE	MATURO	TT2.0	----	N/A
12	ANTENNA MAST	MATURO	TAM-4.0-P	----	N/A
13	Spectrum	R&S	FSU26	1166.1660.26	2013/11/26

Maximum Peak Output Power / 20dB Bandwidth / Number of hopping frequency & Time of Occupancy / Band Edge Compliance of RF Emission / Spurious RF Conducted Emission / Frequency Separation

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Power Sensor	Rohde&Schwarz	NRP-Z81	102638	2013/10/26
2	Spectrum Analyzer	R&S	FSU26	1166.1660.26	2013/11/26
3	Spectrum Analyzer	Aglient	E4407B	MY44210775	2013/11/13

AC Power Conducted Emission


Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Artificial Mains	Rohde&Schwarz	ENV216	100316	2013/11/26
2	EMI Test Receiver	Rohde&Schwarz	ESU8	100316	2013/11/13
3	Pulse Limiter	Rohde&Schwarz	ESH3-Z2	101242	2013/11/26
4	EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	N/A	N/A

The Cal.Interval was one year

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2009.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2009
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2009
- 4 The EUT received DC5V power from PC, the adapter of PC received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :


Frequency (MHz)	Maximum RF Line Voltage (dB μ V)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

* Decreasing linearly with the logarithm of the frequency

TEST RESULTS

Note: We tested Conducted Emission at both TX and RX mode of GFSK, 8DPSK and $\Pi/4$ DQPSK from 0.15KHz to 30MHz and recorded the worst case data at GFSK TX mode.


Line



	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	dB	
1	0.19	43.89	9.89	53.78	63.93	-10.15	9.84	0.05	QP
2	0.26	38.00	9.88	47.88	61.47	-13.59	9.83	0.05	QP
3	0.32	34.43	9.88	44.31	59.66	-15.35	9.82	0.06	QP
4	1.50	28.50	10.27	38.77	56.00	-17.23	9.84	0.43	QP
5	3.28	27.68	10.52	38.20	56.00	-17.80	9.86	0.66	QP

	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	dB	
1	0.19	36.21	9.89	46.10	53.89	-7.79	9.84	0.05	Average
2	0.45	28.04	9.89	37.93	46.85	-8.92	9.81	0.08	Average
3	1.58	22.14	10.29	32.43	46.00	-13.57	9.84	0.45	Average
4	2.45	20.22	10.45	30.67	46.00	-15.33	9.85	0.60	Average
5	3.28	18.77	10.52	29.29	46.00	-16.71	9.86	0.66	Average

Neutral




	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	dB	
1	0.19	44.86	9.85	54.71	63.89	-9.18	9.80	0.05	QP
2	0.26	37.93	9.85	47.78	61.47	-13.69	9.80	0.05	QP
3	0.32	33.11	9.87	42.98	59.66	-16.68	9.81	0.06	QP
4	0.71	28.11	10.05	38.16	56.00	-17.84	9.86	0.19	QP
5	1.03	27.26	10.15	37.41	56.00	-18.59	9.83	0.32	QP
6	3.19	26.94	10.51	37.45	56.00	-18.55	9.85	0.66	QP

	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	dB	
1	0.19	31.70	9.85	41.55	53.89	-12.34	9.80	0.05	Average
2	0.32	27.69	9.87	37.56	49.66	-12.10	9.81	0.06	Average
3	0.71	26.85	10.05	36.90	46.00	-9.10	9.86	0.19	Average
4	1.03	24.42	10.15	34.57	46.00	-11.43	9.83	0.32	Average
5	1.96	19.10	10.39	29.49	46.00	-16.51	9.84	0.55	Average
6	6.59	15.12	10.59	25.71	50.00	-24.29	9.88	0.71	Average


4.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 22.184MHz and maximum operation frequency was 2480MHz.so radiated emission test frequency band from 9KHz to 25GHz.

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

For example

Frequency (MHz)	FS (dB μ V/m)	RA (dB μ V/m)	AF (dB)	CL (dB)	AG (dB)	Transd (dB)
300.00	40	58.1	12.2	1.6	31.90	-18.1

$$\text{Transd} = \text{AF} + \text{CL} - \text{AG}$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

The frequency spectrum above 1 GHz for Transmitter was investigated. All emission not reported are much lower than the prescribed limits. Set the RBW=1MHz,VBW=3MHz for Peak Detector while the RBW=1MHz,VBW=10Hz for Average Detector,Readings are both peak and average values. The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz})) + 40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz})) + 40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30) + 40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS


Remark: 1. We tested three positions and recorded worst case.

For 9KHz to 30MHz

Frequency (MHz)	Corrected Reading (dB μ V/m)@3m	FCC Limit (dB μ V/m) @3m	Margin (dB)	Detector	Result
12.00	43.95	69.54	25.59	QP	PASS
26.00	47.17	69.54	22.37	QP	PASS


For 30MHz to 1000MHz

Horizontal



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	61.0399	-17.89	55.16	37.27	40.00	-2.73	QP			P	
2	199.7500	-16.87	55.41	38.54	43.50	-4.96	QP			P	
3	370.4700	-13.39	52.12	38.73	46.00	-7.27	QP			P	
4	600.3600	-9.60	48.54	38.94	46.00	-7.06	QP			P	
5	800.1799	-6.28	50.34	44.06	46.00	-1.94	QP			P	
6	1000.0000	-2.46	49.84	47.38	54.00	-6.62	QP			P	

Vertical



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	61.0399	-17.89	49.68	31.79	40.00	-8.21	QP			P	
2	143.4900	-17.94	52.09	34.15	43.50	-9.35	QP			P	
3	370.4700	-13.39	50.47	37.08	46.00	-8.92	QP			P	
4	600.3600	-9.60	48.66	39.06	46.00	-6.94	QP			P	
5	800.1799	-6.28	46.12	39.84	46.00	-6.16	QP			P	
6	1000.0000	-2.46	52.81	50.35	54.00	-3.65	QP			P	

For 1GHz to 25GHz

Low Channel @ Channel 00 @ 2402 MHz

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M												
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4804.00	54.14	PK	74.00	19.86	1.00	116	52.06	31.58	7.00	36.5	2.08
2	4804.00	43.02	AV	54.00	10.98	1.00	116	40.94	31.58	7.00	36.5	2.08
3	7206.00	56.96	PK	74.00	17.04	1.00	52	46.30	37.06	8.90	35.3	10.66
4	7206.00	45.43	AV	54.00	8.57	1.00	52	34.77	37.06	8.90	35.3	10.66

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M												
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4804.00	56.01	PK	74.00	17.99	1.00	124	53.93	31.58	7.00	36.5	2.08
2	4804.00	44.94	AV	54.00	9.06	1.00	124	42.86	31.58	7.00	36.5	2.08
3	7206.00	57.78	PK	74.00	16.22	1.00	247	47.12	37.06	8.90	35.3	10.66
4	7206.00	46.64	AV	54.00	7.36	1.00	247	35.98	37.06	8.90	35.3	10.66

Middle Channel @ Channel 39 @ 2441 MHz

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M												
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4880.00	55.66	PK	74.00	18.34	1.00	33	53.52	31.04	7.60	36.5	2.14
2	4880.00	43.71	AV	54.00	10.29	1.00	33	41.57	31.04	7.60	36.5	2.14
3	7320.00	57.82	PK	74.00	16.18	1.00	196	46.68	37.84	8.60	35.3	11.14
4	7320.00	45.99	AV	54.00	8.01	1.00	196	34.52	37.84	8.60	35.3	11.47

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M												
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4880.00	56.61	PK	74.00	17.39	1.00	300	54.47	31.04	7.60	36.5	2.14
2	4880.00	45.55	AV	54.00	8.45	1.00	300	43.41	31.04	7.60	36.5	2.14
3	7320.00	58.12	PK	74.00	15.88	1.00	345	46.98	37.84	8.60	35.3	11.14
4	7320.00	46.33	AV	54.00	7.67	1.00	345	34.86	37.84	8.60	35.3	11.47

High Channel @ Channel 78 @ 2480 MHz

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M												
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4960.00	56.52	PK	74.00	17.48	1.00	129	54.09	31.63	7.00	36.2	2.43
2	4960.00	45.79	AV	54.00	8.21	1.00	129	43.36	31.63	7.00	36.2	2.43
3	7340.00	57.82	PK	74.00	16.18	1.00	104	46.22	38.40	8.50	35.3	11.60
4	7340.00	46.03	AV	54.00	7.97	1.00	104	34.43	38.40	8.50	35.3	11.60


ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M												
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4960.00	57.85	PK	74.00	16.15	1.00	250	55.42	31.63	7.00	-36.2	2.43
2	4960.00	46.11	AV	54.00	7.89	1.00	250	43.68	31.63	7.00	-36.2	2.43
3	7340.00	58.64	PK	74.00	15.36	1.00	224	47.04	38.40	8.50	-35.3	11.60
4	7340.00	46.45	AV	54.00	7.55	1.00	224	34.85	38.40	8.50	35.3	11.60

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. The other emission levels were very low against the limit.
4. Margin value = Limit value - Emission level.
5. The average measurement was not performed when the peak measured data under the limit of average detection.

4.3. Maximum Peak Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to ANSI C63.10:2009 Maximum peak conducted output power for HFSS devices:
 The maximum peak conducted output power may be measured using a broadband peak RF power meter.
 The power meter shall have a video bandwidth that is greater than or equal to the HFSS bandwidth and shall utilize a fast-responding diode detector.

LIMIT

For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

TEST RESULTS

4.3.1 GFSK Test Mode

A. Test Verdict

Channel	Frequency (MHz)	Measured Output Peak Power (dBm)	Limits (dBm)	Verdict
00	2402	1.84	30	PASS
39	2441	2.35	30	PASS
78	2480	2.35	30	PASS

Note: 1.The test results including the cable lose.

4.3.2 8DPSK Test Mode

A. Test Verdict

Channel	Frequency (MHz)	Measured Output Peak Power (dBm)	Limits (dBm)	Verdict
00	2402	1.33	21	PASS
39	2441	1.61	21	PASS
78	2480	1.61	21	PASS

Note: 1.The test results including the cable lose.

4.3.3 $\pi/4$ DQPSK Test Mode


A. Test Verdict

Channel	Frequency (MHz)	Measured Output Peak Power (dBm)	Limits (dBm)	Verdict
00	2402	1.34	21	PASS
39	2441	1.57	21	PASS
78	2480	1.60	21	PASS

Note: 1.The test results including the cable lose.

4.4. 20dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=30 KHz and VBW=100KHz. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

LIMIT

For frequency hopping systems operating in the 2400MHz-2483.5MHz no limit for 20dB bandwidth.

TEST RESULTS

4.4.1 GFSK Test Mode

A. Test Verdict

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot	Limits (MHz)	Verdict
00	2402	0.8293	Plot 4.4.1 A	/	PASS
39	2441	0.8274	Plot 4.4.1 B	/	PASS
78	2480	0.8144	Plot 4.4.1 C	/	PASS

Note: 1.The test results including the cable lose.

B. Test Plots



(Plot 4.4.1 A: Channel 00: 2402MHz @ GFSK)



(Plot 4.4.1 B: Channel 39: 2441MHz @ GFSK)



(Plot 4.4.1 C: Channel 78: 2480MHz @ GFSK)

4.4.2 8DPSK Test Mode

A. Test Verdict


Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot	Limits (MHz)	Verdict
00	2402	1.1427	Plot 4.4.2 A	/	PASS
39	2441	1.1385	Plot 4.4.2 B	/	PASS
78	2480	1.1404	Plot 4.4.2 C	/	PASS

Note: 1.The test results including the cable lose.

B. Test Plots



(Plot 4.4.2 A: Channel 00: 2402MHz @ 8DPSK)



(Plot 4.4.2 B: Channel 39: 2441MHz @ 8DPSK)



(Plot 4.4.2 C: Channel 78: 2480MHz @ 8DPSK)


4.4.3 $\pi/4$ DQPSK Test Mode

A. Test Verdict

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot	Limits (MHz)	Verdict
00	2402	1.1346	Plot 4.4.3 A	/	PASS
39	2441	1.1398	Plot 4.4.3 B	/	PASS
78	2480	1.1332	Plot 4.4.3 C	/	PASS

Note: 1. The test results including the cable lose.

B. Test Plots



(Plot 4.4.3 A: Channel 00: 2402MHz @ $\pi/4$ DQPSK)




(Plot 4.4.3 B: Channel 39: 2441MHz @ $\pi/4$ DQPSK)



(Plot 4.4.3 C: Channel 78: 2480MHz @ $\pi/4$ DQPSK)

4.5. Frequency Separation

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=30 KHz and VBW=100KHz.

LIMIT

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the $2/3 \times 20\text{dB}$ bandwidth of the hopping channel, whichever is greater.


TEST RESULTS

4.6.1 GFSK Test Mode


A. Test Verdict

Channel	Frequency (MHz)	Channel Separation (MHz)	Refer to Plot	Limits (MHz)	Verdict
00	2402	1.006	Plot 4.6.1 A	25KHz or $2/3 \times 20\text{dB}$ bandwidth	PASS
01	2403				
38	2440	1.004	Plot 4.6.1 B	25KHz or $2/3 \times 20\text{dB}$ bandwidth	PASS
39	2441				
77	2479	1.006	Plot 4.6.1 C	25KHz or $2/3 \times 20\text{dB}$ bandwidth	PASS
78	2480				


B. Test Plots



(Plot 4.5.1 A: Channel 00: 2402MHz @ GFSK)



(Plot 4.5.1 B: Channel 39: 2441MHz @ GFSK)




(Plot 4.5.1 C: Channel 78: 2480MHz @ GFSK)

4.6.2 8DPSK Test Mode


A. Test Verdict

Channel	Frequency (MHz)	Channel Separation (MHz)	Refer to Plot	Limits (MHz)	Verdict
00	2402	1.004	Plot 4.6.2 A	25KHz or 2/3*20dB bandwidth	PASS
01	2403				
38	2440	1.006	Plot 4.6.2 B	25KHz or 2/3*20dB bandwidth	PASS
39	2441				
77	2479	1.004	Plot 4.6.2 C	25KHz or 2/3*20dB bandwidth	PASS
78	2480				


B. Test Plots



(Plot 4.5.2 A: Channel 00: 2402MHz @ 8DPSK)



(Plot 4.5.2 B: Channel 39: 2441MHz @ 8DPSK)




(Plot 4.5.2 C: Channel 78: 2480MHz @ 8DPSK)

4.6.3 π/4QPSK Test Mode


A. Test Verdict

Channel	Frequency (MHz)	Channel Separation (MHz)	Refer to Plot	Limits (MHz)	Verdict
00	2402	1.004	Plot 4.6.3 A	25KHz or 2/3*20dB bandwidth	PASS
01	2403				
38	2440	1.006	Plot 4.6.3 B	25KHz or 2/3*20dB bandwidth	PASS
39	2441				
77	2479	1.006	Plot 4.6.3 C	25KHz or 2/3*20dB bandwidth	PASS
78	2480				


B. Test Plots



(Plot 4.5.3 A: Channel 00: 2402MHz @ $\pi/4$ DQPSK)



(Plot 4.5.3 B: Channel 39: 2441MHz @ $\pi/4$ DQPSK)



(Plot 4.5.3 C: Channel 78: 2480MHz @ $\pi/4$ DQPSK)

4.6. Band Edge Compliance of RF Emission

TEST REQUIREMENT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for Peak detector while RBW=1MHz,VBW=10Hz for Average detector.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

LIMIT

Below -20dB of the highest emission level in operating band.

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)


TEST RESULTS

Remark: we measured all conditions(DH1,DH3,DH5) and recorded worst case at DH1


4.6.1 For Radiated Bandedge Measurement

Remark: we tested radiated bandedge at both hopping and no-hopping modes,recorded worst case at no-hopping mode


4.6.1.1 GFSK Test Mode




Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2390.00	36.63	3.32	27.49	36.12	41.94	74.00	37.37	Hor	Peak
2	2402.03	93.44	3.32	27.49	36.12	98.75	74.00	-19.44	Hor	Peak




Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2390.00	22.08	3.32	27.49	36.12	27.39	54.00	31.92	Hor	Average
2	2402.05	81.14	3.32	27.49	36.12	86.45	54.00	-27.14	Hor	Average



Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2390.00	35.39	3.32	27.49	36.12	40.70	74.00	38.61	Ver	Peak
2	2402.03	92.58	3.32	27.49	36.12	97.89	74.00	-18.58	Ver	Peak




Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2390.00	22.64	3.32	27.49	36.12	27.95	54.00	31.36	Ver	Average
2	2402.03	81.69	3.32	27.49	36.12	87.00	54.00	-27.69	Ver	Average




Trace: (Discrete)

Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2480.05	96.09	3.88	27.45	36.55	101.31	74.00	-22.09	Hor	Peak
2	2483.50	56.11	3.88	27.45	36.55	61.33	74.00	17.89	Hor	Peak




Trace: (Discrete)

Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2480.05	84.44	3.88	27.45	36.55	89.66	54.00	-30.44	Hor	Average
2	2483.50	44.97	3.88	27.45	36.55	50.19	54.00	9.03	Hor	Average




Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2480.00	93.71	3.88	27.45	36.55	98.93	74.00	-19.71	Ver	Peak
2	2483.50	55.43	3.88	27.45	36.55	60.65	74.00	18.57	Ver	Peak




Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2480.00	81.05	3.88	27.45	36.55	86.27	54.00	-27.05	Ver	Average
2	2483.50	40.06	3.88	27.45	36.55	45.28	54.00	13.94	Ver	Average

4.6.1.2 8DPSK Test Mode




Trace: (Discrete)

Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2390.00	35.13	3.32	27.49	36.12	40.44	74.00	38.87	Hor	Peak
2	2402.10	91.99	3.32	27.49	36.12	97.30	74.00	-17.99	Hor	Peak




Trace: (Discrete)


Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2390.00	22.04	3.32	27.49	36.12	27.35	54.00	31.96	Hor	Average
2	2402.10	79.07	3.32	27.49	36.12	84.38	54.00	-25.07	Hor	Average




Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2390.00	35.16	3.32	27.49	36.12	40.47	74.00	38.84	Ver	Peak
2	2402.10	91.42	3.32	27.49	36.12	96.73	74.00	-17.42	Ver	Peak




Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2390.00	22.45	3.32	27.49	36.12	27.76	54.00	31.55	Ver	Average
2	2402.10	78.97	3.32	27.49	36.12	84.28	54.00	-24.97	Ver	Average




Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2479.99	92.65	3.88	27.45	36.55	97.01	74.00	-17.79	Hor	Peak
2	2483.50	52.22	3.88	27.45	36.55	56.76	74.00	22.46	Hor	Peak



Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2480.00	79.27	3.88	27.45	36.55	84.49	54.00	-25.27	Hor	Average
2	2483.50	38.96	3.88	27.45	36.55	44.18	54.00	15.04	Hor	Average




Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2480.05	90.93	3.88	27.45	36.55	96.15	74.00	-16.93	Ver	Peak
2	2483.50	51.41	3.88	27.45	36.55	56.63	74.00	22.59	Ver	Peak




Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2480.00	77.11	3.88	27.45	36.55	82.33	54.00	-23.11	Ver	Average
2	2483.50	37.53	3.88	27.45	36.55	42.75	54.00	16.47	Ver	Average

4.6.1.3 $\pi/4$ DQPSK Test Mode




Trace: (Discrete)

Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2390.00	35.12	3.32	27.49	36.12	40.43	74.00	38.88	Hor	Peak
2	2402.00	92.69	3.32	27.49	36.12	98.00	74.00	-18.69	Hor	Peak




Trace: (Discrete)

Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2390.00	22.01	3.32	27.49	36.12	27.32	54.00	31.99	Hor	Average
2	2402.10	78.54	3.32	27.49	36.12	83.85	54.00	-24.54	Hor	Average




Trace: (Discrete)

Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2390.00	36.14	3.32	27.49	36.12	41.45	74.00	37.86	Ver	Peak
2	2402.00	92.22	3.32	27.49	36.12	97.53	74.00	-18.22	Ver	Peak




Trace: (Discrete)


Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2390.00	22.06	3.32	27.49	36.12	27.37	54.00	31.94	Ver	Average
2	2402.10	79.14	3.32	27.49	36.12	84.45	54.00	-25.14	Ver	Average




Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2478.00	91.75	3.88	27.45	36.55	96.97	74.00	-17.75	Hor	Peak
2	2483.50	51.23	3.88	27.45	36.55	56.45	74.00	22.77	Hor	Peak



Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2480.00	78.91	3.88	27.45	36.55	84.13	54.00	-24.91	Hor	Average
2	2483.50	38.44	3.88	27.45	36.55	43.66	54.00	15.56	Hor	Average



Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2480.00	90.13	3.88	27.45	36.55	95.35	74.00	-16.13	Ver	Peak
2	2483.50	51.17	3.88	27.45	36.55	56.39	74.00	22.83	Ver	Peak



Mark	Frequency (MHz)	Level (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Reading Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Polarization	Detector
1	2480.00	77.82	3.88	27.45	36.55	83.04	54.00	-23.82	Ver	Average
2	2483.50	38.09	3.88	27.45	36.55	43.31	54.00	15.91	Ver	Average


4.6.2 For Conducted Bandedge Measurement

4.6.2.1 GFSK Test Mode


A. Test Verdict

Frequency (MHz)	Delta Peak to Band emission (dBc)	Hopping Mode	Detector	Limit (dBc)	Refer to Plot	Verdict
2400.00	44.20	OFF	Peak	20	Plot 4.6.2.1 A	PASS
2400.00	44.20	ON	Peak	20	Plot 4.6.2.1 B	PASS
2483.50	49.10	OFF	Peak	20	Plot 4.6.2.1 C	PASS
2483.50	47.74	ON	Peak	20	Plot 4.6.2.1 D	PASS


B. Test Plots




(Plot 4.6.2.1 A: Channel 00: 2402MHz @ GFSK)




(Plot 4.6.2.1 B: Hopping Mode @ GFSK)




(Plot 4.6.2.1 C: Channel 78: 2480MHz @ GFSK)




(Plot 4.6.2.2 A: Channel 00: 2402MHz @ 8DPSK)



(Plot 4.6.2.2 B: Hopping Mode @ 8DPSK)



(Plot 4.6.2.2 C: Channel 78: 2480MHz @ 8DPSK)




(Plot 4.6.2.2 D: Hopping Mode @ 8DPSK)

4.6.2.3 $\pi/4$ DQPSK Test Mode


A. Test Verdict

Frequency (MHz)	Delta Peak to Band emission (dBc)	Hopping Mode	Detector	Limit (dBc)	Refer to Plot	Verdict
2400.00	46.38	OFF	Peak	20	Plot 4.6.2.3 A	PASS
2400.00	46.67	ON	Peak	20	Plot 4.6.2.3 B	PASS
2483.50	46.25	OFF	Peak	20	Plot 4.6.2.3 C	PASS
2483.50	44.43	ON	Peak	20	Plot 4.6.2.3 D	PASS


B. Test Plots



(Plot 4.6.2.3 A: Channel 00: 2402MHz @ $\pi/4$ DQPSK)




(Plot 4.6.2.3 B: Hopping Mode @ $\pi/4$ DQPSK)



(Plot 4.6.2.3 C: Channel 78: 2480MHz @ $\pi/4$ DQPSK)

4.7. Spurious RF Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2009 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBM= 300KHz to measure the peak field strength, and measure frequency range from 30MHz to 25GHz.

LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

TEST RESULTS

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandedge measurement data.

4.7.1 GFSK Test Mode


A. Test Verdict

Channel	Frequency (MHz)	Frequency Range	Refer to Plot	Limit (dBc)	Verdict
00	2402	30MHz-25GHz	Plot 4.7.1 A1/A2	-20	PASS
39	2441	30MHz-25GHz	Plot 4.7.1 B1/B2	-20	PASS
78	2480	30MHz-25GHz	Plot 4.7.1 C1/C2	-20	PASS


B. Test Plots




(Plot 4.7.1 A1: Channel 00: 2402MHz @ GFSK)



(Plot 4.7.1 A2: Channel 00: 2402MHz @ GFSK)




(Plot 4.7.1 B1: Channel 39: 2441MHz @ GFSK)



(Plot 4.7.1 B2: Channel 39: 2441MHz @ GFSK)



(Plot 4.7.1 C1: Channel 78: 2480MHz @ GFSK)



(Plot 4.7.1 C2: Channel 78: 2480MHz @ GFSK)


4.7.2 $\pi/4$ DQPSK Test Mode

A. Test Verdict

Channel	Frequency (MHz)	Frequency Range	Refer to Plot	Limit (dBc)	Verdict
00	2402	30MHz-25GHz	Plot 4.7.2 A1/A2	-20	PASS
39	2441	30MHz-25GHz	Plot 4.7.2 B1/B2	-20	PASS
78	2480	30MHz-25GHz	Plot 4.7.2 C1/C2	-20	PASS

B. Test Plots


(Plot 4.7.2 A1: Channel 00: 2402MHz @ $\pi/4$ DQPSK)



(Plot 4.7.2 A2: Channel 00: 2402MHz @ $\pi/4$ DQPSK)




(Plot 4.7.2 B1: Channel 39: 2441MHz @ $\pi/4$ DQPSK)



(Plot 4.7.2 B2: Channel 39: 2441MHz @ $\pi/4$ DQPSK)



(Plot 4.7.2 C1: Channel 78: 2480MHz @ $\pi/4$ DQPSK)



(Plot 4.7.2 C2: Channel 78: 2480MHz @ $\pi/4$ DQPSK)

4.7.3 8DPSK Test Mode


A. Test Verdict

Channel	Frequency (MHz)	Frequency Range	Refer to Plot	Limit (dBc)	Verdict
00	2402	30MHz-25GHz	Plot 4.7.3 A1/A2	-20	PASS
39	2441	30MHz-25GHz	Plot 4.7.3 B1/B2	-20	PASS
78	2480	30MHz-25GHz	Plot 4.7.3 C1/C2	-20	PASS

B. Test Plots




(Plot 4.7.3 A1: Channel 00: 2402MHz @8DPSK)



(Plot 4.7.3 A2: Channel 00: 2402MHz @8DPSK)




(Plot 4.7.3 B1: Channel 39: 2441MHz @8DPSK)



(Plot 4.7.3 B2: Channel 39: 2441MHz @8DPSK)




(Plot 4.7.3 C1: Channel 78: 2480MHz @8DPSK)



(Plot 4.7.3 C2: Channel 78: 2480MHz @8DPSK)

4.8. Number of hopping frequency

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. Set spectrum analyzer start 2400MHz to 2483.5MHz with RBW=30 KHz and VBW=100KHz.

LIMIT


Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

4.8.1 GFSK Test Mode

A. Test Verdict

Hopping Channel Frequency Range (MHz)	Number of Hopping Channel	Refer to Plot	Limit	Verdict
2400-2483.5	79	Plot 4.8.1 A1	≥15	PASS

B. Test Plots




(Plot 4.8.1 A: @ GFSK)

4.8.2 8DPSK Test Mode

A. Test Verdict

Hopping Channel Frequency Range (MHz)	Number of Hopping Channel	Refer to Plot	Limit	Verdict
2400-2483.5	79	Plot 4.8.2 A1	≥15	PASS

B. Test Plots




(Plot 4.7.2 A1: @ 8DPSK)

4.8.3 π/4DQPSK Test Mode

A. Test Verdict

Hopping Channel Frequency Range (MHz)	Number of Hopping Channel	Refer to Plot	Limit	Verdict
2400-2483.5	79	Plot 4.8.3 A1	≥15	PASS

B. Test Plots



(Plot 4.7.3 A1: @ $\pi/4$ DQPSK)

4.9. Time Of Occupancy(Dwell Time)

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. Set center frequency of spectrum analyzer=operating frequency with RBW=1MHz and VBW=3MHz,Span=0Hz.

LIMIT

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a pe-riod of 0.4 seconds multiplied by the number of hopping channels employed.


TEST RESULTS

4.9.1 GFSK Test Mode


A. Test Verdict

Mode	Frequency (MHz)	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Refer to Plot	Verdict
DH 1	2402	0.420	0.1344	0.4	Plot 4.9.1 A1	PASS
	2441	0.420	0.1344	0.4	Plot 4.9.1 A2	PASS
	2480	0.420	0.1344	0.4	Plot 4.9.1 A3	PASS
Note: Dwell time=Pulse time (ms) × (1600 ÷ 2 ÷ 79) ×31.6 Second						
DH 3	2402	1.705	0.2728	0.4	Plot 4.9.1 B1	PASS
	2441	1.705	0.2728	0.4	Plot 4.9.1 B2	PASS
	2480	1.705	0.2728	0.4	Plot 4.9.1 B3	PASS
Note: Dwell time=Pulse time (ms) × (1600 ÷ 4 ÷ 79) ×31.6 Second						
DH 5	2402	2.965	0.3163	0.4	Plot 4.9.1 C1	PASS
	2441	2.965	0.3163	0.4	Plot 4.9.1 C2	PASS
	2480	2.965	0.3163	0.4	Plot 4.9.1 C3	PASS
Note: Dwell time=Pulse Time (ms) × (1600 ÷ 6 ÷ 79) ×31.6 Second						


B. Test Plots




(Plot 4.9.1.A1: Channel 00: 2402MHz @ GFSK @ DH1)




(Plot 4.9.1.A2: Channel 39: 2441MHz @ GFSK @ DH1)




(Plot 4.9.1.A3: Channel 78: 2480MHz @ GFSK @ DH1)




(Plot 4.9.1.B1: Channel 00: 2402MHz @ GFSK @ DH3)




(Plot 4.9.1.B2: Channel 39: 2441MHz @ GFSK @ DH3)




(Plot 4.9.1.B3: Channel 78: 2480MHz @ GFSK @ DH3)



(Plot 4.9.1.C1: Channel 00: 2402MHz @ GFSK @ DH5)



(Plot 4.9.1.C2: Channel 39: 2441MHz @ GFSK @ DH5)




(Plot 4.9.1.C3: Channel 78: 2480MHz @ GFSK @ DH5)

4.8.2 8DPSK Test Mode


A. Test Verdict

Mode	Frequency (MHz)	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Refer to Plot	Verdict
DH 1	2402	0.430	0.1376	0.4	Plot 4.9.2 A1	PASS
	2441	0.435	0.1392	0.4	Plot 4.9.2 A2	PASS
	2480	0.430	0.1376	0.4	Plot 4.9.2 A3	PASS
Note: Dwell time=Pulse time (ms) × (1600 ÷ 2 ÷ 79) ×31.6 Second						
DH 3	2402	1.705	0.2728	0.4	Plot 4.9.2 B1	PASS
	2441	1.705	0.2728	0.4	Plot 4.9.2 B2	PASS
	2480	1.705	0.2728	0.4	Plot 4.9.2 B3	PASS
Note: Dwell time=Pulse time (ms) × (1600 ÷ 4 ÷ 79) ×31.6 Second						
DH 5	2402	2.965	0.3163	0.4	Plot 4.9.2 C1	PASS
	2441	2.965	0.3163	0.4	Plot 4.9.2 C2	PASS
	2480	2.965	0.3163	0.4	Plot 4.9.2 C3	PASS
Note: Dwell time=Pulse Time (ms) × (1600 ÷ 6 ÷ 79) ×31.6 Second						


B. Test Plots




(Plot 4.9.2.A1: Channel 00: 2402MHz @ 8DPSK @ DH1)




(Plot 4.9.2.A2: Channel 39: 2441MHz @ 8DPSK @ DH1)




(Plot 4.9.2.A3: Channel 78: 2480MHz @ 8DPSK @ DH1)




(Plot 4.9.2.B1: Channel 00: 2402MHz @ 8DPSK @ DH3)




(Plot 4.9.2.B2: Channel 39: 2441MHz @ 8DPSK @ DH3)




(Plot 4.9.2.B3: Channel 78: 2480MHz @ 8DPSK @ DH3)



(Plot 4.9.2.C1: Channel 00: 2402MHz @ 8DPSK @ DH5)



(Plot 4.9.2.C2: Channel 39: 2441MHz @ 8DPSK @ DH5)




(Plot 4.9.2.C3: Channel 78: 2480MHz @ 8DPSK @ DH5)

4.8.3 π/4DQPSK Test Mode


A. Test Verdict

Mode	Frequency (MHz)	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Refer to Plot	Verdict
DH 1	2402	0.430	0.1376	0.4	Plot 4.9.3 A1	PASS
	2441	0.435	0.1392	0.4	Plot 4.9.3 A2	PASS
	2480	0.430	0.1376	0.4	Plot 4.9.3 A3	PASS
Note: Dwell time=Pulse time (ms) × (1600 ÷ 2 ÷ 79) ×31.6 Second						
DH 3	2402	1.705	0.2728	0.4	Plot 4.9.3 B1	PASS
	2441	1.705	0.2728	0.4	Plot 4.9.3 B2	PASS
	2480	1.705	0.2728	0.4	Plot 4.9.3 B3	PASS
Note: Dwell time=Pulse time (ms) × (1600 ÷ 4 ÷ 79) ×31.6 Second						
DH 5	2402	2.965	0.3163	0.4	Plot 4.9.3 C1	PASS
	2441	2.965	0.3163	0.4	Plot 4.9.3 C2	PASS
	2480	2.965	0.3163	0.4	Plot 4.9.3 C3	PASS
Note: Dwell time=Pulse Time (ms) × (1600 ÷ 6 ÷ 79) ×31.6 Second						


B. Test Plots




(Plot 4.9.3.A1: Channel 00: 2402MHz @ $\pi/4$ DQPSK @ DH1)




(Plot 4.9.3.A2: Channel 39: 2441MHz @ $\pi/4$ DQPSK @ DH1)




(Plot 4.9.3.A3: Channel 78: 2480MHz @ $\pi/4$ DQPSK @ DH1)




(Plot 4.9.3.B1: Channel 00: 2402MHz @ $\pi/4$ DQPSK @ DH3)




(Plot 4.9.3.B2: Channel 39: 2441MHz @ $\pi/4$ DQPSK @ DH3)




(Plot 4.8.3.B3: Channel 78: 2480MHz @ $\pi/4$ DQPSK @ DH3)



(Plot 4.9.3.C1: Channel 00: 2402MHz @ $\pi/4$ DQPSK @ DH5)



(Plot 4.9.3.C2: Channel 39: 2441MHz @ $\pi/4$ DQPSK @ DH5)



(Plot 4.9.3.C3: Channel 78: 2480MHz @ $\pi/4$ DQPSK @ DH5)

4.10. Pseudorandom Frequency Hopping Sequence

TEST APPLICABLE


For 47 CFR Part 15C section 15.247 (a)(1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence Requirement


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros:8(non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally on the average by each transmitter. The system receiver has input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

4.11. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The WLAN and BT share difference antenna and the maximum gain of WLAN antenna was 1.20 dBi.



5. Test Setup Photos of the EUT

Radiated Emission (30MHz-1GHz)



Radiated Emission (1GHz-25GHz)



Conducted Emission (AC Mains)




6. External and Internal Photos of the EUT

External Photos



















Internal Photos


















.....End of Report.....