


RF TEST REPORT



Report No.: 17070865-FCC-R1-V1

Supersede Report No.: N/A

Applicant	Mobiwire Mobiles (Ningbo) Co.,Ltd	
Product Name	Mobile phone	
Model No.	N552	
Serial No.	N/A	
Test Standard	FCC Part 22(H):2016 ;FCC Part 24(E):2016; ANSI/TIA-603-D: 2010	
Test Date	September 09 to 18, 2017	
Issue Date	September 27, 2017	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification		☒
Equipment did not comply with the specification		☐
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION.....	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS.....	10
6.1 RF EXPOSURE (SAR)	10
6.2 RF OUTPUT POWER.....	11
6.3 PEAK-AVERAGE RATIO	23
6.4 OCCUPIED BANDWIDTH	27
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	38
6.6 SPURIOUS RADIATED EMISSIONS.....	51
6.7 BAND EDGE	57
6.8 FREQUENCY STABILITY.....	67
ANNEX A. TEST INSTRUMENT	71
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	73
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	85
ANNEX C.II. EUT OPERATING CONKITIONS	87
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	88
ANNEX E. DECLARATION OF SIMILARITY	89

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070865-FCC-R1	NONE	Original	September 19, 2017
17070865-FCC-R1-V1	V1	Updated the GPRS/ EGPRS Multi-slot class data	September 27, 2017

2. Customer information

Applicant Name	Mobiwire Mobiles (Ningbo) Co.,Ltd
Applicant Add	Mobiwire Mobiles, No. 999 Dacheng East Road Fenghua, Zhejiang China
Manufacturer	Mobiwire Mobiles (Ningbo) Co.,Ltd
Manufacturer Add	Mobiwire Mobiles, No. 999 Dacheng East Road Fenghua, Zhejiang China

3. Test site information

Test Lab A:

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

Test Lab B:

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMG(ver.lcp-03A1)

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile phone
---------------------	--------------

Main Model: N552

Serial Model: N/A

Date EUT received: September 08, 2017

Test Date(s): September 09 to 18, 2017

Equipment Category : PCE

Antenna Gain:	GSM850: -3dBi
	PCS1900: -1dBi
	UMTS-FDD Band V: -3dBi
	UMTS-FDD Band II: -0.5dBi
	LTE Band IV: -2dBi
	WIFI: 1dBi
	Bluetooth/BLE: 1dBi
	GPS: 1dBi

Antenna Type: PIFA antenna

Type of Modulation:	GSM / GPRS: GMSK
	EGPRS: GMSK, 8PSK
	UMTS-FDD: QPSK
	LTE Band: QPSK, 16QAM
	802.11b/g/n: DSSS, OFDM
	Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK
	BLE: GFSK
	GPS: BPSK

RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
	PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
	UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
	UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz
	LTE Band IV TX: 1710.7 ~ 1754.3 MHz; RX : 2110.7~ 2154.3 MHz

WIFI: 802.11b/g/n(20M): 2412-2462 MHz

WIFI: 802.11n(40M): 2422-2452 MHz

Bluetooth& BLE: 2402-2480 MHz

GPS: 1575.42 MHz

GSM Voice:GSM850: 32.05dBm

PCS1900: 28.84dBm

GPRS:GSM850: 31.99dBm

PCS1900: 28.87dBm

EGPRS:GSM850: 32.05dBm

PCS1900: 28.90dBm

Maximum Conducted

EGPRS(MSC5):GSM850: 25.96dBm

AV Power to Antenna:

PCS1900: 25.45dBm

RMC:UMTS-FDD Band V: 22.51dBm

UMTS-FDD Band II: 22.21dBm

HSUPA:UMTS-FDD Band V: 21.89dBm

UMTS-FDD Band II: 21.61dBm

HSDPA:UMTS-FDD Band V: 21.91dBm

UMTS-FDD Band II: 21.61dBm

GSM Voice:GSM850: 26.91dBm / ERP

PCS1900: 27.84dBm / EIRP

GPRS:GSM850: 26.84dBm / ERP

PCS1900: 27.89dBm / EIRP

EGPRS(MCS5):GSM850: 20.81dBm / ERP

PCS1900: 24.45dBm / EIRP

ERP/EIRP:

RMC:UMTS-FDD Band V: 17.36dBm / ERP

UMTS-FDD Band II: 21.71dBm / EIRP

HSDPA:UMTS-FDD Band V: 16.76dBm / ERP

UMTS-FDD Band II: 21.11dBm / EIRP

HSUPA:UMTS-FDD Band V: 16.71dBm / ERP

UMTS-FDD Band II: 21.11dBm / EIRP

GSM 850: 124CH

PCS1900: 299CH

Number of Channels:

UMTS-FDD Band V: 102CH

UMTS-FDD Band II: 277CH

WIFI :802.11b/g/n(20M): 11CH

WIFI :802.11n(40M): 7CH

Bluetooth: 79CH

BLE: 40CH

GPS:1CH

Port: USB Port, Earphone Port

Adapter:

Model: S005UA0500100

Input Power: Input: AC100-240V~50/60Hz,150mA

Output: DC 5.0V,1000mA

Battery:

Spec: 3.85V, 3000mAh,11.55Wh

Trade Name : NOBLEX

GPRS/ EGPRS Multi-slot class 8/10/11/12

FCC ID: 2ADA4N552

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ;	RF Output Power	Compliance
§ 24.232 (d) ;	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238;	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a);	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a);	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a);	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235;	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

6.1 RF Exposure (SAR)

Test Result: Pass


The EUT is a portable device, thus requires SAR evaluation;
Please refer to RF Exposure Evaluation Report: 17070865-FCC-H.

6.2 RF Output Power

Temperature	25 °C
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	September 16, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	☒
§24.232 (c)	b)	EIRP:33dBm	☒

Test Setup	
------------	---

Test Procedure	For Conducted Power: - The transmitter output port was connected to base station. - Set EUT at maximum power through base station. - Select lowest, middle, and highest channels for each band and different test mode. For ERP/EIRP: According with KDB 971168 v02r02 - The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - The frequency range up to tenth harmonic of the fundamental frequency was investigated.
----------------	---

	- Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. - Spurious emissions in dB = $10 \log (\text{TX power in Watts}/0.001)$ – the absolute level - Spurious attenuation limit in dB = $43 + 10 \log_{10} (\text{power out in Watts})$.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Conducted Power

GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	32.01	32.03	32.05	32±1	28.77	28.84	28.77	29±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	31.91	31.96	31.99	32±1	28.72	28.87	28.79	29±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	31.48	31.47	31.48	31±1	28.2	28.35	28.31	28±1
GPRS Multi-Slot Class 11 (3 uplink) GMSK	29.97	29.91	29.89	29±1	26.47	26.79	26.82	26±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	28.78	28.74	28.7	28±1	25.19	25.48	25.58	25±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	31.86	31.91	32.05	32±1	28.78	28.9	28.28	29±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	31.47	31.48	31.48	31±1	28.25	28.39	28.34	28±1
EGPRS Multi-Slot Class 11 (3 uplink) GMSK MCS1	29.99	29.94	29.9	30±1	26.49	26.75	26.85	26±1
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	28.78	28.72	28.66	29±1	25.11	25.43	25.6	25±1
EGPRS Multi-Slot Class 8 (1 uplink) 8PSK MCS5	25.96	25.76	25.69	26±1	24.54	25.21	25.45	25±1

EGPRS Multi-Slot Class 10 (2 uplink) 8PSK MCS5	24.76	24.82	24.71	25±1	23.28	24.07	24.23	24±1
EGPRS Multi-Slot Class 11 (3 uplink) 8PSK MCS5	22.56	22.67	22.54	22±1	20.75	21.66	21.91	21±1
EGPRS Multi-Slot Class 12 (4 uplink) 8PSK MCS5	21.51	21.54	21.42	21±1	19.61	20.28	20.74	20±1

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

EGPRS, MCS5 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

UMTS Mode:

UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	22.23	22±1
	4175	835	22.51	22±1
	4233	846.6	22.23	22±1
HSDPA Subtest1	4132	826.4	21.58	21±1
	4175	835	21.77	21±1
	4233	846.6	21.6	21±1
HSDPA Subtest2	4132	826.4	21.71	21±1
	4175	835	21.87	21±1
	4233	846.6	21.67	21±1
HSDPA Subtest3	4132	826.4	21.62	21±1
	4175	835	21.75	21±1
	4233	846.6	21.58	21±1
HSDPA Subtest4	4132	826.4	21.61	21±1
	4175	835	21.91	21±1
	4233	846.6	21.67	21±1
HSUPA Subtest1	4132	826.4	21.53	21±1
	4175	835	21.86	21±1
	4233	846.6	21.45	21±1
HSUPA Subtest2	4132	826.4	21.36	21±1
	4175	835	21.82	21±1
	4233	846.6	21.32	21±1
HSUPA Subtest3	4132	826.4	21.49	21±1
	4175	835	21.89	21±1
	4233	846.6	21.6	21±1
HSUPA Subtest4	4132	826.4	21.46	21±1
	4175	835	21.53	21±1
	4233	846.6	21.25	21±1
HSUPA Subtest5	4132	826.4	21.58	21±1
	4175	835	21.82	21±1
	4233	846.6	21.68	21±1

UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	22.09	22±1
	9400	1880	22.03	22±1
	9538	1907.6	22.21	22±1
HSDPA Subtest1	9262	1852.4	21.49	21±1
	9400	1880	21.4	21±1
	9538	1907.6	21.54	21±1
HSDPA Subtest2	9262	1852.4	21.59	21±1
	9400	1880	21.45	21±1
	9538	1907.6	21.61	21±1
HSDPA Subtest3	9262	1852.4	21.34	21±1
	9400	1880	21.33	21±1
	9538	1907.6	21.53	21±1
HSDPA Subtest4	9262	1852.4	21.44	21±1
	9400	1880	21.3	21±1
	9538	1907.6	21.5	21±1
HSUPA Subtest1	9262	1852.4	21.45	21±1
	9400	1880	21.23	21±1
	9538	1907.6	21.41	21±1
HSUPA Subtest2	9262	1852.4	21.4	21±1
	9400	1880	21.21	21±1
	9538	1907.6	21.3	21±1
HSUPA Subtest3	9262	1852.4	21.45	21±1
	9400	1880	21.31	21±1
	9538	1907.6	21.61	21±1
HSUPA Subtest4	9262	1852.4	21.27	21±1
	9400	1880	21.2	21±1
	9538	1907.6	21.22	21±1
HSUPA Subtest5	9262	1852.4	21.3	21±1
	9400	1880	21.53	21±1
	9538	1907.6	21.6	21±1

ERP & EIRP

GSM Voice

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	21.29	V	6.1	0.53	26.86	38.45
824.2	20.32	H	6.1	0.53	25.89	38.45
836.6	21.22	V	6.2	0.53	26.89	38.45
836.6	20.26	H	6.2	0.53	25.93	38.45
848.8	21.24	V	6.2	0.53	26.91	38.45
848.8	20.29	H	6.2	0.53	25.96	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	20.61	V	7.88	0.72	27.77	33
1850.2	19.68	H	7.88	0.72	26.84	33
1880	20.68	V	7.88	0.72	27.84	33
1880	19.76	H	7.88	0.72	26.92	33
1909.8	20.63	V	7.86	0.72	27.77	33
1909.8	19.69	H	7.86	0.72	26.83	33

GPRS:

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	21.19	V	6.1	0.53	26.76	38.45
824.2	20.26	H	6.1	0.53	25.83	38.45
836.6	21.14	V	6.2	0.53	26.81	38.45
836.6	20.19	H	6.2	0.53	25.86	38.45
848.8	21.17	V	6.2	0.53	26.84	38.45
848.8	20.2	H	6.2	0.53	25.87	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	20.56	V	7.88	0.72	27.72	33
1850.2	19.68	H	7.88	0.72	26.84	33
1880	20.73	V	7.88	0.72	27.89	33
1880	19.79	H	7.88	0.72	26.95	33
1909.8	20.64	V	7.86	0.72	27.78	33
1909.8	19.71	H	7.86	0.72	26.85	33

EGPRS (MCS5):

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	15.24	V	6.1	0.53	20.81	38.45
824.2	14.27	H	6.1	0.53	19.84	38.45
836.6	14.94	V	6.2	0.53	20.61	38.45
836.6	14.06	H	6.2	0.53	19.73	38.45
848.8	14.87	V	6.2	0.53	20.54	38.45
848.8	13.97	H	6.2	0.53	19.64	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	16.38	V	7.88	0.72	23.54	33
1850.2	15.47	H	7.88	0.72	22.63	33
1880	17.05	V	7.88	0.72	24.21	33
1880	16.12	H	7.88	0.72	23.28	33
1909.8	17.31	V	7.86	0.72	24.45	33
1909.8	16.37	H	7.86	0.72	23.51	33

RMC

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	11.51	V	6.1	0.53	17.08	38.45
826.4	9.66	H	6.1	0.53	15.23	38.45
835	11.69	V	6.2	0.53	17.36	38.45
835	9.82	H	6.2	0.53	15.49	38.45
846.6	11.41	V	6.2	0.53	17.08	38.45
846.6	9.57	H	6.2	0.53	15.24	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	14.43	V	7.88	0.72	21.59	33
1852.4	12.47	H	7.88	0.72	19.63	33
1880	14.37	V	7.88	0.72	21.53	33
1880	12.58	H	7.88	0.72	19.74	33
1907.6	14.57	V	7.86	0.72	21.71	33
1907.6	12.71	H	7.86	0.72	19.85	33

HSDPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	10.99	V	6.1	0.53	16.56	38.45
826.4	9.09	H	6.1	0.53	14.66	38.45
835	11.09	V	6.2	0.53	16.76	38.45
835	9.11	H	6.2	0.53	14.78	38.45
846.6	10.85	V	6.2	0.53	16.52	38.45
846.6	8.94	H	6.2	0.53	14.61	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	13.93	V	7.88	0.72	21.09	33
1852.4	12.06	H	7.88	0.72	19.22	33
1880	13.79	V	7.88	0.72	20.95	33
1880	11.98	H	7.88	0.72	19.14	33
1907.6	13.97	V	7.86	0.72	21.11	33
1907.6	12.14	H	7.86	0.72	19.28	33

HSUPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	10.86	V	6.1	0.53	16.43	38.45
826.4	8.99	H	6.1	0.53	14.56	38.45
835	11.04	V	6.2	0.53	16.71	38.45
835	9.22	H	6.2	0.53	14.89	38.45
846.6	10.86	V	6.2	0.53	16.53	38.45
846.6	8.97	H	6.2	0.53	14.64	38.45


EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	13.79	V	7.88	0.72	20.95	33
1852.4	11.91	H	7.88	0.72	19.07	33
1880	13.87	V	7.88	0.72	21.03	33
1880	12.1	H	7.88	0.72	19.26	33
1907.6	13.97	V	7.86	0.72	21.11	33
1907.6	12.2	H	7.86	0.72	19.34	33

6.3 Peak-Average Ratio

Temperature	25 °C
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	September 16, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13dB.	☒
Test Setup			
Test Procedure	According with KDB 971168 v02r02 5.7.2 Alternate procedure for PAPR 5.1.2 Peak power measurements with a peak power meter The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector. 5.2.3 Average power measurement with average power meter As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions If the EUT can be configured to transmit continuously (i.e., the burst duty cycle $\geq 98\%$) and at all times the EUT is transmitting at its maximum output		

	power level, then a conventional wide-band RF power meter can be used. If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle < 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to $10\log(1/\text{duty cycle})$
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

GSM : GSM 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	29.96	28.77	1.19
1880	29.66	28.84	0.82
1909.8	29.64	28.77	0.87

GPRS 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	29.76	28.78	0.98
1880	29.58	28.9	0.68
1909.8	29.72	28.28	1.44

EGPRS (MSC5) 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	25.68	24.54	1.14
1880	25.79	25.21	0.58
1909.8	25.98	25.45	0.53

RMC : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	21.31	22.09	-0.78
1880	22.74	22.03	0.71
1907.6	22.67	22.21	0.46

HSDPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	21.81	21.49	0.32
1880	21.63	21.4	0.23
1907.6	21.66	21.54	0.12


HSUPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	21.96	21.45	0.51
1880	21.66	21.23	0.43
1907.6	21.95	21.41	0.54

6.4 Occupied Bandwidth

Temperature	25 °C
Relative Humidity	57%
Atmospheric Pressure	1018mbar
Test date :	September 19, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238	a)	99% Occupied Bandwidth(kHz)	☒
	b)	26 dB Bandwidth(kHz)	☒
Test Setup			
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	246.31	315.8
190	836.6	248.29	320.6
251	848.8	245.76	316.9

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850	247.05	320.6
661	1880	243.37	317.2
810	1910	246.52	321.0

GPRS:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	245.69	315.8
190	836.6	247.74	320.7
251	848.8	245.81	317.3

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850	245.50	317.5
661	1880	243.35	316.1
810	1910	245.88	321.0

EGPRS (MSC 5):

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	245.58	315.9
190	836.6	248.10	320.6
251	848.8	246.04	316.9

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850	246.14	320.6
661	1880	248.99	314.2
810	1910	248.22	319.8

RMC:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.6	4.1564	4.658
4175	835.0	4.1581	4.669
4233	846.4	4.1669	4.658

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1853	4.1559	4.693
9400	1880	4.1593	4.683
9538	1907	4.1602	4.660

HSDPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.6	4.1535	4.658
4175	835.0	4.1593	4.663
4233	846.4	4.1585	4.664

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1853	4.1574	4.677
9400	1880	4.1692	4.689
9538	1907	4.1724	4.679

HSUPA:

UMTS-FDD Band V (Part 22H)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.6	4.1573	4.673
4175	835.0	4.1683	4.659
4233	846.4	4.1636	4.664

UMTS-FDD Band II (Part 24E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1853	4.1608	4.693
9400	1880	4.1573	4.687
9538	1907	4.1672	4.653

Test Plots


GSM Voice:




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850MHz




PCS 1900 BW - Mid CH 1880MHz




PCS 1900 BW - High CH 1910MHz


GPRS:




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850MHz




PCS 1900 BW - Mid CH 1880MHz




PCS 1900 BW - High CH 1910MHz


EGPRS (MCS5):




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850MHz




PCS 1900 BW - Mid CH 1880MHz




PCS 1900 BW - High CH 1910MHz


RMC:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz




Band V BW - High CH 846.4 MHz



Band II BW - Low CH 1853MHz




Band II BW - Mid CH 1880MHz




Band II BW - High CH 1907MHz


HSDPA:




HSUPA:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz




Band V BW - High CH 846.4 MHz



Band II BW - Low CH 1853MHz



Band II BW - Mid CH 1880MHz




Band II BW - High CH 1907MHz

6.5 Spurious Emissions at Antenna Terminals

Temperature	25 °C
Relative Humidity	57%
Atmospheric Pressure	1018mbar
Test date :	September 19, 2017
Tested By :	Loren Luo

Requirement(s):


Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB	☒
Test Setup			
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GSM Voice:


Cellular Band (Part 22H) result




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2


PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2




PCS1900 - High Channel-1




PCS 1900 - High Channel-2

GPRS:


Cellular Band (Part 22H) result




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2


PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS1900 - Middle Channel-2




PCS1900 - High Channel-1




PCS1900 - High Channel-2


EGPRS (MSC 5):
Cellular Band (Part 22H) result




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2


PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2




PCS1900 - High Channel-1




PCS 1900 - High Channel-2

RMC


UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2



Band V - High Channel-1



Band V - High Channel-2