




FCC Part 15B Measurement and Test Report

For

XPX TECHNOLOGY CO., LTD

Rm689B, Huafa 411 Bldg. Huafa N. Road, Futian, Shenzhen, China

FCC ID: 2ADIZ-X40

Test Rule(s):	<u>FCC Part 15 Subpart B</u>
Product Description:	<u>Mobile Phone</u>
Tested Model:	<u>X40</u>
Report No.:	<u>STR14118037I-4</u>
Tested Date:	<u>2014-11-06 to 2014-11-24</u>
Issued Date:	<u>2014-11-25</u>
Tested By:	<u>Vigoss Liang / Engineer</u> 
Reviewed By:	<u>Lahm Peng / EMC Manager</u> 
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u> 
Prepared By:	

Shenzhen SEM.Test Technology Co., Ltd.
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....3

 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....3

 1.2 TEST STANDARDS.....4

 1.3 TEST METHODOLOGY4

 1.4 TEST FACILITY4

 1.5 EUT SETUP AND OPERATION MODE5

2. SUMMARY OF TEST RESULTS6

3. CONDUCTED EMISSIONS7

 3.1 MEASUREMENT UNCERTAINTY7

 3.2 TEST EQUIPMENT LIST AND DETAILS7

 3.3 TEST PROCEDURE.....7

 3.4 BASIC TEST SETUP BLOCK DIAGRAM.....7

 3.5 ENVIRONMENTAL CONDITIONS8

 3.6 SUMMARY OF TEST RESULTS/PLOTS8

 3.7 CONDUCTED EMISSIONS TEST DATA.....8

4. RADIATED EMISSIONS.....11

 4.1 MEASUREMENT UNCERTAINTY11

 4.2 TEST EQUIPMENT LIST AND DETAILS11

 4.3 TEST PROCEDURE.....11

 4.4 TEST RECEIVER SETUP12

 4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....12

 4.6 ENVIRONMENTAL CONDITIONS12

 4.7 SUMMARY OF TEST RESULTS/PLOTS12

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: XPX TECHNOLOGY CO., LTD
 Address of applicant: Rm689B, Huafa 411 Bldg. Huafa N. Road, Futian, Shenzhen, China
 Manufacturer: XPX TECHNOLOGY CO., LTD
 Address of manufacturer: Flat2, 2/F, Wah Wai industrial Building, 53-61 Pak Tin Par Street, Tsuen Wan, NT, HK

General Description of EUT	
Product Name:	Mobile Phone
Trade Name:	D3, XPX, ZILO
Model No.:	X40
Adding Model(s):	ZO40; D44Z; D43z; X4
<p><i>The EUT is GSM850/900/DCS1800/PCS1900, WCDMA Band II/V, Mobile Phone. the Mobile Phone is intended for speech and Multimedia Message Service (MMS) transmission. It is equipped with GPRS/EDGE class 12 for GSM850 and GSM1900 and Bluetooth, Wi-Fi and camera functions. For more information see the following datasheet</i></p> <p><i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model X40, but the circuit and the electronic construction do not change, declared by the manufacturer.</i></p>	

Technical Characteristics of EUT	
Rated Voltage:	5.0V
Rated Current:	1.0A
Rated Power:	5W
Power Adapter Model:	XC-0510
Lowest Internal Frequency:	32.768KHz
Highest Internal Frequency:	1.2GHz
Classification of ITE:	Class B

1.2 Test Standards

The following report is prepared on behalf of the XPX TECHNOLOGY CO., LTD in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart B, and section 15.205, 15.107, and 15.109 rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

- **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Mode List:

Test Mode	Description	Remark
TM1	Charging & Playing	Connect to Adapter
TM2	Downloading	Connect to PC
TM3	Camera	/

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
USB Cable	0.8	Shielded	Without Core
Earphone	1.1	Unshielded	Without Core

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E10	LR-63C8R

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.107 (a)	Conducted Emissions	Compliant
§ 15.109 (a)	Radiated Emissions	Compliant

N/A: not applicable

3. Conducted Emissions

3.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.

3.2 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2014-05-28	2015-05-27
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2014-05-28	2015-05-27
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2014-05-28	2015-05-27

3.3 Test Procedure

Test is conducting under the description of ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

Note: Base on the calibrated result, for the impedance characteristic and insertion loss, the effect shall be ignored from the placed multiple outlet power strip between the device and LISN.

3.4 Basic Test Setup Block Diagram



3.5 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

3.6 Summary of Test Results/Plots

According to the data in section 3.7, the EUT complied with the FCC Part 15.107(a) Conducted margin for a Class B device, with the *worst* margin reading of:


-10.36 dB at 23.9980 MHz in the Line, AVG detector, 0.15-30MHz

3.7 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: *Mobile Phone*
 Tested Model: *X40*
 Operating Condition: *TM1*
 Comment: *AC 120V/60Hz*

 Test Specification: *Neutral*



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	35.16	9.50	44.66	66.00	-21.34	peak
2	0.1500	22.86	9.50	32.36	56.00	-23.64	AVG
3	0.3340	19.04	9.50	28.54	49.35	-20.81	AVG
4	0.3380	30.51	9.50	40.01	59.25	-19.24	peak
5	24.0020	36.30	12.67	48.97	60.00	-11.03	peak
6	24.0020	26.94	12.67	39.61	50.00	-10.39	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1540	36.15	9.50	45.65	65.78	-20.13	peak
2	0.1540	23.99	9.50	33.49	55.78	-22.29	AVG
3	0.3660	33.02	9.50	42.52	58.59	-16.07	peak
4	0.3660	23.27	9.50	32.77	48.59	-15.82	AVG
5	23.9980	36.21	12.67	48.88	60.00	-11.12	peak
6	23.9980	26.97	12.67	39.64	50.00	-10.36	AVG

4. Radiated Emissions

4.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any radiation emissions measurement is ± 5.10 dB.


4.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-28	2015-05-27
EMI Test Receiver	R&S	ESVB	825471/005	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23
Loop Antenna	SCHWARZECK	HFRA 5165	9365	2014-05-28	2015-05-27

4.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.



4.4 Test Receiver Setup

Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10KHz,	RBW=120KHz,	RBW=1MHz,
VBW =30KHz	VBW=300KHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = peak	Detector function = peak, QP	Detector function = peak, AV

4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit for a Class B device. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15.109(a) Limit}$$

4.6 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	1011 mbar

4.7 Summary of Test Results/Plots


According to the data, the EUT complied with the FCC Part 15.109(a) rule, and had the worst margin of:

-10.09 dB at 640.6110 MHz in the Vertical polarization, TM2 mode, 9 kHz to 6 GHz, 3Meters

Plot of Radiated Emissions Test Data


EUT: *Mobile Phone*
 Tested Model: *X40*
 Operating Condition: *TM1*
 Comment: *AC 120V/60Hz*

 Test Specification: *Horizontal*



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	38.0783	22.79	6.73	29.52	40.00	-10.48	0	150	peak
2	100.2286	21.78	6.10	27.88	43.50	-15.62	30	100	peak
3	161.4742	28.20	2.63	30.83	43.50	-12.67	29	150	peak
4	180.0165	26.80	2.75	29.55	43.50	-13.95	20	100	peak
5	890.7278	16.21	16.84	33.05	46.00	-12.95	10	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	37.1550	27.13	8.76	35.89	40.00	-4.11	51	100	peak
2	66.7325	28.18	3.24	31.42	40.00	-8.58	308	100	peak
3	159.7844	29.39	2.62	32.01	43.50	-11.49	120	100	peak
4	184.4898	27.73	2.96	30.69	43.50	-12.81	359	100	peak
5	896.9965	17.24	16.85	34.09	46.00	-11.91	0	100	peak

Plot of Radiated Emissions Test Data


EUT: *Mobile Phone*
 Tested Model: *X40*
 Operating Condition: *TM2*
 Comment: *AC 120V/60Hz*

Test Specification: *Horizontal*



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	59.8588	25.76	5.39	31.15	40.00	-8.85	158	100	peak
2	71.8319	35.14	1.97	37.11	40.00	-2.89	226	100	peak
3	144.3348	38.60	2.45	41.05	43.50	-2.45	129	150	peak
4	191.7450	37.38	3.29	40.67	43.50	-2.83	109	100	peak
5	239.9874	36.23	6.33	42.56	46.00	-3.44	0	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	44.9006	28.85	7.79	36.64	40.00	-3.36	51	100	QP
2	143.8295	37.83	2.45	40.28	43.50	-3.22	308	100	QP
3	192.4186	37.23	3.33	40.56	43.50	-2.94	120	100	QP
4	239.9874	36.83	6.33	43.16	46.00	-2.84	359	100	QP
5	287.9904	34.09	8.71	42.80	46.00	-3.20	0	100	QP

Plot of Radiated Emissions Test Data


EUT: *Mobile Phone*
 Tested Model: *X40*
 Operating Condition: *TM3*
 Comment: *AC 120V/60Hz*

 Test Specification: *Horizontal*



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	53.8818	30.98	5.92	36.90	40.00	-3.10	58	150	QP
2	65.8031	33.21	3.52	36.73	40.00	-3.27	326	100	QP
3	192.4186	36.45	3.33	39.78	43.50	-3.72	29	120	QP
4	287.9904	31.11	8.71	39.82	46.00	-6.18	209	100	QP
5	528.2458	29.75	11.35	41.10	46.00	-4.90	125	100	QP

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	34.0365	28.73	8.25	36.98	40.00	-3.02	51	100	QP
2	53.8818	30.68	5.92	36.60	40.00	-3.40	308	100	QP
3	66.4989	33.15	3.31	36.46	40.00	-3.54	120	100	QP
4	90.8554	33.49	3.83	37.32	43.50	-6.18	359	100	QP
5	191.7450	36.75	3.29	40.04	43.50	-3.46	178	100	QP

Note: Testing is carried out with frequency rang 9kHz to the 6GHz, which above 1GHz is close to the noise base even antenna close up to 1meter distance according the measurement of ANSI C63.4.

The measurements greater than 20dB below the limit from 9kHz to 30MHz and test data are not provided.

***** END OF REPORT *****