

1 Cover Page

FCC MPE REPORT

| | |
|---|---|
| Application No.: | SHEM1611007058CR |
| Applicant: | Hangzhou Hikvision Digital Technology Co., Ltd. |
| FCC ID: | 2ADTD-I092400 |
| IC ID: | 20199-I092400 |
| Equipment Under Test (EUT): | |
| NOTE: The following sample(s) submitted was/were identified on behalf of the client as | |
| Product Name: | Network Camera |
| Model No.(EUT): | DS-2CD2420F-IW |
| Add Model No.: | DS-2CD2410F-IW |
| Standards: | FCC Rules 47 CFR §2.1091 RSS-102 Issue 5: 2015 KDB447498 D01 General RF Exposure Guidance v06 |
| Date of Receipt: | 2016-11-03 |
| Date of Test: | 2016-11-28 to 2017-3-20 |
| Date of Issue: | 2017-03-27 |
| Test Result: | Pass* |

* In the configuration tested, the EUT complied with the standards specified above.



Parlam Zhan
E&E Section Manager
SGS-CSTC (Shanghai) Co., Ltd.

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Contents

| | Page |
|--------------------------------------|----------|
| 1 COVER PAGE | 1 |
| 2 CONTENTS | 2 |
| 3 GENERAL INFORMATION | 3 |
| 3.1 CLIENT INFORMATION | 3 |
| 3.2 GENERAL DESCRIPTION OF E.U.T | 3 |
| 3.3 DETAILS OF E.U.T | 3 |
| 3.4 TEST LOCATION | 3 |
| 3.5 TEST FACILITY | 4 |
| 4 TEST STANDARDS AND LIMITS | 5 |
| 5 MEASUREMENT AND CALCULATION | 6 |
| 5.1 MAXIMUM TRANSMIT POWER | 6 |
| 5.2 MPE CALCULATION | 7 |
| 6 EUT CONSTRUCTIONAL DETAILS | 7 |

3 General Information

3.1 Client Information

| | |
|--------------------------|---|
| Applicant: | Hangzhou Hikvision Digital Technology Co., Ltd. |
| Address of Applicant: | No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China |
| Manufacturer: | Hangzhou Hikvision Digital Technology Co., Ltd. |
| Address of Manufacturer: | No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China |
| Factory: | Hangzhou Hikvision Technology Co., Ltd. |
| Address of Factory: | No. 700 Dongliu Road, Binjiang District, Hangzhou 310052, Zhejiang, China |

3.2 General Description of E.U.T.

| | |
|----------------------|--|
| Product Description: | Fixed product with Ethernet port and WiFi monitor function |
| Brand Name: | HIKVISION |
| Rated Input: | DC 12V via adapter |
| Test Voltage: | AC 120V 60Hz for adapter |

3.3 Details of E.U.T.

| | |
|----------------------|---|
| Operation Frequency: | 2412MHz-2462MHz |
| Modulation Type: | 802.11 b DSSS(CCK, DQPSK, DBPSK) 802.11 g/n(HT20)/n(HT40) OFDM(64QAM, 16QAM, QPSK, BPSK) |
| Number of Channel: | 802.11/b/g/n20:11 802.11n40:7 |
| Data Rate: | 802.11b: 1/2/5.5/11Mbps, 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n(HT20/40): MCS0-MCS7 |
| Antenna Type | Integral |
| Antenna Gain | 2.4dBi |

3.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

No.588 West Jindu Road, Songjiang District, Shanghai, China.201612.

Tel: +86 21 6191 5666

Fax: +86 21 6191 5678

3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- FCC – Registration No.: 402683**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered and fully described in a report filed with the Federal Communications Commission (FCC). The acceptance letter from the FCC is maintained in our files. Registration No.: 402683.

- Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

- VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868, C-4336, T-2221, G-830 respectively.

4 Test Standards and Limits

According to §1.1310 Radiofrequency radiation exposure limits:

The limit for general population/uncontrolled exposures

| Frequency | Power density(mW/cm ²) | Averaging time(minutes) |
|---------------|------------------------------------|-------------------------|
| 300MHz~1.5GHz | $f/1500$ | 30 |
| 1.5GHz~100GHz | 1.0 | 30 |

According to RSS-102 section 2.5.2, RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

For 2.4G device, the limit of worse case is 2.68 W

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM161100705802.

For WiFi:

| Test mode | Test Frequency (MHz) | Output Power (dBm) | Output Power (mW) |
|----------------|----------------------|--------------------|-------------------|
| 802.11b | 2412 | 19.56 | 90.36 |
| | 2437 | 21.10 | 128.82 |
| | 2462 | 20.43 | 110.41 |
| 802.11g | 2412 | 18.38 | 68.87 |
| | 2437 | 19.03 | 79.98 |
| | 2462 | 19.74 | 94.19 |
| 802.11 n(HT20) | 2412 | 18.23 | 66.53 |
| | 2437 | 19.18 | 82.79 |
| | 2462 | 19.36 | 86.30 |
| 802.11 n(HT40) | 2422 | 17.22 | 52.72 |
| | 2437 | 17.77 | 59.84 |
| | 2452 | 18.34 | 68.23 |

5.2 MPE Calculation

The Max Conducted Peak Output Power is 128.82mW(0.12882W) in Middle channel of 802.11b;
The best case gain of the antenna is 2.4dBi. 2.4dB logarithmic terms convert to numeric result is nearly 1.738.

For FCC:

According to the formula $S = \frac{PG}{4R^2\pi}$, we can calculate S which is MPE.

Note:

- 1) P (Watts) = Power Input to antenna = $10^{\frac{dBm}{10}} / 1000$
- 2) G (Antenna gain in numeric) = $10^{\frac{dBi}{10}} / 10$
- 3) R = distance to the center of radiation of antenna (in meter) = 20cm
- 4) MPE limit = 1mW/cm²

$$S = \frac{PG}{4R^2\pi} = \frac{128.82 \times 1.738}{4 \times 400 \times 3.14} = 0.045 \text{ mW/cm}^2 < 1 \text{ mW/cm}^2$$

For IC:

$$E.I.R.P. = P \times G = 0.12882 \times 1.738 = 0.2239W < 2.68W$$

So the device is exclusion from SAR test.

6 EUT Constructional Details

Refer to the < DS-2CD2420F-IW _External Photos > & < DS-2CD2420F-IW _Internal Photos>.

--End of the Report--