



BUREAU
VERITAS

Test Report No.: RF171227N015-2



ACCREDITED
Certificate # 2951.01

TEST REPORT

Applicant	Hangzhou Hikvision Digital Technology Co., Ltd.
Address	No. 555, Qianmo Road, Binjiang District, Hangzhou

Manufacturer or Supplier	Hangzhou Hikvision Digital Technology Co., Ltd.
Address	No. 555, Qianmo Road, Binjiang District, Hangzhou
Product	Fingerprint Access Control Terminal, Standalone Access Control Terminal
Brand Name	HIKVISION
Model	DS-K1T201EF-C
Additional Model & Model Difference	DS-K1T201EF, DS-K1T200EF, DS-K1T200EF-C, DS-K1T20XABCD-XYZ, See items 3.1
Date of tests	Dec. 27, 2017 ~ Jan. 30, 2018

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

FCC Part 15, Subpart C

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Andy Zhu Project Engineer / EMC Department	Approved by Glyn He Supervisor/ EMC Department

Date: Feb. 06, 2018

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 SUMMARY OF TEST RESULTS.....	4
2 MEASUREMENT UNCERTAINTY	4
3 GENERAL INFORMATION.....	5
3.1 GENERAL DESCRIPTION OF EUT	5
3.2 DESCRIPTION OF TEST MODES	6
3.2.1. CONFIGURATION OF SYSTEM UNDER TEST	6
3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	6
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	8
3.4 DESCRIPTION OF SUPPORT UNITS	8
4 EMISSION TEST.....	9
4.1 CONDUCTED EMISSION MEASUREMENT	9
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
4.1.2 TEST INSTRUMENTS.....	9
4.1.3 TEST PROCEDURE.....	10
4.1.4 DEVIATION FROM TEST STANDARD	10
4.1.5 TEST SETUP.....	11
4.1.6 EUT OPERATING CONDITIONS	11
4.1.7 TEST RESULTS	12
4.2 RADIATED EMISSION MEASUREMENT	14
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	14
4.2.2 TEST INSTRUMENTS.....	15
4.2.3 TEST PROCEDURE.....	16
4.2.4 DEVIATION FROM TEST STANDARD	16
4.2.5 TEST SETUP.....	17
4.2.6 EUT OPERATING CONDITIONS	17
4.2.7 TEST RESULTS	18
4.3. 20DB BANDWIDTH	24
4.3.1 LIMITS OF 20DB BANDWIDTH	24
4.3.2 TEST INSTRUMENTS.....	24
4.3.3 TEST PROCEDURE.....	25
4.3.4 DEVIATION FROM TEST STANDARD	25
4.3.5 TEST SETUP.....	25
4.3.6 EUT OPERATING CONDITION	26
4.3.7 TEST RESULTS	26
5 PHOTOGRAPHS OF THE TEST CONFIGURATION	27
6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	30



Test Report No.: RF171227N015-2

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF171227N015-2	Original release	Feb. 06, 2018



BUREAU
VERITAS

Test Report No.: RF171227N015-2

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
§15.203	Antenna Requirement	PASS	No antenna connector is used.
§15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.
§15.209	Radiated Emission	PASS	Meet the requirement of limit.
§15.215 (c)	20dB Bandwidth	PASS	Meet the requirement of limit.

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.70dB
Radiated emissions	9KHz ~ 30MHz	2.16dB
	30MHz ~ 1GHz	3.83dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



BUREAU
VERITAS

Test Report No.: RF171227N015-2

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Fingerprint Access Control Terminal, Standalone Access Control Terminal
MODEL NO.	DS-K1T201EF-C
ADDITIONAL MODEL	DS-K1T201EF, DS-K1T200EF, DS-K1T200EF-C, DS-K1T20XABCD-XYZ
FCC ID	2ADTD-K1T201EF
POWER SUPPLY	DC 12V 3.33A from Adapter input: 100-240V 50/60Hz 1.7A
MODULATION TYPE	ASK
OPERATING FREQUENCY	125KHz
NUMBER OF CHANNEL	1
ANTENNA TYPE	Loop Antenna
CABLE SUPPLIED	Signal Line: Unshielded, Detachable, 0.15m with one core

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 171227N015) for detailed product photo.
4. Additional models DS-K1T201EF, DS-K1T200EF, DS-K1T200EF-C, DS-K1T20XABCD-XYZ are identical with the test model DS-K1T201EF-C except the model number for marketing purpose.
5. The EUT can be powered by adapter as list as attach.

ADAPTER	
BRAND:	CWT
MODEL:	KPL-040F-VI
INPUT:	AC 100-240V, 50/60HZ, 1.7A
OUTPUT:	DC 12V 3.33A
CABLE:	AC Line: Unshielded. Detachable 1.4m with one core DC Line: Unshielded. Non-detachable, 1.2m.



BUREAU
VERITAS

Test Report No.: RF171227N015-2

3.2 DESCRIPTION OF TEST MODES

The EUT was tested under the following modes the final worst mode was marked in boldface and recorded in this report.

TEST FREQUENCY	TEST MODE	TEST VOLTAGE
125KHz	Card reader normal Working	DC 12V from Adapter
	Fingerprint normal Working	

3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case was found when positioned on X axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO			DESCRIPTION
	RE	PLC	BW	
A	√	√	√	DC 12V from Adapter Input:AC 120V 60Hz

Where

RE: Radiated Emission

PLC: Power Line Conducted Emission

BW: 20dB Bandwidth



BUREAU
VERITAS

Test Report No.: RF171227N015-2

RADIATED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (KHZ)	MODULATION TYPE	AXIS
A	1	125K	ASK	X

POWER LINE CONDUCTED EMISSION TEST:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (KHZ)	MODULATION TYPE	AXIS
A	1	125K	ASK	X

20dB BANDWIDTH:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (KHZ)	MODULATION TYPE	AXIS
A	1	125K	ASK	X

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE	22deg. C, 54%RH	AC 120V/60Hz	Wang
PLC	22deg. C, 54%RH	AC 120V/60Hz	Dragon
BW	25deg. C, 60%RH	AC 120V/60Hz	Robert Cheng



BUREAU
VERITAS

Test Report No.: RF171227N015-2

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as a dependent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Notebook	DELL	Inspiriron14-3442	N/A	N/A
2	Wireless Router	TP-LINK	TL-WDR3310	N/A	N/A
3	USB Driver 3.0	Kingston	DTSE9G2/16GB	N/A	N/A

NO.	DESCRIPTION OF THE ABOVE SUPPORT UNITS
1,	AC Line: Unshielded, Detachable 1.5m ;DC Line: Unshielded, Non-detachable , 1.5m.
2	RJ45 Line: Unshielded, Detachable, 8m.
3	N/A



BUREAU
VERITAS

Test Report No.: RF171227N015-2

4 EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTES: (1) The lower limit shall apply at the transition frequencies.
(2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
(3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101588	Jan. 22,17	Jan. 21,18
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Mar. 04,17	Mar. 03,18
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Apr. 05,17	Apr. 04,18
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Jan. 08,18	Jan. 07,19
Test software	ADT	ADT_Cond V7.3.7	N/A	N/A	N/A

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in shielding room 553.



BUREAU
VERITAS

Test Report No.: RF171227N015-2

4.1.3 TEST PROCEDURE

The basic test procedure was in accordance with ANSI C63.4:2014 (section 7).

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20dB) were not recorded.

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value

4.1.4 DEVIATION FROM TEST STANDARD


No deviation.



BUREAU
VERITAS

Test Report No.: RF171227N015-2

4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.

4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power of all equipment.
- b. EUT was operated according to the type description in manufacturer's specifications or the User's Manual.



BUREAU
VERITAS


Test Report No.: RF171227N015-2

4.1.7 TEST RESULTS

TEST MODE	Card Reader	6DB BANDWIDTH	9 kHz
TEST VOLTAGE	DC 12V from Adapter Input:AC 120V 60Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	19deg. C, 43% RH	TESTED BY	Dragon

No.	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	(dB)	(dB)	(dB)	(dB)
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16307	10.22	34.62	18.37	44.84	28.59	65.31	55.31	-20.47	-26.72
2	0.25144	10.22	23.72	7.09	33.94	17.31	61.71	51.71	-27.77	-34.40
3	0.53250	10.22	28.17	21.23	38.39	31.45	56.00	46.00	-17.61	-14.55
4	2.86350	10.22	12.29	7.75	22.51	17.97	56.00	46.00	-33.49	-28.03
5	3.49125	10.22	11.23	6.22	21.45	16.44	56.00	46.00	-34.55	-29.56
6	18.09825	10.26	45.55	28.56	55.81	38.82	60.00	50.00	-4.19	-11.18

REMARKS: The emission levels of other frequencies were very low against the limit.






BUREAU
VERITAS

Test Report No.: RF171227N015-2

TEST MODE	Card Reader	6DB BANDWIDTH	9 kHz
TEST VOLTAGE	DC 12V from Adapter Input:AC 120V 60Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	19deg. C, 43% RH	TESTED BY	Dragon

No.	Freq. [MHz]	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	(dB)	(dB)	(dB)	(dB)
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15924	10.01	36.16	17.97	46.17	27.98	65.50	55.50	-19.33	-27.52
2	0.52801	10.02	29.46	23.01	39.48	33.03	56.00	46.00	-16.52	-12.97
3	3.50250	10.02	12.28	7.39	22.30	17.41	56.00	46.00	-33.70	-28.59
4	15.45000	10.13	8.43	3.73	18.56	13.86	60.00	50.00	-41.44	-36.14
5	16.85850	10.13	29.05	12.60	39.18	22.73	60.00	50.00	-20.82	-27.27
6	18.10050	10.14	31.28	25.51	41.42	35.65	60.00	50.00	-18.58	-14.35

REMARKS: The emission levels of other frequencies were very low against the limit.





BUREAU
VERITAS

Test Report No.: RF171227N015-2

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart C, Section 15.209

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_{uV/m}) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
4. The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)

Example:

$$\begin{aligned}13.56\text{MHz} &= 15848\text{uV/m} & 30\text{m} \\ &= 84\text{dB}_{\text{uV/m}} & 30\text{m} \\ &= 84+20\log(30/3)^2 & 3\text{m} \\ &= 124\text{dB}_{\text{uV/m}}\end{aligned}$$



BUREAU
VERITAS

Test Report No.: RF171227N015-2

4.2.2 TEST INSTRUMENTS

FREQUENCY 9KHz-30MHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101564	Feb. 27,17	Feb. 26,18
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	1519B-045	May 31,17	May 30,18
Amplifier	Burjeon	BPA-530	100210	Apr. 05,17	Apr. 04,18
Test Software	ADT	ADT_Radiated_V8.7.07	N/A	N/A	N/A

NOTES:

1. The test was performed in 10m Chamber.
2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRRG/CHINA and NIM/CHINA.
3. The FCC Site Registration No. is 749762.

FREQUENCY 30MHz-1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Mar. 11,17	Mar. 10,18
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 28, 17	Jul. 27, 18
Amplifier	Burjeon	BPA-530	100220	Apr. 05,17	Apr. 04,18
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Mar. 06,17	Mar. 05,18
Test software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A

NOTES:

1. The test was performed in 966 Chamber
2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRRG/CHINA and NIM/CHINA.
3. The FCC Site Registration No. is 749762.



BUREAU
VERITAS

Test Report No.: RF171227N015-2

4.2.3 TEST PROCEDURE

< Below 30MHz >

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meters Semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

<30MHz~1GHz >

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
4. Margin value = Emission level – Limit value.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.


Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China


Tel.: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

4.2.5 TEST SETUP

<Frequency Range below 30MHz>



<Frequency Range 30MHz~1GHz >



* : depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

4.2.6 EUT OPERATING CONDITIONS

- Turn on the power supply of the EUT.
- EUT was operated according to the type description in manufacturer's specifications or the User's Manual.



BUREAU
VERITAS

Test Report No.: RF171227N015-2


4.2.7 TEST RESULTS

TEST MODE	Card Reader	FREQUENCY RANGE	9 -150KHz
TEST VOLTAGE	DC 12V from Adapter Input:AC 120V 60Hz	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 200Hz
ENVIRONMENTAL CONDITIONS	21deg. C, 57% RH	TESTED BY: Xin Peng	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10M								
No .	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	0.0128	-9.63	40.07	30.44	125.46	-95.02	100	75
2	0.0273	-10.15	32.63	22.48	118.88	-96.40	100	25
3	0.0411	-10.28	30.42	20.14	115.33	-95.19	100	36
4	0.0756	-10.41	24.56	14.15	110.03	-95.88	100	42
5	0.1009	-10.35	21.12	10.77	107.52	-96.75	100	265
6	0.1294	-10.48	39.58	29.10	105.36	-76.26	100	78
7	0.0128	-9.63	40.07	30.44	125.46	-95.02	100	75

REMARKS:

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 0.009-0.15MHz.
4. Only emissions significantly above equipment noise floor are reported.





BUREAU
VERITAS


Test Report No.: RF171227N015-2

TEST MODE	Card Reader	FREQUENCY RANGE	9 -150KHz
TEST VOLTAGE	DC 12V from Adapter Input:AC 120V 60Hz	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 200Hz
ENVIRONMENTAL CONDITIONS	21deg. C, 57% RH	TESTED BY: Xin Peng	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	0.0130	-9.64	35.60	25.96	125.33	-99.37	100	125
2	0.0352	-10.27	34.65	24.38	116.67	-92.29	100	41
3	0.0484	-10.30	25.33	15.03	113.91	-98.88	100	75
4	0.0681	-10.38	26.15	15.77	110.94	-95.17	100	24
5	0.0804	-10.41	22.93	12.52	109.50	-96.98	100	325
6	0.1297	-10.48	39.25	28.77	105.34	-76.57	100	347
7	0.0130	-9.64	35.60	25.96	125.33	-99.37	100	125

REMARKS:

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 0.009-0.15MHz.
4. Only emissions significantly above equipment noise floor are reported.





BUREAU
VERITAS


Test Report No.: RF171227N015-2

TEST MODE	Card Reader	FREQUENCY RANGE	150KHz-30MHz
TEST VOLTAGE	DC 12V from Adapter Input:AC 120V 60Hz	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 200Hz
ENVIRONMENTAL CONDITIONS	21deg. C, 57% RH	TESTED BY: Xin Peng	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	0.1836	-10.53	28.20	17.67	102.32	-84.65	100	42
2	3.6984	-10.43	17.64	7.21	69.54	-62.33	100	12
3	7.2170	-10.31	16.42	6.11	69.54	-63.43	100	37
4	10.4147	-10.13	15.30	5.17	69.54	-64.37	100	296
5	14.3922	-9.95	16.22	6.27	69.54	-63.27	100	15
6	17.2839	-10.16	14.98	4.82	69.54	-64.72	100	265
7	0.1836	-10.53	28.20	17.67	102.32	-84.65	100	42

REMARKS:

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 0.15-30MHz.
4. Only emissions significantly above equipment noise floor are reported.





BUREAU
VERITAS


Test Report No.: RF171227N015-2

TEST MODE	Card Reader	FREQUENCY RANGE	150KHz-30MHz
TEST VOLTAGE	DC 12V from Adapter Input:AC 120V 60Hz	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 200Hz
ENVIRONMENTAL CONDITIONS	21deg. C, 57% RH	TESTED BY: Xin Peng	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 M								
No .	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	0.1910	-10.53	30.31	19.78	101.98	-82.20	100	75
2	2.4074	-10.50	15.65	5.15	69.54	-64.39	100	52
3	5.8887	-10.33	16.94	6.61	69.54	-62.93	100	78
4	9.6498	-10.17	15.75	5.58	69.54	-63.96	100	36
5	12.2952	-10.05	14.02	3.97	69.54	-65.57	100	360
6	16.7503	-10.10	16.03	5.93	69.54	-63.61	100	265
7	0.1910	-10.53	30.31	19.78	101.98	-82.20	100	75

REMARKS:

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 0.15-30MHz
4. Only emissions significantly above equipment noise floor are reported.





BUREAU
VERITAS


Test Report No.: RF171227N015-2

TEST MODE	Card Reader	FREQUENCY RANGE	30-1000MHz
TEST VOLTAGE	DC 12V from Adapter Input:AC 120V 60Hz	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	25deg. C, 55% RH	TESTED BY: Arnold	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	30.00	-5.47	39.36	33.89	40.00	-6.11	100	0
2	298.93	-7.13	38.16	31.03	46.00	-14.97	100	0
3	309.81	-5.99	38.83	32.84	46.00	-13.16	100	0
4	420.18	-3.28	34.49	31.21	46.00	-14.79	100	0
5	454.37	-1.88	34.82	32.94	46.00	-13.06	100	0
6	776.15	4.20	37.14	41.34	46.00	-4.66	100	0

REMARKS:

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 30MHz to 1000MHz.
4. Only emissions significantly above equipment noise floor are reported.





BUREAU
VERITAS


Test Report No.: RF171227N015-2

TEST MODE	Card Reader	FREQUENCY RANGE	30-1000MHz
TEST VOLTAGE	DC 12V from Adapter Input:AC 120V 60Hz	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	25deg. C, 55% RH	TESTED BY: Arnold	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	42.44	-12.22	47.38	35.16	40.00	-4.84	100	0
2	57.98	-18.08	51.69	33.61	40.00	-6.39	100	0
3	309.81	-5.99	48.69	42.70	46.00	-3.30	100	0
4	454.37	-1.88	41.59	39.71	46.00	-6.29	100	0
5	620.71	2.95	41.31	44.26	46.00	-1.74	100	0
6	944.04	6.81	32.36	39.17	46.00	-6.83	100	0

REMARKS:

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 30MHz to 1000MHz.
4. Only emissions significantly above equipment noise floor are reported.





BUREAU
VERITAS

Test Report No.: RF171227N015-2

4.3. 20dB BANDWIDTH

4.3.1 LIMITS OF 20dB BANDWIDTH

Reporting only.

4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	May 19,17	May 18,18
Power Sensor	Keysight	U2021XA	MY55060018	May 19,17	May 18,18
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 21, 17	Oct.20, 18
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.05,17	Sep. 04,18
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 08,17	Nov. 07,18
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 04,17	Nov. 03,18
Signal Generator	Agilent	N5183A	MY50140980	Nov. 04,17	Nov. 03,18
Agile Signal Generator	Agilent	8645A	Agilent	Sep.01, 17	Aug.31, 18
Spectrum Analyzer	Keysight	N9020A	MY55400499	Apr. 10,17	Apr. 09,18
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Dec.05, 17	Dec. 04, 18
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug.10, 17	Aug.09, 18
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A	N/A
DC Source	Keysight	E3642A	MY56146098	N/A	N/A

NOTE:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.




4.3.3 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP





BUREAU
VERITAS

Test Report No.: RF171227N015-2


4.3.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously.

4.3.7 TEST RESULTS

CHANNEL	CHANNEL FREQUENCY (KHz)	20dB BANDWIDTH (Hz)
1	125	764

Lower & Upper Test Frequency Point (MHz)	Test Frequency (KHz)	P/F
Lower	124.6223	PASS
Upper	125.3864	PASS





BUREAU
VERITAS

Test Report No.: RF171227N015-2

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST






BUREAU
VERITAS

Test Report No.: RF171227N015-2



<Frequency Range - Below 30MHz>





Test Report No.: RF171227N015-2

<Frequency Range 30MHz~1GHz>





Test Report No.: RF171227N015-2

6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---