



Revision Record			
Version	Description	Date	Remark
00	Original	2019-02-15	/

Authorized for issue by:			
		Vincent Zhu	
		<hr/> Vincent Zhu /Project Engineer	
		Parlam Zhan	
		<hr/> Parlam Zhan /Reviewer	

## **2 Contents**

	Page
<b>1 COVER PAGE</b> .....	<b>1</b>
<b>2 CONTENTS</b> .....	<b>3</b>
<b>3 GENERAL INFORMATION</b> .....	<b>4</b>
3.1 GENERAL DESCRIPTION OF E.U.T. .....	4
3.2 TEST LOCATION .....	4
3.3 TEST FACILITY .....	5
<b>4 TEST STANDARDS AND LIMITS</b> .....	<b>6</b>
4.1 FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS: .....	6
4.2 IC RADIOFREQUENCY RADIATION EXPOSURE LIMITS: .....	6
<b>5 MEASUREMENT AND CALCULATION</b> .....	<b>7</b>
5.1 MAXIMUM TRANSMIT POWER .....	7
5.2 MPE CALCULATION .....	8

### **3 General Information**

#### **3.1 General Description of E.U.T.**

Power supply:	DC 12V by adapter
Test voltage:	AC 120V 60Hz
Antenna Gain	2.6 dBi
Antenna Type	PCB Antenna
Channel Spacing	5MHz
Modulation Type	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels	802.11b/g/n(HT20):11 802.11n(HT40):7
Operation Frequency	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz

#### **3.2 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China.

Tel: +86 21 6191 5666

Fax: +86 21 6191 5678

### **3.3 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- NVLAP (Certificate No. 201034-0)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

- FCC –Designation Number: CN5033**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

- Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

- VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

## 4 Test Standards and Limits

### 4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm <sup>2</sup> )	Averaging time(minutes)
300MHz~1.5GHz	f/1500	30
1.5GHz~100GHz	1.0	30

### 4.2 IC Radiofrequency radiation exposure limits:

According to RSS-102 section 2.5.2, RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

For 2.4G device, the limit of worse case is 2.68 W

## 5 Measurement and Calculation

### 5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM190101059701

Test Mode	Test Channel	Ant	Power [dBm]	Power [mW]
11B	2412	Ant1	15.84	38.37
11B	2442	Ant1	16.38	43.45
11B	2472	Ant1	16.49	<b>44.57</b>
11G	2412	Ant1	14.14	25.94
11G	2442	Ant1	14.77	29.99
11G	2472	Ant1	14.98	31.48
11N20SISO	2412	Ant1	14.02	25.23
11N20SISO	2442	Ant1	14.67	29.31
11N20SISO	2472	Ant1	14.86	30.62
11N40SISO	2422	Ant1	11.69	14.76
11N40SISO	2437	Ant1	11.98	15.78
11N40SISO	2452	Ant1	12.15	16.41

## 5.2 MPE Calculation

The Max Conducted Peak Output Power is 44.57mW;

The best case gain of the antenna is 2.6dBi. 2.6dB logarithmic terms convert to numeric result is nearly 1.82

For FCC:

According to the formula  $S = \frac{PG}{4R^2\pi}$ , we can calculate S which is MPE.

Note:

- 1) P (Watts)
- 2) G (Antenna gain in numeric)
- 3) R = distance to the center of radiation of antenna (in meter) = 20cm
- 4) MPE limit = 1mW/cm<sup>2</sup>

$$S = \frac{PG}{4R^2\pi} = \frac{44.57 \times 1.82}{4 \times 400 \times 3.14} = 0.02 \text{ mW/cm}^2 < 1 \text{ mW/cm}^2$$

For IC:

$$E.I.R.P. = P \times G = 0.04457 \times 1.82 = 0.08 \text{ W} < 2.68 \text{ W}$$

So the device is exclusion from SAR test.

**--End of the Report--**