

# TEST REPORT

**Application No.:** SHEM1908016759CR  
**FCC ID:** 2ADTD-MCW405  
**Applicant:** Hangzhou Hikvision Digital Technology Co., Ltd  
**Address of Applicant:** No.555 Qianmo Road, Binjiang District, Hangzhou 310052, China  
**Manufacturer:** Hangzhou Hikvision Digital Technology Co., Ltd.  
**Address of Manufacturer:** No.555 Qianmo Road, Binjiang District, Hangzhou 310052, China  
**Factory:**  
1, Hangzhou Hikvision Technology Co., Ltd.  
2, Hangzhou Hikvision Electronics Co., Ltd.  
3, Hangzhou Hikvision Digital Technology Co., Ltd.  
4, Chongqing Hikvision technology Co., Ltd.  
**Address of Factory:**  
1, No.700, Dongliu Road, Binjiang District, Hangzhou City, Zhejiang, 310052, China  
2, No.299, Qiushi Road, Tonglu Economic Development Zone, Tonglu County, Hangzhou, Zhejiang, 310052, China.  
3, No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China  
4, No. 118, Haikang Road, Area C, Jianqiao Industrial Park, Dadukou District, Chongqing, 401325, China

### **Equipment Under Test (EUT):**

**EUT Name:** Body Camera

**Model No.:** DS-MCW405,DS-MCW405/32G,DS-MCW405/64G,DS-MCW405/128G,DS-MCW405/32G/GPS/WIFI,DS-MCW405/64G/GPS/WIFI,DS-MCW405/128G/GPS/WIFI,DS-MCW4A5,DS-MCW4A5/32G,DS-MCW4A5/64G,DS-MCW4A5/128G,DS-MCW4A5/32G/GPS/WIFI,DS-MCW4A5/64G/GPS/WIFI,DS-MCW4A5/128G/GPS/WIFI,DS-MCW401-N,DS-MCW401-N/32G,DS-MCW401-N/64G,DS-MCW401-N/128G,DS-MCW401-N/32G/GPS/WIFI,DS-MCW401-N/64G/GPS/WIFI,DS-MCW401-N/128G/GPS/WIFI,DS-MCXXXXXXXXXXXXXXXXXXXX,DS-MDXXXXXXXXXXXXXXXXXXXX,DS-MHXXXXXXXXXXXXXXXXXXXX ☺

>Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.

Trade mark: HIKVISION

**Standard(s) :** 47 CFR Part 15, Subpart C 15.247

**Date of Receipt:** 2019-08-30

**Date of Test:** 2019-09-27 to 2019-10-10

**Date of Issue:** 2019-10-15

## Test Result:

\* In the configuration tested, the EUT complied with the standards specified above.

paran zhan

Parlam Zhan  
E&F Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

approvals in writing. Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,**

or email: CN.Doccheck@sgs.com  
NO.588 West.Jinlu.Road,Songjiang.District,Shanghai,China 201612  
中国·上海·松江区金都西路588号 邮编: 201612  
(86-21)61915666 f(86-21)61915678 www.sgsgroup.com.cn  
(86-21)61915666 f(86-21)61915678 e sgs.china@sgs.com

#### Members of the SOSA Core (SOSA.C)



Revision Record			
Version	Description	Date	Remark
00	Original	2019-10-15	/

Authorized for issue by:				
		Vincent Zhu		
		_____ Vincent Zhu / Project Engineer		
		Parlam Zhan		
		_____ Parlam Zhan / Reviewer		

## 2 Test Summary

<b>Radio Spectrum Technical Requirement</b>				
<b>Item</b>	<b>Standard</b>	<b>Method</b>	<b>Requirement</b>	<b>Result</b>
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Customer Declaration
Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)	Pass

<b>Radio Spectrum Matter Part</b>				
<b>Item</b>	<b>Standard</b>	<b>Method</b>	<b>Requirement</b>	<b>Result</b>
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(1)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

**Declaration of EUT Family Grouping:**

Note: There are series models mentioned in this report, and they are the identical in electrical and electronic characters. Only the model DS-MCW405 was tested since their differences were the model number and appearance.

### **3 Contents**

	Page
<b>1 COVER PAGE</b>	<b>1</b>
<b>2 TEST SUMMARY</b>	<b>3</b>
<b>3 CONTENTS</b>	<b>4</b>
<b>4 GENERAL INFORMATION</b>	<b>5</b>
4.1 DETAILS OF E.U.T	5
4.2 DESCRIPTION OF SUPPORT UNITS	5
4.3 MEASUREMENT UNCERTAINTY	5
4.4 TEST LOCATION	6
4.5 TEST FACILITY	6
4.6 DEVIATION FROM STANDARDS	6
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
<b>5 EQUIPMENT LIST</b>	<b>7</b>
<b>6 RADIO SPECTRUM TECHNICAL REQUIREMENT</b>	<b>8</b>
6.1 ANTENNA REQUIREMENT	8
6.2 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM HOPPING SEQUENCE	9
<b>7 RADIO SPECTRUM MATTER TEST RESULTS</b>	<b>10</b>
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz)	10
7.2 CONDUCTED PEAK OUTPUT POWER	14
7.3 20dB BANDWIDTH	15
7.4 CARRIER FREQUENCIES SEPARATION	16
7.5 HOPPING CHANNEL NUMBER	17
7.6 DWELL TIME	18
7.7 CONDUCTED BAND EDGES MEASUREMENT	19
7.8 CONDUCTED SPURIOUS EMISSIONS	20
7.9 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	21
7.10 RADIATED SPURIOUS EMISSIONS	42
<b>8 TEST SETUP PHOTOGRAPHS</b>	<b>50</b>
<b>9 EUT CONSTRUCTIONAL DETAILS</b>	<b>50</b>

## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	DC 5V by adapter
Test voltage:	AC 120V 60Hz
Cable:	DC Cable 1m for EUT
Antenna Gain	2.15dBi
Antenna Type	PCB Antenna
Channel Spacing	1MHz
Modulation Type	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channels	79
Operation Frequency	2402MHz to 2480MHz
Spectrum Spread Technology	Frequency Hopping Spread Spectrum(FHSS)

### 4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop	Lenovo	ThinkPad X100e	/
SecureCRT	VanDyke	V 6.2.0	/
Serial port adapter plate	/	Test Plate 3	/
AC Adapter	DVE	DSA-12G-12FEU	/

### 4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 8.4 \times 10^{-8}$
2	Timeout	$\pm 2s$
3	Duty cycle	$\pm 0.37\%$
4	Occupied Bandwidth	$\pm 3\%$
5	RF conducted power	$\pm 0.6\text{dB}$
6	RF power density	$\pm 2.84\text{dB}$
7	Conducted Spurious emissions	$\pm 0.75\text{dB}$
8	RF Radiated power	$\pm 4.6\text{dB}$ (Below 1GHz) $\pm 4.1\text{dB}$ (Above 1GHz)
9	Radiated Spurious emission test	$\pm 4.2\text{dB}$ (Below 30MHz) $\pm 4.4\text{dB}$ (30MHz-1GHz) $\pm 4.8\text{dB}$ (1GHz-18GHz) $\pm 5.2\text{dB}$ (Above 18GHz)
10	Temperature test	$\pm 1^\circ\text{C}$
11	Humidity test	$\pm 3\%$
12	Supply voltages	$\pm 1.5\%$
13	Time	$\pm 3\%$

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



#### **4.4 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch  
588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China  
Tel: +86 21 6191 5666      Fax: +86 21 6191 5678

No tests were sub-contracted.

#### **4.5 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- NVLAP (Certificate No. 201034-0)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

- FCC –Designation Number: CN5033**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

- Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

IC Registration No.: 8617A-1. CAB identifier: CN0020.

- VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

#### **4.6 Deviation from Standards**

None

#### **4.7 Abnormalities from Standard Conditions**

None

## 5 Equipment List

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
<b>Conducted Emission at Mains Terminals (150kHz-30MHz)</b>					
EMI test receiver	R&S	ESR7	SHEM162-1	2018-12-20	2019-12-19
LISN	Schwarzbeck	NSLK8127	SHEM061-1	2018-12-20	2019-12-19
LISN	EMCO	3816/2	SHEM019-1	2018-12-20	2019-12-19
Pulse limiter	R&S	ESH3-Z2	SHEM029-1	2018-12-20	2019-12-19
Shielding Room	ZHONGYU	8*4*3M	SHEM079-2	2017-12-20	2020-12-19
CE test Cable	/	CE01	/	2018-12-26	2019-12-25
<b>RF Conducted Test</b>					
Spectrum Analyzer	R&S	FSP-30	SHEM002-1	2018-12-20	2019-12-19
Spectrum Analyzer	Agilent	N9020A	SHEM181-1	2019-08-13	2020-08-12
Signal Generator	R&S	SMR20	SHEM006-1	2019-08-13	2020-08-12
Signal Generator	Agilent	N5182A	SHEM182-1	2019-08-13	2020-08-12
Communication Tester	R&S	CMW270	SHEM183-1	2019-08-13	2020-08-12
Switcher	Tonscend	JS0806	SHEM184-1	2019-08-13	2020-08-12
Power Sensor	Keysight	U2021XA * 4	SHEM184-1	2019-08-13	2020-08-12
Splitter	Anritsu	MA1612A	SHEM185-1	/	/
Coupler	e-meca	803-S-1	SHEM186-1	/	/
High-low Temp Cabinet	Suzhou Zhihe	TL-40	SHEM087-1	2017-09-25	2020-09-24
AC Power Stabilizer	WOCEN	6100	SHEM045-1	2018-12-26	2019-12-25
DC Power Supply	MCN	MCH-303A	SHEM210-1	2018-12-26	2019-12-25
Conducted test Cable	/	RF01~RF04	/	2018-12-26	2019-12-25
<b>RF Radiated Test</b>					
EMI test Receiver	R&S	ESU40	SHEM051-1	2018-12-20	2019-12-19
Spectrum Analyzer	R&S	FSP-30	SHEM002-1	2018-12-20	2019-12-19
Loop Antenna (9kHz-30MHz)	Schwarzbeck	FMZB1519	SHEM135-1	2017-04-10	2020-04-09
Antenna (25MHz-2GHz)	Schwarzbeck	VULB9168	SHEM048-1	2017-02-28	2020-02-27
Antenna (25MHz-2GHz)	Schwarzbeck	VULB9168	SHEM202-1	2019-04-30	2022-04-29
Horn Antenna (1-18GHz)	Schwarzbeck	HF906	SHEM009-1	2017-10-24	2020-10-23
Horn Antenna (1-18GHz)	Schwarzbeck	BBHA9120D	SHEM050-1	2017-01-14	2020-01-13
Horn Antenna (14-40GHz)	Schwarzbeck	BBHA 9170	SHEM049-1	2017-12-03	2020-12-02
Pre-amplifier (9KHz-2GHz)	CLAVIIO	BDLNA-0001	SHEM164-1	2019-08-13	2020-08-12
Pre-amplifier (1-18GHz)	CLAVIIO	BDLNA-0118	SHEM050-2	2019-08-13	2020-08-12
High-amplifier (14-40GHz)	Schwarzbeck	10001	SHEM049-2	2018-12-20	2019-12-19
Signal Generator	R&S	SMR40	SHEM058-1	2019-08-13	2020-08-12
Band Filter	LORCH	9BRX-875/X150	SHEM156-1	/	/
Band Filter	LORCH	13BRX-1950/X500	SHEM083-2	/	/
Band Filter	LORCH	5BRX-2400/X200	SHEM155-1	/	/
Band Filter	LORCH	5BRX-5500/X1000	SHEM157-2	/	/
High pass Filter	Wainwright	WHK3.0/18G	SHEM157-1	/	/
High pass Filter	Wainwright	WHKS1700	SHEM157-3	/	/
Semi/Fully Anechoic	ST	11*6*6M	SHEM078-2	2017-07-22	2020-07-21
RE test Cable	/	RE01, RE02, RE06	/	2018-12-26	2019-12-25

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(c)

#### 6.1.2 Conclusion

Standard Requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is PCB antenna and no consideration of replacement. The best case gain of the antenna is 2.15dBi.



## **6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence**

### **6.2.1 Test Requirement:**

47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)

### **6.2.2 Conclusion**

Standard Requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1):

According to Technical Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

> Number of shift register stages: 9

> Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits

> Longest sequence of zeros: 8 (non-inverted signal)

Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

Each frequency used equally on the average by each transmitter.

According to Technical Specification, the receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g):

According to Technical Specification, the system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h):

According to Technical specification, the system incorporates with an adaptive system to detect other user within the spectrum band s

## 7 Radio Spectrum Matter Test Results

## 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

## Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

## Limit:

Frequency of emission(MHz)	Conducted limit(dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


### 7.1.1 E.U.T. Operation

## Operating Environment:

Temperature: 22 °C      Humidity: 50 % RH      Atmospheric Pressure: 1020 mbar

Test mode a:Charge + TX\_non-Hop mode\_Keep the EUT in charging and continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.1.2 Test Setup Diagram




### **7.1.3 Measurement Procedure and Data**

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50 $\mu$ H + 50hm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

Mode:a; Line:Live Line




LISN : LINE  
EUT/Project No : 16758CR  
Test Mode : a

Freq (MHz)	Read level (dBuV)	LISN Factor (dB)	Cable Loss (dB)	Emission Level (dBuV)	Over Limit (dBuV)	Over Limit (dB)	Remark
1 0.15	18.22	0.09	10.00	28.31	55.87	-27.56	Average
2 0.15	29.68	0.09	10.00	39.77	65.87	-26.10	QP
3 0.21	23.25	0.07	10.00	33.32	53.18	-19.86	Average
4 0.21	34.67	0.07	10.00	44.74	63.18	-18.44	QP
5 0.26	16.11	0.07	10.00	26.18	51.34	-25.16	Average
6 0.26	27.20	0.07	10.00	37.27	61.34	-24.07	QP
7 0.32	15.40	0.08	10.00	25.48	49.80	-24.32	Average
8 0.32	24.30	0.08	10.00	34.38	59.80	-25.42	QP
9 0.37	11.22	0.08	10.00	21.30	48.43	-27.13	Average
10 0.37	23.68	0.08	10.00	33.76	58.43	-24.67	QP
11 0.42	9.80	0.08	10.00	19.88	47.46	-27.58	Average
12 0.42	23.25	0.08	10.00	33.33	57.46	-24.13	QP

Notes: Emission Level = Read Level + LISN Factor + Cable loss

Mode:a; Line:Neutral Line



LISN : NEUTRAL  
 EUT/Project No : 16758CR  
 Test Mode : a

Freq (MHz)	Read level (dBuV)	LISN Factor (dB)	Cable Loss (dB)	Emission Level (dBuV)	Over Limit (dBuV)	Over Limit (dB)	Remark
1 0.17	16.69	0.07	10.00	26.76	54.94	-28.18	Average
2 0.17	27.39	0.07	10.00	37.46	64.94	-27.48	QP
3 0.21	21.01	0.06	10.00	31.07	53.27	-22.20	Average
4 0.21	32.90	0.06	10.00	42.96	63.27	-20.31	QP
5 0.27	12.77	0.06	10.00	22.83	51.20	-28.37	Average
6 0.27	25.09	0.06	10.00	35.15	61.20	-26.05	QP
7 0.37	6.58	0.06	10.00	16.64	48.43	-31.79	Average
8 0.37	23.63	0.06	10.00	33.69	58.43	-24.74	QP
9 0.54	13.08	0.06	10.00	23.14	46.00	-22.86	Average
10 0.54	26.01	0.06	10.00	36.07	56.00	-19.93	QP
11 0.74	11.75	0.07	10.00	21.82	46.00	-24.18	Average
12 0.74	22.99	0.07	10.00	33.06	56.00	-22.94	QP

Notes: Emission Level = Read Level + LISN Factor + Cable loss

## 7.2 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(1)

Test Method: ANSI C63.10 (2013) Section 7.8.5

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation


### 7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 20 °C Humidity: 50 % RH Atmospheric Pressure: 1010 mbar

Test mode a:Charge + TX\_non-Hop mode\_Keep the EUT in charging and continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.2.2 Test Setup Diagram



### 7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEM190801675901

### 7.3 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247(a)(1)

Test Method: ANSI C63.10 (2013) Section 7.8.7


#### 7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 20 °C Humidity: 50 % RH Atmospheric Pressure: 1010 mbar

Test mode a:Charge + TX\_non-Hop mode\_Keep the EUT in charging and continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

#### 7.3.2 Test Setup Diagram



#### 7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEMA190801675901

## 7.4 Carrier Frequencies Separation


Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)  
Test Method: ANSI C63.10 (2013) Section 7.8.2  
Limit: 2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W

### 7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 20 °C      Humidity: 50 % RH      Atmospheric Pressure: 1010 mbar  
Test mode a:Charge + TX\_non-Hop mode\_Keep the EUT in charging and continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.4.2 Test Setup Diagram



### 7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEM190801675901

## 7.5 Hopping Channel Number

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii)

Test Method: ANSI C63.10 (2013) Section 7.8.3

Limit:

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75


### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 20 °C Humidity: 50 % RH Atmospheric Pressure: 1010 mbar

Test mode a:Charge + TX\_non-Hop mode\_Keep the EUT in charging and continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.5.2 Test Setup Diagram



### 7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEMA190801675901

## 7.6 Dwell Time

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii)

Test Method: ANSI C63.10 (2013) Section 7.8.4

Limit:

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period


### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 20 °C Humidity: 50 % RH Atmospheric Pressure: 1010 mbar

Test mode a:Charge + TX\_non-Hop mode\_Keep the EUT in charging and continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.6.2 Test Setup Diagram



### 7.6.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEMA190801675901

## 7.7 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)  
Test Method: ANSI C63.10 (2013) Section 7.8.6  
Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))


### 7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 20 °C      Humidity: 50 % RH      Atmospheric Pressure: 1010 mbar

Test mode a:Charge + TX\_non-Hop mode\_Keep the EUT in charging and continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.7.2 Test Setup Diagram



### 7.7.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEMA190801675901

## 7.8 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 7.8.8

Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))


### 7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 20 °C Humidity: 50 % RH Atmospheric Pressure: 1010 mbar

Test mode a:Charge + TX\_non-Hop mode\_Keep the EUT in charging and continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.8.2 Test Setup Diagram



### 7.8.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEMA190801675901

## **7.9 Radiated Emissions which fall in the restricted bands**

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 20 °C      Humidity: 50 % RH      Atmospheric Pressure: 1010 mbar  
Test mode      a:Charge + TX\_non-Hop mode\_Keep the EUT in charging and continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.9.2 Test Setup Diagram




### **7.9.3 Measurement Procedure and Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.


Mode:a; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2329.96	48.79	25.95	3.03	37.37	40.40	74.00	-33.60	Peak
2390.00	46.50	26.03	3.15	37.40	38.28	74.00	-35.72	Peak
2402.25	104.26	26.05	3.14	37.40	96.05	74.00	22.05	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:a; Polarization:Vertical; Modulation:GFSK; ; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2328.18	48.79	25.94	3.03	37.37	40.39	74.00	-33.61	Peak
2390.00	46.47	26.03	3.15	37.40	38.25	74.00	-35.75	Peak
2402.25	104.02	26.05	3.14	37.40	95.81	74.00	21.81	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:a; Polarization:Horizontal; Modulation:GFSK; ; Channel:High

**Antenna Polarity :HORIZONTAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2480.03	103.04	26.17	3.14	37.57	94.78	74.00	20.78	Peak
2483.50	64.90	26.18	3.14	37.57	56.65	74.00	-17.35	Peak
2483.88	61.43	26.18	3.14	37.57	53.18	74.00	-20.82	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:a; Polarization:Horizontal; Modulation:GFSK; ; Channel:High

**Antenna Polarity :HORIZONTAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2479.96	100.04	26.17	3.14	37.57	91.78	54.00	37.78	Average
2483.50	60.01	26.18	3.14	37.57	51.76	54.00	-2.24	Average
2483.96	55.65	26.18	3.14	37.57	47.40	54.00	-6.60	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:a; Polarization:Vertical; Modulation:GFSK; ; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2480.10	102.53	26.17	3.14	37.57	94.27	74.00	20.27	Peak
2483.50	64.48	26.18	3.14	37.57	56.23	74.00	-17.77	Peak
2483.81	61.91	26.18	3.14	37.57	53.66	74.00	-20.34	Peak


Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:a; Polarization:Vertical; Modulation:GFSK; ; Channel:High

**Antenna Polarity :VERTICAL**


Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit	Over Line Limit	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	dB	
2479.96	100.02	26.17	3.14	37.57	91.76	54.00	37.76	Average	
2483.50	59.98	26.18	3.14	37.57	51.73	54.00	-2.27	Average	
2483.96	55.63	26.18	3.14	37.57	47.38	54.00	-6.62	Average	

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:a; Polarization:Horizontal; Modulation: $\pi/4$  DQPSK; ; Channel:Low**Antenna Polarity :HORIZONTAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2338.76	48.67	25.96	3.08	37.37	40.34	74.00	-33.66	Peak
2390.00	46.02	26.03	3.15	37.40	37.80	74.00	-36.20	Peak
2402.25	101.59	26.05	3.14	37.40	93.38	74.00	19.38	Peak


Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:a; Polarization:Vertical; Modulation: $\pi/4$  DQPSK; ; Channel:Low

Antenna Polarity :VERTICAL


Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2342.33	48.72	25.96	3.08	37.37	40.39	74.00	-33.61	Peak
2390.00	45.73	26.03	3.15	37.40	37.51	74.00	-36.49	Peak
2401.95	101.51	26.05	3.14	37.40	93.30	74.00	19.30	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:a; Polarization:Horizontal; Modulation: $\pi/4$  DQPSK; ; Channel:High**Antenna Polarity :HORIZONTAL**


Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2480.10	101.69	26.17	3.14	37.57	93.43	74.00	19.43	Peak
2483.50	66.86	26.18	3.14	37.57	58.61	74.00	-15.39	Peak
2483.88	63.33	26.18	3.14	37.57	55.08	74.00	-18.92	Peak


Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:a; Polarization:Horizontal; Modulation: $\pi/4$  DQPSK; ; Channel:High**Antenna Polarity :HORIZONTAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2479.96	95.89	26.17	3.14	37.57	87.63	54.00	33.63	Average
2483.50	57.57	26.18	3.14	37.57	49.32	54.00	-4.68	Average
2484.03	52.46	26.18	3.14	37.57	44.21	54.00	-9.79	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:a; Polarization:Vertical; Modulation: $\pi/4$  DQPSK; ; Channel:High

Mode:a; Polarization:Vertical; Modulation: $\pi/4$  DQPSK; ; Channel:High**Antenna Polarity :VERTICAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2480.03	96.12	26.17	3.14	37.57	87.86	54.00	33.86	Average
2483.50	57.74	26.18	3.14	37.57	49.49	54.00	-4.51	Average
2483.96	53.31	26.18	3.14	37.57	45.06	54.00	-8.94	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:a; Polarization:Horizontal; Modulation:8DPSK; ; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2346.51	48.49	25.97	3.10	37.37	40.19	74.00	-33.81	Peak
2390.00	46.44	26.03	3.15	37.40	38.22	74.00	-35.78	Peak
2402.25	101.84	26.05	3.14	37.40	93.63	74.00	19.63	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:a; Polarization:Vertical; Modulation:8DPSK; ; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2363.27	48.19	26.00	3.15	37.38	39.96	74.00	-34.04	Peak
2390.00	46.82	26.03	3.15	37.40	38.60	74.00	-35.40	Peak
2402.05	101.77	26.05	3.14	37.40	93.56	74.00	19.56	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:a; Polarization:Horizontal; Modulation:8DPSK; ; Channel:High

**Antenna Polarity :HORIZONTAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2480.03	101.41	26.17	3.14	37.57	93.15	74.00	19.15	Peak
2483.50	65.63	26.18	3.14	37.57	57.38	74.00	-16.62	Peak
2483.88	62.69	26.18	3.14	37.57	54.44	74.00	-19.56	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:a; Polarization:Horizontal; Modulation:8DPSK; ; Channel:High

**Antenna Polarity :HORIZONTAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2479.96	95.93	26.17	3.14	37.57	87.67	54.00	33.67	Average
2483.50	57.61	26.18	3.14	37.57	49.36	54.00	-4.64	Average
2484.03	52.47	26.18	3.14	37.57	44.22	54.00	-9.78	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:a; Polarization:Vertical; Modulation:8DPSK; ; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2479.96	101.63	26.17	3.14	37.57	93.37	74.00	19.37	Peak
2483.50	65.78	26.18	3.14	37.57	57.53	74.00	-16.47	Peak
2483.88	62.45	26.18	3.14	37.57	54.20	74.00	-19.80	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:a; Polarization:Vertical; Modulation:8DPSK; ; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2480.03	96.05	26.17	3.14	37.57	87.79	54.00	33.79	Average
2483.50	57.68	26.18	3.14	37.57	49.43	54.00	-4.57	Average
2483.96	53.26	26.18	3.14	37.57	45.01	54.00	-8.99	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor



## 7.10 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 7.10.1 E.U.T. Operation

Operating Environment:

Temperature: 20 °C      Humidity: 50 % RH      Atmospheric Pressure: 1010 mbar  
Test mode      a:Charge + TX\_non-Hop mode\_Keep the EUT in charging and continuously transmitting mode with GFSK modulation,  $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

### 7.10.2 Test Setup Diagram



#### **7.10.3 Measurement Procedure and Data**


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown

Below 1GHz:

Mode:a; Polarization:Horizontal



Antenna Polarity :HORIZONTAL


EUT/Project :16758CR

Test mode :a

Freq MHz	Read Level dBuV	Antenna Factor dB/m	Cable Loss dB	Preamp Factor dB	Emission Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1 31.620	43.56	15.48	0.45	42.37	17.12	40.00	-22.88	QP
2 166.651	55.68	12.14	1.49	42.21	27.10	43.50	-16.40	QP
3 204.238	62.98	9.62	1.76	42.17	32.19	43.50	-11.31	QP
4 228.490	65.78	10.65	2.04	42.13	36.34	46.00	-9.66	QP
5 261.058	68.35	11.90	2.21	42.10	40.36	46.00	-5.64	QP
6 359.186	58.17	14.40	3.00	41.94	33.63	46.00	-12.37	QP

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:a; Polarization:Vertical



Antenna Polarity : VERTICAL

EUT/Project : 16758CR

Test mode : a

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	30.531	56.05	15.36	0.45	42.38	29.48	40.00	-10.52	QP
2	39.162	56.07	16.24	0.13	42.33	30.11	40.00	-9.89	QP
3	163.182	55.02	12.56	1.48	42.22	26.84	43.50	-16.66	QP
4	228.490	62.17	10.65	2.04	42.13	32.73	46.00	-13.27	QP
5	261.058	67.35	11.90	2.21	42.10	39.36	46.00	-6.64	QP
6	359.186	60.72	14.40	3.00	41.94	36.18	46.00	-9.82	QP

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Above 1GHz:

Mode:a; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4804	38.81	6.18	44.99	54	-9.01	peak
7206	39.61	10.63	50.24	54	-3.76	peak
9608	35.20	14.38	49.58	54	-4.42	peak

Mode:a; Polarization:Vertical; Modulation:GFSK; ; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4804	35.65	6.18	41.83	54	-12.17	peak
7206	36.46	10.63	47.09	54	-6.91	peak
9608	31.94	14.38	46.32	54	-7.68	peak

Mode:a; Polarization:Horizontal; Modulation:GFSK; ; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4882	35.92	7.00	42.92	54	-11.08	peak
7323	38.70	11.13	49.83	54	-4.17	peak
9764	35.71	14.36	50.07	54	-3.93	peak

Mode:a; Polarization:Vertical; Modulation:GFSK; ; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4882	34.67	7.00	41.67	54	-12.33	peak
7323	33.88	11.13	45.01	54	-8.99	peak
9764	30.50	14.36	44.86	54	-9.14	peak

Mode:a; Polarization:Horizontal; Modulation:GFSK; ; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4960	37.84	7.49	45.33	54	-8.67	peak
7440	35.65	11.65	47.30	54	-6.70	peak
9920	31.51	14.40	45.91	54	-8.09	peak

Mode:a; Polarization:Vertical; Modulation:GFSK; ; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4960	37.50	7.49	44.99	54	-9.01	peak
7440	37.29	11.65	48.94	54	-5.06	peak
9920	33.56	14.40	47.96	54	-6.04	peak

Mode:a; Polarization:Horizontal; Modulation: $\pi/4$  DQPSK; ; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4804	38.39	6.18	44.57	54	-9.43	peak
7206	38.39	10.63	49.02	54	-4.98	peak
9608	33.41	14.38	47.79	54	-6.21	peak

Mode:a; Polarization:Vertical; Modulation: $\pi/4$  DQPSK; ; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4804	36.29	6.18	42.47	54	-11.53	peak
7206	36.30	10.63	46.93	54	-7.07	peak
9608	31.07	14.38	45.45	54	-8.55	peak

Mode:a; Polarization:Horizontal; Modulation: $\pi/4$  DQPSK; ; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4882	38.87	7.00	45.87	54	-8.13	peak
7323	36.08	11.13	47.21	54	-6.79	peak
9764	31.47	14.36	45.83	54	-8.17	peak

Mode:a; Polarization:Vertical; Modulation: $\pi/4$  DQPSK; ; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4882	36.10	7.00	43.10	54	-10.90	peak
7323	38.29	11.13	49.42	54	-4.58	peak
9764	34.66	14.36	49.02	54	-4.98	peak

Mode:a; Polarization:Horizontal; Modulation: $\pi/4$  DQPSK; ; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4960	33.31	7.49	40.80	54	-13.20	peak
7440	35.40	11.65	47.05	54	-6.95	peak
9920	33.22	14.40	47.62	54	-6.38	peak

Mode:a; Polarization:Vertical; Modulation: $\pi/4$  DQPSK; ; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4960	33.69	7.49	41.18	54	-12.82	peak
7440	36.90	11.65	48.55	54	-5.45	peak
9920	31.95	14.40	46.35	54	-7.65	peak

Mode:a; Polarization:Horizontal; Modulation: $\pi/4$  DQPSK; ; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4804	35.71	6.18	41.89	54	-12.11	peak
7206	35.82	10.63	46.45	54	-7.55	peak
9608	35.87	14.38	50.25	54	-3.75	peak

Mode:a; Polarization:Vertical; Modulation:8DPSK; ; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4804	37.82	6.18	44.00	54	-10.00	peak
7206	37.85	10.63	48.48	54	-5.52	peak
9608	33.32	14.38	47.70	54	-6.30	peak

Mode:a; Polarization:Horizontal; Modulation:8DPSK; ; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4882	34.50	7.00	41.50	54	-12.50	peak
7323	39.84	11.13	50.97	54	-3.03	peak
9764	35.43	14.36	49.79	54	-4.21	peak

Mode:a; Polarization:Vertical; Modulation:8DPSK; ; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4882	34.80	7.00	41.80	54	-12.20	peak
7323	39.65	11.13	50.78	54	-3.22	peak
9764	35.30	14.36	49.66	54	-4.34	peak

Mode:a; Polarization:Horizontal; Modulation:8DPSK; ; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4960	35.18	7.49	42.67	54	-11.33	peak
7440	35.58	11.65	47.23	54	-6.77	peak
9920	33.03	14.40	47.43	54	-6.57	peak

Mode:a; Polarization:Vertical; Modulation:8DPSK; ; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Over Limit	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
4960	35.70	7.49	43.19	54	-10.81	peak
7440	34.83	11.65	46.48	54	-7.52	peak
9920	34.64	14.40	49.04	54	-4.96	peak



## **8 Test Setup Photographs**

Refer to the < Test Setup photos-FCC>.

## **9 EUT Constructional Details**

Refer to the < External Photos > & < Internal Photos >.

**- End of the Report -**