

# FCC REPORT (WIFI)

**Applicant:** Light Repute International Limited

**Address of Applicant:** Room 101, No. 91, Avenue 3288 Yanggao South Road,  
Pudong New Area, Shanghai, People's Rep. of China

**Equipment Under Test (EUT)**

Product Name: mobile phone

Model No.: Z5

Trade mark: Smart mobile

**FCC ID:** 2ADVCZ5

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.247

**Date of sample receipt:** 09 Jun., 2015

**Date of Test:** 09 Jun., to 16 Jul., 2015

**Date of report issued:** 16 Jul., 2015

**Test Result:** PASS\*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	16 Jul., 2015	Original

Prepared by:

*Sera Xiang*

**Report Clerk**

Date:

16 Jul., 2015

Reviewed by:

*Gaven Liu*

**Project Engineer**

Date:

16 Jul., 2015

## 3 Contents

	Page
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 VERSION .....</b>	<b>2</b>
<b>3 CONTENTS .....</b>	<b>3</b>
<b>4 TEST SUMMARY.....</b>	<b>4</b>
<b>5 GENERAL INFORMATION.....</b>	<b>5</b>
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST ENVIRONMENT AND MODE .....	7
5.4 LABORATORY FACILITY.....	8
5.5 LABORATORY LOCATION .....	8
5.6 TEST INSTRUMENTS LIST.....	9
<b>6 TEST RESULTS AND MEASUREMENT DATA.....</b>	<b>10</b>
6.1 ANTENNA REQUIREMENT:.....	10
6.2 CONDUCTED EMISSION .....	11
6.3 CONDUCTED OUTPUT POWER .....	14
6.4 OCCUPY BANDWIDTH .....	18
6.5 POWER SPECTRAL DENSITY .....	25
6.6 BAND EDGE .....	29
6.6.1 Conducted Emission Method.....	29
6.6.2 Radiated Emission Method.....	32
6.7 SPURIOUS EMISSION.....	45
6.7.1 Conducted Emission Method.....	45
6.7.2 Radiated Emission Method.....	51
<b>7 TEST SETUP PHOTO .....</b>	<b>58</b>
<b>8 EUT CONSTRUCTIONAL DETAILS .....</b>	<b>59</b>

## 4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

*Pass: The EUT complies with the essential requirements in the standard.*

## 5 General Information

### 5.1 Client Information

Applicant:	Light Repute International Limited
Address of Applicant:	Room 101, No. 91, Avenue 3288 Yanggao South Road, Pudong New Area, Shanghai, People's Rep. of China
Manufacturer:	Light Repute International Limited
Address of Manufacturer:	Room 101, No. 91, Avenue 3288 Yanggao South Road, Pudong New Area, Shanghai, People's Rep. of China

### 5.2 General Description of E.U.T.

Product Name:	mobile phone
Model No.:	Z5
Operation Frequency:	2412MHz~2462MHz (802.11b/802.11g/802.11n(H20))
Channel numbers:	11 for 802.11b/802.11g/802.11(H20)
Channel separation:	5MHz
Modulation technology: (IEEE 802.11b)	Direct Sequence Spread Spectrum (DSSS)
Modulation technology: (IEEE 802.11g/802.11n)	Orthogonal Frequency Division Multiplexing(OFDM)
Data speed (IEEE 802.11b):	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
Data speed (IEEE 802.11g):	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps,54Mbps
Data speed (IEEE 802.11n):	Up to 150Mbps
Antenna Type:	Internal Antenna
Antenna gain:	1 dBi
AC adapter:	Model :A1265 Input:100-240V AC,50/60Hz 0.15A Output:5V DC MAX 1A
Power supply:	Rechargeable Li-ion Battery DC3.7V-2200mAh

Operation Frequency each of channel For 802.11b/g/n(H20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

**Note:**

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

802.11b/802.11g/802.11n (H20)

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The Highest channel	2462MHz

## 5.3 Test environment and mode

<b>Operating Environment:</b>	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
<b>Test mode:</b>	
Operation mode	Keep the EUT in continuous transmitting with modulation
<p>The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.</p>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

<b>Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.</b>	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(H20)	6.5Mbps

**Final Test Mode:**  
 According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup” 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(H20). Duty cycle setting during the transmission is 100% with maximum power setting for all modulations.

## 5.4 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 817957, February 27, 2012.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

## 5.5 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,  
Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282

Fax: +86-755-23116366



## 5.6 Test Instruments list


Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	CCIS0005	03-28-2015	03-28-2016
3	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	CCIS0006	03-28-2015	03-28-2016
4	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
5	Amplifier (10kHz-1.3GHz)	HP	8447D	CCIS0003	04-01-2015	03-31-2016
6	Amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	04-01-2015	03-31-2016
7	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	04-01-2015	03-31-2016
8	Horn Antenna	ETS-LINDGREN	3160	GTS217	04-01-2015	03-31-2016
9	Printer	HP	HP LaserJet P1007	N/A	N/A	N/A
10	Positioning Controller	UC	UC3000	CCIS0015	N/A	N/A
11	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP	CCIS0023	03-28-2015	03-28-2016
12	EMI Test Receiver	Rohde & Schwarz	ESPI	CCIS0022	03-28-2015	03-28-2016
13	Loop antenna	Laplace instrument	RF300	EMC0701	04-01-2015	03-31-2016
14	Universal radio communication tester	Rhode & Schwarz	CMU200	CCIS0069	03-28-2015	03-28-2016
15	Signal Analyzer	Rohde & Schwarz	FSIQ3	CCIS0088	04-08-2015	04-08-2016

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	11-10-2012	11-09-2015
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	03-28-2015	03-28-2016
3	LISN	CHASE	MN2050D	CCIS0074	03-28-2015	03-28-2016
4	Coaxial Cable	CCIS	N/A	CCIS0086	04-01-2015	03-31-2016
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

## 6 Test results and Measurement Data

### 6.1 Antenna requirement:

<b>Standard requirement:</b>	FCC Part 15 C Section 15.203 /247(c)
<p><i>15.203 requirement:</i>  <i>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</i></p> <p><i>15.247(c) (1)(i) requirement:</i>  <i>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</i></p>	
<b>E.U.T Antenna:</b>	
<p><i>The WiFi antenna is an internal antenna which cannot replace by end-user, the best case gain of the antenna is 1 dBi.</i></p>	




## 6.2 Conducted Emission

Test Requirement:	FCC Part 15 C Section 15.207														
Test Method:	ANSI C63.4: 2009														
Test Frequency Range:	150 kHz to 30 MHz														
Class / Severity:	Class B														
Receiver setup:	RBW=9 kHz, VBW=30 kHz														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table> <p>* Decreases with the logarithm of the frequency.</p>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test procedure	<ol style="list-style-type: none"> <li>The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.), which provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2009 on conducted measurement.</li> </ol>														
Test setup:	<p><i>Remark</i>  <i>E.U.T: Equipment Under Test</i>  <i>LISN: Line Impedance Stabilization Network</i>  <i>Test table height=0.8m</i></p>														
Test Instruments:	Refer to section 5.6 for details														
Test mode:	Refer to section 5.3 for details														
Test results:	Passed														

### Measurement Data

Neutral:




Trace: 13

Site : CCIS Shielding Room  
 Condition : FCC CLASS-B QP LISN NEUTRAL  
 EUT : Mobile Phone  
 Model : Z5  
 Test Mode : Wifi mode  
 Power Rating : AC120/60Hz  
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa  
 Test Engineer: Colin  
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.154	28.02	0.25	10.78	39.05	65.78	-26.73	QP
2	0.206	24.18	0.25	10.76	35.19	63.36	-28.17	QP
3	0.277	10.49	0.26	10.74	21.49	50.90	-29.41	Average
4	0.634	6.08	0.21	10.77	17.06	46.00	-28.94	Average
5	0.697	18.77	0.18	10.77	29.72	56.00	-26.28	QP
6	1.628	3.53	0.27	10.93	14.73	46.00	-31.27	Average
7	1.762	14.59	0.28	10.94	25.81	56.00	-30.19	QP
8	2.765	4.07	0.29	10.93	15.29	46.00	-30.71	Average
9	4.027	14.01	0.29	10.89	25.19	56.00	-30.81	QP
10	5.305	3.36	0.28	10.84	14.48	50.00	-35.52	Average
11	7.566	12.93	0.26	10.83	24.02	60.00	-35.98	QP
12	11.807	-1.16	0.25	10.92	10.01	50.00	-39.99	Average

Line:



Trace: 15

Site : CCIS Shielding Room  
 Condition : FCC CLASS-B QP LISN LINE  
 EUT : Mobile Phone  
 Model : Z5  
 Test Mode : Wifi mode  
 Power Rating : AC120/60Hz  
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa  
 Test Engineer: Colin  
 Remark :


	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.154	27.31	0.27	10.78	38.36	65.78	-27.42	QP
2	0.299	20.68	0.26	10.74	31.68	60.28	-28.60	QP
3	0.299	10.76	0.26	10.74	21.76	50.28	-28.52	Average
4	0.686	18.27	0.22	10.77	29.26	56.00	-26.74	QP
5	0.686	6.17	0.22	10.77	17.16	46.00	-28.84	Average
6	1.345	14.71	0.25	10.91	25.87	56.00	-30.13	QP
7	1.345	1.21	0.25	10.91	12.37	46.00	-33.63	Average
8	3.759	2.96	0.28	10.90	14.14	46.00	-31.86	Average
9	5.362	14.02	0.30	10.84	25.16	60.00	-34.84	QP
10	6.988	-1.73	0.32	10.80	9.39	50.00	-40.61	Average
11	12.988	12.25	0.32	10.91	23.48	60.00	-36.52	QP
12	13.768	-1.92	0.32	10.91	9.31	50.00	-40.69	Average

Notes:

1. An initial pre-scan was performed on the live and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss



## 6.3 Conducted Output Power


Test Requirement:	FCC Part 15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013 and KDB558074v03r03 section 9.2.2
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 5.6 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

### Measurement Data

Test CH	Maximum Conducted Output Power (dBm)			Limit(dBm)	Result
	802.11b	802.11g	802.11n(H20)		
Lowest	6.40	5.36	1.93	30.00	Pass
Middle	8.57	7.47	3.73		
Highest	10.78	9.06	5.69		


Test plot as follows:

Test mode: 802.11b




**Tx Channel**  
 Bandwidth 20 MHz Power 6.40 dBm

Lowest channel



**Tx Channel**  
 Bandwidth 20 MHz Power 8.57 dBm


Middle channel



**Tx Channel**  
 Bandwidth 20 MHz Power 10.78 dBm


Highest channel

Test mode: 802.11g




Tx Channel  
Bandwidth 20 MHz Power 5.36 dBm

Lowest channel



Tx Channel  
Bandwidth 20 MHz Power 7.47 dBm

Middle channel




Tx Channel  
Bandwidth 20 MHz Power 9.06 dBm

Highest channel




Test mode: 802.11n(H20)




Tx Channel  
Bandwidth 20 MHz Power 1.93 dBm

Lowest channel



Tx Channel  
Bandwidth 20 MHz Power 3.73 dBm


Middle channel



Tx Channel  
Bandwidth 20 MHz Power 5.69 dBm

Highest channel

## 6.4 Occupy Bandwidth

Test Requirement:	FCC Part 15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013 and KDB558074v03r03 section 8.1
Limit:	>500kHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.6 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

### Measurement Data


Test CH	6dB Emission Bandwidth (MHz)			Limit(kHz)	Result
	802.11b	802.11g	802.11n(H20)		
Lowest	9.68	15.28	16.08	>500	Pass
Middle	9.68	15.28	16.32		
Highest	9.20	15.28	16.32		

Test CH	99% Occupy Bandwidth (MHz)			Limit(kHz)	Result
	802.11b	802.11g	802.11n(H20)		
Lowest	13.12	16.32	17.52	N/A	N/A
Middle	12.80	16.24	17.52		
Highest	12.88	16.32	17.52		

Test plot as follows:


## 6dB EBW

Test mode: 802.11b




Date: 9.JUL.2015 20:34:02

### Lowest channel



Date: 9.JUL.2015 20:34:53


### Middle channel



Date: 9.JUL.2015 20:30:08


### Highest channel

Test mode: 802.11g




Date: 9.JUL.2015 20:36:04

Lowest channel



Date: 9.JUL.2015 20:37:36

Middle channel




Date: 9.JUL.2015 20:39:37

Highest channel




## 99% OBW

Test mode: 802.11b




Date: 9.JUL.2015 20:34:27

### Lowest channel



Date: 9.JUL.2015 20:31:05


### Middle channel



Date: 9.JUL.2015 20:30:34


### Highest channel

Test mode: 802.11g




Date: 9.JUL.2015 20:35:06

Lowest channel



Date: 9.JUL.2015 20:37:56


Middle channel



Date: 9.JUL.2015 20:38:18


Highest channel

Test mode: 802.11n(H20)




Date: 9.JUL.2015 20:44:27

Lowest channel



Date: 9.JUL.2015 20:42:28

Middle channel




Date: 9.JUL.2015 20:42:03

Highest channel



## 6.5 Power Spectral Density


Test Requirement:	FCC Part 15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2013 and KDB558074v03r03 section 10.2
Limit:	8dBm
Test setup:	
Test Instruments:	Refer to section 5.6 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

### Measurement Data

Test CH	Power Spectral Density (dBm)			Limit(dBm)	Result
	802.11b	802.11g	802.11n(H20)		
Lowest	-3.92	-13.01	-16.81	8.00	Pass
Middle	-2.68	-11.00	-14.80		
Highest	-0.54	-8.92	-12.66		


Test plot as follows:

Test mode: 802.11b




Date: 9.JUL.2015 20:08:30

Lowest channel



Date: 9.JUL.2015 20:10:24


Middle channel



Date: 9.JUL.2015 20:12:07


Highest channel

Test mode: 802.11g




Date: 9.JUL.2015 20:13:46

Lowest channel



Date: 9.JUL.2015 20:14:57


Middle channel



Date: 9.JUL.2015 20:16:06


Highest channel

Test mode: 802.11n(H20)




Date: 9.JUL.2015 20:17:38

Lowest channel



Date: 9.JUL.2015 20:19:10

Middle channel




Date: 9.JUL.2015 20:20:39

Highest channel


## 6.6 Band Edge

### 6.6.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074v03r03 section 13
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two legs and sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.6 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Test plot as follows:

## 802.11b



Date: 9.JUL.2015 20:26:51


Lowest channel



Date: 9.JUL.2015 20:27:44


Highest channel

## 802.11g



Date: 9.JUL.2015 20:25:06


Lowest channel



Date: 9.JUL.2015 20:23:54


Highest channel

## 802.11n(H20)



Date: 9.JUL.2015 20:26:02

Lowest channel



Date: 9.JUL.2015 20:23:01

Highest channel

## 6.6.2 Radiated Emission Method


Test Requirement:	FCC Part 15 C Section 15.209 and 15.205			
Test Method:	ANSI C63.10: 2013 and KDB 558074v03r03 section 12.1			
Test Frequency Range:	2.3GHz to 2.5GHz			
Test site:	Measurement Distance: 3m			
Receiver setup:	Frequency	Detector	RBW	VBW
	Above 1GHz	Peak	1MHz	3MHz
		Peak	1MHz	10Hz
Remark	Peak Value			Average Value
Limit:	Frequency	Limit (dBuV/m @3m)		Remark
	Above 1GHz	54.00		Average Value
		74.00		Peak Value
Test Procedure:	<ol style="list-style-type: none"> <li>The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>			
Test setup:				
Test Instruments:	Refer to section 5.6 for details			
Test mode:	Refer to section 5.3 for details			
Test results:	Passed			



**802.11b**

Test channel: Lowest

Horizontal:



```


Site       : 3m chamber
Condition  : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
EUT       : Mobile phone
Model     : Z5
Test mode  : wifi-B-L
Power Rating : AC 120V/60Hz
Environment : Temp:25.5°C Humi:55%
Test Engineer: Colin
REMARK    :
    
```

	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	19.91	27.58	6.63	0.00	54.12	74.00	-19.88 Peak
2	2390.000	8.87	27.58	6.63	0.00	43.08	54.00	-10.92 Average

*Remark:*

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Vertical:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL  
 EUT : Mobile phone  
 Model : Z5  
 Test mode : wifi-B-L  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Colin  
 REMARK :


Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	19.96	27.58	6.63	0.00	54.17	74.00	-19.83 Peak
2	2390.000	9.03	27.58	6.63	0.00	43.24	54.00	-10.76 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel: Highest

Horizontal:




Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL  
 EUT : Mobile phone  
 Model : Z5  
 Test mode : wifi-B-H  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Colin  
 REMARK :

	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	20.94	27.52	6.85	0.00	55.31	74.00	-18.69 Peak
2	2483.500	8.90	27.52	6.85	0.00	43.27	54.00	-10.73 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL  
 EUT : Mobile phone  
 Model : Z5  
 Test mode : wifi-B-H  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Colin  
 REMARK :

Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark
MHz	Level	Factor	Loss	Factor	Line	Limit	
	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	20.42	27.52	6.85	0.00	54.79	74.00 -19.21 Peak
2	2483.500	8.64	27.52	6.85	0.00	43.01	54.00 -10.99 Average


Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 802.11g

Test channel: Lowest

Horizontal:



```


Site       : 3m chamber
Condition  : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
EUT       : Mobile phone
Model     : Z5
Test mode  : wifi-G-L
Power Rating : AC 120V/60Hz
Environment : Temp:25.5°C Humi:55%
Test Engineer: Colin
REMARK    :
    
```

	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Line	Limit	Remark	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	20.02	27.58	6.63	0.00	54.23	74.00	-19.77 Peak
2	2390.000	7.98	27.58	6.63	0.00	42.19	54.00	-11.81 Average

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL  
 EUT : Mobile phone  
 Model : Z5  
 Test mode : wifi-G-L  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Colin  
 REMARK :

	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	21.16	27.58	6.63	0.00	55.37	74.00 -18.63 Peak
2	2390.000	8.05	27.58	6.63	0.00	42.26	54.00 -11.74 Average


Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.



Test channel: Highest

Horizontal:




Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL  
 EUT : Mobile phone  
 Model : Z5  
 Test mode : wifi-G-H  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Colin  
 REMARK :

	Read	Antenna	Cable	Preamp	Level	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	20.22	27.52	6.85	0.00	54.59	74.00	-19.41 Peak
2	2483.500	8.55	27.52	6.85	0.00	42.92	54.00	-11.08 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL  
 EUT : Mobile phone  
 Model : Z5  
 Test mode : wifi-G-H  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Colin  
 REMARK :

	Read	Antenna	Cable	Preamp	Level	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	20.12	27.52	6.85	0.00	54.49	74.00	-19.51 Peak
2	2483.500	8.24	27.52	6.85	0.00	42.61	54.00	-11.39 Average

Remark:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.



**802.11n (H20)**

Test channel: Lowest

Horizontal:



```


Site       : 3m chamber
Condition  : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
EUT       : Mobile phone
Model     : Z5
Test mode  : wifi-N20-L
Power Rating : AC 120V/60Hz
Environment : Temp:25.5°C Humi:55%
Test Engineer: Colin
REMARK    :
    
```

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	19.57	27.58	6.63	0.00	53.78	74.00	-20.22	Peak
2	2390.000	7.51	27.58	6.63	0.00	41.72	54.00	-12.28	Average

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL  
 EUT : Mobile phone  
 Model : Z5  
 Test mode : wifi-N20-L  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Colin  
 REMARK :


	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Line	Limit	Remark
-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	19.59	27.58	6.63	0.00	53.80	74.00 -20.20 Peak
2	2390.000	7.65	27.58	6.63	0.00	41.86	54.00 -12.14 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamp Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel: Highest

Horizontal:




Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL  
 EUT : Mobile phone  
 Model : Z5  
 Test mode : wifi-N20-H  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Colin  
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	19.50	27.52	6.85	0.00	53.87	74.00	-20.13	Peak
2	2483.500	7.95	27.52	6.85	0.00	42.32	54.00	-11.68	Average
3	2485.695	22.22	27.52	6.85	0.00	56.59	74.00	-17.41	Peak
4	2485.695	8.01	27.52	6.85	0.00	42.38	54.00	-11.62	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL  
 EUT : Mobile phone  
 Model : Z5  
 Test mode : wifi-N20-H  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Colin  
 REMARK :


	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	19.86	27.52	6.85	0.00	54.23	74.00	-19.77 Peak
2	2483.500	7.99	27.52	6.85	0.00	42.36	54.00	-11.64 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 6.7 Spurious Emission


### 6.7.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 section 11
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.6 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plot as follows:



### Highest channel




Date: 9.JUL.2015 20:12:46

30MHz~25GHz

### Test mode: 802.11g


### Lowest channel



Date: 9.JUL.2015 20:14:13

30MHz~25GHz


## Middle channel



Date: 9.JUL.2015 20:15:24

30MHz~25GHz

## Highest channel




Date: 9.JUL.2015 20:16:43

30MHz~25GHz



Test mode: 802.11n(H20)


Lowest channel



Date: 9..III..2015 20:18:24

30MHz~25GHz


Middle channel



Date: 9..III..2015 20:20:05

30MHz~25GHz

### Highest channel





Date: 9.JUL.2015 20:21:18

30MHz~25GHz


## 6.7.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205																								
Test Method:	ANSI C63.10:2013																								
Test Frequency Range:	9KHz to 25GHz																								
Test site:	Measurement Distance: 3m																								
Receiver setup:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Detector</th> <th>RBW</th> <th>VBW</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>30MHz-1GHz</td> <td>Quasi-peak</td> <td>120KHz</td> <td>300KHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td rowspan="2">Above 1GHz</td> <td>Peak</td> <td>1MHz</td> <td>3MHz</td> <td>Peak Value</td> </tr> <tr> <td>Peak</td> <td>1MHz</td> <td>10Hz</td> <td>Average Value</td> </tr> </tbody> </table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	Peak	1MHz	10Hz	Average Value	
	Frequency	Detector	RBW	VBW	Remark																				
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value																				
	Above 1GHz	Peak	1MHz	3MHz	Peak Value																				
Peak		1MHz	10Hz	Average Value																					
Limit:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Limit (dBuV/m @3m)</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>30MHz-88MHz</td> <td>40.0</td> <td>Quasi-peak Value</td> </tr> <tr> <td>88MHz-216MHz</td> <td>43.5</td> <td>Quasi-peak Value</td> </tr> <tr> <td>216MHz-960MHz</td> <td>46.0</td> <td>Quasi-peak Value</td> </tr> <tr> <td>960MHz-1GHz</td> <td>54.0</td> <td>Quasi-peak Value</td> </tr> <tr> <td rowspan="2">Above 1GHz</td> <td>54.0</td> <td>Average Value</td> </tr> <tr> <td>74.0</td> <td>Peak Value</td> </tr> </tbody> </table>					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.0	Quasi-peak Value	88MHz-216MHz	43.5	Quasi-peak Value	216MHz-960MHz	46.0	Quasi-peak Value	960MHz-1GHz	54.0	Quasi-peak Value	Above 1GHz	54.0	Average Value	74.0	Peak Value
	Frequency	Limit (dBuV/m @3m)	Remark																						
	30MHz-88MHz	40.0	Quasi-peak Value																						
	88MHz-216MHz	43.5	Quasi-peak Value																						
	216MHz-960MHz	46.0	Quasi-peak Value																						
	960MHz-1GHz	54.0	Quasi-peak Value																						
Above 1GHz	54.0	Average Value																							
	74.0	Peak Value																							
Test Procedure:	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>																								

<p>Test setup:</p>	<p><b>Below 1GHz</b></p>  <p><b>Above 1GHz</b></p> 
<p>Test Instruments:</p>	<p>Refer to section 5.6 for details</p>
<p>Test mode:</p>	<p>Refer to section 5.3 for details</p>
<p>Test results:</p>	<p>Passed</p>
<p>Remark:</p>	<ol style="list-style-type: none"> <li>1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.</li> <li>2. 9 kHz to 30MHz is too low, so only shows the data of above 30MHz in this report.</li> </ol>

**Below 1GHz**


Horizontal :



Site : 3m chamber  
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) HORIZONTAL  
 EUT : Mobile phone  
 Model : Z5  
 Test mode : WIFI  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Colin  
 REMARK :

	Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Level	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	167.824	51.92	8.90	1.34	29.07	33.09	43.50	-10.41	QP
2	177.509	50.77	9.49	1.36	28.99	32.63	43.50	-10.87	QP
3	265.676	47.79	12.26	1.67	28.51	33.21	46.00	-12.79	QP
4	383.932	46.08	14.68	2.06	28.71	34.11	46.00	-11.89	QP
5	576.644	42.35	18.03	2.58	29.01	33.95	46.00	-12.05	QP
6	768.748	40.65	19.68	3.09	28.37	35.05	46.00	-10.95	QP

Vertical :



Site : 3m chamber  
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) VERTICAL  
 EUT : Mobile phone  
 Model : Z5  
 Test mode : WIFI  
 Power Rating : AC 120V/60Hz  
 Environment : Temp:25.5°C Humi:55%  
 Test Engineer: Colin  
 REMARK :

	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	119.856	50.23	10.48	1.12	29.39	32.44	43.50 -11.06 QP
2	167.824	48.85	8.90	1.34	29.07	30.02	43.50 -13.48 QP
3	511.835	43.45	16.84	2.43	28.99	33.73	46.00 -12.27 QP
4	528.246	42.09	17.15	2.48	29.04	32.68	46.00 -13.32 QP
5	552.883	42.87	17.62	2.54	29.09	33.94	46.00 -12.06 QP
6	576.644	42.60	18.03	2.58	29.01	34.20	46.00 -11.80 QP

**Above 1GHz**

Test mode: 802.11b			Test channel: Lowest			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3619.18	65.26	29.18	8.99	40.35	63.08	74.00	-10.92	Vertical
4824.00	49.27	31.53	8.90	40.24	49.46	74.00	-24.54	Vertical
3619.18	60.42	29.18	8.99	40.35	58.24	74.00	-15.76	Horizontal
4824.00	50.95	31.53	8.90	40.24	51.14	74.00	-22.86	Horizontal
Test mode: 802.11b			Test channel: Lowest			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3619.18	55.85	29.18	8.99	40.35	53.67	54.00	-0.33	Vertical
4824.00	40.26	31.53	8.90	40.24	40.45	54.00	-13.55	Vertical
3619.18	52.48	29.18	8.99	40.35	50.30	54.00	-3.70	Horizontal
4824.00	42.36	31.53	8.90	40.24	42.55	54.00	-11.45	Horizontal

Test mode: 802.11b			Test channel: Middle			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3647.46	65.64	29.21	9.04	40.39	63.50	74.00	-10.50	Vertical
4874.00	48.08	31.58	8.98	40.15	48.49	74.00	-25.51	Vertical
3647.46	61.46	29.21	9.04	40.39	59.32	74.00	-14.68	Horizontal
4874.00	51.61	31.58	8.98	40.15	52.02	74.00	-21.98	Horizontal
Test mode: 802.11b			Test channel: Middle			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3647.46	56.03	29.21	9.04	40.39	53.89	54.00	-0.11	Vertical
4874.00	39.25	31.58	8.98	40.15	39.66	54.00	-14.34	Vertical
3647.46	53.31	29.21	9.04	40.39	51.17	54.00	-2.83	Horizontal
4874.00	42.27	31.58	8.98	40.15	42.68	54.00	-11.32	Horizontal

Test mode: 802.11b			Test channel: Highest			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3697.48	65.63	29.26	9.12	40.46	63.55	74.00	-10.45	Vertical
4924.00	48.64	31.69	9.08	40.03	49.38	74.00	-24.62	Vertical
3697.48	61.73	29.26	9.12	40.46	59.65	74.00	-14.35	Horizontal
4924.00	52.14	31.69	9.08	40.03	52.88	74.00	-21.12	Horizontal
Test mode: 802.11b			Test channel: Highest			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3697.48	55.59	29.26	9.12	40.46	53.51	54.00	-0.49	Vertical
4924.00	38.25	31.69	9.08	40.03	38.99	54.00	-15.01	Vertical
3697.48	52.11	29.26	9.12	40.46	50.03	54.00	-3.97	Horizontal
4924.00	49.28	31.69	9.08	40.03	50.02	54.00	-3.98	Horizontal

*Remark:*

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.



Test mode: 802.11g			Test channel: Lowest			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3619.18	64.24	29.18	8.99	40.35	62.06	74.00	-11.94	Vertical
4824.00	47.84	31.53	8.90	40.24	48.03	74.00	-25.97	Vertical
3619.18	59.12	29.18	8.99	40.35	56.94	74.00	-17.06	Horizontal
4824.00	49.24	31.53	8.90	40.24	49.43	74.00	-24.57	Horizontal
Test mode: 802.11g			Test channel: Lowest			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3619.18	53.24	29.18	8.99	40.35	51.06	54.00	-2.94	Vertical
4824.00	38.62	31.53	8.90	40.24	38.81	54.00	-15.19	Vertical
3619.18	51.24	29.18	8.99	40.35	49.06	54.00	-4.94	Horizontal
4824.00	39.61	31.53	8.90	40.24	39.80	54.00	-14.20	Horizontal

Test mode: 802.11g			Test channel: Middle			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3647.46	63.12	29.21	9.04	40.39	60.98	74.00	-13.02	Vertical
4874.00	48.24	31.58	8.98	40.15	48.65	74.00	-25.35	Vertical
3647.46	62.13	29.21	9.04	40.39	59.99	74.00	-14.01	Horizontal
4874.00	49.72	31.58	8.98	40.15	50.13	74.00	-23.87	Horizontal
Test mode: 802.11g			Test channel: Middle			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3647.46	54.12	29.21	9.04	40.39	51.98	54.00	-2.02	Vertical
4874.00	38.11	31.58	8.98	40.15	38.52	54.00	-15.48	Vertical
3647.46	52.01	29.21	9.04	40.39	49.87	54.00	-4.13	Horizontal
4874.00	39.23	31.58	8.98	40.15	39.64	54.00	-14.36	Horizontal

Test mode: 802.11g			Test channel: Highest			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3697.48	65.20	29.26	9.12	40.46	63.12	74.00	-10.88	Vertical
4924.00	48.77	31.69	9.08	40.03	49.51	74.00	-24.49	Vertical
3697.48	60.27	29.26	9.12	40.46	58.19	74.00	-15.81	Horizontal
4924.00	50.27	31.69	9.08	40.03	51.01	74.00	-22.99	Horizontal
Test mode: 802.11g			Test channel: Highest			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3697.48	53.27	29.26	9.12	40.46	51.19	54.00	-2.81	Vertical
4924.00	39.16	31.69	9.08	40.03	39.90	54.00	-14.10	Vertical
3697.48	50.12	29.26	9.12	40.46	48.04	54.00	-5.96	Horizontal
4924.00	40.21	31.69	9.08	40.03	40.95	54.00	-13.05	Horizontal

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.



Test mode: 802.11n(H20)			Test channel: Lowest			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3619.18	63.12	29.18	8.99	40.35	60.94	74.00	-13.06	Vertical
4824.00	47.12	31.53	8.90	40.24	47.31	74.00	-26.69	Vertical
3619.18	58.79	29.18	8.99	40.35	56.61	74.00	-17.39	Horizontal
4824.00	48.37	31.53	8.90	40.24	48.56	74.00	-25.44	Horizontal
Test mode: 802.11n(H20)			Test channel: Lowest			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3619.18	54.25	29.18	8.99	40.35	52.07	54.00	-1.93	Vertical
4824.00	38.22	31.53	8.90	40.24	38.41	54.00	-15.59	Vertical
3619.18	50.66	29.18	8.99	40.35	48.48	54.00	-5.52	Horizontal
4824.00	38.17	31.53	8.90	40.24	38.36	54.00	-15.64	Horizontal

Test mode: 802.11n(H20)			Test channel: Middle			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3647.46	62.06	29.21	9.04	40.39	59.92	74.00	-14.08	Vertical
4874.00	48.13	31.58	8.98	40.15	48.54	74.00	-25.46	Vertical
3647.46	60.00	29.21	9.04	40.39	57.86	74.00	-16.14	Horizontal
4874.00	48.51	31.58	8.98	40.15	48.92	74.00	-25.08	Horizontal
Test mode: 802.11n(H20)			Test channel: Middle			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3647.46	52.48	29.21	9.04	40.39	50.34	54.00	-3.66	Vertical
4874.00	38.09	31.58	8.98	40.15	38.50	54.00	-15.50	Vertical
3647.46	52.07	29.21	9.04	40.39	49.93	54.00	-4.07	Horizontal
4874.00	38.14	31.58	8.98	40.15	38.55	54.00	-15.45	Horizontal

Test mode: 802.11n(H20)			Test channel: Highest			Remark: Peak		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3697.48	64.24	29.26	9.12	40.46	62.16	74.00	-11.84	Vertical
4924.00	47.33	31.69	9.08	40.03	48.07	74.00	-25.93	Vertical
3697.48	62.13	29.26	9.12	40.46	60.05	74.00	-13.95	Horizontal
4924.00	50.33	31.69	9.08	40.03	51.07	74.00	-22.93	Horizontal
Test mode: 802.11n(H20)			Test channel: Highest			Remark: Average		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polar.
3697.48	51.16	29.26	9.12	40.46	49.08	54.00	-4.92	Vertical
4924.00	38.10	31.69	9.08	40.03	38.84	54.00	-15.16	Vertical
3697.48	48.25	29.26	9.12	40.46	46.17	54.00	-7.83	Horizontal
4924.00	40.48	31.69	9.08	40.03	41.22	54.00	-12.78	Horizontal

**Remark:**

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
- The emission levels of other frequencies are very lower than the limit and not show in test report.