

TEST REPORT

Applicant Name : TECNO MOBILE LIMITED
Address : FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35
SHAN MEI STREET FOTAN NT Hong Kong
Report Number : SZ1210927-50387E-RF-00B
FCC ID: 2ADYY-KG5K

Test Standard (s)

FCC PART 15.247


Sample Description

Product Type: Mobile Phone
Model No.: KG5k
Multiple Model(s) No.: N/A
Trade Mark: TECNO
Date Received: 2021/09/27
Date of Test: 2021/09/30~2021/11/16
Report Date: 2021/11/16

Test Result:	Pass*
--------------	-------


* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:



Ting Lü
EMC Engineer

Approved By:



Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC§15.247 (I), §1.1307 (B) (1) & §2.1093 – RF EXPOSURE	12
APPLICABLE STANDARD	12
FCC §15.203 - ANTENNA REQUIREMENT	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER SETUP	14
TEST PROCEDURE	14
TRANSF. FACTOR & MARGIN CALCULATION	15
TEST DATA	15
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	19
TEST PROCEDURE	19
FACTOR & MARGIN CALCULATION	19
TEST DATA	19
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST DATA	27
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST DATA	28
FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	29

APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST DATA	29
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST DATA	30
APPENDIX WI-FI.....	31
APPENDIX A: DTS BANDWIDTH	31
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	36
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	41
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	42
APPENDIX E: BAND EDGE MEASUREMENTS	47
APPENDIX F: DUTY CYCLE	50
APPENDIX BLE.....	53
APPENDIX A: DTS BANDWIDTH	53
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	56
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	59
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	60
APPENDIX E: BAND EDGE MEASUREMENTS	63
APPENDIX F: DUTY CYCLE	65

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	BLE: 2402-2480MHz Wi-Fi: 2412-2472MHz
Maximum Conducted Peak Output Power	BLE 1M: 1.89dBm, BLE 2M: 1.79dBm Wi-Fi: 10.14dBm(802.11b), 13.25dBm(802.11g) 13.47dBm(802.11n20), 13.65dBm(802.11n40)
Modulation Technique	BLE: GFSK Wi-Fi: DSSS, OFDM
Antenna Specification*	1.2 dBi (provided by the applicant)
Voltage Range	DC 3.85V from battery or DC 5.0 from adapter
Sample serial number	SZ1210927-50387E-RF-S1 (Assigned by ATC)
Sample/EUT Status	Good condition
Adapter information	Model: U100TSA Input: AC 100-240V ~ 50/60Hz, 0.3A Output: DC 5.0V, 2.0A

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Line Conducted emission		2.72dB
Emissions, Radiated	30MHz - 1GHz	4.28dB
	1GHz- 18GHz	4.98dB
	18GHz- 26.5GHz	5.06dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 mode, total 13 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442		

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 7 and 13.

802.11n-HT40 mode was tested with Channel 3, 7 and 11.

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

EUT was test in engineering mode, which provided by manufacturer and power level as below:

Item	Mode	Data Rate (Mbps)	Power Level*
Wi-Fi	802.11 b	1Mbps	2
	802.11 g	6Mbps	2
	802.11 n20	MCS0	2
	802.11 n40	MCS0	2
BLE	BLE-1M	1Mbps	Default
	BLE-2M	2Mbps	Default

Duty cycle

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shield Detachable USB Cable	1.0	Adapter	EUT

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1) & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted emission test					
Rohde& Schwarz	Test Receiver	ESPI3	100396	2020/12/24	2021/12/23
R & S	L.I.S.N.	ENV216	101314	2020/12/25	2021/12/24
Anritsu Corp	50ΩCoaxial Switch	MP59B	6200506474	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-2m	No.2	2020/12/25	2021/12/24
Conducted Emission Test Software: e3 19821G (V9)					
Radiated emission test					
Rohde& Schwarz	Test Receiver	ESR	101817	2020/12/24	2021/12/23
Rohde&Schwarz	Spectrum Analyzer	FSV40	101495	2020/12/24	2021/12/23
SONOMA INSTRUMENT	Amplifier	310 N	186131	2020/12/25	2021/12/24
A.H. Systems, inc.	Preamplifier	PAM-0118P	531	2021/11/09	2022/11/08
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2020/11/28	2021/11/27
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2020/12/25	2021/12/24
SCHWARZBECK	LOOP ANTENNA	FMZB1516	1516131	2020/01/05	2023/01/04
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2020/01/05	2023/01/04
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
OREGON SCIENTIFIC	Temperature & Humidity Meter	JB913R	GZ-WS004	2020/01/02	2023/01/01
Unknown	RF Coaxial Cable	N-5m	No.3	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-5m	No.4	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.5	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.6	2020/12/25	2021/12/24
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2020/12/25	2021/12/24
Radiated Emission Test Software: e3 19821G (V9)					
Radiated Emission Test Software: EZ_EMV 1.1.4.2					

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF conducted test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2020/12/24	2021/12/23
Tonscend	RF Control Unit	JS0806-2	19G8060182	2021/07/06	2022/07/05

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For worst case:

Mode	Frequency (MHz)	Max tune-up conducted power (dBm)	Max tune-up conducted power (mW)	Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2402-2480	2.0	1.58	5	0.5	3.0	Yes
WIFI	2412-2472	9.0	7.94	5	2.5	3.0	Yes

Result: No SAR test is required

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna which was permanently attached, and the maximum antenna gain is 1.2dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Transd Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{level}$$

$$\text{Level} = \text{reading level} + \text{Transd Factor}$$

Test Data


Environmental Conditions

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Bin Duan on 2021-11-16.


EUT operation mode: Transmitting (Worst case is 802.11n40, middle channel)

AC 120V/60 Hz, Line



Site : Shielding Room
Condition: Line
Mode : 2.4G WIFI
Model : KG5kTECNO MOBILE LIMITED

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.168	9.86	24.33	34.19	55.04	-20.85	Average
2	0.168	9.86	34.44	44.30	65.04	-20.74	QP
3	0.222	9.80	16.75	26.55	52.73	-26.18	Average
4	0.222	9.80	29.67	39.47	62.73	-23.26	QP
5	0.466	9.80	10.49	20.29	46.59	-26.30	Average
6	0.466	9.80	21.10	30.90	56.59	-25.69	QP
7	0.568	9.81	19.09	28.90	46.00	-17.10	Average
8	0.568	9.81	27.74	37.55	56.00	-18.45	QP
9	3.436	9.93	6.23	16.16	46.00	-29.84	Average
10	3.436	9.93	15.34	25.27	56.00	-30.73	QP
11	5.513	10.02	4.00	14.02	50.00	-35.98	Average
12	5.513	10.02	12.51	22.53	60.00	-37.47	QP

AC 120V/60 Hz, Neutral

Site : Shielding Room
 Condition: Neutral
 Mode : 2.4G WIFI
 Model : KG5kTECNO MOBILE LIMITED

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.161	9.93	24.15	34.08	55.39	-21.31	Average
2	0.161	9.93	32.36	42.29	65.39	-23.10	QP
3	0.223	9.99	19.20	29.19	52.70	-23.51	Average
4	0.223	9.99	30.42	40.41	62.70	-22.29	QP
5	0.330	9.95	23.89	33.84	49.46	-15.62	Average
6	0.330	9.95	27.97	37.92	59.46	-21.54	QP
7	0.551	9.91	26.40	36.31	46.00	-9.69	Average
8	0.551	9.91	33.14	43.05	56.00	-12.95	QP
9	2.203	9.93	18.98	28.91	46.00	-17.09	Average
10	2.203	9.93	24.52	34.45	56.00	-21.55	QP
11	5.828	10.06	13.00	23.06	50.00	-26.94	Average
12	5.828	10.06	18.56	28.62	60.00	-31.38	QP


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Factor} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned} \text{Margin} &= \text{Result} - \text{Limit} \\ \text{Result} &= \text{Reading} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	50~64 %
ATM Pressure:	103.0 kPa

The testing was performed by Bin Deng on 2021-11-09 for below 1GHz and by Chao Mo on 2021-11-07 for above 1GHz.

EUT operation mode: Transmitting(Pre-scan in the X,Y and Z axes of orientation, the worst case of orientation was recorded)

30MHz-1GHz: (Worst case is 802.11n40, middle channel)


Horizontal



Site : chamber
Condition: 3m Horizontal
Job NO. : SZ1210927-50387E-RF
Mode : 2.4G WIFI

	Freq Factor		Read		Limit	Over	Remark
	MHz	dB/m	Level	Level	Line	Limit	
			dBuV	dBuV/m	dBuV/m	dB	
1	30.21	-20.50	38.84	18.34	40.00	-21.66	Peak
2	47.99	-17.32	37.45	20.13	40.00	-19.87	Peak
3	102.72	-19.17	37.37	18.20	43.50	-25.30	Peak
4	390.72	-15.77	38.05	22.28	46.00	-23.72	Peak
5	582.74	-11.18	39.07	27.89	46.00	-18.11	Peak
6	996.50	-7.42	38.03	30.61	54.00	-23.39	Peak

Vertical



Site : chamber
Condition: 3m VERTICAL
Job NO. : SZ1210927-50387E-RF
Mode : 2.4G WIFI

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	37.02	-19.13	34.70	15.57	40.00	-24.43	Peak
2	45.06	-17.44	35.15	17.71	40.00	-22.29	Peak
3	101.64	-19.17	34.15	14.98	43.50	-28.52	Peak
4	383.93	-15.75	35.74	19.99	46.00	-26.01	Peak
5	726.81	-11.33	37.17	25.84	46.00	-20.16	Peak
6	952.09	-8.04	36.69	28.65	46.00	-17.35	Peak

1-25 GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
BLE 1M, Low Channel									
2310	44.72	PK	131	1.7	H	-6.84	37.88	74	-36.12
2310	45.18	PK	111	1.8	V	-6.84	38.34	74	-35.66
2390	44.81	PK	8	1.3	H	-6.44	38.37	74	-35.63
2390	44.11	PK	269	1.1	V	-6.44	37.67	74	-36.33
4804	44.88	PK	290	2.1	H	2.81	47.69	74	-26.31
4804	48.29	PK	129	2.0	V	2.81	51.1	74	-22.9
BLE 1M, Middle Channel									
4880	45.5	PK	109	1.3	H	3.04	48.54	74	-25.46
4880	47.32	PK	332	1.8	V	3.04	50.36	74	-23.64
BLE 1M, High Channel									
2483.5	44.7	PK	15	2.1	H	-5.96	38.74	74	-35.26
2483.5	46.91	PK	198	1.4	V	-5.96	40.95	74	-33.05
2500	46.76	PK	71	1.2	H	-5.88	40.88	74	-33.12
2500	46.28	PK	70	2.2	V	-5.88	40.4	74	-33.60
4960	45.29	PK	129	1.8	H	3.29	48.58	74	-25.42
4960	47.43	PK	312	1.2	V	3.29	50.72	74	-23.28
BLE 2M, Low Channel									
2310	44.36	PK	75	1.8	H	-6.84	37.52	74	-36.48
2310	45.6	PK	162	1.3	V	-6.84	38.76	74	-35.24
2390	45.32	PK	9	1.5	H	-6.44	38.88	74	-35.12
2390	45.18	PK	61	1.3	V	-6.44	38.74	74	-35.26
4804	44.02	PK	227	1.4	H	2.81	46.83	74	-27.17
4804	46.48	PK	297	1.5	V	2.81	49.29	74	-24.71
BLE 2M, Middle Channel									
4880	45.73	PK	200	1.7	H	3.04	48.77	74	-25.23
4880	45.84	PK	306	1.1	V	3.04	48.88	74	-25.12
BLE 2M, High Channel									
2483.5	45.6	PK	16	1.0	H	-5.96	39.64	74	-34.36
2483.5	46.84	PK	99	1.9	V	-5.96	40.88	74	-33.12
2500	45.46	PK	248	2.1	H	-5.88	39.58	74	-34.42
2500	45.76	PK	197	1.7	V	-5.88	39.88	74	-34.12
4960	45.84	PK	262	1.9	H	3.29	49.13	74	-24.87
4960	46.22	PK	240	2.0	V	3.29	49.51	74	-24.49

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude - Limit

The other spurious emission which is 20dB to the limit was not recorded.

The test result of peak was less than the limit of average, so just peak values were recorded.

Wi-Fi:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
802.11B, Low Channel									
2310	46.18	PK	325	1.5	H	-6.84	39.34	74	-34.66
2310	46.6	PK	121	1.6	V	-6.84	39.76	74	-34.24
2390	59.94	PK	242	1.9	H	-6.44	53.5	74	-20.50
2390	47.98	PK	248	1.4	V	-6.44	41.54	74	-32.46
4824	44.28	PK	25	1.1	H	2.87	47.15	74	-26.85
4824	44.68	PK	33	2.1	V	2.87	47.55	74	-26.45
802.11B, Middle Channel									
4884	43.53	PK	182	1.4	H	3.04	46.57	74	-27.43
4884	44.48	PK	94	1.4	V	3.04	47.52	74	-26.48
11B, High Channel									
2483.5	59.82	PK	126	2.1	H	-5.96	53.86	74	-20.14
2483.5	52.84	PK	177	1.1	V	-5.96	46.88	74	-27.12
2500	46	PK	189	1.3	H	-5.88	40.12	74	-33.88
2500	46.46	PK	35	1.5	V	-5.88	40.58	74	-33.42
4944	43.57	PK	195	1.2	H	3.23	46.8	74	-27.2
4944	43.22	PK	153	1.5	V	3.23	46.45	74	-27.55
802.11G, Low Channel									
2310	46.75	PK	64	1.7	H	-6.84	39.91	74	-34.09
2310	44.09	PK	345	1.7	V	-6.84	37.25	74	-36.75
2390	73.6	PK	323	1.7	H	-6.44	67.16	74	-6.84
2390	48.12	AV	323	1.7	H	-6.44	41.68	54	-12.32
2390	62.72	PK	328	1.5	V	-6.44	56.28	74	-17.72
2390	45.41	AV	328	1.5	V	-6.44	38.97	54	-15.03
4824	42.72	PK	258	1.6	H	2.87	45.59	74	-28.41
4824	43.7	PK	165	1.4	V	2.87	46.57	74	-27.43
802.11G, Middle Channel									
4884	42.03	PK	203	2.0	H	3.04	45.07	74	-28.93
4884	42.85	PK	138	1.9	V	3.04	45.89	74	-28.11
802.11G, High Channel									
2483.5	70.98	PK	130	1.5	H	-5.96	65.02	74	-8.98
2483.5	49.81	AV	130	1.5	H	-5.96	43.85	54	-10.15
2483.5	69.76	PK	6	1.6	V	-5.96	63.8	74	-10.20
2483.5	41.79	AV	6	1.6	V	-5.96	35.83	54	-18.17
2500	47.78	PK	68	1.8	H	-5.88	41.9	74	-32.10
2500	46.31	PK	349	1.4	V	-5.88	40.43	74	-33.57
4944	42.14	PK	174	1.4	H	3.23	45.37	74	-28.63
4944	43.32	PK	289	2.0	V	3.23	46.55	74	-27.45

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
802.11N20, Low Channel									
2310	45.82	PK	140	1.6	H	-6.84	38.98	74	-35.02
2310	45.63	PK	124	1.5	V	-6.84	38.79	74	-35.21
2390	75.49	PK	72	1.2	H	-6.44	69.05	74	-4.95
2390	47.92	AV	72	1.2	H	-6.44	41.48	54	-12.52
2390	76.7	PK	233	2.1	V	-6.44	70.26	74	-3.74
2390	43.87	AV	233	2.1	V	-6.44	37.43	54	-16.57
4824	44.39	PK	114	1.9	H	2.87	47.26	74	-26.74
4824	44.19	PK	50	1.6	V	2.87	47.06	74	-26.94
802.11 N20, Middle Channel									
4884	43.32	PK	263	1.5	H	3.04	46.36	74	-27.64
4884	43.55	PK	102	1.2	V	3.04	46.59	74	-27.41
802.11 N20, High Channel									
2483.5	73.41	PK	169	1.5	H	-5.96	67.45	74	-6.55
2483.5	43.77	AV	169	1.5	H	-5.96	37.81	54	-16.19
2483.5	61.93	PK	316	1.9	V	-5.96	55.97	74	-18.03
2483.5	40.65	AV	316	1.9	V	-5.96	34.69	54	-19.31
2500	50.19	PK	71	1.0	H	-5.88	44.31	74	-29.69
2500	45.67	PK	25	1.7	V	-5.88	39.79	74	-34.21
4944	42.15	PK	189	1.9	H	3.23	45.38	74	-28.62
4944	43.34	PK	209	1.4	V	3.23	46.57	74	-27.43
802.11N40, Low Channel									
2310	45.96	PK	266	1.1	H	-6.84	39.12	74	-34.88
2310	46.09	PK	178	2.0	V	-6.84	39.25	74	-34.75
2390	77.43	PK	54	1.1	H	-6.44	70.99	74	-3.01
2390	53.72	AV	54	1.1	H	-6.44	47.28	54	-6.72
2390	76.38	PK	87	1.4	V	-6.44	69.94	74	-4.06
2390	50.2	AV	87	1.4	V	-6.44	43.76	54	-10.24
4844	43.87	PK	232	1.5	H	2.92	46.79	74	-27.21
4844	45.65	PK	260	1.3	V	2.92	48.57	74	-25.43
802.11N40, Middle Channel									
4884	42.98	PK	316	1.8	H	3.04	46.02	74	-27.98
4884	44.47	PK	53	2.0	V	3.04	47.51	74	-26.49
802.11N40, High Channel									
2483.5	77.89	PK	105	2.1	H	-5.96	71.93	74	-2.07
2483.5	50.03	AV	105	2.1	H	-5.96	44.07	54	-9.93
2483.5	74.74	PK	76	1.1	V	-5.96	68.78	74	-5.22
2483.5	49.95	AV	76	1.1	V	-5.96	43.99	54	-10.01
2500	63.38	PK	124	1.9	H	-5.88	57.5	74	-16.50
2500	39.11	AV	124	1.9	H	-5.88	33.23	54	-20.77
2500	58.27	PK	335	1.1	V	-5.88	52.39	74	-21.61
4924	44.76	PK	53	1.8	H	3.17	47.93	74	-26.07
4924	47.47	PK	241	1.7	V	3.17	50.64	74	-23.36

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading


Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB to the limit was not recorded.


The test result of peak was less than the limit of average, so just peak values were recorded.

1-18 GHz:

Pre-scan for Peak
BLE 1M, Low Channel
Horizontal




Vertical




18 -25GHz:

Pre-scan for Peak
BLE 1M, Low Channel
Horizontal



Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	63 %
ATM Pressure:	101.0 kPa

The testing was performed by Paul Liu on 2021-11-11 and 2021-11-13.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	63 %
ATM Pressure:	101.0 kPa

The testing was performed by Paul Liu on 2021-11-11.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	63 %
ATM Pressure:	101.0 kPa

The testing was performed by Paul Liu on 2021-11-11.

EUT operation mode: Transmitting

Test Result: Compliant.

Conducted Band Edge Result:

Please refer to the Appendix Wi-Fi and Appendix BLE.


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	63 %
ATM Pressure:	101.0 kPa

The testing was performed by Paul Liu on 2021-11-11.

EUT operation mode: Transmitting


Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

APPENDIX Wi-Fi


Appendix A: DTS Bandwidth Test Result

Test Mode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.120	0.5	PASS
		2442	8.120	0.5	PASS
		2472	8.160	0.5	PASS
11G	Ant1	2412	16.382	0.5	PASS
		2442	15.800	0.5	PASS
		2472	15.200	0.5	PASS
11N20SISO	Ant1	2412	17.240	0.5	PASS
		2442	16.000	0.5	PASS
		2472	15.200	0.5	PASS
11N40SISO	Ant1	2422	35.760	0.5	PASS
		2442	30.240	0.5	PASS
		2462	35.920	0.5	PASS


Test Graphs




11G Ant1_2412





11G Ant1_2442



11G Ant1_2472










**Appendix B: Occupied Channel Bandwidth
Test Result**


Test Mode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	12.268	---	PASS
		2442	12.028	---	PASS
		2472	11.988	---	PASS
11G	Ant1	2412	17.463	---	PASS
		2442	16.903	---	PASS
		2472	16.823	---	PASS
11N20SISO	Ant1	2412	18.022	---	PASS
		2442	17.582	---	PASS
		2472	17.463	---	PASS
11N40SISO	Ant1	2422	36.683	---	PASS
		2442	35.884	---	PASS
		2462	37.003	---	PASS

Test Graphs









Appendix C: Maximum conducted output power Test Result

PK:

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	9.96	<=30	PASS
		2442	10.14	<=30	PASS
		2472	10.05	<=30	PASS
11G	Ant1	2412	13.15	<=30	PASS
		2442	13.23	<=30	PASS
		2472	13.25	<=30	PASS
11N20SISO	Ant1	2412	13.26	<=30	PASS
		2442	13.47	<=30	PASS
		2472	13.19	<=30	PASS
11N40SISO	Ant1	2422	13.48	<=30	PASS
		2442	13.65	<=30	PASS
		2462	13.54	<=30	PASS


AV:


Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	8.57	<=30	PASS
		2442	8.45	<=30	PASS
		2472	8.47	<=30	PASS
11G	Ant1	2412	8.47	<=30	PASS
		2442	8.56	<=30	PASS
		2472	8.46	<=30	PASS
11N20SISO	Ant1	2412	8.47	<=30	PASS
		2442	8.65	<=30	PASS
		2472	8.56	<=30	PASS
11N40SISO	Ant1	2422	8.46	<=30	PASS
		2442	8.59	<=30	PASS
		2462	8.57	<=30	PASS


**Appendix D: Maximum power spectral density
Test Result**


Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-18.88	<=8	PASS
		2442	-17.94	<=8	PASS
		2472	-18.66	<=8	PASS
11G	Ant1	2412	-23.12	<=8	PASS
		2442	-20.79	<=8	PASS
		2472	-23.16	<=8	PASS
11N20SISO	Ant1	2412	-23.21	<=8	PASS
		2442	-21.83	<=8	PASS
		2472	-23.37	<=8	PASS
11N40SISO	Ant1	2422	-22.85	<=8	PASS
		2442	-25.07	<=8	PASS
		2462	-25.53	<=8	PASS

Test Graphs












11B_Ant1_Low_2412




11G Ant1_High_2472




11N20SISO_Ant1_Low_2412



11N20SISO_Ant1_High_2472







**Appendix F: Duty Cycle
Test Result**

TestMode	Antenna	Channel	TransmissionDuration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2442	0.70	0.82	85.37
11G	Ant1	2442	0.10	0.19	52.63
11N20SISO	Ant1	2442	0.10	0.19	52.63
11N40SISO	Ant1	2442	0.05	0.15	33.33

Test Graphs







APPENDIX BLE

Appendix A: DTS Bandwidth Test Result

Test Mode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.528	0.5	PASS
		2440	0.528	0.5	PASS
		2480	0.532	0.5	PASS
BLE_2M	Ant1	2402	0.888	0.5	PASS
		2440	0.888	0.5	PASS
		2480	0.888	0.5	PASS

Test Graphs







**Appendix B: Occupied Channel Bandwidth
Test Result**

Test Mode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.031	---	PASS
		2440	1.031	---	PASS
		2480	1.031	---	PASS
BLE_2M	Ant1	2402	2.042	---	PASS
		2440	2.042	---	PASS
		2480	2.042	---	PASS

Test Graphs







**Appendix C: Maximum conducted output power
Test Result**

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	1.89	<=30	PASS
		2440	-1.33	<=30	PASS
		2480	-0.59	<=30	PASS
BLE_2M	Ant1	2402	1.79	<=30	PASS
		2440	-1.56	<=30	PASS
		2480	-0.8	<=30	PASS

**Appendix D: Maximum power spectral density
Test Result**


Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-16.73	<=8	PASS
		2440	-19.39	<=8	PASS
		2480	-17.72	<=8	PASS
BLE_2M	Ant1	2402	-22.1	<=8	PASS
		2440	-24.81	<=8	PASS
		2480	-23.2	<=8	PASS

Test Graphs




Appendix E: Band edge measurements Test Graphs





**Appendix F: Duty Cycle
Test Result**

Test Mode	Antenna	Channel	TransmissionDuration [ms]	Transmission Period [ms]	Duty Cycle [%]
BLE_1M	Ant1	2440	1.62	1.85	87.34
BLE_2M	Ant1	2440	0.81	1.23	65.87

Test Graphs

***** END OF REPORT *****