



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: TECNO MOBILE LIMITED

Address: FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25
SHAN MEI STREET FOTAN NT HONGKONG

FCC ID: 2ADYY-LI9

Product Name: Mobile Phone

Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05r02

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR231167220-00C

Date Of Issue: 2023/12/19

Reviewed By: Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China
Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST CONFIGURATION.....	8
1.2.1 EUT Operation Condition:.....	8
1.2.2 Support Equipment List and Details	8
1.2.3 Support Cable List and Details	8
1.2.4 Block Diagram of Test Setup.....	9
1.3 MEASUREMENT UNCERTAINTY	10
2. SUMMARY OF TEST RESULTS	11
3. REQUIREMENTS AND TEST PROCEDURES	12
3.1 AC LINE CONDUCTED EMISSIONS.....	12
3.1.1 Applicable Standard.....	12
3.1.2 EUT Setup.....	13
3.1.3 EMI Test Receiver Setup	13
3.1.4 Test Procedure	14
3.1.5 Corrected Amplitude & Margin Calculation.....	14
3.2 RADIATION SPURIOUS EMISSIONS.....	15
3.2.1 Applicable Standard.....	15
3.2.2 EUT Setup.....	15
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
3.2.4 Test Procedure	17
3.2.5 Corrected Amplitude & Margin Calculation.....	17
3.3 MINIMUM 6 dB EMISSION BANDWIDTH	18
3.3.1 Applicable Standard.....	18
3.3.2 EUT Setup.....	18
3.3.3 Test Procedure	18
3.4 99% OCCUPIED BANDWIDTH.....	19
3.4.1 EUT Setup.....	19
3.4.2 Test Procedure	19
3.5 MAXIMUM CONDUCTED OUTPUT POWER.....	20
3.5.1 Applicable Standard.....	20
3.5.2 EUT Setup.....	20
3.5.3 Test Procedure	20
3.6 MAXIMUM POWER SPECTRAL DENSITY	21
3.6.1 Applicable Standard.....	21
3.6.2 EUT Setup.....	21
3.6.3 Test Procedure	21
3.7 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	22
3.7.1 Applicable Standard.....	22
3.7.2 EUT Setup.....	22
3.7.3 Test Procedure	22

3.8 DUTY CYCLE	23
3.8.1 EUT Setup.....	23
3.8.2 Test Procedure	23
3.9 ANTENNA REQUIREMENT.....	23
3.9.1 Applicable Standard.....	23
3.9.2 Judgment.....	23
4. Test DATA AND RESULTS.....	24
4.1 AC LINE CONDUCTED EMISSIONS.....	24
4.2 RADIATION SPURIOUS EMISSIONS.....	27
4.3 MINIMUM 6 dB EMISSION BANDWIDTH	54
4.4 99% OCCUPIED BANDWIDTH.....	64
4.5 MAXIMUM CONDUCTED OUTPUT POWER.....	74
4.6 MAXIMUM POWER SPECTRAL DENSITY	76
4.7 100 KHz BANDWIDTH OF FREQUENCY BAND EDGE:	86
4.8 DUTY CYCLE:.....	95
5. EUT PHOTOGRAPHS	100
6. TEST SETUP PHOTOGRAPHS	101

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR231167220-00C	Original Report	2023/12/19

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Mobile Phone
Trade Name:	Tecno
EUT Model:	LI9
Operation Frequency:	2412-2472 MHz(802.11b/g/n ht20) 2422-2462 MHz(802.11n ht40)
Maximum Peak Output Power (Conducted):	Main ANT: 16.97dBm Aux ANT: 19.03dBm
Modulation Type:	802.11b:DSSS-DBPSK, DQPSK, CCK 802.11g/n:OFDM-BPSK, QPSK, 16QAM, 64QAM
Rated Input Voltage:	DC 3.91V from battery or DC5V or 5-10V or 11V or 4-20V from adapter
Serial Number:	CE&RE: 2DMI-2 RF: 2DMI-1
EUT Received Date:	2023/11/15
EUT Received Status:	Good

Operation Frequency Detail: For 802.11b/g/n ht20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/
Per section 15.31(m), the below frequencies were performed the test as below:			
Test Channel		Frequency (MHz)	
Lowest		2412	
Middle		2442	
Highest		2472	

For 802.11n ht40:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	8	2447
4	2427	9	2452
5	2432	10	2457
6	2437	11	2462
7	2442	/	/
Per section 15.31(m), the below frequencies were performed the test as below:			
Test Channel		Frequency (MHz)	
Lowest		2422	
Middle		2442	
Highest		2462	

Antenna Information Detail▲:

Antenna	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain (dBi)
Main ANT	Integral	50	2.4~2.5GHz	-0.48
Aux ANT	Integral	50	2.4~2.5GHz	-2.79

The Method of §15.203 Compliance:

☒ Antenna was permanently attached to the unit.

☐ Antenna use a unique type of connector to attach to the EUT.

☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
Adapter	TECNO	U700TSA	Input:100-240V~50/60Hz 2.0A Output:5.0V, 3.0A 15.0W or 5.0-10.0V, 7.0A MAX or 11.0V, 6.4A MAX or 4.0-20.0V, 3.5A 70.0W MAX

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

For 802.11b/g/n:

EUT Operation Mode:		The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
Equipment Modifications:		No		
EUT Exercise Software:		Engineering mode		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲ :				
Test Modes	Data Rate	Power Level Setting (Main ANT: & Aux ANT:)		
		Lowest Channel	Middle Channel	Highest Channel
802.11b	1Mbps	18.5	18.5	18.5
802.11g	6Mbps	13	13	13
802.11n ht20	MCS0	13	13	13
802.11n ht40	MCS0	13	13	13
Note1: The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations. Note2: According to the manufacturer, for 2.4G Wi-Fi, the EUT has two antennas, which will be switched through SW circuit according to environmental conditions during actual operation. Only one antenna is working at any moment in time.				

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Unknown	Earphone	Unknown	Unknown

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	1.0	EUT	adapter
Earphone Cable	No	No	1.2	Earphone	EUT

1.2.4 Block Diagram of Test Setup

AC Line Conducted Emissions:



Spurious emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 4.12dB,30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	Minimum 6 dB Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth Of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.203	Antenna Requirement	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


3.2.2 EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz -1000 MHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	≥1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 Minimum 6 dB Emission Bandwidth

3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.3.2 EUT Setup




3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.4 99% Occupied Bandwidth

3.4.1 EUT Setup



3.4.2 Test Procedure

According to ANSI C63.10-2013 Section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- Step a) through step c) might require iteration to adjust within the specified range.
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).


3.5 Maximum Conducted Output Power

3.5.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

According to ANSI C63.10-2013 Section 11.9.2.3.2

Method AVGPM-G is a measurement using a gated RF average power meter.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.


3.6 Maximum Power Spectral Density

3.6.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.6.2 EUT Setup



3.6.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


3.7 100 kHz Bandwidth of Frequency Band Edge

3.7.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.7.2 EUT Setup



3.7.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.8 Duty Cycle

3.8.1 EUT Setup



3.8.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.9 Antenna Requirement

3.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.9.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	2DMI-2	Test Date:	2023/11/23
Test Site:	CE	Test Mode:	Transmitting (maximum output power mode, Aux ANT, 802.11n ht40, 2442MHz)
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.2	Relative Humidity: (%)	52	ATM Pressure: (kPa)	101.1
----------------------	------	------------------------------	----	------------------------	-------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2023/3/31	2024/3/30
R&S	EMI Test Receiver	ESR3	102726	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2023/8/6	2024/8/5
Audix	Test Software	E3	190306 (V9)	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Project No.: CR231167220-RF
Tester: David Huang
Port: Line
Note: Transmitting(2.4G WIFI)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.716	21.93	9.62	31.55	46.00	14.45	Average
2	0.716	36.88	9.62	46.50	56.00	9.50	QP
3	1.236	21.90	9.62	31.52	46.00	14.48	Average
4	1.236	33.99	9.62	43.61	56.00	12.39	QP
5	2.437	17.85	9.64	27.49	46.00	18.51	Average
6	2.437	29.53	9.64	39.17	56.00	16.83	QP
7	3.620	18.74	9.65	28.39	46.00	17.61	Average
8	3.620	30.09	9.65	39.74	56.00	16.26	QP
9	5.326	16.60	9.66	26.26	50.00	23.74	Average
10	5.326	27.93	9.66	37.59	60.00	22.41	QP
11	14.932	19.19	9.69	28.88	50.00	21.12	Average
12	14.932	31.19	9.69	40.88	60.00	19.12	QP

Project No.: CR231167220-RF
 Tester: David Huang
 Port: neutral
 Note: Transmitting(2.4G WIFI)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.532	15.07	9.61	24.68	46.00	21.32	Average
2	0.532	29.44	9.61	39.05	56.00	16.95	QP
3	0.666	21.77	9.62	31.39	46.00	14.61	Average
4	0.666	35.39	9.62	45.01	56.00	10.99	QP
5	1.239	22.95	9.62	32.57	46.00	13.43	Average
6	1.239	34.23	9.62	43.85	56.00	12.15	QP
7	2.481	17.29	9.64	26.93	46.00	19.07	Average
8	2.481	28.90	9.64	38.54	56.00	17.46	QP
9	3.672	18.49	9.65	28.14	46.00	17.86	Average
10	3.672	30.03	9.65	39.68	56.00	16.32	QP
11	13.580	19.00	9.68	28.68	50.00	21.32	Average
12	13.580	31.00	9.68	40.68	60.00	19.32	QP

4.2 Radiation Spurious Emissions

Serial Number:	2DMI-2	Test Date:	Below 1GHz: 2023/12/2 Above 1GHz: 2023/12/2
Test Site:	966-2, 966-1	Test Mode:	Transmitting
Tester:	Vic Du, Mack Huang	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	24.7~25.7	Relative Humidity: (%)	46~57	ATM Pressure: (kPa)	101~101.7

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-6	2023/9/18	2026/9/17
BACL	Loop Antenna	1313-1P	3092721	2023/10/20	2026/10/19
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/7/16	2024/7/15
Sonoma	Amplifier	310N	186165	2023/7/16	2024/7/15
Audix	Test Software	E3	201021 (V9)	N/A	N/A
AH	Double Ridge Guide Horn Antenna	SAS-571	1394	2023/2/22	2026/2/21
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2023/8/6	2024/8/5
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2023/8/6	2024/8/5
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2023/11/8	2024/11/7
Audix	Test Software	E3	201021 (V9)	N/A	N/A
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/2/5	2024/2/4
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2023/9/15	2024/9/14
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2023/8/6	2024/8/5
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2023/8/6	2024/8/5
Mini Circuits	High Pass Filter	VHF-6010+	31119	2023/8/6	2024/8/5

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

For 9kHz-30MHz, The amplitude of spurious emissions attenuated more than 20 dB below the limit was not be recorded


1) 30MHz-1GHz (Transmitting maximum output power mode 802.11n-ht40 Aux ANT)**Low Channel**

Project No.: CR231167220-RF
Tester: Vic Du
Polarization: horizontal
Note: Transmitting 2.4G WiFi



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.638	32.64	-4.28	28.36	40.00	11.64	Peak
2	68.151	37.83	-16.73	21.10	40.00	18.90	Peak
3	104.536	37.38	-13.44	23.94	43.50	19.56	Peak
4	162.611	35.10	-12.21	22.89	43.50	20.61	Peak
5	208.580	35.89	-12.46	23.43	43.50	20.07	Peak
6	887.610	29.03	-1.09	27.94	46.00	18.06	Peak


Project No.: CR231167220-RF
Tester: Vic Du
Polarization: vertical
Note: Transmitting 2.4G WiFi



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	35.57	-4.20	31.37	40.00	8.63	Peak
2	42.600	39.75	-12.87	26.88	40.00	13.12	Peak
3	64.659	41.36	-16.95	24.41	40.00	15.59	Peak
4	99.878	35.11	-14.35	20.76	43.50	22.74	Peak
5	210.786	34.93	-12.52	22.41	43.50	21.09	Peak
6	912.862	28.09	-0.62	27.47	46.00	18.53	Peak


Middle Channel

Project No.: CR231167220-RF
Tester: Vic Du
Polarization: horizontal
Note: Transmitting 2.4G WiFi



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	28.66	-4.20	24.46	40.00	15.54	Peak
2	65.803	37.99	-16.89	21.10	40.00	18.90	Peak
3	103.806	36.36	-13.58	22.78	43.50	20.72	Peak
4	185.788	37.27	-13.52	23.75	43.50	19.75	Peak
5	210.048	36.29	-12.49	23.80	43.50	19.70	Peak
6	909.667	28.22	-0.62	27.60	46.00	18.40	Peak


Project No.: CR231167220-RF
Tester: Vic Du
Polarization: vertical
Note: Transmitting 2.4G WiFi



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.317	35.64	-4.04	31.60	40.00	8.40	Peak
2	42.900	38.36	-13.05	25.31	40.00	14.69	Peak
3	66.266	42.43	-16.86	25.57	40.00	14.43	Peak
4	103.442	33.12	-13.64	19.48	43.50	24.02	Peak
5	209.313	33.67	-12.48	21.19	43.50	22.31	Peak
6	929.008	28.61	-0.59	28.02	46.00	17.98	Peak


High Channel

Project No.: CR231167220-RF
Tester: Vic Du
Polarization: horizontal
Note: Transmitting 2.4G WiFi



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.317	27.88	-4.04	23.84	40.00	16.16	Peak
2	67.913	38.55	-16.75	21.80	40.00	18.20	Peak
3	104.536	36.36	-13.44	22.92	43.50	20.58	Peak
4	158.668	34.46	-11.95	22.51	43.50	20.99	Peak
5	277.094	35.98	-11.85	24.13	46.00	21.87	Peak
6	821.710	28.95	-1.71	27.24	46.00	18.76	Peak

Project No.: CR231167220-RF
Tester: Vic Du
Polarization: vertical
Note: Transmitting 2.4G WiFi



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.211	34.62	-3.96	30.66	40.00	9.34	Peak
2	42.600	38.37	-12.87	25.50	40.00	14.50	Peak
3	67.202	41.92	-16.80	25.12	40.00	14.88	Peak
4	100.229	34.88	-14.28	20.60	43.50	22.90	Peak
5	209.313	33.58	-12.48	21.10	43.50	22.40	Peak
6	863.056	28.45	-1.25	27.20	46.00	18.80	Peak

2) 1-25GHz:**Main ANT:****802.11b Mode**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2390.000	27.14	PK	H	31.71	58.85	74.00	15.15
2390.000	14.72	AV	H	31.71	46.43	54.00	7.57
2390.000	27.00	PK	V	31.71	58.71	74.00	15.29
2390.000	14.57	AV	V	31.71	46.28	54.00	7.72
4824.000	44.97	PK	H	11.26	56.23	74.00	17.77
4824.000	39.50	AV	H	11.26	50.76	54.00	3.24
4824.000	43.68	PK	V	11.26	54.94	74.00	19.06
4824.000	38.24	AV	V	11.26	49.5	54.00	4.50
Middle Channel: 2442 MHz							
4884.000	44.05	PK	H	11.49	55.54	74.00	18.46
4884.000	38.19	AV	H	11.49	49.68	54.00	4.32
4884.000	42.87	PK	V	11.49	54.36	74.00	19.64
4884.000	37.03	AV	V	11.49	48.52	54.00	5.48
High Channel: 2472 MHz							
2483.500	26.60	PK	H	32.19	58.79	74.00	15.21
2483.500	14.83	AV	H	32.19	47.02	54.00	6.98
2483.500	27.02	PK	V	32.19	59.21	74.00	14.79
2483.500	14.54	AV	V	32.19	46.73	54.00	7.27
4944.000	43.14	PK	H	11.74	54.88	74.00	19.12
4944.000	36.97	AV	H	11.74	48.71	54.00	5.29
4944.000	41.88	PK	V	11.74	53.62	74.00	20.38
4944.000	35.83	AV	V	11.74	47.57	54.00	6.43

802.11g Mode

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2390.000	27.41	PK	H	31.71	59.12	74.00	14.88
2390.000	15.53	AV	H	31.71	47.24	54.00	6.76
2390.000	27.27	PK	V	31.71	58.98	74.00	15.02
2390.000	15.40	AV	V	31.71	47.11	54.00	6.89
4824.000	38.30	PK	H	11.26	49.56	74.00	24.44
4824.000	23.86	AV	H	11.26	35.12	54.00	18.88
4824.000	37.97	PK	V	11.26	49.23	74.00	24.77
4824.000	23.59	AV	V	11.26	34.85	54.00	19.15
Middle Channel: 2442 MHz							
4884.000	37.88	PK	H	11.49	49.37	74.00	24.63
4884.000	23.62	AV	H	11.49	35.11	54.00	18.89
4884.000	37.66	PK	V	11.49	49.15	74.00	24.85
4884.000	23.39	AV	V	11.49	34.88	54.00	19.12
High Channel: 2472 MHz							
2483.500	36.90	PK	H	32.19	69.09	74.00	4.91
2483.500	17.34	AV	H	32.19	49.53	54.00	4.47
2483.500	36.29	PK	V	32.19	68.48	74.00	5.52
2483.500	16.92	AV	V	32.19	49.11	54.00	4.89
4944.000	37.37	PK	H	11.74	49.11	74.00	24.89
4944.000	23.20	AV	H	11.74	34.94	54.00	19.06
4944.000	37.13	PK	V	11.74	48.87	74.00	25.13
4944.000	22.94	AV	V	11.74	34.68	54.00	19.32

802.11n ht20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2390.000	26.63	PK	H	31.71	58.34	74.00	15.66
2390.000	14.68	AV	H	31.71	46.39	54.00	7.61
2390.000	27.35	PK	V	31.71	59.06	74.00	14.94
2390.000	15.49	AV	V	31.71	47.2	54.00	6.80
4824.000	38.48	PK	H	11.26	49.74	74.00	24.26
4824.000	23.82	AV	H	11.26	35.08	54.00	18.92
4824.000	38.25	PK	V	11.26	49.51	74.00	24.49
4824.000	23.60	AV	V	11.26	34.86	54.00	19.14
Middle Channel: 2442 MHz							
4884.000	38.14	PK	H	11.49	49.63	74.00	24.37
4884.000	23.55	AV	H	11.49	35.04	54.00	18.96
4884.000	37.91	PK	V	11.49	49.4	74.00	24.60
4884.000	23.33	AV	V	11.49	34.82	54.00	19.18
High Channel: 2472 MHz							
2483.500	37.40	PK	H	32.19	69.59	74.00	4.41
2483.500	17.89	AV	H	32.19	50.08	54.00	3.92
2483.500	36.76	PK	V	32.19	68.95	74.00	5.05
2483.500	17.34	AV	V	32.19	49.53	54.00	4.47
4944.000	37.71	PK	H	11.74	49.45	74.00	24.55
4944.000	23.18	AV	H	11.74	34.92	54.00	19.08
4944.000	37.50	PK	V	11.74	49.24	74.00	24.76
4944.000	22.96	AV	V	11.74	34.7	54.00	19.30

802.11n ht40 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2422 MHz							
2390.000	26.74	PK	H	31.71	58.45	74.00	15.55
2390.000	15.11	AV	H	31.71	46.82	54.00	7.18
2390.000	26.22	PK	V	31.71	57.93	74.00	16.07
2390.000	14.78	AV	V	31.71	46.49	54.00	7.51
4844.000	38.61	PK	H	11.31	49.92	74.00	24.08
4844.000	24.10	AV	H	11.31	35.41	54.00	18.59
4844.000	38.36	PK	V	11.31	49.67	74.00	24.33
4844.000	23.89	AV	V	11.31	35.2	54.00	18.80
Middle Channel: 2442 MHz							
4884.000	38.19	PK	H	11.49	49.68	74.00	24.32
4884.000	23.83	AV	H	11.49	35.32	54.00	18.68
4884.000	37.94	PK	V	11.49	49.43	74.00	24.57
4884.000	23.62	AV	V	11.49	35.11	54.00	18.89
High Channel: 2462 MHz							
2483.500	35.15	PK	H	32.19	67.34	74.00	6.66
2483.500	16.10	AV	H	32.19	48.29	54.00	5.71
2483.500	34.69	PK	V	32.19	66.88	74.00	7.12
2483.500	15.72	AV	V	32.19	47.91	54.00	6.09
4924.000	37.66	PK	H	11.67	49.33	74.00	24.67
4924.000	23.51	AV	H	11.67	35.18	54.00	18.82
4924.000	37.39	PK	V	11.67	49.06	74.00	24.94
4924.000	23.27	AV	V	11.67	34.94	54.00	19.06

Aux ANT:
802.11b Mode

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2390.000	27.23	PK	H	31.71	58.94	74.00	15.06
2390.000	14.57	AV	H	31.71	46.28	54.00	7.72
2390.000	27.48	PK	V	31.71	59.19	74.00	14.81
2390.000	15.72	AV	V	31.71	47.43	54.00	6.57
4824.000	45.40	PK	H	11.26	56.66	74.00	17.34
4824.000	39.69	AV	H	11.26	50.95	54.00	3.05
4824.000	44.26	PK	V	11.26	55.52	74.00	18.48
4824.000	38.74	AV	V	11.26	50	54.00	4.00
Middle Channel: 2442 MHz							
4884.000	44.82	PK	H	11.49	56.31	74.00	17.69
4884.000	39.26	AV	H	11.49	50.75	54.00	3.25
4884.000	43.75	PK	V	11.49	55.24	74.00	18.76
4884.000	38.33	AV	V	11.49	49.82	54.00	4.18
High Channel: 2472 MHz							
2483.500	26.98	PK	H	32.19	59.17	74.00	14.83
2483.500	15.54	AV	H	32.19	47.73	54.00	6.27
2483.500	27.30	PK	V	32.19	59.49	74.00	14.51
2483.500	15.83	AV	V	32.19	48.02	54.00	5.98
4944.000	44.20	PK	H	11.74	55.94	74.00	18.06
4944.000	38.83	AV	H	11.74	50.57	54.00	3.43
4944.000	43.01	PK	V	11.74	54.75	74.00	19.25
4944.000	37.69	AV	V	11.74	49.43	54.00	4.57

802.11g Mode

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2390.000	26.87	PK	H	31.71	58.58	74.00	15.42
2390.000	15.22	AV	H	31.71	46.93	54.00	7.07
2390.000	27.08	PK	V	31.71	58.79	74.00	15.21
2390.000	15.41	AV	V	31.71	47.12	54.00	6.88
4824.000	37.96	PK	H	11.26	49.22	74.00	24.78
4824.000	23.75	AV	H	11.26	35.01	54.00	18.99
4824.000	37.72	PK	V	11.26	48.98	74.00	25.02
4824.000	23.57	AV	V	11.26	34.83	54.00	19.17
Middle Channel: 2442 MHz							
4884.000	37.99	PK	H	11.49	49.48	74.00	24.52
4884.000	23.74	AV	H	11.49	35.23	54.00	18.77
4884.000	37.75	PK	V	11.49	49.24	74.00	24.76
4884.000	23.52	AV	V	11.49	35.01	54.00	18.99
High Channel: 2472 MHz							
2483.500	36.07	PK	H	32.19	68.26	74.00	5.74
2483.500	16.48	AV	H	32.19	48.67	54.00	5.33
2483.500	36.56	PK	V	32.19	68.75	74.00	5.25
2483.500	16.75	AV	V	32.19	48.94	54.00	5.06
4944.000	37.96	PK	H	11.74	49.7	74.00	24.30
4944.000	23.59	AV	H	11.74	35.33	54.00	18.67
4944.000	37.74	PK	V	11.74	49.48	74.00	24.52
4944.000	23.33	AV	V	11.74	35.07	54.00	18.93


802.11n ht20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2390.000	26.72	PK	H	31.71	58.43	74.00	15.57
2390.000	15.88	AV	H	31.71	47.59	54.00	6.41
2390.000	27.04	PK	V	31.71	58.75	74.00	15.25
2390.000	15.15	AV	V	31.71	46.86	54.00	7.14
4824.000	37.85	PK	H	11.26	49.11	74.00	24.89
4824.000	23.66	AV	H	11.26	34.92	54.00	19.08
4824.000	37.61	PK	V	11.26	48.87	74.00	25.13
4824.000	23.44	AV	V	11.26	34.7	54.00	19.30
Middle Channel: 2442 MHz							
4884.000	37.82	PK	H	11.49	49.31	74.00	24.69
4884.000	23.57	AV	H	11.49	35.06	54.00	18.94
4884.000	37.61	PK	V	11.49	49.1	74.00	24.90
4884.000	23.38	AV	V	11.49	34.87	54.00	19.13
High Channel: 2472 MHz							
2483.500	36.58	PK	H	32.19	68.77	74.00	5.23
2483.500	17.33	AV	H	32.19	49.52	54.00	4.48
2483.500	37.10	PK	V	32.19	69.29	74.00	4.71
2483.500	17.72	AV	V	32.19	49.91	54.00	4.09
4944.000	37.83	PK	H	11.74	49.57	74.00	24.43
4944.000	23.50	AV	H	11.74	35.24	54.00	18.76
4944.000	37.57	PK	V	11.74	49.31	74.00	24.69
4944.000	23.29	AV	V	11.74	35.03	54.00	18.97

802.11n ht40 Mode:


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2422 MHz							
2390.000	31.39	PK	H	31.71	63.1	74.00	10.90
2390.000	15.01	AV	H	31.71	46.72	54.00	7.28
2390.000	31.63	PK	V	31.71	63.34	74.00	10.66
2390.000	15.28	AV	V	31.71	46.99	54.00	7.01
4844.000	38.50	PK	H	11.31	49.81	74.00	24.19
4844.000	24.24	AV	H	11.31	35.55	54.00	18.45
4844.000	38.25	PK	V	11.31	49.56	74.00	24.44
4844.000	24.01	AV	V	11.31	35.32	54.00	18.68
Middle Channel: 2442 MHz							
4884.000	38.21	PK	H	11.49	49.7	74.00	24.30
4884.000	24.02	AV	H	11.49	35.51	54.00	18.49
4884.000	37.99	PK	V	11.49	49.48	74.00	24.52
4884.000	23.78	AV	V	11.49	35.27	54.00	18.73
High Channel: 2462 MHz							
2483.500	35.55	PK	H	32.19	67.74	74.00	6.26
2483.500	16.64	AV	H	32.19	48.83	54.00	5.17
2483.500	36.03	PK	V	32.19	68.22	74.00	5.78
2483.500	16.99	AV	V	32.19	49.18	54.00	4.82
4924.000	37.80	PK	H	11.67	49.47	74.00	24.53
4924.000	23.63	AV	H	11.67	35.3	54.00	18.70
4924.000	37.56	PK	V	11.67	49.23	74.00	24.77
4924.000	23.41	AV	V	11.67	35.08	54.00	18.92

Listed with the worst harmonic margin test plot
Main ANT: 802.11b Mode Low Channel



Horizontal

Project No.: CR231167220-RF
Tester: Mack Huang
Polarization: Horizontal
Note: 802.11b Mode Low Channel




6-18GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	16362.870	22.13	25.71	47.84	54.00	6.16	Average
2	16362.870	34.01	25.71	59.72	74.00	14.28	Peak

Horizontal

Project No.: CR231167220-RF
Tester: Mack Huang
Polarization: Horizontal
Note: 802.11b Mode Low Channel




18-25GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	24171.040	41.28	4.93	46.21	54.00	7.79	Average
2	24171.040	53.16	4.93	58.09	74.00	15.91	Peak

Vertical

Project No.: CR231167220-RF
Tester: Mack Huang
Polarization: Vertical
Note: 802.11b Mode Low Channel




1-6GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4824.000	38.24	11.26	49.50	54.00	4.50	Average
2	4824.000	43.68	11.26	54.94	74.00	19.06	Peak

Vertical

Project No.: CR231167220-RF
Tester: Mack Huang
Polarization: Vertical
Note: 802.11b Mode Low Channel




6-18GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	17039.810	19.40	28.26	47.66	54.00	6.34	Average
2	17039.810	31.41	28.26	59.67	74.00	14.33	Peak

Vertical


Project No.: CR231167220-RF
Tester: Mack Huang
Polarization: Vertical
Note: 802.11b Mode Low Channel



18-25GHz


No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	20313.260	40.78	4.50	45.28	54.00	8.72	Average
2	20313.260	53.18	4.50	57.68	74.00	16.32	Peak

Aux ANT: 802.11b Mode Low Channel



Horizontal

Project No.: CR231167220-RF
Tester: Mack Huang
Polarization: Horizontal
Note: 802.11b Mode Low Channel




6-18GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	16965.390	19.70	27.93	47.63	54.00	6.37	Average
2	16965.390	32.01	27.93	59.94	74.00	14.06	Peak

Horizontal

Project No.: CR231167220-RF
Tester: Mack Huang
Polarization: Horizontal
Note: 802.11b Mode Low Channel




18-25GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	21030.210	40.00	4.62	44.62	54.00	9.38	Average
2	21030.210	51.81	4.62	56.43	74.00	17.57	Peak

Vertical

Project No.: CR231167220-RF
Tester: Mack Huang
Polarization: Vertical
Note: 802.11b Mode Low Channel




1-6GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4824.000	38.74	11.26	50.00	54.00	4.00	Average
2	4824.000	44.26	11.26	55.52	74.00	18.48	Peak

Vertical

Project No.: CR231167220-RF
Tester: Mack Huang
Polarization: Vertical
Note: 802.11b Mode Low Channel




6-18GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	17349.470	18.35	29.30	47.65	54.00	6.35	Average
2	17349.470	30.46	29.30	59.76	74.00	14.24	Peak

Vertical

Project No.: CR231167220-RF
Tester: Mack Huang
Polarization: Vertical
Note: 802.11b Mode Low Channel



18-25GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	24528.110	38.86	5.37	44.23	54.00	9.77	Average
2	24528.110	51.62	5.37	56.99	74.00	17.01	Peak

4.3 Minimum 6 dB Emission Bandwidth

Serial Number:	2DMI-1	Test Date:	2023/12/4
Test Site:	RF	Test Mode:	Transmitting
Tester:	Len Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.7	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	102259	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:**Main ANT: :**


Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	2412	8.10	0.5
	2442	8.10	0.5
	2472	8.10	0.5
802.11g	2412	16.38	0.5
	2442	16.38	0.5
	2472	16.23	0.5
802.11n ht20	2412	17.64	0.5
	2442	17.64	0.5
	2472	17.25	0.5
802.11n ht40	2422	36.48	0.5
	2442	34.50	0.5
	2462	36.18	0.5


Aux ANT:


Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	2412	8.10	0.5
	2442	8.10	0.5
	2472	7.62	0.5
802.11g	2412	16.38	0.5
	2442	16.38	0.5
	2472	15.54	0.5
802.11n ht20	2412	17.64	0.5
	2442	17.64	0.5
	2472	16.38	0.5
802.11n ht40	2422	36.42	0.5
	2442	36.18	0.5
	2462	34.20	0.5

Main ANT:













Aux ANT:









4.4 99% Occupied Bandwidth

Serial Number:	2DMI-1	Test Date:	2023/12/4
Test Site:	RF	Test Mode:	Transmitting
Tester:	Len Huang	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	25.7	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101
----------------------	------	---------------------------	----	------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	102259	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:**Main ANT:**




Test Modes	Test Channel	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)
802.11b	Lowest	2412	12.95
	Middle	2442	12.87
	Highest	2472	12.75
802.11g	Lowest	2412	16.86
	Middle	2442	16.86
	Highest	2472	16.74
802.11n ht20	Lowest	2412	17.78
	Middle	2442	17.82
	Highest	2472	17.66
802.11n ht40	Lowest	2422	36.52
	Middle	2442	36.04
	Highest	2462	36.04




Aux ANT:

Test Modes	Test Channel	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)
802.11b	Lowest	2412	12.95
	Middle	2442	12.95
	Highest	2472	12.63
802.11g	Lowest	2412	16.86
	Middle	2442	16.86
	Highest	2472	16.70
802.11n ht20	Lowest	2412	17.82
	Middle	2442	17.86
	Highest	2472	17.66
802.11n ht40	Lowest	2422	36.28
	Middle	2442	36.20
	Highest	2462	35.80




Main ANT:


99% Occupied Bandwidth




802.11g
Lowest Channel802.11g
Middle Channel802.11g
Highest Channel

99% Occupied Bandwidth802.11n ht20
Lowest Channel802.11n ht20
Middle Channel802.11n ht20
Highest Channel




99% Occupied Bandwidth

802.11n ht40
Lowest ChannelProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 11:39:20802.11n ht40
Middle ChannelProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 11:43:05802.11n ht40
Highest ChannelProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 11:50:01




Aux ANT:

99% Occupied Bandwidth802.11g
Lowest ChannelProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 13:46:09802.11g
Middle ChannelProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 13:51:03802.11g
Highest ChannelProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 13:54:52

99% Occupied Bandwidth

802.11n ht20
Lowest ChannelProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 14:04:33802.11n ht20
Middle ChannelProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 14:09:21802.11n ht20
Highest ChannelProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 14:14:55

99% Occupied Bandwidth

802.11n ht40
Lowest ChannelProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 14:20:53802.11n ht40
Middle ChannelProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 14:24:23802.11n ht40
Highest ChannelProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 14:27:34

4.5 Maximum Conducted Output Power

Serial Number:	2DMI-1	Test Date:	2023/11/22
Test Site:	RF	Test Mode:	Transmitting
Tester:	Len Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.5	Relative Humidity: (%)	50	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Anritsu	Power Meter	ML2495A	1106009	2023/8/4	2024/8/3
Anritsu	Pulse Power Sensor	MA2411A	10780	2023/8/4	2024/8/3
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:**Main ANT:**

Test Modes	Test Frequency (MHz)	Maximum Conducted Peak Output Power (dBm)	Maximum Conducted Average Output Power (dBm)	Limit (dBm)
802.11b	2412	16.89	13.88	30
	2442	16.84	13.83	30
	2472	16.46	13.44	30
802.11g	2412	16.81	8.17	30
	2442	16.68	8.12	30
	2472	16.08	7.52	30
802.11n ht20	2412	16.13	7.58	30
	2442	16.61	8.01	30
	2472	16.04	7.50	30
802.11n ht40	2422	16.86	8.13	30
	2442	16.97	8.27	30
	2462	16.36	7.73	30

Aux ANT:

Test Modes	Test Frequency (MHz)	Maximum Conducted Peak Output Power (dBm)	Maximum Conducted Average Output Power (dBm)	Limit (dBm)
802.11b	2412	18.68	15.68	30
	2442	18.83	15.74	30
	2472	18.09	14.99	30
802.11g	2412	18.66	10.03	30
	2442	18.73	10.27	30
	2472	17.93	9.40	30
802.11n ht20	2412	18.52	9.99	30
	2442	18.82	10.23	30
	2472	17.84	9.35	30
802.11n ht40	2422	18.83	10.14	30
	2442	19.03	10.30	30
	2462	18.75	10.03	30

4.6 Maximum Power Spectral Density

Serial Number:	2DMI-1	Test Date:	2023/12/4
Test Site:	RF	Test Mode:	Transmitting
Tester:	Len Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.7	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	102259	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:**Main ANT:**

Test Channel	Test Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	2412	-7.62	8.00
	2442	-7.85	8.00
	2472	-7.98	8.00
802.11g	2412	-15.67	8.00
	2442	-15.85	8.00
	2472	-16.57	8.00
802.11n ht20	2412	-16.47	8.00
	2442	-16.22	8.00
	2472	-16.43	8.00
802.11n ht40	2422	-18.98	8.00
	2442	-17.91	8.00
	2462	-19.06	8.00




Aux ANT:




Test Channel	Test Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	2412	-5.77	8.00
	2442	-5.74	8.00
	2472	-6.24	8.00
802.11g	2412	-13.91	8.00
	2442	-13.9	8.00
	2472	-14.38	8.00
802.11n ht20	2412	-13.27	8.00
	2442	-13.22	8.00
	2472	-14.1	8.00
802.11n ht40	2422	-16.61	8.00
	2442	-16.37	8.00
	2462	-16.13	8.00

Main ANT:






Maximum power spectral density

802.11g
Lowest Channel802.11g
Middle Channel802.11g
Highest Channel

Maximum power spectral density802.11n ht20
Lowest Channel802.11n ht20
Middle Channel802.11n ht20
Highest Channel

Maximum power spectral density

802.11n ht40
Lowest Channel802.11n ht40
Middle Channel802.11n ht40
Highest Channel

Maximum power spectral density

Spectrum

Ref Level 25.00 dBm Offset 10.50 dB RBW 3 kHz
 Att 30 dB SWT 1.9 ms VBW 10 kHz Mode Auto FFT

1Pk: Max

20 dBm
 10 dBm
 0 dBm
 -10 dBm
 -20 dBm
 -30 dBm
 -40 dBm
 -50 dBm
 -60 dBm
 -70 dBm

M1[1] -5.74 dBm
 2.4412720 GHz

M1

CF 2.442 GHz 1001 pts Span 12.15 MHz

Spectrum

Ref Level 25.00 dBm Offset 10.50 dB RBW 3 kHz
 Att 30 dB SWT 1.9 ms VBW 10 kHz Mode Auto FFT

1PK Max

20 dBm
 10 dBm
 0 dBm
 -10 dBm
 -20 dBm
 -30 dBm
 -40 dBm
 -50 dBm
 -60 dBm
 -70 dBm




M1[1]

-6.24 dBm
 2.4712690 GHz




CF 2.472 GHz 1001 pts Span 11.43 MHz

ProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 13:42:14




Maximum power spectral density

802.11g
Lowest Channel802.11g
Middle Channel802.11g
Highest Channel

Maximum power spectral density

802.11n ht20
Lowest Channel802.11n ht20
Middle Channel802.11n ht20
Highest Channel

Maximum power spectral density

802.11n ht40
Lowest Channel802.11n ht40
Middle Channel802.11n ht40
Highest Channel

4.7 100 kHz Bandwidth of Frequency Band Edge:

Serial Number:	2DMI-1	Test Date:	2023/12/4
Test Site:	RF	Test Mode:	Transmitting
Tester:	Len Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.7	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101
----------------------	------	---------------------------	----	------------------------	-----

Test Equipment List and Details:



Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	102259	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*



Test Data:

Main ANT:



100 kHz Bandwidth of Frequency Band Edge

802.11b
Lowest Band edgeProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 10:04:27802.11b
Highest Band edgeProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 10:53:40



100 kHz Bandwidth of Frequency Band Edge

802.11g
Lowest Band edgeProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 11:06:14802.11g
Highest Band edgeProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 11:15:09

100 kHz Bandwidth of Frequency Band Edge



802.11n ht20
Lowest Band edgeProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 11:25:00802.11n ht20
Highest Band edgeProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 11:35:32

100 kHz Bandwidth of Frequency Band Edge



802.11n ht40
Lowest Band edgeProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 11:40:38802.11n ht40
Highest Band edgeProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 11:51:55

Aux ANT:



100 kHz Bandwidth of Frequency Band Edge

802.11b
Lowest Band edgeProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 13:34:03802.11b
Highest Band edgeProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 13:43:03



100 kHz Bandwidth of Frequency Band Edge

802.11g
Lowest Band edge802.11g
Highest Band edge

100 kHz Bandwidth of Frequency Band Edge

802.11n ht20
Lowest Band edge802.11n ht20
Highest Band edge

100 kHz Bandwidth of Frequency Band Edge

802.11n ht40
Lowest Band edgeProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 14:22:11802.11n ht40
Highest Band edgeProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 14:29:31

4.8 Duty Cycle:

Serial Number:	2DMI-1	Test Date:	2023/12/4
Test Site:	RF	Test Mode:	Transmitting
Tester:	Len Huang	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	25.7	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101
----------------------	------	---------------------------	----	------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	102259	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*


Test Data:**Main ANT:**

Test Modes	Ton (ms)	Ton+off (ms)	Duty cycle (%)	1/T (Hz)	VBW Setting (Hz)
802.11b	100	100	100.00	/	10
802.11g	100	100	100.00	/	10
802.11n ht20	100	100	100.00	/	10
802.11n ht40	100	100	100.00	/	10


Aux ANT:

Test Modes	Ton (ms)	Ton+off (ms)	Duty cycle (%)	1/T (Hz)	VBW Setting (Hz)
802.11b	100	100	100.00	/	10
802.11g	100	100	100.00	/	10
802.11n ht20	100	100	100.00	/	10
802.11n ht40	100	100	100.00	/	10

Main ANT:




802.11n ht40




ProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 11:37:00

Aux ANT:



802.11n ht40



ProjectNo.:CR231167220 Tester:Len Huang
Date: 4.DEC.2023 14:18:59

5. EUT PHOTOGRAPHS

Please refer to the attachment CR231167220-EXP EUT EXTERNAL PHOTOGRAPHS and CR231167220-INP EUT INTERNAL PHOTOGRAPHS

6. TEST SETUP PHOTOGRAPHS

Please refer to the attachment CR231167220-00C-TSP TEST SETUP PHOTOGRAPHS.

===== END OF REPORT =====