



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: TECNO MOBILE LIMITED

Address: FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25
SHAN MEI STREET FOTAN NT HONGKONG

FCC ID: 2ADYY-YY5-CM8

Product Name: Mobile Phone

Standard(s): 47 CFR Part 2
47 CFR Part 22, Subpart H
47 CFR Part 24, Subpart E
47 CFR Part 27
ANSI C63.26-2015

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: 2503P28739E-RF-00E

Date Of Issue: 2025-02-24

Reviewed By: Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China

Tel: +86-769-83085888

www.cctt.com.cn

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.1.1 General:.....	6
1.1.2 Operation Voltage (VDC)▲.....	6
1.1.3 Antenna Information▲.....	6
1.1.4 Accessory Information.....	8
1.2 DESCRIPTION OF TEST CONFIGURATION.....	9
1.2.1 EUT Operation Condition:.....	9
1.2.2 Support Equipment List and Details	12
1.2.3 Support Cable List and Details	12
1.2.4 Block Diagram of Test Setup.....	13
1.3 MEASUREMENT UNCERTAINTY	14
2. SUMMARY OF TEST RESULTS	15
3. REQUIREMENTS AND TEST PROCEDURES	16
3.1 APPLICABLE STANDARD FOR PART 22 SUBPART H:	16
3.1.1 RF Output Power	16
3.1.2 Spurious Emissions.....	16
3.1.3 Frequency stability.....	16
3.2 APPLICABLE STANDARD FOR PART 24 SUBPART E:.....	18
3.2.1 RF Output Power	18
3.2.2 Spurious Emissions.....	18
3.2.3 Frequency stability.....	18
3.3 APPLICABLE STANDARD FOR PART 27:.....	19
3.3.1 RF Output Power	19
3.3.2 Spurious Emissions.....	20
3.3.3 Frequency stability.....	22
3.4 TEST METHOD:	23
3.4.1 RF Output Power	23
3.4.2 Occupied Bandwidth.....	24
3.4.3 Transmitter unwanted emissions-at antenna terminals	25
3.4.4 Out of band emission	26
3.4.5 Frequency stability.....	27
3.4.6 Transmitter unwanted emissions-Radiated Spurious emissions.....	28
4. TEST DATA AND RESULTS	30
4.1 ANTENNA PORT TEST DATA AND RESULTS FOR GSM 850 BAND.....	30
4.2 ANTENNA PORT TEST DATA AND RESULTS FOR GSM 1900 BAND.....	36
4.3 ANTENNA PORT TEST DATA AND RESULTS FOR WCDMA BAND 2	42
4.4 ANTENNA PORT TEST DATA AND RESULTS FOR WCDMA BAND 4	49
4.5 ANTENNA PORT TEST DATA AND RESULTS FOR WCDMA BAND 5:	56
4.6 LTE BAND RF CONDUCTED DATA.....	63
4.7 RADIATED SPURIOUS EMISSIONS.....	65
4.7.1 30 MHz – 1 GHz.....	65

4.7.2 Above 1GHz	78
5. EUT PHOTOGRAPHS	99
6. TEST SETUP PHOTOGRAPHS	100

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2503P28739E-RF-00E	Original Report	2025-02-24

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

1.1.1 General:

EUT Name:	Mobile Phone
EUT Model:	CM8
Operation Bands and modes:	GSM/GPRS/EDGE: 850/1900 WCDMA: Band 2/4/5 LTE: Band2/4/5/7/12/13/17/66/38/41/42
Modulation Type:	GMSK, 8PSK, BPSK, QPSK, 16QAM
Rated Input Voltage:	DC 3.86V from battery or DC 5.0V/5-10.0V/11.0V/4.0-20.0V from adapter
sample number:	RE:2X9R-1 RF:2X9R-2
EUT Received Date:	2025/1/9
EUT Received Status:	Good

1.1.2 Operation Voltage (V_{DC})▲

Lowest:	3.4	Normal:	3.86	Highest:	4.5
---------	-----	---------	------	----------	-----

1.1.3 Antenna Information ▲

LB PRX:

Antenn	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain(G_T) (dBi)	L_c (dB)
ANT2	IFA	GSM850	824-849	-8.00	0.5
		WCDMA B5	824-849	-8.00	0.5
		LTE B5	824-849	-8.00	0.5
		LTE B12	699-716	-6.50	0.5
		LTE B13	777-787	-6.50	0.5
		LTE B17	704-716	-6.50	0.5

Note: L_c = Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.

MHB PRX:

Antenn	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain(G_T) (dBi)	L_c (dB)
ANT3	IFA	PCS1900	1850-1910	-3.00	0.8
		WCDMA B2	1850-1910	-3.00	0.8
		WCDMA B4	1710-1755	-2.80	0.8
		LTE B2	1850-1910	-3.00	0.8
		LTE B4	1710-1755	-2.80	0.8
		LTE B7	2500-2570	-3.20	1
		LTE B38	2570-2620	-3.20	1
		LTE B41	2496-2690	-3.20	1
		LTE B66	1710-1780	-2.80	0.8

Note: L_c = Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.

LB DRX:

Antenn	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain(G_T) (dBi)	L_c (dB)
ANT4	IFA	GSM850	824-849	-6.20	0
		WCDMA B5	824-849	-6.20	0
		LTE B5	824-849	-6.20	0
		LTE B12	699-716	-9.00	0
		LTE B13	777-787	-9.00	0
		LTE B17	704-716	-9.00	0

Note: L_c = Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.

MHB DRX:

Antenna	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain(G_T) (dBi)	L_c (dB)
ANT5	IFA	PCS1900	1850-1910	-7.00	0
		WCDMA B2	1850-1910	-7.00	0
		WCDMA B4	1710-1755	-1.70	0
		LTE B2	1850-1910	-7.00	0
		LTE B4	1710-1755	-1.70	0
		LTE B7	2500-2570	-5.00	0
		LTE B38	2570-2620	-5.00	0
		LTE B41	2496-2690	-5.00	0
		LTE B66	1710-1780	-1.70	0

Note: L_c = Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.

DRX 2:

Antenna	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain(G_T) (dBi)	L_c (dB)
ANT0	IFA	LTE B42	3450-3550	-3	0

Note: L_c = Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.

PRX:

Antenna	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain(G_T) (dBi)	L_c (dB)
ANT6	IFA	LTE B42	3450-3550	-4	0

Note: L_c = Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.

MHB DRX

Antenna	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain(G _T) (dBi)	L _c (dB)
ANT8	IFA	LTE B42	3450-3550	-2.5	0
Note: Lc= Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.					

DRX:

Antenna	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain(G _T) (dBi)	L _c (dB)
ANT 9	IFA	LTE B42	3450-3550	-1.6	0
Note: Lc= Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.					

1.1.4 Accessory Information

Accessory Description	Manufacturer	Model
Adapter	TECNO	U700TSA

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in each operation mode.
Equipment Modifications:	No
EUT Exercise Software:	No
The maximum power was configured per 3GPP Standard for each operation modes as below setting:	
GSM/GPRS/EGPRS	
Function: Menu select > GSM Mobile Station > GSM 850/1900	
Press Connection control to choose the different menus	
Press RESET > choose all the reset all settings	
Connection Press Signal Off to turn off the signal and change settings	
Network Support > GSM + GPRS or GSM + EGPRS	
Main Service > Packet Data	
Service selection > Test Mode A – Auto Slot Config. off	
MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting	
> Slot configuration > Uplink/Gamma	
> 33 dBm for GPRS 850	
> 30 dBm for GPRS 1900	
> 27 dBm for EGPRS 850	
> 26 dBm for EGPRS 1900	
BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel	
Frequency Offset > + 0 Hz	
Mode > BCCH and TCH	
BCCH Level > -85 dBm (May need to adjust if link is not stable)	
BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]	
Channel Type > Off	
P0 > 4 dB	
Slot Config > Unchanged (if already set under MS signal)	
TCH > choose desired test channel	
Hopping > Off	
Main Timeslot > 3	
Network Coding Scheme > CS4 (GPRS) and MCS5 (EGPRS)	
Bit Stream > 2E9-1 PSR Bit Stream	
AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input	
Connection Press Signal on to turn on the signal and change settings	

WCDMA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode Subset	HSUPA 1	HSUPA 2	HSUPA	HSUPA 4	HSUPA 5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β	11/15	6/15	1 /15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30 15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs}=\beta_{hs}/\beta_c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	A Index	20	12	1	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate k ps	242.1	174.9	82.8	205.8	308.9
	Reference E_FCI	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27		E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18		E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27

HSPA+

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

Sub-test	β_c (Note 3)	β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed1} : 30/15 β_{ed2} : 30/15	β_{ed3} : 24/15 β_{ed4} : 24/15	3.5	2.5	14	105	105

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hz} = 30/15 * \beta_c$.

Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0).

Note 3: DPDCH is not configured, therefore the β_c is set to 1 and $\beta_d = 0$ by default.

Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.

LTE (FDD):

The following tests were conducted according to the test requirements in 3GPP TS36.101

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of 'NS_01'.

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	Table 6.2.4-2
	6.6.3.3.2				
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

LTE(TDD):

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink		UpPTS		Extended cyclic prefix in downlink	
	DwPTS	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink	DwPTS	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$7680 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
5	$6592 \cdot T_s$			$20480 \cdot T_s$		
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Calculated Duty Cycle

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-point Periodicity	Subframe Number										Calculated Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33

Calculated Duty Cycle = Extended cyclic prefix in uplink $\times (T_s) \times \# \text{ of S} + \# \text{ of U}$

Example for Calculated Duty Cycle for Uplink-Downlink Configuration 0:

Calculated Duty Cycle = $5120 \times [1/(15000 \times 2048)] \times 2 + 6 \text{ ms} = 63.33\%$

where

$T_s = 1/(15000 \times 2048)$ seconds

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
R&S	Wideband Radio Communication Tester	CMW500	143458
TECNO	Adapter	U700TSA	KX07018884A25
Unknown	Antenna	Unknown	Unknown

1.2.3 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	1	Adapter	EUT
Cable	No	No	10	CMW500	Antenna

1.2.4 Block Diagram of Test Setup

Radiation Test:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	$\pm 5\%$
RF output power, conducted	$\pm 0.61\text{dB}$
Power Spectral Density, conducted	$\pm 0.61\text{ dB}$
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	$\pm 1.26\text{ dB}$
Temperature	$\pm 1^\circ\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 0.4\%$
Duty Cycle	1%
RF Frequency	$\pm 0.082 \times 10^{-6}$

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§2.1046; §22.913; §27.50; § 24.232	RF Output Power	PASS
FCC§2.1046; § 24.232; §27.50; §22.913	Peak-to-average Ratio(PAR)	PASS
FCC§2.1049; §27.53; §22.905, §22.917; § 24.238	Occupied Bandwidth	PASS
FCC§2.1051; §27.53; §22.917; § 24.238	Spurious Emissions at Antenna Terminal	PASS
FCC§2.1051; § 24.238; §22.917; §27.53	Out of band emission,Band Edge	PASS
FCC§ 2.1055; §27.54; § 24.235; § 22.355	Frequency stability vs. temperature &Frequency stability vs. voltage Compliance	PASS
FCC§ 2.1053; § 22.917; §27.53; § 24.238	Field Strength of Spurious Radiation	PASS

3. REQUIREMENTS AND TEST PROCEDURES

3.1 Applicable Standard for Part 22 Subpart H:

3.1.1 RF Output Power

FCC §22.913

(a)(5) The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7watts.

(d) *Power measurement.* Measurement of the ERP of Cellular base transmitters and repeaters must be made using an average power measurement technique. The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB. Power measurements for base transmitters and repeaters must be made in accordance with either of the following:

- (1) A Commission-approved average power technique (see FCC Laboratory's Knowledge Database); or
- (2) For purposes of this section, peak transmit power must be measured over an interval of continuous transmission using instrumentation calibrated in terms of an rms equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

3.1.2 Spurious Emissions

FCC §22.917

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

(b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a reference bandwidth as follows:

- (1) In the spectrum below 1 GHz, instrumentation should employ a reference bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy, provided that the measured power is integrated over the full required reference bandwidth (i.e., 100kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.
- (2) In the spectrum above 1 GHz, instrumentation should employ a reference bandwidth of 1 MHz

3.1.3 Frequency stability

FCC §22.355

Except as otherwise provided in this part, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table C-1 of this section.

Table C-1 - Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency range (MHz)	Base, fixed (ppm)	Mobile >3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20	20	50
50 to 450	5	5	50
450 to 512	2.5	5	5
821 to 896	1.5	2.5	2.5
928 to 929	5	n/a	n/a
929 to 960	1.5	n/a	n/a
2110 to 2220	10	n/a	n/a

3.2 Applicable Standard for Part 24 Subpart E:

3.2.1 RF Output Power

FCC §24.232

(c) Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

(d) Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of § 24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.2.2 Spurious Emissions

FCC §24.238

The rules in this section govern the spectral characteristics of emissions in the Broadband Personal Communications Service.

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

(b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(c) Alternative out of band emission limit. Licensees in this service may establish an alternative out of band emission limit to be used at specified band edge(s) in specified geographical areas, in lieu of that set forth in this section, pursuant to a private contractual arrangement of all affected licensees and applicants. In this event, each party to such contract shall maintain a copy of the contract in their station files and disclose it to prospective assignees or transferees and, upon request, to the FCC.

(d) Interference caused by out of band emissions. If any emission from a transmitter operating in this service results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

3.2.3 Frequency stability

FCC §24.235

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.3 Applicable Standard for Part 27:

3.3.1 RF Output Power

FCC §27.50

(a) The following power limits and related requirements apply to stations transmitting in the 2305-2320 MHz band or the 2345-2360 MHz band.

(3) *Mobile and portable stations.*

(i) For mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, *except that* for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth. For mobile and portable stations using time division duplexing (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands. Mobile and portable stations using FDD technology are restricted to transmitting in the 2305-2315 MHz band. Power averaging shall not include intervals in which the transmitter is off.

(ii) Mobile and portable stations are not permitted to transmit in the 2315-2320 MHz and 2345-2350 MHz bands.

(iii) *Automatic transmit power control.* Mobile and portable stations transmitting in the 2305-2315 MHz band or in the 2350-2360 MHz band must employ automatic transmit power control when operating so the stations operate with the minimum power necessary for successful communications.

(iv) *Prohibition on external vehicle-mounted antennas.* The use of external vehicle-mounted antennas for mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band is prohibited.

(b) The following power and antenna height limits apply to transmitters operating in the 746-758 MHz, 775-788 MHz and 805-806 MHz bands:

(10) Portable stations (hand-held devices) transmitting in the 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP.

(c) The following power and antenna height requirements apply to stations transmitting in the 600 MHz band and the 698-746 MHz band:

(10) Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

(d) The following power and antenna height requirements apply to stations transmitting in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz and 2180-2200 MHz bands:

(4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

(5) Equipment employed must be authorized in accordance with the provisions of § 24.51. Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (d)(6) of this section. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

(h) The following power limits shall apply in the BRS and EBS:

(2) Mobile and other user stations. Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

- (k) The following power requirements apply to stations transmitting in the 3450-3550 MHz band:
- (3) Mobile devices are limited to 1 Watt (30 dBm) EIRP. Mobile devices operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.
- (4) Equipment employed must be authorized in accordance with the provisions of § 27.51. Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (k)(5) of this section. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Spurious Emissions

FCC §27.53

- (a) For operations in the 2305-2320 MHz band and the 2345-2360 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power P (with averaging performed only during periods of transmission) within the licensed band(s) of operation, in watts, by the following amounts:
- (4) For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands:
- (i) By a factor of not less than: $43 + 10 \log (P)$ dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than $55 + 10 \log (P)$ dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than $61 + 10 \log (P)$ dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than $67 + 10 \log (P)$ dB on all frequencies between 2328 and 2337 MHz;
 - (ii) By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2300 and 2305 MHz, $55 + 10 \log (P)$ dB on all frequencies between 2296 and 2300 MHz, $61 + 10 \log (P)$ dB on all frequencies between 2292 and 2296 MHz, $67 + 10 \log (P)$ dB on all frequencies between 2288 and 2292 MHz, and $70 + 10 \log (P)$ dB below 2288 MHz;
 - (iii) By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2360 and 2365 MHz, and not less than $70 + 10 \log (P)$ dB above 2365 MHz.
- (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:
- (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
 - (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
 - (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
 - (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
 - (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

(6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

(g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

(h) AWS emission limits

(1) **General protection levels.** Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

(m) For BRS and EBS stations, the power of any emissions outside the licensee's frequency bands of operation shall be attenuated below the transmitter power (P) measured in watts in accordance with the standards below. If a licensee has multiple contiguous channels, out-of-band emissions shall be measured from the upper and lower edges of the contiguous channels.

(4) For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

(n) 3.45 GHz Service. The following emission limits apply to stations transmitting in the 3450-3550 MHz band:

(2) For mobile operations in the 3450-3550 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz. Compliance with this paragraph (n)(2) is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed, but limited to a maximum of 200 kHz. In the bands between 1 and 5 MHz removed from the licensee's frequency block, the minimum resolution bandwidth for the measurement shall be 500 kHz. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

3.3.3 Frequency stability

FCC §27.54

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

3.4 Test Method:

3.4.1 RF Output Power

According to CFR Part 2.1046, ANSI C63.26-2015 Section 5.2.5.5:

The relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T - L_C$$

where:


ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_T = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

Test Setup Block:



Note: The Insertion loss of the RF cable and coaxial Attenuator was offset into the Reading of CMW500.

3.4.2 Occupied Bandwidth


According to CFR Part 2.1049, ANSI C63.26-2015 Section 5.4.4

The OBW is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.

The following procedure shall be used for measuring (99%) power bandwidth:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (typically a span of $1.5 \times \text{OBW}$ is sufficient).
- b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\geq 3 \times \text{RBW}$.
- c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3. NOTE—Step a), step b), and step c) may require iteration to adjust within the specified tolerances.
- d) Set the detection mode to peak, and the trace mode to max-hold.
- e) If the instrument does not have a 99% OBW function, recover the trace data points and sum directly in linear power terms. Place the recovered amplitude data points, beginning at the lowest frequency, in a running sum until 0.5% of the total is reached. Record that frequency as the lower OBW frequency. Repeat the process until 99.5% of the total is reached and record that frequency as the upper OBW frequency. The 99% power OBW can be determined by computing the difference these two frequencies.
- f) The OBW shall be reported and plot(s) of the measuring instrument display shall be provided with the test report. The frequency and amplitude axis and scale shall be clearly labeled. Tabular data can be reported in addition to the plot(s).

Test Setup Block:




3.4.3 Transmitter unwanted emissions-at antenna terminals

According to ANSI C63.26-2015 Section 5.7.4:

the applicable rule part specifies the reference bandwidth for measuring unwanted emission levels (typically, 100 kHz if the authorized frequency band/block is at or below 1 GHz and 1 MHz if the authorized frequency band/block is above 1 GHz),⁸ effectively depicting the unwanted emission limit in terms of a power spectral density. In those cases where no reference bandwidth is explicitly specified, the values in the preceding sentence should be used.

Test Setup Block:




3.4.4 Out of band emission

According to ANSI C63.26-2015 Section 5.7.3:

Typically, a measurement (resolution) bandwidth smaller than the reference bandwidth is allowed for measurements within a specified frequency range at the edge of the authorized frequency block/band (e.g., within the first Y MHz outside of the authorized frequency band/block, where the value of Y is specified in the relevant rule part). Some FCC out-of-band emission rules permit the use of a narrower RBW (typically limited to a minimum RBW of 1 % of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth. Beyond the specified frequency range in which this relaxation of the uniform reference bandwidth is permitted, it typically is also acceptable to use a narrower RBW (again limited to a minimum of 1 % of OBW) to increase accuracy, but the measurement result must subsequently be integrated over the full reference bandwidth.

Test Setup Block:



3.4.5 Frequency stability

According to ANSI C63.26-2015 Section 5.6:

Frequency stability is a measure of the frequency drift due to temperature and supply voltage variations, with reference to the frequency measured at +20 °C and rated supply voltage.


The operating carrier frequency shall be set up in accordance with the manufacturer's published operation and instruction manual prior to the commencement of these tests. No adjustment of any frequency determining circuit element shall be made subsequent to this initial set-up. Frequency stability is tested:

- a) At 10 °C intervals of temperatures between –30 °C and +50 °C at the manufacturer's rated supply voltage, and
- b) At +20 °C temperature and $\pm 15\%$ supply voltage variations. If a product is specified to operate over a range of input voltage, then the –15% variation is applied to the lowermost voltage and the +15% is applied to the uppermost voltage.

During the test all necessary settings, adjustments and control of the EUT have to be performed without disturbing the test environment, i.e., without opening the environmental chamber. The frequency stabilities can be maintained to a lesser temperature range provided that the transmitter is automatically inhibited from operating outside the lesser temperature range. For handheld equipment that is only capable of operating from internal batteries and the supply voltage cannot be varied, the frequency stability tests shall be performed at the nominal battery voltage and the battery end point voltage specified by the manufacturer. An external supply voltage can be used and set at the internal battery nominal voltage, and again at the battery operating end point voltage which shall be specified by the equipment manufacturer.

If an unmodulated carrier is not available, the mean frequency of a modulated carrier can be obtained by using a frequency counter with gating time set to an appropriately large multiple of bit periods (gating time depending on the required accuracy). Full details on the choice of values shall be included in the test report.

Test Setup Block:



3.4.6 Transmitter unwanted emissions-Radiated Spurious emissions

According to ANSI C63.26-2015 Section 5.5.3:

Test setup:




Figure 6—Test site-up for radiated ERP and/or EIRP measurements




Figure 7—Substitution method set-up for radiated emission

Test Procedure:

- a) Place the EUT in the center of the turntable. The EUT shall be configured to transmit into the standard non-radiating load (for measuring radiated spurious emissions), connected with cables of minimal length unless specified otherwise. If the EUT uses an adjustable antenna, the antenna shall be positioned to the length that produces the worst case emission at the fundamental operating frequency.
- b) Each emission under consideration shall be evaluated:
 - 1) Raise and lower the measurement antenna in accordance 5.5.2, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
 - 2) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
 - 3) Return the turntable to the azimuth where the highest emission amplitude level was observed.
 - 4) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
 - 5) Record the measured emission amplitude level and frequency using the appropriate RBW.
- c) Repeat step b) for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.
- d) Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the initial EUT measurement.
- e) Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna.
- f) Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor.
- g) For each emission that was detected and measured in the initial test [i.e., in step b) and step c)]:
 - 1) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude.
 - 2) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step b) and step c).
 - 3) Record the output power level of the signal generator when equivalence is achieved in step 2).
- h) Repeat step e) through step g) with the measurement antenna oriented in the opposite polarization.
- i) Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:

$$P_e = P_s(\text{dBm}) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$

where

P_e = equivalent emission power in dBm

P_s = source (signal generator) power in dBm

NOTE—dBd refers to the measured antenna gain in decibels relative to a half-wave dipole.

- j) Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from: $\text{gain (dBd)} = \text{gain (dBi)} - 2.15 \text{ dB}$. If necessary, the antenna gain can be calculated from calibrated antenna factor information
- k) Provide the complete measurement results as a part of the test report.

4. TEST DATA AND RESULTS

4.1 Antenna Port Test Data and Results for GSM 850 band

Sample Number:	2X9R-2	Test Date:	2025/2/8
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.7	Relative Humidity: (%)	43	ATM Pressure: (kPa)	102.1
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2024/4/1	2025/3/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Unknown	Coaxial tee connector	Unknown	2204004	Each time	N/A
Anritsu	Radio Communication Analyzer	MT8820C	6201010144	2024/7/12	2025/7/11
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2024/4/1	2025/3/31
UNI-T	Multimeter	UT39A+	C210582554	2025/1/6	2026/1/5
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
GSM	824.2	836.6	848.8
GPRS	824.2	836.6	848.8
EDGE	824.2	836.6	848.8

Test Data:**RF Output Power**

Test Mode	Conducted Peak Output Power(dBm)			Maximum ERP (dBm)	ERP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
GSM	31.53	31.7	31.59	23.35	38.45
GPRS 1 Slot	31.43	31.67	31.55	23.32	38.45
GPRS 2 Slots	30.47	30.83	30.66	22.48	38.45
GPRS 3 Slots	28.52	28.81	28.69	20.46	38.45
GPRS 4 Slots	27.41	27.55	27.42	19.2	38.45
EDGE 1 Slot	25.94	26.19	26.05	17.84	38.45
EDGE 2 Slots	24.84	25.09	25.01	16.74	38.45
EDGE 3 Slots	22.89	23.06	22.95	14.71	38.45
EDGE 4 Slots	21.93	22.09	22.1	13.75	38.45

Note:

ERP= Conducted Power(dBm) - Lc(dB) + Gr(dBd)

Gr(dBd)=Gr(dBi)-2.15

Use ANT4 to calculate maximum ERP.

Result:**Pass****Occupied Bandwidth**

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
GSM	0.237	0.237	0.239	0.258	0.262	0.266
EDGE	0.260	0.256	0.253	0.336	0.333	0.326

Note: The test plots please refer to the Plots of Occupied Bandwidth

Spurious Emissions at Antenna Terminal**Result:****Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.****Out of band emission, Band Edge****Result:****Pass, Please refer to the test plots of Out of band emission, Band Edge.**


Frequency Stability					
Test Modulation:	GMSK		Test Channel:	836.6	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.86	37	0.044	2.5
	-20	3.86	16	0.019	2.5
	-10	3.86	4	0.005	2.5
	0	3.86	19	0.023	2.5
	10	3.86	6	0.007	2.5
	20	3.86	28	0.033	2.5
	30	3.86	14	0.017	2.5
	40	3.86	5	0.006	2.5
	50	3.86	57	0.068	2.5
Frequency Stability vs. Voltage	20	3.4	26	0.031	2.5
	20	4.5	40	0.048	2.5
				Result:	Pass

Test Modulation:	8PSK		Test Channel:	836.6	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.86	25	0.030	2.5
	-20	3.86	48	0.057	2.5
	-10	3.86	41	0.049	2.5
	0	3.86	11	0.013	2.5
	10	3.86	8	0.010	2.5
	20	3.86	9	0.011	2.5
	30	3.86	17	0.020	2.5
	40	3.86	35	0.042	2.5
	50	3.86	6	0.007	2.5
Frequency Stability vs. Voltage	20	3.4	22	0.026	2.5
	20	4.5	20	0.024	2.5
				Result:	Pass


Test Plots(Note: The 14.5 dB is the Insertion loss of the RF cable, Coaxial tee connector and Attenuator, which was offset into the Spectrum Analyzer):

Occupied Bandwidth**Channel****GSM****EDGE**

Lowest




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 17:14:29




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 17:25:34

Middle




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 17:19:42




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 17:27:36

Highest



ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 17:21:24




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 17:29:29

Spurious Emissions at Antenna Terminal

Channel


GSM

Lowest




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 14:22:06

Middle







ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 14:22:57

Highest



ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 14:23:36

Out of band emission, Band Edge

Mode	Lowest	Highest
GSM	 Ref: 40 dBm Att: 50 dB RBW: 3 kHz VBW: 10 kHz SWT: 1 s Marker 1 [T1] -17.16 dBm 823.996794872 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 17:17:40	 Ref: 40 dBm Att: 50 dB RBW: 3 kHz VBW: 10 kHz SWT: 1 s Marker 1 [T1] -20.68 dBm 849.022435897 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 17:22:13
EDGE	 Ref: 40 dBm Att: 50 dB RBW: 3 kHz VBW: 10 kHz SWT: 1 s Marker 1 [T1] -25.01 dBm 823.996794872 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 17:23:55	 Ref: 40 dBm Att: 50 dB RBW: 3 kHz VBW: 10 kHz SWT: 1 s Marker 1 [T1] -24.89 dBm 849.016025641 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 17:30:08

4.2 Antenna Port Test Data and Results for GSM 1900 band

Sample Number:	2X9R-2	Test Date:	2025/2/8
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.7	Relative Humidity: (%)	43	ATM Pressure: (kPa)	102.1
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2024/4/1	2025/3/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Unknown	Coaxial tee connector	Unknown	2204004	Each time	N/A
Anritsu	Radio Communication Analyzer	MT8820C	6201010144	2024/7/12	2025/7/11
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2024/4/1	2025/3/31
UNI-T	Multimeter	UT39A+	C210582554	2025/1/6	2026/1/5
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
GSM	1850.2	1880	1909.8
GPRS	1850.2	1880	1909.8
EDGE	1850.2	1880	1909.8

RF Output Power					
Test Mode	Conducted Peak Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
GSM	25.72	25.58	25.65	21.92	33
GPRS 1 Slot	25.71	25.58	25.64	21.91	33
GPRS 2 Slots	24.65	24.43	24.53	20.85	33
GPRS 3 Slots	22.86	22.75	22.77	19.06	33
GPRS 4 Slots	21.45	21.53	21.45	17.73	33
EDGE 1 Slot	25.12	25.38	25.14	21.58	33
EDGE 2 Slots	24.01	24.25	24.04	20.45	33
EDGE 3 Slots	21.78	22.06	21.78	18.26	33
EDGE 4 Slots	20.58	20.78	20.55	16.98	33
Note: EIRP=Conducted Power(dBm) - L _c (dB) + G _T (dBi) Use ANT3 to calculate maximum EIRP.					
				Result:	Pass

Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
GSM	0.237	0.237	0.237	0.260	0.262	0.260
EDGE	0.247	0.250	0.250	0.319	0.316	0.319
Note: The test plots please refer to the Plots of Occupied Bandwidth						

Spurious Emissions at Antenna Terminal	
Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.

Out of band emission, Band Edge	
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.

Frequency Stability						
Test Mode:	GMSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.86	1850.078	1850.000	1909.931	1910.000
	-20	3.86	1850.064	1850.000	1909.920	1910.000
	-10	3.86	1850.074	1850.000	1909.939	1910.000
	0	3.86	1850.069	1850.000	1909.920	1910.000
	10	3.86	1850.060	1850.000	1909.933	1910.000
	20	3.86	1850.081	1850.000	1909.919	1910.000
	30	3.86	1850.056	1850.000	1909.940	1910.000
	40	3.86	1850.054	1850.000	1909.925	1910.000
	50	3.86	1850.080	1850.000	1909.941	1910.000
Frequency Stability vs. Voltage	20	3.4	1850.054	1850.000	1909.945	1910.000
	20	4.5	1850.072	1850.000	1909.930	1910.000
					Result:	Pass

Test Mode:	8PSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.86	1850.051	1850.000	1909.934	1910.000
	-20	3.86	1850.075	1850.000	1909.926	1910.000
	-10	3.86	1850.071	1850.000	1909.933	1910.000
	0	3.86	1850.067	1850.000	1909.949	1910.000
	10	3.86	1850.066	1850.000	1909.932	1910.000
	20	3.86	1850.077	1850.000	1909.923	1910.000
	30	3.86	1850.060	1850.000	1909.950	1910.000
	40	3.86	1850.051	1850.000	1909.925	1910.000
	50	3.86	1850.076	1850.000	1909.937	1910.000
Frequency Stability vs. Voltage	20	3.4	1850.064	1850.000	1909.951	1910.000
	20	4.5	1850.055	1850.000	1909.947	1910.000
					Result:	Pass

Occupied Bandwidth


Page 39 of 100

Spurious Emissions at Antenna Terminal


Channel

GSM


Lowest







Middle



Highest



Out of band emission, Band Edge

Channel	Lowest	Highest
GSM	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 10:00:55	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 10:07:13
EDGE	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 17:52:25	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 17:59:20

4.3 Antenna Port Test Data and Results for WCDMA Band 2

Sample Number:	2X9R-2	Test Date:	2025/2/8
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.7	Relative Humidity: (%)	43	ATM Pressure: (kPa)	102.1
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2024/4/1	2025/3/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Unknown	Coaxial tee connector	Unknown	2204004	Each time	N/A
Anritsu	Radio Communication Analyzer	MT8820C	6201010144	2024/7/12	2025/7/11
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2024/4/1	2025/3/31
UNI-T	Multimeter	UT39A+	C210582554	2025/1/6	2026/1/5
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Frequency For Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
WCDMA	1852.4	1880	1907.6

Test Data:**RF Output Power**

Test Mode	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	15.30	15.37	15.36	11.57	33
HSDPA Subtest 1	14.35	14.42	14.35	10.62	33
HSDPA Subtest 2	14.40	14.43	14.40	10.63	33
HSDPA Subtest 3	14.39	14.39	14.33	10.59	33
HSDPA Subtest 4	14.38	14.42	14.36	10.62	33
HSUPA Subtest 1	14.43	14.36	14.37	10.63	33
HSUPA Subtest 2	14.37	14.41	14.41	10.61	33
HSUPA Subtest 3	14.34	14.43	14.34	10.63	33
HSUPA Subtest 4	14.43	14.41	14.36	10.63	33
HSUPA Subtest 5	14.36	14.36	14.35	10.56	33
HSPA+ Subtest 1	14.38	14.41	14.39	10.61	33

Note: EIRP=Conducted Power(dBm) - L_c(dB) + G_T(dBi)
Use ANT3 to calculate maximum EIRP.

Result:	Pass
----------------	-------------

Peak-to-average Ratio(PAR)

Test Mode	Peak-to-average Ratio(dB)			Limit (dB)
	Lowest Channel	Middle Channel	Highest Channel	
WCDMA R99	3.08	3.11	3.14	13
HSDPA	4.01	3.81	3.91	13
HSUPA	3.75	3.78	4.36	13

Result:	Pass
----------------	-------------

Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
WCDMA R99	4.151	4.183	4.167	4.721	4.728	4.747
HSDPA	4.183	4.199	4.183	5.378	5.269	5.369
HSUPA	4.183	4.167	4.183	4.747	5.051	5.170

Note: The test plots please refer to the Plots of Occupied Bandwidth

Spurious Emissions at Antenna Terminal

Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
----------------	---

Out of band emission, Band Edge







Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.
----------------	--

Frequency Stability

Test Mode:	WCDMA R99	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.86	1850.301	1850.000	1909.683	1910.000
	-20	3.86	1850.314	1850.000	1909.690	1910.000
	-10	3.86	1850.300	1850.000	1909.679	1910.000
	0	3.86	1850.294	1850.000	1909.690	1910.000
	10	3.86	1850.300	1850.000	1909.688	1910.000
	20	3.86	1850.317	1850.000	1909.667	1910.000
	30	3.86	1850.296	1850.000	1909.672	1910.000
	40	3.86	1850.308	1850.000	1909.674	1910.000
	50	3.86	1850.310	1850.000	1909.684	1910.000
Frequency Stability vs. Voltage	20	3.4	1850.296	1850.000	1909.672	1910.000
	20	4.5	1850.315	1850.000	1909.675	1910.000
					Result:	Pass


Test Plots(Note: The 14.5 dB is the Insertion loss of the RF cable, Coaxial tee connector and Attenuator, which was offset into the Spectrum Analyzer):

Occupied Bandwidth

Channel	WCDMA R99	HSDPA
Lowest	 Ref 40 dBm *Att 30 dB RBW 100 kHz Delta 1 [T1] 1.75 dB VBW 300 kHz SWT 5 ms 4.72153846 MHz OW 4.158641026 MHz Marker 1 [T1] -11.09 dBm Temp 1 [T1 0dB] 1.85802795 GHz Temp 2 [T1 0dB] 1.858214667 GHz Temp 3 [T1 0dB] 1.85446308 GHz Center 1.8524 GHz 1 MHz/ Span 10 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:41:44	 Ref 40 dBm *Att 30 dB RBW 100 kHz Delta 1 [T1] -5.56 dB VBW 300 kHz SWT 5 ms 5.378265128 MHz OW 4.182691308 MHz Marker 1 [T1] -9.26 dBm Temp 1 [T1 0dB] 1.84971388 GHz Temp 2 [T1 0dB] 1.858389641 GHz Temp 3 [T1 0dB] 1.85448333 GHz Center 1.8524 GHz 1 MHz/ Span 10 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:39:30
Middle	 Ref 40 dBm *Att 30 dB RBW 100 kHz Delta 1 [T1] 1.77 dB VBW 300 kHz SWT 5 ms 4.727564163 MHz OW 4.182691308 MHz Marker 1 [T1] -10.72 dBm Temp 1 [T1 0dB] 1.877629000 GHz Temp 2 [T1 0dB] 1.877904641 GHz Temp 3 [T1 0dB] 1.88208333 GHz Center 1.88 GHz 1 MHz/ Span 10 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:43:30	 Ref 40 dBm *Att 30 dB RBW 100 kHz Delta 1 [T1] 0.94 dB VBW 300 kHz SWT 5 ms 5.269230768 MHz OW 4.19071349 MHz Marker 1 [T1] -9.13 dBm Temp 1 [T1 0dB] 1.877294077 GHz Temp 2 [T1 0dB] 1.877884615 GHz Temp 3 [T1 0dB] 1.88208333 GHz Center 1.88 GHz 1 MHz/ Span 10 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:36:50
Highest	 Ref 40 dBm *Att 30 dB RBW 100 kHz Delta 1 [T1] 1.81 dB VBW 300 kHz SWT 5 ms 4.746794872 MHz OW 4.186664667 MHz Marker 1 [T1] -10.77 dBm Temp 1 [T1 0dB] 1.90528769 GHz Temp 2 [T1 0dB] 1.905504641 GHz Temp 3 [T1 0dB] 1.90966308 GHz Center 1.9076 GHz 1 MHz/ Span 10 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:45:11	 Ref 40 dBm *Att 30 dB RBW 100 kHz Delta 1 [T1] -9.40 dB VBW 300 kHz SWT 5 ms 5.368589744 MHz OW 4.182691308 MHz Marker 1 [T1] -8.97 dBm Temp 1 [T1 0dB] 1.904754641 GHz Temp 2 [T1 0dB] 1.905484615 GHz Temp 3 [T1 0dB] 1.90966308 GHz Center 1.9076 GHz 1 MHz/ Span 10 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:35:02


Channel

Lowest




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 16:18:40

Middle



ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 16:21:06


Highest



ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 16:23:39


Channel

Lowest




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 14:29:09

Middle









ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 14:29:44

Highest



ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 14:30:36

Out of band emission, Band Edge

Mode	Lowest	Highest
R99	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 15:51:42	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 15:56:46
HSUPA	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:14:44	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:15:28
HSDPA	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:04:52	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:11:19

4.4 Antenna Port Test Data and Results for WCDMA Band 4

Sample Number:	2X9R-2	Test Date:	2025/2/8
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.7	Relative Humidity: (%)	43	ATM Pressure: (kPa)	102.1
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2024/4/1	2025/3/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Unknown	Coaxial tee connector	Unknown	2204004	Each time	N/A
Anritsu	Radio Communication Analyzer	MT8820C	6201010144	2024/7/12	2025/7/11
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2024/4/1	2025/3/31
UNI-T	Multimeter	UT39A+	C210582554	2025/1/6	2026/1/5
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Frequency For Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
WCDMA	1712.4	1732.6	1752.6

Test Data:**RF Output Power**

Test Mode	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	22.67	22.64	22.70	21.00	30
HSDPA Subtest 1	21.72	21.66	21.74	20.04	30
HSDPA Subtest 2	21.75	21.68	21.78	20.08	30
HSDPA Subtest 3	21.67	21.67	21.75	20.05	30
HSDPA Subtest 4	21.75	21.66	21.73	20.05	30
HSUPA Subtest 1	21.71	21.67	21.75	20.05	30
HSUPA Subtest 2	21.72	21.68	21.80	20.10	30
HSUPA Subtest 3	21.74	21.69	21.74	20.04	30
HSUPA Subtest 4	21.73	21.71	21.78	20.08	30
HSUPA Subtest 5	21.69	21.68	21.75	20.05	30
HSPA+ Subtest 1	21.69	21.72	21.73	20.03	30

Note: EIRP=Conducted Power(dBm) - Lc(dB) + G_T(dBi)

Use ANT5 to calculate maximum EIRP.

Result:**Pass****Peak-to-average Ratio(PAR)**

Test Mode	Peak-to-average Ratio(dB)			Limit (dB)
	Lowest Channel	Middle Channel	Highest Channel	
WCDMA R99	2.95	3.14	3.11	13
HSDPA	3.88	3.56	4.07	13
HSUPA	3.88	3.94	3.97	13

Result:**Pass****Occupied Bandwidth**

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
WCDMA R99	4.167	4.167	4.183	4.721	4.728	4.737
HSDPA	4.151	4.151	4.167	4.737	4.731	4.715
HSUPA	4.151	4.167	4.151	4.731	4.715	4.728

Note: The test plots please refer to the Plots of Occupied Bandwidth

Spurious Emissions at Antenna Terminal

Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
----------------	--

Out of band emission, Band Edge







Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.
----------------	---

Frequency Stability

Test Mode:	WCDMA R99	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.86	1710.293	1710.000	1754.695	1755.000
	-20	3.86	1710.289	1710.000	1754.697	1755.000
	-10	3.86	1710.315	1710.000	1754.689	1755.000
	0	3.86	1710.299	1710.000	1754.683	1755.000
	10	3.86	1710.303	1710.000	1754.699	1755.000
	20	3.86	1710.317	1710.000	1754.683	1755.000
	30	3.86	1710.293	1710.000	1754.705	1755.000
	40	3.86	1710.297	1710.000	1754.701	1755.000
	50	3.86	1710.301	1710.000	1754.687	1755.000
Frequency Stability vs. Voltage	20	3.4	1710.297	1710.000	1754.694	1755.000
	20	4.5	1710.310	1710.000	1754.701	1755.000
					Result:	Pass

Test Plots(Note: The 14.5 dB is the Insertion loss of the RF cable, Coaxial tee connector and Attenuator, which was offset into the Spectrum Analyzer):

Occupied Bandwidth


Channel	WCDMA R99	HSDPA
Lowest	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:46:34	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:32:03
Middle	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:48:45	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:30:33
Highest	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:51:41	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:29:12

Occupied Bandwidth

Channel


HSUPA

Lowest




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 16:25:36

Middle



ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 16:26:49

Highest




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 16:28:07

Spurious Emissions at Antenna Terminal

Channel


WCDMA R99

Lowest




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 14:31:26

Middle









ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 14:32:01

Highest



ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 14:32:35

Out of band emission, Band Edge

Mode	Lowest	Highest
R99	 Ref: 40 dBm Offset: 14.5 dB Att: 30 dB RBW: 100 kHz VBW: 300 kHz SWT: 20 ms Marker 1 [T1] -10.25 dBm 1.710000000 GHz Center: 1.71 GHz Span: 10 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 15:57:39	 Ref: 40 dBm Offset: 14.5 dB Att: 30 dB RBW: 100 kHz VBW: 300 kHz SWT: 20 ms Marker 1 [T1] -19.42 dBm 1.755000000 GHz Center: 1.755 GHz Span: 10 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:02:12
HSUPA	 Ref: 40 dBm Offset: 14.5 dB Att: 30 dB RBW: 100 kHz VBW: 300 kHz SWT: 20 ms Marker 1 [T1] -20.67 dBm 1.710000000 GHz Center: 1.71 GHz Span: 10 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:16:05	 Ref: 40 dBm Offset: 14.5 dB Att: 30 dB RBW: 100 kHz VBW: 300 kHz SWT: 20 ms Marker 1 [T1] -20.79 dBm 1.755000000 GHz Center: 1.755 GHz Span: 10 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:16:31
HSDPA	 Ref: 40 dBm Offset: 14.5 dB Att: 30 dB RBW: 100 kHz VBW: 300 kHz SWT: 20 ms Marker 1 [T1] -21.10 dBm 1.710000000 GHz Center: 1.71 GHz Span: 10 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:13:03	 Ref: 40 dBm Offset: 14.5 dB Att: 30 dB RBW: 100 kHz VBW: 300 kHz SWT: 20 ms Marker 1 [T1] -20.25 dBm 1.755000000 GHz Center: 1.755 GHz Span: 10 MHz ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:13:29

4.5 Antenna Port Test Data and Results for WCDMA Band 5:

Sample Number:	2X9R-2	Test Date:	2025/2/8
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.7	Relative Humidity: (%)	43	ATM Pressure: (kPa)	102.1
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2024/4/1	2025/3/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Unknown	Coaxial tee connector	Unknown	2204004	Each time	N/A
Anritsu	Radio Communication Analyzer	MT8820C	6201010144	2024/7/12	2025/7/11
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2024/4/1	2025/3/31
UNI-T	Multimeter	UT39A+	C210582554	2025/1/6	2026/1/5
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Frequency:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
WCDMA	826.4	836.6	846.6

Test Data:**RF Output Power**

Test Mode	Conducted Average Output Power(dBm)			Maximum ERP (dBm)	ERP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	22.35	22.37	22.32	14.02	38.45
HSDPA Subtest 1	21.41	21.43	21.37	13.08	38.45
HSDPA Subtest 2	21.43	21.42	21.36	13.08	38.45
HSDPA Subtest 3	21.38	21.45	21.32	13.1	38.45
HSDPA Subtest 4	21.41	21.40	21.35	13.06	38.45
HSUPA Subtest 1	21.41	21.41	21.36	13.06	38.45
HSUPA Subtest 2	21.36	21.42	21.38	13.07	38.45
HSUPA Subtest 3	21.44	21.43	21.37	13.09	38.45
HSUPA Subtest 4	21.39	21.46	21.36	13.11	38.45
HSUPA Subtest 5	21.43	21.45	21.33	13.1	38.45
HSPA+ Subtest 1	21.45	21.39	21.41	13.1	38.45
Note: ERP= Conducted Power(dBm) - Lc(dB) + Gr(dBd) Gr(dBd)=Gr(dBi)-2.15 Use ANT4 to calculate maximum ERP.					
				Result:	Pass

Peak-to-average Ratio(PAR)

Test Mode	Peak-to-average Ratio(dB)			Limit (dB)	
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	3.08	3.11	3.14	13	
HSDPA	3.91	4.36	3.72	13	
HSUPA	3.91	3.94	3.91	13	
				Result:	Pass

Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
WCDMA R99	4.167	4.167	4.151	4.721	4.712	4.712
HSDPA	4.183	4.135	4.183	4.747	4.721	4.712
HSUPA	4.167	4.167	4.151	4.747	4.728	4.715
Note: The test plots please refer to the Plots of Occupied Bandwidth						

Spurious Emissions at Antenna Terminal

Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
----------------	--







Out of band emission, Band Edge

Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.
----------------	---

Frequency Stability					
Test Modulation:	WCDMA R99		Test Channel:	836.6	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.86	28	0.033	2.5
	-20	3.86	44	0.053	2.5
	-10	3.86	7	0.008	2.5
	0	3.86	20	0.024	2.5
	10	3.86	2	0.002	2.5
	20	3.86	28	0.033	2.5
	30	3.86	10	0.012	2.5
	40	3.86	3	0.004	2.5
	50	3.86	7	0.008	2.5
Frequency Stability vs. Voltage	20	3.4	10	0.012	2.5
	20	4.5	11	0.013	2.5
				Result:	Pass

Test Plots(Note: The 14.5 dB is the Insertion loss of the RF cable, Coaxial tee connector and Attenuator, which was offset into the Spectrum Analyzer):

Occupied Bandwidth


Channel	WCDMA R99	HSDPA
Lowest	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 16:58:44	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 17:06:57
Middle	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 17:00:44	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 17:05:24
Highest	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 17:02:00	 ProjectNo.:2503P28739E-RF Tester:Arthur Su Date: 8.FEB.2025 17:03:56

Occupied Bandwidth

Channel


HSUPA

Lowest




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 17:08:03

Middle



ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 17:09:29

Highest




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 17:11:26

Spurious Emissions at Antenna Terminal

Channel


WCDMA R99

Lowest




ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 14:25:26

Middle









ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 14:26:05

Highest



ProjectNo.:2503P28739E-RF Tester:Arthur Su
Date: 8.FEB.2025 14:26:40

Out of band emission, Band Edge

Mode	Lowest	Highest
R99	 Ref: 40 dBm, Att: 30 dB, RBW: 100 kHz, VBW: 300 kHz, SWT: 20 ms, Marker 1 [T1]: -19.05 dBm, 824.000000000 MHz Center: 824 MHz, Span: 10 MHz ProjectNo.:2503P28739E-RF, Tester:Arthur Su, Date: 8.FEB.2025 15:12:44	 Ref: 40 dBm, Att: 30 dB, RBW: 100 kHz, VBW: 300 kHz, SWT: 20 ms, Marker 1 [T1]: -19.90 dBm, 849.000000000 MHz Center: 849 MHz, Span: 10 MHz ProjectNo.:2503P28739E-RF, Tester:Arthur Su, Date: 8.FEB.2025 15:17:59
HSUPA	 Ref: 40 dBm, Att: 30 dB, RBW: 100 kHz, VBW: 300 kHz, SWT: 20 ms, Marker 1 [T1]: -19.34 dBm, 824.000000000 MHz Center: 824 MHz, Span: 10 MHz ProjectNo.:2503P28739E-RF, Tester:Arthur Su, Date: 8.FEB.2025 15:43:09	 Ref: 40 dBm, Att: 30 dB, RBW: 100 kHz, VBW: 300 kHz, SWT: 20 ms, Marker 1 [T1]: -21.11 dBm, 849.000000000 MHz Center: 849 MHz, Span: 10 MHz ProjectNo.:2503P28739E-RF, Tester:Arthur Su, Date: 8.FEB.2025 15:47:21
HSDPA	 Ref: 40 dBm, Att: 30 dB, RBW: 100 kHz, VBW: 300 kHz, SWT: 20 ms, Marker 1 [T1]: -20.59 dBm, 824.000000000 MHz Center: 824 MHz, Span: 10 MHz ProjectNo.:2503P28739E-RF, Tester:Arthur Su, Date: 8.FEB.2025 15:42:48	 Ref: 40 dBm, Att: 30 dB, RBW: 100 kHz, VBW: 300 kHz, SWT: 20 ms, Marker 1 [T1]: -19.58 dBm, 849.000000000 MHz Center: 849 MHz, Span: 10 MHz ProjectNo.:2503P28739E-RF, Tester:Arthur Su, Date: 8.FEB.2025 15:36:28

4.6 LTE Band RF Conducted data

Test Frequency for Each Mode:				
Operation Band	Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
B2	1.4MHz	1850.7	1880	1909.3
	3MHz	1851.5	1880	1908.5
	5MHz	1852.5	1880	1907.5
	10MHz	1855	1880	1905
	15MHz	1857.5	1880	1902.5
	20MHz	1860	1880	1900
B4	1.4MHz	1710.7	1732.5	1754.3
	3MHz	1711.5	1732.5	1753.5
	5MHz	1712.5	1732.5	1752.5
	10MHz	1715	1732.5	1750
	15MHz	1717.5	1732.5	1747.5
	20MHz	1720	1732.5	1745
B5	1.4MHz	824.7	836.5	848.3
	3MHz	825.5	836.5	847.5
	5MHz	826.5	836.5	846.5
	10MHz	829	836.5	844
B7	5MHz	2502.5	2535	2567.5
	10MHz	2505	2535	2565
	15MHz	2507.5	2535	2562.5
	20MHz	2510	2535	2560
B12	1.4MHz	699.7	707.5	715.3
	3MHz	700.5	707.5	714.5
	5MHz	701.5	707.5	713.5
	10MHz	704	707.5	711
B13	5MHz	779.5	/	784.5
	10MHz	/	782	/
B17	5MHz	706.5	710	713.5
	10MHz	709	710	711
B38	5MHz	2572.5	2595	2617.5
	10MHz	2575	2595	2615
	15MHz	2577.5	2595	2612.5
	20MHz	2580	2595	2610
B41	5MHz	2498.5	2593	2687.5
	10MHz	2501	2593	2685
	15MHz	2503.5	2593	2682.5
	20MHz	2506	2593	2680
B42	5MHz	3452.5	3500	3547.5
	10MHz	3455	3500	3545
	15MHz	3457.5	3500	3542.5
	20MHz	3460	3500	3540

Operation Band	Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
B66	1.4MHz	1710.7	1745	1779.3
	3MHz	1711.5	1745	1778.5
	5MHz	1712.5	1745	1777.5
	10MHz	1715	1745	1775
	15MHz	1717.5	1745	1772.5
	20MHz	1720	1745	1770

Please refer to Annex "2503P28739E-RF-00E _Appendix A" for detail test data.

4.7 Radiated Spurious Emissions

4.7.1 30 MHz – 1 GHz

Sample Number:	2X9R-1	Test Date:	2025/1/25
Test Site:	966-2	Test Mode:	Transmitting
Tester:	Carl Xue	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.6	Relative Humidity: (%)	51	ATM Pressure: (kPa)	101.1
----------------------	------	---------------------------	----	---------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2023/12/1	2026/11/30
R&S	EMI Test Receiver	ESR3	102724	2024/2/29	2025/2/28
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0100-03	2024/12/3	2025/12/2
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0370-01	2024/12/3	2025/12/2
XQY	Coaxial Cable	XQY-CMR400UF-NJ-NJ-7M	24056379	2024/6/11	2025/6/10
Sonoma	Amplifier	310N	186165	2024/12/3	2025/12/2
EMCO	Adjustable Dipole Antenna	3121C	9109-756	N/A	N/A
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2024/7/15	2025/7/14
Agilent	Signal Generator	E8247C	MY43321352	2025/01/09	2026/01/08

*** Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

ANT2**GSM 850:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:			824.2	MHz				
584.72	H	20.80	-53.36	0.00	0.46	-53.82	-13.00	40.82
562.89	V	20.78	-50.89	0.00	0.46	-51.35	-13.00	38.35
Frequency:			836.6	MHz				
631.87	H	20.58	-53.11	0.00	0.49	-53.60	-13.00	40.60
532.21	V	20.64	-50.99	0.00	0.45	-51.44	-13.00	38.44
Frequency:			848.8	MHz				
663.68	H	21.12	-52.40	0.00	0.50	-52.90	-13.00	39.90
489.29	V	20.61	-51.40	0.00	0.44	-51.84	-13.00	38.84

WCDMA Band 5:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:			826.4	MHz				
532.21	H	20.52	-54.68	0.00	0.45	-55.13	-13.00	42.13
574.85	V	20.39	-51.30	0.00	0.46	-51.76	-13.00	38.76
Frequency:			836.6	MHz				
506.72	H	20.63	-55.07	0.00	0.45	-55.52	-13.00	42.52
537.83	V	20.41	-51.23	0.00	0.46	-51.69	-13.00	38.69
Frequency:			846.6	MHz				
576.86	H	20.69	-53.63	0.00	0.46	-54.09	-13.00	41.09
491.05	V	20.67	-51.27	0.00	0.44	-51.71	-13.00	38.71

LTE Bands:

(The Worst modulation and bandwidth(1RB) was below)

LTE Band 5:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency:			824.7	MHz				
583.72	H	20.35	-53.83	0.00	0.46	-54.29	-13.00	41.29
505.63	V	20.61	-50.98	0.00	0.45	-51.43	-13.00	38.43
1.4MHz QPSK, Frequency:			836.5	MHz				
596.12	H	20.52	-53.42	0.00	0.51	-53.93	-13.00	40.93
577.62	V	20.68	-51.02	0.00	0.46	-51.48	-13.00	38.48
1.4MHz QPSK, Frequency:			848.3	MHz				
512.67	H	20.37	-55.21	0.00	0.44	-55.65	-13.00	42.65
474.92	V	20.32	-52.26	0.00	0.42	-52.68	-13.00	39.68

LTE Band 12:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 699.7 MHz								
332.63	H	20.43	-58.47	0.00	0.35	-58.82	-13.00	45.82
503.18	V	20.57	-51.01	0.00	0.45	-51.46	-13.00	38.46
1.4MHz QPSK, Frequency: 707.5 MHz								
471.49	H	20.52	-55.89	0.00	0.43	-56.32	-13.00	43.32
418.34	V	20.45	-54.37	0.00	0.39	-54.76	-13.00	41.76
1.4MHz QPSK, Frequency: 715.3 MHz								
272.90	H	20.60	-59.54	0.00	0.32	-59.86	-13.00	46.86
466.68	V	20.43	-52.47	0.00	0.42	-52.89	-13.00	39.89

LTE Band 13:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 779.5 MHz								
583.72	H	20.59	-53.59	0.00	0.46	-54.05	-13.00	41.05
476.39	V	20.52	-52.00	0.00	0.42	-52.42	-13.00	39.42
5MHz QPSK, Frequency: 784.5 MHz								
529.19	H	20.51	-54.74	0.00	0.45	-55.19	-13.00	42.19
542.62	V	20.63	-51.01	0.00	0.47	-51.48	-13.00	38.48

LTE Band 17:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:			706.5	MHz				
555.79	H	20.61	-54.12	0.00	0.49	-54.61	-13.00	41.61
461.45	V	20.52	-52.59	0.00	0.41	-53.00	-13.00	40.00
5MHz QPSK, Frequency:			710	MHz				
512.67	H	20.68	-54.90	0.00	0.44	-55.34	-13.00	42.34
446.61	V	20.57	-53.13	0.00	0.43	-53.56	-13.00	40.56
5MHz QPSK, Frequency:			713.5	MHz				
278.74	H	20.53	-59.45	0.00	0.32	-59.77	-13.00	46.77
328.13	V	20.63	-56.36	0.00	0.34	-56.70	-13.00	43.70

ANT3**GSM 1900:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:			1850.2	MHz				
212.26	H	48.96	-63.69	0.00	0.26	-63.95	-13.00	50.95
96.43	V	46.19	-61.66	0.00	0.19	-61.85	-13.00	48.85
Frequency:			1880	MHz				
211.52	H	48.40	-64.26	0.00	0.26	-64.52	-13.00	51.52
99.17	V	46.76	-60.46	0.00	0.19	-60.65	-13.00	47.65
Frequency:			1909.8	MHz				
210.05	H	48.65	-64.04	0.00	0.26	-64.30	-13.00	51.30
93.76	V	47.23	-61.24	0.00	0.18	-61.42	-13.00	48.42

WCDMA Band 2:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:			1852.4	MHz				
213.76	H	49.43	-63.19	0.00	0.27	-63.46	-13.00	50.46
94.67	V	46.29	-61.97	0.00	0.19	-62.16	-13.00	49.16
Frequency:			1880	MHz				
210.05	H	49.85	-62.84	0.00	0.26	-63.10	-13.00	50.10
99.76	V	45.84	-61.25	0.00	0.19	-61.44	-13.00	48.44
Frequency:			1907.6	MHz				
218.30	H	49.61	-62.92	0.00	0.27	-63.19	-13.00	50.19
95.42	V	46.43	-61.65	0.00	0.19	-61.84	-13.00	48.84

WCDMA Band 4:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1712.4 MHz								
211.52	H	50.03	-62.63	0.00	0.26	-62.89	-13.00	49.89
98.48	V	46.93	-60.45	0.00	0.19	-60.64	-13.00	47.64
Frequency: 1732.6 MHz								
212.26	H	49.43	-63.22	0.00	0.26	-63.48	-13.00	50.48
99.18	V	46.31	-60.91	0.00	0.19	-61.10	-13.00	48.10
Frequency: 1752.6 MHz								
209.31	H	49.96	-62.75	0.00	0.26	-63.01	-13.00	50.01
97.45	V	47.36	-60.26	0.00	0.19	-60.45	-13.00	47.45

LTE Bands:

(The Worst modulation and bandwidth(1RB) was below)

LTE Band 2:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1850.7 MHz								
313.27	H	48.83	-61.69	0.00	0.34	-62.03	-13.00	49.03
297.22	V	43.42	-65.51	0.00	0.33	-65.84	-13.00	52.84
1.4MHz QPSK, Frequency: 1880 MHz								
322.18	H	48.48	-61.91	0.00	0.34	-62.25	-13.00	49.25
316.58	V	44.07	-64.31	0.00	0.34	-64.65	-13.00	51.65
1.4MHz QPSK, Frequency: 1909.3 MHz								
306.79	H	47.96	-62.66	0.00	0.34	-63.00	-13.00	50.00
310.01	V	43.78	-64.77	0.00	0.34	-65.11	-13.00	52.11

LTE Band 4:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
332.51	H	48.65	-61.58	0.00	0.35	-61.93	-13.00	48.93
315.48	V	43.10	-65.31	0.00	0.34	-65.65	-13.00	52.65
1.4MHz QPSK, Frequency: 1732.5 MHz								
314.39	H	49.09	-61.41	0.00	0.34	-61.75	-13.00	48.75
296.20	V	43.67	-65.30	0.00	0.33	-65.63	-13.00	52.63
1.4MHz QPSK, Frequency: 1754.3 MHz								
307.85	H	49.39	-61.21	0.00	0.34	-61.55	-13.00	48.55
306.76	V	42.62	-66.01	0.00	0.34	-66.35	-13.00	53.35

LTE Band 7:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2502.5 MHz								
297.24	H	48.96	-61.83	0.00	0.33	-62.16	-25.00	37.16
317.70	V	42.97	-65.38	0.00	0.34	-65.72	-25.00	40.72
5MHz QPSK, Frequency: 2535 MHz								
292.08	H	48.92	-61.99	0.00	0.33	-62.32	-25.00	37.32
322.18	V	43.65	-64.58	0.00	0.34	-64.92	-25.00	39.92
5MHz QPSK, Frequency: 2567.5 MHz								
316.58	H	49.18	-61.29	0.00	0.34	-61.63	-25.00	36.63
298.91	V	42.78	-66.08	0.00	0.34	-66.42	-25.00	41.42

LTE Band 38:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2572.5 MHz								
287.99	H	49.51	-61.49	0.00	0.33	-61.82	-25.00	36.82
193.09	V	43.78	-65.69	0.00	0.26	-65.95	-25.00	40.95
5MHz QPSK, Frequency: 2595 MHz								
311.06	H	48.86	-61.69	0.00	0.34	-62.03	-25.00	37.03
308.78	V	42.93	-65.65	0.00	0.34	-65.99	-25.00	40.99
5MHz QPSK, Frequency: 2617.5 MHz								
299.34	H	48.90	-61.84	0.00	0.34	-62.18	-25.00	37.18
298.13	V	43.13	-65.76	0.00	0.34	-66.10	-25.00	41.10

LTE Band 41(2496- 2690 MHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2498.5 MHz								
313.26	H	49.94	-60.58	0.00	0.34	-60.92	-25.00	35.92
321.06	V	42.96	-65.30	0.00	0.34	-65.64	-25.00	40.64
5MHz QPSK, Frequency: 2593 MHz								
308.92	H	50.11	-60.48	0.00	0.34	-60.82	-25.00	35.82
301.44	V	43.61	-65.16	0.00	0.34	-65.50	-25.00	40.50
5MHz QPSK, Frequency: 2687.5 MHz								
298.26	H	49.57	-61.19	0.00	0.34	-61.53	-25.00	36.53
324.45	V	43.01	-65.16	0.00	0.34	-65.50	-25.00	40.50

LTE Band 66:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
300.36	H	49.81	-60.90	0.00	0.34	-61.24	-13.00	48.24
321.06	V	43.80	-64.46	0.00	0.34	-64.80	-13.00	51.80
1.4MHz QPSK, Frequency: 1745 MHz								
315.46	H	49.45	-61.04	0.00	0.34	-61.38	-13.00	48.38
330.18	V	43.58	-64.45	0.00	0.34	-64.79	-13.00	51.79
1.4MHz QPSK, Frequency: 1779.3 MHz								
292.06	H	49.79	-61.12	0.00	0.33	-61.45	-13.00	48.45
304.62	V	43.55	-65.14	0.00	0.34	-65.48	-13.00	52.48

ANT4**GSM 850:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:			824.2	MHz				
631.87	H	20.61	-53.08	0.00	0.49	-53.57	-13.00	40.57
553.12	V	20.74	-50.92	0.00	0.48	-51.40	-13.00	38.40
Frequency:			836.6	MHz				
470.80	H	20.55	-55.88	0.00	0.43	-56.31	-13.00	43.31
595.34	V	20.43	-51.29	0.00	0.51	-51.80	-13.00	38.80
Frequency:			848.8	MHz				
574.85	H	20.79	-53.57	0.00	0.46	-54.03	-13.00	41.03
570.83	V	20.85	-50.84	0.00	0.46	-51.30	-13.00	38.30

WCDMA Band 5:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:			826.4	MHz				
485.88	H	20.47	-55.65	0.00	0.43	-56.08	-13.00	43.08
539.72	V	20.61	-51.03	0.00	0.46	-51.49	-13.00	38.49
Frequency:			836.6	MHz				
580.92	H	20.84	-53.40	0.00	0.46	-53.86	-13.00	40.86
627.46	V	20.43	-50.80	0.00	0.48	-51.28	-13.00	38.28
Frequency:			846.6	MHz				
636.31	H	20.74	-52.92	0.00	0.52	-53.44	-13.00	40.44
448.26	V	20.68	-52.95	0.00	0.43	-53.38	-13.00	40.38

LTE Bands:

(The Worst modulation and bandwidth(1RB) was below)

LTE Band 5:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency:			824.7	MHz				
567.59	H	20.62	-53.88	0.00	0.46	-54.34	-13.00	41.34
442.62	V	20.38	-53.48	0.00	0.43	-53.91	-13.00	40.91
1.4MHz QPSK, Frequency:			836.5	MHz				
621.39	H	20.51	-53.23	0.00	0.49	-53.72	-13.00	40.72
510.97	V	20.49	-51.11	0.00	0.45	-51.56	-13.00	38.56
1.4MHz QPSK, Frequency:			848.3	MHz				
529.58	H	20.36	-54.89	0.00	0.45	-55.34	-13.00	42.34
553.87	V	20.50	-51.16	0.00	0.49	-51.65	-13.00	38.65

LTE Band 12:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 699.7 MHz								
445.72	H	20.42	-56.52	0.00	0.43	-56.95	-13.00	43.95
486.51	V	20.33	-51.79	0.00	0.43	-52.22	-13.00	39.22
1.4MHz QPSK, Frequency: 707.5 MHz								
493.38	H	20.47	-55.50	0.00	0.45	-55.95	-13.00	42.95
221.98	V	20.63	-58.22	0.00	0.27	-58.49	-13.00	45.49
1.4MHz QPSK, Frequency: 715.3 MHz								
374.18	H	20.64	-57.63	0.00	0.37	-58.00	-13.00	45.00
298.97	V	20.56	-57.05	0.00	0.34	-57.39	-13.00	44.39

LTE Band 13:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 779.5 MHz								
431.89	H	20.50	-56.72	0.00	0.40	-57.12	-13.00	44.12
538.41	V	20.62	-51.02	0.00	0.46	-51.48	-13.00	38.48
5MHz QPSK, Frequency: 784.5 MHz								
505.63	H	20.58	-55.14	0.00	0.45	-55.59	-13.00	42.59
461.14	V	20.41	-52.71	0.00	0.41	-53.12	-13.00	40.12

LTE Band 17:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:			706.5	MHz				
551.91	H	20.54	-54.27	0.00	0.48	-54.75	-13.00	41.75
484.81	V	20.68	-51.50	0.00	0.43	-51.93	-13.00	38.93
5MHz QPSK, Frequency:			710	MHz				
469.77	H	20.43	-56.02	0.00	0.43	-56.45	-13.00	43.45
436.45	V	20.59	-53.51	0.00	0.41	-53.92	-13.00	40.92
5MHz QPSK, Frequency:			713.5	MHz				
527.34	H	20.57	-54.72	0.00	0.43	-55.15	-13.00	42.15
509.18	V	20.55	-51.04	0.00	0.45	-51.49	-13.00	38.49

ANT5**GSM 1900:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:			1850.2	MHz				
210.78	H	49.27	-63.41	0.00	0.26	-63.67	-13.00	50.67
94.76	V	46.50	-61.74	0.00	0.19	-61.93	-13.00	48.93
Frequency:			1880	MHz				
217.53	H	48.31	-64.23	0.00	0.27	-64.50	-13.00	51.50
93.79	V	46.32	-62.14	0.00	0.18	-62.32	-13.00	49.32
Frequency:			1909.8	MHz				
211.57	H	48.71	-63.95	0.00	0.26	-64.21	-13.00	51.21
94.42	V	46.74	-61.57	0.00	0.18	-61.75	-13.00	48.75

WCDMA Band 2:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:			1852.4	MHz				
210.78	H	50.16	-62.52	0.00	0.26	-62.78	-13.00	49.78
94.76	V	46.72	-61.52	0.00	0.19	-61.71	-13.00	48.71
Frequency:			1880	MHz				
212.26	H	49.98	-62.67	0.00	0.26	-62.93	-13.00	49.93
99.17	V	46.53	-60.69	0.00	0.19	-60.88	-13.00	47.88
Frequency:			1907.6	MHz				
217.53	H	49.53	-63.01	0.00	0.27	-63.28	-13.00	50.28
97.11	V	46.90	-60.79	0.00	0.19	-60.98	-13.00	47.98

WCDMA Band 4:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:			1712.4	MHz				
213.76	H	49.84	-62.78	0.00	0.27	-63.05	-13.00	50.05
94.42	V	46.99	-61.32	0.00	0.18	-61.50	-13.00	48.50
Frequency:			1732.6	MHz				
210.52	H	49.66	-63.02	0.00	0.26	-63.28	-13.00	50.28
97.11	V	46.52	-61.17	0.00	0.19	-61.36	-13.00	48.36
Frequency:			1752.6	MHz				
211.59	H	49.61	-63.05	0.00	0.26	-63.31	-13.00	50.31
95.26	V	46.71	-61.41	0.00	0.19	-61.60	-13.00	48.60

LTE Bands:

(The Worst modulation and bandwidth(1RB) was below)

LTE Band 2:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency:			1850.7	MHz				
285.04	H	49.71	-61.36	0.00	0.32	-61.68	-13.00	48.68
311.08	V	42.98	-65.54	0.00	0.34	-65.88	-13.00	52.88
1.4MHz QPSK, Frequency:			1880	MHz				
321.06	H	49.78	-60.62	0.00	0.34	-60.96	-13.00	47.96
316.58	V	43.46	-64.92	0.00	0.34	-65.26	-13.00	52.26
1.4MHz QPSK, Frequency:			1909.3	MHz				
297.25	H	49.34	-61.44	0.00	0.33	-61.77	-13.00	48.77
332.49	V	43.16	-64.81	0.00	0.34	-65.15	-13.00	52.15

LTE Band 4:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency:			1710.7	MHz				
324.45	H	49.12	-61.23	0.00	0.34	-61.57	-13.00	48.57
316.58	V	43.40	-64.98	0.00	0.34	-65.32	-13.00	52.32
1.4MHz QPSK, Frequency:			1732.5	MHz				
295.17	H	49.61	-61.22	0.00	0.33	-61.55	-13.00	48.55
306.76	V	43.20	-65.43	0.00	0.34	-65.77	-13.00	52.77
1.4MHz QPSK, Frequency:			1754.3	MHz				
299.34	H	48.92	-61.82	0.00	0.34	-62.16	-13.00	49.16
321.56	V	43.51	-64.74	0.00	0.34	-65.08	-13.00	52.08

LTE Band 7:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2502.5 MHz								
318.87	H	49.11	-61.33	0.00	0.34	-61.67	-25.00	36.67
314.37	V	43.70	-64.74	0.00	0.34	-65.08	-25.00	40.08
5MHz QPSK, Frequency: 2535 MHz								
311.09	H	49.78	-60.77	0.00	0.34	-61.11	-25.00	36.11
292.08	V	42.77	-66.38	0.00	0.33	-66.71	-25.00	41.71
5MHz QPSK, Frequency: 2567.5 MHz								
313.28	H	49.39	-61.13	0.00	0.34	-61.47	-25.00	36.47
321.54	V	43.45	-64.80	0.00	0.34	-65.14	-25.00	40.14

LTE Band 38:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2572.5 MHz								
298.21	H	49.08	-61.68	0.00	0.34	-62.02	-25.00	37.02
321.06	V	42.63	-65.63	0.00	0.34	-65.97	-25.00	40.97
5MHz QPSK, Frequency: 2595 MHz								
313.28	H	48.95	-61.57	0.00	0.34	-61.91	-25.00	36.91
297.47	V	43.32	-65.60	0.00	0.33	-65.93	-25.00	40.93
5MHz QPSK, Frequency: 2617.5 MHz								
322.18	H	49.66	-60.73	0.00	0.34	-61.07	-25.00	36.07
273.78	V	43.21	-66.73	0.00	0.32	-67.05	-25.00	42.05

LTE Band 41(2496- 2690 MHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2498.5 MHz								
308.91	H	50.46	-60.13	0.00	0.34	-60.47	-25.00	35.47
311.87	V	43.60	-64.90	0.00	0.34	-65.24	-25.00	40.24
5MHz QPSK, Frequency: 2593 MHz								
300.76	H	50.14	-60.57	0.00	0.34	-60.91	-25.00	35.91
302.49	V	43.53	-65.22	0.00	0.34	-65.56	-25.00	40.56
5MHz QPSK, Frequency: 2687.5 MHz								
315.74	H	49.51	-60.97	0.00	0.34	-61.31	-25.00	36.31
313.27	V	43.41	-65.05	0.00	0.34	-65.39	-25.00	40.39

LTE Band 66:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
318.81	H	50.13	-60.31	0.00	0.34	-60.65	-13.00	47.65
307.83	V	42.47	-66.14	0.00	0.34	-66.48	-13.00	53.48
1.4MHz QPSK, Frequency: 1745 MHz								
295.17	H	49.29	-61.54	0.00	0.33	-61.87	-13.00	48.87
319.32	V	42.77	-65.54	0.00	0.34	-65.88	-13.00	52.88
1.4MHz QPSK, Frequency: 1779.3 MHz								
326.73	H	49.41	-60.91	0.00	0.34	-61.25	-13.00	48.25
273.26	V	43.14	-66.83	0.00	0.32	-67.15	-13.00	54.15

ANT0**LTE Band 42:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 3452.5 MHz								
304.60	H	49.76	-60.89	0.00	0.34	-61.23	-13.00	48.23
311.08	V	43.79	-64.73	0.00	0.34	-65.07	-13.00	52.07
5MHz QPSK, Frequency: 3500 MHz								
326.74	H	50.20	-60.12	0.00	0.34	-60.46	-13.00	47.46
315.47	V	42.74	-65.67	0.00	0.34	-66.01	-13.00	53.01
5MHz QPSK, Frequency: 3547.5 MHz								
300.39	H	49.46	-61.25	0.00	0.34	-61.59	-13.00	48.59
321.51	V	43.57	-64.68	0.00	0.34	-65.02	-13.00	52.02

ANT6**LTE Band 42:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 3452.5 MHz								
293.11	H	49.61	-61.27	0.00	0.33	-61.60	-13.00	48.60
317.70	V	43.60	-64.75	0.00	0.34	-65.09	-13.00	52.09
5MHz QPSK, Frequency: 3500 MHz								
287.99	H	49.80	-61.20	0.00	0.33	-61.53	-13.00	48.53
308.95	V	43.36	-65.22	0.00	0.34	-65.56	-13.00	52.56
5MHz QPSK, Frequency: 3547.5 MHz								
295.14	H	49.74	-61.09	0.00	0.33	-61.42	-13.00	48.42
303.55	V	43.11	-65.61	0.00	0.34	-65.95	-13.00	52.95

ANT8**LTE Band 42:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:			3452.5	MHz				
313.27	H	49.50	-61.02	0.00	0.34	-61.36	-13.00	48.36
300.36	V	43.16	-65.64	0.00	0.34	-65.98	-13.00	52.98
5MHz QPSK, Frequency:			3500	MHz				
298.28	H	49.15	-61.61	0.00	0.34	-61.95	-13.00	48.95
295.15	V	42.71	-66.31	0.00	0.33	-66.64	-13.00	53.64
5MHz QPSK, Frequency:			3547.5	MHz				
303.53	H	49.57	-61.10	0.00	0.34	-61.44	-13.00	48.44
322.16	V	42.99	-65.24	0.00	0.34	-65.58	-13.00	52.58

ANT9**LTE Band 42:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 3452.5 MHz								
298.26	H	50.24	-60.52	0.00	0.34	-60.86	-13.00	47.86
310.22	V	43.79	-64.75	0.00	0.34	-65.09	-13.00	52.09
5MHz QPSK, Frequency: 3500 MHz								
302.47	H	49.32	-61.36	0.00	0.34	-61.70	-13.00	48.70
312.28	V	43.30	-65.19	0.00	0.34	-65.53	-13.00	52.53
5MHz QPSK, Frequency: 3547.5 MHz								
306.74	H	49.17	-61.45	0.00	0.34	-61.79	-13.00	48.79
321.05	V	43.29	-64.97	0.00	0.34	-65.31	-13.00	52.31

Note 1: The unit of antenna gain is dBd for frequency below 1GHz and is dBi for frequency above 1GHz.

Note 2: Absolute Level = Substituted Level - Cable Loss+ Antenna Gain

Margin = Limit - Absolute Level

4.7.2 Above 1GHz

Sample Number	2X9R-1	Test Date:	2025/1/23
Test Site:	966-1	Test Mode:	Transmitting
Tester:	Mack Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	22.6	Relative Humidity: (%)	36	ATM Pressure: (kPa)	101.6
----------------------	------	---------------------------	----	---------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	9912-5985	2023/12/6	2026/12/5
R&S	Spectrum Analyzer	FSV40	101591	2024/4/1	2025/3/31
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2025/1/10	2026/1/9
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2025/1/10	2026/1/9
BACL	Preamplifier	1313-A20M18G	4032311	2024/4/1	2025/3/31
AH	Double Ridge Guide Horn Antenna	SAS-571	1396	2023/2/22	2026/2/21
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2024/7/15	2025/7/14
Agilent	Signal Generator	E8247C	MY43321352	2025/1/9	2026/1/8
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2024/2/4	2027/2/3
PASTERNAK	Horn Antenna	PE9852/2F-20	112001	2024/2/4	2027/2/3
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2025/1/6	2026/1/5
PASTERNAK	Horn Antenna	PE9850/2F-20	072001	2024/2/4	2027/2/3
PASTERNAK	Horn Antenna	PE9850/2F-20	072002	2024/2/4	2027/2/3
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2025/1/6	2026/1/5
JD	Multiplex Switch Test Control Set	DT7220SCU	DQ77925	2024/8/5	2025/8/4
JD	Filter Switch Unit	DT7220FSU	DQ77928	2024/8/5	2025/8/4

*** Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

ANT2**GSM850(1-10GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 824.2 MHz								
1648.400	H	42.65	-61.80	8.68	0.80	-53.92	-13.00	40.92
1648.400	V	43.85	-60.68	8.68	0.80	-52.80	-13.00	39.80
2472.600	H	36.88	-64.15	9.38	1.00	-55.77	-13.00	42.77
2472.600	V	34.13	-66.85	9.38	1.00	-58.47	-13.00	45.47
3296.800	H	33.96	-63.42	10.32	1.15	-54.25	-13.00	41.25
3296.800	V	34.74	-62.40	10.32	1.15	-53.23	-13.00	40.23
Frequency: 836.6 MHz								
1673.200	H	43.26	-61.16	8.71	0.85	-53.30	-13.00	40.30
1673.200	V	44.38	-60.15	8.71	0.85	-52.29	-13.00	39.29
2509.800	H	38.67	-62.16	9.42	1.01	-53.75	-13.00	40.75
2509.800	V	39.13	-61.71	9.42	1.01	-53.30	-13.00	40.30
3346.400	H	34.35	-63.71	10.34	1.16	-54.53	-13.00	41.53
3346.400	V	34.62	-63.30	10.34	1.16	-54.12	-13.00	41.12
Frequency: 848.8 MHz								
1697.600	H	42.97	-61.42	8.74	0.90	-53.58	-13.00	40.58
1697.600	V	44.62	-59.90	8.74	0.90	-52.06	-13.00	39.06
2546.400	H	38.47	-62.14	9.47	1.01	-53.68	-13.00	40.68
2546.400	V	39.54	-61.02	9.47	1.01	-52.56	-13.00	39.56
3395.200	H	33.64	-65.15	10.36	1.19	-55.98	-13.00	42.98
3395.200	V	34.58	-64.18	10.36	1.19	-55.01	-13.00	42.01

WCDMA Band 5(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 826.4 MHz								
1652.800	H	55.64	-48.81	8.68	0.81	-40.94	-13.00	27.94
1652.800	V	57.48	-47.05	8.68	0.81	-39.18	-13.00	26.18
2479.200	H	38.64	-62.36	9.39	1.01	-53.98	-13.00	40.98
2479.200	V	39.68	-61.29	9.39	1.01	-52.91	-13.00	39.91
3305.600	H	39.64	-57.81	10.32	1.15	-48.64	-13.00	35.64
3305.600	V	40.35	-56.88	10.32	1.15	-47.71	-13.00	34.71
Frequency: 836.6 MHz								
1673.200	H	54.67	-49.75	8.71	0.85	-41.89	-13.00	28.89
1673.200	V	56.97	-47.56	8.71	0.85	-39.70	-13.00	26.70
2509.800	H	38.64	-62.19	9.42	1.01	-53.78	-13.00	40.78
2509.800	V	39.75	-61.09	9.42	1.01	-52.68	-13.00	39.68
3346.400	H	40.15	-57.91	10.34	1.16	-48.73	-13.00	35.73
3346.400	V	42.35	-55.57	10.34	1.16	-46.39	-13.00	33.39
Frequency: 846.6 MHz								
1693.200	H	54.89	-49.51	8.73	0.89	-41.67	-13.00	28.67
1693.200	V	57.35	-47.17	8.73	0.89	-39.33	-13.00	26.33
2539.800	H	39.48	-61.17	9.46	1.01	-52.72	-13.00	39.72
2539.800	V	39.77	-60.84	9.46	1.01	-52.39	-13.00	39.39
3386.400	H	38.97	-59.69	10.35	1.18	-50.52	-13.00	37.52
3386.400	V	40.17	-58.44	10.35	1.18	-49.27	-13.00	36.27

LTE Bands:

(The Worst modulation and bandwidth(1RB) was below)

LTE Band 5(1-10GHz):

ETL Band 5 (1-16GHz).								
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 824.7 MHz								
1649.400	H	38.52	-65.93	8.68	0.80	-58.05	-13.00	45.05
1649.400	V	37.40	-67.13	8.68	0.80	-59.25	-13.00	46.25
2474.100	H	34.01	-67.01	9.38	1.00	-58.63	-13.00	45.63
2474.100	V	34.96	-66.02	9.38	1.00	-57.64	-13.00	44.64
3298.800	H	33.55	-63.82	10.32	1.15	-54.65	-13.00	41.65
3298.800	V	34.38	-62.75	10.32	1.15	-53.58	-13.00	40.58
1.4MHz QPSK, Frequency: 836.5 MHz								
1673.000	H	37.10	-67.32	8.71	0.85	-59.46	-13.00	46.46
1673.000	V	37.46	-67.07	8.71	0.85	-59.21	-13.00	46.21
2509.500	H	34.02	-66.81	9.42	1.01	-58.40	-13.00	45.40
2509.500	V	33.96	-66.89	9.42	1.01	-58.48	-13.00	45.48
3346.000	H	33.87	-64.19	10.34	1.16	-55.01	-13.00	42.01
3346.000	V	34.12	-63.80	10.34	1.16	-54.62	-13.00	41.62
1.4MHz QPSK, Frequency: 848.3 MHz								
1696.600	H	39.05	-65.34	8.74	0.89	-57.49	-13.00	44.49
1696.600	V	38.55	-65.97	8.74	0.89	-58.12	-13.00	45.12
2544.900	H	34.23	-66.39	9.47	1.01	-57.93	-13.00	44.93
2544.900	V	34.10	-66.47	9.47	1.01	-58.01	-13.00	45.01
3393.200	H	33.67	-65.09	10.36	1.19	-55.92	-13.00	42.92
3393.200	V	33.92	-64.80	10.36	1.19	-55.63	-13.00	42.63

LTE Band 12(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 699.7 MHz								
1399.400	H	34.01	-69.79	8.22	0.71	-62.28	-13.00	49.28
1399.400	V	33.63	-70.21	8.22	0.71	-62.70	-13.00	49.70
2099.100	H	33.52	-68.34	9.16	0.91	-60.09	-13.00	47.09
2099.100	V	34.89	-66.92	9.16	0.91	-58.67	-13.00	45.67
2798.800	H	34.21	-66.31	9.88	1.04	-57.47	-13.00	44.47
2798.800	V	33.96	-66.43	9.88	1.04	-57.59	-13.00	44.59
1.4MHz QPSK, Frequency: 707.5 MHz								
1415.000	H	34.02	-69.73	8.26	0.72	-62.19	-13.00	49.19
1415.000	V	34.21	-69.59	8.26	0.72	-62.05	-13.00	49.05
2122.500	H	33.62	-68.40	9.17	0.92	-60.15	-13.00	47.15
2122.500	V	33.87	-68.13	9.17	0.92	-59.88	-13.00	46.88
2830.000	H	34.17	-66.28	9.93	1.06	-57.41	-13.00	44.41
2830.000	V	33.96	-66.43	9.93	1.06	-57.56	-13.00	44.56
1.4MHz QPSK, Frequency: 715.3 MHz								
1430.600	H	33.88	-69.80	8.31	0.73	-62.22	-13.00	49.22
1430.600	V	33.54	-70.20	8.31	0.73	-62.62	-13.00	49.62
2145.900	H	34.12	-68.07	9.19	0.93	-59.81	-13.00	46.81
2145.900	V	34.39	-67.81	9.19	0.93	-59.55	-13.00	46.55
2861.200	H	33.97	-66.40	9.98	1.07	-57.49	-13.00	44.49
2861.200	V	33.66	-66.72	9.98	1.07	-57.81	-13.00	44.81

LTE Band 13(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 779.5 MHz								
1559.000	H	34.22	-69.83	8.57	0.80	-62.06	-40.00	22.06
1559.000	V	33.47	-70.64	8.57	0.80	-62.87	-40.00	22.87
2338.500	H	35.17	-66.70	9.30	0.97	-58.37	-13.00	45.37
2338.500	V	33.44	-68.20	9.30	0.97	-59.87	-13.00	46.87
3118.000	H	33.98	-64.01	10.25	1.13	-54.89	-13.00	41.89
3118.000	V	34.07	-63.77	10.25	1.13	-54.65	-13.00	41.65
5MHz QPSK, Frequency: 784.5 MHz								
1569.000	H	33.63	-70.54	8.58	0.81	-62.77	-40.00	22.77
1569.000	V	34.01	-70.21	8.58	0.81	-62.44	-40.00	22.44
2353.500	H	34.25	-67.51	9.31	0.97	-59.17	-13.00	46.17
2353.500	V	33.96	-67.56	9.31	0.97	-59.22	-13.00	46.22
3138.000	H	34.74	-63.19	10.26	1.14	-54.07	-13.00	41.07
3138.000	V	34.85	-62.91	10.26	1.14	-53.79	-13.00	40.79

LTE Band 17(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 706.5 MHz								
1413.000	H	34.01	-69.75	8.26	0.72	-62.21	-13.00	49.21
1413.000	V	33.66	-70.14	8.26	0.72	-62.60	-13.00	49.60
2119.500	H	33.87	-68.13	9.17	0.92	-59.88	-13.00	46.88
2119.500	V	34.85	-67.13	9.17	0.92	-58.88	-13.00	45.88
2826.000	H	34.02	-66.44	9.92	1.06	-57.58	-13.00	44.58
2826.000	V	33.61	-66.78	9.92	1.06	-57.92	-13.00	44.92
5MHz QPSK, Frequency: 710 MHz								
1420.000	H	34.21	-69.52	8.28	0.73	-61.97	-13.00	48.97
1420.000	V	33.96	-69.82	8.28	0.73	-62.27	-13.00	49.27
2130.000	H	33.87	-68.20	9.18	0.92	-59.94	-13.00	46.94
2130.000	V	34.28	-67.79	9.18	0.92	-59.53	-13.00	46.53
2840.000	H	33.77	-66.65	9.94	1.06	-57.77	-13.00	44.77
2840.000	V	33.02	-67.37	9.94	1.06	-58.49	-13.00	45.49
5MHz QPSK, Frequency: 713.5 MHz								
1427.000	H	33.77	-69.93	8.30	0.73	-62.36	-13.00	49.36
1427.000	V	33.95	-69.81	8.30	0.73	-62.24	-13.00	49.24
2140.500	H	34.12	-68.03	9.18	0.93	-59.78	-13.00	46.78
2140.500	V	34.53	-67.62	9.18	0.93	-59.37	-13.00	46.37
2854.000	H	33.62	-66.77	9.97	1.07	-57.87	-13.00	44.87
2854.000	V	33.38	-67.00	9.97	1.07	-58.10	-13.00	45.10

ANT3**PCS Band (PART 24E)****GSM1900(1-20GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1850.2 MHz								
3700.400	H	40.64	-58.34	10.60	1.25	-48.99	-13.00	35.99
3700.400	V	42.35	-56.61	10.60	1.25	-47.26	-13.00	34.26
5550.600	H	36.45	-59.72	11.44	1.49	-49.77	-13.00	36.77
5550.600	V	35.25	-60.75	11.44	1.49	-50.80	-13.00	37.80
Frequency: 1880 MHz								
3760.000	H	39.47	-58.23	10.66	1.24	-48.81	-13.00	35.81
3760.000	V	40.26	-57.32	10.66	1.24	-47.90	-13.00	34.90
5640.000	H	35.85	-60.95	11.33	1.54	-51.16	-13.00	38.16
5640.000	V	37.41	-59.27	11.33	1.54	-49.48	-13.00	36.48
Frequency: 1909.8 MHz								
3819.600	H	38.99	-58.00	10.72	1.29	-48.57	-13.00	35.57
3819.600	V	41.03	-55.81	10.72	1.29	-46.38	-13.00	33.38
5729.400	H	36.47	-60.67	11.22	1.59	-51.04	-13.00	38.04
5729.400	V	37.15	-59.86	11.22	1.59	-50.23	-13.00	37.23

WCDMA Band 2(1-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1852.4 MHz								
3704.800	H	37.64	-61.25	10.60	1.25	-51.90	-13.00	38.90
3704.800	V	36.54	-62.32	10.60	1.25	-52.97	-13.00	39.97
5557.200	H	33.64	-62.58	11.43	1.49	-52.64	-13.00	39.64
5557.200	V	34.29	-61.78	11.43	1.49	-51.84	-13.00	38.84
Frequency: 1880 MHz								
3760.000	H	36.49	-61.21	10.66	1.24	-51.79	-13.00	38.79
3760.000	V	35.35	-62.23	10.66	1.24	-52.81	-13.00	39.81
5640.000	H	34.85	-61.95	11.33	1.54	-52.16	-13.00	39.16
5640.000	V	36.38	-60.30	11.33	1.54	-50.51	-13.00	37.51
Frequency: 1907.6 MHz								
3815.200	H	34.69	-62.26	10.72	1.29	-52.83	-13.00	39.83
3815.200	V	35.85	-60.95	10.72	1.29	-51.52	-13.00	38.52
5722.800	H	34.76	-62.37	11.23	1.58	-52.72	-13.00	39.72
5722.800	V	33.69	-63.31	11.23	1.58	-53.66	-13.00	40.66

WCDMA Band 4(1-18GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1712.4 MHz								
3424.800	H	36.45	-62.47	10.37	1.17	-53.27	-13.00	40.27
3424.800	V	36.15	-62.74	10.37	1.17	-53.54	-13.00	40.54
5137.200	H	33.48	-62.72	11.28	1.46	-52.90	-13.00	39.90
5137.200	V	34.38	-61.71	11.28	1.46	-51.89	-13.00	38.89
Frequency: 1732.6 MHz								
3465.200	H	35.85	-63.17	10.39	1.15	-53.93	-13.00	40.93
3465.200	V	36.47	-62.50	10.39	1.15	-53.26	-13.00	40.26
5197.800	H	34.33	-62.62	11.32	1.44	-52.74	-13.00	39.74
5197.800	V	34.29	-62.51	11.32	1.44	-52.63	-13.00	39.63
Frequency: 1752.6 MHz								
3505.200	H	35.94	-63.12	10.41	1.18	-53.89	-13.00	40.89
3505.200	V	37.16	-61.84	10.41	1.18	-52.61	-13.00	39.61
5257.800	H	33.58	-63.22	11.35	1.47	-53.34	-13.00	40.34
5257.800	V	34.16	-62.42	11.35	1.47	-52.54	-13.00	39.54

LTE Bands:

(The Worst modulation and bandwidth(1RB) was below)

LTE Band 2(1-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1850.7 MHz								
3701.400	H	37.54	-61.42	10.60	1.25	-52.07	-13.00	39.07
3701.400	V	38.39	-60.55	10.60	1.25	-51.20	-13.00	38.20
5552.100	H	33.65	-62.53	11.44	1.49	-52.58	-13.00	39.58
5552.100	V	34.18	-61.84	11.44	1.49	-51.89	-13.00	38.89
1.4MHz QPSK, Frequency: 1880 MHz								
3760.000	H	37.34	-60.36	10.66	1.24	-50.94	-13.00	37.94
3760.000	V	37.65	-59.93	10.66	1.24	-50.51	-13.00	37.51
5640.000	H	34.12	-62.68	11.33	1.54	-52.89	-13.00	39.89
5640.000	V	34.55	-62.13	11.33	1.54	-52.34	-13.00	39.34
1.4MHz QPSK, Frequency: 1909.3 MHz								
3818.600	H	36.69	-60.29	10.72	1.29	-50.86	-13.00	37.86
3818.600	V	37.45	-59.38	10.72	1.29	-49.95	-13.00	36.95
5727.900	H	33.62	-63.51	11.23	1.59	-53.87	-13.00	40.87
5727.900	V	33.89	-63.11	11.23	1.59	-53.47	-13.00	40.47

LTE Band 4(1-18GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
3421.400	H	36.45	-62.46	10.37	1.17	-53.26	-13.00	40.26
3421.400	V	35.89	-62.99	10.37	1.17	-53.79	-13.00	40.79
5132.100	H	34.15	-61.99	11.28	1.47	-52.18	-13.00	39.18
5132.100	V	34.26	-61.77	11.28	1.47	-51.96	-13.00	38.96
1.4MHz QPSK, Frequency: 1732.5 MHz								
3465.000	H	36.96	-62.06	10.39	1.15	-52.82	-13.00	39.82
3465.000	V	37.38	-61.59	10.39	1.15	-52.35	-13.00	39.35
5197.500	H	34.03	-62.92	11.32	1.44	-53.04	-13.00	40.04
5197.500	V	34.19	-62.61	11.32	1.44	-52.73	-13.00	39.73
1.4MHz QPSK, Frequency: 1754.3 MHz								
3508.600	H	37.19	-61.85	10.41	1.19	-52.63	-13.00	39.63
3508.600	V	37.45	-61.52	10.41	1.19	-52.30	-13.00	39.30
5262.900	H	33.54	-63.25	11.36	1.47	-53.36	-13.00	40.36
5262.900	V	34.19	-62.37	11.36	1.47	-52.48	-13.00	39.48

LTE Band 7(1-26GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2502.5 MHz								
5005.000	H	37.86	-57.61	11.20	1.47	-47.88	-25.00	22.88
5005.000	V	38.15	-57.19	11.20	1.47	-47.46	-25.00	22.46
7507.500	H	33.98	-60.09	10.90	1.95	-51.14	-25.00	26.14
7507.500	V	33.63	-60.94	10.90	1.95	-51.99	-25.00	26.99
5MHz QPSK, Frequency: 2535 MHz								
5070.000	H	36.85	-58.81	11.24	1.47	-49.04	-25.00	24.04
5070.000	V	37.19	-58.36	11.24	1.47	-48.59	-25.00	23.59
7605.000	H	33.65	-59.83	10.88	2.01	-50.96	-25.00	25.96
7605.000	V	33.85	-60.34	10.88	2.01	-51.47	-25.00	26.47
5MHz QPSK, Frequency: 2567.5 MHz								
5135.000	H	36.74	-59.43	11.28	1.47	-49.62	-25.00	24.62
5135.000	V	37.49	-58.57	11.28	1.47	-48.76	-25.00	23.76
7702.500	H	33.69	-59.53	10.86	1.97	-50.64	-25.00	25.64
7702.500	V	34.85	-59.03	10.86	1.97	-50.14	-25.00	25.14

LTE Band 38(1-26.5GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2572.5 MHz								
5145.000	H	36.99	-59.31	11.29	1.44	-49.46	-25.00	24.46
5145.000	V	38.02	-58.16	11.29	1.44	-48.31	-25.00	23.31
7717.500	H	34.44	-58.81	10.86	1.99	-49.94	-25.00	24.94
7717.500	V	33.98	-59.89	10.86	1.99	-51.02	-25.00	26.02
5MHz QPSK, Frequency: 2595 MHz								
5190.000	H	37.48	-59.38	11.31	1.44	-49.51	-25.00	24.51
5190.000	V	38.02	-58.69	11.31	1.44	-48.82	-25.00	23.82
7785.000	H	33.62	-59.77	10.84	1.99	-50.92	-25.00	25.92
7785.000	V	33.49	-60.33	10.84	1.99	-51.48	-25.00	26.48
5MHz QPSK, Frequency: 2617.5 MHz								
5235.000	H	37.19	-59.68	11.34	1.46	-49.80	-25.00	24.80
5235.000	V	36.48	-60.20	11.34	1.46	-50.32	-25.00	25.32
7852.500	H	33.28	-60.20	10.83	2.03	-51.40	-25.00	26.40
7852.500	V	33.94	-59.93	10.83	2.03	-51.13	-25.00	26.13

LTE Band 41(1-27GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2498.5 MHz								
4997.000	H	34.65	-60.80	11.20	1.48	-51.08	-25.00	26.08
4997.000	V	35.82	-59.49	11.20	1.48	-49.77	-25.00	24.77
7495.500	H	34.15	-59.95	10.90	1.94	-50.99	-25.00	25.99
7495.500	V	33.62	-60.98	10.90	1.94	-52.02	-25.00	27.02
5MHz QPSK, Frequency: 2593 MHz								
5186.000	H	34.79	-62.02	11.31	1.44	-52.15	-25.00	27.15
5186.000	V	35.38	-61.28	11.31	1.44	-51.41	-25.00	26.41
7779.000	H	33.63	-59.75	10.84	1.99	-50.90	-25.00	25.90
7779.000	V	33.58	-60.24	10.84	1.99	-51.39	-25.00	26.39
5MHz QPSK, Frequency: 2687.5 MHz								
5375.000	H	36.63	-59.88	11.43	1.49	-49.94	-25.00	24.94
5375.000	V	35.89	-60.61	11.43	1.49	-50.67	-25.00	25.67
8062.500	H	34.41	-58.53	10.81	2.12	-49.84	-25.00	24.84
8062.500	V	34.47	-58.97	10.81	2.12	-50.28	-25.00	25.28

LTE Band 66(1-18GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
3421.400	H	37.86	-61.05	10.37	1.17	-51.85	-13.00	38.85
3421.400	V	38.54	-60.34	10.37	1.17	-51.14	-13.00	38.14
5132.100	H	34.45	-61.69	11.28	1.47	-51.88	-13.00	38.88
5132.100	V	34.19	-61.84	11.28	1.47	-52.03	-13.00	39.03
1.4MHz QPSK, Frequency: 1745 MHz								
3490.000	H	36.77	-62.31	10.40	1.17	-53.08	-13.00	40.08
3490.000	V	38.02	-61.00	10.40	1.17	-51.77	-13.00	38.77
5235.000	H	33.41	-63.46	11.34	1.46	-53.58	-13.00	40.58
5235.000	V	34.36	-62.32	11.34	1.46	-52.44	-13.00	39.44
1.4MHz QPSK, Frequency: 1779.3 MHz								
3558.600	H	35.86	-62.82	10.46	1.22	-53.58	-13.00	40.58
3558.600	V	37.15	-61.42	10.46	1.22	-52.18	-13.00	39.18
5337.900	H	33.63	-62.96	11.40	1.47	-53.03	-13.00	40.03
5337.900	V	34.29	-62.16	11.40	1.47	-52.23	-13.00	39.23

ANT4**GSM850(1-10GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 824.2 MHz								
1648.400	H	43.21	-61.24	8.68	0.80	-53.36	-13.00	40.36
1648.400	V	42.15	-62.38	8.68	0.80	-54.50	-13.00	41.50
2472.600	H	37.25	-63.78	9.38	1.00	-55.40	-13.00	42.40
2472.600	V	35.32	-65.66	9.38	1.00	-57.28	-13.00	44.28
3296.800	H	34.33	-63.05	10.32	1.15	-53.88	-13.00	40.88
3296.800	V	34.16	-62.98	10.32	1.15	-53.81	-13.00	40.81
Frequency: 836.6 MHz								
1673.200	H	42.45	-61.97	8.71	0.85	-54.11	-13.00	41.11
1673.200	V	43.58	-60.95	8.71	0.85	-53.09	-13.00	40.09
2509.800	H	37.12	-63.71	9.42	1.01	-55.30	-13.00	42.30
2509.800	V	36.97	-63.87	9.42	1.01	-55.46	-13.00	42.46
3346.400	H	34.28	-63.78	10.34	1.16	-54.60	-13.00	41.60
3346.400	V	33.64	-64.28	10.34	1.16	-55.10	-13.00	42.10
Frequency: 848.8 MHz								
1697.600	H	43.15	-61.24	8.74	0.90	-53.40	-13.00	40.40
1697.600	V	43.29	-61.23	8.74	0.90	-53.39	-13.00	40.39
2546.400	H	37.64	-62.97	9.47	1.01	-54.51	-13.00	41.51
2546.400	V	38.12	-62.44	9.47	1.01	-53.98	-13.00	40.98
3395.200	H	33.64	-65.15	10.36	1.19	-55.98	-13.00	42.98
3395.200	V	34.71	-64.05	10.36	1.19	-54.88	-13.00	41.88

WCDMA Band 5(1-10GHz):

WCDMA Band 5 (1-10GHz)								
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:			826.4	MHz				
1652.800	H	52.64	-51.81	8.68	0.81	-43.94	-13.00	30.94
1652.800	V	56.75	-47.78	8.68	0.81	-39.91	-13.00	26.91
2479.200	H	38.97	-62.03	9.39	1.01	-53.65	-13.00	40.65
2479.200	V	39.58	-61.39	9.39	1.01	-53.01	-13.00	40.01
3305.600	H	37.84	-59.61	10.32	1.15	-50.44	-13.00	37.44
3305.600	V	40.12	-57.11	10.32	1.15	-47.94	-13.00	34.94
Frequency:			836.6	MHz				
1673.200	H	53.64	-50.78	8.71	0.85	-42.92	-13.00	29.92
1673.200	V	55.79	-48.74	8.71	0.85	-40.88	-13.00	27.88
2509.800	H	39.44	-61.39	9.42	1.01	-52.98	-13.00	39.98
2509.800	V	40.17	-60.67	9.42	1.01	-52.26	-13.00	39.26
3346.400	H	37.52	-60.54	10.34	1.16	-51.36	-13.00	38.36
3346.400	V	38.64	-59.28	10.34	1.16	-50.10	-13.00	37.10
Frequency:			846.6	MHz				
1693.200	H	55.16	-49.24	8.73	0.89	-41.40	-13.00	28.40
1693.200	V	56.94	-47.58	8.73	0.89	-39.74	-13.00	26.74
2539.800	H	38.99	-61.66	9.46	1.01	-53.21	-13.00	40.21
2539.800	V	41.07	-59.54	9.46	1.01	-51.09	-13.00	38.09
3386.400	H	37.95	-60.71	10.35	1.18	-51.54	-13.00	38.54
3386.400	V	40.08	-58.53	10.35	1.18	-49.36	-13.00	36.36

LTE Band 5(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 824.7 MHz								
1649.400	H	38.63	-65.82	8.68	0.80	-57.94	-13.00	44.94
1649.400	V	39.12	-65.41	8.68	0.80	-57.53	-13.00	44.53
2474.100	H	34.55	-66.47	9.38	1.00	-58.09	-13.00	45.09
2474.100	V	33.37	-67.61	9.38	1.00	-59.23	-13.00	46.23
3298.800	H	33.81	-63.56	10.32	1.15	-54.39	-13.00	41.39
3298.800	V	34.21	-62.92	10.32	1.15	-53.75	-13.00	40.75
1.4MHz QPSK, Frequency: 836.5 MHz								
1673.000	H	36.23	-68.19	8.71	0.85	-60.33	-13.00	47.33
1673.000	V	40.15	-64.38	8.71	0.85	-56.52	-13.00	43.52
2509.500	H	33.65	-67.18	9.42	1.01	-58.77	-13.00	45.77
2509.500	V	34.07	-66.78	9.42	1.01	-58.37	-13.00	45.37
3346.000	H	34.89	-63.17	10.34	1.16	-53.99	-13.00	40.99
3346.000	V	33.68	-64.24	10.34	1.16	-55.06	-13.00	42.06
1.4MHz QPSK, Frequency: 848.3 MHz								
1696.600	H	38.01	-66.38	8.74	0.89	-58.53	-13.00	45.53
1696.600	V	36.94	-67.58	8.74	0.89	-59.73	-13.00	46.73
2544.900	H	34.36	-66.26	9.47	1.01	-57.80	-13.00	44.80
2544.900	V	33.95	-66.62	9.47	1.01	-58.16	-13.00	45.16
3393.200	H	33.74	-65.02	10.36	1.19	-55.85	-13.00	42.85
3393.200	V	34.01	-64.71	10.36	1.19	-55.54	-13.00	42.54

LTE Band 12(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 699.7 MHz								
1399.400	H	33.85	-69.95	8.22	0.71	-62.44	-13.00	49.44
1399.400	V	34.35	-69.49	8.22	0.71	-61.98	-13.00	48.98
2099.100	H	34.78	-67.08	9.16	0.91	-58.83	-13.00	45.83
2099.100	V	33.61	-68.20	9.16	0.91	-59.95	-13.00	46.95
2798.800	H	33.99	-66.53	9.88	1.04	-57.69	-13.00	44.69
2798.800	V	34.28	-66.11	9.88	1.04	-57.27	-13.00	44.27
1.4MHz QPSK, Frequency: 707.5 MHz								
1415.000	H	34.55	-69.20	8.26	0.72	-61.66	-13.00	48.66
1415.000	V	36.01	-67.79	8.26	0.72	-60.25	-13.00	47.25
2122.500	H	34.24	-67.78	9.17	0.92	-59.53	-13.00	46.53
2122.500	V	33.89	-68.11	9.17	0.92	-59.86	-13.00	46.86
2830.000	H	33.66	-66.79	9.93	1.06	-57.92	-13.00	44.92
2830.000	V	34.17	-66.22	9.93	1.06	-57.35	-13.00	44.35
1.4MHz QPSK, Frequency: 715.3 MHz								
1430.600	H	35.01	-68.67	8.31	0.73	-61.09	-13.00	48.09
1430.600	V	34.24	-69.50	8.31	0.73	-61.92	-13.00	48.92
2145.900	H	34.51	-67.68	9.19	0.93	-59.42	-13.00	46.42
2145.900	V	33.37	-68.83	9.19	0.93	-60.57	-13.00	47.57
2861.200	H	33.98	-66.39	9.98	1.07	-57.48	-13.00	44.48
2861.200	V	34.27	-66.11	9.98	1.07	-57.20	-13.00	44.20

LTE Band 13(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 779.5 MHz								
1559.000	H	31.25	-72.80	8.57	0.80	-65.03	-40.00	25.03
1559.000	V	32.30	-71.81	8.57	0.80	-64.04	-40.00	24.04
2338.500	H	32.68	-69.19	9.30	0.97	-60.86	-13.00	47.86
2338.500	V	31.61	-70.03	9.30	0.97	-61.70	-13.00	48.70
3118.000	H	32.37	-65.62	10.25	1.13	-56.50	-13.00	43.50
3118.000	V	31.19	-66.65	10.25	1.13	-57.53	-13.00	44.53
5MHz QPSK, Frequency: 784.5 MHz								
1569.000	H	33.25	-70.92	8.58	0.81	-63.15	-40.00	23.15
1569.000	V	33.74	-70.48	8.58	0.81	-62.71	-40.00	22.71
2353.500	H	33.06	-68.70	9.31	0.97	-60.36	-13.00	47.36
2353.500	V	33.84	-67.68	9.31	0.97	-59.34	-13.00	46.34
3138.000	H	31.84	-66.09	10.26	1.14	-56.97	-13.00	43.97
3138.000	V	33.25	-64.51	10.26	1.14	-55.39	-13.00	42.39

LTE Band 17(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 706.5 MHz								
1413.000	H	33.56	-70.20	8.26	0.72	-62.66	-13.00	49.66
1413.000	V	34.01	-69.79	8.26	0.72	-62.25	-13.00	49.25
2119.500	H	34.87	-67.13	9.17	0.92	-58.88	-13.00	45.88
2119.500	V	33.62	-68.36	9.17	0.92	-60.11	-13.00	47.11
2826.000	H	33.88	-66.58	9.92	1.06	-57.72	-13.00	44.72
2826.000	V	34.58	-65.81	9.92	1.06	-56.95	-13.00	43.95
5MHz QPSK, Frequency: 710 MHz								
1420.000	H	34.10	-69.63	8.28	0.73	-62.08	-13.00	49.08
1420.000	V	33.62	-70.16	8.28	0.73	-62.61	-13.00	49.61
2130.000	H	33.98	-68.09	9.18	0.92	-59.83	-13.00	46.83
2130.000	V	34.28	-67.79	9.18	0.92	-59.53	-13.00	46.53
2840.000	H	33.79	-66.63	9.94	1.06	-57.75	-13.00	44.75
2840.000	V	33.66	-66.73	9.94	1.06	-57.85	-13.00	44.85
5MHz QPSK, Frequency: 713.5 MHz								
1427.000	H	33.66	-70.04	8.30	0.73	-62.47	-13.00	49.47
1427.000	V	33.41	-70.35	8.30	0.73	-62.78	-13.00	49.78
2140.500	H	34.25	-67.90	9.18	0.93	-59.65	-13.00	46.65
2140.500	V	35.02	-67.13	9.18	0.93	-58.88	-13.00	45.88
2854.000	H	34.19	-66.20	9.97	1.07	-57.30	-13.00	44.30
2854.000	V	33.67	-66.71	9.97	1.07	-57.81	-13.00	44.81

ANT5**GSM1900(1-20GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1850.2 MHz								
3700.400	H	39.64	-59.34	10.60	1.25	-49.99	-13.00	36.99
3700.400	V	38.52	-60.44	10.60	1.25	-51.09	-13.00	38.09
5550.600	H	35.47	-60.70	11.44	1.49	-50.75	-13.00	37.75
5550.600	V	36.25	-59.75	11.44	1.49	-49.80	-13.00	36.80
Frequency: 1880 MHz								
3760.000	H	38.24	-59.46	10.66	1.24	-50.04	-13.00	37.04
3760.000	V	40.15	-57.43	10.66	1.24	-48.01	-13.00	35.01
5640.000	H	36.49	-60.31	11.33	1.54	-50.52	-13.00	37.52
5640.000	V	35.88	-60.80	11.33	1.54	-51.01	-13.00	38.01
Frequency: 1909.8 MHz								
3819.600	H	39.25	-57.74	10.72	1.29	-48.31	-13.00	35.31
3819.600	V	40.51	-56.33	10.72	1.29	-46.90	-13.00	33.90
5729.400	H	36.32	-60.82	11.22	1.59	-51.19	-13.00	38.19
5729.400	V	37.02	-59.99	11.22	1.59	-50.36	-13.00	37.36

WCDMA Band 2(1-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1852.4 MHz								
3704.800	H	36.79	-62.10	10.60	1.25	-52.75	-13.00	39.75
3704.800	V	38.02	-60.84	10.60	1.25	-51.49	-13.00	38.49
5557.200	H	34.13	-62.09	11.43	1.49	-52.15	-13.00	39.15
5557.200	V	33.96	-62.11	11.43	1.49	-52.17	-13.00	39.17
Frequency: 1880 MHz								
3760.000	H	35.89	-61.81	10.66	1.24	-52.39	-13.00	39.39
3760.000	V	36.73	-60.85	10.66	1.24	-51.43	-13.00	38.43
5640.000	H	33.47	-63.33	11.33	1.54	-53.54	-13.00	40.54
5640.000	V	34.15	-62.53	11.33	1.54	-52.74	-13.00	39.74
Frequency: 1907.6 MHz								
3815.200	H	37.69	-59.26	10.72	1.29	-49.83	-13.00	36.83
3815.200	V	37.48	-59.32	10.72	1.29	-49.89	-13.00	36.89
5722.800	H	33.38	-63.75	11.23	1.58	-54.10	-13.00	41.10
5722.800	V	34.47	-62.53	11.23	1.58	-52.88	-13.00	39.88

WCDMA Band 4(1-18GHz):

Substituted Method								
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency: 1712.4 MHz								
3424.800	H	36.87	-62.05	10.37	1.17	-52.85	-13.00	39.85
3424.800	V	37.64	-61.25	10.37	1.17	-52.05	-13.00	39.05
5137.200	H	33.49	-62.71	11.28	1.46	-52.89	-13.00	39.89
5137.200	V	34.02	-62.07	11.28	1.46	-52.25	-13.00	39.25
Frequency: 1732.6 MHz								
3465.200	H	36.99	-62.03	10.39	1.15	-52.79	-13.00	39.79
3465.200	V	37.48	-61.49	10.39	1.15	-52.25	-13.00	39.25
5197.800	H	33.45	-63.50	11.32	1.44	-53.62	-13.00	40.62
5197.800	V	33.75	-63.05	11.32	1.44	-53.17	-13.00	40.17
Frequency: 1752.6 MHz								
3505.200	H	36.13	-62.93	10.41	1.18	-53.70	-13.00	40.70
3505.200	V	37.26	-61.74	10.41	1.18	-52.51	-13.00	39.51
5257.800	H	34.01	-62.79	11.35	1.47	-52.91	-13.00	39.91
5257.800	V	34.72	-61.86	11.35	1.47	-51.98	-13.00	38.98

LTE Bands:

(The Worst modulation and bandwidth(1RB) was below)

LTE Band 2(1-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1850.7 MHz								
3701.400	H	36.54	-62.42	10.60	1.25	-53.07	-13.00	40.07
3701.400	V	39.74	-59.20	10.60	1.25	-49.85	-13.00	36.85
5552.100	H	34.58	-61.60	11.44	1.49	-51.65	-13.00	38.65
5552.100	V	34.76	-61.26	11.44	1.49	-51.31	-13.00	38.31
1.4MHz QPSK, Frequency: 1880 MHz								
3760.000	H	37.49	-60.21	10.66	1.24	-50.79	-13.00	37.79
3760.000	V	40.35	-57.23	10.66	1.24	-47.81	-13.00	34.81
5640.000	H	34.77	-62.03	11.33	1.54	-52.24	-13.00	39.24
5640.000	V	33.96	-62.72	11.33	1.54	-52.93	-13.00	39.93
1.4MHz QPSK, Frequency: 1909.3 MHz								
3818.600	H	37.42	-59.56	10.72	1.29	-50.13	-13.00	37.13
3818.600	V	38.89	-57.94	10.72	1.29	-48.51	-13.00	35.51
5727.900	H	33.85	-63.28	11.23	1.59	-53.64	-13.00	40.64
5727.900	V	34.17	-62.83	11.23	1.59	-53.19	-13.00	40.19

LTE Band 4(1-18GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
3421.400	H	36.45	-62.46	10.37	1.17	-53.26	-13.00	40.26
3421.400	V	37.15	-61.73	10.37	1.17	-52.53	-13.00	39.53
5132.100	H	34.23	-61.91	11.28	1.47	-52.10	-13.00	39.10
5132.100	V	34.58	-61.45	11.28	1.47	-51.64	-13.00	38.64
1.4MHz QPSK, Frequency: 1732.5 MHz								
3465.000	H	36.97	-62.05	10.39	1.15	-52.81	-13.00	39.81
3465.000	V	38.52	-60.45	10.39	1.15	-51.21	-13.00	38.21
5197.500	H	34.41	-62.54	11.32	1.44	-52.66	-13.00	39.66
5197.500	V	34.08	-62.72	11.32	1.44	-52.84	-13.00	39.84
1.4MHz QPSK, Frequency: 1754.3 MHz								
3508.600	H	37.88	-61.16	10.41	1.19	-51.94	-13.00	38.94
3508.600	V	39.03	-59.94	10.41	1.19	-50.72	-13.00	37.72
5262.900	H	33.87	-62.92	11.36	1.47	-53.03	-13.00	40.03
5262.900	V	34.19	-62.37	11.36	1.47	-52.48	-13.00	39.48

LTE Band 7(1-26GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2502.5 MHz								
5005.000	H	35.87	-59.60	11.20	1.47	-49.87	-25.00	24.87
5005.000	V	34.89	-60.45	11.20	1.47	-50.72	-25.00	25.72
7507.500	H	33.97	-60.10	10.90	1.95	-51.15	-25.00	26.15
7507.500	V	33.47	-61.10	10.90	1.95	-52.15	-25.00	27.15
5MHz QPSK, Frequency: 2535 MHz								
5070.000	H	35.38	-60.28	11.24	1.47	-50.51	-25.00	25.51
5070.000	V	36.27	-59.28	11.24	1.47	-49.51	-25.00	24.51
7605.000	H	34.11	-59.37	10.88	2.01	-50.50	-25.00	25.50
7605.000	V	33.89	-60.30	10.88	2.01	-51.43	-25.00	26.43
5MHz QPSK, Frequency: 2567.5 MHz								
5135.000	H	34.73	-61.44	11.28	1.47	-51.63	-25.00	26.63
5135.000	V	36.33	-59.73	11.28	1.47	-49.92	-25.00	24.92
7702.500	H	34.02	-59.20	10.86	1.97	-50.31	-25.00	25.31
7702.500	V	34.17	-59.71	10.86	1.97	-50.82	-25.00	25.82

LTE Band 38(1-26.5GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2572.5 MHz								
5145.000	H	35.49	-60.81	11.29	1.44	-50.96	-25.00	25.96
5145.000	V	34.82	-61.36	11.29	1.44	-51.51	-25.00	26.51
7717.500	H	36.47	-56.78	10.86	1.99	-47.91	-25.00	22.91
7717.500	V	34.79	-59.08	10.86	1.99	-50.21	-25.00	25.21
5MHz QPSK, Frequency: 2595 MHz								
5190.000	H	36.77	-60.09	11.31	1.44	-50.22	-25.00	25.22
5190.000	V	37.84	-58.87	11.31	1.44	-49.00	-25.00	24.00
7785.000	H	34.59	-58.80	10.84	1.99	-49.95	-25.00	24.95
7785.000	V	32.58	-61.24	10.84	1.99	-52.39	-25.00	27.39
5MHz QPSK, Frequency: 2617.5 MHz								
5235.000	H	37.01	-59.86	11.34	1.46	-49.98	-25.00	24.98
5235.000	V	38.15	-58.53	11.34	1.46	-48.65	-25.00	23.65
7852.500	H	34.44	-59.04	10.83	2.03	-50.24	-25.00	25.24
7852.500	V	33.97	-59.90	10.83	2.03	-51.10	-25.00	26.10

LTE Band 41(1-27GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2498.5 MHz								
4997.000	H	35.41	-60.04	11.20	1.48	-50.32	-25.00	25.32
4997.000	V	36.29	-59.02	11.20	1.48	-49.30	-25.00	24.30
7495.500	H	34.06	-60.04	10.90	1.94	-51.08	-25.00	26.08
7495.500	V	33.89	-60.71	10.90	1.94	-51.75	-25.00	26.75
5MHz QPSK, Frequency: 2593 MHz								
5186.000	H	37.96	-58.85	11.31	1.44	-48.98	-25.00	23.98
5186.000	V	36.88	-59.78	11.31	1.44	-49.91	-25.00	24.91
7779.000	H	33.62	-59.76	10.84	1.99	-50.91	-25.00	25.91
7779.000	V	34.28	-59.54	10.84	1.99	-50.69	-25.00	25.69
5MHz QPSK, Frequency: 2687.5 MHz								
5375.000	H	36.96	-59.55	11.43	1.49	-49.61	-25.00	24.61
5375.000	V	37.81	-58.69	11.43	1.49	-48.75	-25.00	23.75
8062.500	H	33.64	-59.30	10.81	2.12	-50.61	-25.00	25.61
8062.500	V	34.58	-58.86	10.81	2.12	-50.17	-25.00	25.17

LTE Band 66(1-18GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
3421.400	H	34.75	-64.16	10.37	1.17	-54.96	-13.00	41.96
3421.400	V	35.12	-63.76	10.37	1.17	-54.56	-13.00	41.56
5132.100	H	33.52	-62.62	11.28	1.47	-52.81	-13.00	39.81
5132.100	V	33.96	-62.07	11.28	1.47	-52.26	-13.00	39.26
1.4MHz QPSK, Frequency: 1745 MHz								
3490.000	H	35.14	-63.94	10.40	1.17	-54.71	-13.00	41.71
3490.000	V	35.75	-63.27	10.40	1.17	-54.04	-13.00	41.04
5235.000	H	33.47	-63.40	11.34	1.46	-53.52	-13.00	40.52
5235.000	V	34.71	-61.97	11.34	1.46	-52.09	-13.00	39.09
1.4MHz QPSK, Frequency: 1779.3 MHz								
3558.600	H	34.96	-63.72	10.46	1.22	-54.48	-13.00	41.48
3558.600	V	35.32	-63.25	10.46	1.22	-54.01	-13.00	41.01
5337.900	H	33.62	-62.97	11.40	1.47	-53.04	-13.00	40.04
5337.900	V	34.08	-62.37	11.40	1.47	-52.44	-13.00	39.44

ANT0**LTE Band 42(1-36GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 3452.5 MHz								
6905.000	H	35.34	-60.74	11.22	1.87	-51.39	-13.00	38.39
6905.000	V	34.68	-61.27	11.22	1.87	-51.92	-13.00	38.92
10357.500	H	33.47	-58.83	11.49	2.49	-49.83	-13.00	36.83
10357.500	V	34.03	-58.38	11.49	2.49	-49.38	-13.00	36.38
5MHz QPSK, Frequency: 3500 MHz								
7000.000	H	34.99	-60.11	11.20	1.89	-50.80	-13.00	37.80
7000.000	V	35.37	-59.58	11.20	1.89	-50.27	-13.00	37.27
10500.000	H	33.34	-58.26	11.40	2.52	-49.38	-13.00	36.38
10500.000	V	34.03	-57.66	11.40	2.52	-48.78	-13.00	35.78
5MHz QPSK, Frequency: 3547.5 MHz								
7095.000	H	35.73	-57.61	11.14	1.89	-48.36	-13.00	35.36
7095.000	V	36.85	-56.42	11.14	1.89	-47.17	-13.00	34.17
10642.500	H	33.66	-57.90	11.40	2.50	-49.00	-13.00	36.00
10642.500	V	34.28	-57.42	11.40	2.50	-48.52	-13.00	35.52

ANT6**LTE Band 42(1-36GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 3452.5 MHz								
6905.000	H	35.76	-60.32	11.22	1.87	-50.97	-13.00	37.97
6905.000	V	36.31	-59.64	11.22	1.87	-50.29	-13.00	37.29
10357.500	H	34.12	-58.18	11.49	2.49	-49.18	-13.00	36.18
10357.500	V	33.27	-59.14	11.49	2.49	-50.14	-13.00	37.14
5MHz QPSK, Frequency: 3500 MHz								
7000.000	H	36.47	-58.63	11.20	1.89	-49.32	-13.00	36.32
7000.000	V	35.82	-59.13	11.20	1.89	-49.82	-13.00	36.82
10500.000	H	33.32	-58.28	11.40	2.52	-49.40	-13.00	36.40
10500.000	V	33.79	-57.90	11.40	2.52	-49.02	-13.00	36.02
5MHz QPSK, Frequency: 3547.5 MHz								
7095.000	H	35.54	-57.80	11.14	1.89	-48.55	-13.00	35.55
7095.000	V	36.12	-57.15	11.14	1.89	-47.90	-13.00	34.90
10642.500	H	34.26	-57.30	11.40	2.50	-48.40	-13.00	35.40
10642.500	V	34.59	-57.11	11.40	2.50	-48.21	-13.00	35.21

ANT8**LTE Band 42(1-36GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 3452.5 MHz								
6905.000	H	36.37	-59.71	11.22	1.87	-50.36	-13.00	37.36
6905.000	V	35.82	-60.13	11.22	1.87	-50.78	-13.00	37.78
10357.500	H	33.79	-58.51	11.49	2.49	-49.51	-13.00	36.51
10357.500	V	34.09	-58.32	11.49	2.49	-49.32	-13.00	36.32
5MHz QPSK, Frequency: 3500 MHz								
7000.000	H	35.79	-59.31	11.20	1.89	-50.00	-13.00	37.00
7000.000	V	36.13	-58.82	11.20	1.89	-49.51	-13.00	36.51
10500.000	H	33.52	-58.08	11.40	2.52	-49.20	-13.00	36.20
10500.000	V	34.01	-57.68	11.40	2.52	-48.80	-13.00	35.80
5MHz QPSK, Frequency: 3547.5 MHz								
7095.000	H	35.29	-58.05	11.14	1.89	-48.80	-13.00	35.80
7095.000	V	36.37	-56.90	11.14	1.89	-47.65	-13.00	34.65
10642.500	H	34.52	-57.04	11.40	2.50	-48.14	-13.00	35.14
10642.500	V	33.64	-58.06	11.40	2.50	-49.16	-13.00	36.16

ANT9**LTE Band 42(1-36GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 3452.5 MHz								
6905.000	H	36.49	-59.59	11.22	1.87	-50.24	-13.00	37.24
6905.000	V	37.53	-58.42	11.22	1.87	-49.07	-13.00	36.07
10357.500	H	34.16	-58.14	11.49	2.49	-49.14	-13.00	36.14
10357.500	V	33.73	-58.68	11.49	2.49	-49.68	-13.00	36.68
5MHz QPSK, Frequency: 3500 MHz								
7000.000	H	37.01	-58.09	11.20	1.89	-48.78	-13.00	35.78
7000.000	V	36.54	-58.41	11.20	1.89	-49.10	-13.00	36.10
10500.000	H	33.38	-58.22	11.40	2.52	-49.34	-13.00	36.34
10500.000	V	34.29	-57.40	11.40	2.52	-48.52	-13.00	35.52
5MHz QPSK, Frequency: 3547.5 MHz								
7095.000	H	35.97	-57.37	11.14	1.89	-48.12	-13.00	35.12
7095.000	V	36.44	-56.83	11.14	1.89	-47.58	-13.00	34.58
10642.500	H	33.93	-57.63	11.40	2.50	-48.73	-13.00	35.73
10642.500	V	33.71	-57.99	11.40	2.50	-49.09	-13.00	36.09

Note 1: The unit of antenna gain is dBd for frequency below 1GHz and is dBi for frequency above 1GHz.

Note 2: Absolute Level = Substituted Level - Cable Loss+ Antenna Gain

Margin = Limit - Absolute Level

5. EUT PHOTOGRAPHS

Please refer to the attachment 2503P28739E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2503P28739E-RF-INP EUT INTERNAL PHOTOGRAPHS

6. TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2503P28739E-RF-00E-TSP TEST SETUP PHOTOGRAPHS.

==== END OF REPORT =====