

SAR Compliance Test Report

Date of Report	1/07/2020	Client's Contact person:	Juha Pikkarainen
Number of pages:	4	Responsible Test engineer:	Kirsi Kyllönen
Testing laboratory:	Verkotan Oy Elektroniikkatie 17 90590 Oulu Finland	Client:	Haltian Products Oy Yrttipellontie 1D 90230 Oulu Finland
Tested devices	Thingsee Beam		
Related reports:	-		
Testing has been carried out in accordance with:	47CFR §2.1091 Radiofrequency Radiation Exposure Evaluation: Mobile Devices FCC published RF exposure KDB procedures		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory		
Test Results:	The DUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		

Date and signatures: 01.07.2020

For the contents:

Laboratory Manager

TABLE OF CONTENTS

1. SUMMARY OF SAR TEST REPORT	4
1.1 TEST DETAILS.....	4
1.2 EVALUATION RESULTS	4
2. DESCRIPTION OF THE DEVICE UNDER TEST (DUT)	4
2.1 SUPPORTED FREQUENCY BANDS AND OPERATIONAL MODES	4
2.2 TEST EXCLUSIONS	5
3. OUTPUT POWER	5
3.1 MAXIMUM DEFINED OUTPUT POWER.....	5
4. RESULTS.....	5

1. SUMMARY OF SAR TEST REPORT

1.1 Test Details

Device under Test (DUT):

Product:	Jones sensor
Manufacturer:	Haltian Products Oy
Model:	TSD2
Hardware Version:	TSD2_02
FCC ID:	2AEU3TSBEAM
Document ID:	FCC SAR test report_Thingsee Beam_ID4267_01072020.docx

1.2 Evaluation Results

The device conforms to the requirements of the standards when the maximum output power is less than or equal to the Test Exclusion Threshold Limit.

Regulator	System	Equipment Class	Test Exclusion Threshold/ Exemption Limit [mW]	Maximum Output Power [mW]	Result
FCC	BLE	DTS	10	2.5	PASS

2. DESCRIPTION OF THE DEVICE UNDER TEST (DUT)

The DUT is a general-purpose sensor device.

The device is typically used with 20 cm or larger separation distance of the user. As device is Bluetooth low energy device thus having low output power, the evaluation is done at 5mm separation.

Exposure Environment	General population, uncontrolled
-----------------------------	----------------------------------

2.1 Supported Frequency Bands and Operational Modes

Bands	Modes of Operation	Transmitter Frequency Range (MHz)
2.4	Bluetooth low energy	2.402- 2.480

2.2 Test Exclusions

FCC SAR test exclusion thresholds in 447498D01 are shown in a table below.

Appendix A

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

3. OUTPUT POWER

3.1 Maximum defined Output Power

Transmission mode	Output power [dBm]	Output power [mW]
BLE	4.0	2.5

4. RESULTS

According Appendix A in 447498D01 the SAR test exclusion power threshold for 2450MHz is 10mW at 5mm separation distance.

The maximum output power of the DUT is 2.51mW thus it is below the test exclusion threshold.