

FCC Part 1 Subpart I
FCC Part 2 Subpart J
RSS 102 ISSUE 5

RF EXPOSURE EXEMPTION REPORT

FOR

Indoor Lighting Control

MODEL NUMBER: SNS412 MC & SNS212 MC

**FCC ID: 2AF2N-SSM2
IC: 20659-SSM2**

REPORT NUMBER: NBK14480730B.V1

ISSUE DATE: 2023-02-01

Prepared for
Signify North America Corporation
O'Hare International Center
10275 W. Higgins Rd
Rosemont, IL 60018

Prepared by
UL LLC
333 Pfingsten Road
Northbrook, IL 60062 U.S.A.
TEL: (847) 272-8800



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
<u>V1</u>	<u></u>	<u>Initial Issue</u>	<u></u>

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. REFERENCES	5
4. FACILITIES AND ACCREDITATION	5
5. DECISION RULES AND MEASUREMENT UNCERTAINTY	6
5.1. <i>METROLOGICAL TRACEABILITY</i>	<i>6</i>
5.2. <i>DECISION RULES.....</i>	<i>6</i>
5.3. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>6</i>
6. MAXIMUM PERMISSIBLE EXPOSURE (LIMITS AND EQUATIONS)	7
6.1. <i>FCC RULES</i>	<i>7</i>
6.2. <i>ISED RULES</i>	<i>8</i>
6.3. <i>EQUATIONS.....</i>	<i>9</i>
7. RF EXPOSURE RESULTS.....	10

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: Signify North America Corporation
O'Hare International Center
10275 W. Higgins Rd
Rosemont, IL 60018

EUT DESCRIPTION: Indoor Lighting Control

MODEL: SNS412 MC & SNS212 MC

SERIAL NUMBER: see report NBK14480730A.V1, section 2 for information on samples tested

SAMPLE RECEIPT DATE: 2022-09-15

DATE TESTED: 2022-09-15 TO 2022-12-20

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Complies
RSS 102 ISSUE 5	Complies

UL LLC. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL LLC. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC. will constitute fraud and shall nullify the document.

Approved & Released For
UL LLC. By:

Prepared By:



Mike Antola
Staff Engineer
CONSUMER TECHNOLOGY DIVISION
UL LLC.

Bart Mucha
Test Engineer
CONSUMER TECHNOLOGY DIVISION
UL LLC.

2. TEST METHODOLOGY

All calculations/exemptions were made in accordance with FCC Parts 1.1310, 2.1091, 2.1093, KDB 447498 D01 v06, KDB 447498 D03 V01, IEEE Std C95.1-2005, IEEE Std C95.3-2002, IC Safety Code 6 and RSS 102 Issue 5.

3. REFERENCES

All measurements were made as documented in test report UL LLC Document NBK14480730A.V1 for operation in the 2.4 GHz band.

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports.

4. FACILITIES AND ACCREDITATION

UL LLC is accredited by A2LA, Certificate Number 0751.07, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address
<input checked="" type="checkbox"/>	Building: 333 Pfingsten Road Northbrook, IL 60062

5. DECISION RULES AND MEASUREMENT UNCERTAINTY

5.1. METROLOGICAL TRACEABILITY

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

5.2. DECISION RULES

For all tests where the applicable $U_{LAB} \leq U_{MAX}$ the Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2, where $U_{MAX} = 30\%$ (0.3) for RF Exposure evaluations. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

For all tests where the applicable $U_{LAB} > U_{MAX}$ the Decision Rule is based on Guarded Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.3.2, with a guard band equal to $(U_{LAB} - U_{MAX})$, where $U_{MAX} = 30\%$ (0.3) for RF Exposure evaluations. (Test results are adjusted by the value of the guard band to determine conformity with a specified requirement.)

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U_{Lab}	U_{MAX}
Spectrum Analyzer Peak Power Measurement	1.94dB	-

Uncertainty figures are valid to a confidence level of 95%.

6. MAXIMUM PERMISSIBLE EXPOSURE (LIMITS AND EQUATIONS)

6.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Notes:

- (1) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
- (2) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure

6.2. ISED RULES

For the purpose of this standard, Innovation, Science and Economic Development (ISED) has adopted the SAR and RF field strength limits established in Health Canada’s RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ <i>f</i> ^{0.5}	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	58.07/ <i>f</i> ^{0.25}	0.1540/ <i>f</i> ^{0.25}	8.944/ <i>f</i> ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 <i>f</i> ^{0.3417}	0.008335 <i>f</i> ^{0.3417}	0.02619 <i>f</i> ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> ^{1.2}
150000-300000	0.158 <i>f</i> ^{0.5}	4.21 x 10 ⁻⁴ <i>f</i> ^{0.5}	6.67 x 10 ⁻⁵ <i>f</i>	616000/ <i>f</i> ^{1.2}

Note: *f* is frequency in MHz.

* Based on nerve stimulation (NS).

** Based on specific absorption rate (SAR).

6.3. EQUATIONS

POWER DENSITY

Power density is given by:

$$S = \text{EIRP} / (4 * \text{Pi} * \text{D}^2)$$

Where

S = Power density in mW/cm²

EIRP = Equivalent Isotropic Radiated Power in mW

D = Separation distance in cm

Power density in units of mW/cm² is converted to units of W/m² by multiplying by 10.

DISTANCE

Distance is given by:

$$D = \text{SQRT} (\text{EIRP} / (4 * \text{Pi} * S))$$

Where

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power in mW

S = Power density in mW/cm²

SOURCE-BASED DUTY CYCLE

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

$$\text{Source-based time-averaged EIRP} = (\text{DC} / 100) * \text{EIRP}$$

Where

DC = Duty Cycle in %, as applicable

EIRP = Equivalent Isotropic Radiated Power in mW

7. RF EXPOSURE RESULTS

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

This report contains data provided by the applicant which can impact the validity of results. UL LLC is only responsible for the validity of results after the integration of the data provided by the customer. This pertains only to antenna gain.

(Single chain transmitters, no colocation, 20 cm MPE distance)

Single Chain and non-colocated transmitters											
Band	Mode	Separ. Distance (cm)	Output Peak Power (dBm)	Ant. Gain (dBi)	EIRP (dBm)	Duty Cycle (%)	EIRP (mW)	FCC PD (mW/cm ²)	ISED PD (W/m ²)	FCC PD Limit (mW/cm ²)	ISED PD Limit (W/m ²)
*2.4 GHz	Bluetooth	20	5.94	-2.00	3.94	100.0	2.48	0.0005	0.0049	1.00	5.46
*2.4 GHz	ZigBee	20	5.98	-2.00	3.98	100.0	2.50	0.0005	0.0050	1.00	5.46
**2.4 GHz	BT/ZigBee	20	6	-2	4.00	100	2.51	0.0005	0.0050	1.00	5.46

* maximum peak power measured during testing

** maximum power as declared in operational description with +/-2dB tolerance.

END OF TEST REPORT