



FCC RADIO TEST REPORT

FCC ID : 2AF3K-SPD3
Equipment : Square Handheld
Brand Name : Square
Model Name : SPD3-01
Applicant : Block, Inc.
1955 Broadway, Suite 600 Oakland, CA 94612 United States
Manufacturer : Block, Inc.
1955 Broadway, Suite 600 Oakland, CA 94612 United States
Standard : FCC Part 15 Subpart E §15.407

The product was received on Dec. 04, 2024 and testing was performed from Dec. 20, 2024 to Mar. 06, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	7
1.3 Testing Location	7
1.4 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 Test Result	12
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	12
3.2 Maximum Conducted Output Power Measurement	13
3.3 Power Spectral Density Measurement	14
3.4 Unwanted Emissions Measurement.....	16
3.5 AC Conducted Emission Measurement.....	21
3.6 Antenna Requirements.....	23
4 List of Measuring Equipment.....	24
5 Measurement Uncertainty	26
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Data	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR4N2203F	01	Initial issue of report	Mar. 27, 2025
FR4N2203F	02	Revise section 2.2 This report is an updated version, replacing the report issued on Mar. 27, 2025.	Mar. 31, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	Pass	-
3.3	15.407(a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	-
3.5	15.207	AC Conducted Emission	Pass	-
3.6	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng

Report Producer: Clio Lo



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
General Specs Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, Wi-Fi 6GHz 802.11a/ax and NFC.		
Antenna Type WLAN: <Ant. 1>: PIFA Antenna <Ant. 2>: PIFA Antenna		
Antenna information		
5725 MHz ~ 5850 MHz	Peak Gain (dBi)	Ant. 1: 3.3 Ant. 2: 2.9

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.1.1 Antenna Directional Gain

<For CDD Mode>

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F2)f)ii)

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows:

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements, the directional gain calculation.

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

As minimum $N_{SS}=1$ is supported by EUT, the formula can be simplified as:

Directional gain = $10 \cdot \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi

Where $G_1, G_2, \dots, G_N$ denote single antenna gain.

The directional gain "DG" is calculated as following table.

			DG for Power	DG for PSD	Power Limit Reduction	PSD Limit Reduction
	Ant 1 (dBi)	Ant 2 (dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	3.30	2.90	3.30	6.11	0.00	0.11

Calculation example:

If a device has two antenna, $G_{ANT1} = 3.3\text{dBi}$; $G_{ANT2} = 2.9\text{dBi}$

Directional gain of power measurement = $\max(3.3, 2.9) + 0 = 3.3$ dBi

Directional gain of PSD derived from formula which is

$$10 \times \log \left\{ \left[10^{(3.30 \text{ dBi} / 20)} + 10^{(2.90 \text{ dBi} / 20)} \right]^2 / 2 \right\} \\ = 6.11 \text{ dBi}$$

Power and PSD limit reduction = Composite gain – 6dBi, (min = 0)



1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, CO07-HY, 03CH15-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel with "*" are 802.11n HT40 and 802.11ac VHT40 and 802.11ax HE40.
2. The above Frequency and Channel with "[#]" are 802.11ac VHT80 and 802.11ax HE80.

2.2 Test Mode

This device support 26/52/106/242/484/996-tone RU but does not support 2x996-tone RU on 160MHz channel.

The PSD of partial RU is reduced to be smaller than full RU according to TCB workshop interim guidance Oct. 2022.

The 802.11ax mode is investigated among different tones, full resource units (RU), partial resource units. The partial RU has no higher power than full RU's, thus the full RU is chosen as main test configuration.

The 242-tone RU is covered by 20MHz channel, 484-tone RU is covered by 40MHz channel and 996-tone RU is covered by 80MHz channel.

The SISO mode conducted power is covered by MIMO mode per chain, so only the MIMO mode is tested.

The power for 802.11n mode is smaller than 802.11ac mode, so all other conducted and radiated test is covered by 802.11ac mode.

The final test modes include the worst data rates for each modulation shown in the table below.


MIMO Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20 (Covered by VHT20)	MCS0
802.11n HT40 (Covered by VHT40)	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

Remark: The conducted power level of each chain in MIMO mode is equal or higher than SISO mode.

Test Cases	
AC Conducted Emission	Mode 1 : Bluetooth Link + WLAN (5GHz) Link + Camera On + USB Cable (Charging from AC Adapter) + EMV Slot (Smart Card)(Load)
Remark: - The detailed Radiated test modes are shown in Appendix C. - For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	Netgear	RAXE500	PY320300508	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m



2.5 EUT Operation Test Setup

The RF test items, utility "QRCT 4.0.00206.0" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section C) Emission bandwidth for the band 5.725-5.85 GHz
2. Set RBW = 100 kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section F) Maximum power spectral density.

Method SA-2


(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300kHz.
 - Set VBW ≥ 1 MHz.
 - Add $10 \log(500 \text{ kHz/RBW})$ to the measured result, whereas RBW ($< 500 \text{ kHz}$) is the reduced resolution bandwidth of the spectrum analyzer set during measurement
 - Number of points in sweep $\geq 2 \text{ Span / RBW}$.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6 \text{ dB}$ if the duty cycle is 25 percent.
1. The RF output of EUT is connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
 3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add $10 \log(N_{\text{ANT}})$ dB.

With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity $10 \log(N_{\text{ANT}})$ dB is added to each spectrum value before comparing to the emission limit. The addition of $10 \log(N_{\text{ANT}})$ dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{\text{ANT}}^{\text{th}}$ of the PSD limit.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions falls in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

- (3) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.


6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.

3.4.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz





3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.6.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Aug. 29, 2024	Jan. 24, 2025~ Feb. 06, 2025	Aug. 28, 2025	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	802N1D01N-0 6	47020 & 06	30MHz~1GHz	Oct. 05, 2024	Jan. 24, 2025~ Feb. 06, 2025	Oct. 04, 2025	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-02294	1GHz~18GHz	Jun. 20, 2024	Jan. 24, 2025~ Feb. 06, 2025	Jun. 19, 2025	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	1220	18GHz~40GHz	Oct. 25, 2024	Jan. 24, 2025~ Feb. 06, 2025	Oct. 24, 2025	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 24, 2024	Jan. 24, 2025~ Feb. 06, 2025	Dec. 23, 2025	Radiation (03CH15-HY)
Preamplifier	EMEC	EM01G18G	060837	1GHz~18GHz	Feb. 15, 2024	Jan. 24, 2025~ Feb. 06, 2025	Feb. 14, 2025	Radiation (03CH15-HY)
Preamplifier	EM Electronics	EM01G18G	060802	1GHz~18GHz	Feb. 29, 2024	Jan. 24, 2025~ Feb. 06, 2025	Feb. 28, 2025	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	May 27, 2024	Jan. 24, 2025~ Feb. 06, 2025	May 26, 2025	Radiation (03CH15-HY)
Spectrum Analyzer	Keysight	N9010B	MY60241058	10Hz~44GHz	Jul. 11, 2024	Jan. 24, 2025~ Feb. 06, 2025	Jul. 10, 2025	Radiation (03CH15-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	20MHz~8.4GHz	Oct. 16, 2024	Jan. 24, 2025~ Feb. 06, 2025	Oct. 15, 2025	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jan. 24, 2025~ Feb. 06, 2025	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jan. 24, 2025~ Feb. 06, 2025	N/A	Radiation (03CH15-HY)
Software	Audix	E3_V9_23062 1	RK-002394	N/A	N/A	Jan. 24, 2025~ Feb. 06, 2025	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104, 102E	MY582185/4, 519228/2,803 950/2	N/A	Jun. 11, 2024	Jan. 24, 2025~ Feb. 06, 2025	Jun. 10, 2025	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804011/2,804 012/2	18-40G	Dec. 31, 2024	Jan. 24, 2025~ Feb. 06, 2025	Dec. 30, 2025	Radiation (03CH15-HY)
Filter	Wainwright	WLJ4-1000-15 30-6000-40ST	SN4	1.53GHz Low Pass Filter	Jun. 05, 2024	Jan. 24, 2025~ Feb. 06, 2025	Jun. 04, 2025	Radiation (03CH15-HY)
Filter	Wainwright	WHKX8-5872. 5-6750-18000- 40ST	SN6	6.75GHz High Pass Filter	Jun. 05, 2024	Jan. 24, 2025~ Feb. 06, 2025	Jun. 04, 2025	Radiation (03CH15-HY)
Hygrometer	TECPEL	DTM-302	SN4	N/A	Aug. 29, 2024	Jan. 24, 2025~ Feb. 06, 2025	Aug. 28, 2025	Radiation (03CH15-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Dec. 20, 2024	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Dec. 20, 2024	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	9561-FN00373	9kHz-200MHz	Oct. 23, 2024	Dec. 20, 2024	Oct. 22, 2025	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz-30MHz	Mar. 14, 2024	Dec. 20, 2024	Mar. 13, 2025	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 10, 2024	Dec. 20, 2024	Mar. 09, 2025	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 07, 2024	Dec. 20, 2024	Mar. 06, 2025	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz-3.6GHz	Sep. 23, 2024	Dec. 20, 2024	Sep. 22, 2025	Conduction (CO07-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 01, 2024	Dec. 27, 2024~Mar. 06, 2025	Oct. 31, 2025	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13I00030SNO32 (NO:43)	9kHz-6GHz	Nov. 22, 2024	Dec. 27, 2024~Mar. 06, 2025	Nov. 21, 2025	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz-40GHz	Aug. 23, 2024	Dec. 27, 2024~Mar. 06, 2025	Aug. 22, 2025	Conducted (TH05-HY)
Switch Control Mainframe	Burgeon	ETF-058	EC1300484 (BOX3)	N/A	May 20, 2024	Dec. 27, 2024~Mar. 06, 2025	May 19, 2025	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_240513	N/A	Conducted Other Test Item	N/A	Dec. 27, 2024~Mar. 06, 2025	N/A	Conducted (TH05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.3 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.4 dB
--	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.4 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2 dB
--	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Junyu Jhou	Temperature:	21~25	°C
Test Date:	2024/12/27~2025/3/6	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 MIMO												
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	2	149	5745	16.43	16.40	19.94	19.73	16.30	16.30	0.5	Pass
11a	6Mbps	2	157	5785	16.43	16.40	19.98	19.76	16.29	16.32	0.5	Pass
11a	6Mbps	2	165	5825	16.43	16.40	19.90	19.57	16.29	16.30	0.5	Pass
VHT20	MCS0	2	149	5745	17.60	17.59	20.77	21.03	16.54	17.28	0.5	Pass
VHT20	MCS0	2	157	5785	17.60	17.60	20.90	21.00	16.31	16.93	0.5	Pass
VHT20	MCS0	2	165	5825	17.62	17.60	20.91	21.05	17.30	16.91	0.5	Pass
VHT40	MCS0	2	151	5755	36.19	36.21	41.02	40.51	36.29	35.96	0.5	Pass
VHT40	MCS0	2	159	5795	36.18	36.21	40.98	40.75	36.05	35.69	0.5	Pass
VHT80	MCS0	2	155	5775	75.33	75.34	82.40	82.69	72.66	74.70	0.5	Pass

TEST RESULTS DATA**Average Power Table**

U-NII-3 MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	149	5745	18.30	18.12	21.22	30.00		3.30		Pass
11a	6Mbps	2	157	5785	18.49	18.45	21.48	30.00		3.30		Pass
11a	6Mbps	2	165	5825	18.32	18.49	21.42	30.00		3.30		Pass
HT20	MCS0	2	149	5745	17.91	17.90	20.92	30.00		3.30		Pass
HT20	MCS0	2	157	5785	18.05	18.10	21.09	30.00		3.30		Pass
HT20	MCS0	2	165	5825	17.98	18.21	21.11	30.00		3.30		Pass
HT40	MCS0	2	151	5755	18.15	17.84	21.01	30.00		3.30		Pass
HT40	MCS0	2	159	5795	18.21	18.20	21.22	30.00		3.30		Pass
VHT20	MCS0	2	149	5745	18.01	18.00	21.02	30.00		3.30		Pass
VHT20	MCS0	2	157	5785	18.15	18.20	21.19	30.00		3.30		Pass
VHT20	MCS0	2	165	5825	18.08	18.31	21.21	30.00		3.30		Pass
VHT40	MCS0	2	151	5755	18.25	17.94	21.11	30.00		3.30		Pass
VHT40	MCS0	2	159	5795	18.31	18.30	21.32	30.00		3.30		Pass
VHT80	MCS0	2	155	5775	17.99	18.22	21.12	30.00		3.30		Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-3 MIMO														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	149	5745	0.03	0.04	3.45	3.51	6.52	29.89		6.11		Pass
11a	6Mbps	2	157	5785	0.03	0.04	3.95	3.99	7.00	29.89		6.11		Pass
11a	6Mbps	2	165	5825	0.03	0.04	3.60	4.06	7.07	29.89		6.11		Pass
VHT20	MCS0	2	149	5745	0.02	0.01	3.09	3.38	6.39	29.89		6.11		Pass
VHT20	MCS0	2	157	5785	0.02	0.01	3.06	3.36	6.37	29.89		6.11		Pass
VHT20	MCS0	2	165	5825	0.02	0.01	2.79	3.51	6.52	29.89		6.11		Pass
VHT40	MCS0	2	151	5755	0.02	0.02	-0.02	-0.02	2.99	29.89		6.11		Pass
VHT40	MCS0	2	159	5795	0.02	0.02	0.36	0.73	3.74	29.89		6.11		Pass
VHT80	MCS0	2	155	5775	0.02	0.00	-2.62	-2.64	0.39	29.89		6.11		Pass

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
						Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
HE20	MCS0	2	149	5745	Full	18.90	18.91	21.89	21.29	18.60	18.39	0.5	Pass
HE20	MCS0	2	157	5785	Full	18.92	18.91	21.58	21.47	18.53	18.51	0.5	Pass
HE20	MCS0	2	165	5825	Full	18.92	18.92	21.62	21.59	18.85	18.68	0.5	Pass
HE40	MCS0	2	151	5755	Full	37.86	37.84	41.38	41.30	37.69	37.45	0.5	Pass
HE40	MCS0	2	159	5795	Full	37.83	37.86	41.60	41.50	37.88	37.88	0.5	Pass
HE80	MCS0	2	155	5775	Full	77.13	77.12	82.02	82.40	74.99	75.12	0.5	Pass

TEST RESULTS DATA**Average Power Table**

U-NII-3 MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
HE20	MCS0	2	149	5745	Full	18.11	18.04	21.09	30.00		3.30		Pass
HE20	MCS0	2	149	5745	26/0	6.71	8.10	10.47	30.00		3.30		Pass
HE20	MCS0	2	149	5745	52/37	11.51	11.70	14.62	30.00		3.30		Pass
HE20	MCS0	2	149	5745	106/53	14.61	14.45	17.54	30.00		3.30		Pass
HE20	MCS0	2	157	5785	Full	18.40	18.26	21.34	30.00		3.30		Pass
HE20	MCS0	2	157	5785	26/4	8.89	8.67	11.79	30.00		3.30		Pass
HE20	MCS0	2	157	5785	52/38	11.73	11.22	14.49	30.00		3.30		Pass
HE20	MCS0	2	157	5785	106/53	15.46	15.27	18.38	30.00		3.30		Pass
HE20	MCS0	2	165	5825	Full	18.18	18.41	21.31	30.00		3.30		Pass
HE20	MCS0	2	165	5825	26/8	7.96	8.29	11.14	30.00		3.30		Pass
HE20	MCS0	2	165	5825	52/40	11.90	11.38	14.66	30.00		3.30		Pass
HE20	MCS0	2	165	5825	106/54	14.92	14.70	17.82	30.00		3.30		Pass
HE40	MCS0	2	151	5755	Full	18.35	18.04	21.21	30.00		3.30		Pass
HE40	MCS0	2	151	5755	242/61	15.80	15.70	18.76	30.00		3.30		Pass
HE40	MCS0	2	159	5795	Full	18.41	18.40	21.42	30.00		3.30		Pass
HE40	MCS0	2	159	5795	242/62	15.77	15.68	18.74	30.00		3.30		Pass
HE80	MCS0	2	155	5775	Full	18.09	18.32	21.22	30.00		3.30		Pass
HE80	MCS0	2	155	5775	484/65	15.99	15.76	18.89	30.00		3.30		Pass
HE80	MCS0	2	155	5775	484/66	15.80	15.61	18.72	30.00		3.30		Pass

TEST RESULTS DATA
Power Spectral Density


U-NII-3 MIMO															
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
						Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
HE20	MCS0	2	149	5745	Full	0.02	0.02	2.72	2.85	5.86	29.89		6.11		Pass
HE20	MCS0	2	149	5745	26/0	0.01	0.02	0.78	2.44	5.45	29.89		6.11		Pass
HE20	MCS0	2	149	5745	52/37	0.00	0.00	2.46	2.69	5.70	29.89		6.11		Pass
HE20	MCS0	2	149	5745	106/53	0.01	0.01	2.37	2.46	5.47	29.89		6.11		Pass
HE20	MCS0	2	157	5785	Full	0.02	0.02	3.21	3.44	6.45	29.89		6.11		Pass
HE20	MCS0	2	157	5785	26/4	0.01	0.02	3.11	2.88	6.12	29.89		6.11		Pass
HE20	MCS0	2	157	5785	52/38	0.00	0.00	2.99	2.76	6.00	29.89		6.11		Pass
HE20	MCS0	2	157	5785	106/53	0.01	0.01	3.34	3.31	6.35	29.89		6.11		Pass
HE20	MCS0	2	165	5825	Full	0.02	0.02	3.02	3.53	6.54	29.89		6.11		Pass
HE20	MCS0	2	165	5825	26/8	0.01	0.02	2.30	2.85	5.86	29.89		6.11		Pass
HE20	MCS0	2	165	5825	52/40	0.00	0.00	3.10	2.69	6.11	29.89		6.11		Pass
HE20	MCS0	2	165	5825	106/54	0.01	0.01	2.99	2.86	6.00	29.89		6.11		Pass
HE40	MCS0	2	151	5755	Full	0.01	0.01	0.11	0.00	3.12	29.89		6.11		Pass
HE40	MCS0	2	151	5755	242/61	0.03	0.03	0.08	-0.01	3.09	29.89		6.11		Pass
HE40	MCS0	2	159	5795	Full	0.01	0.01	0.65	0.71	3.72	29.89		6.11		Pass
HE40	MCS0	2	159	5795	242/62	0.03	0.03	0.43	0.41	3.44	29.89		6.11		Pass
HE80	MCS0	2	155	5775	Full	0.01	0.01	-2.81	-2.50	0.51	29.89		6.11		Pass
HE80	MCS0	2	155	5775	484/65	0.05	0.05	-2.64	-2.74	0.37	29.89		6.11		Pass
HE80	MCS0	2	155	5775	484/66	0.05	0.05	-2.53	-2.56	0.48	29.89		6.11		Pass

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)

**Test Result of 6dB and 26dB and 99% Occupied Bandwidth**


MIMO <Ant. 1+2>

<802.11a>






<802.11ac VHT20>






<802.11ac VHT40>






<802.11ac VHT80>






<802.11ax HE20>


6dB Bandwidth



26dB Bandwidth




99% Occupied Bandwidth



N/A




<802.11ax HE40>






<802.11ax HE80>


6dB Bandwidth



26dB Bandwidth



99% Occupied Bandwidth




N/A




Test Result of Power Spectral Density

<802.11a>




<802.11ac VHT20>






<802.11ac VHT40>




<802.11ac VHT80>






<802.11ax HE20>




<802.11ax HE40>





<802.11ax HE80>





Appendix B. AC Conducted Emission Test Results


Test Engineer :	Louis Chung	Temperature :	18.8~20.6°C
		Relative Humidity :	38.2~43.5%

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

4N2203
Mode 1
120Vac/60Hz
Line

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.152520	---	24.51	55.86	31.35	L1	FLO	19.9
0.152520	38.07	---	65.86	27.79	L1	FLO	19.9
0.172500	---	20.98	54.84	33.86	L1	FLO	19.9
0.172500	37.80	---	64.84	27.04	L1	FLO	19.9
0.180780	---	20.33	54.45	34.12	L1	FLO	19.9
0.180780	36.17	---	64.45	28.28	L1	FLO	19.9
0.397500	---	20.04	47.91	27.87	L1	FLO	19.9
0.397500	28.39	---	57.91	29.52	L1	FLO	19.9
0.464010	---	19.18	46.62	27.44	L1	FLO	19.9
0.464010	29.61	---	56.62	27.01	L1	FLO	19.9
0.523770	---	18.73	46.00	27.27	L1	FLO	19.9
0.523770	28.36	---	56.00	27.64	L1	FLO	19.9
0.594510	---	13.65	46.00	32.35	L1	FLO	19.9
0.594510	28.42	---	56.00	27.58	L1	FLO	19.9
1.295250	---	17.97	46.00	28.03	L1	FLO	19.9
1.295250	27.14	---	56.00	28.86	L1	FLO	19.9
2.069250	---	17.13	46.00	28.87	L1	FLO	20.0
2.069250	23.49	---	56.00	32.51	L1	FLO	20.0
3.021450	---	19.12	46.00	26.88	L1	FLO	20.0


3.021450	24.29	---	56.00	31.71	L1	FLO	20.0
7.718550	---	19.28	50.00	30.72	L1	FLO	20.1
7.718550	24.19	---	60.00	35.81	L1	FLO	20.1
21.723000	---	19.59	50.00	30.41	L1	FLO	20.2
21.723000	23.46	---	60.00	36.54	L1	FLO	20.2

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

4N2203
Mode 1
120Vac/60Hz
Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.150000	---	22.61	56.00	33.39	N	FLO	20.0
0.150000	39.64	---	66.00	26.36	N	FLO	20.0
0.179250	---	23.27	54.52	31.25	N	FLO	19.9
0.179250	38.97	---	64.52	25.55	N	FLO	19.9
0.230820	---	19.27	52.42	33.15	N	FLO	19.9
0.230820	35.97	---	62.42	26.45	N	FLO	19.9
0.379500	---	21.67	48.29	26.62	N	FLO	19.9
0.379500	34.27	---	58.29	24.02	N	FLO	19.9
0.399750	---	22.96	47.86	24.90	N	FLO	19.9
0.399750	27.53	---	57.86	30.33	N	FLO	19.9
0.402090	---	23.87	47.81	23.94	N	FLO	19.9
0.402090	28.19	---	57.81	29.62	N	FLO	19.9
0.586500	---	19.72	46.00	26.28	N	FLO	19.9
0.586500	31.18	---	56.00	24.82	N	FLO	19.9
0.613230	---	22.18	46.00	23.82	N	FLO	19.9
0.613230	29.95	---	56.00	26.05	N	FLO	19.9
0.683250	---	18.61	46.00	27.39	N	FLO	19.9
0.683250	31.28	---	56.00	24.72	N	FLO	19.9
0.712500	---	18.95	46.00	27.05	N	FLO	19.9

0.712500	30.98	---	56.00	25.02	N	FLO	19.9
1.080780	---	20.06	46.00	25.94	N	FLO	20.0
1.080780	30.27	---	56.00	25.73	N	FLO	20.0
1.182750	---	20.23	46.00	25.77	N	FLO	20.0
1.182750	31.87	---	56.00	24.13	N	FLO	20.0
1.220730	---	19.03	46.00	26.97	N	FLO	20.0
1.220730	32.25	---	56.00	23.75	N	FLO	20.0
2.181750	---	21.27	46.00	24.73	N	FLO	20.0
2.181750	27.51	---	56.00	28.49	N	FLO	20.0
2.857920	---	22.15	46.00	23.85	N	FLO	20.0
2.857920	27.92	---	56.00	28.08	N	FLO	20.0
21.912000	---	19.96	50.00	30.04	N	FLO	20.2
21.912000	24.12	---	60.00	35.88	N	FLO	20.2



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Sam Pan, Quentin Liu and Bigshow Wang	Temperature :	21.9~22.3
		Relative Humidity :	49~53

Note symbol

-L	Low channel location
-R	High channel location

C1. Radiated Spurious Emission Test Modes

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 61	U-NII-3	5.725-5.85	1+2	802.11a	149	5745	6Mbps	-	-
Mode 62	U-NII-3	5.725-5.85	1+2	802.11a	157	5785	6Mbps	-	-
Mode 63	U-NII-3	5.725-5.85	1+2	802.11a	165	5825	6Mbps	-	-
Mode 64	U-NII-3	5.725-5.85	1+2	802.11ax HE20	149	5745	MCS0	Full RU	-
Mode 65	U-NII-3	5.725-5.85	1+2	802.11ax HE20	157	5785	MCS0	Full RU	-
Mode 66	U-NII-3	5.725-5.85	1+2	802.11ax HE20	165	5825	MCS0	Full RU	-
Mode 67	U-NII-3	5.725-5.85	1+2	802.11ax HE40	151	5755	MCS0	Full RU	-
Mode 68	U-NII-3	5.725-5.85	1+2	802.11ax HE40	159	5795	MCS0	Full RU	-
Mode 69	U-NII-3	5.725-5.85	1+2	802.11ax HE80	155	5775	MCS0	Full RU	-
Mode 71	U-NII-3	5.725-5.85	1+2	802.11ax HE20	149	5745	MCS0	Partial RU 106/53	-
Mode 72	U-NII-3	5.725-5.85	1+2	802.11ax HE40	159	5795	MCS0	Partial RU 242/62	-



Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 73	U-NII-3	5.725-5.85	1+2	802.11ax HE80	155	5775	MCS0	Partial RU 484/66	-
Mode 75	U-NII-3	5.725-5.85	1+2	802.11ac VHT20	149	5745	MCS0	-	-
Mode 76	U-NII-3	5.725-5.85	1+2	802.11ac VHT40	159	5795	MCS0	-	-
Mode 77	U-NII-3	5.725-5.85	1+2	802.11ac VHT80	155	5775	MCS0	-	-
Mode 78	U-NII-3	5.725-5.85	1+2	802.11ax HE80	155	5775	MCS0	Partial RU 484/66	LF
Mode 79	U-NII-3	5.725-5.85	1+2	802.11ax HE80	155	5775	MCS0	Partial RU 484/66	SHF



C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
61	802.11a	149	5631.18	49.04	68.20	-19.16	H	Peak	Pass	-	Band Edge
	802.11a	149	17235.00	47.39	68.20	-20.81	V	Peak	Pass	-	Harmonic
62	802.11a	157	5637.74	51.30	68.20	-16.90	V	Peak	Pass	-	Band Edge
	802.11a	157	17355.00	47.52	68.20	-20.68	V	Peak	Pass	-	Harmonic
63	802.11a	165	5930.13	48.76	68.20	-19.44	V	Peak	Pass	-	Band Edge
	802.11a	165	17475.00	48.50	68.20	-19.70	V	Peak	Pass	-	Harmonic
64	802.11ax HE20	149	5600.29	48.25	68.20	-19.95	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE20	149	17235.00	47.93	68.20	-20.27	V	Peak	Pass	Full RU	Harmonic
65	802.11ax HE20	157	5637.37	51.22	68.20	-16.98	H	Peak	Pass	Full RU	Band Edge
	802.11ax HE20	157	17355.00	47.22	68.20	-20.98	V	Peak	Pass	Full RU	Harmonic
66	802.11ax HE20	165	5935.50	48.23	68.20	-19.97	H	Peak	Pass	Full RU	Band Edge






Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
66	802.11ax HE20	165	17475.00	48.70	68.20	-19.50	V	Peak	Pass	Full RU	Harmonic
67	802.11ax HE40	151	5619.07	50.90	68.20	-17.30	H	Peak	Pass	Full RU	Band Edge
	802.11ax HE40	151	17265.00	47.55	68.20	-20.65	V	Peak	Pass	Full RU	Harmonic
68	802.11ax HE40	159	5645.24	52.16	68.20	-16.04	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE40	159	17385.00	48.41	68.20	-19.79	V	Peak	Pass	Full RU	Harmonic
69	802.11ax HE80	155	5646.03	51.80	68.20	-16.40	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE80	155	17325.00	48.73	68.20	-19.47	V	Peak	Pass	Full RU	Harmonic
71	802.11ax HE20	149	5645.24	49.56	68.20	-18.64	V	Peak	Pass	Partial RU 106/53	Band Edge
	802.11ax HE20	149	-	-	-	-	-	-	-	Partial RU 106/53	Harmonic
72	802.11ax HE40	159	5932.18	60.53	68.20	-7.67	V	Peak	Pass	Partial RU 242/62	Band Edge
	802.11ax HE40	159	-	-	-	-	-	-	-	Partial RU 242/62	Harmonic






Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
73	802.11ax HE80	155	5611.73	66.14	68.20	-2.06	V	Peak	Pass	Partial RU 484/66	Band Edge
	802.11ax HE80	155	-	-	-	-	-	-	-	Partial RU 484/66	Harmonic
75	802.11ac VHT20	149	5648.29	48.46	68.20	-19.74	H	Peak	Pass	-	Band Edge
	802.11ac VHT20	149	17235.00	46.76	68.20	-21.44	V	Peak	Pass	-	Harmonic
76	802.11ac VHT40	159	5928.77	52.82	68.20	-15.38	V	Peak	Pass	-	Band Edge
	802.11ac VHT40	159	17385.00	47.35	68.20	-20.85	V	Peak	Pass	-	Harmonic
77	802.11ac VHT80	155	5650.40	62.39	68.50	-6.11	V	Peak	Pass	-	Band Edge
	802.11ac VHT80	155	17325.00	47.58	68.20	-20.62	H	Peak	Pass	-	Harmonic
78	LF	155	58.13	32.27	40.00	-7.73	V	Peak	Pass	-	LF
79	SHF	155	39367.75	48.38	74.00	-25.62	V	Peak	Pass	-	SHF





Mode	61																																																																																																																																												
	Band Edge																																																																																																																																												
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																																																																																												
ANT	1+2																																																																																																																																												
Pol.	Horizontal						Fundamental																																																																																																																																						
Peak																																																																																																																																													
	Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5631.18</td><td>49.04</td><td>68.20</td><td>-19.16</td><td>43.50</td><td>33.19</td><td>8.66</td><td>36.31</td><td>0.00</td><td>228</td><td>247</td><td>PEAK</td></tr><tr><td>2</td><td>5651.48</td><td>47.71</td><td>69.30</td><td>-21.59</td><td>42.03</td><td>33.31</td><td>8.69</td><td>36.32</td><td>0.00</td><td>228</td><td>247</td><td>PEAK</td></tr><tr><td>3</td><td>5702.08</td><td>49.20</td><td>105.78</td><td>-56.58</td><td>43.09</td><td>33.70</td><td>8.74</td><td>36.33</td><td>0.00</td><td>228</td><td>247</td><td>PEAK</td></tr><tr><td>4</td><td>5720.35</td><td>51.72</td><td>111.60</td><td>-59.88</td><td>45.55</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>228</td><td>247</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5631.18	49.04	68.20	-19.16	43.50	33.19	8.66	36.31	0.00	228	247	PEAK	2	5651.48	47.71	69.30	-21.59	42.03	33.31	8.69	36.32	0.00	228	247	PEAK	3	5702.08	49.20	105.78	-56.58	43.09	33.70	8.74	36.33	0.00	228	247	PEAK	4	5720.35	51.72	111.60	-59.88	45.55	33.74	8.76	36.33	0.00	228	247	PEAK	Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>107.18</td><td>-----</td><td>-----</td><td>100.94</td><td>33.79</td><td>8.79</td><td>36.34</td><td>0.00</td><td>228</td><td>247</td><td>PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	107.18	-----	-----	100.94	33.79	8.79	36.34	0.00	228	247
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																			
1	5631.18	49.04	68.20	-19.16	43.50	33.19	8.66	36.31	0.00	228	247	PEAK																																																																																																																																	
2	5651.48	47.71	69.30	-21.59	42.03	33.31	8.69	36.32	0.00	228	247	PEAK																																																																																																																																	
3	5702.08	49.20	105.78	-56.58	43.09	33.70	8.74	36.33	0.00	228	247	PEAK																																																																																																																																	
4	5720.35	51.72	111.60	-59.88	45.55	33.74	8.76	36.33	0.00	228	247	PEAK																																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																			
1	5745.00	107.18	-----	-----	100.94	33.79	8.79	36.34	0.00	228	247	PEAK																																																																																																																																	
Avg	Blank																																																																																																																																												
							Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>100.33</td><td>-----</td><td>-----</td><td>94.09</td><td>33.79</td><td>8.79</td><td>36.34</td><td>0.00</td><td>228</td><td>247</td><td>AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	100.33	-----	-----	94.09	33.79	8.79	36.34	0.00	228	247	AVERAGE																																																																																				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																			
1	5745.00	100.33	-----	-----	94.09	33.79	8.79	36.34	0.00	228	247	AVERAGE																																																																																																																																	






Mode	61																																																																																																																																										
	Band Edge																																																																																																																																										
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																																																																																										
ANT	1+2																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5623.20</td><td>48.88</td><td>68.20</td><td>-19.32</td><td>43.39</td><td>33.14</td><td>8.66</td><td>36.31</td><td>0.00</td><td>100</td><td>354</td><td>PEAK</td></tr><tr><td>2</td><td>5650.17</td><td>48.19</td><td>68.33</td><td>-20.14</td><td>42.52</td><td>33.30</td><td>8.69</td><td>36.32</td><td>0.00</td><td>100</td><td>354</td><td>PEAK</td></tr><tr><td>3</td><td>5717.60</td><td>61.42</td><td>110.13</td><td>-48.71</td><td>55.25</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>100</td><td>354</td><td>PEAK</td></tr><tr><td>4</td><td>5720.06</td><td>62.37</td><td>110.94</td><td>-48.57</td><td>56.20</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>100</td><td>354</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5623.20	48.88	68.20	-19.32	43.39	33.14	8.66	36.31	0.00	100	354	PEAK	2	5650.17	48.19	68.33	-20.14	42.52	33.30	8.69	36.32	0.00	100	354	PEAK	3	5717.60	61.42	110.13	-48.71	55.25	33.74	8.76	36.33	0.00	100	354	PEAK	4	5720.06	62.37	110.94	-48.57	56.20	33.74	8.76	36.33	0.00	100	354	PEAK	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>110.39</td><td>-----</td><td>-----</td><td>104.15</td><td>33.79</td><td>8.79</td><td>36.34</td><td>0.00</td><td>100</td><td>354</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	110.39	-----	-----	104.15	33.79	8.79	36.34	0.00	100	354	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5623.20	48.88	68.20	-19.32	43.39	33.14	8.66	36.31	0.00	100	354	PEAK																																																																																																																															
2	5650.17	48.19	68.33	-20.14	42.52	33.30	8.69	36.32	0.00	100	354	PEAK																																																																																																																															
3	5717.60	61.42	110.13	-48.71	55.25	33.74	8.76	36.33	0.00	100	354	PEAK																																																																																																																															
4	5720.06	62.37	110.94	-48.57	56.20	33.74	8.76	36.33	0.00	100	354	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5745.00	110.39	-----	-----	104.15	33.79	8.79	36.34	0.00	100	354	PEAK																																																																																																																															
Avg	Blank						 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>103.79</td><td>-----</td><td>-----</td><td>97.55</td><td>33.79</td><td>8.79</td><td>36.34</td><td>0.00</td><td>100</td><td>354</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	103.79	-----	-----	97.55	33.79	8.79	36.34	0.00	100	354	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5745.00	103.79	-----	-----	97.55	33.79	8.79	36.34	0.00	100	354	AVERAGE																																																																																																																															




Mode	61																																																																		
	Harmonic																																																																		
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																		
ANT	1+2																																																																		
Pol.	Horizontal						Vertical																																																												
Peak Avg																																																																			
	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL																																																																		
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11490.00</td><td>46.66</td><td>74.00</td><td>-27.34</td><td></td><td>52.41</td><td>38.91</td><td>12.58</td><td>58.16</td><td>0.92</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17235.00</td><td>47.31</td><td>68.20</td><td>-20.89</td><td></td><td>51.96</td><td>38.20</td><td>15.47</td><td>59.26</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></table>													Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11490.00	46.66	74.00	-27.34		52.41	38.91	12.58	58.16	0.92	--	--	PEAK	2	17235.00	47.31	68.20	-20.89		51.96	38.20	15.47	59.26	0.94	--	--
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																							
1	11490.00	46.66	74.00	-27.34		52.41	38.91	12.58	58.16	0.92	--	--	PEAK																																																						
2	17235.00	47.31	68.20	-20.89		51.96	38.20	15.47	59.26	0.94	--	--	PEAK																																																						
Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 VERTICAL																																																																			
<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11490.00</td><td>46.05</td><td>74.00</td><td>-27.95</td><td></td><td>51.80</td><td>38.91</td><td>12.58</td><td>58.16</td><td>0.92</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17235.00</td><td>47.39</td><td>68.20</td><td>-20.81</td><td></td><td>52.04</td><td>38.20</td><td>15.47</td><td>59.26</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></table>													Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11490.00	46.05	74.00	-27.95		51.80	38.91	12.58	58.16	0.92	--	--	PEAK	2	17235.00	47.39	68.20	-20.81		52.04	38.20	15.47	59.26	0.94	--	--	PEAK
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																							
1	11490.00	46.05	74.00	-27.95		51.80	38.91	12.58	58.16	0.92	--	--	PEAK																																																						
2	17235.00	47.39	68.20	-20.81		52.04	38.20	15.47	59.26	0.94	--	--	PEAK																																																						






		62																																																																																																																																											
Mode		Band Edge - L																																																																																																																																											
		U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																																																																																											
ANT		1+2																																																																																																																																											
Pol.		Horizontal					Fundamental																																																																																																																																						
Peak																																																																																																																																													
	Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5632.93</td><td>49.56</td><td>68.20</td><td>-18.64</td><td>44.00</td><td>33.20</td><td>8.67</td><td>36.31</td><td>0.00</td><td>300</td><td>258</td><td>PEAK</td></tr><tr><td>2</td><td>5650.32</td><td>45.64</td><td>68.44</td><td>-22.80</td><td>39.97</td><td>33.30</td><td>8.69</td><td>36.32</td><td>0.00</td><td>300</td><td>258</td><td>PEAK</td></tr><tr><td>3</td><td>5702.31</td><td>48.24</td><td>105.85</td><td>-57.61</td><td>42.13</td><td>33.70</td><td>8.74</td><td>36.33</td><td>0.00</td><td>300</td><td>258</td><td>PEAK</td></tr><tr><td>4</td><td>5720.44</td><td>49.15</td><td>111.79</td><td>-62.64</td><td>42.98</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>300</td><td>258</td><td>PEAK</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5632.93	49.56	68.20	-18.64	44.00	33.20	8.67	36.31	0.00	300	258	PEAK	2	5650.32	45.64	68.44	-22.80	39.97	33.30	8.69	36.32	0.00	300	258	PEAK	3	5702.31	48.24	105.85	-57.61	42.13	33.70	8.74	36.33	0.00	300	258	PEAK	4	5720.44	49.15	111.79	-62.64	42.98	33.74	8.76	36.33	0.00	300	258	PEAK	Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5785.00</td><td>100.22</td><td>-----</td><td>-----</td><td>101.75</td><td>33.99</td><td>8.83</td><td>36.35</td><td>0.00</td><td>300</td><td>258</td><td>PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5785.00	100.22	-----	-----	101.75	33.99	8.83	36.35	0.00	300	258
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																			
1	5632.93	49.56	68.20	-18.64	44.00	33.20	8.67	36.31	0.00	300	258	PEAK																																																																																																																																	
2	5650.32	45.64	68.44	-22.80	39.97	33.30	8.69	36.32	0.00	300	258	PEAK																																																																																																																																	
3	5702.31	48.24	105.85	-57.61	42.13	33.70	8.74	36.33	0.00	300	258	PEAK																																																																																																																																	
4	5720.44	49.15	111.79	-62.64	42.98	33.74	8.76	36.33	0.00	300	258	PEAK																																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																			
1	5785.00	100.22	-----	-----	101.75	33.99	8.83	36.35	0.00	300	258	PEAK																																																																																																																																	
Avg	Blank																																																																																																																																												
	Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5785.00</td><td>102.16</td><td>-----</td><td>-----</td><td>95.64</td><td>34.03</td><td>8.84</td><td>36.35</td><td>0.00</td><td>300</td><td>258</td><td>AVERAGE</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5785.00	102.16	-----	-----	95.64	34.03	8.84	36.35	0.00	300	258	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																			
1	5785.00	102.16	-----	-----	95.64	34.03	8.84	36.35	0.00	300	258	AVERAGE																																																																																																																																	




Mode	62																																																																																
	Band Edge - R																																																																																
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																																
ANT	1+2																																																																																
Pol.	Horizontal	Fundamental																																																																															
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5854.80</td><td>47.35</td><td>111.27</td><td>-63.92</td><td>40.59</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>300</td><td>258</td><td>PEAK</td></tr><tr><td>2 5874.93</td><td>47.84</td><td>105.22</td><td>-57.38</td><td>40.98</td><td>34.30</td><td>8.93</td><td>36.37</td><td>0.00</td><td>300</td><td>258</td><td>PEAK</td></tr><tr><td>3 5921.95</td><td>48.18</td><td>70.45</td><td>-22.27</td><td>41.27</td><td>34.31</td><td>8.98</td><td>36.38</td><td>0.00</td><td>300</td><td>258</td><td>PEAK</td></tr><tr><td>4 5933.17</td><td>48.36</td><td>68.20</td><td>-19.84</td><td>41.47</td><td>34.27</td><td>9.00</td><td>36.38</td><td>0.00</td><td>300</td><td>258</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 5854.80	47.35	111.27	-63.92	40.59	34.22	8.91	36.37	0.00	300	258	PEAK	2 5874.93	47.84	105.22	-57.38	40.98	34.30	8.93	36.37	0.00	300	258	PEAK	3 5921.95	48.18	70.45	-22.27	41.27	34.31	8.98	36.38	0.00	300	258	PEAK	4 5933.17	48.36	68.20	-19.84	41.47	34.27	9.00	36.38	0.00	300	258	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																							
1 5854.80	47.35	111.27	-63.92	40.59	34.22	8.91	36.37	0.00	300	258	PEAK																																																																						
2 5874.93	47.84	105.22	-57.38	40.98	34.30	8.93	36.37	0.00	300	258	PEAK																																																																						
3 5921.95	48.18	70.45	-22.27	41.27	34.31	8.98	36.38	0.00	300	258	PEAK																																																																						
4 5933.17	48.36	68.20	-19.84	41.47	34.27	9.00	36.38	0.00	300	258	PEAK																																																																						





Mode	62																																																																																																																																			
	Band Edge - L																																																																																																																																			
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																																																																																			
ANT	1+2																																																																																																																																			
Pol.	Vertical						Fundamental																																																																																																																													
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5637.74</td><td>51.30</td><td>68.20</td><td>-16.90</td><td>45.71</td><td>33.23</td><td>8.67</td><td>36.31</td><td>0.00</td><td>100</td><td>0 PEAK</td></tr><tr><td>2 5650.32</td><td>47.01</td><td>68.44</td><td>-21.43</td><td>41.34</td><td>33.30</td><td>8.69</td><td>36.32</td><td>0.00</td><td>100</td><td>0 PEAK</td></tr><tr><td>3 5700.64</td><td>48.39</td><td>105.38</td><td>-56.99</td><td>42.28</td><td>33.70</td><td>8.74</td><td>36.33</td><td>0.00</td><td>100</td><td>0 PEAK</td></tr><tr><td>4 5720.25</td><td>47.52</td><td>111.37</td><td>-63.85</td><td>41.35</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>100</td><td>0 PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 5637.74	51.30	68.20	-16.90	45.71	33.23	8.67	36.31	0.00	100	0 PEAK	2 5650.32	47.01	68.44	-21.43	41.34	33.30	8.69	36.32	0.00	100	0 PEAK	3 5700.64	48.39	105.38	-56.99	42.28	33.70	8.74	36.33	0.00	100	0 PEAK	4 5720.25	47.52	111.37	-63.85	41.35	33.74	8.76	36.33	0.00	100	0 PEAK	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5785.00</td><td>111.48</td><td>-----</td><td>-----</td><td>104.96</td><td>34.03</td><td>8.84</td><td>36.35</td><td>0.00</td><td>100</td><td>0 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 5785.00	111.48	-----	-----	104.96	34.03	8.84	36.35	0.00	100	0 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																										
1 5637.74	51.30	68.20	-16.90	45.71	33.23	8.67	36.31	0.00	100	0 PEAK																																																																																																																										
2 5650.32	47.01	68.44	-21.43	41.34	33.30	8.69	36.32	0.00	100	0 PEAK																																																																																																																										
3 5700.64	48.39	105.38	-56.99	42.28	33.70	8.74	36.33	0.00	100	0 PEAK																																																																																																																										
4 5720.25	47.52	111.37	-63.85	41.35	33.74	8.76	36.33	0.00	100	0 PEAK																																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																										
1 5785.00	111.48	-----	-----	104.96	34.03	8.84	36.35	0.00	100	0 PEAK																																																																																																																										
Avg	Blank						 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5785.00</td><td>104.27</td><td>-----</td><td>-----</td><td>97.75</td><td>34.03</td><td>8.84</td><td>36.35</td><td>0.00</td><td>100</td><td>0 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 5785.00	104.27	-----	-----	97.75	34.03	8.84	36.35	0.00	100	0 AVERAGE																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																										
1 5785.00	104.27	-----	-----	97.75	34.03	8.84	36.35	0.00	100	0 AVERAGE																																																																																																																										






Mode	62																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																							
ANT	1+2																																																																							
Pol.	Vertical	Fundamental																																																																						
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5854.96</td><td>48.86</td><td>110.89</td><td>-62.83</td><td>41.30</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>100 0 PEAK</td></tr><tr><td>2 5873.77</td><td>47.98</td><td>105.54</td><td>-57.56</td><td>41.12</td><td>34.30</td><td>8.93</td><td>36.37</td><td>0.00</td><td>100 0 PEAK</td></tr><tr><td>3 5924.43</td><td>48.80</td><td>68.62</td><td>-19.82</td><td>41.89</td><td>34.30</td><td>8.99</td><td>36.38</td><td>0.00</td><td>100 0 PEAK</td></tr><tr><td>4 5939.94</td><td>48.76</td><td>68.20</td><td>-19.44</td><td>41.91</td><td>34.24</td><td>9.00</td><td>36.39</td><td>0.00</td><td>100 0 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5854.96	48.86	110.89	-62.83	41.30	34.22	8.91	36.37	0.00	100 0 PEAK	2 5873.77	47.98	105.54	-57.56	41.12	34.30	8.93	36.37	0.00	100 0 PEAK	3 5924.43	48.80	68.62	-19.82	41.89	34.30	8.99	36.38	0.00	100 0 PEAK	4 5939.94	48.76	68.20	-19.44	41.91	34.24	9.00	36.39	0.00	100 0 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																															
1 5854.96	48.86	110.89	-62.83	41.30	34.22	8.91	36.37	0.00	100 0 PEAK																																																															
2 5873.77	47.98	105.54	-57.56	41.12	34.30	8.93	36.37	0.00	100 0 PEAK																																																															
3 5924.43	48.80	68.62	-19.82	41.89	34.30	8.99	36.38	0.00	100 0 PEAK																																																															
4 5939.94	48.76	68.20	-19.44	41.91	34.24	9.00	36.39	0.00	100 0 PEAK																																																															






Mode	62																																																																																																																								
	Harmonic																																																																																																																								
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																																																																								
ANT	1+2																																																																																																																								
Pol.	Horizontal						Vertical																																																																																																																		
Peak Avg																																																																																																																									
	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11570.00</td><td>45.93</td><td>74.00</td><td>-28.07</td><td>51.87</td><td>38.62</td><td>12.63</td><td>58.11</td><td>0.92</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17355.00</td><td>47.52</td><td>68.20</td><td>-20.68</td><td>51.91</td><td>38.37</td><td>15.54</td><td>59.24</td><td>0.94</td><td>--</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11570.00	45.93	74.00	-28.07	51.87	38.62	12.63	58.11	0.92	--	PEAK	2	17355.00	47.52	68.20	-20.68	51.91	38.37	15.54	59.24	0.94	--	PEAK	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11570.00</td><td>45.47</td><td>74.00</td><td>-28.53</td><td>51.41</td><td>38.62</td><td>12.63</td><td>58.11</td><td>0.92</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17355.00</td><td>47.12</td><td>68.20</td><td>-21.08</td><td>51.51</td><td>38.37</td><td>15.54</td><td>59.24</td><td>0.94</td><td>--</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11570.00	45.47	74.00	-28.53	51.41	38.62	12.63	58.11	0.92	--	PEAK	2	17355.00	47.12	68.20	-21.08	51.51	38.37	15.54	59.24	0.94	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																															
1	11570.00	45.93	74.00	-28.07	51.87	38.62	12.63	58.11	0.92	--	PEAK																																																																																																														
2	17355.00	47.52	68.20	-20.68	51.91	38.37	15.54	59.24	0.94	--	PEAK																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																															
1	11570.00	45.47	74.00	-28.53	51.41	38.62	12.63	58.11	0.92	--	PEAK																																																																																																														
2	17355.00	47.12	68.20	-21.08	51.51	38.37	15.54	59.24	0.94	--	PEAK																																																																																																														





Mode	63																																																																																																																																																								
	Band Edge																																																																																																																																																								
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz																																																																																																																																																								
ANT	1+2																																																																																																																																																								
Pol.	Horizontal																																																																																																																																																								
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5855.00</td><td>50.29</td><td>110.80</td><td>-60.51</td><td>43.53</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>300</td><td>235</td><td>PEAK</td></tr><tr><td>2</td><td>5873.50</td><td>49.01</td><td>105.62</td><td>-56.61</td><td>42.16</td><td>34.29</td><td>8.93</td><td>36.37</td><td>0.00</td><td>300</td><td>235</td><td>PEAK</td></tr><tr><td>3</td><td>5922.50</td><td>48.67</td><td>70.04</td><td>-21.37</td><td>41.76</td><td>34.31</td><td>8.98</td><td>36.38</td><td>0.00</td><td>300</td><td>235</td><td>PEAK</td></tr><tr><td>4</td><td>5930.13</td><td>48.56</td><td>68.20</td><td>-19.64</td><td>41.67</td><td>34.28</td><td>8.99</td><td>36.38</td><td>0.00</td><td>300</td><td>235</td><td>PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5855.00	50.29	110.80	-60.51	43.53	34.22	8.91	36.37	0.00	300	235	PEAK	2	5873.50	49.01	105.62	-56.61	42.16	34.29	8.93	36.37	0.00	300	235	PEAK	3	5922.50	48.67	70.04	-21.37	41.76	34.31	8.98	36.38	0.00	300	235	PEAK	4	5930.13	48.56	68.20	-19.64	41.67	34.28	8.99	36.38	0.00	300	235	PEAK	 Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>107.33</td><td>-----</td><td>-----</td><td>100.65</td><td>34.16</td><td>8.88</td><td>36.36</td><td>0.00</td><td>300</td><td>235</td><td>PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	107.33	-----	-----	100.65	34.16	8.88	36.36	0.00	300	235	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																															
	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																															
1	5855.00	50.29	110.80	-60.51	43.53	34.22	8.91	36.37	0.00	300	235	PEAK																																																																																																																																													
2	5873.50	49.01	105.62	-56.61	42.16	34.29	8.93	36.37	0.00	300	235	PEAK																																																																																																																																													
3	5922.50	48.67	70.04	-21.37	41.76	34.31	8.98	36.38	0.00	300	235	PEAK																																																																																																																																													
4	5930.13	48.56	68.20	-19.64	41.67	34.28	8.99	36.38	0.00	300	235	PEAK																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																															
1	5825.00	107.33	-----	-----	100.65	34.16	8.88	36.36	0.00	300	235	PEAK																																																																																																																																													
Avg	Blank											 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>100.82</td><td>-----</td><td>-----</td><td>94.14</td><td>34.16</td><td>8.88</td><td>36.36</td><td>0.00</td><td>300</td><td>235</td><td>AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	100.82	-----	-----	94.14	34.16	8.88	36.36	0.00	300	235	AVERAGE																																																																																					
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																															
	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																															
1	5825.00	100.82	-----	-----	94.14	34.16	8.88	36.36	0.00	300	235	AVERAGE																																																																																																																																													






Mode	63																																																																																																																															
	Band Edge																																																																																																																															
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz																																																																																																																															
ANT	1+2																																																																																																																															
Pol.	Vertical						Fundamental																																																																																																																									
Peak																																																																																																																																
	Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5855.00</td><td>49.69</td><td>110.80</td><td>-61.11</td><td>42.93</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>200</td><td>321</td><td>PEAK</td></tr><tr><td>2</td><td>5874.00</td><td>49.36</td><td>105.48</td><td>-56.12</td><td>42.50</td><td>34.30</td><td>8.93</td><td>36.37</td><td>0.00</td><td>200</td><td>321</td><td>PEAK</td></tr><tr><td>3</td><td>5924.25</td><td>47.53</td><td>68.75</td><td>-21.22</td><td>40.62</td><td>34.30</td><td>8.99</td><td>36.38</td><td>0.00</td><td>200</td><td>321</td><td>PEAK</td></tr><tr><td>4</td><td>5938.13</td><td>48.76</td><td>68.20</td><td>-19.44</td><td>41.87</td><td>34.28</td><td>8.99</td><td>36.38</td><td>0.00</td><td>200</td><td>321</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5855.00	49.69	110.80	-61.11	42.93	34.22	8.91	36.37	0.00	200	321	PEAK	2	5874.00	49.36	105.48	-56.12	42.50	34.30	8.93	36.37	0.00	200	321	PEAK	3	5924.25	47.53	68.75	-21.22	40.62	34.30	8.99	36.38	0.00	200	321	PEAK	4	5938.13	48.76	68.20	-19.44	41.87	34.28	8.99	36.38	0.00	200	321	PEAK	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>107.33</td><td>-----</td><td>-----</td><td>100.65</td><td>34.16</td><td>8.88</td><td>36.36</td><td>0.00</td><td>200</td><td>321</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5825.00	107.33	-----	-----	100.65	34.16	8.88	36.36	0.00	200	321
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																				
1	5855.00	49.69	110.80	-61.11	42.93	34.22	8.91	36.37	0.00	200	321	PEAK																																																																																																																				
2	5874.00	49.36	105.48	-56.12	42.50	34.30	8.93	36.37	0.00	200	321	PEAK																																																																																																																				
3	5924.25	47.53	68.75	-21.22	40.62	34.30	8.99	36.38	0.00	200	321	PEAK																																																																																																																				
4	5938.13	48.76	68.20	-19.44	41.87	34.28	8.99	36.38	0.00	200	321	PEAK																																																																																																																				
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																				
1	5825.00	107.33	-----	-----	100.65	34.16	8.88	36.36	0.00	200	321	PEAK																																																																																																																				
Avg	Blank																																																																																																																															
							Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>100.16</td><td>-----</td><td>-----</td><td>93.49</td><td>34.15</td><td>8.88</td><td>36.36</td><td>0.00</td><td>200</td><td>321</td><td>AVERAGE</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5825.00	100.16	-----	-----	93.49	34.15	8.88	36.36	0.00	200	321	AVERAGE																																																																													
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																				
1	5825.00	100.16	-----	-----	93.49	34.15	8.88	36.36	0.00	200	321	AVERAGE																																																																																																																				






Mode	63																																																																																																																		
	Harmonic																																																																																																																		
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz																																																																																																																		
ANT	1+2																																																																																																																		
Pol.	Horizontal								Vertical																																																																																																										
Peak Avg																																																																																																																			
	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>11650.00</td><td>46.14</td><td>74.00</td><td>-27.86</td><td>52.04</td><td>38.55</td><td>12.68</td><td>58.06</td><td>0.93 -- -- PEAK</td></tr><tr><td>2</td><td>17475.00</td><td>48.50</td><td>68.20</td><td>-19.70</td><td>52.67</td><td>38.50</td><td>15.61</td><td>59.22</td><td>0.94 -- -- PEAK</td></tr></tbody></table>									Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	11650.00	46.14	74.00	-27.86	52.04	38.55	12.68	58.06	0.93 -- -- PEAK	2	17475.00	48.50	68.20	-19.70	52.67	38.50	15.61	59.22	0.94 -- -- PEAK	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>11650.00</td><td>45.78</td><td>74.00</td><td>-28.22</td><td>51.68</td><td>38.55</td><td>12.68</td><td>58.06</td><td>0.93 -- -- PEAK</td></tr><tr><td>2</td><td>17475.00</td><td>48.08</td><td>68.20</td><td>-20.12</td><td>52.25</td><td>38.50</td><td>15.61</td><td>59.22</td><td>0.94 -- -- PEAK</td></tr></tbody></table>									Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	11650.00	45.78	74.00	-28.22	51.68	38.55	12.68	58.06	0.93 -- -- PEAK	2	17475.00	48.08	68.20	-20.12	52.25	38.50	15.61	59.22
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																										
1	11650.00	46.14	74.00	-27.86	52.04	38.55	12.68	58.06	0.93 -- -- PEAK																																																																																																										
2	17475.00	48.50	68.20	-19.70	52.67	38.50	15.61	59.22	0.94 -- -- PEAK																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																										
1	11650.00	45.78	74.00	-28.22	51.68	38.55	12.68	58.06	0.93 -- -- PEAK																																																																																																										
2	17475.00	48.08	68.20	-20.12	52.25	38.50	15.61	59.22	0.94 -- -- PEAK																																																																																																										





Mode	64																																																																																																																																														
	Band Edge																																																																																																																																														
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz																																																																																																																																														
ANT	1+2																																																																																																																																														
Pol.	Horizontal																																																																																																																																														
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5600.58</td><td>48.15</td><td>68.20</td><td>-20.05</td><td>42.82</td><td>33.00</td><td>8.63</td><td>36.30</td><td>0.00</td><td>223 248 PEAK</td></tr><tr><td>2</td><td>5651.19</td><td>47.67</td><td>69.08</td><td>-21.41</td><td>41.99</td><td>33.31</td><td>8.69</td><td>36.32</td><td>0.00</td><td>223 248 PEAK</td></tr><tr><td>3</td><td>5703.53</td><td>50.07</td><td>106.19</td><td>-56.12</td><td>43.95</td><td>33.71</td><td>8.74</td><td>36.33</td><td>0.00</td><td>223 248 PEAK</td></tr><tr><td>4</td><td>5720.35</td><td>52.32</td><td>111.60</td><td>-59.28</td><td>46.15</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>223 248 PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5600.58	48.15	68.20	-20.05	42.82	33.00	8.63	36.30	0.00	223 248 PEAK	2	5651.19	47.67	69.08	-21.41	41.99	33.31	8.69	36.32	0.00	223 248 PEAK	3	5703.53	50.07	106.19	-56.12	43.95	33.71	8.74	36.33	0.00	223 248 PEAK	4	5720.35	52.32	111.60	-59.28	46.15	33.74	8.76	36.33	0.00	223 248 PEAK	 Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>107.27</td><td>-----</td><td>-----</td><td>101.05</td><td>33.78</td><td>8.78</td><td>36.34</td><td>0.00</td><td>223 248 PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	107.27	-----	-----	101.05	33.78	8.78	36.34	0.00	223 248 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																					
1	5600.58	48.15	68.20	-20.05	42.82	33.00	8.63	36.30	0.00	223 248 PEAK																																																																																																																																					
2	5651.19	47.67	69.08	-21.41	41.99	33.31	8.69	36.32	0.00	223 248 PEAK																																																																																																																																					
3	5703.53	50.07	106.19	-56.12	43.95	33.71	8.74	36.33	0.00	223 248 PEAK																																																																																																																																					
4	5720.35	52.32	111.60	-59.28	46.15	33.74	8.76	36.33	0.00	223 248 PEAK																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																					
1	5745.00	107.27	-----	-----	101.05	33.78	8.78	36.34	0.00	223 248 PEAK																																																																																																																																					
Avg	Blank											 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>99.93</td><td>-----</td><td>-----</td><td>93.69</td><td>33.79</td><td>8.79</td><td>36.34</td><td>0.00</td><td>223 248 AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	99.93	-----	-----	93.69	33.79	8.79	36.34	0.00	223 248 AVERAGE																																																																													
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																					
1	5745.00	99.93	-----	-----	93.69	33.79	8.79	36.34	0.00	223 248 AVERAGE																																																																																																																																					






Mode	64																																																																																							
	Band Edge																																																																																							
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz																																																																																							
ANT	1+2																																																																																							
Pol.	Vertical																																																																																							
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5600.29</td><td>48.25</td><td>68.20</td><td>-19.95</td><td>42.92</td><td>33.00</td><td>8.63</td><td>36.30</td><td>0.00</td><td>300 311 PEAK</td></tr><tr><td>2</td><td>5650.03</td><td>46.74</td><td>68.22</td><td>-21.48</td><td>41.07</td><td>33.30</td><td>8.69</td><td>36.32</td><td>0.00</td><td>300 311 PEAK</td></tr><tr><td>3</td><td>5711.07</td><td>54.30</td><td>108.30</td><td>-54.00</td><td>48.16</td><td>33.72</td><td>8.75</td><td>36.33</td><td>0.00</td><td>300 311 PEAK</td></tr><tr><td>4</td><td>5720.06</td><td>56.13</td><td>110.94</td><td>-54.81</td><td>49.96</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>300 311 PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5600.29	48.25	68.20	-19.95	42.92	33.00	8.63	36.30	0.00	300 311 PEAK	2	5650.03	46.74	68.22	-21.48	41.07	33.30	8.69	36.32	0.00	300 311 PEAK	3	5711.07	54.30	108.30	-54.00	48.16	33.72	8.75	36.33	0.00	300 311 PEAK	4	5720.06	56.13	110.94	-54.81	49.96	33.74	8.76	36.33	0.00	300 311 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	5600.29	48.25	68.20	-19.95	42.92	33.00	8.63	36.30	0.00	300 311 PEAK																																																																														
2	5650.03	46.74	68.22	-21.48	41.07	33.30	8.69	36.32	0.00	300 311 PEAK																																																																														
3	5711.07	54.30	108.30	-54.00	48.16	33.72	8.75	36.33	0.00	300 311 PEAK																																																																														
4	5720.06	56.13	110.94	-54.81	49.96	33.74	8.76	36.33	0.00	300 311 PEAK																																																																														
Fundamental	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>111.25</td><td>-----</td><td>-----</td><td>105.01</td><td>33.79</td><td>8.79</td><td>36.34</td><td>0.00</td><td>300 311 PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	111.25	-----	-----	105.01	33.79	8.79	36.34	0.00	300 311 PEAK																																	
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	5745.00	111.25	-----	-----	105.01	33.79	8.79	36.34	0.00	300 311 PEAK																																																																														
Avg	Blank																																																																																							
	 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>103.00</td><td>-----</td><td>-----</td><td>96.76</td><td>33.79</td><td>8.79</td><td>36.34</td><td>0.00</td><td>300 311 AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	103.00	-----	-----	96.76	33.79	8.79	36.34	0.00	300 311 AVERAGE																																	
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	5745.00	103.00	-----	-----	96.76	33.79	8.79	36.34	0.00	300 311 AVERAGE																																																																														




Mode	64																																																																																																																							
	Harmonic																																																																																																																							
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz																																																																																																																							
ANT	1+2																																																																																																																							
Pol.	Horizontal						Vertical																																																																																																																	
Peak Avg																																																																																																																								
	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL						Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 VERTICAL																																																																																																																	
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 11490.00</td><td>46.35</td><td>74.00</td><td>-27.65</td><td>52.10</td><td>38.91</td><td>12.58</td><td>58.16</td><td>0.92</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2 17235.00</td><td>47.35</td><td>68.20</td><td>-20.85</td><td>52.00</td><td>38.20</td><td>15.47</td><td>59.26</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 11490.00	46.35	74.00	-27.65	52.10	38.91	12.58	58.16	0.92	--	--	PEAK	2 17235.00	47.35	68.20	-20.85	52.00	38.20	15.47	59.26	0.94	--	--	PEAK	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 11490.00</td><td>46.32</td><td>74.00</td><td>-27.68</td><td>52.07</td><td>38.91</td><td>12.58</td><td>58.16</td><td>0.92</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2 17235.00</td><td>47.93</td><td>68.20</td><td>-20.27</td><td>52.58</td><td>38.20</td><td>15.47</td><td>59.26</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 11490.00	46.32	74.00	-27.68	52.07	38.91	12.58	58.16	0.92	--	--	PEAK	2 17235.00	47.93	68.20	-20.27	52.58	38.20	15.47	59.26	0.94	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																														
1 11490.00	46.35	74.00	-27.65	52.10	38.91	12.58	58.16	0.92	--	--	PEAK																																																																																																													
2 17235.00	47.35	68.20	-20.85	52.00	38.20	15.47	59.26	0.94	--	--	PEAK																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																														
1 11490.00	46.32	74.00	-27.68	52.07	38.91	12.58	58.16	0.92	--	--	PEAK																																																																																																													
2 17235.00	47.93	68.20	-20.27	52.58	38.20	15.47	59.26	0.94	--	--	PEAK																																																																																																													






Mode	65																																																																																																																								
	Band Edge - L																																																																																																																								
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz																																																																																																																								
ANT	1+2																																																																																																																								
Pol.	Horizontal						Fundamental																																																																																																																		
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5637.37</td><td>51.22</td><td>68.20</td><td>-16.98</td><td>45.64</td><td>33.22</td><td>8.67</td><td>36.31</td><td>0.00</td><td>167 256 PEAK</td></tr><tr><td>2 5650.51</td><td>45.68</td><td>68.58</td><td>-22.90</td><td>40.01</td><td>33.30</td><td>8.69</td><td>36.32</td><td>0.00</td><td>167 256 PEAK</td></tr><tr><td>3 5700.09</td><td>47.33</td><td>105.22</td><td>-57.89</td><td>41.22</td><td>33.70</td><td>8.74</td><td>36.33</td><td>0.00</td><td>167 256 PEAK</td></tr><tr><td>4 5720.07</td><td>48.29</td><td>110.95</td><td>-62.66</td><td>42.12</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>167 256 PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5637.37	51.22	68.20	-16.98	45.64	33.22	8.67	36.31	0.00	167 256 PEAK	2 5650.51	45.68	68.58	-22.90	40.01	33.30	8.69	36.32	0.00	167 256 PEAK	3 5700.09	47.33	105.22	-57.89	41.22	33.70	8.74	36.33	0.00	167 256 PEAK	4 5720.07	48.29	110.95	-62.66	42.12	33.74	8.76	36.33	0.00	167 256 PEAK	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5785.00</td><td>110.56</td><td>-----</td><td>104.09</td><td>33.99</td><td>8.83</td><td>36.35</td><td>0.00</td><td>167</td><td>256 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5785.00	110.56	-----	104.09	33.99	8.83	36.35	0.00	167	256 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5637.37	51.22	68.20	-16.98	45.64	33.22	8.67	36.31	0.00	167 256 PEAK																																																																																																																
2 5650.51	45.68	68.58	-22.90	40.01	33.30	8.69	36.32	0.00	167 256 PEAK																																																																																																																
3 5700.09	47.33	105.22	-57.89	41.22	33.70	8.74	36.33	0.00	167 256 PEAK																																																																																																																
4 5720.07	48.29	110.95	-62.66	42.12	33.74	8.76	36.33	0.00	167 256 PEAK																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5785.00	110.56	-----	104.09	33.99	8.83	36.35	0.00	167	256 PEAK																																																																																																																
Avg	Blank						 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5785.00</td><td>101.93</td><td>-----</td><td>95.41</td><td>34.03</td><td>8.84</td><td>36.35</td><td>0.00</td><td>167</td><td>256 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5785.00	101.93	-----	95.41	34.03	8.84	36.35	0.00	167	256 AVERAGE																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5785.00	101.93	-----	95.41	34.03	8.84	36.35	0.00	167	256 AVERAGE																																																																																																																




Mode	65																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz																																																																																				
ANT	1+2																																																																																				
Pol.	Horizontal	Fundamental																																																																																			
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.63</td><td>47.28</td><td>111.64</td><td>-64.36</td><td>40.52</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>167</td><td>256</td><td>PEAK</td></tr><tr><td>2</td><td>5872.95</td><td>48.12</td><td>105.77</td><td>-57.65</td><td>41.27</td><td>34.29</td><td>8.93</td><td>36.37</td><td>0.00</td><td>167</td><td>256</td><td>PEAK</td></tr><tr><td>3</td><td>5924.76</td><td>45.59</td><td>68.38</td><td>-22.79</td><td>38.68</td><td>34.30</td><td>8.99</td><td>36.38</td><td>0.00</td><td>167</td><td>256</td><td>PEAK</td></tr><tr><td>4</td><td>5926.90</td><td>48.06</td><td>68.20</td><td>-20.14</td><td>41.16</td><td>34.29</td><td>8.99</td><td>36.38</td><td>0.00</td><td>167</td><td>256</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5854.63	47.28	111.64	-64.36	40.52	34.22	8.91	36.37	0.00	167	256	PEAK	2	5872.95	48.12	105.77	-57.65	41.27	34.29	8.93	36.37	0.00	167	256	PEAK	3	5924.76	45.59	68.38	-22.79	38.68	34.30	8.99	36.38	0.00	167	256	PEAK	4	5926.90	48.06	68.20	-20.14	41.16	34.29	8.99	36.38	0.00	167	256	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																													
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																											
1	5854.63	47.28	111.64	-64.36	40.52	34.22	8.91	36.37	0.00	167	256	PEAK																																																																									
2	5872.95	48.12	105.77	-57.65	41.27	34.29	8.93	36.37	0.00	167	256	PEAK																																																																									
3	5924.76	45.59	68.38	-22.79	38.68	34.30	8.99	36.38	0.00	167	256	PEAK																																																																									
4	5926.90	48.06	68.20	-20.14	41.16	34.29	8.99	36.38	0.00	167	256	PEAK																																																																									





Mode	65																																																																																																																								
	Band Edge - L																																																																																																																								
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz																																																																																																																								
ANT	1+2																																																																																																																								
Pol.	Vertical						Fundamental																																																																																																																		
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5628.12</td><td>50.73</td><td>68.20</td><td>-17.47</td><td>45.21</td><td>33.17</td><td>8.66</td><td>36.31</td><td>0.00</td><td>100 7 PEAK</td></tr><tr><td>2 5651.25</td><td>46.59</td><td>69.13</td><td>-22.54</td><td>40.91</td><td>33.31</td><td>8.69</td><td>36.32</td><td>0.00</td><td>100 7 PEAK</td></tr><tr><td>3 5701.94</td><td>48.66</td><td>105.74</td><td>-57.08</td><td>42.55</td><td>33.70</td><td>8.74</td><td>36.33</td><td>0.00</td><td>100 7 PEAK</td></tr><tr><td>4 5728.07</td><td>47.76</td><td>110.95</td><td>-63.19</td><td>41.59</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>100 7 PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5628.12	50.73	68.20	-17.47	45.21	33.17	8.66	36.31	0.00	100 7 PEAK	2 5651.25	46.59	69.13	-22.54	40.91	33.31	8.69	36.32	0.00	100 7 PEAK	3 5701.94	48.66	105.74	-57.08	42.55	33.70	8.74	36.33	0.00	100 7 PEAK	4 5728.07	47.76	110.95	-63.19	41.59	33.74	8.76	36.33	0.00	100 7 PEAK	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5785.00</td><td>112.65</td><td>-----</td><td>-----</td><td>106.13</td><td>34.03</td><td>8.84</td><td>36.35</td><td>0.00</td><td>100 7 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5785.00	112.65	-----	-----	106.13	34.03	8.84	36.35	0.00	100 7 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5628.12	50.73	68.20	-17.47	45.21	33.17	8.66	36.31	0.00	100 7 PEAK																																																																																																																
2 5651.25	46.59	69.13	-22.54	40.91	33.31	8.69	36.32	0.00	100 7 PEAK																																																																																																																
3 5701.94	48.66	105.74	-57.08	42.55	33.70	8.74	36.33	0.00	100 7 PEAK																																																																																																																
4 5728.07	47.76	110.95	-63.19	41.59	33.74	8.76	36.33	0.00	100 7 PEAK																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5785.00	112.65	-----	-----	106.13	34.03	8.84	36.35	0.00	100 7 PEAK																																																																																																																
Avg	Blank						 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5785.00</td><td>104.32</td><td>-----</td><td>-----</td><td>97.80</td><td>34.03</td><td>8.84</td><td>36.35</td><td>0.00</td><td>100 7 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5785.00	104.32	-----	-----	97.80	34.03	8.84	36.35	0.00	100 7 AVERAGE																																																																						
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5785.00	104.32	-----	-----	97.80	34.03	8.84	36.35	0.00	100 7 AVERAGE																																																																																																																






Mode	65																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz																																																																							
ANT	1+2																																																																							
Pol.	Vertical	Fundamental																																																																						
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5854.80</td><td>47.19</td><td>111.27</td><td>-64.08</td><td>40.43</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>100 7 PEAK</td></tr><tr><td>2 5870.14</td><td>49.61</td><td>106.56</td><td>-56.95</td><td>42.77</td><td>34.28</td><td>8.93</td><td>36.37</td><td>0.00</td><td>100 7 PEAK</td></tr><tr><td>3 5924.59</td><td>46.71</td><td>68.50</td><td>-21.79</td><td>39.80</td><td>34.30</td><td>8.99</td><td>36.38</td><td>0.00</td><td>100 7 PEAK</td></tr><tr><td>4 5927.73</td><td>47.60</td><td>68.20</td><td>-20.60</td><td>40.70</td><td>34.29</td><td>8.99</td><td>36.38</td><td>0.00</td><td>100 7 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5854.80	47.19	111.27	-64.08	40.43	34.22	8.91	36.37	0.00	100 7 PEAK	2 5870.14	49.61	106.56	-56.95	42.77	34.28	8.93	36.37	0.00	100 7 PEAK	3 5924.59	46.71	68.50	-21.79	39.80	34.30	8.99	36.38	0.00	100 7 PEAK	4 5927.73	47.60	68.20	-20.60	40.70	34.29	8.99	36.38	0.00	100 7 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																															
1 5854.80	47.19	111.27	-64.08	40.43	34.22	8.91	36.37	0.00	100 7 PEAK																																																															
2 5870.14	49.61	106.56	-56.95	42.77	34.28	8.93	36.37	0.00	100 7 PEAK																																																															
3 5924.59	46.71	68.50	-21.79	39.80	34.30	8.99	36.38	0.00	100 7 PEAK																																																															
4 5927.73	47.60	68.20	-20.60	40.70	34.29	8.99	36.38	0.00	100 7 PEAK																																																															






Mode	65																																																																	
	Harmonic																																																																	
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz																																																																	
ANT	1+2																																																																	
Pol.	Horizontal						Vertical																																																											
Peak Avg																																																																		
	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL						Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 VERTICAL																																																											
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11570.00</td><td>45.77</td><td>74.00</td><td>-28.23</td><td>51.71</td><td>38.62</td><td>12.63</td><td>58.11</td><td>0.92</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17355.00</td><td>46.95</td><td>68.20</td><td>-21.25</td><td>51.34</td><td>38.37</td><td>15.54</td><td>59.24</td><td>0.94</td><td>--</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11570.00	45.77	74.00	-28.23	51.71	38.62	12.63	58.11	0.92	--	PEAK	2	17355.00	46.95	68.20	-21.25	51.34	38.37	15.54	59.24	0.94	--	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																								
1	11570.00	45.77	74.00	-28.23	51.71	38.62	12.63	58.11	0.92	--	PEAK																																																							
2	17355.00	46.95	68.20	-21.25	51.34	38.37	15.54	59.24	0.94	--	PEAK																																																							





Mode	66																																																																																																																																										
	Band Edge																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz																																																																																																																																										
ANT	1+2																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5855.00</td><td>47.90</td><td>110.80</td><td>-62.90</td><td>41.14</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>300</td><td>237</td><td>PEAK</td></tr><tr><td>2</td><td>5874.13</td><td>48.87</td><td>105.44</td><td>-56.57</td><td>42.01</td><td>34.30</td><td>8.93</td><td>36.37</td><td>0.00</td><td>300</td><td>237</td><td>PEAK</td></tr><tr><td>3</td><td>5925.00</td><td>47.06</td><td>68.20</td><td>-21.14</td><td>40.15</td><td>34.30</td><td>8.99</td><td>36.38</td><td>0.00</td><td>300</td><td>237</td><td>PEAK</td></tr><tr><td>4</td><td>5935.50</td><td>48.23</td><td>68.20</td><td>-19.97</td><td>41.35</td><td>34.26</td><td>9.00</td><td>36.38</td><td>0.00</td><td>300</td><td>237</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5855.00	47.90	110.80	-62.90	41.14	34.22	8.91	36.37	0.00	300	237	PEAK	2	5874.13	48.87	105.44	-56.57	42.01	34.30	8.93	36.37	0.00	300	237	PEAK	3	5925.00	47.06	68.20	-21.14	40.15	34.30	8.99	36.38	0.00	300	237	PEAK	4	5935.50	48.23	68.20	-19.97	41.35	34.26	9.00	36.38	0.00	300	237	PEAK	 Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>106.62</td><td>-----</td><td>-----</td><td>99.94</td><td>34.16</td><td>8.88</td><td>36.36</td><td>0.00</td><td>300</td><td>237</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	106.62	-----	-----	99.94	34.16	8.88	36.36	0.00	300	237	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5855.00	47.90	110.80	-62.90	41.14	34.22	8.91	36.37	0.00	300	237	PEAK																																																																																																																															
2	5874.13	48.87	105.44	-56.57	42.01	34.30	8.93	36.37	0.00	300	237	PEAK																																																																																																																															
3	5925.00	47.06	68.20	-21.14	40.15	34.30	8.99	36.38	0.00	300	237	PEAK																																																																																																																															
4	5935.50	48.23	68.20	-19.97	41.35	34.26	9.00	36.38	0.00	300	237	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	106.62	-----	-----	99.94	34.16	8.88	36.36	0.00	300	237	PEAK																																																																																																																															
Avg	Blank						 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>100.09</td><td>-----</td><td>-----</td><td>93.41</td><td>34.16</td><td>8.88</td><td>36.36</td><td>0.00</td><td>300</td><td>237</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	100.09	-----	-----	93.41	34.16	8.88	36.36	0.00	300	237	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	100.09	-----	-----	93.41	34.16	8.88	36.36	0.00	300	237	AVERAGE																																																																																																																															






Mode	66																																																																																							
	Band Edge																																																																																							
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz																																																																																							
ANT	1+2																																																																																							
Pol.	Vertical																																																																																							
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.88</td><td>50.71</td><td>111.08</td><td>-60.37</td><td>43.95</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>200 328 PEAK</td></tr><tr><td>2</td><td>5867.63</td><td>49.97</td><td>107.26</td><td>-57.29</td><td>43.15</td><td>34.27</td><td>8.92</td><td>36.37</td><td>0.00</td><td>200 328 PEAK</td></tr><tr><td>3</td><td>5924.25</td><td>47.06</td><td>68.75</td><td>-21.69</td><td>40.15</td><td>34.30</td><td>8.99</td><td>36.38</td><td>0.00</td><td>200 328 PEAK</td></tr><tr><td>4</td><td>5933.25</td><td>48.15</td><td>68.20</td><td>-20.05</td><td>41.26</td><td>34.27</td><td>9.00</td><td>36.38</td><td>0.00</td><td>200 328 PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.88	50.71	111.08	-60.37	43.95	34.22	8.91	36.37	0.00	200 328 PEAK	2	5867.63	49.97	107.26	-57.29	43.15	34.27	8.92	36.37	0.00	200 328 PEAK	3	5924.25	47.06	68.75	-21.69	40.15	34.30	8.99	36.38	0.00	200 328 PEAK	4	5933.25	48.15	68.20	-20.05	41.26	34.27	9.00	36.38	0.00	200 328 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	5854.88	50.71	111.08	-60.37	43.95	34.22	8.91	36.37	0.00	200 328 PEAK																																																																														
2	5867.63	49.97	107.26	-57.29	43.15	34.27	8.92	36.37	0.00	200 328 PEAK																																																																														
3	5924.25	47.06	68.75	-21.69	40.15	34.30	8.99	36.38	0.00	200 328 PEAK																																																																														
4	5933.25	48.15	68.20	-20.05	41.26	34.27	9.00	36.38	0.00	200 328 PEAK																																																																														
Fundamental	 Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>107.66</td><td>-----</td><td>-----</td><td>101.01</td><td>34.14</td><td>8.87</td><td>36.36</td><td>0.00</td><td>200 328 PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	107.66	-----	-----	101.01	34.14	8.87	36.36	0.00	200 328 PEAK																																	
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	5825.00	107.66	-----	-----	101.01	34.14	8.87	36.36	0.00	200 328 PEAK																																																																														
Avg	Blank																																																																																							
	 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>100.42</td><td>-----</td><td>-----</td><td>93.74</td><td>34.16</td><td>8.88</td><td>36.36</td><td>0.00</td><td>200 328 AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	100.42	-----	-----	93.74	34.16	8.88	36.36	0.00	200 328 AVERAGE																																	
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	5825.00	100.42	-----	-----	93.74	34.16	8.88	36.36	0.00	200 328 AVERAGE																																																																														




Mode	66																																																																																																															
	Harmonic																																																																																																															
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz																																																																																																															
ANT	1+2																																																																																																															
Pol.	Horizontal	Vertical																																																																																																														
Peak Avg	 Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11650.00</td><td>45.68</td><td>74.00</td><td>-28.32</td><td>51.58</td><td>38.55</td><td>12.68</td><td>58.06</td><td>0.93</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17475.00</td><td>47.57</td><td>68.20</td><td>-20.63</td><td>51.74</td><td>38.50</td><td>15.61</td><td>59.22</td><td>0.94</td><td>--</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11650.00	45.68	74.00	-28.32	51.58	38.55	12.68	58.06	0.93	--	PEAK	2	17475.00	47.57	68.20	-20.63	51.74	38.50	15.61	59.22	0.94	--	PEAK	 Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11650.00</td><td>45.95</td><td>74.00</td><td>-28.05</td><td>51.85</td><td>38.55</td><td>12.68</td><td>58.06</td><td>0.93</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17475.00</td><td>48.70</td><td>68.20</td><td>-19.50</td><td>52.87</td><td>38.50</td><td>15.61</td><td>59.22</td><td>0.94</td><td>--</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11650.00	45.95	74.00	-28.05	51.85	38.55	12.68	58.06	0.93	--	PEAK	2	17475.00	48.70	68.20	-19.50	52.87	38.50	15.61	59.22	0.94	--	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	11650.00	45.68	74.00	-28.32	51.58	38.55	12.68	58.06	0.93	--	PEAK																																																																																																					
2	17475.00	47.57	68.20	-20.63	51.74	38.50	15.61	59.22	0.94	--	PEAK																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	11650.00	45.95	74.00	-28.05	51.85	38.55	12.68	58.06	0.93	--	PEAK																																																																																																					
2	17475.00	48.70	68.20	-19.50	52.87	38.50	15.61	59.22	0.94	--	PEAK																																																																																																					






Mode	67																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																																																																																										
ANT	1+2																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5619.07</td><td>50.90</td><td>68.20</td><td>-17.30</td><td>45.45</td><td>33.11</td><td>8.65</td><td>36.31</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr><tr><td>2</td><td>5651.46</td><td>48.94</td><td>69.29</td><td>-20.35</td><td>43.26</td><td>33.31</td><td>8.69</td><td>36.32</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr><tr><td>3</td><td>5709.90</td><td>56.69</td><td>107.97</td><td>-51.28</td><td>50.55</td><td>33.72</td><td>8.75</td><td>36.33</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr><tr><td>4</td><td>5720.28</td><td>56.86</td><td>111.44</td><td>-54.58</td><td>50.69</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5619.07	50.90	68.20	-17.30	45.45	33.11	8.65	36.31	0.00	200	243	PEAK	2	5651.46	48.94	69.29	-20.35	43.26	33.31	8.69	36.32	0.00	200	243	PEAK	3	5709.90	56.69	107.97	-51.28	50.55	33.72	8.75	36.33	0.00	200	243	PEAK	4	5720.28	56.86	111.44	-54.58	50.69	33.74	8.76	36.33	0.00	200	243	PEAK	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5755.00</td><td>105.71</td><td>-----</td><td>-----</td><td>99.44</td><td>33.81</td><td>8.80</td><td>36.34</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	105.71	-----	-----	99.44	33.81	8.80	36.34	0.00	200	243	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5619.07	50.90	68.20	-17.30	45.45	33.11	8.65	36.31	0.00	200	243	PEAK																																																																																																																															
2	5651.46	48.94	69.29	-20.35	43.26	33.31	8.69	36.32	0.00	200	243	PEAK																																																																																																																															
3	5709.90	56.69	107.97	-51.28	50.55	33.72	8.75	36.33	0.00	200	243	PEAK																																																																																																																															
4	5720.28	56.86	111.44	-54.58	50.69	33.74	8.76	36.33	0.00	200	243	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5755.00	105.71	-----	-----	99.44	33.81	8.80	36.34	0.00	200	243	PEAK																																																																																																																															
Avg	Blank						 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5755.00</td><td>97.07</td><td>-----</td><td>-----</td><td>90.80</td><td>33.81</td><td>8.80</td><td>36.34</td><td>0.00</td><td>200</td><td>243</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	97.07	-----	-----	90.80	33.81	8.80	36.34	0.00	200	243	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5755.00	97.07	-----	-----	90.80	33.81	8.80	36.34	0.00	200	243	AVERAGE																																																																																																																															




Mode	67																																																																																
	Band Edge - R																																																																																
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																																
ANT	1+2																																																																																
Pol.	Horizontal	Fundamental																																																																															
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5854.84</td><td>46.69</td><td>111.17</td><td>-64.48</td><td>39.93</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr><tr><td>2 5872.59</td><td>48.09</td><td>105.88</td><td>-57.79</td><td>41.24</td><td>34.29</td><td>8.93</td><td>36.37</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr><tr><td>3 5924.85</td><td>47.43</td><td>68.31</td><td>-20.88</td><td>40.52</td><td>34.30</td><td>8.99</td><td>36.38</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr><tr><td>4 5941.23</td><td>47.09</td><td>68.20</td><td>-21.11</td><td>40.23</td><td>34.24</td><td>9.01</td><td>36.39</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 5854.84	46.69	111.17	-64.48	39.93	34.22	8.91	36.37	0.00	200	243	PEAK	2 5872.59	48.09	105.88	-57.79	41.24	34.29	8.93	36.37	0.00	200	243	PEAK	3 5924.85	47.43	68.31	-20.88	40.52	34.30	8.99	36.38	0.00	200	243	PEAK	4 5941.23	47.09	68.20	-21.11	40.23	34.24	9.01	36.39	0.00	200	243	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																							
1 5854.84	46.69	111.17	-64.48	39.93	34.22	8.91	36.37	0.00	200	243	PEAK																																																																						
2 5872.59	48.09	105.88	-57.79	41.24	34.29	8.93	36.37	0.00	200	243	PEAK																																																																						
3 5924.85	47.43	68.31	-20.88	40.52	34.30	8.99	36.38	0.00	200	243	PEAK																																																																						
4 5941.23	47.09	68.20	-21.11	40.23	34.24	9.01	36.39	0.00	200	243	PEAK																																																																						





		67																																																																																																																																													
Mode	Band Edge - L																																																																																																																																														
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																																																																																														
ANT	1+2																																																																																																																																														
Pol.	Vertical																																																																																																																																														
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5617.05</td><td>50.74</td><td>68.20</td><td>-17.46</td><td>45.30</td><td>33.10</td><td>8.65</td><td>36.31</td><td>0.00</td><td>100 3 PEAK</td></tr><tr><td>2</td><td>5651.62</td><td>49.24</td><td>69.40</td><td>-20.16</td><td>43.56</td><td>33.31</td><td>8.69</td><td>36.32</td><td>0.00</td><td>100 3 PEAK</td></tr><tr><td>3</td><td>5709.59</td><td>59.91</td><td>107.89</td><td>-47.98</td><td>53.77</td><td>33.72</td><td>8.75</td><td>36.33</td><td>0.00</td><td>100 3 PEAK</td></tr><tr><td>4</td><td>5720.75</td><td>61.41</td><td>112.50</td><td>-51.09</td><td>55.24</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>100 3 PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5617.05	50.74	68.20	-17.46	45.30	33.10	8.65	36.31	0.00	100 3 PEAK	2	5651.62	49.24	69.40	-20.16	43.56	33.31	8.69	36.32	0.00	100 3 PEAK	3	5709.59	59.91	107.89	-47.98	53.77	33.72	8.75	36.33	0.00	100 3 PEAK	4	5720.75	61.41	112.50	-51.09	55.24	33.74	8.76	36.33	0.00	100 3 PEAK	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5755.00</td><td>100.61</td><td>-----</td><td>-----</td><td>102.50</td><td>33.85</td><td>8.80</td><td>36.34</td><td>0.00</td><td>100 3 PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	100.61	-----	-----	102.50	33.85	8.80	36.34	0.00	100 3 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																					
1	5617.05	50.74	68.20	-17.46	45.30	33.10	8.65	36.31	0.00	100 3 PEAK																																																																																																																																					
2	5651.62	49.24	69.40	-20.16	43.56	33.31	8.69	36.32	0.00	100 3 PEAK																																																																																																																																					
3	5709.59	59.91	107.89	-47.98	53.77	33.72	8.75	36.33	0.00	100 3 PEAK																																																																																																																																					
4	5720.75	61.41	112.50	-51.09	55.24	33.74	8.76	36.33	0.00	100 3 PEAK																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																					
1	5755.00	100.61	-----	-----	102.50	33.85	8.80	36.34	0.00	100 3 PEAK																																																																																																																																					
Avg	Blank											 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5755.00</td><td>100.13</td><td>-----</td><td>-----</td><td>93.82</td><td>33.85</td><td>8.80</td><td>36.34</td><td>0.00</td><td>100 3 AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	100.13	-----	-----	93.82	33.85	8.80	36.34	0.00	100 3 AVERAGE																																																																													
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																					
1	5755.00	100.13	-----	-----	93.82	33.85	8.80	36.34	0.00	100 3 AVERAGE																																																																																																																																					






Mode	67																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																							
ANT	1+2																																																																							
Pol.	Vertical	Fundamental																																																																						
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5854.06</td><td>47.77</td><td>112.94</td><td>-65.17</td><td>41.00</td><td>34.22</td><td>8.91</td><td>36.36</td><td>0.00</td><td>100 3 PEAK</td></tr><tr><td>2 5873.76</td><td>47.52</td><td>105.55</td><td>-58.03</td><td>40.66</td><td>34.30</td><td>8.93</td><td>36.37</td><td>0.00</td><td>100 3 PEAK</td></tr><tr><td>3 5923.68</td><td>47.17</td><td>69.18</td><td>-22.01</td><td>40.25</td><td>34.31</td><td>8.99</td><td>36.38</td><td>0.00</td><td>100 3 PEAK</td></tr><tr><td>4 5929.72</td><td>47.62</td><td>68.20</td><td>-20.58</td><td>40.73</td><td>34.28</td><td>8.99</td><td>36.38</td><td>0.00</td><td>100 3 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5854.06	47.77	112.94	-65.17	41.00	34.22	8.91	36.36	0.00	100 3 PEAK	2 5873.76	47.52	105.55	-58.03	40.66	34.30	8.93	36.37	0.00	100 3 PEAK	3 5923.68	47.17	69.18	-22.01	40.25	34.31	8.99	36.38	0.00	100 3 PEAK	4 5929.72	47.62	68.20	-20.58	40.73	34.28	8.99	36.38	0.00	100 3 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																															
1 5854.06	47.77	112.94	-65.17	41.00	34.22	8.91	36.36	0.00	100 3 PEAK																																																															
2 5873.76	47.52	105.55	-58.03	40.66	34.30	8.93	36.37	0.00	100 3 PEAK																																																															
3 5923.68	47.17	69.18	-22.01	40.25	34.31	8.99	36.38	0.00	100 3 PEAK																																																															
4 5929.72	47.62	68.20	-20.58	40.73	34.28	8.99	36.38	0.00	100 3 PEAK																																																															




Mode	67																																																																		
	Harmonic																																																																		
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																		
ANT	1+2																																																																		
Pol.	Horizontal						Vertical																																																												
Peak Avg																																																																			
	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL																																																																		
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11510.00</td><td>46.45</td><td>74.00</td><td>-27.55</td><td>52.21</td><td>38.06</td><td>12.60</td><td>58.14</td><td>0.92</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17265.00</td><td>47.36</td><td>68.20</td><td>-20.84</td><td>51.99</td><td>38.20</td><td>15.49</td><td>59.26</td><td>0.94</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr></table>													Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11510.00	46.45	74.00	-27.55	52.21	38.06	12.60	58.14	0.92	--	--	--	PEAK	2	17265.00	47.36	68.20	-20.84	51.99	38.20	15.49	59.26	0.94	--	--	--
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																							
1	11510.00	46.45	74.00	-27.55	52.21	38.06	12.60	58.14	0.92	--	--	--	PEAK																																																						
2	17265.00	47.36	68.20	-20.84	51.99	38.20	15.49	59.26	0.94	--	--	--	PEAK																																																						
Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 VERTICAL																																																																			
<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11510.00</td><td>46.22</td><td>74.00</td><td>-27.78</td><td>51.98</td><td>38.06</td><td>12.60</td><td>58.14</td><td>0.92</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17265.00</td><td>47.55</td><td>68.20</td><td>-20.65</td><td>52.18</td><td>38.20</td><td>15.49</td><td>59.26</td><td>0.94</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr></table>													Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11510.00	46.22	74.00	-27.78	51.98	38.06	12.60	58.14	0.92	--	--	--	PEAK	2	17265.00	47.55	68.20	-20.65	52.18	38.20	15.49	59.26	0.94	--	--	--	PEAK
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																							
1	11510.00	46.22	74.00	-27.78	51.98	38.06	12.60	58.14	0.92	--	--	--	PEAK																																																						
2	17265.00	47.55	68.20	-20.65	52.18	38.20	15.49	59.26	0.94	--	--	--	PEAK																																																						






Mode	68																																																																																																																																																								
	Band Edge - L																																																																																																																																																								
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																																																																																								
ANT	1+2																																																																																																																																																								
Pol.	Horizontal																																																																																																																																																								
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th><th></th></tr><tr><td>1</td><td>5636.27</td><td>49.65</td><td>68.20</td><td>-18.55</td><td>44.07</td><td>33.22</td><td>8.67</td><td>36.31</td><td>0.00</td><td>100</td><td>253</td><td>PEAK</td></tr><tr><td>2</td><td>5651.48</td><td>50.16</td><td>69.30</td><td>-19.14</td><td>44.48</td><td>33.31</td><td>8.69</td><td>36.32</td><td>0.00</td><td>100</td><td>253</td><td>PEAK</td></tr><tr><td>3</td><td>5700.62</td><td>48.28</td><td>105.37</td><td>-57.09</td><td>42.17</td><td>33.70</td><td>8.74</td><td>36.33</td><td>0.00</td><td>100</td><td>253</td><td>PEAK</td></tr><tr><td>4</td><td>5720.12</td><td>48.82</td><td>111.07</td><td>-62.25</td><td>42.65</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>100</td><td>253</td><td>PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB			1	5636.27	49.65	68.20	-18.55	44.07	33.22	8.67	36.31	0.00	100	253	PEAK	2	5651.48	50.16	69.30	-19.14	44.48	33.31	8.69	36.32	0.00	100	253	PEAK	3	5700.62	48.28	105.37	-57.09	42.17	33.70	8.74	36.33	0.00	100	253	PEAK	4	5720.12	48.82	111.07	-62.25	42.65	33.74	8.76	36.33	0.00	100	253	PEAK	 Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th><th></th></tr><tr><td>1</td><td>5795.00</td><td>105.48</td><td>-----</td><td>-----</td><td>98.06</td><td>34.11</td><td>8.86</td><td>36.35</td><td>0.00</td><td>100</td><td>253</td><td>PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB			1	5795.00	105.48	-----	-----	98.06	34.11	8.86	36.35	0.00	100	253	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																															
	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg																																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																																																																																	
1	5636.27	49.65	68.20	-18.55	44.07	33.22	8.67	36.31	0.00	100	253	PEAK																																																																																																																																													
2	5651.48	50.16	69.30	-19.14	44.48	33.31	8.69	36.32	0.00	100	253	PEAK																																																																																																																																													
3	5700.62	48.28	105.37	-57.09	42.17	33.70	8.74	36.33	0.00	100	253	PEAK																																																																																																																																													
4	5720.12	48.82	111.07	-62.25	42.65	33.74	8.76	36.33	0.00	100	253	PEAK																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg																																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																																																																																	
1	5795.00	105.48	-----	-----	98.06	34.11	8.86	36.35	0.00	100	253	PEAK																																																																																																																																													
Avg	Blank																																																																																																																																																								
	 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th><th></th></tr><tr><td>1</td><td>5795.00</td><td>98.48</td><td>-----</td><td>-----</td><td>91.93</td><td>34.06</td><td>8.84</td><td>36.35</td><td>0.00</td><td>100</td><td>253</td><td>AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB			1	5795.00	98.48	-----	-----	91.93	34.06	8.84	36.35	0.00	100	253	AVERAGE																																																																																																
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																															
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg																																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																																																																																	
1	5795.00	98.48	-----	-----	91.93	34.06	8.84	36.35	0.00	100	253	AVERAGE																																																																																																																																													




Mode	68																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																				
ANT	1+2																																																																																				
Pol.	Horizontal	Fundamental																																																																																			
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.99</td><td>53.25</td><td>110.83</td><td>-57.58</td><td>46.49</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>100</td><td>253</td><td>PEAK</td></tr><tr><td>2</td><td>5856.23</td><td>57.26</td><td>110.46</td><td>-53.20</td><td>50.50</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>100</td><td>253</td><td>PEAK</td></tr><tr><td>3</td><td>5924.74</td><td>46.56</td><td>68.40</td><td>-21.84</td><td>39.65</td><td>34.30</td><td>8.99</td><td>36.38</td><td>0.00</td><td>100</td><td>253</td><td>PEAK</td></tr><tr><td>4</td><td>5935.90</td><td>48.90</td><td>68.20</td><td>-19.30</td><td>42.02</td><td>34.26</td><td>9.00</td><td>36.38</td><td>0.00</td><td>100</td><td>253</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5854.99	53.25	110.83	-57.58	46.49	34.22	8.91	36.37	0.00	100	253	PEAK	2	5856.23	57.26	110.46	-53.20	50.50	34.22	8.91	36.37	0.00	100	253	PEAK	3	5924.74	46.56	68.40	-21.84	39.65	34.30	8.99	36.38	0.00	100	253	PEAK	4	5935.90	48.90	68.20	-19.30	42.02	34.26	9.00	36.38	0.00	100	253	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																													
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																											
1	5854.99	53.25	110.83	-57.58	46.49	34.22	8.91	36.37	0.00	100	253	PEAK																																																																									
2	5856.23	57.26	110.46	-53.20	50.50	34.22	8.91	36.37	0.00	100	253	PEAK																																																																									
3	5924.74	46.56	68.40	-21.84	39.65	34.30	8.99	36.38	0.00	100	253	PEAK																																																																									
4	5935.90	48.90	68.20	-19.30	42.02	34.26	9.00	36.38	0.00	100	253	PEAK																																																																									





Mode	68																																																																																							
	Band Edge - L																																																																																							
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																							
ANT	1+2																																																																																							
Pol.	Vertical																																																																																							
Peak	 Level (dBuV/m) Frequency (MHz) PEAK_BE(B4)_16-24 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5645.24</td><td>52.16</td><td>68.20</td><td>-16.04</td><td>46.52</td><td>33.27</td><td>8.68</td><td>36.31</td><td>0.00</td><td>100 7 PEAK</td></tr><tr><td>2</td><td>5654.99</td><td>51.85</td><td>71.91</td><td>-20.06</td><td>46.14</td><td>33.34</td><td>8.69</td><td>36.32</td><td>0.00</td><td>100 7 PEAK</td></tr><tr><td>3</td><td>5708.42</td><td>55.83</td><td>107.56</td><td>-51.73</td><td>49.69</td><td>33.72</td><td>8.75</td><td>36.33</td><td>0.00</td><td>100 7 PEAK</td></tr><tr><td>4</td><td>5728.12</td><td>52.10</td><td>111.07</td><td>-58.97</td><td>45.93</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>100 7 PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5645.24	52.16	68.20	-16.04	46.52	33.27	8.68	36.31	0.00	100 7 PEAK	2	5654.99	51.85	71.91	-20.06	46.14	33.34	8.69	36.32	0.00	100 7 PEAK	3	5708.42	55.83	107.56	-51.73	49.69	33.72	8.75	36.33	0.00	100 7 PEAK	4	5728.12	52.10	111.07	-58.97	45.93	33.74	8.76	36.33	0.00	100 7 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	5645.24	52.16	68.20	-16.04	46.52	33.27	8.68	36.31	0.00	100 7 PEAK																																																																														
2	5654.99	51.85	71.91	-20.06	46.14	33.34	8.69	36.32	0.00	100 7 PEAK																																																																														
3	5708.42	55.83	107.56	-51.73	49.69	33.72	8.75	36.33	0.00	100 7 PEAK																																																																														
4	5728.12	52.10	111.07	-58.97	45.93	33.74	8.76	36.33	0.00	100 7 PEAK																																																																														
Fundamental	 Level (dBuV/m) Frequency (MHz) PEAK(UNI) Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>108.01</td><td>-----</td><td>-----</td><td>101.49</td><td>34.03</td><td>8.84</td><td>36.35</td><td>0.00</td><td>100 7 PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	108.01	-----	-----	101.49	34.03	8.84	36.35	0.00	100 7 PEAK																																	
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	5795.00	108.01	-----	-----	101.49	34.03	8.84	36.35	0.00	100 7 PEAK																																																																														
Avg	Blank																																																																																							
	 Level (dBuV/m) Frequency (MHz) AVG_54 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>101.23</td><td>-----</td><td>-----</td><td>94.71</td><td>34.03</td><td>8.84</td><td>36.35</td><td>0.00</td><td>100 7 AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	101.23	-----	-----	94.71	34.03	8.84	36.35	0.00	100 7 AVERAGE																																	
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	5795.00	101.23	-----	-----	94.71	34.03	8.84	36.35	0.00	100 7 AVERAGE																																																																														






Mode	68																																																																																	
	Band Edge - R																																																																																	
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																	
ANT	1+2																																																																																	
Pol.	Vertical	Fundamental																																																																																
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5854.99</td><td>57.04</td><td>110.83</td><td>-53.79</td><td>50.28</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>100</td><td>7</td><td>PEAK</td></tr><tr><td>2</td><td>5874.52</td><td>52.78</td><td>105.34</td><td>-52.56</td><td>45.92</td><td>34.30</td><td>8.93</td><td>36.37</td><td>0.00</td><td>100</td><td>7</td><td>PEAK</td></tr><tr><td>3</td><td>5923.34</td><td>49.39</td><td>69.42</td><td>-20.03</td><td>42.47</td><td>34.31</td><td>8.99</td><td>36.38</td><td>0.00</td><td>100</td><td>7</td><td>PEAK</td></tr><tr><td>4</td><td>5938.38</td><td>49.38</td><td>68.20</td><td>-18.82</td><td>42.52</td><td>34.25</td><td>9.00</td><td>36.39</td><td>0.00</td><td>100</td><td>7</td><td>PEAK</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5854.99	57.04	110.83	-53.79	50.28	34.22	8.91	36.37	0.00	100	7	PEAK	2	5874.52	52.78	105.34	-52.56	45.92	34.30	8.93	36.37	0.00	100	7	PEAK	3	5923.34	49.39	69.42	-20.03	42.47	34.31	8.99	36.38	0.00	100	7	PEAK	4	5938.38	49.38	68.20	-18.82	42.52	34.25	9.00	36.39	0.00	100	7	PEAK	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																						
1	5854.99	57.04	110.83	-53.79	50.28	34.22	8.91	36.37	0.00	100	7	PEAK																																																																						
2	5874.52	52.78	105.34	-52.56	45.92	34.30	8.93	36.37	0.00	100	7	PEAK																																																																						
3	5923.34	49.39	69.42	-20.03	42.47	34.31	8.99	36.38	0.00	100	7	PEAK																																																																						
4	5938.38	49.38	68.20	-18.82	42.52	34.25	9.00	36.39	0.00	100	7	PEAK																																																																						




Mode	68																																																																																																																	
	Harmonic																																																																																																																	
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																																																	
ANT	1+2																																																																																																																	
Pol.	Horizontal	Vertical																																																																																																																
Peak Avg	 Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>11590.00</td><td>46.03</td><td>74.00</td><td>-27.97</td><td>52.00</td><td>38.54</td><td>12.65</td><td>58.09</td><td>0.93</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17385.00</td><td>48.18</td><td>68.20</td><td>-20.02</td><td>52.45</td><td>38.46</td><td>15.56</td><td>59.23</td><td>0.94</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr></tbody></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11590.00	46.03	74.00	-27.97	52.00	38.54	12.65	58.09	0.93	--	--	--	PEAK	2	17385.00	48.18	68.20	-20.02	52.45	38.46	15.56	59.23	0.94	--	--	--	PEAK	 Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 VERTICAL <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>11590.00</td><td>46.12</td><td>74.00</td><td>-27.88</td><td>52.09</td><td>38.54</td><td>12.65</td><td>58.09</td><td>0.93</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17385.00</td><td>48.41</td><td>68.20</td><td>-19.79</td><td>52.68</td><td>38.46</td><td>15.56</td><td>59.23</td><td>0.94</td><td>--</td><td>--</td><td>--</td><td>PEAK</td></tr></tbody></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11590.00	46.12	74.00	-27.88	52.09	38.54	12.65	58.09	0.93	--	--	--	PEAK	2	17385.00	48.41	68.20	-19.79	52.68	38.46	15.56	59.23	0.94	--	--	--	PEAK
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																						
1	11590.00	46.03	74.00	-27.97	52.00	38.54	12.65	58.09	0.93	--	--	--	PEAK																																																																																																					
2	17385.00	48.18	68.20	-20.02	52.45	38.46	15.56	59.23	0.94	--	--	--	PEAK																																																																																																					
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																						
1	11590.00	46.12	74.00	-27.88	52.09	38.54	12.65	58.09	0.93	--	--	--	PEAK																																																																																																					
2	17385.00	48.41	68.20	-19.79	52.68	38.46	15.56	59.23	0.94	--	--	--	PEAK																																																																																																					






Mode	69																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																																																																										
ANT	1+2																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5638.33</td><td>50.44</td><td>68.20</td><td>-17.76</td><td>44.85</td><td>33.23</td><td>8.67</td><td>36.31</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr><tr><td>2</td><td>5651.28</td><td>48.25</td><td>69.15</td><td>-20.90</td><td>42.57</td><td>33.31</td><td>8.69</td><td>36.32</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr><tr><td>3</td><td>5700.28</td><td>57.95</td><td>105.28</td><td>-47.33</td><td>51.84</td><td>33.70</td><td>8.74</td><td>36.33</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr><tr><td>4</td><td>5720.40</td><td>55.63</td><td>111.71</td><td>-56.08</td><td>49.46</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5638.33	50.44	68.20	-17.76	44.85	33.23	8.67	36.31	0.00	200	243	PEAK	2	5651.28	48.25	69.15	-20.90	42.57	33.31	8.69	36.32	0.00	200	243	PEAK	3	5700.28	57.95	105.28	-47.33	51.84	33.70	8.74	36.33	0.00	200	243	PEAK	4	5720.40	55.63	111.71	-56.08	49.46	33.74	8.76	36.33	0.00	200	243	PEAK	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>101.61</td><td>-----</td><td>-----</td><td>95.41</td><td>33.92</td><td>8.82</td><td>36.34</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	101.61	-----	-----	95.41	33.92	8.82	36.34	0.00	200	243	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5638.33	50.44	68.20	-17.76	44.85	33.23	8.67	36.31	0.00	200	243	PEAK																																																																																																																															
2	5651.28	48.25	69.15	-20.90	42.57	33.31	8.69	36.32	0.00	200	243	PEAK																																																																																																																															
3	5700.28	57.95	105.28	-47.33	51.84	33.70	8.74	36.33	0.00	200	243	PEAK																																																																																																																															
4	5720.40	55.63	111.71	-56.08	49.46	33.74	8.76	36.33	0.00	200	243	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	101.61	-----	-----	95.41	33.92	8.82	36.34	0.00	200	243	PEAK																																																																																																																															
Avg	Blank						 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>94.42</td><td>-----</td><td>-----</td><td>87.95</td><td>33.99</td><td>8.83</td><td>36.35</td><td>0.00</td><td>200</td><td>243</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	94.42	-----	-----	87.95	33.99	8.83	36.35	0.00	200	243	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	94.42	-----	-----	87.95	33.99	8.83	36.35	0.00	200	243	AVERAGE																																																																																																																															




Mode	69																																																																																	
	Band Edge - R																																																																																	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																	
ANT	1+2																																																																																	
Pol.	Horizontal	Fundamental																																																																																
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5854.98</td><td>50.94</td><td>110.86</td><td>-59.92</td><td>44.18</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr><tr><td>2</td><td>5873.35</td><td>50.75</td><td>105.66</td><td>-54.91</td><td>43.90</td><td>34.29</td><td>8.93</td><td>36.37</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr><tr><td>3</td><td>5924.98</td><td>47.12</td><td>68.22</td><td>-21.10</td><td>40.21</td><td>34.30</td><td>8.99</td><td>36.38</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr><tr><td>4</td><td>5938.23</td><td>48.89</td><td>68.20</td><td>-19.31</td><td>42.00</td><td>34.28</td><td>8.99</td><td>36.38</td><td>0.00</td><td>200</td><td>243</td><td>PEAK</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5854.98	50.94	110.86	-59.92	44.18	34.22	8.91	36.37	0.00	200	243	PEAK	2	5873.35	50.75	105.66	-54.91	43.90	34.29	8.93	36.37	0.00	200	243	PEAK	3	5924.98	47.12	68.22	-21.10	40.21	34.30	8.99	36.38	0.00	200	243	PEAK	4	5938.23	48.89	68.20	-19.31	42.00	34.28	8.99	36.38	0.00	200	243	PEAK	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																						
1	5854.98	50.94	110.86	-59.92	44.18	34.22	8.91	36.37	0.00	200	243	PEAK																																																																						
2	5873.35	50.75	105.66	-54.91	43.90	34.29	8.93	36.37	0.00	200	243	PEAK																																																																						
3	5924.98	47.12	68.22	-21.10	40.21	34.30	8.99	36.38	0.00	200	243	PEAK																																																																						
4	5938.23	48.89	68.20	-19.31	42.00	34.28	8.99	36.38	0.00	200	243	PEAK																																																																						



Mode	69																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																																																																									
ANT	1+2																																																																																																																																									
Pol.	Vertical						Fundamental																																																																																																																																			
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5646.03</td><td>51.80</td><td>68.20</td><td>-16.40</td><td>46.16</td><td>33.28</td><td>8.68</td><td>36.32</td><td>0.00</td><td>200</td><td>300</td><td>PEAK</td></tr><tr><td>2</td><td>5650.05</td><td>48.87</td><td>68.24</td><td>-19.37</td><td>43.20</td><td>33.30</td><td>8.69</td><td>36.32</td><td>0.00</td><td>200</td><td>300</td><td>PEAK</td></tr><tr><td>3</td><td>5705.18</td><td>56.74</td><td>106.65</td><td>-49.91</td><td>50.61</td><td>33.71</td><td>8.75</td><td>36.33</td><td>0.00</td><td>200</td><td>300</td><td>PEAK</td></tr><tr><td>4</td><td>5720.23</td><td>55.17</td><td>111.31</td><td>-56.14</td><td>49.00</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>200</td><td>300</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5646.03	51.80	68.20	-16.40	46.16	33.28	8.68	36.32	0.00	200	300	PEAK	2	5650.05	48.87	68.24	-19.37	43.20	33.30	8.69	36.32	0.00	200	300	PEAK	3	5705.18	56.74	106.65	-49.91	50.61	33.71	8.75	36.33	0.00	200	300	PEAK	4	5720.23	55.17	111.31	-56.14	49.00	33.74	8.76	36.33	0.00	200	300	PEAK	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>104.11</td><td>-----</td><td>97.59</td><td>34.03</td><td>8.84</td><td>36.35</td><td>0.00</td><td>200</td><td>300</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	104.11	-----	97.59	34.03	8.84	36.35	0.00	200	300	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5646.03	51.80	68.20	-16.40	46.16	33.28	8.68	36.32	0.00	200	300	PEAK																																																																																																																														
2	5650.05	48.87	68.24	-19.37	43.20	33.30	8.69	36.32	0.00	200	300	PEAK																																																																																																																														
3	5705.18	56.74	106.65	-49.91	50.61	33.71	8.75	36.33	0.00	200	300	PEAK																																																																																																																														
4	5720.23	55.17	111.31	-56.14	49.00	33.74	8.76	36.33	0.00	200	300	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5775.00	104.11	-----	97.59	34.03	8.84	36.35	0.00	200	300	PEAK																																																																																																																															
Avg	Blank						 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>96.60</td><td>-----</td><td>90.00</td><td>34.03</td><td>8.84</td><td>36.35</td><td>0.00</td><td>200</td><td>300</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	96.60	-----	90.00	34.03	8.84	36.35	0.00	200	300	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5775.00	96.60	-----	90.00	34.03	8.84	36.35	0.00	200	300	AVERAGE																																																																																																																															






Mode	69																																																																																	
	Band Edge - R																																																																																	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																	
ANT	1+2																																																																																	
Pol.	Vertical	Fundamental																																																																																
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5854.28</td><td>54.86</td><td>112.45</td><td>-57.59</td><td>48.10</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>200</td><td>300</td><td>PEAK</td></tr><tr><td>2</td><td>5868.45</td><td>56.65</td><td>107.03</td><td>-50.38</td><td>49.02</td><td>34.27</td><td>8.93</td><td>36.37</td><td>0.00</td><td>200</td><td>300</td><td>PEAK</td></tr><tr><td>3</td><td>5923.93</td><td>48.31</td><td>68.99</td><td>-20.68</td><td>41.40</td><td>34.30</td><td>8.99</td><td>36.38</td><td>0.00</td><td>200</td><td>300</td><td>PEAK</td></tr><tr><td>4</td><td>5928.13</td><td>50.01</td><td>68.20</td><td>-18.19</td><td>43.11</td><td>34.29</td><td>8.99</td><td>36.38</td><td>0.00</td><td>200</td><td>300</td><td>PEAK</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5854.28	54.86	112.45	-57.59	48.10	34.22	8.91	36.37	0.00	200	300	PEAK	2	5868.45	56.65	107.03	-50.38	49.02	34.27	8.93	36.37	0.00	200	300	PEAK	3	5923.93	48.31	68.99	-20.68	41.40	34.30	8.99	36.38	0.00	200	300	PEAK	4	5928.13	50.01	68.20	-18.19	43.11	34.29	8.99	36.38	0.00	200	300	PEAK	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																						
1	5854.28	54.86	112.45	-57.59	48.10	34.22	8.91	36.37	0.00	200	300	PEAK																																																																						
2	5868.45	56.65	107.03	-50.38	49.02	34.27	8.93	36.37	0.00	200	300	PEAK																																																																						
3	5923.93	48.31	68.99	-20.68	41.40	34.30	8.99	36.38	0.00	200	300	PEAK																																																																						
4	5928.13	50.01	68.20	-18.19	43.11	34.29	8.99	36.38	0.00	200	300	PEAK																																																																						







Mode	69																																																																																																															
	Harmonic																																																																																																															
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																																															
ANT	1+2																																																																																																															
Pol.	Horizontal	Vertical																																																																																																														
Peak Avg	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11550.00</td><td>45.59</td><td>74.00</td><td>-28.41</td><td>51.47</td><td>38.70</td><td>12.62</td><td>58.12</td><td>0.92</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17325.00</td><td>48.73</td><td>68.20</td><td>-19.47</td><td>53.23</td><td>38.28</td><td>15.52</td><td>59.24</td><td>0.94</td><td>--</td><td>PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11550.00	45.59	74.00	-28.41	51.47	38.70	12.62	58.12	0.92	--	PEAK	2	17325.00	48.73	68.20	-19.47	53.23	38.28	15.52	59.24	0.94	--	PEAK	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11550.00</td><td>45.74</td><td>74.00</td><td>-28.26</td><td>51.62</td><td>38.70</td><td>12.62</td><td>58.12</td><td>0.92</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17325.00</td><td>48.15</td><td>68.20</td><td>-20.05</td><td>52.65</td><td>38.28</td><td>15.52</td><td>59.24</td><td>0.94</td><td>--</td><td>PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11550.00	45.74	74.00	-28.26	51.62	38.70	12.62	58.12	0.92	--	PEAK	2	17325.00	48.15	68.20	-20.05	52.65	38.28	15.52	59.24	0.94	--	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																						
1	11550.00	45.59	74.00	-28.41	51.47	38.70	12.62	58.12	0.92	--	PEAK																																																																																																					
2	17325.00	48.73	68.20	-19.47	53.23	38.28	15.52	59.24	0.94	--	PEAK																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																						
1	11550.00	45.74	74.00	-28.26	51.62	38.70	12.62	58.12	0.92	--	PEAK																																																																																																					
2	17325.00	48.15	68.20	-20.05	52.65	38.28	15.52	59.24	0.94	--	PEAK																																																																																																					






Mode	71																																																																																																																																																				
	Band Edge																																																																																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Partial RU 106/53_5745MHz																																																																																																																																																				
ANT	1+2																																																																																																																																																				
Pol.	Horizontal						Fundamental																																																																																																																																														
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5638.72</td><td>49.56</td><td>68.20</td><td>-18.64</td><td>43.97</td><td>33.23</td><td>8.67</td><td>36.31</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr><tr><td>2</td><td>5650.32</td><td>47.08</td><td>68.43</td><td>-21.35</td><td>41.41</td><td>33.30</td><td>8.69</td><td>36.32</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr><tr><td>3</td><td>5718.76</td><td>72.14</td><td>110.45</td><td>-38.31</td><td>65.97</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr><tr><td>4</td><td>5720.06</td><td>70.67</td><td>110.94</td><td>-40.27</td><td>64.50</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5638.72	49.56	68.20	-18.64	43.97	33.23	8.67	36.31	0.00	200	259	PEAK	2	5650.32	47.08	68.43	-21.35	41.41	33.30	8.69	36.32	0.00	200	259	PEAK	3	5718.76	72.14	110.45	-38.31	65.97	33.74	8.76	36.33	0.00	200	259	PEAK	4	5720.06	70.67	110.94	-40.27	64.50	33.74	8.76	36.33	0.00	200	259	PEAK	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>111.39</td><td>-----</td><td>-----</td><td>105.17</td><td>33.78</td><td>8.78</td><td>36.34</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	111.39	-----	-----	105.17	33.78	8.78	36.34	0.00	200	259	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																												
1	5638.72	49.56	68.20	-18.64	43.97	33.23	8.67	36.31	0.00	200	259	PEAK																																																																																																																																									
2	5650.32	47.08	68.43	-21.35	41.41	33.30	8.69	36.32	0.00	200	259	PEAK																																																																																																																																									
3	5718.76	72.14	110.45	-38.31	65.97	33.74	8.76	36.33	0.00	200	259	PEAK																																																																																																																																									
4	5720.06	70.67	110.94	-40.27	64.50	33.74	8.76	36.33	0.00	200	259	PEAK																																																																																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																												
1	5745.00	111.39	-----	-----	105.17	33.78	8.78	36.34	0.00	200	259	PEAK																																																																																																																																									
Avg	Blank												 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>104.48</td><td>-----</td><td>-----</td><td>98.26</td><td>33.78</td><td>8.78</td><td>36.34</td><td>0.00</td><td>200</td><td>259</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	104.48	-----	-----	98.26	33.78	8.78	36.34	0.00	200	259	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																												
1	5745.00	104.48	-----	-----	98.26	33.78	8.78	36.34	0.00	200	259	AVERAGE																																																																																																																																									




Mode	71																																																																																																																																			
	Band Edge																																																																																																																																			
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Partial RU 106/53_5745MHz																																																																																																																																			
ANT	1+2																																																																																																																																			
Pol.	Vertical						Fundamental																																																																																																																													
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5645.24</td><td>49.56</td><td>68.20</td><td>-18.64</td><td>43.92</td><td>33.27</td><td>8.68</td><td>36.31</td><td>0.00</td><td>106</td><td>8</td><td>PEAK</td></tr><tr><td>2</td><td>5652.35</td><td>50.23</td><td>69.94</td><td>-19.71</td><td>44.54</td><td>33.32</td><td>8.69</td><td>36.32</td><td>0.00</td><td>106</td><td>8</td><td>PEAK</td></tr><tr><td>3</td><td>5719.92</td><td>77.86</td><td>110.78</td><td>-32.92</td><td>71.69</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>106</td><td>8</td><td>PEAK</td></tr><tr><td>4</td><td>5720.06</td><td>77.78</td><td>110.94</td><td>-33.16</td><td>71.61</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>106</td><td>8</td><td>PEAK</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5645.24	49.56	68.20	-18.64	43.92	33.27	8.68	36.31	0.00	106	8	PEAK	2	5652.35	50.23	69.94	-19.71	44.54	33.32	8.69	36.32	0.00	106	8	PEAK	3	5719.92	77.86	110.78	-32.92	71.69	33.74	8.76	36.33	0.00	106	8	PEAK	4	5720.06	77.78	110.94	-33.16	71.61	33.74	8.76	36.33	0.00	106	8	PEAK	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5745.00</td><td>112.79</td><td>-----</td><td>-----</td><td>106.57</td><td>33.78</td><td>8.78</td><td>36.34</td><td>0.00</td><td>106</td><td>8</td><td>PEAK</td></tr></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5745.00	112.79	-----	-----	106.57	33.78	8.78	36.34	0.00	106	8	PEAK
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																								
1	5645.24	49.56	68.20	-18.64	43.92	33.27	8.68	36.31	0.00	106	8	PEAK																																																																																																																								
2	5652.35	50.23	69.94	-19.71	44.54	33.32	8.69	36.32	0.00	106	8	PEAK																																																																																																																								
3	5719.92	77.86	110.78	-32.92	71.69	33.74	8.76	36.33	0.00	106	8	PEAK																																																																																																																								
4	5720.06	77.78	110.94	-33.16	71.61	33.74	8.76	36.33	0.00	106	8	PEAK																																																																																																																								
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																								
1	5745.00	112.79	-----	-----	106.57	33.78	8.78	36.34	0.00	106	8	PEAK																																																																																																																								
Avg	 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5745.00</td><td>106.87</td><td>-----</td><td>-----</td><td>100.65</td><td>33.78</td><td>8.78</td><td>36.34</td><td>0.00</td><td>106</td><td>8</td><td>AVERAGE</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5745.00	106.87	-----	-----	100.65	33.78	8.78	36.34	0.00	106	8	AVERAGE	 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5745.00</td><td>106.87</td><td>-----</td><td>-----</td><td>100.65</td><td>33.78</td><td>8.78</td><td>36.34</td><td>0.00</td><td>106</td><td>8</td><td>AVERAGE</td></tr></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5745.00	106.87	-----	-----	100.65	33.78	8.78	36.34	0.00	106	8	AVERAGE																																							
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																								
1	5745.00	106.87	-----	-----	100.65	33.78	8.78	36.34	0.00	106	8	AVERAGE																																																																																																																								
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																								
1	5745.00	106.87	-----	-----	100.65	33.78	8.78	36.34	0.00	106	8	AVERAGE																																																																																																																								






Mode	72																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Partial RU 242/62_5795MHz																																																																																																																																										
ANT	1+2																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5635.69</td><td>58.69</td><td>68.20</td><td>-9.51</td><td>53.12</td><td>33.21</td><td>8.67</td><td>36.31</td><td>0.00</td><td>300</td><td>262</td><td>PEAK</td></tr><tr><td>2</td><td>5652.26</td><td>58.58</td><td>69.88</td><td>-11.30</td><td>52.89</td><td>33.32</td><td>8.69</td><td>36.32</td><td>0.00</td><td>300</td><td>262</td><td>PEAK</td></tr><tr><td>3</td><td>5701.60</td><td>59.56</td><td>105.65</td><td>-46.09</td><td>53.45</td><td>33.70</td><td>8.74</td><td>36.33</td><td>0.00</td><td>300</td><td>262</td><td>PEAK</td></tr><tr><td>4</td><td>5723.24</td><td>63.44</td><td>118.19</td><td>-54.75</td><td>57.25</td><td>33.75</td><td>8.77</td><td>36.33</td><td>0.00</td><td>300</td><td>262</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5635.69	58.69	68.20	-9.51	53.12	33.21	8.67	36.31	0.00	300	262	PEAK	2	5652.26	58.58	69.88	-11.30	52.89	33.32	8.69	36.32	0.00	300	262	PEAK	3	5701.60	59.56	105.65	-46.09	53.45	33.70	8.74	36.33	0.00	300	262	PEAK	4	5723.24	63.44	118.19	-54.75	57.25	33.75	8.77	36.33	0.00	300	262	PEAK	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>100.35</td><td>-----</td><td>-----</td><td>101.00</td><td>34.06</td><td>8.84</td><td>36.35</td><td>0.00</td><td>300</td><td>262</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	100.35	-----	-----	101.00	34.06	8.84	36.35	0.00	300	262	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5635.69	58.69	68.20	-9.51	53.12	33.21	8.67	36.31	0.00	300	262	PEAK																																																																																																																															
2	5652.26	58.58	69.88	-11.30	52.89	33.32	8.69	36.32	0.00	300	262	PEAK																																																																																																																															
3	5701.60	59.56	105.65	-46.09	53.45	33.70	8.74	36.33	0.00	300	262	PEAK																																																																																																																															
4	5723.24	63.44	118.19	-54.75	57.25	33.75	8.77	36.33	0.00	300	262	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5795.00	100.35	-----	-----	101.00	34.06	8.84	36.35	0.00	300	262	PEAK																																																																																																																															
Avg	Blank						 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>101.27</td><td>-----</td><td>-----</td><td>94.72</td><td>34.06</td><td>8.84</td><td>36.35</td><td>0.00</td><td>300</td><td>262</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	101.27	-----	-----	94.72	34.06	8.84	36.35	0.00	300	262	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5795.00	101.27	-----	-----	94.72	34.06	8.84	36.35	0.00	300	262	AVERAGE																																																																																																																															




Mode	72																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Partial RU 242/62_5795MHz																																																																																				
ANT	1+2																																																																																				
Pol.	Horizontal	Fundamental																																																																																			
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz Sift:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.52</td><td>65.08</td><td>111.89</td><td>-46.81</td><td>58.32</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>300</td><td>262</td><td>PEAK</td></tr><tr><td>2</td><td>5867.85</td><td>65.31</td><td>107.20</td><td>-41.89</td><td>58.49</td><td>34.27</td><td>8.92</td><td>36.37</td><td>0.00</td><td>300</td><td>262</td><td>PEAK</td></tr><tr><td>3</td><td>5924.74</td><td>53.51</td><td>68.40</td><td>-14.89</td><td>46.60</td><td>34.30</td><td>8.99</td><td>36.38</td><td>0.00</td><td>300</td><td>262</td><td>PEAK</td></tr><tr><td>4</td><td>5939.62</td><td>56.73</td><td>68.20</td><td>-11.47</td><td>49.88</td><td>34.24</td><td>9.00</td><td>36.39</td><td>0.00</td><td>300</td><td>262</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.52	65.08	111.89	-46.81	58.32	34.22	8.91	36.37	0.00	300	262	PEAK	2	5867.85	65.31	107.20	-41.89	58.49	34.27	8.92	36.37	0.00	300	262	PEAK	3	5924.74	53.51	68.40	-14.89	46.60	34.30	8.99	36.38	0.00	300	262	PEAK	4	5939.62	56.73	68.20	-11.47	49.88	34.24	9.00	36.39	0.00	300	262	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	5854.52	65.08	111.89	-46.81	58.32	34.22	8.91	36.37	0.00	300	262	PEAK																																																																									
2	5867.85	65.31	107.20	-41.89	58.49	34.27	8.92	36.37	0.00	300	262	PEAK																																																																									
3	5924.74	53.51	68.40	-14.89	46.60	34.30	8.99	36.38	0.00	300	262	PEAK																																																																									
4	5939.62	56.73	68.20	-11.47	49.88	34.24	9.00	36.39	0.00	300	262	PEAK																																																																									






Mode	72																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Partial RU 242/62_5795MHz																																																																																																																																										
ANT	1+2																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5642.51</td><td>59.19</td><td>68.20</td><td>-9.01</td><td>53.56</td><td>33.26</td><td>8.68</td><td>36.31</td><td>0.00</td><td>400</td><td>308</td><td>PEAK</td></tr><tr><td>2</td><td>5651.68</td><td>59.18</td><td>69.44</td><td>-10.26</td><td>53.50</td><td>33.31</td><td>8.69</td><td>36.32</td><td>0.00</td><td>400</td><td>308</td><td>PEAK</td></tr><tr><td>3</td><td>5701.79</td><td>61.00</td><td>105.70</td><td>-44.70</td><td>54.89</td><td>33.70</td><td>8.74</td><td>36.33</td><td>0.00</td><td>400</td><td>308</td><td>PEAK</td></tr><tr><td>4</td><td>5721.29</td><td>61.61</td><td>113.74</td><td>-52.13</td><td>55.44</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>400</td><td>308</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5642.51	59.19	68.20	-9.01	53.56	33.26	8.68	36.31	0.00	400	308	PEAK	2	5651.68	59.18	69.44	-10.26	53.50	33.31	8.69	36.32	0.00	400	308	PEAK	3	5701.79	61.00	105.70	-44.70	54.89	33.70	8.74	36.33	0.00	400	308	PEAK	4	5721.29	61.61	113.74	-52.13	55.44	33.74	8.76	36.33	0.00	400	308	PEAK	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>110.19</td><td>-----</td><td>-----</td><td>103.59</td><td>34.10</td><td>8.85</td><td>36.35</td><td>0.00</td><td>400</td><td>308</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	110.19	-----	-----	103.59	34.10	8.85	36.35	0.00	400	308	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5642.51	59.19	68.20	-9.01	53.56	33.26	8.68	36.31	0.00	400	308	PEAK																																																																																																																															
2	5651.68	59.18	69.44	-10.26	53.50	33.31	8.69	36.32	0.00	400	308	PEAK																																																																																																																															
3	5701.79	61.00	105.70	-44.70	54.89	33.70	8.74	36.33	0.00	400	308	PEAK																																																																																																																															
4	5721.29	61.61	113.74	-52.13	55.44	33.74	8.76	36.33	0.00	400	308	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5795.00	110.19	-----	-----	103.59	34.10	8.85	36.35	0.00	400	308	PEAK																																																																																																																															
Avg	Blank						 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>103.87</td><td>-----</td><td>-----</td><td>97.27</td><td>34.10</td><td>8.85</td><td>36.35</td><td>0.00</td><td>400</td><td>308</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	103.87	-----	-----	97.27	34.10	8.85	36.35	0.00	400	308	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5795.00	103.87	-----	-----	97.27	34.10	8.85	36.35	0.00	400	308	AVERAGE																																																																																																																															




Mode	72																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Partial RU 242/62_5795MHz																																																																																				
ANT	1+2																																																																																				
Pol.	Vertical	Fundamental																																																																																			
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5852.35</td><td>66.27</td><td>116.84</td><td>-50.57</td><td>59.51</td><td>34.21</td><td>8.91</td><td>36.36</td><td>0.00</td><td>400</td><td>300</td><td>PEAK</td></tr><tr><td>2</td><td>5867.85</td><td>63.82</td><td>107.20</td><td>-43.38</td><td>57.00</td><td>34.27</td><td>8.92</td><td>36.37</td><td>0.00</td><td>400</td><td>300</td><td>PEAK</td></tr><tr><td>3</td><td>5922.10</td><td>60.43</td><td>70.34</td><td>-9.91</td><td>53.52</td><td>34.31</td><td>8.98</td><td>36.38</td><td>0.00</td><td>400</td><td>300</td><td>PEAK</td></tr><tr><td>4</td><td>5932.18</td><td>60.53</td><td>68.20</td><td>-7.67</td><td>53.64</td><td>34.27</td><td>9.00</td><td>36.38</td><td>0.00</td><td>400</td><td>300</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5852.35	66.27	116.84	-50.57	59.51	34.21	8.91	36.36	0.00	400	300	PEAK	2	5867.85	63.82	107.20	-43.38	57.00	34.27	8.92	36.37	0.00	400	300	PEAK	3	5922.10	60.43	70.34	-9.91	53.52	34.31	8.98	36.38	0.00	400	300	PEAK	4	5932.18	60.53	68.20	-7.67	53.64	34.27	9.00	36.38	0.00	400	300	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																													
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																											
1	5852.35	66.27	116.84	-50.57	59.51	34.21	8.91	36.36	0.00	400	300	PEAK																																																																									
2	5867.85	63.82	107.20	-43.38	57.00	34.27	8.92	36.37	0.00	400	300	PEAK																																																																									
3	5922.10	60.43	70.34	-9.91	53.52	34.31	8.98	36.38	0.00	400	300	PEAK																																																																									
4	5932.18	60.53	68.20	-7.67	53.64	34.27	9.00	36.38	0.00	400	300	PEAK																																																																									



		73																																																																																																																																					
Mode		Band Edge - L																																																																																																																																					
		U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial RU 484/66_5775MHz																																																																																																																																					
ANT		1+2																																																																																																																																					
Pol.		Horizontal					Fundamental																																																																																																																																
Peak																																																																																																																																							
	Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5611.73</td><td>65.78</td><td>68.20</td><td>-2.42</td><td></td><td>60.38</td><td>33.07</td><td>8.64</td><td>36.31</td><td>0.00</td><td>200</td><td>244</td><td>PEAK</td></tr><tr><td>2</td><td>5654.25</td><td>66.29</td><td>71.36</td><td>-5.07</td><td></td><td>60.59</td><td>33.33</td><td>8.69</td><td>36.32</td><td>0.00</td><td>200</td><td>244</td><td>PEAK</td></tr><tr><td>3</td><td>5719.88</td><td>82.23</td><td>110.77</td><td>-28.54</td><td></td><td>76.06</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>200</td><td>244</td><td>PEAK</td></tr><tr><td>4</td><td>5720.05</td><td>82.35</td><td>110.91</td><td>-28.56</td><td></td><td>76.18</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>200</td><td>244</td><td>PEAK</td></tr></tbody></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	Factor	Loss	Factor	Factor	dB	cm	deg	1	5611.73	65.78	68.20	-2.42		60.38	33.07	8.64	36.31	0.00	200	244	PEAK	2	5654.25	66.29	71.36	-5.07		60.59	33.33	8.69	36.32	0.00	200	244	PEAK	3	5719.88	82.23	110.77	-28.54		76.06	33.74	8.76	36.33	0.00	200	244	PEAK	4	5720.05	82.35	110.91	-28.56		76.18	33.74	8.76	36.33	0.00	200	244	PEAK	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5775.00</td><td>108.46</td><td>-----</td><td>-----</td><td></td><td>101.94</td><td>34.03</td><td>8.84</td><td>36.35</td><td>0.00</td><td>200</td><td>244</td><td>PEAK</td></tr></tbody></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	Factor	Loss	Factor	Factor	dB	cm	deg	1	5775.00	108.46	-----	-----		101.94	34.03	8.84	36.35	0.00	200	244
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB		dBuV	Factor	Loss	Factor	Factor	dB	cm	deg																																																																																																																										
1	5611.73	65.78	68.20	-2.42		60.38	33.07	8.64	36.31	0.00	200	244	PEAK																																																																																																																										
2	5654.25	66.29	71.36	-5.07		60.59	33.33	8.69	36.32	0.00	200	244	PEAK																																																																																																																										
3	5719.88	82.23	110.77	-28.54		76.06	33.74	8.76	36.33	0.00	200	244	PEAK																																																																																																																										
4	5720.05	82.35	110.91	-28.56		76.18	33.74	8.76	36.33	0.00	200	244	PEAK																																																																																																																										
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB		dBuV	Factor	Loss	Factor	Factor	dB	cm	deg																																																																																																																										
1	5775.00	108.46	-----	-----		101.94	34.03	8.84	36.35	0.00	200	244	PEAK																																																																																																																										
Avg	Blank																																																																																																																																						
						Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5775.00</td><td>99.11</td><td>-----</td><td>-----</td><td></td><td>92.64</td><td>33.99</td><td>8.83</td><td>36.35</td><td>0.00</td><td>200</td><td>244</td><td>AVERAGE</td></tr></tbody></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	Factor	Loss	Factor	Factor	dB	cm	deg	1	5775.00	99.11	-----	-----		92.64	33.99	8.83	36.35	0.00	200	244	AVERAGE																																																																																			
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB		dBuV	Factor	Loss	Factor	Factor	dB	cm	deg																																																																																																																										
1	5775.00	99.11	-----	-----		92.64	33.99	8.83	36.35	0.00	200	244	AVERAGE																																																																																																																										




Mode	73																																																																																	
	Band Edge - R																																																																																	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial RU 484/66_5775MHz																																																																																	
ANT	1+2																																																																																	
Pol.	Horizontal	Fundamental																																																																																
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5854.28</td><td>73.38</td><td>112.45</td><td>-39.07</td><td>66.62</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>200</td><td>244</td><td>PEAK</td></tr><tr><td>2</td><td>5873.00</td><td>71.83</td><td>105.76</td><td>-33.93</td><td>64.98</td><td>34.29</td><td>8.93</td><td>36.37</td><td>0.00</td><td>200</td><td>244</td><td>PEAK</td></tr><tr><td>3</td><td>5920.00</td><td>63.46</td><td>71.83</td><td>-8.37</td><td>56.54</td><td>34.32</td><td>8.98</td><td>36.38</td><td>0.00</td><td>200</td><td>244</td><td>PEAK</td></tr><tr><td>4</td><td>5928.65</td><td>63.30</td><td>68.20</td><td>-4.90</td><td>56.40</td><td>34.29</td><td>8.99</td><td>36.38</td><td>0.00</td><td>200</td><td>244</td><td>PEAK</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5854.28	73.38	112.45	-39.07	66.62	34.22	8.91	36.37	0.00	200	244	PEAK	2	5873.00	71.83	105.76	-33.93	64.98	34.29	8.93	36.37	0.00	200	244	PEAK	3	5920.00	63.46	71.83	-8.37	56.54	34.32	8.98	36.38	0.00	200	244	PEAK	4	5928.65	63.30	68.20	-4.90	56.40	34.29	8.99	36.38	0.00	200	244	PEAK	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																						
1	5854.28	73.38	112.45	-39.07	66.62	34.22	8.91	36.37	0.00	200	244	PEAK																																																																						
2	5873.00	71.83	105.76	-33.93	64.98	34.29	8.93	36.37	0.00	200	244	PEAK																																																																						
3	5920.00	63.46	71.83	-8.37	56.54	34.32	8.98	36.38	0.00	200	244	PEAK																																																																						
4	5928.65	63.30	68.20	-4.90	56.40	34.29	8.99	36.38	0.00	200	244	PEAK																																																																						






Mode	73										
	Band Edge - L										
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial RU 484/66_5775MHz										
ANT	1+2										
Pol.	Vertical										
Peak											



Mode	73																																																																																	
	Band Edge - R																																																																																	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Partial RU 484/66_5775MHz																																																																																	
ANT	1+2																																																																																	
Pol.	Vertical	Fundamental																																																																																
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5854.98</td><td>73.05</td><td>110.86</td><td>-37.81</td><td>66.29</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>300</td><td>298</td><td>PEAK</td></tr><tr><td>2</td><td>5869.50</td><td>74.94</td><td>106.74</td><td>-31.80</td><td>68.10</td><td>34.28</td><td>8.93</td><td>36.37</td><td>0.00</td><td>300</td><td>298</td><td>PEAK</td></tr><tr><td>3</td><td>5922.53</td><td>63.17</td><td>70.02</td><td>-6.85</td><td>56.26</td><td>34.31</td><td>8.98</td><td>36.38</td><td>0.00</td><td>300</td><td>298</td><td>PEAK</td></tr><tr><td>4</td><td>5932.68</td><td>63.64</td><td>68.20</td><td>-4.56</td><td>56.75</td><td>34.27</td><td>9.00</td><td>36.38</td><td>0.00</td><td>300</td><td>298</td><td>PEAK</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5854.98	73.05	110.86	-37.81	66.29	34.22	8.91	36.37	0.00	300	298	PEAK	2	5869.50	74.94	106.74	-31.80	68.10	34.28	8.93	36.37	0.00	300	298	PEAK	3	5922.53	63.17	70.02	-6.85	56.26	34.31	8.98	36.38	0.00	300	298	PEAK	4	5932.68	63.64	68.20	-4.56	56.75	34.27	9.00	36.38	0.00	300	298	PEAK	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																						
1	5854.98	73.05	110.86	-37.81	66.29	34.22	8.91	36.37	0.00	300	298	PEAK																																																																						
2	5869.50	74.94	106.74	-31.80	68.10	34.28	8.93	36.37	0.00	300	298	PEAK																																																																						
3	5922.53	63.17	70.02	-6.85	56.26	34.31	8.98	36.38	0.00	300	298	PEAK																																																																						
4	5932.68	63.64	68.20	-4.56	56.75	34.27	9.00	36.38	0.00	300	298	PEAK																																																																						





Mode	75																																																																																																																															
	Band Edge																																																																																																																															
	U-NII-3_5.725-5.85_802.11ac VHT20_CH149_5745MHz																																																																																																																															
ANT	1+2																																																																																																																															
Pol.	Horizontal						Fundamental																																																																																																																									
Peak																																																																																																																																
	Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5648.29</td><td>48.46</td><td>68.20</td><td>-19.74</td><td>42.81</td><td>33.29</td><td>8.68</td><td>36.32</td><td>0.00</td><td>244</td><td>236</td><td>PEAK</td></tr><tr><td>2</td><td>5650.32</td><td>46.78</td><td>68.43</td><td>-21.65</td><td>41.11</td><td>33.30</td><td>8.69</td><td>36.32</td><td>0.00</td><td>244</td><td>236</td><td>PEAK</td></tr><tr><td>3</td><td>5700.05</td><td>48.68</td><td>105.21</td><td>-56.53</td><td>42.57</td><td>33.70</td><td>8.74</td><td>36.33</td><td>0.00</td><td>244</td><td>236</td><td>PEAK</td></tr><tr><td>4</td><td>5720.21</td><td>48.44</td><td>111.27</td><td>-62.83</td><td>42.27</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>244</td><td>236</td><td>PEAK</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5648.29	48.46	68.20	-19.74	42.81	33.29	8.68	36.32	0.00	244	236	PEAK	2	5650.32	46.78	68.43	-21.65	41.11	33.30	8.69	36.32	0.00	244	236	PEAK	3	5700.05	48.68	105.21	-56.53	42.57	33.70	8.74	36.33	0.00	244	236	PEAK	4	5720.21	48.44	111.27	-62.83	42.27	33.74	8.76	36.33	0.00	244	236	PEAK	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>106.73</td><td>-----</td><td>-----</td><td>100.49</td><td>33.79</td><td>8.79</td><td>36.34</td><td>0.00</td><td>244</td><td>236</td><td>PEAK</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5745.00	106.73	-----	-----	100.49	33.79	8.79	36.34	0.00	244	236
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																				
1	5648.29	48.46	68.20	-19.74	42.81	33.29	8.68	36.32	0.00	244	236	PEAK																																																																																																																				
2	5650.32	46.78	68.43	-21.65	41.11	33.30	8.69	36.32	0.00	244	236	PEAK																																																																																																																				
3	5700.05	48.68	105.21	-56.53	42.57	33.70	8.74	36.33	0.00	244	236	PEAK																																																																																																																				
4	5720.21	48.44	111.27	-62.83	42.27	33.74	8.76	36.33	0.00	244	236	PEAK																																																																																																																				
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																				
1	5745.00	106.73	-----	-----	100.49	33.79	8.79	36.34	0.00	244	236	PEAK																																																																																																																				
Avg	Blank																																																																																																																															
							Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>100.27</td><td>-----</td><td>-----</td><td>94.05</td><td>33.78</td><td>8.78</td><td>36.34</td><td>0.00</td><td>244</td><td>236</td><td>AVERAGE</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5745.00	100.27	-----	-----	94.05	33.78	8.78	36.34	0.00	244	236	AVERAGE																																																																													
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																				
1	5745.00	100.27	-----	-----	94.05	33.78	8.78	36.34	0.00	244	236	AVERAGE																																																																																																																				






Mode	75										
	Band Edge										
	U-NII-3_5.725-5.85_802.11ac VHT20_CH149_5745MHz										
ANT	1+2										
Pol.	Vertical										
Peak											




Mode	75																																																																																																																								
	Harmonic																																																																																																																								
	U-NII-3_5.725-5.85_802.11ac VHT20_CH149_5745MHz																																																																																																																								
ANT	1+2																																																																																																																								
Pol.	Horizontal						Vertical																																																																																																																		
Peak Avg																																																																																																																									
	Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL						Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 VERTICAL																																																																																																																		
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 11490.00</td><td>46.09</td><td>74.00</td><td>-27.91</td><td>51.84</td><td>38.91</td><td>12.58</td><td>58.16</td><td>0.92</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2 17235.00</td><td>46.36</td><td>68.20</td><td>-21.84</td><td>51.01</td><td>38.20</td><td>15.47</td><td>59.26</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 11490.00	46.09	74.00	-27.91	51.84	38.91	12.58	58.16	0.92	--	--	PEAK	2 17235.00	46.36	68.20	-21.84	51.01	38.20	15.47	59.26	0.94	--	--	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 11490.00</td><td>46.61</td><td>74.00</td><td>-27.39</td><td>52.36</td><td>38.91</td><td>12.58</td><td>58.16</td><td>0.92</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2 17235.00</td><td>46.76</td><td>68.20</td><td>-21.44</td><td>51.41</td><td>38.20</td><td>15.47</td><td>59.26</td><td>0.94</td><td>--</td><td>--</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 11490.00	46.61	74.00	-27.39	52.36	38.91	12.58	58.16	0.92	--	--	PEAK	2 17235.00	46.76	68.20	-21.44	51.41	38.20	15.47	59.26	0.94	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																															
1 11490.00	46.09	74.00	-27.91	51.84	38.91	12.58	58.16	0.92	--	--	PEAK																																																																																																														
2 17235.00	46.36	68.20	-21.84	51.01	38.20	15.47	59.26	0.94	--	--	PEAK																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																															
1 11490.00	46.61	74.00	-27.39	52.36	38.91	12.58	58.16	0.92	--	--	PEAK																																																																																																														
2 17235.00	46.76	68.20	-21.44	51.41	38.20	15.47	59.26	0.94	--	--	PEAK																																																																																																														






Mode	76																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-3_5.725-5.85_802.11ac VHT40_CH159_5795MHz																																																																																																																																									
ANT	1+2																																																																																																																																									
Pol.	Horizontal						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5647.78</td><td>51.46</td><td>68.20</td><td>-16.74</td><td>45.81</td><td>33.29</td><td>8.68</td><td>36.32</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr><tr><td>2</td><td>5651.09</td><td>51.11</td><td>69.01</td><td>-17.90</td><td>45.43</td><td>33.31</td><td>8.69</td><td>36.32</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr><tr><td>3</td><td>5701.40</td><td>53.85</td><td>105.59</td><td>-51.74</td><td>47.74</td><td>33.70</td><td>8.74</td><td>36.33</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr><tr><td>4</td><td>5728.12</td><td>53.34</td><td>111.07</td><td>-57.73</td><td>47.17</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5647.78	51.46	68.20	-16.74	45.81	33.29	8.68	36.32	0.00	200	259	PEAK	2	5651.09	51.11	69.01	-17.90	45.43	33.31	8.69	36.32	0.00	200	259	PEAK	3	5701.40	53.85	105.59	-51.74	47.74	33.70	8.74	36.33	0.00	200	259	PEAK	4	5728.12	53.34	111.07	-57.73	47.17	33.74	8.76	36.33	0.00	200	259	PEAK	Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>106.06</td><td>-----</td><td>-----</td><td>100.26</td><td>34.10</td><td>8.85</td><td>36.35</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	106.06	-----	-----	100.26	34.10	8.85	36.35	0.00	200	259
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5647.78	51.46	68.20	-16.74	45.81	33.29	8.68	36.32	0.00	200	259	PEAK																																																																																																																														
2	5651.09	51.11	69.01	-17.90	45.43	33.31	8.69	36.32	0.00	200	259	PEAK																																																																																																																														
3	5701.40	53.85	105.59	-51.74	47.74	33.70	8.74	36.33	0.00	200	259	PEAK																																																																																																																														
4	5728.12	53.34	111.07	-57.73	47.17	33.74	8.76	36.33	0.00	200	259	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5795.00	106.06	-----	-----	100.26	34.10	8.85	36.35	0.00	200	259	PEAK																																																																																																																														
Avg	Blank																																																																																																																																									
							Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>99.14</td><td>-----</td><td>-----</td><td>92.62</td><td>34.03</td><td>8.84</td><td>36.35</td><td>0.00</td><td>200</td><td>259</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	99.14	-----	-----	92.62	34.03	8.84	36.35	0.00	200	259	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5795.00	99.14	-----	-----	92.62	34.03	8.84	36.35	0.00	200	259	AVERAGE																																																																																																																														



Mode	76																																																																																
	Band Edge - R																																																																																
	U-NII-3_5.725-5.85_802.11ac VHT40_CH159_5795MHz																																																																																
ANT	1+2																																																																																
Pol.	Horizontal	Fundamental																																																																															
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5854.83</td><td>52.01</td><td>111.19</td><td>-59.18</td><td>45.25</td><td>34.22</td><td>8.91</td><td>36.37</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr><tr><td>2 5870.49</td><td>54.94</td><td>106.46</td><td>-51.52</td><td>48.10</td><td>34.28</td><td>8.93</td><td>36.37</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr><tr><td>3 5924.89</td><td>48.34</td><td>68.28</td><td>-19.94</td><td>41.43</td><td>34.30</td><td>8.99</td><td>36.38</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr><tr><td>4 5931.71</td><td>49.39</td><td>68.20</td><td>-18.81</td><td>42.51</td><td>34.27</td><td>8.99</td><td>36.38</td><td>0.00</td><td>200</td><td>259</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 5854.83	52.01	111.19	-59.18	45.25	34.22	8.91	36.37	0.00	200	259	PEAK	2 5870.49	54.94	106.46	-51.52	48.10	34.28	8.93	36.37	0.00	200	259	PEAK	3 5924.89	48.34	68.28	-19.94	41.43	34.30	8.99	36.38	0.00	200	259	PEAK	4 5931.71	49.39	68.20	-18.81	42.51	34.27	8.99	36.38	0.00	200	259	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																							
1 5854.83	52.01	111.19	-59.18	45.25	34.22	8.91	36.37	0.00	200	259	PEAK																																																																						
2 5870.49	54.94	106.46	-51.52	48.10	34.28	8.93	36.37	0.00	200	259	PEAK																																																																						
3 5924.89	48.34	68.28	-19.94	41.43	34.30	8.99	36.38	0.00	200	259	PEAK																																																																						
4 5931.71	49.39	68.20	-18.81	42.51	34.27	8.99	36.38	0.00	200	259	PEAK																																																																						



Mode	76																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ac VHT40_CH159_5795MHz																																																																																																																																										
ANT	1+2																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5647.00</td><td>50.65</td><td>68.20</td><td>-17.55</td><td>45.01</td><td>33.28</td><td>8.68</td><td>36.32</td><td>0.00</td><td>200</td><td>298</td><td>PEAK</td></tr><tr><td>2</td><td>5652.07</td><td>50.96</td><td>69.73</td><td>-18.77</td><td>45.27</td><td>33.32</td><td>8.69</td><td>36.32</td><td>0.00</td><td>200</td><td>298</td><td>PEAK</td></tr><tr><td>3</td><td>5708.03</td><td>58.20</td><td>107.45</td><td>-49.25</td><td>52.06</td><td>33.72</td><td>8.75</td><td>36.33</td><td>0.00</td><td>200</td><td>298</td><td>PEAK</td></tr><tr><td>4</td><td>5728.12</td><td>56.34</td><td>111.07</td><td>-54.73</td><td>50.17</td><td>33.74</td><td>8.76</td><td>36.33</td><td>0.00</td><td>200</td><td>298</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5647.00	50.65	68.20	-17.55	45.01	33.28	8.68	36.32	0.00	200	298	PEAK	2	5652.07	50.96	69.73	-18.77	45.27	33.32	8.69	36.32	0.00	200	298	PEAK	3	5708.03	58.20	107.45	-49.25	52.06	33.72	8.75	36.33	0.00	200	298	PEAK	4	5728.12	56.34	111.07	-54.73	50.17	33.74	8.76	36.33	0.00	200	298	PEAK	 Site : 03CH15-HY Condition: PEAK(UNI) 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>107.18</td><td>-----</td><td>-----</td><td>100.71</td><td>33.99</td><td>8.83</td><td>36.35</td><td>0.00</td><td>200</td><td>298</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	107.18	-----	-----	100.71	33.99	8.83	36.35	0.00	200	298	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5647.00	50.65	68.20	-17.55	45.01	33.28	8.68	36.32	0.00	200	298	PEAK																																																																																																																															
2	5652.07	50.96	69.73	-18.77	45.27	33.32	8.69	36.32	0.00	200	298	PEAK																																																																																																																															
3	5708.03	58.20	107.45	-49.25	52.06	33.72	8.75	36.33	0.00	200	298	PEAK																																																																																																																															
4	5728.12	56.34	111.07	-54.73	50.17	33.74	8.76	36.33	0.00	200	298	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5795.00	107.18	-----	-----	100.71	33.99	8.83	36.35	0.00	200	298	PEAK																																																																																																																															
Avg	Blank						 Site : 03CH15-HY Condition: AVG_54 3m BBHA 9120 D_91200-02294 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5795.00</td><td>100.57</td><td>-----</td><td>-----</td><td>94.05</td><td>34.03</td><td>8.84</td><td>36.35</td><td>0.00</td><td>200</td><td>298</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	100.57	-----	-----	94.05	34.03	8.84	36.35	0.00	200	298	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5795.00	100.57	-----	-----	94.05	34.03	8.84	36.35	0.00	200	298	AVERAGE																																																																																																																															

76

Mode

Band Edge - R

U-NII-3_5.725-5.85_802.11ac VHT40_CH159_5795MHz

ANT


1+2

Pol.

Vertical

Fundamental

Peak





Site : 03CH15-HY
Condition: PEAK_BE(B4)_16-24 3m BBHA 9120 D 91200-02294 VERTICAL
: RBW:1000.000kHz VBW:3000.000kHz SMT:Auto

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	5854.83	59.68	111.19	-51.51	52.92	34.22	8.91	36.37	0.00	200	298	PEAK	
2	5874.36	57.75	105.38	-47.63	50.89	34.30	8.93	36.37	0.00	200	298	PEAK	
3	5924.43	50.17	68.62	-18.45	43.26	34.30	8.99	36.38	0.00	200	298	PEAK	
4	5928.77	52.82	68.20	-15.38	45.93	34.28	8.99	36.38	0.00	200	298	PEAK	

Blank



Mode	76																																																																																																															
	Harmonic																																																																																																															
	U-NII-3_5.725-5.85_802.11ac VHT40_CH159_MHz																																																																																																															
ANT	1+2																																																																																																															
Pol.	Horizontal	Vertical																																																																																																														
Peak Avg	 Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11590.00</td><td>45.70</td><td>74.00</td><td>-28.30</td><td>51.67</td><td>38.54</td><td>12.65</td><td>58.09</td><td>0.93</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17385.00</td><td>47.15</td><td>68.20</td><td>-21.05</td><td>51.42</td><td>38.46</td><td>15.56</td><td>59.23</td><td>0.94</td><td>--</td><td>PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11590.00	45.70	74.00	-28.30	51.67	38.54	12.65	58.09	0.93	--	PEAK	2	17385.00	47.15	68.20	-21.05	51.42	38.46	15.56	59.23	0.94	--	PEAK	 Site : 03CH15-HY Condition: PEAK(UNII) 3m BBHA 9120 D_91200-02294 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11590.00</td><td>45.57</td><td>74.00</td><td>-28.43</td><td>51.54</td><td>38.54</td><td>12.65</td><td>58.09</td><td>0.93</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>17385.00</td><td>47.35</td><td>68.20</td><td>-20.85</td><td>51.62</td><td>38.46</td><td>15.56</td><td>59.23</td><td>0.94</td><td>--</td><td>PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11590.00	45.57	74.00	-28.43	51.54	38.54	12.65	58.09	0.93	--	PEAK	2	17385.00	47.35	68.20	-20.85	51.62	38.46	15.56	59.23	0.94	--	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																						
1	11590.00	45.70	74.00	-28.30	51.67	38.54	12.65	58.09	0.93	--	PEAK																																																																																																					
2	17385.00	47.15	68.20	-21.05	51.42	38.46	15.56	59.23	0.94	--	PEAK																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																						
1	11590.00	45.57	74.00	-28.43	51.54	38.54	12.65	58.09	0.93	--	PEAK																																																																																																					
2	17385.00	47.35	68.20	-20.85	51.62	38.46	15.56	59.23	0.94	--	PEAK																																																																																																					