

Page: 1 of 12

Issued date: 2023/11/7

FCC ID: 2AFB3-VSTRACKER100

# **Maximum Permissible Exposure Report**

**Product** : VS Tracker

**Model Name** : VS Tracker 100

FCC ID : 2AFB3-VSTRACKER100

**Test Regulation**: 47 CFR FCC Part 2.1093

**Received Date** : 2023/7/26

**Test Date** : 2023/8/18 ~ 2023/8/25

**Issued Date** : 2023/11/7

**Applicant** : Medimaging Integrated Solution Inc.

3F., No.24-2, Industry E. Rd. IV, Hsinchu Science Park,

Hsinchu, Taiwan 30077, R.O.C.

**Issued By** : Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd.,

Zhudong Township, Hsinchu County, Taiwan





The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948



Page: 2 of 12

Issued date: 2023/11/7

FCC ID: 2AFB3-VSTRACKER100

# **REVISION HISTORY**

Original Test Report No.: 4790935379-US-R1-V1

Revision	Test report No.	Date	Page revised	Contents
Original	4790935379-US-R1-V0	2023/10/4	-	Initial issue
V1	4790935379-US-R1-V1	2023/11/7	12	Address TCB 1st comment
				l



Page: 3 of 12

Issued date: 2023/11/7

FCC ID: 2AFB3-VSTRACKER100

Doc No: Form-ULID-004725 (DCS:17-EM-F0864) / 5.1

# **Table of Contents**

1.	Attestation of Test Results	4
2.	Test Methodology and Reference Procedures	5
3.	Facilities and Accreditation	5
4.	Equipment Under Test	6
2	4.1. Description of EUT	6 8
	Requirement	
6.	General RF Exposure Test Exemption	10
7.	Radio Frequency Radiation Exposure Evaluation	12



Page: 4 of 12

Issued date: 2023/11/7

FCC ID: 2AFB3-VSTRACKER100

### 1. Attestation of Test Results

**APPLICANT:** Medimaging Integrated Solution Inc.

3F., No.24-2, Industry E. Rd. IV, Hsinchu Science Park,

Hsinchu, Taiwan 30077, R.O.C.

**MANUFACTURER:** Medimaging Integrated Solution Inc.

3F., No.24-2, Industry E. Rd. IV, Hsinchu Science Park,

Hsinchu, Taiwan 30077, R.O.C.

**EUT DESCRIPTION:** VS Tracker

BRAND: TWENTY

MODEL: VS Tracker 100

**SAMPLE STAGE:** Pilot-run Verification Test sample

#### APPLICABLE STANDARDS

**STANDARD** 

**Test Results** 

47 CFR FCC Part 2.1093

**PASS** 

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By: Approved and Authorized By:

Sally Lu Date: 2023/11/7 Eric Lee Date: 2023/11/7

Project Handler Senior Laboratory Engineer

#### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX): +886-3-583-7948 Doc No: Form-ULID-004725 (DCS:17-EM-F0864) / 5.1



Page: 5 of 12

Issued date: 2023/11/7

FCC ID: 2AFB3-VSTRACKER100

## 2. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with KDB 447498 D04 Interim General RF Exposure Guidance v01.

## 3. Facilities and Accreditation

Test Location	Underwriters Laboratories Taiwan Co., Ltd.
Address	Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Accreditation Certificate	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398.

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948



Page: 6 of 12

Issued date: 2023/11/7

FCC ID: 2AFB3-VSTRACKER100

# 4. Equipment Under Test

# **4.1. Description of EUT**

Product Name	VS Tracker		
Brand Name	TWENTY/ TWENTY		
Model Name	VS Tracker 100		
Operating Frequency	Bluetooth LE	2402MHz ~ 2480MHz	
Modulation	Bluetooth LE	GFSK	
Number of Channel	Bluetooth LE 40		
	3.7Vdc from batte	ry	
Normal Voltage	5Vdc from adapter		
	5Vdc from host		
Sample ID	6288950		

### Note:

1. The EUT contains following accessory devices:

Product	Manufacturer	Model	Description
Collar	Medimaging Integrated Solution Inc.	VS Tracker 100 Collar A	Datachable collars for various botles
Collar	Medimaging Integrated Solution Inc.	VS Tracker 100 Collar B	Datachable collars for various botles
Collar	Medimaging Integrated Solution Inc.	VS Tracker 100 Collar C	Datachable collars for various botles
Collar	Medimaging Integrated Solution Inc.	VS Tracker 100 Collar D	Datachable collars for various botles



Page: 7 of 12

Issued date: 2023/11/7

FCC ID: 2AFB3-VSTRACKER100

Doc No: Form-ULID-004725 (DCS:17-EM-F0864) / 5.1

2. The EUT could be supplied with rechargeable battery as the following table:

Product Manufacturer		Model	Description
Internal Rechargeable Lithium Battery	GUANGDONG ZHAONENG TECHNOLOGY CO., LTD.	ZN 502630	3.7V / 350mAh

- 3. For this report measurement uncertainty, statement of conformity, determining compliance, it is necessary to refer to the original measurement report of EUT.
- 4. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual, the laboratory shall not be held responsible.



Page: 8 of 12

Issued date: 2023/11/7

FCC ID: 2AFB3-VSTRACKER100

## 4.2. Description of Available Antennas

#### For Bluetooth LE

Ant. No.	Transmitter Circuit	Brand Name	Model Name	Ant. Type	Maximum Gain (dBi)
1	Chain (0)	Würth Elektronik	NA	PCB	-1.6

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual, the laboratory shall not be held responsible.

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948



Page: 9 of 12

Issued date: 2023/11/7

FCC ID: 2AFB3-VSTRACKER100

### 5. Requirement

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure							
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time  E 2,  H 2 or S (minutes)			
0.3-1.34	614	1.63	*100	30			
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30			
30-300	27.5	0.073	0.2	30			
300-1500			f/1500	30			
1500-100,000			1.0	30			

Note 1: f = frequency in MHz, \* means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Power Density (S) is calculated by the following formula:

 $S=(P*G)/4\pi R^2$ 

where: S = power density (in appropriate units, e.g. mW/ cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator <math>R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Page: 10 of 12 Issued date: 2023/11/7

FCC ID: 2AFB3-VSTRACKER100

### 6. General RF Exposure Test Exemption

The corresponding Exclusion Threshold condition, listed below:

- 1) Blanket Exempt: Following 47 CFR 1.1307(b)(3)(i)(A), the available maximum time-averaged power is no more than 1 mW.
- 2) SAR Exempt: Following 47 CFR 1.1307(b)(3)(i)(B), the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold *P<sub>th</sub>* (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). *P<sub>th</sub>* is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \ cm} (d/20 \ \text{cm})^x & d \leq 20 \ \text{cm} \\ ERP_{20 \ cm} & 20 \ \text{cm} < d \leq 40 \ \text{cm} \end{cases}$$

Where

$$x = -\log_{10}\left(\frac{60}{ERP_{20,cm}\sqrt{f}}\right)$$
 and f is in GHz;

and

$$\mathit{ERP}_{20\;cm}\;(\mathrm{mW}) = \begin{cases} 2040f & 0.3\;\mathrm{GHz} \leq f < 1.5\;\mathrm{GHz} \\ \\ 3060 & 1.5\;\mathrm{GHz} \leq f \leq 6\;\mathrm{GHz} \end{cases}$$

Doc No: Form-ULID-004725 (DCS:17-EM-F0864) / 5.1

d =the separation distance (cm);



Page: 11 of 12 Issued date: 2023/11/7

FCC ID: 2AFB3-VSTRACKER100

3) MPE Exempt: Following 47 CFR 1.1307(b)(3)(i)(C), using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R <sup>2</sup> .
1.34-30	3,450 R <sup>2</sup> /f <sup>2</sup> .
30-300	3.83 R <sup>2</sup> .
300-1,500	0.0128 R <sup>2</sup> f.
1,500-100,000	19.2R <sup>2</sup> .



Page: 12 of 12

Issued date: 2023/11/7

FCC ID: 2AFB3-VSTRACKER100

## 7. Radio Frequency Radiation Exposure Evaluation

(1) General RF Exposure Test Exemption

Option	<b>Evaluation Method</b>	Clause
	Blanket Exempt	47 CFR 1.1307(b)(3)(i)(A)
$\boxtimes$	SAR Exempt	47 CFR 1.1307(b)(3)(i)(B)
	MPE Exempt	47 CFR 1.1307(b)(3)(i)(C)

Note: Max. ERP (dBm) = Max. Average power (dBm) + Antenna Gain (dBi) - 2.15 (dB)

Operating Mode	Evaluation Frequency	Max. Average Power	Antenna Gain	Min. Test Separation Distance	Max. ERP Power	Limits of SAR Exempt	Result
	(MHz)	(mW)	(dBi)	(mm)	(mW)	(mW)	
BT LE	2402 -2480	2.443	-1.60	0.5	1.03	2.71	PASS

Note:

- 1. Max. ERP (dBm) = Max. Average power (dBm) + Antenna Gain (dBi) -2.15
- 2. Max. ERP (mW) =  $10^{(\text{Max. ERP (dBm)}/10)}$

### **END OF REPORT**

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948