



Product Service

**Choose certainty.
Add value.**

Report On

RF Exposure Assessment of the
Mix Telematics
440FT0964 Magix Pico Base Station

FCC ID: 2AFMS-PBS9
IC: 20545-PBS9

Document 75932793 Report 02 Issue 2

January 2016



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuv-sud.co.uk

REPORT ON

RF Exposure Assessment of the
Mix Telematics
440FT0964 Magix Pico Base Station

Document 75932793 Report 02 Issue 2

January 2016

PREPARED FOR

MiX Telematics International (PTY) Ltd
Blaauwklip Office Park 2
cnr Strand & Webersvallei Streets
Stellenbosch
Cape Town
South Africa

PREPARED BY

A handwritten signature in blue ink, appearing to read 'Ryan Henley', written over a horizontal line.

Ryan Henley
Project Manager

APPROVED BY

A handwritten signature in blue ink, appearing to read 'Matthew Russell', written over a horizontal line.

Matthew Russell
Authorised Signatory

DATED

14 January 2016

This report has been up-issued to Issue 2 to correct a typographical error.



Product Service

CONTENTS

Section	Page No
1	REPORT SUMMARY 3
1.1	Introduction 4
1.2	Regional Requirements 5
1.3	Product Information 6
1.3.1	Technical Description 6
1.3.2	Supported Features 6
1.3.3	Antennas 6
1.4	Brief Summary of Results 7
2	TEST DETAILS 9
2.1	Rationale for Assessment of the RF Exposure 10
2.2	Test Result Details 11
3	DISCLAIMERS AND COPYRIGHT 12
3.1	Disclaimers and Copyright 13



Product Service

SECTION 1

REPORT SUMMARY

RF Exposure Assessment of the
Mix Telematics
440FT0964 Magix Pico Base Station



Product Service

1.1 INTRODUCTION

The information contained in this report is intended to show verification of the RF Exposure Assessment of the Mix Telematics 440FT0964 Magix Pico Base Station to the requirements of the applied test specifications.

Objective	To perform RF Exposure Assessment to determine the Equipment Under Test's (EUT's) compliance of the applied rules.
Applicant	Mix Telematics
Manufacturer	Mix Telematics
Manufacturing Description	Magix Pico Base Station
Model Number(s)	440FT0964
Test Specification/Issue/Date	CFR 47 Pt1.1310 Health Canada Safety Code 6



Product Service

1.2 REGIONAL REQUIREMENTS

The table below shows the regional requirements that are referenced in this test report. A full list of the requirements is shown in Annex A.

Report Reference	Regional Requirement
FCC	CFR 47 Pt1.1310
IC	Health Canada Safety Code 6



Product Service

1.3 PRODUCT INFORMATION

1.3.1 Technical Description

The Equipment under test was a Mix Telematics 440FT0964 Magix Pico Base Station. A full technical description can be found in the manufacturer's documentation.

All reported calculations were carried out on the relevant information supplied for the 440FT0964 Magix Pico Base Station to demonstrate compliance with the applied test specification(s). The sample assessed was found to comply with the requirements of the applied rules.

1.3.2 Supported Features

The following radio access technologies and frequency bands are supported by the equipment under test.

Radio Access Technology	Digital Modulation
Frequency Band	902 to 928

1.3.3 Antennas

The following antennas are supported by the equipment under test.

No.	Model	Gain (dBi)
1	Integral	0



Product Service

1.4 BRIEF SUMMARY OF RESULTS

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General Public and Occupational. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s).

Required Compliance Boundary (m)	
Occupational	General Population
0.01	0.02

Table 1 – Compliance Boundary Results



Product Service

Regional Requirement	Calculated RF exposure level at compliance boundary of 0.01 m					
	S Field (W/m ²)		E Field (V/m)		H Field (A/m)	
	Result	Limit	Result	Limit	Result	Limit
FCC*	0.7958	3.0067	N/A	N/A	N/A	N/A
IC	7.9577	19.3865	54.7723	85.4921	0.1453	0.2268

* Requirement and Result in mW/cm²

Table 2 – Occupational Results

The calculations show that the EUT complies with the occupational exposure levels described in the CFR 47 Pt1.1310 and Health Canada Safety Code 6 at the point of investigation, 0.01 m.

Regional Requirement	Calculated RF exposure level at compliance boundary of 0.02 m					
	S Field (W/m ²)		E Field (V/m)		H Field (A/m)	
	Result	Limit	Result	Limit	Result	Limit
FCC*	0.1989	0.6013	N/A	N/A	N/A	N/A
IC	1.9894	2.7398	27.3861	32.1366	0.0726	0.0853

* Requirement and Result in mW/cm²

Table 3 – General Population Results

The calculations show that the EUT complies with the occupational exposure levels described in the CFR 47 Pt1.1310 and Health Canada Safety Code 6 at the point of investigation, 0.02 m.



Product Service

SECTION 2

TEST DETAILS

2.1 RATIONALE FOR ASSESSMENT OF THE RF EXPOSURE

The aim of the assessment report is to evaluate the compliance boundary for a set of given input power(s) according to the basic restrictions (directly or indirectly via compliance with reference levels) related to human exposure to radio frequency electromagnetic fields. The chosen assessment method to establish the compliance boundary in the far-field region is the reference method as defined in the relevant specifications.

The RF exposure assessment is based upon the following criteria:

The 440FT0964 Magix Pico Base Station operates with the following transmitters active on the antenna ports shown in Section 1.3.3. For each transmitter, the Radio Access Technology (RAT), EIRP inclusive of antenna gain and duty cycle, gain of the antenna and lowest frequency of operation are shown as they contribute to the calculation of S Field, E field and H field values according to the following formulas.

The power flux (S Field):

$$S = \frac{PG_{(\theta, \phi)}}{4\pi r^2}$$

The electric field strength (E Field):

$$E = \frac{\sqrt{30PG_{(\theta, \phi)}}}{r}$$

The magnetic field strength (H Field):

$$H = \frac{E}{\eta_0}$$

Where:

P = Average Power (W)
 G = Antenna Gain (dBi)
 r = Distance (cm) or (m)
 $\eta_0 = 377$



Product Service

2.2 TEST RESULT DETAILS

The frequencies shown in the tables below have been chosen based on the lowest possible frequency that the EUT can transmit.

Antenna Port	Tx No.	Ant No.	RAT	EIRP (W)	Duty Cycle (%)	Gain (dBi)	Frequency (MHz)	RF Exposure Level at compliance boundary of 0.01 m		
								S Field (W/m ²)	E Field (V/m)	H Field (A/m)
1	1	1	Digital Modulation	0.010	10	0	902	7.9577	54.7723	0.1453

Table 4 – Occupational Transmitter Summary

Antenna Port	Tx No.	Ant No.	RAT	EIRP (W)	Duty Cycle (%)	Gain (dBi)	Frequency (MHz)	RF Exposure Level at compliance boundary of 0.02 m		
								S Field (W/m ²)	E Field (V/m)	H Field (A/m)
1	1	1	Digital Modulation	0.010	10	0	902	1.9894	27.3861	0.0726

Table 5 – General Population Transmitter Summary



Product Service

SECTION 3

DISCLAIMERS AND COPYRIGHT



Product Service

3.1 DISCLAIMERS AND COPYRIGHT

This report relates only to the actual item/items tested.

This report must not be reproduced, except in its entirety, without the written permission of
TÜV SÜD Product Service

© 2016 TÜV SÜD Product Service



Product Service

ANNEX A

REGIONAL REQUIREMENTS



Product Service

Frequency Range (MHz)	S Field (mW/cm ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	$900/f^2$	$1842/f$	$4.89/f$
30 - 300	1	61.4	0.163
300 - 1500	$f/300$	-	-
1500 - 100000	5	-	-

Table A.1 – CFR 47 Pt1.1310 Occupational Limits

Frequency Range (MHz)	S Field (mW/cm ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	$180/f^2$	$824/f$	$2.19/f$
30 - 300	0.2	27.5	0.073
300 - 1500	$f/1500$	-	-
1500 - 100000	1	-	-

Table A.2 – CFR 47 Pt1.1310 General Population Limits

Frequency Range (MHz)	Power Density (W/m ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
10 - 20	10	61.4	0.163
20 - 48	$44.72/f^{0.5}$	$129.8/f^{0.25}$	$0.3444/f^{0.25}$
48 - 100	6.455	49.33	0.1309
100 - 6000	$0.6455*f^{0.5}$	$15.60*f^{0.25}$	$0.04138*f^{0.25}$
6000 - 150000	50	137	0.364

Table A.3 – Health Canada Safety Code 6 Occupational Limits

Frequency Range (MHz)	Power Density (W/m ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
10 - 20	2	27.46	0.0728
20 - 48	$8.944/f^{0.5}$	$58.07/f^{0.25}$	$0.1540/f^{0.25}$
48 - 300	1.291	22.06	0.05852
300 - 6000	$0.02619*f^{0.6834}$	$3.142*f^{0.3417}$	$0.008335*f^{0.3417}$
6000 - 15000	10	61.4	0.163

Table A.4 – Health Canada Safety Code 6 General Population Limits