

## **Statement of compliance to SAR**

Applicant : Anhui Jiugong Wellness Industry Co., Ltd.  
Taiyanghe Road, Hexian Economic Development Zone,  
Maanshan City, Anhui 213000, China

Manufacturer : Anhui Jiugong Wellness Industry Co., Ltd.  
Taiyanghe Road, Hexian Economic Development Zone,  
Maanshan City, Anhui 213000, China

Product Name : Massager Chair

Type/Model : LC7800S+, LC8800

TEST RESULT : PASS

**According to KDB 447498, if [the max output power / min test separation distance]\*  
[ $\sqrt{f}(\text{GHz})$ ]  $\leq 3.0$ , it can follow the test exclusion procedure.**

Date of issue: February 1, 2016

Prepared by:



Nemo Li (Project engineer)

Approved by:



Daniel Zhao (Reviewer)

For Bluetooth, as we can see from the test report 151100728SHA-001:

The maximum P = -10.90dBm

Min test separation distance = 5mm

F(GHz) = 2.5GHz

G = 0dBi

EIRP = PG =  $-10.90 + 0 = -10.90\text{dBm} = 0.08\text{ mW}$

The test exclusion limit =  $[0.08/5]*[\sqrt{2.5}] = 0.01 \leq 3.0$

It is found the EIRP of EUT is lower than the test exclusion limit. Therefore, the EUT complies the requirement of 15.247(I) without test.