

## RF Exposure evaluation

According to 447498 D01 General RF Exposure Guidance v05  
The 1-g and 10-g SAR test exclusion thresholds for 100 MHz  
to 6 GHz at test separation distances  $\leq 50$  mm are determined  
by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm  
before calculation

The result is rounded to one decimal place for comparison

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{Exd})^2 / 30$$

where:

pt = transmitter output power in watts,  
gt = numeric gain of the transmitting antenna (unitless),  
E = electric field strength in V/m, ---  $10^{(\text{dBuV/m})/20} / 10^6$   
d = measurement distance in meters (m) --- 3m  
So  $\text{pt} = (\text{Exd})^2 / 30 \times \text{gt}$

Field strength = 83.96 dBuV/m @ 3m

Ant gain 0 dBi; so Ant numeric gain=1

So  $\text{pt} = \{ [10^{(83.96/20)} / 10^6 \times 3]^2 / 30 \times 1 \} \times 1000 \text{ mW} = 0.075 \text{ mW}$

So  $(0.075 \text{ mW} / 5 \text{ mm}) \times \sqrt{2.440 \text{ GHz}} = 0.023 < 3$

Then SAR evaluation is not required