



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20180300001E-02

Applicant: Avantree Technology Co., Ltd.

Address of Applicant: The 4th Floor, Yuepeng Building, No.1019 Jiabin Rd, Luohu District, Shenzhen, China

Manufacturer: Avantree Technology Co., Ltd.

Address of Manufacturer: The 4th Floor, Yuepeng Building, No.1019 Jiabin Rd, Luohu District, Shenzhen, China

Factory: Avantree Technology Co., Ltd.

Address of Factory: The 4th Floor, Yuepeng Building, No.1019 Jiabin Rd, Luohu District, Shenzhen, China

Equipment Under Test (EUT):

Product: Avantree Audikast

Model No.: BTTC-418

Brand Name: Avantree

FCC ID: 2AITF-BTTC-418

Standards: 47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2018-03-05 to 2018-03-10

Date of Issue: 2018-03-10

Test Result : PASS*


Tested By:


(Aaron Ma)

Reviewed By:


(Owen Zhou)

Approved By:


(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

2 Version

Revision History Of Report

| Report No. | Version | Description | Issue Date |
|----------------------|---------|----------------|------------|
| CQASZ20180300001E-02 | Rev.01 | Initial report | 2018-03-10 |

3 Contents

| | Page |
|--|-------------|
| 1 COVER PAGE | 1 |
| 2 VERSION | 2 |
| 3 CONTENTS | 3 |
| 4 GENERAL INFORMATION | 4 |
| 4.1 CLIENT INFORMATION..... | 4 |
| 4.2 GENERAL DESCRIPTION OF EUT..... | 4 |
| 5 SAR EVALUATION | 5 |
| 5.1 RF EXPOSURE COMPLIANCE REQUIREMENT | 5 |
| 5.1.1 <i>Standard Requirement</i> | 5 |
| 5.1.2 <i>Limits</i> | 5 |
| 5.1.3 <i>EUT RF Exposure</i> | 5 |

4 General Information

4.1 Client Information

| | |
|--------------------------|---|
| Applicant: | Avantree Technology Co., Ltd. |
| Address of Applicant: | The 4th Floor, Yuepeng Building, No.1019 Jiabin Rd, Luohu District, Shenzhen, China |
| Manufacturer: | Avantree Technology Co., Ltd. |
| Address of Manufacturer: | The 4th Floor, Yuepeng Building, No.1019 Jiabin Rd, Luohu District, Shenzhen, China |
| Factory: | Avantree Technology Co., Ltd. |
| Address of Factory: | The 4th Floor, Yuepeng Building, No.1019 Jiabin Rd, Luohu District, Shenzhen, China |

4.2 General Description of EUT

| | |
|-----------------------|---|
| Product Name: | Avantree Audikast |
| Model No.: | BTTC-418 |
| Trade Mark: | Avantree |
| Hardware Version: | TC418_V1.49 (File version 12638 (0x315e)) |
| Software Version: | CSR8670C |
| Operation Frequency: | 2402MHz~2480MHz |
| Bluetooth Version: | V4.2 |
| Modulation Technique: | Frequency Hopping Spread Spectrum(FHSS) |
| Modulation Type: | GFSK, $\pi/4$ DQPSK, 8DPSK |
| Number of Channel: | 79 |
| Hopping Channel Type: | Adaptive Frequency Hopping systems |
| Sample Type: | portable production |
| Test Software of EUT: | Blue test 3.0 (manufacturer declare) |
| Antenna Type: | PCB antenna |
| Antenna Gain: | 0dBi |
| Power Supply: | Input: DC5V 0.5A |

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

For BT:

Measurement Data

| GFSK mode | |
|--------------------|-------------------------|
| Test channel | Peak Output Power (dBm) |
| Lowest | 5.500 |
| Middle | 6.380 |
| Highest | 5.760 |
| $\pi/4$ DQPSK mode | |
| Test channel | Peak Output Power (dBm) |
| Lowest | 5.160 |
| Middle | 6.160 |
| Highest | 5.530 |
| 8DPSK mode | |
| Test channel | Peak Output Power (dBm) |
| Lowest | 5.710 |
| Middle | 6.610 |
| Highest | 5.940 |

The Max Conducted Peak Output Power is 6.61dBm in middle channel(2.441GHz);

The best case gain of the antenna is 0dBi.

$$\text{EIRP} = 6.61\text{dBm} + 0\text{dBi} = 6.61\text{dBm}$$

6.61dBm logarithmic terms convert to numeric result is nearly 4.58mW

According to the formula. calculate the EIRP test result:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$$

$$\text{General RF Exposure} = (4.58\text{mW} / 5 \text{ mm}) \times \sqrt{2.441\text{GHz}} = 1.43 \text{ (1)}$$

SAR requirement:

$$S = 3.0 \quad (2);$$

$$(1) < (2).$$

So the SAR report is not required.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20180300001E-01