

TEST REPORT

FCC ID: 2AIZN-X1101B

Product: Tablet

Model No.: X1101B

Trade Mark: Infinix

Report No.: WSCT-ANAB-R&E241100056A-BT

Issued Date: 14 November 2024

Issued for:

INFINIX MOBILITY LIMITED

FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI
STREET FOTAN NT HONGKONG

Issued By:

World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.
Building A-B, Baoli' an Industrial Park, No. 58 and 60, Tangtou Avenue, Shiyan
Street, Bao' an District, Shenzhen City, Guangdong Province, China

TEL: +86-755-26996192

FAX: +86-755-86376605

Note: This report shall not be reproduced except in full, without the written approval of World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. This document may be altered or revised by World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

| | |
|--|-----------|
| 1. Test Certification | 3 |
| 2. Test Result Summary | 4 |
| 3. EUT Description..... | 5 |
| 4. Genera Information..... | 7 |
| 4.1. TEST ENVIRONMENT AND MODE | 7 |
| 4.2. DESCRIPTION OF SUPPORT UNITS | 7 |
| 5. Facilities and Accreditations | 8 |
| 5.1. FACILITIES | 8 |
| 5.2. ACCREDITATIONS | 8 |
| 5.3. MEASUREMENT UNCERTAINTY | 9 |
| 5.4. MEASUREMENT INSTRUMENTS | 10 |
| 6. Test Results and Measurement Data | 11 |
| 6.1. ANTENNA REQUIREMENT | 11 |
| 6.2. CONDUCTED EMISSION | 12 |
| 6.3. CONDUCTED OUTPUT POWER | 15 |
| 6.4. 20dB OCCUPY BANDWIDTH | 22 |
| 6.5. CARRIER FREQUENCIES SEPARATION | 29 |
| 6.6. HOPPING CHANNEL NUMBER | 36 |
| 6.7. DWELL TIME..... | 39 |
| 6.8. PSEUDORANDOM FREQUENCY HOPPING SEQUENCE | 50 |
| 6.9. CONDUCTED BAND EDGE MEASUREMENT | 51 |
| 6.10. CONDUCTED SPURIOUS EMISSION MEASUREMENT..... | 54 |
| 6.11. RADIATED SPURIOUS EMISSION MEASUREMENT | 64 |
| 7. Test Setup Photographs | 76 |

Report No.: WSCT-ANAB-R&E241100056A-BT

1. Test Certification

Product: Tablet

Model No.: X1101B

Additional Model: Infinix

Applicant: INFINIX MOBILITY LIMITED
FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN
MEI STREET FOTAN NT HONGKONG

Manufacturer: INFINIX MOBILITY LIMITED
FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN
MEI STREET FOTAN NT HONGKONG

Date of Test: 29 September 2024 to 13 November 2024

Applicable Standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

The above equipment has been tested by World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: Wang Xiang
(Wang Xiang)

Checked By: Qin Shuiquan
(Qin Shuiquan)

Approved By: Li Huaibi
(Li Huaibi)

Date: 14 November 2024



Report No.: WSCT-ANAB-R&E241100056A-BT

2. Test Result Summary

| Requirement | CFR 47 Section | Result |
|----------------------------------|-------------------------------------|--------|
| Antenna Requirement | §15.203/§15.247 (c) | PASS |
| AC Power Line Conducted Emission | §15.207 | PASS |
| Maximum conducted output power | §15.247 (b)(1) §2.1046 | PASS |
| 20dB Occupied Bandwidth | §15.247 (a)(1) §2.1049 | PASS |
| Carrier Frequencies Separation | §15.247 (a)(1) | PASS |
| Hopping Channel Number | §15.247 (a)(1) | PASS |
| Dwell Time | §15.247 (a)(1) | PASS |
| Radiated Emission | §15.205/§15.209 §2.1053, §2.1057 | PASS |
| Band Edge | §15.247(d) §2.1051, §2.1057 | PASS |

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

Report No.: WSCT-ANAB-R&E241100056A-BT

3. EUT Description

| | |
|-----------------------------|--|
| Product Name: | Tablet |
| Model : | X1101B |
| Trade Mark: | Infinix |
| Software version: | X1101B-M1101CDEGHIJKL |
| Hardware version: | V1.0 |
| Operation Frequency: | 2402MHz~2480MHz |
| Channel Separation: | 1MHz |
| Number of Channel: | 79 |
| Modulation Type: | GFSK, $\pi/4$ -DQPSK, 8-DPSK |
| Antenna Type: | Internal Antenna |
| Antenna Gain: | 1dBi |
| Operating Voltage: | Adapter1: U180XKB Input: 100-240V~50/60Hz 0.6A Output: 5.0V~2.4A , 7.5V~2.4A 18W max Adapter2: U180XED Input: 100-240V~50/60Hz 0.6A Output: 5.0V~2.4A , 7.5V~2.4A 18W max Rechargeable Li-ion Polymer Battery: BL-68CX Rated Voltage: 3.85V Rated Capacity: 6800mAh /26.18Wh Typical Capacity: 7000mAh /26.95Wh Limited Charge Voltage: 4.4V |
| Remark: | N/A. |

Note: 1. N/A stands for no applicable.

2. Antenna gain provided by the customer.

Report No.: WSCT-ANAB-R&E241100056A-BT

Operation Frequency each of channel for GFSK, $\pi/4$ -DQPSK, 8DPSK

| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|---------|-----------|
| 0 | 2402MHz | 20 | 2422MHz | 40 | 2442MHz | 60 | 2462MHz |
| 1 | 2403MHz | 21 | 2423MHz | 41 | 2443MHz | 61 | 2463MHz |
| ... | ... | ... | ... | ... | ... | ... | ... |
| 10 | 2412MHz | 30 | 2432MHz | 50 | 2452MHz | 70 | 2472MHz |
| 11 | 2413MHz | 31 | 2433MHz | 51 | 2453MHz | 71 | 2473MHz |
| ... | ... | ... | ... | ... | ... | ... | ... |
| 18 | 2420MHz | 38 | 2440MHz | 58 | 2460MHz | 78 | 2480MHz |
| 19 | 2421MHz | 39 | 2441MHz | 59 | 2461MHz | - | - |

Remark: Channel 0, 39 & 78 have been tested for GFSK, $\pi/4$ -DQPSK, 8DPSK modulation mode.

Report No.: WSCT-ANAB-R&E241100056A-BT

4. General Information

4.1. Test environment and mode

| Operating Environment: | |
|---|--|
| Temperature: | 25.0 °C |
| Humidity: | 56 % RH |
| Atmospheric Pressure: | 1010 mbar |
| Test Mode: | |
| Engineering mode: | Keep the EUT in continuous transmitting by select channel and modulations with Fully-charged battery |
| The sample was placed 0.8m & 1.5m for the measurement below & above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. | |

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Equipment | Model No. | Serial No. | FCC ID | Trade Name |
|-----------|-----------|------------|--------|------------|
| / | / | / | / | / |

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

Report No.: WSCT-ANAB-R&E241100056A-BT

5. Facilities and Accreditations

5.1. Facilities

All measurement facilities used to collect the measurement data are located at **Building A-B, Baoli'an Industrial Park, No.58 and 60, Tangtou Avenue, Shiyao Street, Bao'an District, Shenzhen City, Guangdong Province, China of the World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.**

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.2. ACCREDITATIONS

ANAB - Certificate Number: AT-3951

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (ANAB). Certification Number: AT-3951

5.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

| No. | Item | MU |
|-----|---|---------------------------|
| 1 | Duty Cycle and Tx-Sequence and Tx-Gap | $\pm 1\%$ |
| 2 | Dwell Time and Minimum Frequency Occupation | $\pm 1.2\%$ |
| 3 | Medium Utilisation Factor | $\pm 1.3\%$ |
| 4 | Occupied Channel Bandwidth | $\pm 2.4\%$ |
| 5 | Transmitter Unwanted Emission in the out-of Band | $\pm 1.3\%$ |
| 6 | Transmitter Unwanted Emissions in the Spurious Domain | $\pm 2.5\%$ |
| 7 | Receiver Spurious Emissions | $\pm 2.5\%$ |
| 8 | Conducted Emission Test | $\pm 3.2\text{dB}$ |
| 9 | RF power, conducted | $\pm 0.16\text{dB}$ |
| 10 | Spurious emissions, conducted | $\pm 0.21\text{dB}$ |
| 11 | All emissions, radiated(<1GHz) | $\pm 4.7\text{dB}$ |
| 12 | All emissions, radiated(>1GHz) | $\pm 4.7\text{dB}$ |
| 13 | Temperature | $\pm 0.5^{\circ}\text{C}$ |
| 14 | Humidity | $\pm 2.0\%$ |

Report No.: WSCT-ANAB-R&E241100056A-BT

5.4. MEASUREMENT INSTRUMENTS

| NAME OF EQUIPMENT | MANUFACTURER | MODEL | SERIAL NUMBER | Calibration Date | Calibration Due. |
|--------------------------------------|------------------------|--------------|---------------|------------------|------------------|
| Test software | -- | EZ-EMC | CON-03A | - | - |
| Test software | -- | MTS8310 | | - | |
| EMI Test Receiver | R&S | ESCI | 100005 | 11/05/2024 | 11/04/2025 |
| LISN | AFJ | LS16 | 16010222119 | 11/05/2024 | 11/04/2025 |
| LISN(EUT) | Mestec | AN3016 | 04/10040 | 11/05/2024 | 11/04/2025 |
| Universal Radio Communication Tester | R&S | CMU 200 | 1100.0008.02 | 11/05/2024 | 11/04/2025 |
| Coaxial cable | Megalon | LMR400 | N/A | 11/05/2024 | 11/04/2025 |
| GPIO cable | Megalon | GPIO | N/A | 11/05/2024 | 11/04/2025 |
| Spectrum Analyzer | R&S | FSU | 100114 | 11/05/2024 | 11/04/2025 |
| Pre Amplifier | H.P. | HP8447E | 2945A02715 | 11/05/2024 | 11/04/2025 |
| Pre-Amplifier | CDSI | PAP-1G18-38 | -- | 11/05/2024 | 11/04/2025 |
| Bi-log Antenna | SCHWARZBECK | VULB9168 | 01488 | 07/29/2024 | 07/28/2025 |
| 9*6*6 Anechoic | -- | -- | -- | 11/05/2024 | 11/04/2025 |
| Horn Antenna | COMPLIANCE ENGINEERING | CE18000 | -- | 11/05/2024 | 11/04/2025 |
| Horn Antenna | SCHWARZBECK | BBHA9120D | 9120D-631 | 11/05/2024 | 11/04/2025 |
| Cable | TIME MICROWAVE | LMR-400 | N-TYPE04 | 11/05/2024 | 11/04/2025 |
| System-Controller | CCS | N/A | N/A | N.C.R | N.C.R |
| Turn Table | CCS | N/A | N/A | N.C.R | N.C.R |
| Antenna Tower | CCS | N/A | N/A | N.C.R | N.C.R |
| RF cable | Murata | MXHQ87WA3000 | - | 11/05/2024 | 11/04/2025 |
| Loop Antenna | EMCO | 6502 | 00042960 | 11/05/2024 | 11/04/2025 |
| Horn Antenna | SCHWARZBECK | BBHA 9170 | 1123 | 11/05/2024 | 11/04/2025 |
| Power meter | Anritsu | ML2487A | 6K00003613 | 11/05/2024 | 11/04/2025 |
| Power sensor | Anritsu | MX248XD | -- | 11/05/2024 | 11/04/2025 |
| Spectrum Analyzer | Keysight | N9010B | MY60241089 | 11/05/2024 | 11/04/2025 |

Report No.: WSCT-ANAB-R&E241100056A-BT

6. Test Results and Measurement Data


6.1. Antenna requirement

| | |
|--|-------------------------------------|
| Standard requirement: | FCC Part15 C Section 15.203 /247(c) |
| <p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p> | |
| E.U.T Antenna: | |
| <p>The Bluetooth antenna is a Internal Antenna. it meets the standards, and the best case gain of the antenna is 1dBi.</p> | |

Report No.: WSCT-ANAB-R&E241100056A-BT

6.2. Conducted Emission

6.2.1. Test Specification

| Test Requirement: | FCC Part15 C Section 15.207 | | | | | | | | | | | | | | |
|-----------------------|--|-----------------------|--------------|--|------------|---------|----------|-----------|-----------|-------|----|----|------|----|----|
| Test Method: | ANSI C63.10:2014 | | | | | | | | | | | | | | |
| Frequency Range: | 150 kHz to 30 MHz | | | | | | | | | | | | | | |
| Receiver setup: | RBW=9 kHz, VBW=30 kHz, Sweep time=auto | | | | | | | | | | | | | | |
| Limits: | <table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table> | Frequency range (MHz) | Limit (dBuV) | | Quasi-peak | Average | 0.15-0.5 | 66 to 56* | 56 to 46* | 0.5-5 | 56 | 46 | 5-30 | 60 | 50 |
| Frequency range (MHz) | Limit (dBuV) | | | | | | | | | | | | | | |
| | Quasi-peak | Average | | | | | | | | | | | | | |
| 0.15-0.5 | 66 to 56* | 56 to 46* | | | | | | | | | | | | | |
| 0.5-5 | 56 | 46 | | | | | | | | | | | | | |
| 5-30 | 60 | 50 | | | | | | | | | | | | | |
| Test Setup: | <div><p>Reference Plane</p><p>Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p></div> | | | | | | | | | | | | | | |
| Test Mode: | Refer to item 4.1 | | | | | | | | | | | | | | |
| Test Procedure: | <ol style="list-style-type: none">1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2014 on conducted measurement. | | | | | | | | | | | | | | |
| Test Result: | PASS | | | | | | | | | | | | | | |

Report No.: WSCT-ANAB-R&E241100056A-BT


6.2.2. EUT OPERATING CONDITIONS

The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Test data


Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)
For multiple adapters, the report only displays the adapter with the worst data.



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1 | 0.1680 | 18.04 | 20.72 | 38.76 | 65.06 | -26.30 | QP |
| 2 | 0.1680 | 1.76 | 20.72 | 22.48 | 55.06 | -32.58 | AVG |
| 3 | 0.1905 | 17.14 | 20.70 | 37.84 | 64.01 | -26.17 | QP |
| 4 | 0.1905 | -2.47 | 20.70 | 18.23 | 54.01 | -35.78 | AVG |
| 5 | 0.4290 | 14.49 | 20.55 | 35.04 | 57.27 | -22.23 | QP |
| 6 | 0.4290 | 1.08 | 20.55 | 21.63 | 47.27 | -25.64 | AVG |
| 7 * | 0.5190 | 15.96 | 20.51 | 36.47 | 56.00 | -19.53 | QP |
| 8 | 0.5190 | 0.70 | 20.51 | 21.21 | 46.00 | -24.79 | AVG |
| 9 | 0.9195 | 12.40 | 20.64 | 33.04 | 56.00 | -22.96 | QP |
| 10 | 0.9195 | -3.13 | 20.64 | 17.51 | 46.00 | -28.49 | AVG |
| 11 | 1.4280 | 11.59 | 20.64 | 32.23 | 56.00 | -23.77 | QP |
| 12 | 1.4280 | -3.57 | 20.64 | 17.07 | 46.00 | -28.93 | AVG |

Report No.: WSCT-ANAB-R&E241100056A-BT

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1 | 0.1635 | 18.13 | 20.72 | 38.85 | 65.28 | -26.43 | QP |
| 2 | 0.1635 | 0.18 | 20.72 | 20.90 | 55.28 | -34.38 | AVG |
| 3 | 0.1905 | 17.67 | 20.70 | 38.37 | 64.01 | -25.64 | QP |
| 4 | 0.1905 | -3.59 | 20.70 | 17.11 | 54.01 | -36.90 | AVG |
| 5 | 0.2580 | 14.98 | 20.66 | 35.64 | 61.50 | -25.86 | QP |
| 6 | 0.2580 | -5.67 | 20.66 | 14.99 | 51.50 | -36.51 | AVG |
| 7 | 0.4605 | 15.97 | 20.53 | 36.50 | 56.68 | -20.18 | QP |
| 8 | 0.4605 | 0.34 | 20.53 | 20.87 | 46.68 | -25.81 | AVG |
| 9 * | 0.5685 | 17.47 | 20.52 | 37.99 | 56.00 | -18.01 | QP |
| 10 | 0.5685 | 1.02 | 20.52 | 21.54 | 46.00 | -24.46 | AVG |
| 11 | 0.6720 | 12.54 | 20.54 | 33.08 | 56.00 | -22.92 | QP |
| 12 | 0.6720 | -3.95 | 20.54 | 16.59 | 46.00 | -29.41 | AVG |

Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = LISN Factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard


Margin (dB) = Measurement (dBuV) - Limits (dBuV)

Q.P. =Quasi-Peak AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

6.3. Conducted Output Power

6.3.1. Test Specification

| | |
|--------------------------|---|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3) |
| Test Method: | ANSI C63.10:2014 |
| Limit: | Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. |
| Test Setup: |  <p>Spectrum Analyzer EUT</p> |
| Test Mode: | Transmitting mode with modulation |
| Test Procedure: | <p>Use the following spectrum analyzer settings:</p> <p>Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel</p> <p>RBW > the 20 dB bandwidth of the emission being measured $VBW \geq RBW$</p> <p>Sweep = auto</p> <p>Detector function = peak</p> <p>Trace = max hold</p> <p>Allow the trace to stabilize.</p> <p>Use the marker-to-peak function to set the marker to the peak of the emission.</p> |
| Test Result: | PASS |

Report No.: WSCT-ANAB-R&E241100056A-BT

6.3.2. Test Data

| GFSK mode | | | |
|--------------|--------------------------------------|-------------|--------|
| Test channel | Maximum conducted output power (dBm) | Limit (dBm) | Result |
| Lowest | 13.42 | 20.97 | PASS |
| Middle | 14.61 | 20.97 | PASS |
| Highest | 14.55 | 20.97 | PASS |

| Pi/4DQPSK mode | | | |
|----------------|--------------------------------------|-------------|--------|
| Test channel | Maximum conducted output power (dBm) | Limit (dBm) | Result |
| Lowest | 12.55 | 20.97 | PASS |
| Middle | 14.26 | 20.97 | PASS |
| Highest | 14.24 | 20.97 | PASS |


| 8DPSK mode | | | |
|--------------|--------------------------------------|-------------|--------|
| Test channel | Maximum conducted output power (dBm) | Limit (dBm) | Result |
| Lowest | 12.38 | 20.97 | PASS |
| Middle | 13.69 | 20.97 | PASS |
| Highest | 13.7 | 20.97 | PASS |

Test plots as follows:


Report No.: WSCT-ANAB-R&E241100056A-BT

Test Graphs

Power NVNT 1-DH5 2402MHz Ant1




Power NVNT 1-DH5 2441MHz Ant1




Report No.: WSCT-ANAB-R&E241100056A-BT

Power NVNT 1-DH5 2480MHz Ant1




Power NVNT 2-DH5 2402MHz Ant1




Report No.: WSCT-ANAB-R&E241100056A-BT

Power NVNT 2-DH5 2441MHz Ant1




Power NVNT 2-DH5 2480MHz Ant1




Report No.: WSCT-ANAB-R&E241100056A-BT


Power NVNT 3-DH5 2402MHz Ant1



Power NVNT 3-DH5 2441MHz Ant1




Report No.: WSCT-ANAB-R&E241100056A-BT



Report No.: WSCT-ANAB-R&E241100056A-BT

6.4. 20dB Occupy Bandwidth

6.4.1. Test Specification

| | |
|--------------------------|--|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1) |
| Test Method: | ANSI C63.10:2014 |
| Limit: | N/A |
| Test Setup: |  <p style="text-align: center;">Spectrum Analyzer EUT</p> |
| Test Mode: | Transmitting mode with modulation |
| Test Procedure: | <ol style="list-style-type: none"> 1. The testing follows ANSI C63.10:2014 Measurement Guidelines. 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement. Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel; $1\% \leq RBW \leq 5\%$ of the 20 dB bandwidth; $VBW \geq 3RBW$; Sweep = auto; Detector function = peak; Trace = max hold. 5. Measure and record the results in the test report. |
| Test Result: | PASS |

Report No.: WSCT-ANAB-R&E241100056A-BT

6.4.2. Test data


| Test channel | 20dB Occupy Bandwidth (MHz) | | | |
|--------------|-----------------------------|----------------|-------|------------|
| | GFSK | $\pi/4$ -DQPSK | 8DPSK | Conclusion |
| Lowest | 0.7678 | 1.024 | 1.051 | PASS |
| Middle | 0.7123 | 1.113 | 1.077 | PASS |
| Highest | 0.7830 | 1.052 | 1.052 | PASS |

Test plots as follows:


Report No.: WSCT-ANAB-R&E241100056A-BT

Test Graphs



-20dB Bandwidth NVNT 1-DH5 2402MHz Ant1





-20dB Bandwidth NVNT 1-DH5 2441MHz Ant1





Report No.: WSCT-ANAB-R&E241100056A-BT




Report No.: WSCT-ANAB-R&E241100056A-BT



Report No.: WSCT-ANAB-R&E241100056A-BT




Report No.: WSCT-ANAB-R&E241100056A-BT



Report No.: WSCT-ANAB-R&E241100056A-BT

6.5. Carrier Frequencies Separation

6.5.1. Test Specification

| | |
|--------------------------|---|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1) |
| Test Method: | ANSI C63.10:2014 |
| Limit: | Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater. |
| Test Setup: |  <p style="text-align: center;">Spectrum Analyzer EUT</p> |
| Test Mode: | Hopping mode |
| Test Procedure: | <ol style="list-style-type: none"> 1. The testing follows ANSI C63.10:2014 Measurement Guidelines. 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Enable the EUT hopping function. 5. Use the following spectrum analyzer settings: Span = wide enough to capture the peaks of two adjacent channels; RBW is set to approximately 30% of the channel spacing, adjust as necessary to best identify the center of each individual channel; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold. 6. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Record the value in report. |
| Test Result: | PASS |

Report No.: WSCT-ANAB-R&E241100056A-BT

6.5.2. Test data

| GFSK mode | | | |
|--------------|--------------------------------------|-------------------------|--------|
| Test channel | Carrier Frequencies Separation (MHz) | Limit (2/3*20dB BW MHz) | Result |
| Lowest | 1.000 | 0.512 | PASS |
| Middle | 1.000 | 0.475 | PASS |
| Highest | 1.000 | 0.522 | PASS |

| Pi/4 DQPSK mode | | | |
|-----------------|--------------------------------------|-------------------------|--------|
| Test channel | Carrier Frequencies Separation (MHz) | Limit (2/3*20dB BW MHz) | Result |
| Lowest | 1.000 | 0.683 | PASS |
| Middle | 1.000 | 0.742 | PASS |
| Highest | 1.002 | 0.701 | PASS |


| 8DPSK mode | | | |
|--------------|--------------------------------------|-------------------------|--------|
| Test channel | Carrier Frequencies Separation (MHz) | Limit (2/3*20dB BW MHz) | Result |
| Lowest | 0.84 | 0.701 | PASS |
| Middle | 1.162 | 0.718 | PASS |
| Highest | 1.000 | 0.701 | PASS |

Test plots as follows:


Report No.: WSCT-ANAB-R&E241100056A-BT

Test Graphs

CFS NVNT 1-DH5 2402MHz Ant1




CFS NVNT 1-DH5 2441MHz Ant1




Report No.: WSCT-ANAB-R&E241100056A-BT

CFS NVNT 1-DH5 2480MHz Ant1




CFS NVNT 2-DH5 2402MHz Ant1




Report No.: WSCT-ANAB-R&E241100056A-BT

CFS NVNT 2-DH5 2441MHz Ant1




CFS NVNT 2-DH5 2480MHz Ant1




Report No.: WSCT-ANAB-R&E241100056A-BT

CFS NVNT 3-DH5 2402MHz Ant1




CFS NVNT 3-DH5 2441MHz Ant1




Report No.: WSCT-ANAB-R&E241100056A-BT

CFS NVNT 3-DH5 2480MHz Ant1



6.6. Hopping Channel Number

6.6.1. Test Specification


| | |
|--------------------------|--|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1) |
| Test Method: | ANSI C63.10:2014 |
| Limit: | Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. |
| Test Setup: |  <p>Spectrum Analyzer EUT</p> |
| Test Mode: | Hopping mode |
| Test Procedure: | <ol style="list-style-type: none"> 1. The testing follows ANSI C63.10:2014 Measurement Guidelines. 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Enable the EUT hopping function. 5. Use the following spectrum analyzer settings: Span = the frequency band of operation; set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold. 6. The number of hopping frequency used is defined as the number of total channel. 7. Record the measurement data in report. |
| Test Result: | PASS |

Report No.: WSCT-ANAB-R&E241100056A-BT


6.6.2. Test data

| Mode | Hopping channel numbers | Limit | Result |
|------------------------|-------------------------|-------|--------|
| GFSK, P/4-DQPSK, 8DPSK | 79 | 15 | PASS |

Test plots as follows:




Report No.: WSCT-ANAB-R&E241100056A-BT



Report No.: WSCT-ANAB-R&E241100056A-BT

6.7. Dwell Time

6.7.1. Test Specification

| | |
|--------------------------|--|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1) |
| Test Method: | ANSI C63.10:2014 |
| Limit: | The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. |
| Test Setup: |  <p style="text-align: center;">Spectrum Analyzer EUT</p> |
| Test Mode: | Hopping mode |
| Test Procedure: | <ol style="list-style-type: none"> 1. The testing follows ANSI C63.10:2014 Measurement Guidelines. 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Enable the EUT hopping function. 5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW shall be \leq channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold. 6. Measure and record the results in the test report. |
| Test Result: | PASS |

Report No.: WSCT-ANAB-R&E241100056A-BT

6.7.2. Test Data

| Mode | Frequency (MHz) | Pulse Time (ms) | Total Dwell Time (ms) | Burst Count | Period Time (ms) | Limit (ms) | Verdict |
|-------|-----------------|-----------------|-----------------------|-------------|------------------|------------|---------|
| 1-DH1 | 2402 | 0.375 | 118.875 | 317 | 31600 | 400 | Pass |
| 1-DH1 | 2441 | 0.374 | 116.688 | 312 | 31600 | 400 | Pass |
| 1-DH1 | 2480 | 0.375 | 119.25 | 318 | 31600 | 400 | Pass |
| 1-DH3 | 2402 | 1.631 | 274.008 | 168 | 31600 | 400 | Pass |
| 1-DH3 | 2441 | 1.629 | 265.527 | 163 | 31600 | 400 | Pass |
| 1-DH3 | 2480 | 1.629 | 265.527 | 163 | 31600 | 400 | Pass |
| 1-DH5 | 2402 | 2.879 | 316.69 | 110 | 31600 | 400 | Pass |
| 1-DH5 | 2441 | 2.879 | 328.206 | 114 | 31600 | 400 | Pass |
| 1-DH5 | 2480 | 2.879 | 293.658 | 102 | 31600 | 400 | Pass |

Note: 1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.

For DH1, With channel hopping rate (1600 / 2 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 2 / 79) x (0.4 x 79) = 320 hops

For DH3, With channel hopping rate (1600 / 4 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 4 / 79) x (0.4 x 79) = 160 hops

For DH5, With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops


2. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

Test plots as follows:


Report No.: WSCT-ANAB-R&E241100056A-BT

Test Graphs



Dwell NVNT 1-DH1 2402MHz Ant1 One Burst



Dwell NVNT 1-DH1 2402MHz Ant1 Accumulated



Report No.: WSCT-ANAB-R&E241100056A-BT



Report No.: WSCT-ANAB-R&E241100056A-BT

