

Appendix A: Effective (Isotropic) Radiated Power Output Data

Test Result

Band	Channel	PCL	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GSM850	128	5	32.37	24.12	38.45	PASS
GSM850	190	5	32.53	24.28	38.45	PASS
GSM850	251	5	32.58	24.33	38.45	PASS
GSM1900	512	0	28.58	27.38	33.00	PASS
GSM1900	661	0	29.26	28.06	33.00	PASS
GSM1900	810	0	29.44	28.24	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GPRS850	128	5	1	32.01	23.76	38.45	PASS
GPRS850	128	5	2	30.92	22.67	38.45	PASS
GPRS850	128	5	3	28.79	20.54	38.45	PASS
GPRS850	128	5	4	27.42	19.17	38.45	PASS
GPRS850	190	5	1	32.54	24.29	38.45	PASS
GPRS850	190	5	2	31.44	23.19	38.45	PASS
GPRS850	190	5	3	29.33	21.08	38.45	PASS
GPRS850	190	5	4	27.97	19.72	38.45	PASS
GPRS850	251	5	1	32.63	24.38	38.45	PASS
GPRS850	251	5	2	31.56	23.31	38.45	PASS
GPRS850	251	5	3	29.45	21.2	38.45	PASS
GPRS850	251	5	4	28.11	19.86	38.45	PASS
GPRS1900	512	0	1	28.58	27.38	33.00	PASS
GPRS1900	512	0	2	27.44	26.24	33.00	PASS
GPRS1900	512	0	3	25.32	24.12	33.00	PASS
GPRS1900	512	0	4	24.05	22.85	33.00	PASS
GPRS1900	661	0	1	29.17	27.97	33.00	PASS
GPRS1900	661	0	2	28.10	26.9	33.00	PASS
GPRS1900	661	0	3	25.96	24.76	33.00	PASS
GPRS1900	661	0	4	24.72	23.52	33.00	PASS
GPRS1900	810	0	1	29.35	28.15	33.00	PASS
GPRS1900	810	0	2	28.26	27.06	33.00	PASS
GPRS1900	810	0	3	26.15	24.95	33.00	PASS
GPRS1900	810	0	4	24.89	23.69	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
EGPRS850	128	8	1	27.37	19.12	38.45	PASS
EGPRS850	128	8	2	25.42	17.17	38.45	PASS
EGPRS850	128	8	3	22.55	14.3	38.45	PASS
EGPRS850	128	8	4	21.05	12.8	38.45	PASS
EGPRS850	190	8	1	27.58	19.33	38.45	PASS
EGPRS850	190	8	2	25.98	17.73	38.45	PASS
EGPRS850	190	8	3	23.41	15.16	38.45	PASS
EGPRS850	190	8	4	21.46	13.21	38.45	PASS
EGPRS850	251	8	1	27.69	19.44	38.45	PASS
EGPRS850	251	8	2	26.05	17.8	38.45	PASS
EGPRS850	251	8	3	23.55	15.3	38.45	PASS
EGPRS850	251	8	4	21.54	13.29	38.45	PASS
EGPRS1900	512	2	1	25.94	24.74	33.00	PASS
EGPRS1900	512	2	2	24.79	23.59	33.00	PASS
EGPRS1900	512	2	3	22.72	21.52	33.00	PASS
EGPRS1900	512	2	4	21.41	20.21	33.00	PASS
EGPRS1900	661	2	1	26.44	25.24	33.00	PASS
EGPRS1900	661	2	2	25.28	24.08	33.00	PASS
EGPRS1900	661	2	3	23.20	22	33.00	PASS
EGPRS1900	661	2	4	21.94	20.74	33.00	PASS
EGPRS1900	810	2	1	26.55	25.35	33.00	PASS
EGPRS1900	810	2	2	25.42	24.22	33.00	PASS
EGPRS1900	810	2	3	23.34	22.14	33.00	PASS
EGPRS1900	810	2	4	22.10	20.9	33.00	PASS

Remark: EIRP (dBm) = Conducted power (dBm) + Antenna Gain (dBi). (For GSM1900)

ERP (dBm) = EIRP (dBm) - 2.15 (dB). (For GSM850)


Appendix B: Peak-to-Average Ratio(CCDF)

Test Result

Band	Channel	PCL	Result(dB)	Limit(dB)	Verdict
GSM850	190	5	2.73	13	PASS
EGPRS850	190	8	5.59	13	PASS
GSM1900	661	0	2.8	13	PASS
EGPRS1900	661	2	5.5	13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





Appendix C: 26dB Bandwidth and Occupied Bandwidth

Test Result

Band	Channel	PCL	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
GSM850	128	5	0.24626	0.3134	---	PASS
GSM850	190	5	0.24493	0.3156	---	PASS
GSM850	251	5	0.24700	0.3184	---	PASS
EGPRS850	128	8	0.25012	0.3088	---	PASS
EGPRS850	190	8	0.24758	0.3168	---	PASS
EGPRS850	251	8	0.25095	0.3125	---	PASS
GSM1900	512	0	0.24534	0.3131	---	PASS
GSM1900	661	0	0.24380	0.3131	---	PASS
GSM1900	810	0	0.24596	0.3133	---	PASS
EGPRS1900	512	2	0.25203	0.3221	---	PASS
EGPRS1900	661	2	0.24901	0.3242	---	PASS
EGPRS1900	810	2	0.25037	0.3205	---	PASS

Test Graphs







Appendix D: Band Edge

Test Result

Band	Channel	PCL	Freq (MHz)	Result (dBm)	Limit(dBm)	Verdict
GSM850	128	5	823.98	-25.54	-13	PASS
GSM850	251	5	849.02	-22.54	-13	PASS
EGPRS850	128	8	823.99	-33.92	-13	PASS
EGPRS850	251	8	849.02	-34.07	-13	PASS
GSM1900	512	0	1850.00	-14.05	-13	PASS
GSM1900	810	0	1910.02	-13.99	-13	PASS
EGPRS1900	512	2	1849.99	-22.70	-13	PASS
EGPRS1900	810	2	1910.01	-19.79	-13	PASS

Test Graphs






Appendix E: Conducted Spurious Emission

Test Result

Band	Channel	PCL	Frequency Range(MHz)	Max.Freq. (MHz)	Result (dBm)	Limit (dBm)	Verdict
GSM850	128	5	0.009~0.15MHz	0.01	-53.45	-33	PASS
GSM850	128	5	0.15~30MHz	0.15	-42.37	-13	PASS
GSM850	128	5	30~1000MHz	928.67	-44.33	-13	PASS
GSM850	128	5	1000~10000MHz	2473	-23.83	-13	PASS
GSM850	190	5	0.009~0.15MHz	0.01	-52.15	-33	PASS
GSM850	190	5	0.15~30MHz	0.15	-42.38	-13	PASS
GSM850	190	5	30~1000MHz	493.72	-44.68	-13	PASS
GSM850	190	5	1000~10000MHz	2509.6	-24.78	-13	PASS
GSM850	251	5	0.009~0.15MHz	0.01	-55.23	-33	PASS
GSM850	251	5	0.15~30MHz	0.15	-42.5	-13	PASS
GSM850	251	5	30~1000MHz	720.32	-45.32	-13	PASS
GSM850	251	5	1000~10000MHz	2546.5	-26.03	-13	PASS
GSM1900	512	0	0.009~0.15MHz	0.01	-56.54	-43	PASS
GSM1900	512	0	0.15~30MHz	0.15	-42.54	-23	PASS
GSM1900	512	0	30~1000MHz	710.71	-45.09	-13	PASS
GSM1900	512	0	1000~18000MHz	17043.47	-21.69	-13	PASS
GSM1900	661	0	0.009~0.15MHz	0.01	-54.49	-43	PASS
GSM1900	661	0	0.15~30MHz	0.16	-41.43	-23	PASS
GSM1900	661	0	30~1000MHz	942.38	-45.36	-13	PASS
GSM1900	661	0	1000~18000MHz	16719.9	-21.75	-13	PASS
GSM1900	810	0	0.009~0.15MHz	0.01	-53.75	-43	PASS
GSM1900	810	0	0.15~30MHz	0.16	-40.7	-23	PASS
GSM1900	810	0	30~1000MHz	576.27	-44.87	-13	PASS
GSM1900	810	0	1000~18000MHz	16991.33	-21.77	-13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





JianYan Testing Group Shenzhen Co., Ltd.


No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Project No.: JYTSZR2407075







Appendix F: Frequency Stability

Test Result

Reference Frequency: GSM850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	-0.52	-0.000622	±2.5	Pass
	-20	-1.39	-0.001661		
	-10	0.42	0.000502		
	0	0.81	0.000968		
	10	-0.61	-0.000729		
	20	-0.36	-0.000430		
	30	0.97	0.001159		
	40	1.81	0.002164		
	50	-1.39	-0.001661		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.00	-1.13	-0.001351	±2.5	Pass
	3.85	-0.29	-0.000347		
	4.40	0.19	0.000227		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	3.26	0.003897	±2.5	Pass
	-20	11.78	0.014081		
	-10	11.95	0.014284		
	0	9.56	0.011427		
	10	13.88	0.016591		
	20	18.21	0.021767		
	30	17.66	0.021109		
	40	16.69	0.019950		
	50	15.82	0.018910		
Voltage					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.00	9.40	0.011236	±2.5	Pass
	3.85	9.98	0.011929		
	4.40	9.78	0.011690		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: PCS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	27.02	0.014372	Within authorized band for PCS 1900	Pass
	-20	24.05	0.012793		
	-10	30.74	0.016351		
	0	27.41	0.014580		
	10	23.70	0.012606		
	20	28.99	0.015420		
	30	25.18	0.013394		
	40	27.51	0.014633		
	50	22.54	0.011989		
Voltage					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.00	24.92	0.013255	Within authorized band for PCS 1900	Pass
	3.85	30.61	0.016282		
	4.40	24.70	0.013138		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	19.15	0.010186	Within authorized band for PCS 1900	Pass
	-20	25.44	0.013532		
	-10	24.63	0.013101		
	0	21.60	0.011489		
	10	15.63	0.008314		
	20	19.79	0.010527		
	30	20.47	0.010888		
	40	15.95	0.008484		
	50	10.91	0.005803		
Voltage					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.00	23.05	0.012261	Within authorized band for PCS 1900	Pass
	3.85	28.86	0.015351		
	4.40	22.21	0.011814		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Appendix G: Modulation Characteristics

Test Result

Band	Channel	Result	Verdict
GSM850	190	PASS	PASS
EGPRS850	190	PASS	PASS
GSM1900	661	PASS	PASS
EGPRS1900	661	PASS	PASS

Remark: All channel had been tested, but only the worst case data displayed in this report.

Test Graphs

