

Report No.: WSCT-ANAB-R&E241200075A-RF

NR Bands

n5:

Horizontal:



Susputed Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1517.5000	-64.42	0.39	-64.81	-13	-51.42	80.6	Horizontal	PK	Pass
1	1517.5000		0.39		54		80.6	Horizontal	AV	Pass
2	1932.5000	-63.24	2.39	-65.63	-13	-50.24	340	Horizontal	PK	Pass
2	1932.5000		2.39		54		340	Horizontal	AV	Pass
3	2423.5000	-51.72	5.79	-57.51	-13	-38.72	282.6	Horizontal	PK	Pass
3	2423.5000		5.79		54		282.6	Horizontal	AV	Pass
4	6429.3750	-74.13	33.96	-108.09	-13	-61.13	67.8	Horizontal	PK	Pass
4	6429.3750		33.96		54		67.8	Horizontal	AV	Pass
5	9129.3750	-67.33	37.49	-104.82	-13	-54.33	-0.1	Horizontal	PK	Pass
5	9129.3750		37.49		54		-0.1	Horizontal	AV	Pass
6	14336.2500	-57.1	41.06	-98.16	-13	-44.1	145.5	Horizontal	PK	Pass
6	14336.2500		41.06		54		145.5	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

Vertical:




Suspected Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1485.5000	-65.34	0.21	-65.55	-13	-52.34	56.6	Vertical	PK	Pass
1	1485.5000		0.21		54		56.6	Vertical	AV	Pass
2	1865.7500	-63.88	2.02	-65.9	-13	-50.88	0.5	Vertical	PK	Pass
2	1865.7500		2.02		54		0.5	Vertical	AV	Pass
3	2434.7500	-54.01	5.8	-59.81	-13	-41.01	258.7	Vertical	PK	Pass
3	2434.7500		5.8		54		258.7	Vertical	AV	Pass
4	7018.1250	-73.14	35.53	-108.67	-13	-60.14	223.3	Vertical	PK	Pass
4	7018.1250		35.53		54		223.3	Vertical	AV	Pass
5	9748.1250	-64.94	37.92	-102.86	-13	-51.94	0	Vertical	PK	Pass
5	9748.1250		37.92		54		0	Vertical	AV	Pass
6	15123.7500	-57.64	39.82	-97.46	-13	-44.64	126.4	Vertical	PK	Pass
6	15123.7500		39.82		54		126.4	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF


n7:
Horizontal:



Susputed Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2501.2500	-60.14	7.42	-67.56	-13	-47.14	335.2	Horizontal	PK	Pass
1	2501.2500		7.42		54		335.2	Horizontal	AV	Pass
2	3872.5000	-54.48	12.54	-67.02	-13	-41.48	141.5	Horizontal	PK	Pass
2	3872.5000		12.54		54		141.5	Horizontal	AV	Pass
3	5735.0000	-48.18	22.59	-70.77	-13	-35.18	360	Horizontal	PK	Pass
3	5735.0000		22.59		54		360	Horizontal	AV	Pass
4	9798.0000	-65.75	37.96	-103.71	-13	-52.75	-0.1	Horizontal	PK	Pass
4	9798.0000		37.96		54		-0.1	Horizontal	AV	Pass
5	11046.0000	-62.38	39.46	-101.84	-13	-49.38	127.5	Horizontal	PK	Pass
5	11046.0000		39.46		54		127.5	Horizontal	AV	Pass
6	14211.0000	-57.85	41.23	-99.08	-13	-44.85	48.6	Horizontal	PK	Pass
6	14211.0000		41.23		54		48.6	Horizontal	AV	Pass

Vertical:



Susputed Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2663.7500	-59.85	7.65	-67.5	-13	-46.85	151.1	Vertical	PK	Pass
1	2663.7500		7.65		54		151.1	Vertical	AV	Pass
2	3835.6250	-54.93	12.41	-67.34	-13	-41.93	360.1	Vertical	PK	Pass
2	3835.6250		12.41		54		360.1	Vertical	AV	Pass
3	5748.1250	-32.01	22.46	-54.47	-13	-19.01	49.5	Vertical	PK	Pass
3	5748.1250		22.46		54		49.5	Vertical	AV	Pass
4	9682.5000	-66.61	37.88	-104.49	-13	-53.61	83.4	Vertical	PK	Pass
4	9682.5000		37.88		54		83.4	Vertical	AV	Pass
5	11548.5000	-61.45	39.01	-100.46	-13	-48.45	359	Vertical	PK	Pass
5	11548.5000		39.01		54		359	Vertical	AV	Pass
6	14271.0000	-57.51	41.15	-98.66	-13	-44.51	0	Vertical	PK	Pass
6	14271.0000		41.15		54		0	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

n12:
Horizontal:



Suspected Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1768.7500	-65.87	1.56	-67.43	-13	-52.87	149.9	Horizontal	PK	Pass
1	1768.7500		1.56		54		149.9	Horizontal	AV	Pass
2	2406.2500	-58.2	6.12	-64.32	-13	-45.2	18.2	Horizontal	PK	Pass
2	2406.2500		6.12		54		18.2	Horizontal	AV	Pass
3	3416.2500	-36.82	10.52	-47.34	-13	-23.82	255.1	Horizontal	PK	Pass
3	3416.2500		10.52		54		255.1	Horizontal	AV	Pass
4	9750.0000	-66.51	37.92	-104.43	-13	-53.51	0.1	Horizontal	PK	Pass
4	9750.0000		37.92		54		0.1	Horizontal	AV	Pass
5	12055.5000	-61.28	38.62	-99.9	-13	-48.28	136.1	Horizontal	PK	Pass
5	12055.5000		38.62		54		136.1	Horizontal	AV	Pass
6	14424.0000	-57.52	40.95	-98.47	-13	-44.52	268.8	Horizontal	PK	Pass
6	14424.0000		40.95		54		268.8	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

Vertical:



Susputed Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1691.8750	-61.95	1.22	-63.17	-13	-48.95	193	Vertical	PK	Pass
1	1691.8750		1.22		54		193	Vertical	AV	Pass
2	3744.3750	-54.97	11.87	-66.84	-13	-41.97	320.8	Vertical	PK	Pass
2	3744.3750		11.87		54		320.8	Vertical	AV	Pass
3	5791.2500	-40.05	22.04	-62.09	-13	-27.05	360	Vertical	PK	Pass
3	5791.2500		22.04		54		360	Vertical	AV	Pass
4	9025.5000	-67.7	37.42	-105.12	-13	-54.7	129.9	Vertical	PK	Pass
4	9025.5000		37.42		54		129.9	Vertical	AV	Pass
5	11745.0000	-60.66	38.83	-99.49	-13	-47.66	141.9	Vertical	PK	Pass
5	11745.0000		38.83		54		141.9	Vertical	AV	Pass
6	13989.0000	-57.61	41.47	-99.08	-13	-44.61	64.2	Vertical	PK	Pass
6	13989.0000		41.47		54		64.2	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

n38:
Horizontal:



Suspected Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1678.7500	-62.52	24.94	-87.46	-13	-49.52	1.3	Horizontal	PK	Pass
1	1678.7500		24.94		54		1.3	Horizontal	AV	Pass
2	3497.5000	-53.76	28.5	-82.26	-13	-40.76	177.4	Horizontal	PK	Pass
2	3497.5000		28.5		54		177.4	Horizontal	AV	Pass
3	5744.3750	-38.64	32.39	-71.03	-13	-25.64	360.1	Horizontal	PK	Pass
3	5744.3750		32.39		54		360.1	Horizontal	AV	Pass
4	10276.5000	-65.45	13.22	-78.67	-13	-52.45	327.3	Horizontal	PK	Pass
4	10276.5000		13.22		54		327.3	Horizontal	AV	Pass
5	11854.5000	-60.85	16.38	-77.23	-13	-47.85	250.7	Horizontal	PK	Pass
5	11854.5000		16.38		54		250.7	Horizontal	AV	Pass
6	17962.5000	-52.87	23.66	-76.53	-13	-39.87	204.1	Horizontal	PK	Pass
6	17962.5000		23.66		54		204.1	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

Vertical:




Susputed Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2226.2500	-62.83	4.84	-67.67	-13	-49.83	126.1	Vertical	PK	Pass
1	2226.2500		4.84		54		126.1	Vertical	AV	Pass
2	3343.1250	-58.69	9.94	-68.63	-13	-45.69	274.2	Vertical	PK	Pass
2	3343.1250		9.94		54		274.2	Vertical	AV	Pass
3	5991.8750	-48.27	22.69	-70.96	-13	-35.27	332.9	Vertical	PK	Pass
3	5991.8750		22.69		54		332.9	Vertical	AV	Pass
4	10969.5000	-62.74	39.46	-102.2	-13	-49.74	5.5	Vertical	PK	Pass
4	10969.5000		39.46		54		5.5	Vertical	AV	Pass
5	13669.5000	-58.61	40.64	-99.25	-13	-45.61	298.5	Vertical	PK	Pass
5	13669.5000		40.64		54		298.5	Vertical	AV	Pass
6	17968.5000	-53.72	46.29	-100.01	-13	-40.72	79.8	Vertical	PK	Pass
6	17968.5000		46.29		54		79.8	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

n41:
Horizontal:




Susputed Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1771.2500	-54.65	0.61	-55.26	-13	-41.65	31.7	Horizontal	PK	Pass
1	1771.2500		0.61		54		31.7	Horizontal	AV	Pass
2	3633.7500	-57.88	10.76	-68.64	-13	-44.88	348.2	Horizontal	PK	Pass
2	3633.7500		10.76		54		348.2	Horizontal	AV	Pass
3	5270.0000	-51.41	18.97	-70.38	-13	-38.41	289.8	Horizontal	PK	Pass
3	5270.0000		18.97		54		289.8	Horizontal	AV	Pass
4	10201.5000	-64.8	38.38	-103.18	-13	-51.8	-0.1	Horizontal	PK	Pass
4	10201.5000		38.38		54		-0.1	Horizontal	AV	Pass
5	11745.0000	-60.57	38.83	-99.4	-13	-47.57	193.4	Horizontal	PK	Pass
5	11745.0000		38.83		54		193.4	Horizontal	AV	Pass
6	14307.0000	-57.33	41.1	-98.43	-13	-44.33	-0.1	Horizontal	PK	Pass
6	14307.0000		41.1		54		-0.1	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

Vertical:




Susputed Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	3068.7500	-59.7	8.3	-68	-13	-46.7	360.1	Vertical	PK	Pass
1	3068.7500		8.3		54		360.1	Vertical	AV	Pass
2	4711.2500	-52.68	15.93	-68.61	-13	-39.68	224	Vertical	PK	Pass
2	4711.2500		15.93		54		224	Vertical	AV	Pass
3	5770.0000	-38.33	21.54	-59.87	-13	-25.33	239.6	Vertical	PK	Pass
3	5770.0000		21.54		54		239.6	Vertical	AV	Pass
4	10018.5000	-64.98	38.13	-103.11	-13	-51.98	0	Vertical	PK	Pass
4	10018.5000		38.13		54		0	Vertical	AV	Pass
5	11745.0000	-60.69	38.83	-99.52	-13	-47.69	40.4	Vertical	PK	Pass
5	11745.0000		38.83		54		40.4	Vertical	AV	Pass
6	15087.0000	-57.7	39.93	-97.63	-13	-44.7	95.4	Vertical	PK	Pass
6	15087.0000		39.93		54		95.4	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF


n66:
Horizontal:



Susputed Data List										
NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2208.7500	-62.9	4.05	-66.95	-13	-49.9	171.5	Horizontal	PK	Pass
1	2208.7500		4.05		54		171.5	Horizontal	AV	Pass
2	3251.8750	-58.3	8.99	-67.29	-13	-45.3	126	Horizontal	PK	Pass
2	3251.8750		8.99		54		126	Horizontal	AV	Pass
3	5308.1250	-50.51	19.24	-69.75	-13	-37.51	128.4	Horizontal	PK	Pass
3	5308.1250		19.24		54		128.4	Horizontal	AV	Pass
4	9001.5000	-67.82	37.4	-105.22	-13	-54.82	342.6	Horizontal	PK	Pass
4	9001.5000		37.4		54		342.6	Horizontal	AV	Pass
5	11502.0000	-61.25	39.05	-100.3	-13	-48.25	359.4	Horizontal	PK	Pass
5	11502.0000		39.05		54		359.4	Horizontal	AV	Pass
6	15111.0000	-57.46	39.86	-97.32	-13	-44.46	359.6	Horizontal	PK	Pass
6	15111.0000		39.86		54		359.6	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

Vertical:




Susputed Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2228.7500	-63.18	4.27	-67.45	-13	-50.18	48.2	Vertical	PK	Pass
1	2228.7500		4.27		54		48.2	Vertical	AV	Pass
2	3316.8750	-59.41	9.28	-68.69	-13	-46.41	173.7	Vertical	PK	Pass
2	3316.8750		9.28		54		173.7	Vertical	AV	Pass
3	4708.1250	-52.35	15.95	-68.3	-13	-39.35	24.3	Vertical	PK	Pass
3	4708.1250		15.95		54		24.3	Vertical	AV	Pass
4	9633.0000	-40.14	37.84	-77.98	-13	-27.14	71.4	Vertical	PK	Pass
4	9633.0000		37.84		54		71.4	Vertical	AV	Pass
5	11007.0000	-36.97	39.49	-76.46	-13	-23.97	199.3	Vertical	PK	Pass
5	11007.0000		39.49		54		199.3	Vertical	AV	Pass
6	14079.0000	-34.8	41.4	-76.2	-13	-21.8	-0.1	Vertical	PK	Pass
6	14079.0000		41.4		54		-0.1	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

n71:
Horizontal:




Susputed Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2120.6250	-64.01	3.61	-67.62	-13	-51.01	0.9	Horizontal	PK	Pass
1	2120.6250		3.61		54		0.9	Horizontal	AV	Pass
2	4158.7500	-55.66	12.93	-68.59	-13	-42.66	215.7	Horizontal	PK	Pass
2	4158.7500		12.93		54		215.7	Horizontal	AV	Pass
3	5963.7500	-47.49	22.58	-70.07	-13	-34.49	17.3	Horizontal	PK	Pass
3	5963.7500		22.58		54		17.3	Horizontal	AV	Pass
4	9510.0000	-67.5	37.76	-105.26	-13	-54.5	206.1	Horizontal	PK	Pass
4	9510.0000		37.76		54		206.1	Horizontal	AV	Pass
5	11745.0000	-61.01	38.83	-99.84	-13	-48.01	267.1	Horizontal	PK	Pass
5	11745.0000		38.83		54		267.1	Horizontal	AV	Pass
6	17998.5000	-54.19	46.49	-100.68	-13	-41.19	181	Horizontal	PK	Pass
6	17998.5000		46.49		54		181	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

Vertical:




Suspected Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2033.7500	-63.43	26.01	-89.44	-13	-50.43	228.6	Vertical	PK	Pass
1	2033.7500		26.01		54		228.6	Vertical	AV	Pass
2	3834.3750	-55.99	29.3	-85.29	-13	-42.99	202.3	Vertical	PK	Pass
2	3834.3750		29.3		54		202.3	Vertical	AV	Pass
3	5743.1250	-38.98	32.39	-71.37	-13	-25.98	349	Vertical	PK	Pass
3	5743.1250		32.39		54		349	Vertical	AV	Pass
4	8484.0000	-40.67	9.19	-49.86	-13	-27.67	91.8	Vertical	PK	Pass
4	8484.0000		9.19		54		91.8	Vertical	AV	Pass
5	13938.0000	-35.67	18.94	-54.61	-13	-22.67	-0.1	Vertical	PK	Pass
5	13938.0000		18.94		54		-0.1	Vertical	AV	Pass
6	17866.5000	-31.42	23.05	-54.47	-13	-18.42	327.3	Vertical	PK	Pass
6	17866.5000		23.05		54		327.3	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

n77(3450-3550Mhz):

Horizontal:




Susputed Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2556.2500	-62.08	5.79	-67.87	-13	-49.08	260.3	Horizontal	PK	Pass
1	2556.2500				54		260.3	Horizontal	AV	Pass
2	4225.6250	-56.66	12.77	-69.43	-13	-43.66	260.3	Horizontal	PK	Pass
2	4225.6250				54		260.3	Horizontal	AV	Pass
3	5708.1250	-49.91	21.79	-71.7	-13	-36.91	284.2	Horizontal	PK	Pass
3	5708.1250				54		284.2	Horizontal	AV	Pass
4	11884.5000	-60.69	38.7	-99.39	-13	-47.69	275.4	Horizontal	PK	Pass
4	11884.5000				54		275.4	Horizontal	AV	Pass
5	14337.0000	-57.08	41.06	-98.14	-13	-44.08	0.4	Horizontal	PK	Pass
5	14337.0000				54		0.4	Horizontal	AV	Pass
6	17905.5000	-53.56	45.87	-99.43	-13	-40.56	21.1	Horizontal	PK	Pass
6	17905.5000				54		21.1	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

Vertical:




Suspected Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2530.0000	-61.37	5.69	-67.06	-13	-48.37	0	Vertical	PK	Pass
1	2530.0000				54		0	Vertical	AV	Pass
2	3401.8750	-53.59	9.16	-62.75	-13	-40.59	29.6	Vertical	PK	Pass
2	3401.8750				54		29.6	Vertical	AV	Pass
3	5706.2500	-49.77	21.76	-71.53	-13	-36.77	349.8	Vertical	PK	Pass
3	5706.2500				54		349.8	Vertical	AV	Pass
4	10636.5000	-63.45	38.99	-102.44	-13	-50.45	72.2	Vertical	PK	Pass
4	10636.5000				54		72.2	Vertical	AV	Pass
5	13617.0000	-58.91	40.5	-99.41	-13	-45.91	208.5	Vertical	PK	Pass
5	13617.0000				54		208.5	Vertical	AV	Pass
6	17935.5000	-53.99	46.07	-100.06	-13	-40.99	332.8	Vertical	PK	Pass
6	17935.5000				54		332.8	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

n77(3700-3980Mhz):
Horizontal:




Suspected Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	3497.5000	-54.75	10.46	-65.21	-13	-41.75	135.9	Horizontal	PK	Pass
1	3497.5000				54		135.9	Horizontal	AV	Pass
2	4251.2500	-51.64	17.45	-69.09	-13	-38.64	46.2	Horizontal	PK	Pass
2	4251.2500				54		46.2	Horizontal	AV	Pass
3	5792.5000	-47.61	20.88	-68.49	-13	-34.61	123.9	Horizontal	PK	Pass
3	5792.5000				54		123.9	Horizontal	AV	Pass
4	10813.5000	-63.87	39.24	-103.11	-13	-50.87	290.9	Horizontal	PK	Pass
4	10813.5000				54		290.9	Horizontal	AV	Pass
5	14368.5000	-58.24	41.02	-99.26	-13	-45.24	192.8	Horizontal	PK	Pass
5	14368.5000				54		192.8	Horizontal	AV	Pass
6	17958.0000	-52.79	46.22	-99.01	-13	-39.79	355	Horizontal	PK	Pass
6	17958.0000				54		355	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

Vertical:




Suspected Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2304.3750	-62.81	26.93	-89.74	-13	-49.81	244.4	Vertical	PK	Pass
1	2304.3750		26.93		54		244.4	Vertical	AV	Pass
2	4252.5000	-52.18	30.15	-82.33	-13	-39.18	291	Vertical	PK	Pass
2	4252.5000		30.15		54		291	Vertical	AV	Pass
3	5747.5000	-49.44	32.4	-81.84	-13	-36.44	158.3	Vertical	PK	Pass
3	5747.5000		32.4		54		158.3	Vertical	AV	Pass
4	10539.0000	-64.45	14.08	-78.53	-13	-51.45	250.8	Vertical	PK	Pass
4	10539.0000		14.08		54		250.8	Vertical	AV	Pass
5	13912.5000	-58.42	18.86	-77.28	-13	-45.42	359.5	Vertical	PK	Pass
5	13912.5000		18.86		54		359.5	Vertical	AV	Pass
6	17988.0000	-54.05	23.84	-77.89	-13	-41.05	103.8	Vertical	PK	Pass
6	17988.0000		23.84		54		103.8	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

n78(3450-3550Mhz):
Horizontal:



Suspected Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2475.0000	-62.38	5.34	-67.72	-13	-49.38	205	Horizontal	PK	Pass
1	2475.0000		5.34		54		205	Horizontal	AV	Pass
2	3498.1250	-53.82	9.22	-63.04	-13	-40.82	128.4	Horizontal	PK	Pass
2	3498.1250		9.22		54		128.4	Horizontal	AV	Pass
3	5700.0000	-50.05	21.64	-71.69	-13	-37.05	355.9	Horizontal	PK	Pass
3	5700.0000		21.64		54		355.9	Horizontal	AV	Pass
4	9406.5000	-67.54	37.68	-105.22	-13	-54.54	301	Horizontal	PK	Pass
4	9406.5000		37.68		54		301	Horizontal	AV	Pass
5	13963.5000	-58.64	41.41	-100.05	-13	-45.64	359	Horizontal	PK	Pass
5	13963.5000		41.41		54		359	Horizontal	AV	Pass
6	17958.0000	-54	46.22	-100.22	-13	-41	301	Horizontal	PK	Pass
6	17958.0000		46.22		54		301	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

Vertical:



Suspected Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2183.1250	-64.23	3.47	-67.7	-13	-51.23	90.2	Vertical	PK	Pass
1	2183.1250		3.47		54		90.2	Vertical	AV	Pass
2	3495.6250	-52.37	9.22	-61.59	-13	-39.37	360.1	Vertical	PK	Pass
2	3495.6250		9.22		54		360.1	Vertical	AV	Pass
3	5732.5000	-49.27	21.53	-70.8	-13	-36.27	360.1	Vertical	PK	Pass
3	5732.5000		21.53		54		360.1	Vertical	AV	Pass
4	10533.0000	-62.9	38.85	-101.75	-13	-49.9	159.9	Vertical	PK	Pass
4	10533.0000		38.85		54		159.9	Vertical	AV	Pass
5	13966.5000	-57.96	41.41	-99.37	-13	-44.96	281.8	Vertical	PK	Pass
5	13966.5000		41.41		54		281.8	Vertical	AV	Pass
6	17802.0000	-53.87	45.17	-99.04	-13	-40.87	169.5	Vertical	PK	Pass
6	17802.0000		45.17		54		169.5	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

n78(3700-3800Mhz):
Horizontal:




Suspected Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	3242.5000	-59.22	10.31	-69.53	-13	-46.22	136.7	Horizontal	PK	Pass
1	3242.5000		10.31		54		136.7	Horizontal	AV	Pass
2	4224.3750	-52.25	16.38	-68.63	-13	-39.25	196.5	Horizontal	PK	Pass
2	4224.3750		16.38		54		196.5	Horizontal	AV	Pass
3	5690.6250	-48.82	21.65	-70.47	-13	-35.82	136.7	Horizontal	PK	Pass
3	5690.6250		21.65		54		136.7	Horizontal	AV	Pass
4	10692.0000	-63.5	39.07	-102.57	-13	-50.5	138.3	Horizontal	PK	Pass
4	10692.0000		39.07		54		138.3	Horizontal	AV	Pass
5	13993.5000	-57.35	41.48	-98.83	-13	-44.35	52.2	Horizontal	PK	Pass
5	13993.5000		41.48		54		52.2	Horizontal	AV	Pass
6	17928.0000	-54.24	46.02	-100.26	-13	-41.24	-0.1	Horizontal	PK	Pass
6	17928.0000		46.02		54		-0.1	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

Vertical:



Suspected Data List

NO.	Freq. [MHz]	Reading [dB(m)]	Factor [dB]	Level [dB(m)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2453.1250	-63.08	5.98	-69.06	-13	-50.08	6.2	Vertical	PK	Pass
1	2453.1250				54		6.2	Vertical	AV	Pass
2	3402.5000	-52.46	10.4	-62.86	-13	-39.46	188.2	Vertical	PK	Pass
2	3402.5000				54		188.2	Vertical	AV	Pass
3	5919.3750	-49.21	21.33	-70.54	-13	-36.21	20.2	Vertical	PK	Pass
3	5919.3750				54		20.2	Vertical	AV	Pass
4	11368.5000	-61.92	39.17	-101.09	-13	-48.92	177.8	Vertical	PK	Pass
4	11368.5000				54		177.8	Vertical	AV	Pass
5	14343.0000	-56.91	41.05	-97.96	-13	-43.91	12.9	Vertical	PK	Pass
5	14343.0000				54		12.9	Vertical	AV	Pass
6	17988.0000	-53.43	46.42	-99.85	-13	-40.43	9.8	Vertical	PK	Pass
6	17988.0000				54		9.8	Vertical	AV	Pass

9. OCCUPIED BANDWIDTH & EMISSION BANDWIDTH

Test limit:

The occupied bandwidth (OBW), that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission, shall be measured when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudo-random generators or other devices required in normal service. Additionally, the occupied bandwidth shall be shown for operation with any devices used for modifying the spectrum when such devices are optional at the discretion of the user. [i2.1049(h)]

Many of the individual rule parts specify a relative OBW in lieu of the 99% OBW. In such cases, the OBW is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated by at least X dB below the transmitter power, where the value of X is typically specified as 26.

The relative OBW must be measured and reported when it is specified in the applicable rule part; otherwise, the 99% OBW shall be measured and reported. The test report shall specify which OBW is reported.

A spectrum/signal analyzer or other instrument providing a spectral display is recommended for these measurements and the video bandwidth shall be set to a value at least three times greater than the IF/resolution bandwidth to avoid any amplitude smoothing. Video filtering shall not be used during occupied bandwidth tests.

The OBW shall be measured for all operating conditions that will affect the bandwidth results (e.g. variable modulations, coding, or channel bandwidth settings). See section 4.

Test procedure:

Occupied bandwidth – relative measurement procedure

The reference value is the highest level of the spectral envelope of the modulated signal.

- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
- The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- Set the reference level of the instrument as required to prevent the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least 10log (OBW / RBW) below the reference level.
- NOTE—Steps a) through c) may require iteration to adjust within the specified tolerances.
- The dynamic range of the spectrum analyzer at the selected RBW shall be at least 10 dB below the target “-X dB down” requirement (i.e., if the requirement calls for measuring the -26 dB OBW, the spectrum analyzer noise floor at the selected RBW shall be at least 36 dB below the reference value).
- Set the detection mode to peak, and the trace mode to max hold.
- Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- Determine the “-X dB down amplitude” as equal to (Reference Value – X). Alternatively, this calculation can be performed by the analyzer by using the marker-delta function.
- Place two markers, one at the lowest and the other at the highest frequency of the

Report No.: WSCT-ANAB-R&E241200075A-RF

envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step g). If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.

j) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display. The frequency and amplitude axes and scale shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Occupied bandwidth – power bandwidth (99%) measurement procedure

The following procedure shall be used for measuring (99 %) power bandwidth

a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).

b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.

c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least 10log (OBW / RBW) below the reference level.

d) NOTE—Steps a) through c) may require iteration to adjust within the specified tolerances.


e) Set the detection mode to peak, and the trace mode to max hold..

f) Use the 99 % power bandwidth function of the spectrum analyzer (if available) and report the measured bandwidth.

g) If the instrument does not have a 99 % power bandwidth function, the trace data points are to be recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99 % power bandwidth is the difference between these two frequencies.

h) The OBW shall be reported by providing plot(s) of the measuring instrument display. The frequency and amplitude axes and scale shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Test setup:



9.1. Measurement Result

GSM850:

Frequency	OBW(99%)	26dB BW
824.2	241.99KHz	299.68KHz
836.6	240.38KHz	298.08KHz
848.8	241.99KHz	296.47KHz

PCS1900:

Frequency	OBW(99%)	26dB BW
1850.2	241.99KHz	298.08KHz
1880	243.59KHz	299.68KHz
1909.8	243.59KHz	301.28KHz

GPRS850:

Frequency	OBW(99%)	26dB BW
824.2	243.59KHz	314.10KHz
836.6	243.59KHz	317.31KHz
848.8	241.99KHz	316.03KHz

GPRS 1900:

Frequency	OBW(99%)	26dB BW
1850.2	243.59KHz	307.69KHz
1880	245.19KHz	315.71KHz
1909.8	243.59KHz	314.10KHz

EGPRS 850:

Frequency	OBW(99%)	26dB BW
824.2	240.38KHz	301.28KHz
836.6	241.99KHz	306.09KHz
848.8	240.38KHz	296.47KHz

EGPRS 1900:

Frequency	OBW(99%)	26dB BW
1850.2	240.38KHz	299.68KHz
1880	238.78KHz	301.28KHz
1909.8	240.38KHz	301.28KHz

UTRA BANDS

Band 2:

Frequency	OBW(99%)	26dB BW
1852.4	4.167MHz	4.679MHz
1880	4.151MHz	4.679MHz
1907.6	4.167MHz	4.696MHz

Band 4:

Frequency	OBW(99%)	26dB BW
1712.4	4.151MHz	4.696MHz
1732.6	4.151MHz	4.696MHz
1752.6	4.119MHz	4.715MHz


Band 5:

Frequency	OBW(99%)	26dB BW
826.4	4.151MHz	4.679MHz
836.4	4.151MHz	4.679MHz
846.6	4.167MHz	4.675MHz

Report No.: WSCT-ANAB-R&E241200075A-RF


Test Plot(s)

Occupied Bandwidth (99% and -26dBc) GSM 850 Band CH 128




Report No.: WSCT-ANAB-R&E241200075A-RF

Occupied Bandwidth (99% and -26dBc) GSM 850 Band CH 190




Date: 3.DEC.2024 15:49:32

Occupied Bandwidth (99% and -26dBc) GSM 850 Band CH 251




Date: 3.DEC.2024 15:46:03

Occupied Bandwidth (99% and -26dBc) PCS 1900 Band CH 512



Date: 3.DEC.2024 16:47:08


Occupied Bandwidth (99% and -26dBc) PCS 1900 Band CH 661



Date: 3.DEC.2024 16:45:54


Report No.: WSCT-ANAB-R&E241200075A-RF

Occupied Bandwidth (99% and -26dBc) PCS 1900 Band CH 810



Date: 3.DEC.2024 16:44:17


Occupied Bandwidth (99% and -26dBc) GPRS 850 Band CH 128



Date: 3.DEC.2024 15:27:25


Report No.: WSCT-ANAB-R&E241200075A-RF

Occupied Bandwidth (99% and -26dBc) GPRS 850 Band CH 190



Date: 3.DEC.2024 15:23:38


Occupied Bandwidth (99% and -26dBc) GPRS 850 Band CH 251




Date: 3.DEC.2024 15:20:47

Report No.: WSCT-ANAB-R&E241200075A-RF

Occupied Bandwidth (99% and -26dBc) GPRS 1900 Band CH 512




Occupied Bandwidth (99% and -26dBc) GPRS 1900 Band CH 661




Report No.: WSCT-ANAB-R&E241200075A-RF

Occupied Bandwidth (99% and -26dBc) GPRS 1900 Band CH 810



Date: 3.DEC.2024 16:23:04


Occupied Bandwidth (99% and -26dBc) EGPRS 850 Band CH 128



Date: 3.DEC.2024 15:33:20


Report No.: WSCT-ANAB-R&E241200075A-RF

Occupied Bandwidth (99% and -26dBc) EGPRS 850 Band CH 190



Date: 3.DEC.2024 15:37:43


Occupied Bandwidth (99% and -26dBc) EGPRS 850 Band CH 251




Date: 3.DEC.2024 15:41:39

Report No.: WSCT-ANAB-R&E241200075A-RF

Occupied Bandwidth (99% and -26dBc) EGPRS 1900 Band CH 512




Occupied Bandwidth (99% and -26dBc) EGPRS 1900 Band CH 661



Report No.: WSCT-ANAB-R&E241200075A-RF


Occupied Bandwidth (99% and -26dBc) EGPRS 1900 Band CH 810



Date: 3.DEC.2024 16:37:31

UTRA BANDS


Occupied Bandwidth (99% and -26dBc) WCDMA Band 2 CH 9262



Date: 3.DEC.2024 14:30:06


Report No.: WSCT-ANAB-R&E241200075A-RF

Occupied Bandwidth (99%and-26dBc) WCDMA Band 2 CH 9400



Date: 3.DEC.2024 14:28:40


Occupied Bandwidth (99%and-26dBc) WCDMA Band 2 CH 9538



Date: 3.DEC.2024 14:26:52


Report No.: WSCT-ANAB-R&E241200075A-RF

Occupied Bandwidth (99% and -26dBc) WCDMA Band 4 CH 1312



Date: 3.DEC.2024 09:33:21


Occupied Bandwidth (99% and -26dBc) WCDMA Band 4 CH 1413



Date: 3.DEC.2024 09:31:27


Report No.: WSCT-ANAB-R&E241200075A-RF

Occupied Bandwidth (99% and -26dBc) WCDMA Band 4 CH 1513



Date: 3.DEC.2024 09:28:25


Occupied Bandwidth (99%and-26dBc) WCDMA Band 5 CH 4132



Date: 3.DEC.2024 14:13:54


Report No.: WSCT-ANAB-R&E241200075A-RF

Occupied Bandwidth (99%and-26dBc) WCDMA Band 5 CH 4182



Date: 3.DEC.2024 14:12:09

Occupied Bandwidth (99%and-26dBc) WCDMA Band 5 CH 4233



Date: 3.DEC.2024 14:07:52

Note: Please refer to Annex (LTE&NR Occupied Bandwidth) for more test data

10. BAND EDGE


Test Limit:

The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in §2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified. See section 4.

Test procedure:

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.


Test setup:



10.1. Measurement Result


Test Plot(s)

Low Band Edge GSM 850 Band CH 128




Date: 3.DEC.2024 14:43:06

High Band Edge GSM 850 Band CH 251




Low Band Edge PCS 1900 Band CH 512




Date: 3.DEC.2024 16:09:25

High Band Edge PCS 1900 Band CH 810




Date: 3.DEC.2024 16:12:09


Low Band Edge WCDMA Band 2 CH 9263




High Band Edge WCDMA Band 2 CH 9537




Low Band Edge WCDMA Band 4 CH 1312



Low Band Edge WCDMA Band 4 CH 1513




Low Band Edge WCDMA Band 5 CH 4132



Date: 3.DEC.2024 14:03:31

High Band Edge WCDMA Band 5 CH 4233



Date: 3.DEC.2024 14:05:35

Note: Please refer to Annex (LTE&NR Band Edge) for more test data

11. SPURIOUS EMISSION (Conducted and Radiated)

11.1. Measurement Result (Pre-measurement)

GSM850:

Test Channel	BW(MHz)	UL Channel	Frequency(MHz)	Judgment
Low Range	0.2	128	824.2	Pass
Middle Range	0.2	190	836.6	Pass
High Range	0.2	251	848.8	Pass

PCS 1900 :

Test Channel	BW(MHz)	UL Channel	Frequency(MHz)	Judgment
Low Range	0.2	512	1850.2	Pass
Middle Range	0.2	661	1880.0	Pass
High Range	0.2	810	1909.8	Pass

UTRA BANDS

Band 2:

Test Channel	BW(MHz)	UL Channel	Frequency(MHz)	Judgment
Low Range	5	9262	1852.4	Pass
Middle Range	5	9400	1880.0	Pass
High Range	5	9538	1907.6	Pass

Band 4:

Test Channel	BW(MHz)	UL Channel	Frequency(MHz)	Judgment
Low Range	5	1312	1712.4	Pass
Middle Range	5	1413	1732.6	Pass
High Range	5	1513	1752.6	Pass

Band 5:

Test Channel	BW(MHz)	UL Channel	Frequency(MHz)	Judgment
Low Range	5	4132	826.4	Pass
Middle Range	5	4182	836.4	Pass
High Range	5	4233	846.6	Pass

Report No.: WSCT-ANAB-R&E241200075A-RF

Test Plot(s)

Conducted method

Test limit:


The spurious (unwanted) emission limits specified in the individual FCC rule parts applicable to licensed digital transmitters (typically referred to under the heading 'emission limits') normally apply to any and all emissions that are present outside of the authorized frequency band/block and apply to emissions in both the out-of-band and spurious domains. In some rule parts, the unwanted emission limits are specified by an emission mask that defines the applicable limit as a function of the frequency range relative to the authorized frequency block.

Typically, unwanted emissions are required by the licensed rule parts to be attenuated below the transmitter power by a factor of at least $X + 10\log(P)$ dB, where P represents the transmitter power expressed in watts and X is a specified scalar value (e.g., 43). This specification can be interpreted in one of two equivalent ways. First, the required attenuation can be construed to be relative to the mean carrier power, with the resultant of the equation $X + 10\log(P)$ being expressed in dBc (dB relative to the maximum carrier power). Alternatively, the specification can be interpreted as an absolute limit when the specified attenuation is actually subtracted from the maximum permissible transmitter power [i.e., $10\log(P) - \{X + 10\log(P)\}$], resulting in an absolute level of -X dBW [or $(-X + 30)$ dBm]. See section 4.

Test procedure:

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz below 1 GHz and 1 MHz above 1 GHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonics.


Conducted Emission Test-Up:



Report No.: WSCT-ANAB-R&E241200075A-RF


CONDUCTED EMISSION IN GSM850 Band

Conducted Emission Transmitting Mode CH 128 30MHz – 1GHz




Date: 3.DEC.2024 14:53:44

Conducted Emission Transmitting Mode CH 128 1GHz – 9GHz




Date: 3.DEC.2024 14:52:26

Conducted Emission Transmitting Mode CH 190 30MHz – 1GHz




Date: 3.DEC.2024 14:54:57

Conducted Emission Transmitting Mode CH 190 1GHz – 9GHz




Date: 3.DEC.2024 14:50:50

Conducted Emission Transmitting Mode CH 251 30MHz – 1GHz




Date: 3.DEC.2024 14:58:51

Conducted Emission Transmitting Mode CH 251 1GHz – 9GHz



Date: 3.DEC.2024 14:49:47


CONDUCTED EMISSION IN PCS1900 BAND Conducted Emission Transmitting Mode CH 512 30MHz – 1GHz



Date: 3.DEC.2024 16:17:11


Report No.: WSCT-ANAB-R&E241200075A-RF

Conducted Emission Transmitting Mode CH 512 1GHz – 20GHz




Date: 3.DEC.2024 16:18:08

Conducted Emission Transmitting Mode CH 661 30MHz – 1GHz




Date: 3.DEC.2024 16:14:48

Conducted Emission Transmitting Mode CH 661 1GHz – 20GHz




Date: 3.DEC.2024 16:18:59

Conducted Emission Transmitting Mode CH 810 30MHz – 1GHz




Date: 3.DEC.2024 16:13:46


Conducted Emission Transmitting Mode CH 810 1GHz – 20GHz




CONDUCTED EMISSION IN WCDMA Band 2 Conducted Emission Transmitting Mode CH 9262 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 9262 1GHz – 20GHz



Conducted Emission Transmitting Mode CH 9400 30MHz – 1GHz




Conducted Emission Transmitting Mode CH 9400 1GHz – 20GHz



Date: 3.DEC.2024 14:33:22

Conducted Emission Transmitting Mode CH 9538 30MHz – 1GHz



Date: 3.DEC.2024 14:36:10