



FCC ID: 2AJ4RJOMOK3

According to KDB 447498 D01 General RF Exposure Guidance v06, section 4.3.1

At 100 MHz to 6 GHz and for test separation distances  $\leq 50\text{mm}$ , the SAR test exclusion threshold is determined according to the following

$$[(\text{max. power of channel, mW}) / (\text{min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] \leq 3.0$$

### 1. SAR test exclusion threshold

**Frequency: 2 480 MHz (min. separation distances = 5 mm)**

$$\text{SAR test exclusion thresholds (5 mm)} = 3 \times 5 / (\sqrt{2.480}) = 9.525 \text{ mW}$$

Test mode	Max. Tune-up Tolerance (mW)	SAR Test Exclusion Thresholds (5mm) (mW)
Classic BT	1.58	9.525
BLE	0.79	9.525

$$\text{Calculation value: } 2 \text{ (mW)} / 5 \text{ (mm)} \times \sqrt{2.480} = 0.63$$

$$1 \text{ (mW)} / 5 \text{ (mm)} \times \sqrt{2.480} = 0.32$$

So, Calculation value  $\leq 3.0$

Remark:

-For Classic BT Max. conducted power 1.58 (mW) is closet 2 (mW), so 2 (mW) was calculated.

-For BLE Max. conducted power 0.79 (mW) is closet 1 (mW), so 1 (mW) was calculated.

-When the minimum test separation distance is  $< 5 \text{ mm}$ , a distance of 5 mm is applied to determine SAR test exclusion.

**2. Conclusion: No SAR is required.**