

RF Exposure Evaluation Report

Product : Smart projector
Trade mark : TOUMEI
: C900, C800, C800i, C800S, C800Pro, C900Pro, C1000, C1000Pro, C2000, C2000Pro, K1, K2, K3, K4, K5, K6, K7, K8, K9, K1Pro, K2Pro, K3Pro, K5Pro, K6Pro, K7Pro, K8Pro, K9Pro, S900, S1000,
Model/Type reference : V3, V5, V6, V7, V8, V9, V3Pro, V5Pro, V6Pro, V7Pro, V8Pro, V9Pro, Q1, Q2, Q3, Q5, Q6, Q8, C1, C2, C3, C4, C5, C6, C7, C8, C9, T5, T6, T7, T8, T9, X1, X2, X3, X4, X5, X6, X7, X8, X9, S1, S2, S3, S4, S5, S6, S7, S8, S9, A3, A4, A5, A6, A7, A8, A9
Serial Number : N/A
Report Number : EED32N80001605
FCC ID : 2AJCM-TMSERIES
Date of Issue : Mar. 09, 2021
47 CFR Part 1.1307
Test Standards : 47 CFR Part 1.1310
KDB447498D01v06
Test result : PASS

Prepared for:

SHENZHEN TOUMEI TECHNOLOGY CO., LTD
Building 601, JinChongda Building, Building 00082,
Shangwei Industrial Zone, Yukeng Trail Community,
Guanhu Street, Longhua District, Shenzhen, China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385



Compiled by:

Ken. cai

Ken Cai

Approved by:

David Wang

Report Seal

David Wang

Reviewed by:

Aaron Ma

Aaron Ma

Date:

Mar. 09, 2021

Check No.:4710040121

1 Version

| Version No. | Date | Description |
|-------------|---------------|-------------|
| 00 | Mar. 09, 2021 | Original |
| | | |
| | | |

2 Contents

| | |
|--|---|
| 1 VERSION | 2 |
| 2 CONTENTS | 3 |
| 3 GENERAL INFORMATION | 4 |
| 3.1 CLIENT INFORMATION..... | 4 |
| 3.2 GENERAL DESCRIPTION OF EUT..... | 4 |
| 3.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD..... | 4 |
| 3.4 TEST LOCATION..... | 5 |
| 3.5 DEVIATION FROM STANDARDS..... | 5 |
| 3.6 ABNORMALITIES FROM STANDARD CONDITIONS..... | 5 |
| 3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER..... | 5 |
| 4 RF EXPOSURE EVALUATION | 6 |
| 4.1 RF EXPOSURE COMPLIANCE REQUIREMENT..... | 6 |
| 4.1.1 Limits..... | 6 |
| 4.1.2 Test Procedure..... | 7 |
| 4.1.3 EUT RF Exposure Evaluation..... | 7 |
| PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS | 8 |

3 General Information

3.1 Client Information

| | |
|--------------------------|---|
| Applicant: | SHENZHEN TOUMEI TECHNOLOGY CO., LTD |
| Address of Applicant: | Building 601, JinChongda Building, Building 00082, Shangwei Industrial Zone, Yukeng Trail Community, Guanhu Street, Longhua District, Shenzhen, China |
| Manufacturer: | SHENZHEN TOUMEI TECHNOLOGY CO., LTD |
| Address of Manufacturer: | Building 601, JinChongda Building, Building 00082, Shangwei Industrial Zone, Yukeng Trail Community, Guanhu Street, Longhua District, Shenzhen, China |
| Factory: | SHENZHEN TOUMEI TECHNOLOGY CO., LTD |
| Address of Factory: | Building 601, JinChongda Building, Building 00082, Shangwei Industrial Zone, Yukeng Trail Community, Guanhu Street, Longhua District, Shenzhen, China |

3.2 General Description of EUT

| | |
|---------------------------------|--|
| Product Name: | Smart projector |
| Test Model No.: | C900 |
| Trade Mark: | TOUMEI |
| EUT Supports Radios application | BT 4.2 Dual mode, 2402-2480MHz 2.4G WiFi, 802.11b/g/n(20MHz)/n(40MHz), 2412-2462MHz 5G WiFi, 802.11a/n(HT20)/n(HT40)/ac(HT20)/ac(HT40)/ac(HT80) 5G WiFi, 5150-5250MHz; 5725-5850MHz |

3.3 Product Specification subjective to this standard

| | |
|--|--|
| Frequency Range: | BT 4.2 Dual mode, 2402-2480MHz 2.4G WiFi, 802.11b/g/n(20MHz)/n(40MHz), 2412-2462MHz 5G WiFi, 802.11a/n(HT20)/n(HT40)/ac(HT20)/ac(HT40)/ac(HT80) 5G WiFi, 5150-5250MHz; 5725-5850MHz |
| Antenna Type: | integral antenna |
| Antenna gain: | BT ANT: 3.5dBi; WIFI ANT1: 3.5dBi; WIFI ANT2: 3.5dBi |
| Product Type: | <input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location |
| Power Supply: | DC 12V |
| Conducted Peak Output Power: | 14.58dBm |
| | The Conducted Peak Output Power data refer to the report EED32N80001601, EED32N80001602, EED32N80001603, EED32N80001604 |
| Sample Received Date: | Jan. 07, 2021 |
| Sample tested Date: | Jan. 07, 2021 to Feb. 26, 2021 |
| Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified. | |

Report No. : EED32N80001605

Page 5 of 8

3.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.

3.7 Other Information Requested by the Customer

None.

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures | | | | |
| 0.3–3.0 | 614 | 1.63 | *(100) | 6 |
| 3.0–30 | 1842/f | 4.89/f | *(900/f ²) | 6 |
| 30–300 | 61.4 | 0.163 | 1.0 | 6 |
| 300–1500 | | | f/300 | 6 |
| 1500–100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | | | f/1500 | 30 |
| 1500–100,000 | | | 1.0 | 30 |

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the centre of radiation of the antenna

EIRP = P*G

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user.

Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limits, then we can conclude the device complies with the rules.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure Evaluation

Antenna Gain: 3.5 dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

| Channel | Frequency (MHz) | Max Conducted Peak Output Power(dBm) | Gain (dBi) | EIRP* (dBm) | EIRP (mW) | R (cm) | S (mW/cm ²) | Limit (mW/cm ²) | Result |
|---------|-----------------|--------------------------------------|------------|-------------|-----------|--------|-------------------------|-----------------------------|--------|
| Highest | 2462 | 14.58 | 3.50 | 18.08 | 64.27 | 20 | 0.0128 | 1.0 | Pass |

Note: Refer to report No. EED32N80001601, EED32N80001602, EED32N80001603, EED32N80001604 for EUT test Max Conducted Peak Output Power value.

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32N80001601 for EUT external and internal photos.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***