

Test Report

Prepared for: Qdes Works BV

Model: Receiver Station

Description: Wireless Audio Receiver

Serial Number: N/A

FCC ID: 2AJK5-RE001

To

FCC Part 1.1310

Date of Issue: June 26, 2024

On the behalf of the applicant:

Qdes Works BV
Kroopstraat 12
1032 LA Amsterdam,
The Netherlands

Attention of:

Jochem Welvaadt, CEO
Ph: 31621556176
E-mail: jwelvaadt@systecdesigns.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p2430010

Reviewed / Authorized By:



John Michalowicz
Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested

Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	6/26/24	John Michalowicz	Original Document

ANAB

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communiqué dated January 2009).

The tests results contained within this test report all fall within our scope of accreditation, unless noted below.

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: Receiver Station

Description: Wireless Guitar Receiver

Firmware: Main PCB: v0.04, Display PCB: v0.08

Software: NA

Serial Number: NA

Additional Information: The EUT is a wireless guitar receiver that is powered by an AC/DC adaptor. The products is available in two versions, Jack Receiver Station and mXLR Receiver Station, which differ only in the type of charge port.

Minimum Safe Distance Evaluation

This is a mobile device used in Uncontrolled Exposure environment.

Limits Controlled Exposure 47 CFR 1.1310 Table 1, (A)

0.3-3.0 MHz:	Limit [mW/cm ²] = 100
3.0-30 MHz:	Limit [mW/cm ²] = (900/f ²)
30-300 MHz:	Limit [mW/cm ²] = 1.0
300-1500 MHz:	Limit [mW/cm ²] = f/300
1500-100,000 MHz	Limit [mW/cm ²] = 5

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	5732
Power, Conducted, mW (P)	27.23
Antenna Gain Isotropic	2.7 dBi
Antenna Gain Numeric (G)	1.86
Antenna Type	Omni
Limit (L)	1.0

$S = P \cdot G / 4 \cdot \pi \cdot r^2$			
Power Density (S) mw/cm2	Power mW (P)	Numeric Gain (G)	Limit (L)
0.0100763568	27.23	1.86	20

Note: Max output power value is obtained from associated report.

The power density is below the 1.0 limit