



FCC RF Test Report

APPLICANT : RealWear, Inc.
EQUIPMENT : Head Mounted Tablet
BRAND NAME : i.safe MOBILE, realwear
MODEL NAME : T21S
FCC ID : 2AJOR2101SAA
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Jun. 05, 2023 ~ Sep. 26, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	7
1.7 Test Software.....	7
1.8 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 6dB and 99% Bandwidth Measurement	12
3.2 Output Power Measurement.....	13
3.3 Power Spectral Density Measurement	18
3.4 Conducted Band Edges and Spurious Emission Measurement	20
3.5 Radiated Band Edges and Spurious Emission Measurement	21
3.6 AC Conducted Emission Measurement.....	25
3.7 Antenna Requirements.....	27
4 LIST OF MEASURING EQUIPMENT	28
5 MEASUREMENT UNCERTAINTY	29
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR382801C	Rev. 01	Initial issue of report	Oct. 19, 2023



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report Only	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.92 dB at 2388.65 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 14.87 dB at 4.647 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

RealWear, Inc.

600 Hatheway Road, Vancouver, WA, 98661

1.2 Manufacturer

i.safe MOBILE GmbH

i_Park Tauberfranken 10, 97922, Lauda-Koenigshofen, Germany

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Head Mounted Tablet
Brand Name	i.safe MOBILE, realwear
Model Name	T21S
FCC ID	2AJOR2101SAA
SN	Conducted: D2B6P806N2761239 Conduction: D2B6P806N2761109 Radiation: D2B6P806N2761020
HW Version	A
SW Version	1.0.4-14-T.NAVIGATOR-Z1.S
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	<MIMO Ant.1+2> 802.11b : 20.16 dBm (0.1038 W) 802.11g : 24.10 dBm (0.2570 W) 802.11n HT20 : 24.66 dBm (0.2924 W) 802.11n HT40 : 23.20 dBm (0.2089 W) 802.11ac VHT20 : 24.61 dBm (0.2891 W) 802.11ac VHT40 : 23.15 dBm (0.2065 W) 802.11ax HE20 : 24.71 dBm (0.2958 W) 802.11ax HE40 : 23.23 dBm (0.2104 W)
99% Occupied Bandwidth	<MIMO Ant.1+2> 802.11b : 13.147 MHz 802.11g : 16.783 MHz 802.11n HT20 : 17.782 MHz 802.11n HT40 : 36.284 MHz 802.11ax HE20 : 19.021 MHz 802.11ax HE40 : 38.042 MHz
Antenna Type / Gain	Ant.1: PIFA Antenna with gain 2.86 dBi Ant.2: PIFA Antenna with gain 2.54 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n/ac/ax : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM)

Note:

1. For WLAN SISO & CDD MIMO mode, the whole testing has assessed only MIMO mode by referring to the higher normal conducted power.
2. For 802.11n HT20 / ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing has assessed only 802.11n HT20/ HT40 by referring to their higher conducted power.
3. 802.11ax support OFDMA full RU tone and partial RU tone, both full RU and partial RU-left (for low CH) and partial RU-right (for high CH) test output power/PSD/RSE, the full RU Power > partial RU, therefore the full RU perform full test and Partial RU verified power/PSD/RSE.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH06-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH06-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-



2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

MIMO Antenna


Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : WLAN Link (2.4G) + Bluetooth Link + Adaptor + USB Cable + Earphone
Remark: For Radiated Test Cases, The tests were performance with Adapter, Earphone and USB Cable	


RSE Co-location
BLE CH39 2Mbps TX + 802.11g CH01 2412

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
2.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m Unshielded AC I/P cable 1.8m
3.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
4.	Adapter	realwear	CK18W02U	N/A	N/A	N/A
5.	Earphone	apple	NA	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.25 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 2.25 + 10 = 12.25 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1%~5% of OBW and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant1	Ant2	SUM	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	
11b	1Mbps	2	1	2412	17.43	16.84	20.16	30.00		2.86		23.02		36.00		Pass
11b	1Mbps	2	6	2437	17.37	16.85	20.13	30.00		2.86		22.99		36.00		Pass
11b	1Mbps	2	11	2462	16.99	16.83	19.92	30.00		2.86		22.78		36.00		Pass
11g	6Mbps	2	1	2412	21.78	20.26	24.10	30.00		2.86		26.96		36.00		Pass
11g	6Mbps	2	6	2437	21.23	20.47	23.88	30.00		2.86		26.74		36.00		Pass
11g	6Mbps	2	11	2462	20.74	20.82	23.79	30.00		2.86		26.65		36.00		Pass
HT20	MCS0	2	1	2412	22.31	20.62	24.56	30.00		2.86		27.42		36.00		Pass
HT20	MCS0	2	6	2437	22.16	21.07	24.66	30.00		2.86		27.52		36.00		Pass
HT20	MCS0	2	11	2462	21.23	21.24	24.25	30.00		2.86		27.11		36.00		Pass
HT40	MCS0	2	3	2422	20.71	19.24	23.05	30.00		2.86		25.91		36.00		Pass
HT40	MCS0	2	6	2437	20.37	19.93	23.17	30.00		2.86		26.03		36.00		Pass
HT40	MCS0	2	9	2452	20.44	19.92	23.20	30.00		2.86		26.06		36.00		Pass
VHT20	MCS0	2	1	2412	22.26	20.56	24.50	30.00		2.86		27.36		36.00		Pass
VHT20	MCS0	2	6	2437	22.12	21.01	24.61	30.00		2.86		27.47		36.00		Pass
VHT20	MCS0	2	11	2462	21.21	21.20	24.22	30.00		2.86		27.08		36.00		Pass
VHT40	MCS0	2	3	2422	20.64	19.19	22.99	30.00		2.86		25.85		36.00		Pass
VHT40	MCS0	2	6	2437	20.32	19.87	23.11	30.00		2.86		25.97		36.00		Pass
VHT40	MCS0	2	9	2452	20.40	19.86	23.15	30.00		2.86		26.01		36.00		Pass



Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant1	Ant2	SUM	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	
HE20	MCS0	2	1	2412	Full	22.34	20.66	24.59	30.00		2.86		27.45		36.00		Pass
HE20	MCS0	2	1	2412	26/0	13.25	14.11	16.71	30.00		2.86		19.57		36.00		Pass
HE20	MCS0	2	1	2412	52/37	15.75	15.38	18.58	30.00		2.86		21.44		36.00		Pass
HE20	MCS0	2	1	2412	106/53	17.92	16.92	20.46	30.00		2.86		23.32		36.00		Pass
HE20	MCS0	2	6	2437	Full	22.21	21.12	24.71	30.00		2.86		27.57		36.00		Pass
HE20	MCS0	2	6	2437	26/0	12.88	14.14	16.57	30.00		2.86		19.43		36.00		Pass
HE20	MCS0	2	6	2437	52/37	15.38	15.12	18.26	30.00		2.86		21.12		36.00		Pass
HE20	MCS0	2	6	2437	106/53	17.08	17.25	20.18	30.00		2.86		23.04		36.00		Pass
HE20	MCS0	2	11	2462	Full	21.27	21.31	24.30	30.00		2.86		27.16		36.00		Pass
HE20	MCS0	2	11	2462	26/8	13.14	14.61	16.95	30.00		2.86		19.81		36.00		Pass
HE20	MCS0	2	11	2462	52/40	15.37	15.90	18.65	30.00		2.86		21.51		36.00		Pass
HE20	MCS0	2	11	2462	106/54	18.14	18.35	21.26	30.00		2.86		24.12		36.00		Pass
HE40	MCS0	2	3	2422	Full	20.75	19.26	23.08	30.00		2.86		25.94		36.00		Pass
HE40	MCS0	2	6	2437	Full	20.42	19.98	23.22	30.00		2.86		26.08		36.00		Pass
HE40	MCS0	2	11	2462	Full	20.48	19.95	23.23	30.00		2.86		26.09		36.00		Pass



3.2.6 Test Result of Average Output Power (Reporting Only)

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power with duty factor (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail	Setting	
					Ant 1	Ant 2	Ant1	Ant2	SUM	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2		Ant1	Ant2
11b	1Mbps	2	1	2412	0.09	0.08	15.05	14.52	17.80	30.00		2.86		20.66		36.00		Pass	15.00	
11b	1Mbps	2	6	2437	0.09	0.08	15.00	14.50	17.77	30.00		2.86		20.63		36.00		Pass	15.00	
11b	1Mbps	2	11	2462	0.09	0.08	14.66	14.51	17.60	30.00		2.86		20.46		36.00		Pass	15.00	
11g	6Mbps	2	1	2412	0.02	0.02	13.26	12.63	15.97	30.00		2.86		18.83		36.00		Pass	13.00	
11g	6Mbps	2	6	2437	0.02	0.02	12.95	12.68	15.83	30.00		2.86		18.69		36.00		Pass	13.00	
11g	6Mbps	2	11	2462	0.02	0.02	12.61	12.81	15.72	30.00		2.86		18.58		36.00		Pass	13.00	
HT20	MCS0	2	1	2412	0.00	0.00	12.96	12.61	15.80	30.00		2.86		18.66		36.00		Pass	13.00	
HT20	MCS0	2	6	2437	0.00	0.00	12.91	12.76	15.85	30.00		2.86		18.71		36.00		Pass	13.00	
HT20	MCS0	2	11	2462	0.00	0.00	12.45	12.68	15.58	30.00		2.86		18.44		36.00		Pass	13.00	
HT40	MCS0	2	3	2422	0.00	0.00	11.83	11.61	14.73	30.00		2.86		17.59		36.00		Pass	12.00	
HT40	MCS0	2	6	2437	0.00	0.00	11.84	11.64	14.75	30.00		2.86		17.61		36.00		Pass	12.00	
HT40	MCS0	2	9	2452	0.00	0.00	11.51	11.63	14.58	30.00		2.86		17.44		36.00		Pass	12.00	
VHT20	MCS0	2	1	2412	0.00	0.00	12.89	12.56	15.74	30.00		2.86		18.60		36.00		Pass	13.00	
VHT20	MCS0	2	6	2437	0.00	0.00	12.83	12.71	15.78	30.00		2.86		18.64		36.00		Pass	13.00	
VHT20	MCS0	2	11	2462	0.00	0.00	12.38	12.64	15.52	30.00		2.86		18.38		36.00		Pass	13.00	
VHT40	MCS0	2	3	2422	0.00	0.00	11.76	11.55	14.67	30.00		2.86		17.53		36.00		Pass	12.00	
VHT40	MCS0	2	6	2437	0.00	0.00	11.79	11.59	14.70	30.00		2.86		17.56		36.00		Pass	12.00	
VHT40	MCS0	2	9	2452	0.00	0.00	11.47	11.60	14.55	30.00		2.86		17.41		36.00		Pass	12.00	



Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Conducted Power with duty factor (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail	Setting	
						Ant1	Ant2	Ant1	Ant2	SUM	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2		Ant1	Ant2
HE20	MCS0	2	1	2412	Full	0.00	0.00	13.04	12.64	15.85	30.00		2.86		18.71		36.00		Pass	13.00	
HE20	MCS0	2	1	2412	26/0	0.00	0.00	2.49	4.51	6.63	30.00		2.86		9.49		36.00		Pass	2.50	
HE20	MCS0	2	1	2412	52/37	0.00	0.00	5.05	4.35	7.72	30.00		2.86		10.58		36.00		Pass	4.50	
HE20	MCS0	2	1	2412	106/53	0.00	0.00	7.65	6.46	10.11	30.00		2.86		12.97		36.00		Pass	7.00	
HE20	MCS0	2	6	2437	Full	0.00	0.00	12.92	12.83	15.89	30.00		2.86		18.75		36.00		Pass	13.00	
HE20	MCS0	2	6	2437	26/0	0.00	0.00	2.16	4.48	6.48	30.00		2.86		9.34		36.00		Pass	2.50	
HE20	MCS0	2	6	2437	52/37	0.00	0.00	4.87	4.38	7.64	30.00		2.86		10.50		36.00		Pass	4.50	
HE20	MCS0	2	6	2437	106/53	0.00	0.00	6.77	6.53	9.66	30.00		2.86		12.52		36.00		Pass	7.00	
HE20	MCS0	2	11	2462	Full	0.00	0.00	12.49	12.71	15.61	30.00		2.86		18.47		36.00		Pass	13.00	
HE20	MCS0	2	11	2462	26/8	0.00	0.00	2.50	5.33	7.15	30.00		2.86		10.01		36.00		Pass	3.00	
HE20	MCS0	2	11	2462	52/40	0.00	0.00	4.68	5.32	8.02	30.00		2.86		10.88		36.00		Pass	5.00	
HE20	MCS0	2	11	2462	106/54	0.00	0.00	7.41	7.82	10.63	30.00		2.86		13.49		36.00		Pass	8.00	
HE40	MCS0	2	3	2422	Full	0.00	0.00	11.87	11.62	14.76	30.00		2.86		17.62		36.00		Pass	12.00	
HE40	MCS0	2	6	2437	Full	0.00	0.00	11.88	11.67	14.79	30.00		2.86		17.65		36.00		Pass	12.00	
HE40	MCS0	2	9	2452	Full	0.00	0.00	11.57	11.66	14.63	30.00		2.86		17.49		36.00		Pass	12.00	

Remark: The duty cycle factor has been added to average power results.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (b): Measure and sum spectral maxima across the outputs.

The measurement on each individual output were performed with the same span and number on each individual output. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<CDD Modes>						
			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant. 1	Ant. 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
2.4 GHz	2.86	2.54	2.86	5.71	0.00	0.00



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Max 30dBm	Oct. 13, 2022	Sep. 19, 2023~Sep. 23, 2023	Oct. 12, 2023	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY60242126	10Hz~44GHz	Oct. 13, 2022	Sep. 19, 2023~Sep. 23, 2023	Oct. 12, 2023	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 16, 2022	Sep. 19, 2023~Sep. 23, 2023	Oct. 15, 2023	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz~1GHz	Apr. 09, 2023	Sep. 19, 2023~Sep. 23, 2023	Apr. 08, 2024	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 06, 2023	Sep. 19, 2023~Sep. 23, 2023	Apr. 05, 2024	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 08, 2023	Sep. 19, 2023~Sep. 23, 2023	Jan. 07, 2024	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	380827	9KHz ~1GHZ	Jul. 06, 2023	Sep. 19, 2023~Sep. 23, 2023	Jul. 05, 2024	Radiation (03CH06-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 05, 2023	Sep. 19, 2023~Sep. 23, 2023	Jan. 04, 2024	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-00101800-30-10P	2082395	1Ghz~18Ghz	Jan. 05, 2023	Sep. 19, 2023~Sep. 23, 2023	Jan. 04, 2024	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270319	500MHz~26.5GHz	Oct. 12, 2022	Sep. 19, 2023~Sep. 23, 2023	Oct. 12, 2023	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Sep. 19, 2023~Sep. 23, 2023	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Sep. 19, 2023~Sep. 23, 2023	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Sep. 19, 2023~Sep. 23, 2023	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 16, 2023	Sep. 12, 2023	May 15, 2024	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2022	Sep. 12, 2023	Oct. 12, 2023	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 16, 2023	Sep. 12, 2023	May 15, 2024	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2022	Sep. 12, 2023	Oct. 11, 2023	Conduction (CO01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 12, 2022	Jun. 05, 2023~Sep. 26, 2023	Oct. 11, 2023	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 05, 2023	Jun. 05, 2023~Sep. 26, 2023	Jan. 04, 2024	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1435004	50MHz Bandwidth	Jan. 05, 2023	Jun. 05, 2023~Sep. 26, 2023	Jan. 04, 2024	Conducted (TH01-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±0.46 dB
Conducted Emissions	±2.26 dB
Occupied Channel Bandwidth	±0.001 %
Conducted Power Spectral Density	±0.88 dB

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.94 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.26 dB
---	---------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.02 dB
---	---------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.26 dB
---	---------

----- THE END -----



Appendix A. Conducted Test Results



Ambient Condition: 25 °C, 45 %RH

Test Date: 2023.6.5~2023.9.26

Test Engineer: Long Wu


DTS Bandwidth


Test Result


TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B-CDD	Ant1	2412	7.56	2408.00	2415.56	0.5	PASS
	Ant2	2412	7.56	2408.00	2415.56	0.5	PASS
	Ant1	2437	7.12	2433.44	2440.56	0.5	PASS
	Ant2	2437	7.56	2433.44	2441.00	0.5	PASS
	Ant1	2462	7.60	2457.96	2465.56	0.5	PASS
	Ant2	2462	8.00	2458.00	2466.00	0.5	PASS
11G-CDD	Ant1	2412	16.32	2403.84	2420.16	0.5	PASS
	Ant2	2412	16.32	2403.84	2420.16	0.5	PASS
	Ant1	2437	16.32	2428.84	2445.16	0.5	PASS
	Ant2	2437	16.32	2428.84	2445.16	0.5	PASS
	Ant1	2462	16.32	2453.84	2470.16	0.5	PASS
	Ant2	2462	16.32	2453.84	2470.16	0.5	PASS
11N20MIMO	Ant1	2412	17.16	2403.24	2420.40	0.5	PASS
	Ant2	2412	16.92	2403.48	2420.40	0.5	PASS
	Ant1	2437	17.16	2428.24	2445.40	0.5	PASS
	Ant2	2437	17.16	2428.24	2445.40	0.5	PASS
	Ant1	2462	17.56	2453.20	2470.76	0.5	PASS
	Ant2	2462	16.84	2453.56	2470.40	0.5	PASS
11N40MIMO	Ant1	2422	35.76	2403.84	2439.60	0.5	PASS
	Ant2	2422	35.76	2403.84	2439.60	0.5	PASS
	Ant1	2437	35.44	2419.16	2454.60	0.5	PASS
	Ant2	2437	35.44	2419.16	2454.60	0.5	PASS
	Ant1	2452	35.52	2434.08	2469.60	0.5	PASS
	Ant2	2452	35.52	2434.08	2469.60	0.5	PASS
11AX20MIMO	Ant1	2412	18.60	2402.68	2421.28	0.5	PASS
	Ant2	2412	17.68	2402.60	2420.28	0.5	PASS
	Ant1	2437	18.76	2427.64	2446.40	0.5	PASS
	Ant2	2437	18.80	2427.60	2446.40	0.5	PASS
	Ant1	2462	18.60	2452.80	2471.40	0.5	PASS
	Ant2	2462	18.60	2452.68	2471.28	0.5	PASS
11AX40MIMO	Ant1	2422	37.92	2402.96	2440.88	0.5	PASS
	Ant2	2422	37.68	2403.04	2440.72	0.5	PASS
	Ant1	2437	37.28	2418.20	2455.48	0.5	PASS
	Ant2	2437	37.60	2418.12	2455.72	0.5	PASS
	Ant1	2452	37.68	2433.12	2470.80	0.5	PASS
	Ant2	2452	37.68	2433.04	2470.72	0.5	PASS





Test Graphs





















































Occupied Channel Bandwidth


Test Result


TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]
11B-CDD	Ant1	2412	13.107	2405.4865	2418.5934
	Ant2	2412	13.107	2405.4066	2418.5135
	Ant1	2437	13.107	2430.4865	2443.5934
	Ant2	2437	13.067	2430.4865	2443.5534
	Ant1	2462	13.147	2455.4466	2468.5934
	Ant2	2462	13.147	2455.4066	2468.5534
11G-CDD	Ant1	2412	16.623	2403.7283	2420.3516
	Ant2	2412	16.743	2403.5684	2420.3117
	Ant1	2437	16.623	2428.7283	2445.3516
	Ant2	2437	16.783	2428.5684	2445.3516
	Ant1	2462	16.623	2453.7283	2470.3516
	Ant2	2462	16.743	2453.5684	2470.3117
11N20MIMO	Ant1	2412	17.782	2403.1289	2420.9111
	Ant2	2412	17.782	2403.0889	2420.8711
	Ant1	2437	17.742	2428.1688	2445.9111
	Ant2	2437	17.782	2428.1289	2445.9111
	Ant1	2462	17.742	2453.1688	2470.9111
	Ant2	2462	17.782	2453.1289	2470.9111
11N40MIMO	Ant1	2422	36.284	2403.9381	2440.2218
	Ant2	2422	36.284	2403.8581	2440.1419
	Ant1	2437	36.124	2419.0180	2455.1419
	Ant2	2437	36.284	2418.8581	2455.1419
	Ant1	2452	36.204	2433.9381	2470.1419
	Ant2	2452	36.204	2433.8581	2470.0619
11AX20MIMO	Ant1	2412	19.021	2402.5295	2421.5504
	Ant2	2412	18.941	2402.5295	2421.4705
	Ant1	2437	18.941	2427.5694	2446.5105
	Ant2	2437	18.941	2427.5295	2446.4705
	Ant1	2462	18.981	2452.5295	2471.5105
	Ant2	2462	18.981	2452.5295	2471.5105
11AX40MIMO	Ant1	2422	38.042	2403.0589	2441.1009
	Ant2	2422	37.882	2403.0589	2440.9411
	Ant1	2437	37.882	2418.1389	2456.0210
	Ant2	2437	37.962	2417.9790	2455.9411
	Ant1	2452	37.962	2432.9790	2470.9411
	Ant2	2452	37.802	2433.1389	2470.9411





Test Graphs




















































Maximum power spectral density

Test Result

TestMode	Antenna	Freq(MHz)	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
11B-CDD	Ant1	2412	-9.85	≤8.00	PASS
	Ant2	2412	-9.45	≤8.00	PASS
	total	2412	-6.64	≤8.00	PASS
	Ant1	2437	-8.89	≤8.00	PASS
	Ant2	2437	-9.02	≤8.00	PASS
	total	2437	-5.94	≤8.00	PASS
	Ant1	2462	-8.32	≤8.00	PASS
	Ant2	2462	-8.7	≤8.00	PASS
	total	2462	-5.50	≤8.00	PASS
11G-CDD	Ant1	2412	-12	≤8.00	PASS
	Ant2	2412	-13.26	≤8.00	PASS
	total	2412	-9.57	≤8.00	PASS
	Ant1	2437	-12.87	≤8.00	PASS
	Ant2	2437	-13.34	≤8.00	PASS
	total	2437	-10.09	≤8.00	PASS
	Ant1	2462	-13.49	≤8.00	PASS
	Ant2	2462	-13.54	≤8.00	PASS
	total	2462	-10.50	≤8.00	PASS
11N20MIMO	Ant1	2412	-13.64	≤8.00	PASS
	Ant2	2412	-13.98	≤8.00	PASS
	total	2412	-10.80	≤8.00	PASS
	Ant1	2437	-13.45	≤8.00	PASS
	Ant2	2437	-13.66	≤8.00	PASS
	total	2437	-10.54	≤8.00	PASS
	Ant1	2462	-13.34	≤8.00	PASS
	Ant2	2462	-13.85	≤8.00	PASS
	total	2462	-10.58	≤8.00	PASS
11N40MIMO	Ant1	2422	-17.2	≤8.00	PASS
	Ant2	2422	-17.53	≤8.00	PASS
	total	2422	-14.35	≤8.00	PASS
	Ant1	2437	-17.44	≤8.00	PASS
	Ant2	2437	-17.49	≤8.00	PASS
	total	2437	-14.45	≤8.00	PASS



	Ant1	2452	-17.09	≤ 8.00	PASS
	Ant2	2452	-16.87	≤ 8.00	PASS
	total	2452	-13.97	≤ 8.00	PASS
11AX20MIMO	Ant1	2412	-14.05	≤ 8.00	PASS
	Ant2	2412	-13.72	≤ 8.00	PASS
	total	2412	-10.87	≤ 8.00	PASS
	Ant1	2437	-14.41	≤ 8.00	PASS
	Ant2	2437	-14.31	≤ 8.00	PASS
	total	2437	-11.35	≤ 8.00	PASS
	Ant1	2462	-13.23	≤ 8.00	PASS
	Ant2	2462	-14.26	≤ 8.00	PASS
	total	2462	-10.70	≤ 8.00	PASS
11AX40MIMO	Ant1	2422	-16.86	≤ 8.00	PASS
	Ant2	2422	-18.03	≤ 8.00	PASS
	total	2422	-14.40	≤ 8.00	PASS
	Ant1	2437	-17.56	≤ 8.00	PASS
	Ant2	2437	-16.16	≤ 8.00	PASS
	total	2437	-13.79	≤ 8.00	PASS
	Ant1	2452	-17.69	≤ 8.00	PASS
	Ant2	2452	-16.85	≤ 8.00	PASS
	total	2452	-14.24	≤ 8.00	PASS



Test Graphs

