TESTING
NVLAP LAB CODE 600118-0

SAR TEST REPORT

No. I19Z62186-SEM01

For

HMD Global Oy

Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN

Model name: TA-1216

With

Hardware Version: 89572_1_12

Software Version: 000T_0_110

FCC ID: 2AJOTTA-1216

Issued Date: 2020-1-16

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 51, Xueyuan Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: cttl_terminals@caict.ac.cn, website: www.caict.ac.cn

©Copyright. All rights reserved by CTTL.

REPORT HISTORY

Report Number	Revision	Issue Date	Description
I19Z62186-SEM01	Rev.0	2020-1-7	Initial creation of test report
I19Z62186-SEM01	Rev.1	2020-1-16	Update the information on section 14.1 of test report.

©Copyright. All rights reserved by CTTL.

TABLE OF CONTENT

1 TEST LABORATORY 5

1.1 TESTING LOCATION 5
1.2 TESTING ENVIRONMENT 5
1.3 PROJECT DATA 5
1.4 SIGNATURE 5

2 STATEMENT OF COMPLIANCE 6

3 CLIENT INFORMATION 7

3.1 APPLICANT INFORMATION 7
3.2 MANUFACTURER INFORMATION 7

4 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) 8

4.1 ABOUT EUT 8
4.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST 8
4.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST 8

5 TEST METHODOLOGY 9

5.1 APPLICABLE LIMIT REGULATIONS 9
5.2 APPLICABLE MEASUREMENT STANDARDS 9

6 SPECIFIC ABSORPTION RATE (SAR) 10

6.1 INTRODUCTION 10
6.2 SAR DEFINITION 10

7 TISSUE SIMULATING LIQUIDS 11

7.1 TARGETS FOR TISSUE SIMULATING LIQUID 11
7.2 DIELECTRIC PERFORMANCE 11

8 SYSTEM VERIFICATION 14

8.1 SYSTEM SETUP 14
8.2 SYSTEM VERIFICATION 15

9 MEASUREMENT PROCEDURES 16

9.1 TESTS TO BE PERFORMED 16
9.2 GENERAL MEASUREMENT PROCEDURE 18
9.3 WCDMA MEASUREMENT PROCEDURES FOR SAR 19
9.4 SAR MEASUREMENT FOR LTE 20
9.5 BLUETOOTH & WI-FI MEASUREMENT PROCEDURES FOR SAR 20
9.6 POWER DRIFT 21

10 AREA SCAN BASED 1-G SAR 22

10.1 REQUIREMENT OF KDB 22
10.2 FAST SAR ALGORITHMS 22

©Copyright. All rights reserved by CTTL.

11 CONDUCTED OUTPUT POWER 23

11.1 GSM MEASUREMENT RESULT 23
11.2 WCDMA MEASUREMENT RESULT 25
11.3 LTE MEASUREMENT RESULT 26
11.4 WI-FI AND BT MEASUREMENT RESULT 32

12 SIMULTANEOUS TX SAR CONSIDERATIONS 33

12.1 INTRODUCTION 33
12.2 TRANSMIT ANTENNA SEPARATION DISTANCES 33
12.3 SAR MEASUREMENT POSITIONS 34
12.4 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS 34

13 EVALUATION OF SIMULTANEOUS 34

14 SAR TEST RESULT 36

14.1 SAR RESULTS FOR FAST SAR 37
14.2 SAR RESULTS FOR STANDARD PROCEDURE 41
14.3 WLAN EVALUATION FOR 2.4G 44

15 MEASUREMENT UNCERTAINTY 47

15.1 MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (300MHZ~3GHZ) 47
15.2 MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (3~6GHZ) 48
15.3 MEASUREMENT UNCERTAINTY FOR FAST SAR TESTS (300MHZ~3GHZ) 49
15.4 MEASUREMENT UNCERTAINTY FOR FAST SAR TESTS (3~6GHZ) 50

16 MAIN TEST INSTRUMENTS 51

ANNEX A GRAPH RESULTS 52

ANNEX B SYSTEM VERIFICATION RESULTS 68

ANNEX C SAR MEASUREMENT SETUP 73

ANNEX D POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM 79

ANNEX E EQUIVALENT MEDIA RECIPES 82

ANNEX F SYSTEM VALIDATION 83

ANNEX G PROBE CALIBRATION CERTIFICATE 84

ANNEX H DIPOLE CALIBRATION CERTIFICATE 103

ANNEX I SENSOR TRIGGERING DATA SUMMARY 135

ANNEX J ACCREDITATION CERTIFICATE 138

©Copyright. All rights reserved by CTTL.

1 Test Laboratory

1.1 Testing Location

Company Name:	CTTL(Shouxiang)
Address:	No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191

1.2 Testing Environment

Temperature:	18°C~25°C,
Relative humidity:	30%~ 70%
Ground system resistance:	< 0.5 Ω
Ambient noise & Reflection:	< 0.012 W/kg

1.3 Project Data

Project Leader:	Qi Dianyuan
Test Engineer:	Lin Xiaojun
Testing Start Date:	December 11, 2019
Testing End Date:	December 14, 2019

1.4 Signature

Lin Xiaojun

(Prepared this test report)



Qi Dianyuan

(Reviewed this test report)



Lu Bingsong

Deputy Director of the laboratory

(Approved this test report)

©Copyright. All rights reserved by CTTL.

2 Statement of Compliance

The maximum results of SAR found during testing for HMD Global Oy Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN TA-1216 are as follows:

Table 2.1: Highest Reported SAR (1g)

Exposure Configuration	Technology Band	Highest Reported SAR 1g(W/kg)	Equipment Class
Head	GSM 850	0.24	PCE
	PCS 1900	0.16	
	UMTS FDD 5	0.37	
	LTE Band 5	0.25	
	LTE Band 7	0.23	
	WLAN 2.4 GHz	0.46	DTS
Body	GSM 850	0.43	PCE
	PCS 1900	0.28	
	UMTS FDD 5	0.56	
	LTE Band 5	0.47	
	LTE Band 7	0.68	
	WLAN 2.4 GHz	0.19	DTS

The SAR values found for the Mobile Phone are below the maximum recommended levels of 1.6 W/kg as averaged over any 1g tissue according to the ANSI C95.1-1992.

For body operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and which provides a minimum separation distance of 10 mm between this device and the body of the user. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output.

The measurement together with the test system set-up is described in annex C of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report. The highest reported SAR value is obtained at the case of **(Table 2.1),** and the values are**: 0.68 W/kg(1g).**

Table 2.2: The sum of reported SAR values for main antenna and WiFi

	Position	**Main antenna**	**WiFi**	**Sum**
Highest reported SAR value for Head	Left hand, Touch cheek	0.37 (WCDMA850)	0.46	**0.83**
Highest reported SAR value for Body	Rear 10mm	0.68 (LTE Band7)	0.19	**0.87**

©Copyright. All rights reserved by CTTL.

Table 2.3: The sum of reported SAR values for main antenna and BT

	Position	Main antenna	BT	Sum
Maximum reported SAR value for Head	Left hand, Touch cheek	0.37 (WCDMA850)	0.17[1]	**0.54**
Maximum reported SAR value for Body	Rear 10mm	0.68 (LTE Band7)	0.08[1]	**0.76**

[1] - Estimated SAR for Bluetooth (see the table 13.3)

According to the above tables, the highest sum of reported SAR values is **0.87 W/kg (1g)**. The detail for simultaneous transmission consideration is described in chapter 13.

3 Client Information

3.1 Applicant Information

Company Name:	HMD Global Oy
Address/Post:	Bertel Jungin aukio 9,02600 Espoo, Finland
Contact Person:	Rosario Casillo
Contact Email:	Rosario.Casillo@hmdglobal.com
Telephone:	NA
Fax:	NA

3.2 Manufacturer Information

Company Name:	HMD Global Oy
Address/Post:	Bertel Jungin aukio 9,02600 Espoo, Finland
Contact Person:	Rosario Casillo
Contact Email:	Rosario.Casillo@hmdglobal.com
Telephone:	NA
Fax:	NA

©Copyright. All rights reserved by CTTL.

4 Equipment Under Test (EUT) and Ancillary Equipment (AE)

4.1 About EUT

Description:	Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN
Model name:	TA-1216
Operating mode(s):	GSM 850/900/1800/1900, UMTS FDD1/5/8, BT, Wi-Fi LTE Band1/3/5/7/8/20/28
Tested Tx Frequency:	824 – 849 MHz (GSM 850)
	1850 – 1910 MHz (GSM 1900)
	824–849 MHz (WCDMA 850 Band V)
	824.7 – 848.3 MHz (LTE Band 5)
	2502.5 – 2567.5 MHz (LTE Band 7)
	2412 – 2462 MHz (Wi-Fi 2.4G)
GPRS/EGPRS Multislot Class:	33
GPRS capability Class:	B
Test device Production information:	Production unit
Device type:	Portable device
Antenna type:	Integrated antenna
Hotspot mode:	Support

4.2 Internal Identification of EUT used during the test

EUT ID*	IMEI	HW	SW Version
EUT1	354225100003875	89572_1_12	000T_0_110
EUT2	355781100006218	89572_1_12	000T_0_110
EUT3	354224100012325	89572_1_12	000T_0_110
EUT4	354224100025681	89572_1_12	000T_0_110

*EUT ID: is used to identify the test sample in the lab internally.

Note: It is performed to test SAR with the EUT1&2 and conducted power with the EUT3~4.

4.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Battery	WT130	/	GUANGDONG FENGHUA NEW ENERGY CO.,LTD
AE2	Headset	HS-34	/	New Leader Industry Co.,Ltd

*AE ID: is used to identify the test sample in the lab internally.

©Copyright. All rights reserved by CTTL.

5 TEST METHODOLOGY

5.1 Applicable Limit Regulations

ANSI C95.1–1992:IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

IEEE 1528–2013: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

KDB447498 D01: General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

KDB648474 D04 Handset SAR v01r03: SAR Evaluation Considerations for Wireless Handsets.

KDB941225 D01 SAR test for 3G devices v03r01: SAR Measurement Procedures for 3G Devices

KDB941225 D05 SAR for LTE Devices v02r05: SAR Evaluation Considerations for LTE Devices

KDB941225 D06 Hotspot Mode SAR v02r01: SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities

KDB248227 D01 802.11 Wi-Fi SAR v02r02: SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS

KDB865664 D01SAR measurement 100 MHz to 6 GHz v01r04: SAR Measurement Requirements for 100 MHz to 6 GHz.

KDB865664 D02RF Exposure Reporting v01r02: RF Exposure Compliance Reporting and Documentation Considerations

©Copyright. All rights reserved by CTTL.

6 Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ) . The equation description is as below:

$$SAR = \frac{d}{dt}\left(\frac{dW}{dm}\right) = \frac{d}{dt}\left(\frac{dW}{\rho dv}\right)$$

SAR is expressed in units of Watts per kilogram (W/kg)
SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c\left(\frac{\delta T}{\delta t}\right)$$

Where: C is the specific head capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

©Copyright. All rights reserved by CTTL.

7 Tissue Simulating Liquids

7.1 Targets for tissue simulating liquid

Table 7.1: Targets for tissue simulating liquid

Frequency(MHz)	Liquid Type	Conductivity(σ)	± 5% Range	Permittivity(ε)	± 5% Range
835	Head	0.90	0.86～0.95	41.5	39.4～43.6
1900	Head	1.40	1.33～1.47	40.0	38.0～42.0
2450	Head	1.80	1.71～1.89	39.2	37.2～41.2
2600	Head	1.96	1.86～2.06	39.01	37.1～41.0

7.2 Dielectric Performance

Table 7.2: Dielectric Performance of Tissue Simulating Liquid

Measurement Date (yyyy-mm-dd)	Type	Frequency	Permittivity ε	Drift (%)	Conductivity σ (S/m)	Drift (%)
2019-12-11	Head	835 MHz	41.63	0.31	0.907	0.78
2019-12-12	Head	1900 MHz	39.95	-0.12	1.375	-1.79
2019-12-13	Head	2450 MHz	38.58	-1.58	1.805	0.28
2019-12-14	Head	2600 MHz	38.36	-1.67	1.935	-1.28

Note: The liquid temperature is 22.0℃



Picture 7-1 Liquid depth in the Head Phantom (835 MHz)

©Copyright. All rights reserved by CTTL.



Picture 7-2 Liquid depth in the Head Phantom (1900 MHz)



Picture 7-3 Liquid depth in the Head Phantom (2450MHz)

©Copyright. All rights reserved by CTTL.

Picture 7-4 Liquid depth in the Head Phantom (2600 MHz)

©Copyright. All rights reserved by CTTL.

8 System verification

8.1 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Picture 8.1 System Setup for System Evaluation



Picture 8.2 Photo of Dipole Setup

©Copyright. All rights reserved by CTTL.

8.2 System Verification

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device.

The system verification results are required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR. The details are presented in annex B.

Table 8.1: System Verification of Head

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value(W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2019-12-11	835 MHz	6.29	9.70	6.4	9.64	1.75%	-0.62%
2019-12-12	1900 MHz	20.8	39.7	20.6	40	-0.96%	0.76%
2019-12-13	2450 MHz	24.2	51.6	24.12	50.92	-0.33%	-1.32%
2019-12-14	2600 MHz	25.1	55.8	25.52	55.92	1.67%	0.22%

©Copyright. All rights reserved by CTTL.

9 Measurement Procedures

9.1 Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in picture 9.1.

Step 1: The tests described in 9.2 shall be performed at the channel that is closest to the centre of the transmit frequency band (f_c) for:

a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in annex D),
b) all configurations for each device position in a), e.g., antenna extended and retracted, and
c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.

If more than three frequencies need to be tested according to 11.1 (i.e., $N_c > 3$), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

Step 2: For the condition providing highest peak spatial-average SAR determined in Step 1,perform all tests described in 9.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

Step 3: Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.

©Copyright. All rights reserved by CTTL.



Picture a – Tests to be performed

Picture b – General procedure

Picture 9.1Block diagram of the tests to be performed

©Copyright. All rights reserved by CTTL.

9.2 General Measurement Procedure

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements and fully documented in SAR reports to qualify for TCB approval. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2003. The results should be documented as part of the system validation records and may be requested to support test results when all the measurement parameters in the following table are not satisfied.

<table>
<tr><td colspan="3"></td><td>≤ 3 GHz</td><td>> 3 GHz</td></tr>
<tr><td colspan="3">Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface</td><td>5 ± 1 mm</td><td>½·δ·ln(2) ± 0.5 mm</td></tr>
<tr><td colspan="3">Maximum probe angle from probe axis to phantom surface normal at the measurement location</td><td>30° ± 1°</td><td>20° ± 1°</td></tr>
<tr><td colspan="3" rowspan="2">Maximum area scan spatial resolution: Δx_{Area}, Δy_{Area}</td><td>≤ 2 GHz: ≤ 15 mm
2 – 3 GHz: ≤ 12 mm</td><td>3 – 4 GHz: ≤ 12 mm
4 – 6 GHz: ≤ 10 mm</td></tr>
<tr><td colspan="2">When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.</td></tr>
<tr><td colspan="3">Maximum zoom scan spatial resolution: Δx_{Zoom}, Δy_{Zoom}</td><td>≤ 2 GHz: ≤ 8 mm
2 – 3 GHz: ≤ 5 mm*</td><td>3 – 4 GHz: ≤ 5 mm*
4 – 6 GHz: ≤ 4 mm*</td></tr>
<tr><td rowspan="3">Maximum zoom scan spatial resolution, normal to phantom surface</td><td colspan="2">uniform grid: $\Delta z_{Zoom}(n)$</td><td>≤ 5 mm</td><td>3 – 4 GHz: ≤ 4 mm
4 – 5 GHz: ≤ 3 mm
5 – 6 GHz: ≤ 2 mm</td></tr>
<tr><td rowspan="2">graded grid</td><td>$\Delta z_{Zoom}(1)$: between 1st two points closest to phantom surface</td><td>≤ 4 mm</td><td>3 – 4 GHz: ≤ 3 mm
4 – 5 GHz: ≤ 2.5 mm
5 – 6 GHz: ≤ 2 mm</td></tr>
<tr><td>$\Delta z_{Zoom}(n>1)$: between subsequent points</td><td colspan="2">≤ 1.5·$\Delta z_{Zoom}(n-1)$</td></tr>
<tr><td>Minimum zoom scan volume</td><td colspan="2">x, y, z</td><td>≥ 30 mm</td><td>3 – 4 GHz: ≥ 28 mm
4 – 5 GHz: ≥ 25 mm
5 – 6 GHz: ≥ 22 mm</td></tr>
<tr><td colspan="5">Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.
* When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.</td></tr>
</table>

©Copyright. All rights reserved by CTTL.

9.3 WCDMA Measurement Procedures for SAR

The following procedures are applicable to WCDMA handsets operating under 3GPP Release99, Release 5 and Release 6. The default test configuration is to measure SAR with an established radio link between the DUT and a communication test set using a 12.2kbps RMC (reference measurement channel) configured in Test Loop Mode 1. SAR is selectively confirmed for other physical channel configurations (DPCCH & $DPDCH_n$), HSDPA and HSPA (HSUPA/HSDPA) modes according to output power, exposure conditions and device operating capabilities. Both uplink and downlink should be configured with the same RMC or AMR, when required. SAR for Release 5 HSDPA and Release 6 HSPA are measured using the applicable FRC (fixed reference channel) and E-DCH reference channel configurations. Maximum output power is verified according to applicable versions of 3GPP TS 34.121 and SAR must be measured according to these maximum output conditions. When Maximum Power Reduction (MPR) is not implemented according to Cubic Metric (CM) requirements for Release 6 HSPA, the following procedures do not apply.

For Release 5 HSDPA Data Devices:

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs}	CM/dB
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15	15/15	64	12/15	24/25	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

For Release 6 HSPA Data Devices

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs}	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (dB)	MPR (dB)	AG Index	E-TFCI
1	11/15	15/15	64	11/15	22/15	209/225	1039/225	4	1	1.5	1.5	20	75
2	6/15	15/15	64	6/15	12/15	12/15	12/15	4	1	1.5	1.5	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1}:47/15 β_{ed2}:47/15	4	2	1.5	1.5	15	92
4	2/15	15/15	64	2/15	4/15	4/15	56/75	4	1	1.5	1.5	17	71
5	15/15	15/15	64	15/15	24/15	30/15	134/15	4	1	1.5	1.5	21	81

Rel.8 DC-HSDPA (Cat 24)

SAR test exclusion for Rel.8 DC-HSDPA must satisfy the SAR test exclusion requirements of Rel.5 HSDPA. SAR test exclusion for DC-HSDPA devices is determined by power measurements according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to qualify for SAR test exclusion.

©Copyright. All rights reserved by CTTL.

9.4 SAR Measurement for LTE

SAR tests for LTE are performed with a base station simulator, Rohde & Rchwarz CMW500. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. All powers were measured with the CMW 500.
It is performed for conducted power and SAR based on the KDB941225 D05.
SAR is evaluated separately according to the following procedures for the different test positions in each exposure condition – head, body, body-worn accessories and other use conditions. The procedures in the following subsections are applied separately to test each LTE frequency band.

1) QPSK with 1 RB allocation
   Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.
2) QPSK with 50% RB allocation
   The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.
3) QPSK with 100% RB allocation
   For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

9.5 Bluetooth & Wi-Fi Measurement Procedures for SAR

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.
Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

©Copyright. All rights reserved by CTTL.

9.6 Power Drift

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in section14 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

©Copyright. All rights reserved by CTTL.

10 Area Scan Based 1-g SAR

10.1 Requirement of KDB

According to the KDB447498 D01 v05, when the implementation is based the specific polynomial fit
algorithm as presented at the 29th Bioelectromagnetics Society meeting (2007) and the estimated 1-gSAR is ≤ 1.2 W/kg, a zoom scan measurement is not required provided it is also not needed for any other purpose; for example, if the peak SAR location required for simultaneous transmission SAR test exclusion can be determined accurately by the SAR system or manually to discriminate between distinctive peaks and scattered noisy SAR distributions from area scans.

There must not be any warning or alert messages due to various measurement concerns identified by the SAR system; for example, noise in measurements, peaks too close to scan boundary, peaks are too sharp, spatial resolution and uncertainty issues etc. The SAR system verification must also demonstrate that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR (See Annex B). When all the SAR results for each exposure condition in a frequency band and wireless mode are based on estimated 1-g SAR, the 1-g SAR for the highest SAR configuration must be determined by a zoom scan.

10.2 Fast SAR Algorithms

The approach is based on the area scan measurement applying a frequency dependent attenuation parameter. This attenuation parameter was empirically determined by analyzing a large number of phones. The MOTOROLA FAST SAR was developed and validated by the MOTOROLA Research Group in Ft. Lauderdale.

In the initial study, an approximation algorithm based on Linear fit was developed. The accuracy of the algorithm has been demonstrated across a broad frequency range (136-2450 MHz)and for both 1- and 10-g averaged SAR using a sample of 264 SAR measurements from 55wireless handsets. For the sample size studied, the root-mean-squared errors of the algorithm mare 1.2% and 5.8% for 1- and 10-g averaged SAR, respectively. The paper describing the algorithm in detail is expected to be published in August 2004 within the Special Issue of Transactions on MTT.

In the second step, the same research group optimized the fitting algorithm to an Polynomial fit whereby the frequency validity was extended to cover the range 30-6000MHz. Details of this study can be found in the BEMS 2007 Proceedings.

Both algorithms are implemented in DASY software.

©Copyright. All rights reserved by CTTL.

11 Conducted Output Power

For Main antenna, there are two sets of tune-up power, Normal power and Low power, used for different use cases for PCS1900 and LTE Band7. Normal power status is applied for head test and body worn test of above bands. Low power status is applied for sensor test of above bands. For other bands, Normal power status is applied for both head and body test. The detail of sensor is presented in annex I.

11.1 GSM Measurement result

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (E5515C) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

Table 11.1-1: The conducted power measurement results for GSM, GPRS and EGPRS-Normal power

GSM 850	Measured Power (dBm)			Tune up	calculation	Averaged Power (dBm)		
Speech (GMSK)	251	190	128			251	190	128
1 Txslot	32.58	32.76	32.60	33.00	/	/	/	/
GSM 850	Measured Power (dBm)				calculation	Averaged Power (dBm)		
GPRS (GMSK)	251	190	128			251	190	128
1 Txslot	32.76	32.65	32.68	33.00	-9.03	23.73	23.62	23.65
2 Txslots	29.76	29.68	29.68	30.00	-6.02	23.74	23.66	23.66
3Txslots	27.83	27.59	27.36	28.00	-4.26	23.57	23.33	23.10
4 Txslots	26.65	26.60	26.64	27.50	-3.01	23.64	23.59	23.63
GSM 850	Measured Power (dBm)				calculation	Averaged Power (dBm)		
EGPRS (GMSK)	251	190	128			251	190	128
1 Txslot	32.55	32.25	32.59	33.00	-9.03	23.52	23.22	23.56
2 Txslots	29.61	29.66	29.60	30.00	-6.02	23.59	23.64	23.58
3Txslots	27.70	27.47	27.27	28.00	-4.26	23.44	23.21	23.01
4 Txslots	26.52	26.54	26.55	27.50	-3.01	23.51	23.53	23.54
GSM 850	Measured Power (dBm)				calculation	Averaged Power (dBm)		
EGPRS (8PSK)	251	190	128			251	190	128
1 Txslot	25.61	26.58	25.82	27.00	-9.03	16.58	17.55	16.79
2 Txslots	21.97	22.17	22.12	23.00	-6.02	15.95	16.15	16.10
3Txslots	21.16	21.22	21.32	22.50	-4.26	16.90	16.96	17.06
4 Txslots	20.92	20.95	20.93	22.00	-3.01	17.91	17.94	17.92
PCS1900	Measured Power (dBm)			Tune up	calculation	Averaged Power (dBm)		
Speech (GMSK)	810	661	512			810	661	512
1 Txslot	30.12	30.21	30.34	30.50	/	/	/	/
PCS1900	Measured Power (dBm)				calculation	Averaged Power (dBm)		
GPRS (GMSK)	810	661	512			810	661	512
1 Txslot	30.26	30.12	30.19	30.50	-9.03	21.23	21.09	21.16

©Copyright. All rights reserved by CTTL.

2 Txslots	27.76	27.82	27.83	28.00	-6.02	21.74	21.80	21.81
3Txslots	25.08	25.16	25.17	25.50	-4.26	20.82	20.90	20.91
4 Txslots	24.84	24.95	24.95	25.00	-3.01	21.83	21.94	21.94
PCS1900	Measured Power (dBm)				calculation	Averaged Power (dBm)		
EGPRS (GMSK)	810	661	512			810	661	512
1 Txslot	30.17	30.09	30.12	30.50	-9.03	21.14	21.06	21.09
2 Txslots	27.61	27.73	27.76	28.00	-6.02	21.59	21.71	21.74
3Txslots	24.96	25.07	25.09	25.50	-4.26	20.70	20.81	20.83
4 Txslots	24.74	24.86	24.89	25.00	-3.01	21.73	21.85	21.88
PCS1900	Measured Power (dBm)				calculation	Averaged Power (dBm)		
EGPRS (8PSK)	810	661	512			810	661	512
1 Txslot	25.33	25.34	25.44	25.50	-9.03	16.30	16.31	16.41
2 Txslots	23.76	23.79	23.90	24.00	-6.02	17.74	17.77	17.88
3Txslots	23.55	23.60	23.71	24.00	-4.26	19.29	19.34	19.45
4 Txslots	23.27	23.49	23.45	23.50	-3.01	20.26	20.48	20.44

NOTES:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 2Txslots for GSM850 and 4Txslots for GSM1900.

Table 11.1-1: The conducted power measurement results for GSM, GPRS and EGPRS- Low power

PCS1900	Measured Power (dBm)			Tune up	calculation	Averaged Power (dBm)		
Speech (GMSK)	810	661	512			810	661	512
1 Txslot	26.44	26.62	25.40	27.00	/	/	/	/
PCS1900	Measured Power (dBm)				calculation	Averaged Power (dBm)		
GPRS (GMSK)	810	661	512			810	661	512
1 Txslot	26.36	26.43	25.27	27.00	-9.03	17.33	17.40	16.24
2 Txslots	23.39	22.51	22.66	24.50	-6.02	17.37	16.49	16.64
3Txslots	20.75	20.93	21.09	21.50	-4.26	16.49	16.67	16.83
4 Txslots	20.40	20.61	19.88	21.00	-3.01	17.39	17.60	16.87
PCS1900	Measured Power (dBm)				calculation	Averaged Power (dBm)		
EGPRS (GMSK)	810	661	512			810	661	512
1 Txslot	26.29	26.39	25.25	27.00	-9.03	17.26	17.36	16.22
2 Txslots	23.34	22.52	22.64	24.50	-6.02	17.32	16.50	16.62
3Txslots	20.71	20.91	21.15	21.50	-4.26	16.45	16.65	16.89
4 Txslots	20.37	20.59	19.96	21.00	-3.01	17.36	17.58	16.95

©Copyright. All rights reserved by CTTL.

PCS1900 EGPRS (8PSK)	Measured Power (dBm)				calculation	Averaged Power (dBm)		
	810	661	512			810	661	512
1 Txslot	22.59	22.23	22.34	23.00	-9.03	13.56	13.20	13.31
2 Txslots	20.33	20.26	20.35	21.00	-6.02	14.31	14.24	14.33
3Txslots	20.02	20.07	20.14	20.50	-4.26	15.76	15.81	15.88
4 Txslots	19.71	19.73	19.83	20.00	-3.01	16.70	16.72	16.82

NOTES:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 4Txslots for GSM1900.

11.2 WCDMA Measurement result

Table 11.2-1: The conducted Power for WCDMA- Normal power

Item	band	FDDV result			
	ARFCN	4233 (846.6MHz)	4182 (836.4MHz)	4132 (826.4MHz)	Tune up
WCDMA	\	24.37	24.39	24.35	25.00
HSUPA	1	23.23	23.13	23.42	24.00
	2	22.27	22.29	21.79	23.50
	3	22.19	21.81	21.90	22.50
	4	22.61	22.61	22.36	23.00
	5	23.31	23.29	23.38	23.50
DC-HSDPA	1	23.43	23.37	23.36	23.50
	2	23.38	23.36	23.39	23.50
	3	23.01	22.86	22.93	23.50
	4	22.98	22.91	22.89	23.50

©Copyright. All rights reserved by CTTL.

11.3 LTE Measurement result

Table 13.3-1: Maximum Power Reduction (MPR) for LTE

Modulation	Channel bandwidth / Transmission bandwidth configuration [RB]						MPR (dB)
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	2
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	2
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	3

Table 13.3-2: The tune up for LTE – Normal Power

Band	Tune up
LTE Band 5	24.5
LTE Band 7	25

Table 13.3-3: The tune up for LTE – Low Power

Band	Tune up
LTE Band 7	20.5

Normal Power

Table 11.3-4: The conducted Power for LTE

Band 5					
Bandwidth (MHz)	RB allocation RB offset (Start RB)	Frequency (MHz)	QPSK Actual output power (dBm)	16QAM Actual output power (dBm)	64QAM Actual output power (dBm)
1.4 MHz	1RB High (5)	848.3	24.14	22.80	21.99
		836.5	23.91	22.51	21.70
		824.7	24.18	22.85	22.04
	1RB Middle (3)	848.3	24.27	22.75	21.93
		836.5	24.14	22.84	22.03
		824.7	24.13	23.25	22.42
	1RB Low (0)	848.3	24.06	23.00	22.18
		836.5	23.84	22.83	22.01
		824.7	24.03	23.05	22.23
	3RB High (3)	848.3	24.22	22.75	21.94
		836.5	24.09	22.95	22.13
		824.7	23.80	23.06	22.24
	3RB Middle (1)	848.3	24.17	22.80	21.99
		836.5	24.03	23.10	22.27
		824.7	24.11	22.82	22.01
	3RB Low (0)	848.3	24.21	23.04	22.22
		836.5	24.00	23.00	22.18

©Copyright. All rights reserved by CTTL.

		824.7	24.04	23.09	22.26
	6RB (0)	848.3	23.00	22.33	21.53
		836.5	23.03	22.14	21.35
		824.7	23.04	22.20	21.41
3 MHz	1RB High (14)	847.5	24.48	23.12	22.37
		836.5	24.19	23.30	22.44
		825.5	23.96	22.96	22.21
	1RB Middle (7)	847.5	24.32	23.24	22.48
		836.5	24.11	23.07	22.32
		825.5	24.32	23.11	22.36
	1RB Low (0)	847.5	24.40	22.46	21.73
		836.5	24.15	23.00	22.25
		825.5	24.01	23.09	22.34
	8RB High (7)	847.5	23.01	21.79	21.08
		836.5	23.07	21.81	21.10
		825.5	23.08	22.09	21.37
	8RB Middle (4)	847.5	23.08	21.89	21.18
		836.5	23.04	21.90	21.18
		825.5	23.08	21.62	20.91
	8RB Low (0)	847.5	22.99	21.90	21.19
		836.5	23.07	22.17	21.45
		825.5	23.06	22.06	21.34
	15RB (0)	847.5	23.12	22.16	21.44
		836.5	23.02	22.06	21.34
		825.5	23.02	21.98	21.26
5 MHz	1RB High (24)	846.5	24.49	22.65	21.95
		836.5	23.94	23.03	22.32
		826.5	24.05	22.90	22.19
	1RB Middle (12)	846.5	24.42	22.50	21.81
		836.5	24.49	22.63	21.94
		826.5	24.23	22.56	21.86
	1RB Low (0)	846.5	24.05	22.56	21.86
		836.5	23.91	22.98	22.28
		826.5	23.90	22.78	22.07
	12RB High (13)	846.5	23.03	22.01	21.34
		836.5	23.16	21.87	21.19
		826.5	23.11	21.98	21.30
	12RB Middle (6)	846.5	23.02	21.99	21.31
		836.5	23.07	22.22	21.43
		826.5	23.05	21.97	21.29
	12RB Low (0)	846.5	23.04	21.89	21.22
		836.5	23.02	21.99	21.31
		826.5	23.11	22.23	21.48
	25RB (0)	846.5	22.96	21.85	21.18
		836.5	22.97	22.07	21.39
		826.5	23.11	22.07	21.39
10 MHz	1RB High (49)	844.0	24.09	23.16	22.39
		836.5	24.45	23.17	22.41

©Copyright. All rights reserved by CTTL.

		829.0	24.02	23.29	22.42
	1RB Middle (24)	844.0	24.09	23.06	22.30
		836.5	24.26	23.42	22.48
		829.0	24.31	22.98	22.22
	1RB Low (0)	844.0	24.10	22.90	22.15
		836.5	24.13	22.99	22.23
		829.0	23.80	22.67	21.92
	25RB High (25)	844.0	22.96	22.26	21.45
		836.5	23.08	21.99	21.26
		829.0	22.86	22.13	21.40
	25RB Middle (12)	844.0	22.89	22.20	21.47
		836.5	22.91	22.07	21.34
		829.0	22.91	22.13	21.40
	25RB Low (0)	844.0	22.97	22.20	21.46
		836.5	22.84	21.92	21.20
		829.0	22.95	22.08	21.35
	50RB (0)	844.0	22.92	21.90	21.18
		836.5	22.94	22.07	21.34
		829.0	22.99	22.19	21.46

Band 7					
Bandwidth (MHz)	RB allocation RB offset (Start RB)	Frequency (MHz)	QPSK Actual output power (dBm)	16QAM Actual output power (dBm)	64QAM Actual output power (dBm)
5 MHz	1RB High (24)	2567.5	24.21	22.57	22.10
		2535	24.06	22.73	22.25
		2502.5	24.12	22.53	22.05
	1RB Middle (12)	2567.5	24.45	22.82	22.33
		2535	24.41	22.82	22.33
		2502.5	24.37	22.87	22.39
	1RB Low (0)	2567.5	24.26	22.65	22.17
		2535	24.24	22.81	22.32
		2502.5	24.12	22.95	22.46
	12RB High (13)	2567.5	23.14	22.32	21.85
		2535	23.24	22.10	21.63
		2502.5	23.22	22.16	21.69
	12RB Middle (6)	2567.5	23.21	22.27	21.80
		2535	23.22	22.09	21.62
		2502.5	23.20	22.21	21.74
	12RB Low (0)	2567.5	23.19	22.31	21.84
		2535	23.18	22.13	21.66
		2502.5	23.21	22.11	21.64
	25RB (0)	2567.5	23.12	22.42	21.95
		2535	23.19	22.36	21.89
		2502.5	23.22	22.29	21.81
10 MHz	1RB	2565	24.68	23.91	22.40

©Copyright. All rights reserved by CTTL.

	High (49)	2535	24.40	22.91	22.43
		2505	24.17	23.29	22.80
	1RB Middle (24)	2565	24.43	23.74	22.94
		2535	24.53	22.84	22.35
		2505	24.30	23.42	22.92
	1RB Low (0)	2565	24.58	23.53	22.93
		2535	24.54	23.07	22.58
		2505	24.33	23.19	22.70
	25RB High (25)	2565	23.26	22.26	21.79
		2535	23.37	22.26	21.79
		2505	23.33	22.48	21.41
	25RB Middle (12)	2565	23.32	22.54	21.97
		2535	23.26	22.48	22.00
		2505	23.17	22.32	21.84
	25RB Low (0)	2565	23.24	22.39	21.91
		2535	23.33	22.30	21.83
		2505	23.30	22.52	21.94
	50RB (0)	2565	23.26	22.45	21.98
		2535	23.34	22.28	21.80
		2505	23.24	22.31	21.83
15 MHz	1RB High (74)	2562.5	24.38	23.44	22.95
		2535	24.22	23.61	22.81
		2507.5	24.12	23.69	22.99
	1RB Middle (37)	2562.5	24.25	23.37	22.87
		2535	24.26	23.60	23.00
		2507.5	24.11	23.75	22.94
	1RB Low (0)	2562.5	24.24	23.33	22.83
		2535	24.28	22.83	22.34
		2507.5	24.14	23.85	22.94
	36RB High (38)	2562.5	23.00	22.25	21.77
		2535	23.18	22.27	21.79
		2507.5	23.21	22.29	21.82
	36RB Middle (19)	2562.5	23.10	22.23	21.76
		2535	23.10	22.20	21.73
		2507.5	23.07	22.15	21.68
	36RB Low (0)	2562.5	23.03	22.20	21.73
		2535	23.13	22.25	21.77
		2507.5	23.11	22.32	21.84
	75RB (0)	2562.5	23.03	22.11	21.64
		2535	23.18	22.28	21.80
		2507.5	23.08	22.24	21.77
20 MHz	1RB High (99)	2560	24.06	23.33	22.83
		2535	24.51	23.19	22.70
		2510	24.12	23.14	22.64
	1RB Middle (50)	2560	24.46	23.42	22.93
		2535	24.49	23.31	22.81
		2510	24.27	23.34	22.85
	1RB	2560	24.36	23.40	22.91

©Copyright. All rights reserved by CTTL.

	Low (0)	2535	24.25	23.18	22.69
		2510	24.17	23.10	22.61
	50RB High (50)	2560	23.16	22.09	21.62
		2535	23.30	22.17	21.70
		2510	23.23	22.24	21.77
	50RB Middle (25)	2560	23.24	22.45	21.97
		2535	23.18	22.25	21.77
		2510	23.23	22.22	21.75
	50RB Low (0)	2560	23.24	22.45	21.97
		2535	23.19	22.17	21.70
		2510	23.15	22.21	21.73
	100RB (0)	2560	23.19	22.24	21.77
		2535	23.34	22.29	21.82
		2510	23.15	22.30	21.83

Low Power

Table 11.3-4: The conducted Power for LTE

Band 7					
Bandwidth (MHz)	RB allocation RB offset (Start RB)	Frequency (MHz)	QPSK Actual output power (dBm)	16QAM Actual output power (dBm)	64QAM Actual output power (dBm)
5 MHz	1RB High (24)	2567.5	19.40	18.33	17.79
		2535	19.87	18.24	17.70
		2502.5	19.37	18.24	17.71
	1RB Middle (12)	2567.5	19.78	18.43	17.89
		2535	19.99	18.67	18.13
		2502.5	19.78	18.33	17.79
	1RB Low (0)	2567.5	19.76	18.26	17.73
		2535	19.94	18.25	17.72
		2502.5	19.50	18.44	17.90
	12RB High (13)	2567.5	18.65	17.62	17.11
		2535	18.91	17.77	17.25
		2502.5	18.85	17.70	17.19
	12RB Middle (6)	2567.5	18.75	17.80	17.28
		2535	18.86	17.81	17.29
		2502.5	18.78	17.75	17.23
	12RB Low (0)	2567.5	18.74	17.63	17.12
		2535	18.79	17.84	17.32
		2502.5	18.83	17.73	17.21
	25RB (0)	2567.5	18.65	17.65	17.14
		2535	18.86	17.95	17.43
		2502.5	18.80	17.72	17.21
10 MHz	1RB High (49)	2565	19.68	18.43	17.89
		2535	19.85	18.95	18.40
		2505	19.78	18.97	18.42
	1RB	2565	19.89	18.95	18.39

©Copyright. All rights reserved by CTTL.

	Middle (24)	2535	19.82	18.98	18.42
		2505	19.84	18.37	17.83
	1RB Low (0)	2565	19.81	18.84	18.29
		2535	19.92	18.99	18.44
		2505	19.73	19.00	18.44
	25RB High (25)	2565	18.80	17.99	17.46
		2535	18.87	17.99	17.46
		2505	18.77	17.86	17.34
	25RB Middle (12)	2565	18.81	17.96	17.43
		2535	18.87	17.94	17.42
		2505	18.84	17.94	17.42
	25RB Low (0)	2565	18.81	17.99	17.46
		2535	18.82	17.89	17.37
		2505	18.81	17.80	17.28
	50RB (0)	2565	18.76	17.84	17.31
		2535	18.87	17.93	17.41
		2505	18.82	17.92	17.39
15 MHz	1RB High (74)	2562.5	19.44	18.93	18.37
		2535	19.90	18.95	18.40
		2507.5	19.78	18.95	18.40
	1RB Middle (37)	2562.5	19.56	18.98	18.43
		2535	19.79	18.94	18.38
		2507.5	19.61	18.30	17.77
	1RB Low (0)	2562.5	19.74	18.92	18.36
		2535	19.93	18.97	18.42
		2507.5	19.64	18.93	18.37
	36RB High (38)	2562.5	18.67	17.85	17.32
		2535	18.88	17.78	17.26
		2507.5	18.77	17.85	17.33
	36RB Middle (19)	2562.5	18.78	17.84	17.32
		2535	18.74	17.79	17.27
		2507.5	18.67	17.75	17.23
	36RB Low (0)	2562.5	18.82	17.86	17.33
		2535	18.77	17.79	17.27
		2507.5	18.78	17.88	17.36
	75RB (0)	2562.5	18.81	17.80	17.28
		2535	18.86	17.90	17.37
		2507.5	18.84	17.91	17.39
20 MHz	1RB High (99)	2560	19.52	18.69	18.14
		2535	19.55	18.45	17.91
		2510	19.39	18.38	17.85
	1RB Middle (50)	2560	19.99	18.91	18.36
		2535	19.85	18.58	18.03
		2510	19.60	18.70	18.15
	1RB Low (0)	2560	19.83	18.77	18.22
		2535	19.79	18.74	18.19
		2510	19.46	18.37	17.83
	50RB	2560	18.88	17.54	17.03

©Copyright. All rights reserved by CTTL.

	High (50)	2535	18.87	17.80	17.28
		2510	18.78	17.79	17.27
	50RB Middle (25)	2560	18.85	17.68	17.16
		2535	18.82	17.75	17.23
		2510	18.76	17.77	17.25
	50RB Low (0)	2560	18.81	17.65	17.13
		2535	18.76	17.69	17.17
		2510	18.74	17.88	17.36
	100RB (0)	2560	18.82	17.65	17.14
		2535	18.82	17.77	17.25
		2510	18.84	17.87	17.35

11.4 Wi-Fi and BT Measurement result

The maximum output power of BT is 5.42dBm.
The maximum tune up of BT is 6dBm.

The average conducted power for Wi-Fi is as following:

802.11b	Channel\data	1Mbps	2Mbps	5.5Mbps	11Mbps				
WLAN2450	11(2462MHz)	17.26	/	/	/				
	6(2437(MHz)	17.71	/	/	/				
	1(2412MHz)	18.16	18.07	18.11	18.13				
	Tuneup	18.50	18.50	18.50	18.50				
802.11g	Channel\data	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
WLAN2450	11(2462MHz)	12.85	/	/	/	/	/	/	/
	6(2437(MHz)	13.12	/	/	/	/	/	/	/
	1(2412MHz)	13.52	13.29	13.27	13.26	13.24	13.25	13.20	13.19
	Tuneup	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00
802.11n-20MHz	Channel\data	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
WLAN2450	11(2462MHz)	11.98	/	/	/	/	/	/	/
	6(2437(MHz)	12.14	/	/	/	/	/	/	/
	1(2412MHz)	12.55	12.16	12.08	12.02	12.00	11.97	11.96	11.93
	Tuneup	13.00	13.00	13.00	13.00	13.00	13.00	13.00	13.00

©Copyright. All rights reserved by CTTL.

12 Simultaneous TX SAR Considerations

12.1 Introduction

The following procedures adopted from “FCC SAR Considerations for Cell Phones with Multiple Transmitters” are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter.
For this device, the BT and Wi-Fi can transmit simultaneous with other transmitters.

12.2 Transmit Antenna Separation Distances



Picture 12.1 Antenna Locations

©Copyright. All rights reserved by CTTL.

12.3 SAR Measurement Positions

According to the KDB941225 D06 Hot Spot SAR v01, the edges with less than 2.5 cm distance to the antennas need to be tested for SAR.

SAR measurement positions						
Mode	Front	Rear	Left edge	Right edge	Top edge	Bottom edge
Main antenna	Yes	Yes	Yes	Yes	No	Yes
WLAN	Yes	Yes	No	Yes	Yes	No

12.4 Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied. The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0 for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Table 12.1: Standalone SAR test exclusion considerations

Band/Mode	F(GHz)	Position	SAR test exclusion threshold(mW)	RF output power		SAR test exclusion
				dBm	mW	
Bluetooth	2.441	Head	9.60	6	3.98	Yes
		Body	19.20	6	3.98	Yes
2.4GHz WLAN	2.45	Head	9.58	18.5	70.79	No
		Body	19.17	18.5	70.79	No

©Copyright. All rights reserved by CTTL.

13 Evaluation of Simultaneous

Table 13.1: The sum of reported SAR values for main antenna and WiFi

	Position	Main antenna	WiFi	Sum
Highest reported SAR value for Head	Left hand, Touch cheek	0.37 (WCDMA850)	0.46	**0.83**
Highest reported SAR value for Body	Rear 10mm	0.68 (LTE Band7)	0.19	**0.87**

Table 13.2: The sum of reported SAR values for main antenna and BT

	Position	Main antenna	BT	Sum
Maximum reported SAR value for Head	Left hand, Touch cheek	0.37 (WCDMA850)	0.17[1]	**0.54**
Maximum reported SAR value for Body	Rear 10mm	0.68 (LTE Band7)	0.08[1]	**0.76**

[1] - Estimated SAR for Bluetooth (see the table 13.3)

Table 13.3: Estimated SAR for Bluetooth

Mode/Band	F (GHz)	Position	Distance (mm)	Upper limit of power *		Estimated$_{1g}$ (W/kg)
				dBm	mW	
Bluetooth	2.441	Head	5	6	3.98	0.17
Bluetooth	2.441	Body	10	6	3.98	0.08

* - Maximum possible output power declared by manufacturer

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,mm)]·[√f(GHz)/x] W/kg for test separation distances ≤ 50 mm;
where x = 7.5 for 1-g SAR.
When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

Conclusion:
According to the above tables, the sum of reported SAR values is<1.6W/kg. So the simultaneous transmission SAR with volume scans is not required.

©Copyright. All rights reserved by CTTL.

14 SAR Test Result

It is determined by user manual for the distance between the EUT and the phantom bottom. The distance is 10 mm or 15mm and just applied to the condition of body worn accessory.

It is performed for all SAR measurements with area scan based 1-g SAR estimation (Fast SAR). A zoom scan measurement is added when the estimated 1-gSAR is the highest measured SAR in each exposure configuration, wireless mode and frequency band combination or more than 1.2W/kg.

The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} \times 10^{(P_{Target}-P_{Measured})/10}$$

Where P_{Target} is the power of manufacturing upper limit;

$P_{Measured}$ is the measured power in chapter 11.

Table 14.1: Duty Cycle

Mode	Duty Cycle
Speech for GSM850/1900	1:8.3
GPRS&EGPRS for GSM850	1:4
GPRS&EGPRS for 1900	1:2
WCDMA&LTE FDD	1:1

©Copyright. All rights reserved by CTTL.

Note

H1: The Headset of HS-34 by New Leader Industry Co.,Ltd

14.1 SAR results for Fast SAR

Table 14.1-1: SAR Values (GSM 850 MHz Band - Head)

Ambient Temperature: 22.9 ºC Liquid Temperature: 22.5ºC											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
251	848.8	Left	Touch	/	32.58	33	0.161	**0.18**	0.206	**0.23**	-0.05
190	836.6	Left	Touch	Fig.1	32.76	33	0.17	**0.18**	0.224	**0.24**	-0.11
128	824.2	Left	Touch	/	32.6	33	0.147	**0.16**	0.189	**0.21**	-0.17
190	836.6	Left	Tilt	/	32.76	33	0.147	**0.16**	0.189	**0.20**	-0.02
190	836.6	Right	Touch	/	32.76	33	0.156	**0.16**	0.202	**0.21**	-0.15
190	836.6	Right	Tilt	/	32.76	33	0.137	**0.14**	0.178	**0.19**	0.10

Table 14.1-2: SAR Values (GSM 850 MHz Band - Body)

Ambient Temperature: 22.9 ºC Liquid Temperature: 22.5ºC											
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
190	836.6	GPRS (2)	Front	/	29.68	30	0.155	**0.17**	0.201	**0.22**	-0.12
251	848.8	GPRS (2)	Rear	/	29.76	30	0.286	**0.30**	0.379	**0.40**	-0.14
190	836.6	GPRS (2)	Rear	/	29.68	30	0.281	**0.30**	0.38	**0.41**	-0.13
128	824.2	GPRS (2)	Rear	Fig.2	29.68	30	0.306	**0.33**	0.403	**0.43**	0.14
190	836.6	GPRS (2)	Left	/	29.68	30	0.171	**0.18**	0.242	**0.26**	0.16
190	836.6	GPRS (2)	Right	/	29.68	30	0.139	**0.15**	0.193	**0.21**	0.01
190	836.6	GPRS (2)	Bottom	/	29.68	30	0.027	**0.03**	0.049	**0.05**	0.15
128	824.2	EGPRS (2)	Rear	/	29.6	30	0.299	**0.33**	0.375	**0.41**	0.08

Note: The distance between the EUT and the phantom bottom is 10mm.

©Copyright. All rights reserved by CTTL.

Table 14.1-3: SAR Values (GSM 1900 MHz Band - Head)

Ambient Temperature: 22.9 ℃ Liquid Temperature: 22.5℃											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
810	1909.8	Left	Touch	Fig.3	30.12	30.5	0.094	**0.10**	0.146	**0.16**	0.06
661	1880	Left	Touch	/	30.21	30.5	0.077	**0.08**	0.143	**0.15**	-0.08
512	1850.2	Left	Touch	/	30.34	30.5	0.073	**0.08**	0.118	**0.12**	-0.18
661	1880	Left	Tilt	/	30.21	30.5	0.066	**0.07**	0.107	**0.11**	0.18
661	1880	Right	Touch	/	30.21	30.5	0.097	**0.10**	0.137	**0.15**	0.05
661	1880	Right	Tilt	/	30.21	30.5	0.064	**0.07**	0.1	**0.11**	0.07

Table 14.1-4: SAR Values (GSM 1900 MHz Band - Body)

Ambient Temperature: 22.9 ℃ Liquid Temperature: 22.5℃											
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
661	1880	GPRS (4)	Front	/	24.95	25	0.074	**0.07**	0.15	**0.15**	-0.11
661	1880	GPRS (4)	Rear	Note2	24.95	25	0.047	**0.05**	0.102	**0.10**	-0.18
661	1880	GPRS (4)	Left	/	24.95	25	0.038	**0.04**	0.079	**0.08**	-0.14
661	1880	GPRS (4)	Right	/	24.95	25	0.032	**0.03**	0.069	**0.07**	-0.03
661	1880	GPRS (4)	Bottom	Note2	24.95	25	0.058	**0.06**	0.126	**0.13**	-0.01
810	1909.8	GPRS (4)	Rear	/	20.4	21	0.065	**0.07**	0.162	**0.19**	-0.15
661	1880	GPRS (4)	Rear	/	20.61	21	0.076	**0.08**	0.198	**0.22**	0.02
512	1850.2	GPRS (4)	Rear	Fig.4	19.88	21	0.087	**0.11**	0.217	**0.28**	-0.01
661	1880	GPRS (4)	Bottom	/	20.61	21	0.072	**0.08**	0.176	**0.19**	-0.05
512	1850.2	EGPRS (4)	Rear	/	19.96	21	0.068	**0.09**	0.167	**0.21**	-0.19

Note1: The distance between the EUT and the phantom bottom is 10mm

Note2: The distance between the EUT and the phantom bottom is 17mm by sensor (See detail in annex I).

Table 14.1-5: SAR Values (WCDMA 850 MHz Band - Head)

Ambient Temperature: 22.9 ℃ Liquid Temperature: 22.5℃											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
4233	846.6	Left	Touch	/	24.37	25	0.229	**0.26**	0.304	**0.35**	0.14
4183	836.6	Left	Touch	Fig.5	24.39	25	0.247	**0.28**	0.325	**0.37**	0.15
4132	826.4	Left	Touch	/	24.35	25	0.197	**0.23**	0.257	**0.30**	0.16
4183	836.6	Left	Tilt	/	24.39	25	0.188	**0.22**	0.241	**0.28**	-0.19

©Copyright. All rights reserved by CTTL.

4183	836.6	Right	Touch	/	24.39	25	0.193	**0.22**	0.255	**0.29**	0.12
4183	836.6	Right	Tilt	/	24.39	25	0.181	**0.21**	0.233	**0.27**	-0.04

Table 14.1-6: SAR Values (WCDMA 850 MHz Band - Body)

Ambient Temperature: 22.9 ºC Liquid Temperature: 22.5ºC										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
4182	836.4	Front	/	24.39	25	0.218	**0.25**	0.279	**0.32**	0.03
4233	846.6	Rear	Fig.6	24.37	25	0.372	**0.43**	0.485	**0.56**	0.09
4182	836.4	Rear	/	24.39	25	0.369	**0.42**	0.477	**0.55**	0.03
4132	826.4	Rear	/	24.35	25	0.32	**0.37**	0.426	**0.49**	0.15
4182	836.4	Left	/	24.39	25	0.242	**0.28**	0.339	**0.39**	0.03
4182	836.4	Right	/	24.39	25	0.202	**0.23**	0.279	**0.32**	0.01
4182	836.4	Bottom	/	24.39	25	0.036	**0.04**	0.059	**0.07**	-0.16

Note: The distance between the EUT and the phantom bottom is 10mm.

Table 14.1-7: SAR Values (LTE Band5 - Head)

Ambient Temperature: 22.9ºC Liquid Temperature: 22.5ºC												
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
20525	836.5	1RB-High	Left	Touch	Fig.7	24.45	24.5	0.187	**0.19**	0.246	**0.25**	0.05
20525	836.5	1RB-High	Left	Tilt	/	24.45	24.5	0.155	**0.16**	0.195	**0.20**	-0.18
20525	836.5	1RB-High	Right	Touch	/	24.45	24.5	0.152	**0.15**	0.196	**0.20**	0.08
20525	836.5	1RB-High	Right	Tilt	/	24.45	24.5	0.142	**0.14**	0.181	**0.18**	-0.12
20525	836.5	25RB_High	Left	Touch	/	23.08	23.5	0.15	**0.17**	0.197	**0.22**	0.12
20525	836.5	25RB_High	Left	Tilt	/	23.08	23.5	0.119	**0.13**	0.152	**0.17**	0.02
20525	836.5	25RB_High	Right	Touch	/	23.08	23.5	0.114	**0.13**	0.148	**0.16**	0.06
20525	836.5	25RB_High	Right	Tilt	/	23.08	23.5	0.109	**0.12**	0.14	**0.15**	0.14

Note1: The LTE mode is QPSK_10MHz.

Table 14.1-8: SAR Values (LTE Band5 - Body)

Ambient Temperature: 22.9 ºC Liquid Temperature: 22.5ºC											
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
20525	836.5	1RB-High	Front	/	24.45	24.5	0.195	**0.20**	0.255	**0.26**	-0.09
20525	836.5	1RB-High	Rear	Fig.8	24.45	24.5	0.357	**0.36**	0.465	**0.47**	0.13
20525	836.5	1RB-High	Left	/	24.45	24.5	0.235	**0.24**	0.33	**0.33**	-0.18
20525	836.5	1RB-High	Right	/	24.45	24.5	0.197	**0.20**	0.28	**0.28**	0.11

©Copyright. All rights reserved by CTTL.

20525	836.5	1RB-High	Bottom	/	24.45	24.5	0.04	**0.04**	0.085	**0.09**	0.03
20525	836.5	25RB_High	Front	/	23.08	23.5	0.156	**0.17**	0.205	**0.23**	-0.03
20525	836.5	25RB_High	Rear	/	23.08	23.5	0.281	**0.31**	0.366	**0.40**	-0.06
20525	836.5	25RB_High	Left	/	23.08	23.5	0.186	**0.20**	0.262	**0.29**	0.07
20525	836.5	25RB_High	Right	/	23.08	23.5	0.156	**0.17**	0.223	**0.25**	-0.13
20525	836.5	25RB_High	Bottom	/	23.08	23.5	0.031	**0.03**	0.065	**0.07**	-0.16

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

Table 14.1-9: SAR Values (LTE Band7 - Head)

Ambient Temperature: 22.9 ℃						Liquid Temperature: 22.5℃						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
21100	2535	1RB-High	Left	Touch	/	24.51	25	0.05	**0.06**	0.089	**0.10**	0.08
21100	2535	1RB-High	Left	Tilt	/	24.51	25	0.038	**0.04**	0.071	**0.08**	0.03
21100	2535	1RB-High	Right	Touch	Fig.9	24.51	25	0.109	**0.12**	0.205	**0.23**	0.05
21100	2535	1RB-High	Right	Tilt	/	24.51	25	0.027	**0.03**	0.052	**0.06**	0.05
21100	2535	50RB_High	Left	Touch	/	23.3	24	0.042	**0.05**	0.078	**0.09**	-0.13
21100	2535	50RB_High	Left	Tilt	/	23.3	24	0.028	**0.03**	0.054	**0.06**	0.11
21100	2535	50RB_High	Right	Touch	/	23.3	24	0.083	**0.10**	0.158	**0.19**	-0.09
21100	2535	50RB_High	Right	Tilt	/	23.3	24	0.021	**0.02**	0.04	**0.05**	-0.02

Note1: The LTE mode is QPSK_20MHz.

Table 14.1-10: SAR Values (LTE Band7 - Body)

Ambient Temperature: 22.9 ℃						Liquid Temperature: 22.5℃					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
21100	2535	1RB-High	Front	/	24.51	25	0.191	**0.21**	0.356	**0.40**	-0.01
21100	2535	1RB-High	Rear	Note2	24.51	25	0.284	**0.32**	0.588	**0.66**	-0.05
21100	2535	1RB-High	Left	/	24.51	25	0.058	**0.06**	0.105	**0.12**	-0.02
21100	2535	1RB-High	Right	/	24.51	25	0.139	**0.16**	0.259	**0.29**	0.00
21100	2535	1RB-High	Bottom	Note2	24.51	25	0.24	**0.27**	0.478	**0.54**	-0.15
21100	2535	50RB_High	Front	/	23.3	24	0.153	**0.18**	0.285	**0.33**	0.05
21100	2535	50RB_High	Rear	Note2	23.3	24	0.212	**0.25**	0.44	**0.52**	-0.08
21100	2535	50RB_High	Left	/	23.3	24	0.043	**0.05**	0.08	**0.09**	0.06
21100	2535	50RB_High	Right	/	23.3	24	0.106	**0.12**	0.198	**0.23**	0.09
21100	2535	50RB_High	Bottom	Note2	23.3	24	0.177	**0.21**	0.352	**0.41**	-0.17

©Copyright. All rights reserved by CTTL.

21350	2560	1RB-Mid	Rear	Fig.10	19.99	20.5	0.266	**0.30**	0.609	**0.68**	-0.04
21350	2560	1RB-Mid	Bottom	/	19.99	20.5	0.18	**0.20**	0.393	**0.44**	-0.15
21350	2560	50RB_High	Rear	/	18.88	19.5	0.224	**0.26**	0.514	**0.59**	-0.08
21350	2560	50RB_High	Bottom	/	18.88	19.5	0.144	**0.17**	0.314	**0.36**	0.00

Note1: The distance between the EUT and the phantom bottom is 10mm

Note2: The distance between the EUT and the phantom bottom is 17mm by sensor (See detail in annex I).

Note3: The LTE mode is QPSK_20MHz.

14.2 SAR results for Standard procedure

There is zoom scan measurement to be added for the highest measured SAR in each exposure configuration/band.

Table 14.2-1: SAR Values (GSM 850 MHz Band - Head)

Ambient Temperature: 22.9 ºC Liquid Temperature: 22.5ºC											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
190	836.6	Left	Touch	Fig.1	32.76	33	0.17	**0.18**	0.224	**0.24**	-0.11

Table 14.2-2: SAR Values (GSM 850 MHz Band - Body)

Ambient Temperature: 22.9 ºC Liquid Temperature: 22.5ºC											
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
128	824.2	GPRS (2)	Rear	Fig.2	29.68	30	0.306	**0.33**	0.403	**0.43**	0.14

Note: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-3: SAR Values (GSM 1900 MHz Band - Head)

Ambient Temperature: 22.9 ºC Liquid Temperature: 22.5ºC											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
810	1909.8	Left	Touch	Fig.3	30.12	30.5	0.094	**0.10**	0.146	**0.16**	0.06

©Copyright. All rights reserved by CTTL.

Table 14.2-4: SAR Values (GSM 1900 MHz Band - Body)

Ambient Temperature: 22.9 ℃ Liquid Temperature: 22.5℃											
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
512	1850.2	GPRS (4)	Rear	Fig.4	19.88	21	0.087	**0.11**	0.217	**0.28**	-0.01

Note1: The distance between the EUT and the phantom bottom is 10mm

Table 14.2-5: SAR Values (WCDMA 850 MHz Band - Head)

Ambient Temperature: 22.9 ℃ Liquid Temperature: 22.5℃											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
4183	836.6	Left	Touch	Fig.5	24.39	25	0.247	**0.28**	0.325	**0.37**	0.15

Table 14.2-6: SAR Values (WCDMA 850 MHz Band - Body)

Ambient Temperature: 22.9 ℃ Liquid Temperature: 22.5℃										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
4233	846.6	Rear	Fig.6	24.37	25	0.372	**0.43**	0.485	**0.56**	0.09

Note: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-7: SAR Values (LTE Band5 - Head)

Ambient Temperature: 22.9℃ Liquid Temperature: 22.5℃												
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
20525	836.5	1RB-High	Left	Touch	Fig.7	24.45	24.5	0.187	**0.19**	0.246	**0.25**	0.05

Note1: The LTE mode is QPSK_10MHz.

Table 14.2-8: SAR Values (LTE Band5 - Body)

Ambient Temperature: 22.9 ℃ Liquid Temperature: 22.5℃											
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
20525	836.5	1RB-High	Rear	Fig.8	24.45	24.5	0.357	**0.36**	0.465	**0.47**	0.13

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

©Copyright. All rights reserved by CTTL.

Table 14.2-9: SAR Values (LTE Band7 - Head)

Ambient Temperature: 22.9 ºC Liquid Temperature: 22.5ºC												
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
21100	2535	1RB-High	Right	Touch	Fig.9	24.51	25	0.109	**0.12**	0.205	**0.23**	0.05

Note1: The LTE mode is QPSK_20MHz.

Table 14.2-10: SAR Values (LTE Band7 - Body)

Ambient Temperature: 22.9 ºC Liquid Temperature: 22.5ºC											
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
21350	2560	1RB-Mid	Rear	Fig.10	19.99	20.5	0.266	**0.30**	0.609	**0.68**	-0.04

Note1: The distance between the EUT and the phantom bottom is 10mm

Note2: The LTE mode is QPSK_20MHz.

©Copyright. All rights reserved by CTTL.

14.3 WLAN Evaluation for 2.4G

According to the KDB248227 D01, SAR is measured for 2.4GHz 802.11b DSSS using the initial test position procedure.

Head Evaluation

Table 14.3-1: SAR Values (WLAN - Head)– 802.11b (Fast SAR)

Ambient Temperature: 22.9 ℃ Liquid Temperature: 22.5℃											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g)(W/kg)	Power Drift (dB)
MHz	Ch.										
2412	1	Left	Touch	/	18.16	18.5	0.218	**0.24**	0.409	**0.44**	-0.06
2412	1	Left	Tilt	/	18.16	18.5	0.225	**0.24**	0.397	**0.43**	-0.02
2412	1	Right	Touch	/	18.16	18.5	0.111	**0.12**	0.188	**0.20**	0.06
2412	1	Right	Tilt	/	18.16	18.5	0.103	**0.11**	0.179	**0.19**	-0.18

As shown above table, the initial test position for head is “Left Touch”. So the head SAR of WLAN is presented as below:

Table 14.3-2: SAR Values (WLAN - Head)– 802.11b (Full SAR)

Ambient Temperature: 22.9 ℃ Liquid Temperature: 22.5℃											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g)(W/kg)	Power Drift (dB)
MHz	Ch.										
2412	1	Left	Touch	Fig.11	18.16	18.5	0.218	**0.24**	0.423	**0.46**	-0.06
Note1: When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest estimated 1-g SAR conditions determined by area scans, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg. Note2: For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.										

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. The scaled reported SAR is presented as below.

Table 14.3-3: SAR Values (WLAN - Head) – 802.11b (Scaled Reported SAR)

Ambient Temperature: 22.9 ℃ Liquid Temperature: 22.5℃							
Frequency		Side	Test Position	Actual duty factor	maximum duty factor	Reported SAR (1g)(W/kg)	Scaled reported SAR (1g)(W/kg)
MHz	Ch.						
2412	1	Left	Touch	100%	100%	**0.46**	**0.46**

SAR is not required for OFDM because the 802.11b adjusted SAR ≤ 1.2 W/kg.

©Copyright. All rights reserved by CTTL.

Body Evaluation

Table 14.3-4: SAR Values (WLAN - Body)– 802.11b (Fast SAR)

Ambient Temperature: 22.9 ℃ Liquid Temperature: 22.5℃										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g)(W/kg)	Power Drift (dB)
MHz	Ch.									
2412	1	Front	/	18.16	18.5	0.054	**0.06**	0.101	**0.11**	0.10
2412	1	Rear	/	18.16	18.5	0.088	**0.10**	0.181	**0.20**	0.01
2412	1	Right	/	18.16	18.5	0.065	**0.07**	0.135	**0.15**	-0.11
2412	1	Top	/	18.16	18.5	0.056	**0.06**	0.112	**0.12**	0.04

As shown above table, the initial test position for body is “Rear”. So the body SAR of WLAN is presented as below:

Table 14.3-5: SAR Values (WLAN - Body)– 802.11b (Full SAR)

Ambient Temperature: 22.9 ℃ Liquid Temperature: 22.5℃										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g)(W/kg)	Power Drift (dB)
MHz	Ch.									
2412	1	Rear	Fig.12	18.16	18.5	0.072	**0.08**	0.179	**0.19**	0.01
Note1: When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest estimated 1-g SAR conditions determined by area scans, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg. Note2: For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.										

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. The scaled reported SAR is presented as below.

Table 14.3-6: SAR Values (WLAN - Body) – 802.11b (Scaled Reported SAR)

Ambient Temperature: 22.9 ℃ Liquid Temperature: 22.5℃						
Frequency		Test Position	Actual duty factor	maximum duty factor	Reported SAR (1g)(W/kg)	Scaled reported SAR (1g)(W/kg)
MHz	Ch.					
2412	1	Rear	100%	100%	**0.19**	**0.19**

SAR is not required for OFDM because the 802.11b adjusted SAR ≤ 1.2 W/kg.

©Copyright. All rights reserved by CTTL.



Picture 14.1 Duty factor plot

©Copyright. All rights reserved by CTTL.

15 Measurement Uncertainty

15.1 Measurement Uncertainty for Normal SAR Tests (300MHz~3GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	6.0	N	1	1	1	6.0	6.0	∞
2	Isotropy	B	4.7	R	√3	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	1.0	R	√3	1	1	0.6	0.6	∞
4	Linearity	B	4.7	R	√3	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	N	1	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	√3	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	√3	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	√3	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	√3	1	1	0	0	∞
10	RFambient conditions-reflection	B	0	R	√3	1	1	0	0	∞
11	Probe positioned mech. restrictions	B	0.4	R	√3	1	1	0.2	0.2	∞
12	Probe positioning with respect to phantom shell	B	2.9	R	√3	1	1	1.7	1.7	∞
13	Post-processing	B	1.0	R	√3	1	1	0.6	0.6	∞
Test sample related										
14	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
15	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
16	Drift of output power	B	5.0	R	√3	1	1	2.9	2.9	∞
Phantom and set-up										
17	Phantom uncertainty	B	4.0	R	√3	1	1	2.3	2.3	∞
18	Liquid conductivity (target)	B	5.0	R	√3	0.64	0.43	1.8	1.2	∞
19	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
20	Liquid permittivity (target)	B	5.0	R	√3	0.6	0.49	1.7	1.4	∞
21	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521

©Copyright. All rights reserved by CTTL.

Combined standard uncertainty	$u_c^{'} = \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$					9.55	9.43	257
Expanded uncertainty (confidence interval of 95 %)	$u_e = 2u_c$					19.1	18.9	

15.2 Measurement Uncertainty for Normal SAR Tests (3~6GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	6.55	N	1	1	1	6.55	6.55	∞
2	Isotropy	B	4.7	R	√3	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	2.0	R	√3	1	1	1.2	1.2	∞
4	Linearity	B	4.7	R	√3	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	√3	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	√3	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	√3	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	√3	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	√3	1	1	0	0	∞
10	RFambient conditions-reflection	B	0	R	√3	1	1	0	0	∞
11	Probe positioned mech. restrictions	B	0.8	R	√3	1	1	0.5	0.5	∞
12	Probe positioning with respect to phantom shell	B	6.7	R	√3	1	1	3.9	3.9	∞
13	Post-processing	B	4.0	R	√3	1	1	2.3	2.3	∞
Test sample related										
14	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
15	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
16	Drift of output power	B	5.0	R	√3	1	1	2.9	2.9	∞
Phantom and set-up										
17	Phantom uncertainty	B	4.0	R	√3	1	1	2.3	2.3	∞
18	Liquid conductivity (target)	B	5.0	R	√3	0.64	0.43	1.8	1.2	∞
19	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
20	Liquid permittivity (target)	B	5.0	R	√3	0.6	0.49	1.7	1.4	∞

©Copyright. All rights reserved by CTTL.

21	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c^{'} = \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$						10.7	10.6	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						21.4	21.1	

15.3 Measurement Uncertainty for Fast SAR Tests (300MHz~3GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	6.0	N	1	1	1	6.0	6.0	∞
2	Isotropy	B	4.7	R	√3	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	1.0	R	√3	1	1	0.6	0.6	∞
4	Linearity	B	4.7	R	√3	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	√3	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	√3	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	√3	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	√3	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	√3	1	1	0	0	∞
10	RFambient conditions-reflection	B	0	R	√3	1	1	0	0	∞
11	Probe positioned mech. Restrictions	B	0.4	R	√3	1	1	0.2	0.2	∞
12	Probe positioning with respect to phantom shell	B	2.9	R	√3	1	1	1.7	1.7	∞
13	Post-processing	B	1.0	R	√3	1	1	0.6	0.6	∞
14	Fast SAR z-Approximation	B	7.0	R	√3	1	1	4.0	4.0	∞
Test sample related										
15	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
16	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
17	Drift of output power	B	5.0	R	√3	1	1	2.9	2.9	∞
Phantom and set-up										
18	Phantom uncertainty	B	4.0	R	√3	1	1	2.3	2.3	∞
19	Liquid conductivity (target)	B	5.0	R	√3	0.64	0.43	1.8	1.2	∞

©Copyright. All rights reserved by CTTL.

20	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
21	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
22	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c^{'} = \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$						10.4	10.3	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						20.8	20.6	

15.4 Measurement Uncertainty for Fast SAR Tests (3~6GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	6.55	N	1	1	1	6.55	6.55	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	2.0	R	$\sqrt{3}$	1	1	1.2	1.2	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RFambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. Restrictions	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
12	Probe positioning with respect to phantom shell	B	6.7	R	$\sqrt{3}$	1	1	3.9	3.9	∞
13	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
14	Fast SAR z-Approximation	B	14.0	R	$\sqrt{3}$	1	1	8.1	8.1	∞
Test sample related										
15	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
16	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5

©Copyright. All rights reserved by CTTL.

17	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up										
18	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
19	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
20	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
21	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
22	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c^{'} = \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$						13.5	13.4	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						27.0	26.8	

16 MAIN TEST INSTRUMENTS

Table 16.1: List of Main Instruments

No.	Name	Type	Serial Number	Calibration Date	Valid Period
01	Network analyzer	E5071C	MY46110673	January 24, 2019	One year
02	Power meter	NRP2	106277	September 4, 2019	One year
03	Power sensor	NRP8S	104291		
04	Signal Generator	E4438C	MY49070393	January 4, 2019	One Year
05	Amplifier	60S1G4	0331848	No Calibration Requested	
06	BTS	E5515C	MY50263375	January 17, 2019	One year
07	BTS	CMW500	159890	January 3, 2019	One year
08	E-field Probe	SPEAG EX3DV4	3617	January 31, 2019	One year
09	DAE	SPEAG DAE4	771	January 11,2019	One year
10	Dipole Validation Kit	SPEAG D835V2	4d069	July 18, 2019	One year
11	Dipole Validation Kit	SPEAG D1900V2	5d101	July 17, 2019	One year
12	Dipole Validation Kit	SPEAG D2450V2	853	July 17, 2019	One year
13	Dipole Validation Kit	SPEAG D2600V2	1012	July 17, 2019	One year

END OF REPORT BODY

©Copyright. All rights reserved by CTTL.

ANNEX A Graph Results

GSM850_CH190 Left Cheek
Date: 12/11/2019
Electronics: DAE4 Sn771
Medium: head 835 MHz
Medium parameters used: f = 836.6 MHz; σ = 0.909 mho/m; εr = 41.63; ρ = 1000 kg/m^3
Ambient Temperature: 22.9ºC, Liquid Temperature: 22.5ºC
Communication System: GSM850 836.6 MHz Duty Cycle: 1:8.3
Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.261 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 4.133 V/m; Power Drift = -0.11 dB
Peak SAR (extrapolated) = 0.283 W/kg
SAR(1 g) = 0.224 W/kg; SAR(10 g) = 0.17 W/kg
Maximum value of SAR (measured) = 0.256 W/kg



Fig A.1

©Copyright. All rights reserved by CTTL.

GSM850_CH128 Rear 10mm
Date: 12/11/2019
Electronics: DAE4 Sn771
Medium: body 835 MHz
Medium parameters used: f = 824.2 MHz; σ = 0.897 mho/m; εr = 41.64; ρ = 1000 kg/m^3
Ambient Temperature: 22.9ºC, Liquid Temperature: 22.5ºC
Communication System: GSM850 824.2 MHz Duty Cycle: 1:4
Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.431 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 19.48 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 0.532 W/kg
SAR(1 g) = 0.403 W/kg; SAR(10 g) = 0.306 W/kg
Maximum value of SAR (measured) = 0.487 W/kg



Fig A.2

©Copyright. All rights reserved by CTTL.

PCS1900_CH810 Left Cheek
Date: 12/12/2019
Electronics: DAE4 Sn771
Medium: head 1900 MHz
Medium parameters used: f = 1909.8 MHz; σ = 1.384 mho/m; εr = 39.94; ρ = 1000 kg/m^3
Ambient Temperature: 22.9ºC, Liquid Temperature: 22.5ºC
Communication System: PCS1900 1909.8 MHz Duty Cycle: 1:8.3
Probe: EX3DV4 – SN3617 ConvF(8.14,8.14,8.14)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.204 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 1.752 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 0.229 W/kg
SAR(1 g) = 0.146 W/kg; SAR(10 g) = 0.094 W/kg
Maximum value of SAR (measured) = 0.191 W/kg



Fig A.3

©Copyright. All rights reserved by CTTL.

PCS1900_CH512 Rear 10mm
Date: 12/12/2019
Electronics: DAE4 Sn771
Medium: body 1900 MHz
Medium parameters used: f = 1850.2 MHz; σ = 1.328 mho/m; εr = 40.01; ρ = 1000 kg/m^3
Ambient Temperature: 22.9ºC, Liquid Temperature: 22.5ºC
Communication System: PCS1900 1850.2 MHz Duty Cycle: 1:2
Probe: EX3DV4 – SN3617 ConvF(8.14,8.14,8.14)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.275 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 5.737 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 0.538 W/kg
SAR(1 g) = 0.217 W/kg; SAR(10 g) = 0.087 W/kg
Maximum value of SAR (measured) = 0.324 W/kg



Fig A.4

©Copyright. All rights reserved by CTTL.

WCDMA850-BV_CH4183 Left Cheek
Date: 12/11/2019
Electronics: DAE4 Sn771
Medium: head 835 MHz
Medium parameters used: f = 836.6 MHz; σ = 0.909 mho/m; εr = 41.63; ρ = 1000 kg/m^3
Ambient Temperature: 22.9ºC, Liquid Temperature: 22.5ºC
Communication System: WCDMA850-BV 836.6 MHz Duty Cycle: 1:1
Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.382 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 5.251 V/m; Power Drift = 0.15 dB
Peak SAR (extrapolated) = 0.407 W/kg
SAR(1 g) = 0.325 W/kg; SAR(10 g) = 0.247 W/kg
Maximum value of SAR (measured) = 0.367 W/kg



Fig A.5

©Copyright. All rights reserved by CTTL.

WCDMA850-BV_CH4233 Rear 10mm
Date: 12/11/2019
Electronics: DAE4 Sn771
Medium: body 835 MHz
Medium parameters used: f = 846.6 MHz; σ = 0.918 mho/m; εr = 41.62; ρ = 1000 kg/m^3
Ambient Temperature: 22.9ºC, Liquid Temperature: 22.5ºC
Communication System: WCDMA850-BV 846.6 MHz Duty Cycle: 1:1
Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.544 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 22.02 V/m; Power Drift = 0.09 dB
Peak SAR (extrapolated) = 0.636 W/kg
SAR(1 g) = 0.485 W/kg; SAR(10 g) = 0.372 W/kg
Maximum value of SAR (measured) = 0.583 W/kg



Fig A.6

©Copyright. All rights reserved by CTTL.

LTE850-FDD5_CH20525 Left Cheek
Date: 12/11/2019
Electronics: DAE4 Sn771
Medium: head 835 MHz
Medium parameters used: f = 836.5 MHz; σ = 0.908 mho/m; εr = 41.63; ρ = 1000 kg/m^3
Ambient Temperature: 22.9ºC, Liquid Temperature: 22.5ºC
Communication System: LTE850-FDD5 836.5 MHz Duty Cycle: 1:1
Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.284 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 4.217 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 0.310 W/kg
SAR(1 g) = 0.246 W/kg; SAR(10 g) = 0.187 W/kg
Maximum value of SAR (measured) = 0.280 W/kg



Fig A.7

©Copyright. All rights reserved by CTTL.

LTE850-FDD5_CH20525 Rear 10mm
Date: 12/11/2019
Electronics: DAE4 Sn771
Medium: body 835 MHz
Medium parameters used: f = 836.5 MHz; σ = 0.908 mho/m; εr = 41.63; ρ = 1000 kg/m^3
Ambient Temperature: 22.9ºC, Liquid Temperature: 22.5ºC
Communication System: LTE850-FDD5 836.5 MHz Duty Cycle: 1:1
Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.532 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 21.34 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 0.615 W/kg
SAR(1 g) = 0.465 W/kg; SAR(10 g) = 0.357 W/kg
Maximum value of SAR (measured) = 0.562 W/kg



Fig A.8

©Copyright. All rights reserved by CTTL.

LTE2500-FDD7_CH21100 Right Cheek
Date: 12/14/2019
Electronics: DAE4 Sn771
Medium: head 2600 MHz
Medium parameters used: f = 2535 MHz; σ = 1.873 mho/m; εr = 38.44; ρ = 1000 kg/m^3
Ambient Temperature: 22.9°C, Liquid Temperature: 22.5°C
Communication System: LTE2500-FDD7 2535 MHz Duty Cycle: 1:1
Probe: EX3DV4 – SN3617 ConvF(7.19,7.19,7.19)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.304 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.438 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 0.370 W/kg
SAR(1 g) = 0.205 W/kg; SAR(10 g) = 0.109 W/kg
Maximum value of SAR (measured) = 0.278 W/kg



Fig A.9

©Copyright. All rights reserved by CTTL.

LTE2500-FDD7_CH21350 Rear 10mm
Date: 12/14/2019
Electronics: DAE4 Sn771
Medium: body 2600 MHz
Medium parameters used: f = 2560 MHz; σ = 1.897 mho/m; εr = 38.41; ρ = 1000 kg/m^3
Ambient Temperature: 22.9°C, Liquid Temperature: 22.5°C
Communication System: LTE2500-FDD7 2560 MHz Duty Cycle: 1:1
Probe: EX3DV4 – SN3617 ConvF(7.19,7.19,7.19)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.857 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 3.926 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 1.26 W/kg
SAR(1 g) = 0.609 W/kg; SAR(10 g) = 0.266 W/kg
Maximum value of SAR (measured) = 0.958 W/kg



Fig A.10

©Copyright. All rights reserved by CTTL.

WLAN2450_CH1 Left Cheek
Date: 12/13/2019
Electronics: DAE4 Sn771
Medium: head 2450 MHz
Medium parameters used: f = 2412 MHz; σ = 1.769 mho/m; εr = 38.63; ρ = 1000 kg/m^3
Ambient Temperature: 22.9°C, Liquid Temperature: 22.5°C
Communication System: WLAN2450 2412 MHz Duty Cycle: 1:1
Probe: EX3DV4 – SN3617 ConvF(7.62,7.62,7.62)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.635 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 9.057 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 0.830 W/kg
SAR(1 g) = 0.423 W/kg; SAR(10 g) = 0.218 W/kg
Maximum value of SAR (measured) = 0.665 W/kg



Fig A.11

©Copyright. All rights reserved by CTTL.

WLAN2450_CH1 Rear 10mm
Date: 12/13/2019
Electronics: DAE4 Sn771
Medium: body 2450 MHz
Medium parameters used: f = 2412 MHz; σ = 1.769 mho/m; εr = 38.63; ρ = 1000 kg/m^3
Ambient Temperature: 22.9ºC, Liquid Temperature: 22.5ºC
Communication System: WLAN2450 2412 MHz Duty Cycle: 1:1
Probe: EX3DV4 – SN3617 ConvF(7.62,7.62,7.62)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.282 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.789 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 0.657 W/kg
SAR(1 g) = 0.179 W/kg; SAR(10 g) = 0.072 W/kg
Maximum value of SAR (measured) = 0.291 W/kg



Fig A.12

©Copyright. All rights reserved by CTTL.



Fig. 1-1 Z-Scan at power reference point (GSM850)



Fig. 1-2 Z-Scan at power reference point (GSM850)



Fig. 1-3 Z-Scan at power reference point (PCS1900)

©Copyright. All rights reserved by CTTL.



Fig. 1-4 Z-Scan at power reference point (PCS1900)



Fig. 1-5 Z-Scan at power reference point (WCDMA850)



Fig. 1-6 Z-Scan at power reference point (WCDMA850)

©Copyright. All rights reserved by CTTL.



Fig. 1-7 Z-Scan at power reference point (LTE Band5)



Fig. 1-8 Z-Scan at power reference point (LTE Band5)



Fig. 1-9 Z-Scan at power reference point (LTE Band7)

©Copyright. All rights reserved by CTTL.



Fig. 1-10 Z-Scan at power reference point (LTE Band7)



Fig. 1-11 Z-Scan at power reference point (2450 MHz)



Fig. 1-12 Z-Scan at power reference point (2450 MHz)

©Copyright. All rights reserved by CTTL.

ANNEX B System Verification Results

835 MHz

Date: 12/11/2019
Electronics: DAE4 Sn771
Medium: Head 835 MHz
Medium parameters used: f = 835 MHz; σ =0.907 mho/m; ε_r = 41.63; ρ = 1000 kg/m^3
Ambient Temperature: 22.9ºC Liquid Temperature: 22.5ºC
Communication System: CW Frequency: 835 MHz Duty Cycle: 1:1
Probe: EX3DV4 – SN3617 ConvF(9.75,9.75,9.75)

System Validation /Area Scan (81x191x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Reference Value = 62.98 V/m; Power Drift = -0.1
Fast SAR: SAR(1 g) = 2.38 W/kg; SAR(10 g) = 1.6 W/kg
Maximum value of SAR (interpolated) = 3.1 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value =62.98 V/m; Power Drift = -0.1 dB
Peak SAR (extrapolated) = 3.63 W/kg
SAR(1 g) = 2.41 W/kg; SAR(10 g) = 1.6 W/kg
Maximum value of SAR (measured) = 3.28 W/kg



0 dB = 3.28 W/kg = 5.16 dB W/kg

Fig.B.1 validation 835 MHz 250mW

©Copyright. All rights reserved by CTTL.

1900 MHz

Date: 12/12/2019
Electronics: DAE4 Sn771
Medium: Head 1900 MHz
Medium parameters used: f = 1900 MHz; σ =1.375 mho/m; ε_r = 39.95; ρ = 1000 kg/m^3
Ambient Temperature: 22.9ºC Liquid Temperature: 22.5ºC
Communication System: CW Frequency: 1900 MHz Duty Cycle: 1:1
Probe: EX3DV4 – SN3617 ConvF(8.14,8.14,8.14)

System Validation /Area Scan (81x191x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Reference Value = 108.93 V/m; Power Drift = -0.05
Fast SAR: SAR(1 g) = 9.96 W/kg; SAR(10 g) = 5.29 W/kg
Maximum value of SAR (interpolated) = 15.3 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value =108.93 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 17.83 W/kg
SAR(1 g) = 10 W/kg; SAR(10 g) = 5.15 W/kg
Maximum value of SAR (measured) = 14.67 W/kg



0 dB = 14.67 W/kg = 11.66 dB W/kg

Fig.B.2 validation 1900 MHz 250mW

©Copyright. All rights reserved by CTTL.

2450 MHz

Date: 12/13/2019
Electronics: DAE4 Sn771
Medium: Head 2450 MHz
Medium parameters used: f = 2450 MHz; σ =1.805 mho/m; ε_r = 38.58; ρ = 1000 kg/m^3
Ambient Temperature: 22.9ºC Liquid Temperature: 22.5ºC
Communication System: CW Frequency: 2450 MHz Duty Cycle: 1:1
Probe: EX3DV4 – SN3617 ConvF(7.62,7.62,7.62)

System Validation /Area Scan (81x191x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Reference Value = 114.6 V/m; Power Drift = -0.04
Fast SAR: SAR(1 g) = 13.05 W/kg; SAR(10 g) = 6 W/kg
Maximum value of SAR (interpolated) = 22.02 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value =114.6 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 25.5 W/kg
SAR(1 g) = 12.73 W/kg; SAR(10 g) = 6.03 W/kg
Maximum value of SAR (measured) = 21.68 W/kg



0 dB = 21.68 W/kg = 13.36 dB W/kg

Fig.B.3 validation 2450 MHz 250mW

©Copyright. All rights reserved by CTTL.

2600 MHz

Date: 12/14/2019
Electronics: DAE4 Sn771
Medium: Head 2600 MHz
Medium parameters used: f = 2600 MHz; σ =1.935 mho/m; ε_r = 38.36; ρ = 1000 kg/m^3
Ambient Temperature: 22.9ºC Liquid Temperature: 22.5ºC
Communication System: CW Frequency: 2600 MHz Duty Cycle: 1:1
Probe: EX3DV4 – SN3617 ConvF(7.19,7.19,7.19)

System Validation /Area Scan (81x191x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Reference Value = 120.52 V/m; Power Drift = 0.06
Fast SAR: SAR(1 g) = 14.02 W/kg; SAR(10 g) = 6.26 W/kg
Maximum value of SAR (interpolated) = 25.21 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value =120.52 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 28.56 W/kg
SAR(1 g) = 13.98 W/kg; SAR(10 g) = 6.38 W/kg
Maximum value of SAR (measured) = 23.54 W/kg



0 dB = 23.54 W/kg = 13.72 dB W/kg

Fig.B.4 validation 2600 MHz 250mW

©Copyright. All rights reserved by CTTL.

The SAR system verification must be required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR.

Table B.1 Comparison between area scan and zoom scan for system verification

Date	Band	Position	Area scan (1g)	Zoom scan (1g)	Drift (%)
2019-12-11	835	Head	2.38	2.41	-1.24
2019-12-12	1900	Head	9.96	10	-0.40
2019-12-13	2450	Head	13.05	12.73	2.51
2019-12-14	2600	Head	14.02	13.98	0.29

©Copyright. All rights reserved by CTTL.

ANNEX C SAR Measurement Setup

C.1 Measurement Set-up

The Dasy4 or DASY5 system for performing compliance tests is illustrated above graphically. This system consists of the following items:



Picture C.1SAR Lab Test Measurement Set-up

- A standard high precision 6-axis robot (StäubliTX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY4 or DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as
- warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

©Copyright. All rights reserved by CTTL.

C.2 Dasy4 or DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 or DASY5 software reads the reflection durning a software approach and looks for the maximum using 2nd ord curve fitting. The approach is stopped at reaching the maximum.

Probe Specifications:

Model: ES3DV3, EX3DV4
Frequency 10MHz — 6.0GHz(EX3DV4)
Range: 10MHz — 4GHz(ES3DV3)
Calibration: In head and body simulating tissue at Frequencies from 835 up to 5800MHz
Linearity: ± 0.2 dB(30 MHz to 6 GHz) for EX3DV4
± 0.2 dB(30 MHz to 4 GHz) for ES3DV3
DynamicRange: 10 mW/kg — 100W/kg
Probe Length: 330 mm
Probe Tip Length: 20 mm
Body Diameter: 12 mm
Tip Diameter: 2.5 mm (3.9 mm for ES3DV3)
Tip-Center: 1 mm (2.0mm for ES3DV3)
Application: SAR Dosimetry Testing
Compliance tests ofmobile phones
Dosimetry in strong gradient fields

Picture C.2Near-field Probe

Picture C.3E-field Probe

C.3 E-field Probe Calibration

Each E-Probe/Probe Amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm^2) using an RF Signal generator, TEM cell, and RF Power Meter.

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and inn a waveguide or

©Copyright. All rights reserved by CTTL.

other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm^2.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C\frac{\Delta T}{\Delta t}$$

Where:

Δt = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

ΔT = Temperature increase due to RF exposure.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

σ = Simulated tissue conductivity,

ρ = Tissue density (kg/m^3).

C.4 Other Test Equipment

C.4.1 Data Acquisition Electronics(DAE)

The data acquisition electronics consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

PictureC.4: DAE

©Copyright. All rights reserved by CTTL.

C.4.2 Robot

The SPEAG DASY system uses the high precision robots (DASY4: RX90XL; DASY5: RX160L) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchron motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

Picture C.5DASY 4

Picture C.6DASY 5

C.4.3 Measurement Server

The Measurement server is based on a PC/104 CPU broad with CPU (dasy4: 166 MHz, Intel Pentium; DASY5: 400 MHz, Intel Celeron), chipdisk (DASY4: 32 MB; DASY5: 128MB), RAM (DASY4: 64 MB, DASY5: 128MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O broad, which is directly connected to the PC/104 bus of the CPU broad.

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.

©Copyright. All rights reserved by CTTL.

Picture C.7 Server for DASY 4

Picture C.8 Server for DASY 5

C.4.4 Device Holder for Phantom

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5mm distance, a positioning uncertainty of ±0.5mm would produce a SAR uncertainty of ±20%. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity ε=3 and loss tangent δ =0.02. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

<Laptop Extension Kit>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin-SAM and ELI phantoms.

Picture C.9-1: Device Holder



Picture C.9-2: Laptop Extension Kit

C.4.5 Phantom

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a table. The shape of the shell is based on data from an anatomical study designed to

Represent the 90th percentile of the population. The phantom enables the dissymmetric evaluation

©Copyright. All rights reserved by CTTL.

of SAR for both left and right handed handset usage, as well as body-worn usage using the flat phantom region. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. The shell phantom has a 2mm shell thickness (except the ear region where shell thickness increases to 6 mm).

Shell Thickness: 2±0. 2 mm
Filling Volume: Approx. 25 liters
Dimensions: 810 x l000 x 500 mm (H x L x W)
Available: Special

Picture C.10: SAM Twin Phantom

©Copyright. All rights reserved by CTTL.

ANNEX D Position of the wireless device in relation to the phantom

D.1 General considerations

This standard specifies two handset test positions against the head phantom – the “cheek” position and the “tilt” position.





W_t	Width of the handset at the level of the acoustic
W_b	Width of the bottom of the handset
A	Midpoint of the width W_t of the handset at the level of the acoustic output
B	Midpoint of the width W_b of the bottom of the handset

Picture D.1-a Typical “fixed” case handset **Picture D.1-b Typical “clam-shell” case handset**



Picture D.2 Cheek position of the wireless device on the left side of SAM

©Copyright. All rights reserved by CTTL.



Picture D.3 Tilt position of the wireless device on the left side of SAM

D.2 Body-worn device

A typical example of a body-worn device is a mobile phone, wireless enabled PDA or other battery operated wireless device with the ability to transmit while mounted on a person's body using a carry accessory approved by the wireless device manufacturer.



Picture D.4Test positions for body-worn devices

D.3 Desktop device

A typical example of a desktop device is a wireless enabled desktop computer placed on a table or desk when used.

The DUT shall be positioned at the distance and in the orientation to the phantom that corresponds to the intended use as specified by the manufacturer in the user instructions. For devices that employ an external antenna with variable positions, tests shall be performed for all antenna positions specified. Picture8.5 show positions for desktop device SAR tests. If the intended use is not specified, the device shall be tested directly against the flat phantom.

©Copyright. All rights reserved by CTTL.



Picture D.5 Test positions for desktop devices

D.4 DUT Setup Photos

Picture D.6

©Copyright. All rights reserved by CTTL.

ANNEX E Equivalent Media Recipes

The liquid used for the frequency range of 800-3000 MHz consisted of water, sugar, salt, preventol, glycol monobutyl and Cellulose. The liquid has been previously proven to be suited for worst-case. The Table E.1 shows the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the IEEE 1528 and IEC 62209.

TableE.1: Composition of the Tissue Equivalent Matter

Frequency (MHz)	835Head	835Body	1900 Head	1900 Body	2450 Head	2450 Body	5800 Head	5800 Body
Ingredients (% by weight)								
Water	41.45	52.5	55.242	69.91	58.79	72.60	65.53	65.53
Sugar	56.0	45.0	\	\	\	\	\	\
Salt	1.45	1.4	0.306	0.13	0.06	0.18	\	\
Preventol	0.1	0.1	\	\	\	\	\	\
Cellulose	1.0	1.0	\	\	\	\	\	\
Glycol Monobutyl	\	\	44.452	29.96	41.15	27.22	\	\
Diethylenglycol monohexylether	\	\	\	\	\	\	17.24	17.24
Triton X-100	\	\	\	\	\	\	17.24	17.24
Dielectric Parameters Target Value	ε=41.5 σ=0.90	ε=55.2 σ=0.97	ε=40.0 σ=1.40	ε=53.3 σ=1.52	ε=39.2 σ=1.80	ε=52.7 σ=1.95	ε=35.3 σ=5.27	ε=48.2 σ=6.00

Note: There are a little adjustment respectively for 750, 1750, 2600, 5200, 5300 and 5600 based on the recipe of closest frequency in table E.1.

©Copyright. All rights reserved by CTTL.

ANNEX F System Validation

The SAR system must be validated against its performance specifications before it is deployed. When SAR probes, system components or software are changed, upgraded or recalibrated, these must be validated with the SAR system(s) that operates with such components.

Table F.1: System Validation for 3617

Probe SN.	Liquid name	Validation date	Frequency point	Status (OK or Not)
3617	Head 750MHz	Feb.14,2019	750 MHz	OK
3617	Head 850MHz	Feb.14,2019	835 MHz	OK
3617	Head 900MHz	Feb.14,2019	900 MHz	OK
3617	Head 1750MHz	Feb.14,2019	1750 MHz	OK
3617	Head 1810MHz	Feb.14,2019	1810 MHz	OK
3617	Head 1900MHz	Feb.15,2019	1900 MHz	OK
3617	Head 2000MHz	Feb.15,2019	2000 MHz	OK
3617	Head 2100MHz	Feb.15,2019	2100 MHz	OK
3617	Head 2300MHz	Feb.15,2019	2300 MHz	OK
3617	Head 2450MHz	Feb.15,2019	2450 MHz	OK
3617	Head 2600MHz	Feb.16,2019	2600 MHz	OK
3617	Head 3500MHz	Feb.16,2019	3500 MHz	OK
3617	Head 3700MHz	Feb.16,2019	3700 MHz	OK
3617	Head 5200MHz	Feb.16,2019	5250 MHz	OK
3617	Head 5500MHz	Feb.16,2019	5600 MHz	OK
3617	Head 5800MHz	Feb.16,2019	5800 MHz	OK
3617	Body 750MHz	Feb.16,2019	750 MHz	OK
3617	Body 850MHz	Feb.13,2019	835 MHz	OK
3617	Body 900MHz	Feb.13,2019	900 MHz	OK
3617	Body 1750MHz	Feb.13,2019	1750 MHz	OK
3617	Body 1810MHz	Feb.13,2019	1810 MHz	OK
3617	Body 1900MHz	Feb.13,2019	1900 MHz	OK
3617	Body 2000MHz	Feb.17,2019	2000 MHz	OK
3617	Body 2100MHz	Feb.17,2019	2100 MHz	OK
3617	Body 2300MHz	Feb.17,2019	2300 MHz	OK
3617	Body 2450MHz	Feb.17,2019	2450 MHz	OK
3617	Body 2600MHz	Feb.17,2019	2600 MHz	OK
3617	Body 3500MHz	Feb.12,2019	3500 MHz	OK
3617	Body 3700MHz	Feb.12,2019	3700 MHz	OK
3617	Body 5200MHz	Feb.12,2019	5250 MHz	OK
3617	Body 5500MHz	Feb.12,2019	5600 MHz	OK
3617	Body 5800MHz	Feb.12,2019	5800 MHz	OK

©Copyright. All rights reserved by CTTL.

ANNEX G Probe Calibration Certificate

Probe 3617 Calibration Certificate

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client CTTL (Auden) **Certificate No: EX3-3617_Jan19**

CALIBRATION CERTIFICATE

Object: EX3DV4 - SN:3617

Calibration procedure(s): QA CAL-01.v9, QA CAL-12.v9, QA CAL-14.v5, QA CAL-23.v5, QA CAL-25.v7
Calibration procedure for dosimetric E-field probes

Calibration date: January 31, 2019

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-18 (No. 217-02682)	Apr-19
DAE4	SN: 660	19-Dec-18 (No. DAE4-660_Dec18)	Dec-19
Reference Probe ES3DV2	SN: 3013	31-Dec-18 (No. ES3-3013_Dec18)	Dec-19
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-18)	In house check: Jun-20
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-18)	In house check: Oct-19

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: February 2, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

©Copyright. All rights reserved by CTTL.

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S C S Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary:

TSL	tissue simulating liquid
NORMx,y,z	sensitivity in free space
ConvF	sensitivity in TSL / NORMx,y,z
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., ϑ = 0 is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, ", "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- *NORMx,y,z:* Assessed for E-field polarization ϑ = 0 (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not affect the E^2-field uncertainty inside TSL (see below *ConvF*).
- *NORM(f)x,y,z = NORMx,y,z * frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- *DCPx,y,z:* DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- *PAR:* PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- *Ax,y,z; Bx,y,z; Cx,y,z; Dx,y,z; VRx,y,z*: *A, B, C, D* are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. *VR* is the maximum calibration range expressed in RMS voltage across the diode.
- *ConvF and Boundary Effect Parameters:* Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to *NORMx,y,z * ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- *Spherical isotropy (3D deviation from isotropy)*: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- *Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- *Connector Angle*: The angle is assessed using the information gained by determining the *NORMx* (no uncertainty required).

©Copyright. All rights reserved by CTTL.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3617

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu V/(V/m)^2$)[A]	0.35	0.21	0.32	± 10.1 %
DCP (mV)[B]	102.9	95.7	101.9	

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB√μV	C	D dB	VR mV	Max dev.	Max Unc[E] (k=2)
0	CW	X	0.00	0.00	1.00	0.00	151.4	± 3.0 %	± 4.7 %
		Y	0.00	0.00	1.00		154.7		
		Z	0.00	0.00	1.00		150.4		
10352-AAA	Pulse Waveform (200Hz, 10%)	X	5.31	73.42	14.63	10.00	60.0	± 2.6 %	± 9.6 %
		Y	2.86	65.84	11.90		60.0		
		Z	15.00	87.67	20.10		60.0		
10353-AAA	Pulse Waveform (200Hz, 20%)	X	10.57	81.97	16.23	6.99	80.0	± 1.7 %	± 9.6 %
		Y	2.03	65.40	10.27		80.0		
		Z	15.00	89.79	19.80		80.0		
10354-AAA	Pulse Waveform (200Hz, 40%)	X	15.00	86.62	16.29	3.98	95.0	± 1.1 %	± 9.6 %
		Y	0.82	61.50	6.58		95.0		
		Z	15.00	97.47	22.01		95.0		
10355-AAA	Pulse Waveform (200Hz, 60%)	X	15.00	89.99	16.64	2.22	120.0	± 1.2 %	± 9.6 %
		Y	0.40	60.00	3.98		120.0		
		Z	15.00	114.21	28.32		120.0		
10387-AAA	QPSK Waveform, 1 MHz	X	0.65	62.36	8.93	0.00	150.0	± 3.9 %	± 9.6 %
		Y	0.45	60.00	5.43		150.0		
		Z	0.90	65.62	10.92		150.0		
10388-AAA	QPSK Waveform, 10 MHz	X	2.42	70.53	17.16	0.00	150.0	± 1.8 %	± 9.6 %
		Y	1.99	67.57	15.24		150.0		
		Z	2.71	72.39	18.22		150.0		
10396-AAA	64-QAM Waveform, 100 kHz	X	3.78	75.33	20.79	3.01	150.0	± 0.7 %	± 9.6 %
		Y	3.23	71.01	18.81		150.0		
		Z	3.71	74.94	20.97		150.0		
10399-AAA	64-QAM Waveform, 40 MHz	X	3.58	68.11	16.37	0.00	150.0	± 4.0 %	± 9.6 %
		Y	3.32	66.75	15.59		150.0		
		Z	3.71	68.68	16.83		150.0		
10414-AAA	WLAN CCDF, 64-QAM, 40MHz	X	4.84	66.21	15.87	0.00	150.0	± 6.7 %	± 9.6 %
		Y	4.48	64.72	15.19		150.0		
		Z	4.93	66.43	16.14		150.0		

Note: For details on UID parameters see Appendix

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

[A] The uncertainties of Norm X,Y,Z do not affect the E^2-field uncertainty inside TSL (see Pages 5 and 6).
[B] Numerical linearization parameter: uncertainty not required.
[E] Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

©Copyright. All rights reserved by CTTL.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3617

Sensor Model Parameters

	C1 fF	C2 fF	α V^{-1}	T1 $ms.V^{-2}$	T2 $ms.V^{-1}$	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
X	38.8	281.02	33.92	10.58	0.71	4.99	1.88	0.20	1.01
Y	39.2	310.65	39.54	8.92	1.27	5.05	0.00	0.75	1.01
Z	40.7	300.62	35.22	10.39	0.59	5.05	1.28	0.33	1.01

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	14.6
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

©Copyright. All rights reserved by CTTL.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3617

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) [C]	Relative Permittivity [F]	Conductivity (S/m) [F]	ConvF X	ConvF Y	ConvF Z	Alpha [G]	Depth [G] (mm)	Unc (k=2)
64	54.2	0.75	12.45	12.45	12.45	0.00	1.00	± 13.3 %
150	52.3	0.76	11.88	11.88	11.88	0.00	1.00	± 13.3 %
300	45.3	0.87	11.40	11.40	11.40	0.08	1.20	± 13.3 %
450	43.5	0.87	10.54	10.54	10.54	0.14	1.40	± 13.3 %
750	41.9	0.89	10.03	10.03	10.03	0.63	0.84	± 12.0 %
835	41.5	0.90	9.75	9.75	9.75	0.39	0.95	± 12.0 %
900	41.5	0.97	9.66	9.66	9.66	0.47	0.85	± 12.0 %
1450	40.5	1.20	8.68	8.68	8.68	0.37	0.80	± 12.0 %
1640	40.2	1.31	8.48	8.48	8.48	0.38	0.80	± 12.0 %
1750	40.1	1.37	8.38	8.38	8.38	0.36	0.82	± 12.0 %
1810	40.0	1.40	8.11	8.11	8.11	0.32	0.84	± 12.0 %
1900	40.0	1.40	8.14	8.14	8.14	0.32	0.85	± 12.0 %
2000	40.0	1.40	8.13	8.13	8.13	0.28	0.84	± 12.0 %
2100	39.8	1.49	8.30	8.30	8.30	0.37	0.85	± 12.0 %
2300	39.5	1.67	7.74	7.74	7.74	0.32	0.84	± 12.0 %
2450	39.2	1.80	7.62	7.62	7.62	0.31	0.95	± 12.0 %
2600	39.0	1.96	7.19	7.19	7.19	0.43	0.85	± 12.0 %
3300	38.2	2.71	6.98	6.98	6.98	0.25	1.20	± 13.1 %
3500	37.9	2.91	6.97	6.97	6.97	0.50	1.20	± 13.1 %
3700	37.7	3.12	6.89	6.89	6.89	0.20	1.20	± 13.1 %
3900	37.5	3.32	6.88	6.88	6.88	0.20	1.20	± 13.1 %
4600	36.7	4.04	6.84	6.84	6.84	0.20	1.50	± 13.1 %
4950	36.3	4.40	5.60	5.60	5.60	0.40	1.80	± 13.1 %
5200	36.0	4.66	5.50	5.50	5.50	0.40	1.80	± 13.1 %
5250	35.9	4.71	5.39	5.39	5.39	0.40	1.80	± 13.1 %
5300	35.9	4.76	5.25	5.25	5.25	0.40	1.80	± 13.1 %
5500	35.6	4.96	5.18	5.18	5.18	0.40	1.80	± 13.1 %
5600	35.5	5.07	5.06	5.06	5.06	0.40	1.80	± 13.1 %
5750	35.4	5.22	5.07	5.07	5.07	0.40	1.80	± 13.1 %
5800	35.3	5.27	5.04	5.04	5.04	0.40	1.80	± 13.1 %

[C] Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-9 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.
[F] At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.
[G] Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

©Copyright. All rights reserved by CTTL.