


CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 41 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 42 of 76

5.6 Frequency Separation

Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement:

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable the band edge of the lowest and highest channels were measured. The peak detector is used and RBW is set to 100 kHz and VBW is set to 300 kHz on spectrum analyzer.

Limits:

Rule Part 15.247(a)(1) specifies that "Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. "

Note: The value of two-thirds of 20 dB bandwidth is always greater than 25 kHz.

Test Setup:



Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U=936$ Hz.

CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 43 of 76

Test Results:

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	Hop	1.003	≥0.940	PASS
2DH5	Ant1	Hop	1	≥0.820	PASS
3DH5	Ant1	Hop	1.316	≥1.250	PASS


Test Graphs



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 44 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 45 of 76

5.7 Time of Occupancy (Dwell Time)

Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement:

The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss. RBW is set to 1MHz and VBW is set to 3MHz on spectrum analyzer. The dwell time is calculated by:

Dwell time = time slot length * hop rate * 0.4s with:

The selected EUT Packet type uses a slot type of 5-Tx&1-Rx and a hopping rate of 1600(ch*hop/s) for all channels. So the final hopping rate for all channel is $1600/6=266.67(\text{ch*hop/s})$

Limits:

Rule Part15.247(a) specifies that " Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed."

Dwell time	$\leq 400\text{ms}$
------------	---------------------

Test Setup:



Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$.

Requirements	Uncertainty					
Dwell Time	DH5	U=0.70ms	2DH5	U=0.70ms	3DH5	U=0.70ms

CVC Testing Technology Co., Ltd.


Test Report No. FCC2022-0035-RF/R3

Page 46 of 76

Test Results:

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.37	320	0.118	≤0.4	PASS
DH3	Ant1	Hop	1.61	160	0.258	≤0.4	PASS
DH5	Ant1	Hop	2.85	106.67	0.304	≤0.4	PASS
2DH1	Ant1	Hop	0.38	320	0.122	≤0.4	PASS
2DH3	Ant1	Hop	1.62	160	0.259	≤0.4	PASS
2DH5	Ant1	Hop	2.86	106.67	0.305	≤0.4	PASS
3DH1	Ant1	Hop	0.38	320	0.122	≤0.4	PASS
3DH3	Ant1	Hop	1.62	160	0.259	≤0.4	PASS
3DH5	Ant1	Hop	2.86	106.67	0.305	≤0.4	PASS


Test Graphs:



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 47 of 76




CVC Testing Technology Co., Ltd.


Test Report No. FCC2022-0035-RF/R3

Page 48 of 76

2DH3_Ant1_Hop




2DH5_Ant1_Hop



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3


Page 49 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 50 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 51 of 76

5.8 Band Edge Measurement

Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement:

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable the band edge of the lowest and highest channels were measured. The peak detector is used and RBW is set to 100 kHz and VBW is set to 300 kHz on spectrum analyzer.

Limits:

Rule Part 15.247(d) specifies that "In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Setup:



Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 936 \text{ Hz}$, $2 \text{ GHz} - 3 \text{ GHz} = 1.407 \text{ dB}$.

CVC Testing Technology Co., Ltd.


Test Report No. FCC2022-0035-RF/R3

Page 52 of 76

Test Result:

TestMode	Antenna	ChName	Channel	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	2.92	-40.75	≤-17.08	PASS
		High	2480	4.28	-47.29	≤-15.72	PASS
		Low	Hop 2402	2.16	-48.96	≤-17.84	PASS
		High	Hop 2480	3.89	-47.72	≤-16.11	PASS
2DH5	Ant1	Low	2402	0.20	-44.25	≤-19.8	PASS
		High	2480	1.50	-47.98	≤-18.5	PASS
		Low	Hop 2402	-6.55	-49.8	≤-26.55	PASS
		High	Hop 2480	1.47	-48.1	≤-18.53	PASS
3DH5	Ant1	Low	2402	0.19	-44.32	≤-19.81	PASS
		High	2480	1.52	-48.12	≤-18.48	PASS
		Low	Hop 2402	-3.08	-49.41	≤-23.08	PASS
		High	Hop 2480	1.48	-48.15	≤-18.52	PASS


Test Graphs:



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 53 of 76




CVC Testing Technology Co., Ltd.


Test Report No. FCC2022-0035-RF/R3

Page 54 of 76

2DH5_Ant1_Low_2402



2DH5_Ant1_High_2480



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 55 of 76




CVC Testing Technology Co., Ltd.


Test Report No. FCC2022-0035-RF/R3

Page 56 of 76

3DH5_Ant1_Low_2402



3DH5_Ant1_High_2480



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 57 of 76



5.9 Number of hopping Frequency

Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement:

The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss. RBW is set to 100KHz and VBW is set to 300KHz on spectrum analyzer. Set EUT on Hopping on mode.

Limits:

Rule Part 15.247(a) (1) (iii) specifies that” Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.”

Limits	≥ 15 channels
--------	--------------------

Test Setup:



Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.75\text{dB}$.

CVC Testing Technology Co., Ltd.


Test Report No. FCC2022-0035-RF/R3

Page 59 of 76

Test Results:

TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS
3DH5	Ant1	Hop	79	≥15	PASS


Test Graphs:



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 60 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 61 of 76

5.10 Spurious RF Conducted Emissions

Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement:

The EUT was connected to the spectrum analyzer with a known loss. The spectrum analyzer scans from 30MHz to the 10th harmonic of the carrier. The peak detector is used. Set RBW to 100kHz and VBW to 300 kHz, Sweep is set to AUTO. The test is in transmitting mode.

Limits:

Rule Part 15.247(d) specifies that "In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power."

Test Setup:



Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-26GHz	1.407 dB

CVC Testing Technology Co., Ltd.


Test Report No. FCC2022-0035-RF/R3

Page 62 of 76

Test Results:

TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	Reference	2.97	2.97	---	PASS
			30~1000	2.97	-60.4	≤-17.03	PASS
			1000~26500	2.97	-44.03	≤-17.03	PASS
		2441	Reference	3.04	3.04	---	PASS
			30~1000	3.04	-60.47	≤-16.96	PASS
			1000~26500	3.04	-46.2	≤-16.96	PASS
		2480	Reference	4.28	4.28	---	PASS
			30~1000	4.28	-58.51	≤-15.72	PASS
			1000~26500	4.28	-47.79	≤-15.72	PASS
2DH5	Ant1	2402	Reference	0.24	0.24	---	PASS
			30~1000	0.24	-59.16	≤-19.76	PASS
			1000~26500	0.24	-42.5	≤-19.76	PASS
		2441	Reference	0.29	0.29	---	PASS
			30~1000	0.29	-60.24	≤-19.71	PASS
			1000~26500	0.29	-44.1	≤-19.71	PASS
		2480	Reference	1.56	1.56	---	PASS
			30~1000	1.56	-57.81	≤-18.44	PASS
			1000~26500	1.56	-41.58	≤-18.44	PASS
3DH5	Ant1	2402	Reference	0.24	0.24	---	PASS
			30~1000	0.24	-60.26	≤-19.76	PASS
			1000~26500	0.24	-44.82	≤-19.76	PASS
		2441	Reference	0.30	0.30	---	PASS
			30~1000	0.30	-60.18	≤-19.7	PASS
			1000~26500	0.30	-40.64	≤-19.7	PASS
		2480	Reference	1.54	1.54	---	PASS
			30~1000	1.54	-60.16	≤-18.46	PASS
			1000~26500	1.54	-43.76	≤-18.46	PASS


Test Graphs:



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3


Page 63 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3


Page 64 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3


Page 65 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3


Page 66 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3


Page 67 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3


Page 68 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3


Page 69 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3


Page 70 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3


Page 71 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3


Page 72 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3


Page 73 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3


Page 74 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 75 of 76



CVC Testing Technology Co., Ltd.

Test Report No. FCC2022-0035-RF/R3

Page 76 of 76

6. Appendix A

Test Equipment	Type/Mode	SERIAL NO.	Equipment No.	Manufacturer	Cal. Due
Spectrum Analyzer	FSV40	101580	DZ-000238-3	R&S	2023/06/05
Comprehensive Test Instrument	CMW270	100304	DZ-000240-1	R&S	2022/12/09
Analog Signal Generator	SMB100A	181858	DZ-000238-2	R&S	2023/06/05
Vector Signal Generator	SGT100A	111661	DZ-000238-1	R&S	2023/06/05
RF Radio Frequency Switch	JS0806-2	19H9080187	DZ-000241	Tonscend	2023/06/06
Programmable DC Power Supply	E3644A	MY58036222	DZ-000178	KEYSIGHT	2023/04/21
3m Semi-Anechoic Chamber	FACT-4	ST08035	WKNA-0024	ETS	2024/12/12
Spectrum Analyzer	N9010B	MY57470323	DZ-000174	KEYSIGHT	2023/03/02
EMI Test Receiver	N9038A-508	MY532290079	EM-000397	Agilent	2023/03/02
Broadband Antenna	VULB 9163	9163-530	EM-000342	SCHWARZBECK	2023/06/25
Waveguide Horn Antenna	HF906	360306/008	WKNA-0024-8	R&S	2023/03/04
Waveguide Horn Antenna	BBHA9170	00949	EM-000383	SCHWARZBECK	2023/08/26
Bandstop Filters	SW-BSF-2400-100-7-A1	/	EM-000495	/	2023/08/30
5G Bandstop Filters	WRCJV12-4900-5100-5900-6100-50EE	1	DZ-000186	WI	2022/12/20
Preamplifier	BBV 9721	9721-050	DZ-000209-1	SCHWARZBECK	2023/06/05

The End