



# **Compliance Testing, LLC**

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

[info@ComplianceTesting.com](mailto:info@ComplianceTesting.com)

## **Test Report**

**Prepared for: Mark A. Davis**

**Model: HH021**

**Description: Wireless Helmet Headset**

**Serial Number: N/A**

**FCC ID: 2AKXKHH021**

**To**

**FCC Part 1.1310**

**Date of Issue: April 14, 2017**

**On the behalf of the applicant:**

**Mark A. Davis  
73 Buckboard Road  
Box 430  
Tijeras, NM 87059**

**Attention of:**

**Mark Davis  
Ph: (505)379-1210  
Email: madavis@nuail.com**

**Prepared By  
Compliance Testing, LLC  
1724 S. Nevada Way  
Mesa, AZ 85204  
(480) 926-3100 phone / (480) 926-3598 fax  
[www.compliancetesting.com](http://www.compliancetesting.com)  
Project No: p1720025**

**Kenneth Lee  
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing  
All results contained herein relate only to the sample tested



### Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	March 21, 2017	Kenneth Lee	Original Document
2.0	April 14, 2017	Kenneth Lee	Updated Minimum Test distance to 5 mm



## ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



**FCC Site Reg. #349717**

**IC Site Reg. #2044A-2**

**Non-accredited tests contained in this report:**

**N/A**

### **EUT Description**

**Model:** HH021

**Description:** Wireless Helmet Headset

**Firmware:** PurePath Wireless Configurator 1.4.2.38775 – Texas Instruments

**Software:** N/A

**Serial Number:** N/A

**Additional Information:** This device incorporates the TI PurePath protocol.



## SAR Exclusion

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$$\left[ \frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{25} \text{ where}$$

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>26</sup>
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Max Power in mW = 0.475 mW  
Min. Test Separation Distance = 5 mm  
Frequency of Operation = 2406

$$\frac{0.475 \text{ mW}}{5 \text{ mm}} \times [\sqrt{f(2.406)}] = 0.1458$$

END OF TEST REPORT