



Shenzhen Shun reach technology Co.,LTD

Manufacturer's address:4th Floor, Building B5, Xinfu Industrial Park, Chongqing Road, Fuyong Town, Bao 'an District, Shenzhen City

顺达成科技

Antenna Test Report



客户名称：秋雨

项目名称：CF-1012W-TEQ-ZD

频段：WIFI

版本：A

制作日期：2025-6-20



Content

- 1. Antenna Matching Network**
- 2. *S11 Parameter-VSWR***
- 3. 1 Gain & Efficiency**
- 3. 2 3D Pattern**
- 4. OTA Data**
- 5. Antenna Assembly & environmental processing**
- 6. conclusion**
- 7. Antenna Size**



Shenzhen Shun reach technology Co.,LTD

Manufacturer's address:4th Floor, Building B5, Xinfu Industrial Park, Chongqing Road, Fuyong Town, Bao 'an District, Shenzhen City

顺达成科技

1.Test system

Sequence Number	Test Item	equipment
S parameter	VSWR	Agilent 5071C & Agilent 5062A
OTA Test	TRP&TIS	Agilent 8960 E5515C& Agilent 4438C&CMW500 &CMW2 ETS&SATIMO
Gain & Efficiency	Gain & Efficiency	ETS&SATIMO Agilent 5071C






Shenzhen Shun reach technology Co.,LTD

Manufacturer's address:401A, Xinfu Industrial Park, Zhongqing Road, Heping Community, Fuhai Street, Baoan District,Shenzhen

顺达成科技

2. Antenna Matching Network




Location	Description	Vendor
Shunt 01	N/A	N/A
Series	N/A	N/A
Shunt 02	N/A	N/A

未改动主板
匹配电路



S11 Parameter-SWR

顺达成科技



Frequency(MHz)	2400	2450	2500
VSWR	1.49	1.07	1.37




Gain & Efficiency


顺达成科技

Passive Test For 2.4G												
Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	UHS (%)	DHS (%)	Max (dB)	Min (dB)	Directivity (dBi)	Beamwidth (3dB)	AttH (dB)	AttV (dB)
2400	49.18	-2.91	1.81	-0.34	27.675	23.506	1.81	-12.91	4.72	0	48.27	48.32
2425	50.87	-2.77	2.01	-0.14	28.82	24.055	2.01	-12.76	4.78	0	48.35	48.41
2450	51.29	-2.13	2.66	0.51	33.173	28.12	2.66	-11.25	4.78	0	48.97	48.93
2475	51.73	-2.1	2.69	0.54	33.177	28.553	2.69	-10.28	4.78	0	48.91	48.71
2500	52.16	-1.6	3.13	0.98	36.869	32.291	3.13	-10.83	4.74	0	49.09	48.78


2400.000MHz




2400.000MHz H




2425.000MHz




2425.000MHz H




2450.000MHz




2450.000MHz H




2400.000MHz E1




2400.000MHz E2




2425.000MHz E1




2425.000MHz E2



2450.000MHz E1



2450.000MHz E2






Gain & Efficiency


顺达成科技

Passive Test For 2.4G												
Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	UHS (%)	DHS (%)	Max (dB)	Min (dB)	irectivit (dBi)	Beamwidth (3dB)	AttH (dB)	AttV (dB)
2400	49.18	-2.91	1.81	-0.34	27.675	23.506	1.81	-12.91	4.72	0	48.27	48.32
2425	50.87	-2.77	2.01	-0.14	28.82	24.055	2.01	-12.76	4.78	0	48.35	48.41
2450	51.29	-2.13	2.66	0.51	33.173	28.12	2.66	-11.25	4.78	0	48.97	48.93
2475	51.73	-2.1	2.69	0.54	33.177	28.553	2.69	-10.28	4.78	0	48.91	48.71
2500	52.16	-1.6	3.13	0.98	36.869	32.291	3.13	-10.83	4.74	0	49.09	48.78


2475.000MHz




2475.000MHz H




2500.000MHz




2500.000MHz H




2475.000MHz E1




2475.000MHz E2



2500.000MHz E1



2500.000MHz E2






WIFI OTA Data

2.4G WIFI	TRP			TIS		
Channel	CH1	CH6	CH11	CH1	CH6	CH11
802.11 b , 11M	14.85	14.61	14.29	-81.2	-81.29	-82.33
802.11 g , 54M	12.46	12.71	13.02	-71.65	-71.54	-71.43
802.11 n , MCS7 (65M)	12.31	12.29	12.75	-70.29	-70.55	-70.31



顺达成科技

Antenna Assembly & environmental processing




Conductive sponge should be used to ground the upper part of the motherboard shield.



顺达成科技

Antenna Assembly & environmental processing


Please refer to the right picture for the installation position of the antenna



WIFI Antenna



Antenna Size





Shenzhen Shun reach technology Co.,LTD

顺达成科技

Manufacturer's address:4th Floor, Building B5, Xinfu Industrial Park, Chongqing Road,
Fuyong Town, Bao 'an District, Shenzhen City