



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM170600546701
Page: 1 of 113

TEST REPORT

Application No.: SZEM1706005467CR
Applicant: Hangzhou Yudu Hardware Co.,Ltd.
Address of Applicant: No.5 Liansheng Road, Wuchang, Yuhang, Hangzhou
Manufacturer: Hangzhou Yudu Hardware Co.,Ltd.
Address of Manufacturer: No.5 Liansheng Road, Wuchang, Yuhang, Hangzhou
Factory: Hangzhou Yudu Hardware Co.,Ltd.
Address of Factory: No.5 Liansheng Road, Wuchang, Yuhang, Hangzhou
Equipment Under Test (EUT):
EUT Name: Hearing protector with Radio, Bluetooth
Model No.: 78288
FCC ID: 2AL7C78288
Standards: 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2017-06-02
Date of Test: 2017-06-05 to 2017-07-05
Date of Issue: 2017-07-06

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.





Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-07-06		Original

Authorized for issue by:				
				
		Leo Li /Project Engineer		
				
		Eric Fu /Reviewer		



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.247(a)(1),(g), (h)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(1)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	6
4.1 DETAILS OF E.U.T.	6
4.2 DESCRIPTION OF SUPPORT UNITS	6
4.3 MEASUREMENT UNCERTAINTY	7
4.4 TEST LOCATION	8
4.5 TEST FACILITY	8
4.6 DEVIATION FROM STANDARDS	8
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	8
5 EQUIPMENT LIST	9
6 RADIO SPECTRUM TECHNICAL REQUIREMENT	11
6.1 ANTENNA REQUIREMENT	11
6.1.1 Test Requirement:	11
6.1.2 Conclusion	11
6.2 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM HOPPING SEQUENCE	12
6.2.1 Test Requirement:	12
6.2.2 Conclusion	12
7 RADIO SPECTRUM MATTER TEST RESULTS	13
7.1 CONDUCTED PEAK OUTPUT POWER	13
7.1.1 E.U.T. Operation	14
7.1.2 Test Setup Diagram	14
7.1.3 Measurement Procedure and Data	14
7.2 20dB BANDWIDTH	15
7.2.1 E.U.T. Operation	15
7.2.2 Test Setup Diagram	15
7.2.3 Measurement Procedure and Data	15
7.3 CARRIER FREQUENCIES SEPARATION	16
7.3.1 E.U.T. Operation	16
7.3.2 Test Setup Diagram	16
7.3.3 Measurement Procedure and Data	16
7.4 HOPPING CHANNEL NUMBER	17
7.4.1 E.U.T. Operation	17
7.4.2 Test Setup Diagram	17
7.4.3 Measurement Procedure and Data	17
7.5 DWELL TIME	18
7.5.1 E.U.T. Operation	18
7.5.2 Test Setup Diagram	18
7.5.3 Measurement Procedure and Data	18
7.6 CONDUCTED BAND EDGES MEASUREMENT	19
7.6.1 E.U.T. Operation	19
7.6.2 Test Setup Diagram	19
7.6.3 Measurement Procedure and Data	19
7.7 CONDUCTED SPURIOUS EMISSIONS	20
7.7.1 E.U.T. Operation	20



7.7.2	Test Setup Diagram	20
7.7.3	Measurement Procedure and Data	20
7.8	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	21
7.8.1	E.U.T. Operation	21
7.8.2	Test Setup Diagram	21
7.8.3	Measurement Procedure and Data	22
7.9	RADIATED SPURIOUS EMISSIONS	27
7.9.1	E.U.T. Operation	28
7.9.2	Test Setup Diagram	28
7.9.3	Measurement Procedure and Data	29
8	PHOTOGRAPHS	38
8.1	RADIATED SPURIOUS EMISSIONS TEST SETUP	38
8.2	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	39
8.3	EUT CONSTRUCTIONAL DETAILS	40
9	APPENDIX	41
9.1	APPENDIX 15.247	41-113



4 General Information

4.1 Details of E.U.T.

Power supply:	4.5V DC(1.5V x 3 "AAA" Size Batteries)
Test voltage	DC 4.5V
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.0 single mode
Modulation Type:	GFSK; 8DPSK; $\pi/4$ DQPSK;
Number of Channel:	79
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi

4.2 Description of Support Units

The EUT has been tested as an independent unit.



4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10 ⁻⁸
2	Duty cycle	0.37%
3	Occupied Bandwidth	3%
4	RF conducted power	0.75dB
5	RF power density	2.84dB
6	Conducted Spurious emissions	0.75dB
7	RF Radiated power	4.5dB (below 1GHz)
		4.8dB (above 1GHz)
8	Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-18GHz)
9	Temperature test	1°C
10	Humidity test	3%
11	Supply voltages	1.5%
12	Time	3%



4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-13
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

20dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-13
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Carrier Frequencies Separation					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-13
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Hopping Channel Number					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-13
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Dwell Time



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170600546701

Page: 10 of 113

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-13
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Conducted Band Edges Measurement

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-13
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Conducted Spurious Emissions

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-13
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

General used equipment

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2016-10-12	2017-10-12
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2017-04-18	2018-04-18

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(c)

6.1.2 Conclusion


Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0 dBi.



6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence

6.2.1 Test Requirement:

47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)

6.2.2 Conclusion

Standard Requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1):

According to Technical Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

> Number of shift register stages: 9

> Length of pseudo-random sequence: $2^9 - 1 = 511$ bits

> Longest sequence of zeros: 8 (non-inverted signal)

Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

Each frequency used equally on the average by each transmitter.

According to Technical Specification, the receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g):

According to Technical Specification, the system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h):

According to Technical specification, the system incorporates with an adaptive system to detect other user within the spectrum band so that it individ



7 Radio Spectrum Matter Test Results

7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(1)

Test Method: ANSI C63.10 (2013) Section 7.8.5

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation


7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode d:TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.1.2 Test Setup Diagram



7.1.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.2 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247(a)(1)

Test Method: ANSI C63.10 (2013) Section 7.8.7


7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode d:TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.2.2 Test Setup Diagram



7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247


7.3 Carrier Frequencies Separation

Test Requirement: 47 CFR Part 15, Subpart C 15.247a(1)
Test Method: ANSI C63.10 (2013) Section 7.8.2
Limit: 2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W

7.3.1 E.U.T. Operation

Operating Environment:
Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar
Test mode: c:TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.3.2 Test Setup Diagram



7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.4 Hopping Channel Number

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii)

Test Method: ANSI C63.10 (2013) Section 7.8.3

Limit:

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75


7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode c:TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.4.2 Test Setup Diagram



7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.5 Dwell Time

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii)

Test Method: ANSI C63.10 (2013) Section 7.8.4

Limit:

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period


7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode c:TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.5.2 Test Setup Diagram



7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.6 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 7.8.6


7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode d:TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.6.2 Test Setup Diagram



7.6.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.7 Conducted Spurious Emissions

Test Requirement	47 CFR Part 15, Subpart C 15.247(d)
Test Method:	ANSI C63.10 (2013) Section 7.8.8
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.


7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode d:TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.7.2 Test Setup Diagram



7.7.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.8 Radiated Emissions which fall in the restricted bands


Test Requirement: 47 CFR Part 15, Subpart C 15.205 & 15.209
Test Method: ANSI C63.10 (2013) Section 6.10.5
Measurement Distance: 3m

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C Humidity: 54 % RH Atmospheric Pressure: 1010 mbar
Test mode: d:TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.8.2 Test Setup Diagram





7.8.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 23 of 113

Mode:d; Polarization:Horizontal; Modulation Type:GFSK; ; Channel:Low



Condition: 3m HORIZONTAL

Job No: : 05467CR

Mode: : 2402 Band edge
: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2349.890	5.31	28.96	37.97	48.85	45.15	74.00	-28.85	peak
2	2390.000	5.34	29.08	37.96	44.71	41.17	74.00	-32.83	peak
3 pp	2402.148	5.35	29.11	37.96	98.86	95.36	74.00	21.36	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 24 of 113

Mode:d; Polarization:Vertical; Modulation Type:GFSK; ; Channel:Low



Condition: 3m VERTICAL

Job No: : 05467CR

Mode: : 2402 Band edge

: BT

	Freq	Cable	Ant	Preamp	Read	Limit	Over	
	MHz	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2350.090	5.31	28.96	37.96	49.97	46.28	74.00	-27.72 peak
2	2390.000	5.34	29.08	37.96	44.16	40.62	74.00	-33.38 peak
3 pp	2402.148	5.35	29.11	37.96	103.58	100.08	74.00	26.08 peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 25 of 113

Mode:d; Polarization:Horizontal; Modulation Type:GFSK; ; Channel:High



Condition: 3m HORIZONTAL
Job No: : 05467CR
Mode: : 2480 Band edge
: BT

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 2479.830	5.41	29.34	37.95	99.49	96.29	74.00	22.29 peak
2	2483.500	5.41	29.35	37.95	49.09	45.90	74.00	-28.10 peak
3	2487.019	5.41	29.36	37.95	46.07	42.89	74.00	-31.11 peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 26 of 113

Mode:d; Polarization:Vertical; Modulation Type:GFSK; ; Channel:High



Condition: 3m VERTICAL

Job No: : 05467CR

Mode: : 2480 Band edge

: BT

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp 2479.805	5.41	29.34	37.95	102.21	99.01	74.00	25.01 peak
2	2483.500	5.41	29.35	37.95	51.51	48.32	74.00	-25.68 peak
3	2483.946	5.41	29.35	37.95	46.66	43.47	74.00	-30.53 peak



7.9 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1010 mbar

Test mode d:TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, $\pi/4$ DQPSK modulation, 8DPSK modulation. All modes have been tested and only the data of worst case is recorded in the report.

7.9.2 Test Setup Diagram






7.9.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Radiated Emission below 1GHz

30MHz~1GHz (QP)

Horizontal



Condition: 3m HORIZONTAL


Job No. : 05476CR

Test mode: d

		Cable	Ant	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.00	0.60	18.70	27.36	23.03	14.97	40.00	-25.03
2	116.13	1.24	8.17	27.09	37.01	19.33	43.50	-24.17
3	139.85	1.30	8.09	26.96	35.95	18.38	43.50	-25.12
4	219.84	1.52	11.23	26.63	34.15	20.27	46.00	-25.73
5	316.59	1.95	14.50	26.52	24.99	14.92	46.00	-31.08
6	989.54	3.69	23.88	26.37	21.88	23.08	54.00	-30.92



Vertical



Condition: 3m VERTICAL

Job No. : 05476CR


Test mode: d

	Freq	Cable	Ant	Preamp	Read	Limit	Over
	MHz	Loss	Factor	Factor	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	43.51	0.68	11.56	27.31	30.49	15.42	40.00 -24.58
2	53.32	0.80	8.20	27.28	28.95	10.67	40.00 -29.33
3	116.13	1.24	8.17	27.09	33.53	15.85	43.50 -27.65
4	219.84	1.52	11.23	26.63	28.89	15.01	46.00 -30.99
5	312.18	1.94	14.34	26.50	26.05	15.83	46.00 -30.17
6 pp	884.50	3.54	23.08	26.85	24.07	23.84	46.00 -22.16



Transmitter Emission above 1GHz

Mode:d; Polarization:Horizontal; Modulation Type:GFSK; ; Channel:Low



Condition: 3m HORIZONTAL

Job No: : 05467CR

Mode: : 2402 TX SE

: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1473.013	4.44	25.69	38.05	43.92	36.00	74.00	-38.00	peak
2	4456.315	7.23	33.60	38.23	45.28	47.88	74.00	-26.12	peak
3	4804.000	7.73	34.16	38.40	47.63	51.12	74.00	-22.88	peak
4 pp	7206.000	9.65	36.42	37.11	43.32	52.28	74.00	-21.72	peak
5	9608.000	11.06	37.52	35.10	38.19	51.67	74.00	-22.33	peak
6	14830.960	14.81	41.00	38.92	34.77	51.66	74.00	-22.34	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 33 of 113

Mode:d; Polarization:Vertical; Modulation Type:GFSK; ; Channel:Low



Condition: 3m VERTICAL

Job No: : 05467CR

Mode: : 2402 TX SE

: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1481.553	4.45	25.73	38.05	43.25	35.38	74.00	-38.62	peak
2	4405.090	7.18	33.60	38.20	44.36	46.94	74.00	-27.06	peak
3	4804.000	7.73	34.16	38.40	49.31	52.80	74.00	-21.20	peak
4	7206.000	9.65	36.42	37.12	43.25	52.20	74.00	-21.80	Peak
5	9608.000	11.06	37.52	35.10	38.51	51.99	74.00	-22.01	peak
6	pp14873.890	14.82	41.08	38.91	36.01	53.00	74.00	-21.00	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 34 of 113

Mode:d; Polarization:Horizontal; Modulation Type:GFSK; ; Channel:middle



Condition: 3m HORIZONTAL

Job No: : 05467CR

Mode: : 2441 TX SE

: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	4.27	25.11	38.07	44.54	35.85	74.00	-38.15	peak
2	4392.376	7.16	33.60	38.20	44.65	47.21	74.00	-26.79	peak
3	4882.000	7.84	34.30	38.44	43.56	47.26	74.00	-26.74	peak
4 pp	7323.000	9.73	36.37	37.01	37.26	46.35	54.00	-7.65	Average
5 pk	7323.000	9.73	36.37	37.01	46.54	55.63	74.00	-18.37	peak
6	9764.000	11.21	37.55	35.02	38.59	52.33	74.00	-21.67	peak
7	14873.890	14.82	41.08	38.91	33.10	50.09	74.00	-23.91	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 35 of 113

Mode:d; Polarization:Vertical; Modulation Type:GFSK; ; Channel:middle



Condition: 3m VERTICAL

Job No: : 05467CR

Mode: : 2441 TX SE

: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1498.781	4.47	25.80	38.05	45.40	37.62	74.00	-36.38	peak
2	4379.699	7.15	33.60	38.19	44.53	47.09	74.00	-26.91	peak
3	4882.000	7.84	34.30	38.44	49.78	53.48	74.00	-20.52	peak
4 pp	7323.000	9.73	36.37	37.01	41.66	50.75	54.00	-3.25	Average
5 pk	7323.000	9.73	36.37	37.01	49.53	58.62	74.00	-15.38	peak
6	9764.000	11.21	37.55	35.02	38.77	52.51	74.00	-21.49	peak
7	14873.890	14.82	41.08	38.91	35.66	52.65	74.00	-21.35	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 36 of 113

Mode:d; Polarization:Horizontal; Modulation Type:GFSK; ; Channel:High



Condition: 3m HORIZONTAL

Job No: : 05467CR


Mode: : 2480 TX SE

: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1672.779	4.67	26.56	38.03	43.29	36.49	74.00	-37.51	peak
2	4367.058	7.13	33.60	38.18	44.31	46.86	74.00	-27.14	peak
3	4960.000	7.95	34.43	38.48	44.59	48.49	74.00	-25.51	peak
4	6995.172	9.51	36.49	37.30	43.07	51.77	74.00	-22.23	peak
5 pp	7440.000	9.81	36.33	36.91	41.25	50.48	54.00	-3.52	Average
6 pk	7440.000	9.81	36.32	36.90	47.55	56.78	74.00	-17.22	peak
7	9920.000	11.36	37.58	34.94	39.96	53.96	74.00	-20.04	peak



Mode:d; Polarization:Vertical; Modulation Type:GFSK; ; Channel:High



Condition: 3m VERTICAL

Job No: : 05467CR

Mode: : 2480 TX SE
: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1697.129	4.70	26.66	38.03	43.57	36.90	74.00	-37.10	peak
2	4291.977	7.05	33.60	38.15	44.60	47.10	74.00	-26.90	peak
3	4960.000	7.95	34.43	38.48	48.15	52.05	74.00	-21.95	peak
4	6855.063	9.38	36.10	37.44	43.75	51.79	74.00	-22.21	peak
5 pp	7440.000	9.81	36.33	36.91	43.10	52.33	54.00	-1.67	Average
6 pk	7440.000	9.81	36.32	36.90	49.24	58.47	74.00	-15.53	peak
7	9920.000	11.36	37.58	34.94	39.06	53.06	74.00	-20.94	peak

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:


Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.


3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

8 Photographs

8.1 Radiated Spurious Emissions Test Setup



8.2 Radiated Emissions which fall in the restricted bands





8.3 EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1706005467CR.



9 Appendix

9.1 Appendix 15.247

1.20 dB Bandwidth


Test Mode	Test Channel	Ant	EBW[MHz]	Limit[MHz]	Verdict
DH5	2402	Ant1	0.948	---	PASS
DH5	2441	Ant1	0.948	---	PASS
DH5	2480	Ant1	0.948	---	PASS
2DH5	2402	Ant1	1.270	---	PASS
2DH5	2441	Ant1	1.266	---	PASS
2DH5	2480	Ant1	1.272	---	PASS
3DH5	2402	Ant1	1.238	---	PASS
3DH5	2441	Ant1	1.240	---	PASS
3DH5	2480	Ant1	1.238	---	PASS





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


Report No.: SZEM170600546701


Page: 42 of 113














SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170600546701

Page: 47 of 113






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170600546701

Page: 48 of 113






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170600546701

Page: 49 of 113






SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 50 of 113





2. Conducted Peak Output Power


Test Mode	Test Channel	Ant	Power[dBm]	Limit[dBm]	Verdict
DH5	2402	Ant1	-0.15	<20.97	PASS
DH5	2441	Ant1	2.35	<20.97	PASS
DH5	2480	Ant1	2.98	<20.97	PASS
2DH5	2402	Ant1	-3.21	<20.97	PASS
2DH5	2441	Ant1	-0.74	<20.97	PASS
2DH5	2480	Ant1	-0.18	<20.97	PASS
3DH5	2402	Ant1	-2.7	<20.97	PASS
3DH5	2441	Ant1	-0.35	<20.97	PASS
3DH5	2480	Ant1	0.34	<20.97	PASS





SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 52 of 113












Conducted Peak Output Power_2DH5_2402_ANT1






Conducted Peak Output Power_2DH5_2441_ANT1











Conducted Peak Output Power_3DH5_2441_ANT1









3.Carrier Frequency Separation


Test Mode	Test Channel	Ant	Result[MHz]	Limit[MHz]	Verdict
DH5	2441	Ant1	0.993	≥ 0.632	PASS
2DH5	2441	Ant1	0.999	≥ 0.848	PASS
3DH5	2441	Ant1	0.999	≥ 0.827	PASS





Carrier Frequency Separation_2DH5_2441_ANT1








4.Dwell Time

Test Mode	Test Channel	Ant	Burst Width[ms/hop/ch]	Total Hops[hop*ch]	Dwell Time[s]	Limit[s]	Verdict
DH1	2402	Ant1	0.39	320	0.125	<0.4	PASS
DH3	2402	Ant1	1.65	150	0.248	<0.4	PASS
DH5	2402	Ant1	2.89	110	0.318	<0.4	PASS
2DH1	2402	Ant1	0.4	320	0.128	<0.4	PASS
2DH3	2402	Ant1	1.66	150	0.249	<0.4	PASS
2DH5	2402	Ant1	2.9	110	0.319	<0.4	PASS
3DH1	2402	Ant1	0.4	320	0.128	<0.4	PASS
3DH3	2402	Ant1	1.66	160	0.266	<0.4	PASS
3DH5	2402	Ant1	2.9	110	0.319	<0.4	PASS







SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 66 of 113









SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 68 of 113









SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 70 of 113








SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 72 of 113






SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 73 of 113







SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 74 of 113









SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 76 of 113









SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170600546701

Page: 78 of 113









SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 80 of 113








SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701


Page: 82 of 113






5.Hopping Channel Number

Test Mode	Test Channel	Ant	Number of Hopping Channel[N]	Limit[N]	Verdict
DH5	2402	Ant1	79	>=15	PASS
2DH5	2402	Ant1	79	>=15	PASS
3DH5	2402	Ant1	79	>=15	PASS






Hopping Channel Number_2DH5_2402_ANT1





Hopping Channel Number_3DH5_2402_ANT1





6.Band-edge for RF Conducted Emissions


Test Mode	Test Channel	Ant	Hopping	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit[dBm]	Verdict
DH5	2402	Ant1	On	1.930	-53.598	<-18.07	PASS
DH5	2402	Ant1	Off	-1.090	-62.370	<-21.09	PASS
DH5	2480	Ant1	On	2.600	-54.004	<-17.4	PASS
DH5	2480	Ant1	Off	2.010	-57.218	<-17.99	PASS
2DH5	2402	Ant1	On	-3.690	-58.057	<-23.69	PASS
2DH5	2402	Ant1	Off	-7.980	-65.854	<-27.98	PASS
2DH5	2480	Ant1	On	-3.070	-57.813	<-23.07	PASS
2DH5	2480	Ant1	Off	-4.040	-61.581	<-24.04	PASS
3DH5	2402	Ant1	On	-2.930	-57.705	<-22.93	PASS
3DH5	2402	Ant1	Off	-6.690	-65.865	<-26.69	PASS
3DH5	2480	Ant1	On	-4.280	-58.433	<-24.28	PASS
3DH5	2480	Ant1	Off	-3.560	-59.726	<-23.56	PASS



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701

Page: 87 of 113






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170600546701


Page: 88 of 113


Band-edge for RF Conducted Emissions_DH5_2402_ANT1_Hopping Off






Band-edge for RF Conducted Emissions_DH5_2480_ANT1_Hopping On








Band-edge for RF Conducted Emissions_2DH5_2402_ANT1_Hopping On






Band-edge for RF Conducted Emissions_2DH5_2402_ANT1_Hopping Off






Band-edge for RF Conducted Emissions_2DH5_2480_ANT1_Hopping On






Band-edge for RF Conducted Emissions_2DH5_2480_ANT1_Hopping Off






Band-edge for RF Conducted Emissions_3DH5_2402_ANT1_Hopping On






Band-edge for RF Conducted Emissions_3DH5_2402_ANT1_Hopping Off






Band-edge for RF Conducted Emissions_3DH5_2480_ANT1_Hopping On





Band-edge for RF Conducted Emissions_3DH5_2480_ANT1_Hopping Off






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


Report No.: SZEM170600546701


Page: 99 of 113


7.RF Conducted Spurious Emissions


Test Mode	Test Channel	Ant	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
DH5	2402	Ant1	30	10000	1000	3000	-0.66	-35.910	<-20.66	PASS
DH5	2402	Ant1	10000	25000	1000	3000	-0.66	-64.740	<-20.66	PASS
DH5	2441	Ant1	30	10000	1000	3000	1.51	-44.310	<-18.49	PASS
DH5	2441	Ant1	10000	25000	1000	3000	1.51	-64.840	<-18.49	PASS
DH5	2480	Ant1	30	10000	1000	3000	2.26	-45.530	<-17.74	PASS
DH5	2480	Ant1	10000	25000	1000	3000	2.26	-64.890	<-17.74	PASS
2DH5	2402	Ant1	30	10000	1000	3000	-6.81	-49.540	<-26.81	PASS
2DH5	2402	Ant1	10000	25000	1000	3000	-6.81	-64.990	<-26.81	PASS
2DH5	2441	Ant1	30	10000	1000	3000	-4.21	-48.680	<-24.21	PASS
2DH5	2441	Ant1	10000	25000	1000	3000	-4.21	-64.610	<-24.21	PASS
2DH5	2480	Ant1	30	10000	1000	3000	-3.62	-49.680	<-23.62	PASS
2DH5	2480	Ant1	10000	25000	1000	3000	-3.62	-64.820	<-23.62	PASS
3DH5	2402	Ant1	30	10000	1000	3000	-6.92	-48.870	<-26.92	PASS
3DH5	2402	Ant1	10000	25000	1000	3000	-6.92	-64.820	<-26.92	PASS
3DH5	2441	Ant1	30	10000	1000	3000	-4.18	-47.990	<-24.18	PASS
3DH5	2441	Ant1	10000	25000	1000	3000	-4.18	-64.820	<-24.18	PASS
3DH5	2480	Ant1	30	10000	1000	3000	-3.64	-49.750	<-23.64	PASS
3DH5	2480	Ant1	10000	25000	1000	3000	-3.64	-64.940	<-23.64	PASS
























SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600546701
Page: 108 of 113







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170600546701

Page: 110 of 113

