


# RF TEST REPORT



Report No.: 17020576-FCC-R2  
 Supersede Report No.: N/A

<b>Applicant</b>	Sangoma Technologies Corp.	
<b>Product Name</b>	IP PHONE	
<b>Model No.</b>	S705	
<b>Serial No.</b>	S505	
<b>Test Standard</b>	FCC Part 15.247: 2016, ANSI C63.10: 2013	
<b>Test Date</b>	June 09 to June 23, 2017	
<b>Issue Date</b>	June 28, 2017	
<b>Test Result</b>	<input checked="" type="checkbox"/> <b>Pass</b> <input type="checkbox"/> <b>Fail</b>	
<b>Equipment complied with the specification</b>	<input checked="" type="checkbox"/>	
<b>Equipment did not comply with the specification</b>	<input type="checkbox"/>	
<i>Trety Lu</i>	<i>Deon Dai</i>	
Trety Lu Test Engineer	Deon Dai Engineer Reviewer	
<b>This test report may be reproduced in full only</b> <b>Test result presented in this test report is applicable to the tested sample only</b>		

**Issued by:**  
**SIEMIC (Nanjing-China) Laboratories**  
 2-1 Longcang Avenue Yuhua Economic and  
 Technology Development Park, Nanjing, China  
 Tel: +86(25)86730128/86730129 Fax: +86(25)86730127 Email: China@siemic.com.cn

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	17020576-FCC-R2
Page	3 of 90

---

This page has been left blank intentionally.

## CONTENTS

<b>1. REPORT REVISION HISTORY .....</b>	<b>5</b>
<b>2. CUSTOMER INFORMATION .....</b>	<b>5</b>
<b>3. TEST SITE INFORMATION.....</b>	<b>5</b>
<b>4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....</b>	<b>6</b>
<b>5. TEST SUMMARY .....</b>	<b>8</b>
<b>6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....</b>	<b>9</b>
6.1 ANTENNA REQUIREMENT .....	9
6.2 DTS (6 DB&20 DB) CHANNEL BANDWIDTH .....	10
6.3 MAXIMUM OUTPUT POWER .....	19
6.4 POWER SPECTRAL DENSITY .....	24
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS .....	29
6.6 AC POWER LINE CONDUCTED EMISSIONS.....	47
6.7 RADIATED EMISSIONS.....	61
<b>ANNEX A. TEST INSTRUMENT .....</b>	<b>72</b>
<b>ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS .....</b>	<b>73</b>
<b>ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....</b>	<b>86</b>
<b>ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST.....</b>	<b>89</b>
<b>ANNEX E. DECLARATION OF SIMILARITY .....</b>	<b>90</b>

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
17020576-FCC-R2	NONE	Original	June 28, 2017

## 2. Customer information

Applicant Name	Sangoma Technologies Corp.
Applicant Add	100 Renfrew Drive, Suite 100 / Markham, ON L3R 9R6 CANADA
Manufacturer	Sangoma Technologies Corp.
Manufacturer Add	100 Renfrew Drive, Suite 100 / Markham, ON L3R 9R6 CANADA

## 3. Test site information

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	986914
IC Test Site No.	4842B-1
Test Software	EZ_EMG

#### 4. Equipment under Test (EUT) Information

Description of EUT:	IP PHONE
Main Model:	S705
Serial Model:	S505
Date EUT received:	May 18, 2017
Test Date(s):	June 09 to June 23, 2017
Antenna Gain:	WIFI :802.11b/g/n(20M): 13CH WIFI :802.11n(40M): 9CH
Type of Modulation:	WIFI:802.11b/g/n(20M/40M): DSSS, OFDM
RF Operating Frequency (ies):	WIFI:802.11b/g/n(20M): 2412-2472 MHz 802.11n(40M):2422-2462 MHz
Max. Output Power:	WIFI:802.11b: 19.24 dBm 802.11n(40M): 15.07 dBm
Number of Channels:	WIFI :802.11b/g/n(20M): 13CH WIFI :802.11n(40M): 9CH
Port:	Power Port、 Ext Port、 Internet Port、 PC Port、 Earphone Port、 Telephone Port
Input Power:	Adapter: Model:NBS05B050120VU Input Power:100-240V,50/60Hz,0.2A Output:5V,1.2A
Trade Name :	Sangoma
FCC ID:	2AL9Y-PHONS705A

**Operating channel list**

Channel	Frequency (MHz)
1	2412
2	2417
3	2422
4	2427
5	2432
6	2437
7	2442
8	2447
9	2452
10	2457
11	2462
12	2467
13	2472

## 5. Test Summary

The product was tested in accordance with the following specifications.  
All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Non-Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-



## 6. Measurements, Examination And Derived Results

### 6.1 Antenna Requirement

#### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit. And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has 1 antennas:


A permanently attached PCB antenna for WIFI, the gain is 2.8 dBi for Bluetooth.

**Antenna must be permanently attached to the unit ,it meets up with the ANTENNA REQUIREMENT.**

**Result:** Compliant.

## 6.2 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	June 23, 2017
Tested By :	Trety Lu


Spec	Item	Requirement	Applicable
§ 15.247(a)(2) RSS Gen(4.6.1)	a)	6dB BW≥500kHz;	<input checked="" type="checkbox"/>
	b)	99% BW: For FCC reference only; required by IC.	N/A
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>558074 D01 DTS MEAS Guidance V04, 8.1 DTS bandwidth  <u>6dB bandwidth</u>            a) Set RBW = 100 kHz.            b) Set the video bandwidth (VBW) ≥ 3 × RBW.            c) Detector = Peak.            d) Trace mode = max hold.            e) Sweep = auto couple.            f) Allow the trace to stabilize.            g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.</p> <p><u>20dB bandwidth</u>            C63.10 Occupied Bandwidth (OBW=20dB bandwidth)            1. Set RBW = 1%-5% OBW.            2. Set the video bandwidth (VBW) ≥ 3 x RBW.            3. Set the span range between 2 times and 5 times of the OBW.            4. Sweep time=Auto, Detector=PK, Trace=Max hold.            5. Once the reference level is established, the equipment is conditioned with typical modulating signals to produce the worst-case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB levels with respect to the reference level.</p>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data     Yes                       N/A  
 Test Plot     Yes (See below)                       N/A

### Measurement result

Test mode	CH	Freq (MHz)	6dB Bandwidth (MHz)	20dB Bandwidth (MHz)	Limit (MHz)
802.11b	1	2412	9.06	13.36	≥0.5
	6	2437	9.06	13.36	≥0.5
	11	2462	9.08	13.39	≥0.5
	12	2467	9.05	13.38	≥0.5
	13	2472	9.08	13.38	≥0.5
802.11g	1	2412	16.03	18.85	≥0.5
	6	2437	16.00	18.78	≥0.5
	11	2462	15.78	18.76	≥0.5
	12	2467	16.01	18.99	≥0.5
	13	2472	15.80	18.73	≥0.5
802.11n (20M)	1	2412	17.03	19.31	≥0.5
	6	2437	15.96	19.36	≥0.5
	11	2462	16.66	19.30	≥0.5
	12	2467	16.31	19.22	≥0.5
	13	2472	17.02	19.28	≥0.5
802.11n (40M)	3	2422	35.67	39.13	≥0.5
	6	2437	35.71	39.34	≥0.5
	9	2452	35.39	39.00	≥0.5
	10	2457	35.21	39.19	≥0.5
	11	2462	35.48	39.22	≥0.5

### Test Plots 6dB Bandwidth measurement result







802.11b 6dB Bandwidth - CH 11




802.11b 6dB Bandwidth - CH 12




802.11b 6dB Bandwidth - CH 13




802.11g 6dB Bandwidth - CH 1




802.11g 6dB Bandwidth - CH 6




802.11g 6dB Bandwidth - CH 11



802.11g 6dB Bandwidth - CH 12



802.11g 6dB Bandwidth - CH 13




802.11n20 6dB Bandwidth - CH 1




802.11n20 6dB Bandwidth - CH 6




802.11n20 6dB Bandwidth - CH 11




802.11n20 6dB Bandwidth - CH 12



802.11n20 6dB Bandwidth - CH 13




802.11n40 6dB Bandwidth - CH 3




802.11n40 6dB Bandwidth - CH 6



802.11n40 6dB Bandwidth - CH 9



802.11n40 6dB Bandwidth - CH 10



802.11n40 6dB Bandwidth - CH 11



### 20 dB Bandwidth measurement result




802.11b 20dB Bandwidth - CH 1

802.11b 20dB Bandwidth - CH 6




802.11b 20dB Bandwidth - CH 11

802.11b 20dB Bandwidth - CH 12




802.11b 20dB Bandwidth - CH 13


802.11g 20dB Bandwidth - CH 1



802.11g 20dB Bandwidth - CH 6



802.11g 20dB Bandwidth - CH 11



802.11g 20dB Bandwidth - CH 12



802.11g 20dB Bandwidth - CH 13




802.11n20 20dB Bandwidth - CH 1




802.11n20 20dB Bandwidth - CH 6







802.11n20 20dB Bandwidth - CH 11



802.11n20 20dB Bandwidth - CH 12



802.11n20 20dB Bandwidth - CH 13




802.11n40 20dB Bandwidth - CH 3




802.11n40 20dB Bandwidth - CH 6



802.11n40 20dB Bandwidth - CH 9



802.11n40 20dB Bandwidth - CH 10




802.11n40 20dB Bandwidth - CH 11

### 6.3 Maximum Output Power

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	June 23, 2017
Tested By :	Trety Lu

#### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3)	a)	FHSS in 2400-2483.5MHz with $\geq 75$ channels: $\leq 1$ Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: $\leq 1$ Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: $\leq 0.125$ Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with $\geq 50$ channels: $\leq 1$ Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with $\geq 25$ & $< 50$ channels: $\leq 0.25$ Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: $\leq 1$ Watt	<input checked="" type="checkbox"/>

Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
------------	--

Test Procedure	<p>558074 D01 DTS MEAS GuidanceV04, 9.1.2 Integrated band power method Maximum output power measurement procedure</p> <ul style="list-style-type: none"> <li>- a) Set span to at least 1.5 times the OBW.</li> <li>- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.</li> <li>- c) Set VBW <math>\geq 3 \times</math> RBW.</li> <li>- d) Number of points in sweep <math>\geq 2 \times</math> span / RBW. (This gives bin-to-bin spacing <math>\leq</math> RBW/2, so that narrowband signals are not lost between frequency bins.)</li> <li>- e) Sweep time = auto.</li> <li>- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.</li> <li>- g) If transmit duty cycle <math>&lt; 98\%</math>, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle <math>\geq 98\%</math>, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".</li> <li>- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.</li> <li>- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.</li> </ul>
----------------	---

Remark	
--------	--

Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
--------	--


Test Data     Yes                       N/A


Test Plot     Yes (See below)                       N/A

**Output Power measurement result**


Type	Test mode	CH	Freq (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	802.11b	1	2412	19.14	30	Pass
		6	2437	19.20	30	Pass
		11	2462	19.24	30	Pass
		12	2467	19.06	30	Pass
		13	2472	19.08	30	Pass
	802.11g	1	2412	17.81	30	Pass
		6	2437	18.22	30	Pass
		11	2462	18.39	30	Pass
		12	2467	18.36	30	Pass
		13	2472	17.98	30	Pass
	802.11n(20M)	1	2412	18.09	30	Pass
		6	2437	18.25	30	Pass
		11	2462	18.39	30	Pass
		12	2467	18.23	30	Pass
		13	2472	18.09	30	Pass
	802.11n(40M)	3	2422	14.69	30	Pass
		6	2437	15.03	30	Pass
9		2452	15.07	30	Pass	
10		2457	15.02	30	Pass	
11		2462	14.95	30	Pass	

**Test Plots**







802.11b - AV Output power - CH 11




802.11b - AV Output power - CH 12




802.11b - AV Output power - CH 13




802.11g - AV Output power - CH 1




802.11g - AV Output power - CH 6




802.11g - AV Output power - CH 11




802.11g - AV Output power - CH 12




802.11g - AV Output power - CH 13



802.11n20 - AV Output power - CH 1



802.11n20 - AV Output power - CH 6




802.11n20 - AV Output power - CH 11



802.11n20 - AV Output power - CH 12






802.11n20 - AV Output power - CH 13




802.11n40 - AV Output power - CH 3




802.11n40 - AV Output power - CH 6



802.11n40 - AV Output power - CH 9




802.11n40 - AV Output power - CH 10



802.11n40 - AV Output power - CH 11

## 6.4 Power Spectral Density

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	June 23, 2017
Tested By :	Trety Lu

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	558074 D01 DTS MEAS Guidance V04, 10.2 power spectral density method power spectral density measurement procedure <ul style="list-style-type: none"> <li>- a) Set analyzer center frequency to DTS channel center frequency.</li> <li>- b) Set the span to 1.5 times the DTS bandwidth.</li> <li>- c) Set the RBW to: <math>3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}</math>.</li> <li>- d) Set the VBW <math>\geq 3 \times \text{RBW}</math>.</li> <li>- e) Detector = peak.</li> <li>- f) Sweep time = auto couple.</li> <li>- g) Trace mode = max hold.</li> <li>- h) Allow trace to fully stabilize.</li> <li>- i) Use the peak marker function to determine the maximum amplitude level within the RBW.</li> <li>- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data     Yes                       N/A  
 Test Plot     Yes (See below)                       N/A



### Power Spectral Density measurement result

Type	Test mode	CH	Freq (MHz)	PSD (dBm)	Limit (dBm)	Result
PSD	802.11b	1	2412	3.440	8	Pass
		6	2437	4.509	8	Pass
		11	2462	5.864	8	Pass
		12	2467	5.624	8	Pass
		13	2472	3.017	8	Pass
	802.11g	1	2412	-3.629	8	Pass
		6	2437	-3.273	8	Pass
		11	2462	-3.557	8	Pass
		12	2467	-2.813	8	Pass
		13	2472	-3.915	8	Pass
	802.11n(20M)	1	2412	-3.329	8	Pass
		6	2437	-3.148	8	Pass
		11	2462	-2.955	8	Pass
		12	2467	-3.116	8	Pass
		13	2472	-3.284	8	Pass
	802.11n(40M)	3	2422	-9.568	8	Pass
		6	2437	-9.310	8	Pass
		9	2452	-8.940	8	Pass
		10	2457	-9.226	8	Pass
11		2462	-9.534	8	Pass	

### Test Plots Power Spectral Density measurement result






PSD - CH 11 - 802.11b




PSD - CH 12 - 802.11b




PSD - CH 13 - 802.11b




PSD - CH 1 - 802.11g




PSD - CH 6 - 802.11g




PSD - CH 11 - 802.11g




PSD - CH 12 - 802.11g




PSD - CH 13 - 802.11g




PSD - CH 1 - 802.11n20




PSD - CH 6 - 802.11n20




PSD - CH 11 - 802.11n20




PSD - CH 12 - 802.11n20




PSD - CH 13 - 802.11n20




PSD - CH 3 - 802.11n40




PSD - CH 6 - 802.11n40



PSD - CH 9 - 802.11n40



PSD - CH 10 - 802.11n40




PSD - CH 11 - 802.11n40

## 6.5 Band-Edge & Unwanted Emissions into Non-Restricted Frequency Bands

Temperature	24 °C
Relative Humidity	52%
Atmospheric Pressure	1019mbar
Test date :	June 15 to June 19, 2017
Tested By :	Trety Lu

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>

Test Setup	 <p>The diagram illustrates the test setup. On the left, 'EUT &amp; Support Units' are placed on a 'Turn Table' which is 0.8/1.5m high. A 3m distance is marked between the turn table and the 'Ant. Tower'. The antenna tower has a '1-4m Variable' height section. Below the ground plane, a 'Test Receiver' is connected to the antenna tower.</p>
------------	--

Test Procedure	<p>Radiated Method Only</p> <ul style="list-style-type: none"> <li>- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.</li> <li>- 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.</li> <li>- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> <li>a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz.</li> <li>b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</li> <li>c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</li> </ul> </li> <li>- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.</li> <li>- 5. Repeat above procedures until all measured frequencies were complete.</li> </ul>
----------------	---

Remark	
--------	--

Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail
--------	--

Test Report No.	17020576-FCC-R2
Page	30 of 90

Test Data  Yes  N/A

Test Plot  Yes (See below)  N/A