

RF EXPOSURE REPORT

FOR

Applicant	:	Yunke China Information Technology Limited
Address	:	Digital Technology Plaza, No. 9 shangdi 9th street, Haidian District Beijing China
Equipment under Test	:	Outdoor Access Point
Model No.	:	WL8200-IT3
Trade Mark	:	DCN
FCC ID	:	2AM4IWL8200-IT3
Manufacturer	:	Yunke China Information Technology Limited
Address	:	Digital Technology Plaza, No. 9 shangdi 9th street, Haidian District Beijing China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan
City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

TABLE OF CONTENTS

	Test report declares.....	3
1.	General information	5
1.1.	Description of Equipment.....	5
1.2.	Assess laboratory.....	6
2.	RF Exposure evaluation.....	6
2.1.	Requirement.....	6
2.2.	Calculation Method	7
2.3.	Estimation Result	7

TEST REPORT DECLARE

Applicant	:	Yunke China Information Technology Limited
Address	:	Digital Technology Plaza, No. 9 shangdi 9th street, Haidian District Beijing China
Equipment under Test	:	Outdoor Access Point
Model No.	:	WL8200-IT3
Trade mark	:	DCN
Manufacturer	:	Yunke China Information Technology Limited
Address	:	Digital Technology Plaza, No. 9 shangdi 9th street, Haidian District Beijing China

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above.

The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R18080906-1E14		
Date of Receipt:	Aug. 17, 2018	Date of Test:	Aug. 17, 2018 ~ Sep. 19, 2018

Prepared By:

Ella Gong
Ella Gong/Engineer

Approved By:


Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Sep. 19, 2018	

1. General information

1.1. Description of Equipment

EUT* Name	: Outdoor Access Point
Model Number	: WL8200-IT3
EUT function description	: Please reference user manual of this device
Power supply	: 48V DC from POE Network switch
Radio Specification	: Bluetooth V4.1, IEEE802.11b/g/n, IEEE802.11a/n/ac
Operation frequency	: Bluetooth: 2402MHz-2480MHz 2412MHz-2462MHz, 5150MHz-5250MHz, 5725MHz-5850MHz
Modulation	: Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK IEEE 802.11b: DSSS (CCK, QPSK, BPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Data rate	: Bluetooth: 1Mbps, 2Mbps, 3Mbps IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11n HT20: 6.5, 13, 19.5, 26, 39, 52, 58.5, 65, 78, 104, 117, 130 Mbps IEEE 802.11n HT40: 13.5, 27, 40.5, 54, 81, 108, 121.5, 135, 162, 216, 243, 270 Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n HT20: 14.4, 28.9, 43.3, 57.8, 86.7, 115.6, 130.0, 144.4 Mbps IEEE 802.11n HT40: 30, 60, 90, 120, 180, 240, 270, 300 Mbps IEEE 802.11ac HT20: 14.4, 28.8, 43.4, 57.8, 86.6, 115.6, 130, 144.4, 173.4 Mbps IEEE 802.11ac HT40: 30, 60, 90, 120, 180, 240, 270, 300, 360, 400 Mbps IEEE 802.11ac HT80: 65, 130, 195, 260, 390, 520, 585, 650, 780, 866.6 Mbps
Antenna Type	: Antenna 1: Internal antenna, 2.4G band maximum PK gain: 7dBi Antenna 2: Internal antenna, 2.4G band maximum PK gain: 7dBi Antenna 3: Internal antenna, 2.4G band maximum PK gain: 7dBi Antenna 4: Internal antenna, 5G band maximum PK gain: 8dBi Antenna 5: Internal antenna, 5G band maximum PK gain: 8dBi The EUT incorporates a MIMO function. Physically, it provides two completed transmitters and receivers(2T2R), two transmit signals are completely uncorrelated, then, Direction gain=GANT
Sample Type	: Series production

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

2. RF Exposure evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation Method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation Result

Mode	PK Output power (dBm)	Output power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
Bluetooth Max power	9.91	9.79	7	5.01	0.00956	1
BLE Max power	6.61	4.58	7	5.01	0.00456	1
2.4G WIFI Max power	23.75	237.14	7	5.01	0.236	1
5G WIFI Max power	23.97	249.46	8	6.31	0.313	1

Maximum Simultaneous transmission MPE Ratio for Bluetooth and 2.4G WLAN and 5G WLAN

Maximum MPE ratio Bluetooth	Maximum MPE ratio 2.4GWLAN	Maximum MPE ratio 5GWLAN	ΣMPE ratios	Limit	Results
0.00956	0.236	0.313	0.559	1.000	Pass

Note: The estimation distance is 20cm

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold

END OF REPORT