

# TEST REPORT

**Product Name** : Haylou RS3  
**Brand Mark** : Haylou  
**Model No.** : Haylou-LS04  
**FCC ID** : 2AMQ6-LS04  
**Report Number** : BLA-EMC-202101-A1502  
**Date of Sample Receipt** : 2021/1/6  
**Date of Test** : 2021/1/6 to 2021/1/26  
**Date of Issue** : 2021/1/28  
**Test Standard** : 47 CFR Part 15, Subpart C 15.247  
**Test Result** : Pass

Prepared for:

**Dongguan Liesheng Electronic Co., Ltd.**

**Room 401-410, Building 1, No.86 Hongtu Road, Nancheng District, Dongguan City,  
Guangdong, China.**

Prepared by:

**BlueAsia of Technical Services(Shenzhen) Co.,Ltd.**

**Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,  
Shenzhen, Guangdong Province, China**

**TEL: +86-755-23059481**

Compiled by:

*Sven*

Review by:

*Sweet. Liang*

Approved by:

*Jimen Li*

Date: 2021/1/28



**REPORT REVISE RECORD**

<b>Version No.</b>	<b>Date</b>	<b>Description</b>
00	2021/1/28	Original

BlueAsia

## TABLE OF CONTENTS

<b>1</b>	<b>TEST SUMMARY .....</b>	<b>6</b>
<b>2</b>	<b>GENERAL INFORMATION .....</b>	<b>7</b>
<b>3</b>	<b>GENERAL DESCRIPTION OF E.U.T. ....</b>	<b>7</b>
<b>4</b>	<b>TEST ENVIRONMENT .....</b>	<b>8</b>
<b>5</b>	<b>TEST MODE .....</b>	<b>8</b>
<b>6</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>8</b>
<b>7</b>	<b>DESCRIPTION OF SUPPORT UNIT.....</b>	<b>9</b>
<b>8</b>	<b>LABORATORY LOCATION.....</b>	<b>9</b>
<b>9</b>	<b>TEST INSTRUMENTS LIST .....</b>	<b>10</b>
<b>1</b>	<b>CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....</b>	<b>14</b>
1.1	LIMITS .....	14
1.2	BLOCK DIAGRAM OF TEST SETUP .....	14
1.3	PROCEDURE .....	14
1.4	TEST DATA .....	16
<b>2</b>	<b>CONDUCTED BAND EDGES MEASUREMENT.....</b>	<b>18</b>
2.1	LIMITS .....	18
2.2	BLOCK DIAGRAM OF TEST SETUP .....	18
2.3	TEST DATA .....	18
<b>3</b>	<b>CONDUCTED PEAK OUTPUT POWER .....</b>	<b>19</b>
3.1	LIMITS .....	19
3.2	BLOCK DIAGRAM OF TEST SETUP .....	19
3.3	EST DATA .....	19
<b>4</b>	<b>MINIMUM 6DB BANDWIDTH .....</b>	<b>20</b>
4.1	LIMITS .....	20
4.2	BLOCK DIAGRAM OF TEST SETUP .....	20
4.3	TEST DATA .....	20
<b>5</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>21</b>
5.1	CONCLUSION .....	21
<b>6</b>	<b>RADIATED SPURIOUS EMISSIONS.....</b>	<b>22</b>

6.1	LIMITS .....	22
6.2	BLOCK DIAGRAM OF TEST SETUP .....	23
6.3	PROCEDURE .....	23
6.4	TEST DAT .....	25
<b>7</b>	<b>RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....</b>	<b>33</b>
7.1	LIMITS .....	33
7.2	BLOCK DIAGRAM OF TEST SETUP .....	34
7.3	PROCEDURE .....	34
7.4	TEST DATA .....	36
<b>8</b>	<b>CONDUCTED SPURIOUS EMISSIONS .....</b>	<b>40</b>
8.1	LIMITS .....	40
8.2	BLOCK DIAGRAM OF TEST SETUP .....	40
8.3	TEST DATA .....	40
<b>9</b>	<b>POWER SPECTRUM DENSITY.....</b>	<b>41</b>
9.1	LIMITS .....	41
9.2	BLOCK DIAGRAM OF TEST SETUP .....	41
9.3	TEST DATA .....	41
<b>10</b>	<b>APPENDIX.....</b>	<b>42</b>
10.1	APPENDIX : DTS BANDWIDTH .....	42
	<i>Test Result</i> .....	42
	<i>Test Graphs</i> .....	43
10.2	APPENDIX B: OCCUPIED CHANNEL BANDWIDTH .....	45
	<i>Test Result</i> .....	45
	<i>Test Graphs</i> .....	46
10.3	APPENDIX : MAXIMUM CONDUCTED OUTPUT POWER .....	48
	<i>Test Result</i> .....	48
	<i>Test Graphs</i> .....	49
10.4	APPENDIX : MAXIMUM POWER SPECTRAL DENSITY .....	51
	<i>Test Result</i> .....	51
	<i>Test Graphs</i> .....	52
10.5	APPENDIX : BAND EDGE MEASUREMENTS .....	54
	<i>Test Result</i> .....	54
	<i>Test Graphs</i> .....	54
10.6	APPENDIX : CONDUCTED SPURIOUS EMISSION.....	56

*Test Result*..... 56

*Test Graphs*..... 57

**APPENDIX A: PHOTOGRAPHS OF TEST SETUP ..... 63**

**APPENDIX B: PHOTOGRAPHS OF EUT ..... 65**

BlueAsia

## 1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass

## 2 GENERAL INFORMATION

<b>Applicant</b>	Dongguan Liesheng Electronic Co., Ltd.
<b>Address</b>	Room 401-410, Building 1, No.86 Hongtu Road, Nancheng District, Dongguan City, Guangdong, China.
<b>Manufacturer</b>	Dongguan Liesheng Electronic Co., Ltd.
<b>Address</b>	Room 401-410, Building 1, No.86 Hongtu Road, Nancheng District, Dongguan City, Guangdong, China.
<b>Factory</b>	Dongguan Liesheng Electronic Co., Ltd.
<b>Address</b>	Room 401-410, Building 1, No.86 Hongtu Road, Nancheng District, Dongguan City, Guangdong, China.
<b>Product Name</b>	Haylou RS3
<b>Test Model No.</b>	Haylou-LS04

## 3 GENERAL DESCRIPTION OF E.U.T.

<b>Hardware Version</b>	V1.0
<b>Software Version</b>	V1.0
<b>Operation Frequency:</b>	2402MHz-2480MHz
<b>Modulation Type:</b>	GFSK
<b>Channel Spacing:</b>	1Mbps,2Mbps
<b>Number of Channels:</b>	2MHz
<b>Antenna Type:</b>	Internal Antenna
<b>Antenna Gain:</b>	-4.91dBi ( Provided by the customer )

#### 4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	+25℃	DC3.7V

#### 5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
TX	Keep the EUT in transmitting mode with modulation

Remark: Only the data of the worst mode would be recorded in this report.

#### 6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

## 7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC Adapter	UGREEN	CD112	N/A	N/A

## 8 LABORATORY LOCATION

All tests were performed at:  
BlueAsia of Technical Services(Shenzhen) Co., Ltd.  
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District, Shenzhen, Guangdong Province,  
China  
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673  
No tests were sub-contracted.

## 9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	2020/11/25	2023/11/24
Receiver	R&S	ESPI3	101082	2020/10/12	2021/10/11
LISN	R&S	ENV216	3560.6550.15	2020/10/12	2021/10/11
LISN	AT	AT166-2	AKK1806000003	2020/10/12	2021/10/11
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

Test Equipment Of Conducted Band Edges Measurement					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Conducted Peak Output Power					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due

Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

**Test Equipment Of Radiated Spurious Emissions**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

**Test Equipment Of Radiated Emissions which fall in the restricted bands**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9

Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

**Test Equipment Of Conducted Spurious Emissions**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

**Test Equipment Of Power Spectrum Density**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11

Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11
------------------	---------	--------	------------	------------	------------

BlueAsia

## 1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	60%

### 1.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### 1.2 BLOCK DIAGRAM OF TEST SETUP



Remark  
 E.U.T: Equipment Under Test  
 LISN: Line Impedance Stabilization Network  
 Test table height=0.8m

### 1.3 PROCEDURE


- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50 $\mu$ H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
  - 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
  - 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
- Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

### 1.4 TEST DATA

[Test Mode: TX]; [Line: Line]  
 Power: AC120V60Hz



Site:      Phase: **L1**      Temperature:      Humidity: %  
 Limit: FCC Class B Conduction(QP)      Power:  
 EUT: Haylou Smart Watch  
 M/N: Haylou-LS04  
 Mode:  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2380	25.08	9.93	35.01	62.17	-27.16	QP	
2		0.2380	17.17	9.93	27.10	52.17	-25.07	AVG	
3		0.5380	29.69	9.73	39.42	56.00	-16.58	QP	
4	*	0.5380	19.97	9.73	29.70	46.00	-16.30	AVG	
5		0.9180	23.09	9.77	32.86	56.00	-23.14	QP	
6		0.9180	15.33	9.77	25.10	46.00	-20.90	AVG	
7		1.7500	20.21	9.83	30.04	56.00	-25.96	QP	
8		1.7500	13.92	9.83	23.75	46.00	-22.25	AVG	
9		2.4500	17.59	9.81	27.40	56.00	-28.60	QP	
10		2.4500	9.67	9.81	19.48	46.00	-26.52	AVG	
11		3.7020	16.43	9.85	26.28	56.00	-29.72	QP	
12		3.7020	7.27	9.85	17.12	46.00	-28.88	AVG	


\*:Maximum data    x:Over limit    !:over margin

(Reference Only)

**Test Result: Pass**

[Test Mode: TX]; [Line: Neutral]  
Power: AC120V60Hz

**Conducted Emission Measurement**



File :CE Data :#1 Date: 2021/1/13 Time: 15:39:41  
80.0 dBuV

Site Phase: **N** Temperature:  
Limit: FCC Class B Conduction(QP) Power: Humidity: %  
EUT: Haylou Smart Watch  
M/N: Haylou-LS04  
Mode:  
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.2630	24.07	9.82	33.89	61.34	-27.45	QP	
2		0.2630	17.20	9.82	27.02	51.34	-24.32	AVG	
3		0.5340	27.93	9.73	37.66	56.00	-18.34	QP	
4	*	0.5340	23.15	9.73	32.88	46.00	-13.12	AVG	
5		0.9060	21.91	9.75	31.66	56.00	-24.34	QP	
6		0.9060	16.75	9.75	26.50	46.00	-19.50	AVG	
7		1.6180	20.86	9.84	30.70	56.00	-25.30	QP	
8		1.6180	15.51	9.84	25.35	46.00	-20.65	AVG	
9		3.2500	12.64	9.87	22.51	56.00	-33.49	QP	
10		3.2500	7.11	9.87	16.98	46.00	-29.02	AVG	
11		5.2340	11.16	9.90	21.06	60.00	-38.94	QP	
12		5.2340	5.98	9.90	15.88	50.00	-34.12	AVG	

\*:Maximum data x:Over limit !:over margin

(Reference Only)

**Test Result: Pass**


## 2 CONDUCTED BAND EDGES MEASUREMENT

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Sven
<b>Temperature</b>	25°C
<b>Humidity</b>	60%

### 2.1 LIMITS

<b>Limit:</b>	<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).</p>
---------------	---

### 2.2 BLOCK DIAGRAM OF TEST SETUP



### 2.3 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**


### 3 CONDUCTED PEAK OUTPUT POWER

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.5
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Sven
<b>Temperature</b>	25°C
<b>Humidity</b>	60%

#### 3.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

#### 3.2 BLOCK DIAGRAM OF TEST SETUP



#### 3.3 EST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**


#### 4 MINIMUM 6DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.8.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	60%

##### 4.1 LIMITS

Limit:	$\geq 500$ kHz
--------	----------------

##### 4.2 BLOCK DIAGRAM OF TEST SETUP



##### 4.3 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**

## 5 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


### 5.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -4.91dBi.



## 6 RADIATED SPURIOUS EMISSIONS


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.4,6.5,6.6
<b>Test Mode (Pre-Scan)</b>	TX mode (SE) below 1G;TX mode (SE) Above 1G
<b>Test Mode (Final Test)</b>	TX mode (SE) below 1G;TX mode (SE) Above 1G
<b>Tester</b>	Sven
<b>Temperature</b>	25°C
<b>Humidity</b>	60%

### 6.1 LIMITS

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## 6.2 BLOCK DIAGRAM OF TEST SETUP



## 6.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor + Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



[TestMode: TX mode (SE) below 1G]; [Polarity: Vertical]




Site:      Polarization: *Vertical*      Temperature:      Humidity: %  
 Limit: FCC Part15 Class B      Power:      Distance: 3m  
 EUT: Haylou Smart Watch  
 M/N: Haylou-LS04  
 Mode: TX  
 Note:

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1 *	40.7016	10.68	13.69	24.37	40.00	-15.63	QP	
2	66.7325	10.47	11.72	22.19	40.00	-17.81	QP	
3	93.1132	11.16	9.30	20.46	43.50	-23.04	QP	
4	157.0074	9.92	12.99	22.91	43.50	-20.59	QP	
5	232.5318	10.82	12.22	23.04	46.00	-22.96	QP	
6	369.4047	10.13	16.10	26.23	46.00	-19.77	QP	

**Test Result: Pass**

Remark: During the test, pre-scan the 1Mbps, 2 Mbps rate, and found the 2Mbps rate which it is worse case.

[TestMode: TX Low channel]; [Polarity: Horizontal]




Site	Polarization: <b>Horizontal</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Smart Watch	Distance: 3m	
M/N: Haylou-LS04		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4804.000	51.12	-7.27	43.85	74.00	-30.15	peak		
2		7206.000	51.99	-4.42	47.57	74.00	-26.43	peak		
3	*	9608.000	49.53	-0.29	49.24	74.00	-24.76	peak		

\*:Maximum data    x:Over limit    !:over margin      (Reference Only)

**Test Result: Pass**

[TestMode: TX Low channel]; [Polarity: Vertical]



Site	Polarization: <b>Vertical</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Smart Watch	Distance: 3m	
M/N: Haylou-LS04		
Mode: TX-L		
Note:		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		4804.000	51.95	-7.27	44.68	74.00	-29.32 peak		
2		7206.000	51.88	-4.42	47.46	74.00	-26.54 peak		
3	*	9608.000	50.30	-0.29	50.01	74.00	-23.99 peak		

\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX middle channel]; [Polarity: Horizontal]



Site	Polarization: <b>Horizontal</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Smart Watch	Distance: 3m	
M/N: Haylou-LS04		
Mode: TX-M		
Note:		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4882.000	53.20	-7.51	45.69	74.00	-28.31	peak		
2		7323.000	51.22	-3.35	47.87	74.00	-26.13	peak		
3	*	9764.000	49.09	0.56	49.65	74.00	-24.35	peak		

\*:Maximum data    x:Over limit    !:over margin

⟨Reference Only

**Test Result: Pass**

[TestMode: TX middle channel]; [Polarity: Vertical]



Site	Polarization: <b>Vertical</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Smart Watch	Distance: 3m	
M/N: Haylou-LS04		
Mode: TX-M		
Note:		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4882.000	52.36	-7.51	44.85	74.00	-29.15	peak		
2		7323.000	50.97	-3.35	47.62	74.00	-26.38	peak		
3	*	9764.000	48.75	0.56	49.31	74.00	-24.69	peak		

\*:Maximum data    x:Over limit    !:over margin

⟨Reference Only

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Horizontal]



Site	Polarization: <b>Horizontal</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Smart Watch	Distance: 3m	
M/N: Haylou-LS04		
Mode: TX-H		
Note:		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4960.000	51.99	-6.99	45.00	74.00	-29.00	peak		
2		7440.000	51.61	-2.43	49.18	74.00	-24.82	peak		
3	*	9920.000	49.57	1.63	51.20	74.00	-22.80	peak		

\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Vertical]



Site	Polarization: <b>Vertical</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Smart Watch	Distance: 3m	
M/N: Haylou-LS04		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4960.000	51.94	-6.99	44.95	74.00	-29.05	peak		
2		7440.000	51.20	-2.43	48.77	74.00	-25.23	peak		
3	*	9920.000	48.18	1.63	49.81	74.00	-24.19	peak		

\*:Maximum data    x:Over limit    !:over margin

⟨Reference Only

**Test Result: Pass**

## 7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.10.5
<b>Test Mode (Pre-Scan)</b>	TX Low channel;TX high channel
<b>Test Mode (Final Test)</b>	TX Low channel;TX high channel
<b>Tester</b>	Sven
<b>Temperature</b>	25°C
<b>Humidity</b>	60%

### 7.1 LIMITS

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## 7.2 BLOCK DIAGRAM OF TEST SETUP



## 7.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1:  $Level = Read\ Level + Cable\ Loss + Antenna\ Factor - Preamp\ Factor$


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

### 7.4 TEST DATA

Remark: During the test, pre-scan the 1Mbps, 2 Mbps rate, and found the 2Mbps rate which it is worse case.

[TestMode: TX Low channel]; [Polarity: Horizontal]




Site	Polarization: <b>Horizontal</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Smart Watch	Distance: 3m	
M/N: Haylou-LS04		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	2310.000	57.06	-12.97	44.09	74.00	-29.91	peak		
2		2390.000	55.57	-11.78	43.79	74.00	-30.21	peak		

\*:Maximum data    x:Over limit    !:over margin      <Reference Only

**Test Result: Pass**

[TestMode: TX Low channel]; [Polarity: Vertical]



Site	Polarization: <b>Vertical</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Smart Watch	Distance: 3m	
M/N: Haylou-LS04		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	55.88	-12.97	42.91	74.00	-31.09	peak		
2	*	2390.000	55.35	-11.78	43.57	74.00	-30.43	peak		


\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Horizontal]

**Radiated Emission Measurement**



Site	Polarization: <b>Horizontal</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Smart Watch	Distance: 3m	
M/N: Haylou-LS04		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	2483.500	63.85	-12.21	51.64	74.00	-22.36	peak		
2		2500.000	57.28	-12.28	45.00	74.00	-29.00	peak		


\*:Maximum data x:Over limit !:over margin

<Reference Only

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Vertical]

**Radiated Emission Measurement**



Site	Polarization: <b>Vertical</b>	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Smart Watch	Distance: 3m	
M/N: Haylou-LS04		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	2483.500	63.56	-12.21	51.35	74.00	-22.65	peak		
2		2500.000	56.09	-12.28	43.81	74.00	-30.19	peak		

\*:Maximum data    x:Over limit    !:over margin

<Reference Only

**Test Result: Pass**


## 8 CONDUCTED SPURIOUS EMISSIONS

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Sven
<b>Temperature</b>	25°C
<b>Humidity</b>	60%

### 8.1 LIMITS

<b>Limit:</b>	<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).</p>
---------------	---

### 8.2 BLOCK DIAGRAM OF TEST SETUP



### 8.3 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**


## 9 POWER SPECTRUM DENSITY

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.10.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	60%

### 9.1 LIMITS

<b>Limit:</b>	$\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission
---------------	--

### 9.2 BLOCK DIAGRAM OF TEST SETUP



### 9.3 TEST DATA

<b>Pass: Please Refer To Appendix: Appendix1 For Details</b>
--

## 10 APPENDIX

### 10.1 APPENDIX : DTS BANDWIDTH

#### Test Result

TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE-1M	Ant1	2402	0.672	2401.676	2402.348	>=0.5	PASS
		2442	0.672	2441.680	2442.352	>=0.5	PASS
		2480	0.692	2479.672	2480.364	>=0.5	PASS

TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE-2M	Ant1	2402	1.356	2401.340	2402.696	>=0.5	PASS
		2442	1.356	2441.344	2442.700	>=0.5	PASS
		2480	1.364	2479.336	2480.700	>=0.5	PASS


### Test Graphs



BLE 2M Ant1 2402



BLE 2M Ant1 2442



BLE 2M Ant1 2480



## 10.2 APPENDIX B: OCCUPIED CHANNEL BANDWIDTH

### Test Result


TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE-1M	Ant1	2402	1.0409	2401.495	2402.536	---	PASS
		2442	1.0422	2441.494	2442.537	---	PASS
		2480	1.0446	2479.496	2480.540	---	PASS

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_2M	Ant1	2402	2.0812	2400.974	2403.055	---	PASS
		2442	2.0707	2440.978	2443.049	---	PASS
		2480	2.0786	2478.971	2481.050	---	PASS


### Test Graphs



BLE 2M Ant1 2402



BLE 2M Ant1 2442



BLE 2M Ant1 2480




### 10.3 APPENDIX : MAXIMUM CONDUCTED OUTPUT POWER

#### Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE-1M	Ant1	2402	-0.34	<=30	PASS
		2442	-1.20	<=30	PASS
		2480	-1.75	<=30	PASS

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_2M	Ant1	2402	-0.22	<=30	PASS
		2442	-1.37	<=30	PASS
		2480	-1.91	<=30	PASS

### Test Graphs



BLE 2M Ant1 2402



BLE 2M Ant1 2442



BLE 2M Ant1 2480



**10.4 APPENDIX : MAXIMUM POWER SPECTRAL DENSITY**


**Test Result**

TestMode	Antenna	Channel	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
BLE-1M	Ant1	2402	-7.69	<=8	PASS
		2442	-8.96	<=8	PASS
		2480	-9.23	<=8	PASS

TestMode	Antenna	Channel	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
BLE_2M	Ant1	2402	-10.7	<=8	PASS
		2442	-10.84	<=8	PASS
		2480	-12.72	<=8	PASS

BlueAsia

### Test Graphs




BLE 2M Ant1 2402



BLE 2M Ant1 2442



BLE 2M Ant1 2480



### 10.5 APPENDIX : BAND EDGE MEASUREMENTS

#### Test Result

TestMode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE-1M	Ant1	Low	2402	-0.87	-56.62	<=-20.87	PASS
		High	2480	-2.11	-55.54	<=-22.11	PASS

TestMode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_2M	Ant1	Low	2402	-2.04	-56.14	<=-22.04	PASS
		High	2480	-3.80	-55.85	<=-23.8	PASS


#### Test Graphs



BLE 2M Ant1 Low 2402



BLE 2M Ant1 High 2480



**10.6 APPENDIX : CONDUCTED SPURIOUS EMISSION**
**Test Result**

TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE-1M	Ant1	2402	Reference	-0.93	-0.93	---	PASS
			30~1000	30~1000	-67.673	<=-30.927	PASS
			1000~26500	1000~26500	-52.91	<=-30.927	PASS
		2442	Reference	-2.33	-2.33	---	PASS
			30~1000	30~1000	-67.813	<=-32.334	PASS
			1000~26500	1000~26500	-53.678	<=-32.334	PASS
		2480	Reference	-2.32	-2.32	---	PASS
			30~1000	30~1000	-68.153	<=-32.318	PASS
			1000~26500	1000~26500	-54.303	<=-32.318	PASS

TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_2M	Ant1	2402	Reference	-2.91	-2.91	---	PASS
			30~1000	30~1000	-67.519	<=-32.907	PASS
			1000~26500	1000~26500	-53.877	<=-32.907	PASS
		2442	Reference	-3.03	-3.03	---	PASS
			30~1000	30~1000	-66.32	<=-33.025	PASS
			1000~26500	1000~26500	-53.935	<=-33.025	PASS
		2480	Reference	-4.05	-4.05	---	PASS
			30~1000	30~1000	-67.455	<=-34.047	PASS
			1000~26500	1000~26500	-53.81	<=-34.047	PASS


### Test Graphs




BLE 1M Ant1 2442 0~Reference



BLE 1M Ant1 2442 30~1000




BLE 1M Ant1 2442 1000~26500




BLE 1M Ant1 2480 0~Reference



BLE 1M Ant1 2480 30~1000




BLE 1M Ant1 2480 1000~26500




BLE 2M Ant1 2402 0~Reference



BLE 2M Ant1 2402 30~1000




BLE 2M Ant1 2402 1000~26500




BLE 2M Ant1 2442 0~Reference



BLE 2M Ant1 2442 30~1000




BLE 2M Ant1 2442 1000~26500




BLE 2M Ant1 2480 0~Reference



BLE 2M Ant1 2480 30~1000




BLE 2M Ant1 2480 1000~26500



## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

### Radiated Spurious Emissions



**Conducted Emissions at AC Power Line (150kHz-30MHz)**






### APPENDIX B: PHOTOGRAPHS OF EUT














----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.