

RF Exposure Report

FCC ID: 2AMSC-SH20

1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

Equipment	Smart watch
Model Name	SH20
Additional Model Number(s)	N/A
Model Difference	N/A
Frequency Range	Bluetooth 4.1(BLE): 2402~2480 MHz
Number of Channel:	40 Channels
Modulation Type	GFSK
RF Output Power	3.270dBm
Antenna Type	PCB Antenna (Gain: 2.41dBi)
Power Source	DC power by Button Battery.
Power Rating	DC 3.0V by Button Battery.
Remark	More details EUT technical specifications, please refer to the User's Manual.

2. RF EXPOSURE INFORMATION

SAR Test Exclusion Calculations

2.1 FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

(1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance \leq 5 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation, mm})]^*[\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR}$

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation, mm})]^*[\sqrt{f_{(\text{GHz})}}] \leq 7.5.0 \text{ for 10-g SAR}$

2.2

Calculation:

BLE Mode						
GFSK(1Mbps)						
Frequency (MHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	MAX Power of Turn-up Tolerance (dbm)	MAX Power of Turn-up Tolerance (mW)	Calculation Value	Threshold Value
2402	0.027	0 \pm 1	1	1.259	0.390	3.0
2442	3.270	3 \pm 1	4	2.512	0.785	3.0
2480	2.317	2 \pm 1	3	1.995	0.628	3.0

So standalone SAR measurements are not required.

*****END OF REPORT*****