

TEST REPORT

Product Name : TENS&EMS
Model Number : HZ9151B, HZ9151C, HZ9151D
FCC ID : 2AMYMHZ9151BCD

Prepared for : Hong Qiangxing(Shenzhen) electronics Limited
Address : 2F, Yongcheng Blvd, Xicheng Industrial area, Xixiang Street, Bao'an District, Shenzhen City, Guangdong Province, 518126, China

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

TEL:(0755) 26954280
FAX:(0755) 26954282

Report Number : ENS2505150111W00202R
Date of sample receipt : May 13, 2025
Date(s) of Tests : May 13, 2025 to Jun 19, 2025
Date of issue : Jun 20, 2025

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : Hong Qiangxing(Shenzhen) electronics Limited
 Address : 2F, Yongcheng Blvd, Xicheng Industrial area, Xixiang Street, Bao'an District, Shenzhen City, Guangdong Province, 518126, China
 Manufacturer : Hong Qiangxing(Shenzhen) electronics Limited
 Address : 2F, Yongcheng Blvd, Xicheng Industrial area, Xixiang Street, Bao'an District, Shenzhen City, Guangdong Province, 518126, China
 Factory : Hong Qiangxing(Shenzhen) electronics Limited
 Address : 2F, Yongcheng Blvd, Xicheng Industrial area, Xixiang Street, Bao'an District, Shenzhen City, Guangdong Province, 518126, China
 EUT : TENS&EMS
 Model Name : HZ9151B, HZ9151C, HZ9151D
 Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : May 13, 2025 to Jun 19, 2025

Prepared by : Una Yu
Una Yu /Editor

Reviewer : Joe Xia
Joe Xia/Supervisor

Approve & Authorized Signer : Lisa Wang
Lisa Wang/Manager



Modified History

Version	Report No.	Revision Date	Summary
	ENS2505150111W00202R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	TENS&EMS
Model Number:	HZ9151B, HZ9151C, HZ9151D (Note: These models are the same, except for the model numbers and the accessories sold as a set; HZ9151B was selected for full test.)
Sample:	1#
Device Type :	2.4G SRD
Channe Separation :	1MHz
Modulation:	GFSK
Operating Frequency Range(s) :	2402-2470MHz
Number of Channels:	69 Channels
Transmit Power Max:	4.98 dBm(0.003148 W)
Antenna Gain:	2 dBi
Power supply:	DC 5V from USB DC3.7V from battery
Evaluation applied:	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

3. Test Requirement

SAR Evaluation

According to 447498 D01 V06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

Antenna gain: 2 dBi

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	Tune up Power (dBm)	Max tune up power (dBm)	Calculation Result	Calculation threshold(1-g SAR)
2402	GFSK	4.87	5±1	6	1.2340	3
2436	GFSK	4.98	5±1	6	1.2427	3
2470	GFSK	4.64	4±1	5	0.9940	3

According to KDB 447498 D01 V06, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

*** End of Report ***